# Fraudulent Activity Notifications ★

45 more points to get your gold badge!

Rank: 196305 | Points: 805/850



Problem

Submissions

Leaderboard

Editorial

#### RATE THIS CHALLENGE



HackerLand National Bank has a simple policy for warning clients about possible fraudulent account activity. If the amount spent by a client on a particular day is greater than or equal to 2 imes the client's median spending for a trailing number of days, they send the client a notification about potential fraud. The bank doesn't send the client any notifications until they have at least that trailing number of prior days' transaction data.

Given the number of trailing days  $m{d}$  and a client's total daily expenditures for a period of  $m{n}$  days, determine the number of times the client will receive a notification over all  $\boldsymbol{n}$  days.

### Example

expenditure = [10, 20, 30, 40, 50]

d = 3

On the first three days, they just collect spending data. At day  $\mathbf{4}$ , trailing expenditures are  $[\mathbf{10}, \mathbf{20}, \mathbf{30}]$ . The median is  $\mathbf{20}$  and the day's expenditure is  $\mathbf{40}$ . Because  $40 \ge 2 \times 20$ , there will be a notice. The next day, trailing expenditures are [20, 30, 40] and the expenditures are 50. This is less than  $2 \times 30$  so no notice will be sent. Over the period, there was one notice sent.

Note: The median of a list of numbers can be found by first sorting the numbers ascending. If there is an odd number of values, the middle one is picked. If there is an even number of values, the median is then defined to be the average of the two middle values. (Wikipedia)

### **Function Description**

Complete the function activityNotifications in the editor below.

activityNotifications has the following parameter(s):

- int expenditure[n]: daily expenditures
- int d: the lookback days for median spending

#### Returns

• int: the number of notices sent

#### **Input Format**

The first line contains two space-separated integers n and d, the number of days of transaction data, and the number of trailing days' data used to calculate median spending respectively.

The second line contains n space-separated non-negative integers where each integer i denotes expenditure[i].

#### Constraints

- $1 \le n \le 2 \times 10^5$
- $1 \leq d \leq n$
- $0 \le expenditure[i] \le 200$

## **Output Format**

# Sample Input 0

STDIN	Function
9 5	expenditure[] size n =9, d = 5
2 3 4 2 3 6 8 4 5	expenditure = [2, 3, 4, 2, 3, 6, 8, 4, 5]

2

# **Explanation 0**

Determine the total number of **notifications** the client receives over a period of n = 9 days. For the first five days, the customer receives no notifications because the bank has insufficient transaction data: **notifications** = 0.

On the sixth day, the bank has d=5 days of prior transaction data,  $\{2,3,4,2,3\}$ , and median=3 dollars. The client spends 6 dollars, which triggers a notification because  $6 \ge 2 \times median$ : notifications=0+1=1.

On the seventh day, the bank has d=5 days of prior transaction data,  $\{3,4,2,3,6\}$ , and median=3 dollars. The client spends 8 dollars, which triggers a notification because  $8 \ge 2 \times median$ : notifications=1+1=2.

On the eighth day, the bank has d=5 days of prior transaction data,  $\{4,2,3,6,8\}$ , and median=4 dollars. The client spends 4 dollars, which does not trigger a notification because  $4 < 2 \times median$ : notifications = 2.

On the ninth day, the bank has d=5 days of prior transaction data,  $\{2,3,6,8,4\}$ , and a transaction median of 4 dollars. The client spends 5 dollars, which does not trigger a notification because  $5 < 2 \times median$ : notifications = 2.

### Sample Input 1

```
5 4
1 2 3 4 4
```

# Sample Output 1

0

There are f 4 days of data required so the first day a notice might go out is day f 5. Our trailing expenditures are f [1,2,3,4] with a median of f 2.5 The client spends f 4 which is less than f 2 imes 2.5 so no notification is sent.

```
Change Theme Language C#
                                                                                                          K Z
                                                                                                  10
                                                                                                                :
1
   using System.CodeDom.Compiler;
    using System.Collections.Generic;
 3
    using System.Collections;
    using System.ComponentModel;
    using System.Diagnostics.CodeAnalysis;
 5
 6
    using System.Globalization;
 7
    using System.IO;
8
    using System.Linq;
    using System.Reflection;
9
    using System.Runtime.Serialization;
10
11
    using System.Text.RegularExpressions;
12
    using System.Text;
13
    using System;
14
    class Result
15
16
17
18
          * Complete the 'activityNotifications' function below.
19
20
21
          * The function is expected to return an INTEGER.
          * The function accepts following parameters:
22
          * 1. INTEGER_ARRAY expenditure
23
          *, 2. INTEGER d
34
```

26 27 public static int activityNotifications(List <int> expenditure, int d)</int>		Line: 114 Col: 1
① UploadCodeasFile Test against custom input	Run Code	Submit Code
Contest Calendar   Blog   Scoring   Environment   FAQ   About Us   Support   Careers   Terms Of Serv	ice   Privacy Policy   Re	equest a Feature