

# CS110: Introduction to Linux Commands

Vijaya Saradhi

**IIT Guwahati**

16<sup>th</sup> Jan 2019

# Commands

**Shell** A program which accepts **commands** and passes it to the **operating system**

# Commands

**Shell** A program which accepts **commands** and passes it to the **operating system**

**Terminal** A graphical user interface (GUI) to interact with the shell

# Commands

**Shell** A program which accepts **commands** and passes it to the **operating system**

**Terminal** A graphical user interface (GUI) to interact with the shell

**How to Invoke?** - 1 Alt+F2 and provide input: `gnome-terminal`

# Commands

**Shell** A program which accepts **commands** and passes it to the **operating system**

**Terminal** A graphical user interface (GUI) to interact with the shell

**How to Invoke? - 1** Alt+F2 and provide input: `gnome-terminal`

**How to Invoke? - 2** Click on **9-dots** symbol on the left bottom menu-bar.  
Search for “terminal” or “gnome-terminal” and select the left most icon

# Commands

**Shell** A program which accepts **commands** and passes it to the **operating system**

**Terminal** A graphical user interface (GUI) to interact with the shell

**How to Invoke? - 1** Alt+F2 and provide input: `gnome-terminal`

**How to Invoke? - 2** Click on **9-dots** symbol on the left bottom menu-bar. Search for “terminal” or “gnome-terminal” and select the left most icon

**How to Invoke? - 3** No GUI mode: Most difficult for beginners: type **Ctrl + Alt + F3**. Enter login and password. You are taken to the shell.

# Commands

**Shell** A program which accepts **commands** and passes it to the **operating system**

**Terminal** A graphical user interface (GUI) to interact with the shell

**How to Invoke? - 1** Alt+F2 and provide input: `gnome-terminal`

**How to Invoke? - 2** Click on **9-dots** symbol on the left bottom menu-bar. Search for “terminal” or “gnome-terminal” and select the left most icon

**How to Invoke? - 3** No GUI mode: Most difficult for beginners: type **Ctrl + Alt + F3**. Enter login and password. You are taken to the shell.

**Need More Terminals?** Repeat any of the above steps any number of times.

# Commands

**Shell** A program which accepts **commands** and passes it to the **operating system**

**Terminal** A graphical user interface (GUI) to interact with the shell

**How to Invoke? - 1** Alt+F2 and provide input: `gnome-terminal`

**How to Invoke? - 2** Click on **9-dots** symbol on the left bottom menu-bar. Search for “terminal” or “gnome-terminal” and select the left most icon

**How to Invoke? - 3** No GUI mode: Most difficult for beginners: type **Ctrl + Alt + F3**. Enter login and password. You are taken to the shell.

**Need More Terminals?** Repeat any of the above steps any number of times.

**Important** shell treats the contents you type as is: PWD is different from `pwd`



# Terminal Images - 1



## Terminal Images - 2



```
saradhi@beta01:~$ pwd
/home/saradhi
saradhi@beta01:~$
```

`pwd` - 1 Present Working Directory (i. read as folder; ii. read `guest` instead of `saradhi`)

# Terminal Images - 2



```
saradhi@bataal:~$ pwd
/home/saradhi
saradhi@bataal:~$
```

- `pwd` - 1 Present Working Directory (i. read as folder; ii. read `guest` instead of `saradhi`)
- `pwd` - 2 Present Working Folder

## Terminal Images - 2



```
saradhi@bataal:~$ pwd
/home/saradhi
saradhi@bataal:~$
```

- `pwd` - 1 Present Working Directory (i. read as folder; ii. read `guest` instead of `saradhi`)
- `pwd` - 2 Present Working Folder
- `pwd` - 3 It is important to identify where you are working; when you create files or folders it is with respect to the `present working folder`


## Terminal Images - 2

A terminal window with a dark purple background. The text shows a user named 'saradhi' at a prompt 'saradhi@bataal:~\$' typing the command 'pwd'. The output of the command is '/home/saradhi', which is displayed on the next line. The prompt then changes to 'saradhi@bataal:~\$' with a cursor at the end.

```
saradhi@bataal:~$ pwd
/home/saradhi
saradhi@bataal:~$
```

- `pwd` - 1 Present Working Directory (i. read as folder; ii. read `guest` instead of `saradhi`)
- `pwd` - 2 Present Working Folder
- `pwd` - 3 It is important to identify where you are working; when you create files or folders it is with respect to the `present working folder`
- `pwd` - 4 `/home/saradhi` is the `home folder`

## Terminal Images - 2

A terminal window with a dark purple background. The prompt is 'saradhi@betaal:~\$'. The command 'pwd' has been entered, and the output is '/home/saradhi'. The prompt is now 'saradhi@betaal:~\$' with a cursor at the end.

```
saradhi@betaal:~$ pwd
/home/saradhi
saradhi@betaal:~$
```

- `pwd` - 1 Present Working Directory (i. read as folder; ii. read `guest` instead of `saradhi`)
  - `pwd` - 2 Present Working Folder
  - `pwd` - 3 It is important to identify where you are working; when you create files or folders it is with respect to the `present working folder`
  - `pwd` - 4 `/home/saradhi` is the `home folder`
- Creation** Files and folders which are created `reside` in the `HOME` folder

# Terminal - Where it takes you?

```
saradhi@betaal:~$ pwd
/home/saradhi
saradhi@betaal:~$ cd Documents/
saradhi@betaal:~/Documents$
```

## Navigation - List folder contents

List folder contents that is asking what are the files and folder within home folder.



# Navigation - List folder contents

List folder contents that is asking what are the files and folder within home folder.

Command `ls`

# Navigation - List folder contents

List folder contents that is asking what are the files and folder within home folder.

Command `ls`

# Navigation - List folder contents

List folder contents that is asking what are the files and folder within home folder.

Command `ls`

Input to `ls`    • `-a`

# Navigation - List folder contents

List folder contents that is asking what are the files and folder within home folder.

Command `ls`

Input to `ls`

- `-a`
- `-l`

# Navigation - List folder contents

List folder contents that is asking what are the files and folder within home folder.

Command `ls`

Input to `ls`

- `-a`
- `-l`
- `-h`

# Navigation - List folder contents

List folder contents that is asking what are the files and folder within home folder.

Command `ls`

Input to `ls`

- `-a`
- `-l`
- `-h`
- `-Q`

# Navigation - List folder contents

List folder contents that is asking what are the files and folder within home folder.

Command `ls`

Input to `ls`

- `-a`
- `-l`
- `-h`
- `-Q`

Input to `ls -a`

# Navigation - List folder contents

List folder contents that is asking what are the files and folder within home folder.

Command `ls`

Input to `ls`

- `-a`
- `-l`
- `-h`
- `-Q`

Input to `ls -a`

Input to `ls -l`



# Navigation - List folder contents

List folder contents that is asking what are the files and folder within home folder.

Command `ls`

Input to `ls`

- `-a`
- `-l`
- `-h`
- `-Q`

Input to `ls -a`

Input to `ls -l`

Input to `ls -h`

# Navigation - List folder contents

List folder contents that is asking what are the files and folder within home folder.

Command `ls`

Input to `ls`

- `-a`
- `-l`
- `-h`
- `-Q`

Input to `ls -a`

Input to `ls -l`

Input to `ls -h`

Input to `ls -Q`

## Navigation - List folder contents

List folder contents that is asking what are the files and folder within home folder.

Command `ls`

Input to `ls`

- `-a`
- `-l`
- `-h`
- `-Q`

Input to `ls -a`

Input to `ls -l`

Input to `ls -h`

Input to `ls -Q`

Combine inputs You can construct combination of inputs mentioned above

## Navigation - List folder contents

List folder contents that is asking what are the files and folder within home folder.

Command `ls`

Input to `ls`

- `-a`
- `-l`
- `-h`
- `-Q`

Input to `ls -a`

Input to `ls -l`

Input to `ls -h`

Input to `ls -Q`

Combine inputs You can construct combination of inputs mentioned above  
`-al`; `-alh`; `-alhQ` all are valid inputs to command `ls`

## Navigation - List folder contents

List folder contents that is asking what are the files and folder within home folder.

Command `ls`

Input to `ls`

- `-a`
- `-l`
- `-h`
- `-Q`

Input to `ls -a`

Input to `ls -l`

Input to `ls -h`

Input to `ls -Q`

Combine inputs You can construct combination of inputs mentioned above  
`-al`; `-alh`; `-alhQ` all are valid inputs to command `ls`

Input to `ls -alhQ`

## Navigation - List folder contents

List folder contents that is asking what are the files and folder within home folder.

Command `ls`

Input to `ls`

- `-a`
- `-l`
- `-h`
- `-Q`

Input to `ls -a`

Input to `ls -l`

Input to `ls -h`

Input to `ls -Q`


Combine inputs You can construct combination of inputs mentioned above  
`-al`; `-alh`; `-alhQ` all are valid inputs to command `ls`

Input to `ls -alhQ`

Contents of another folder `ls Downloads`

# Navigation - Change to another folder - 1


`cd` Change directory  
(change folder)



# Navigation - Change to another folder - 1

`cd` Change directory  
(change folder)

`cd` What is the notation?






# Navigation - Change to another folder - 1

`cd` Change directory  
(change folder)

`cd` What is the notation?

`pwd` /home/guest/Music  
Known as **absolute**  
**path**



# Navigation - Change to another folder - 1

`cd` Change directory  
(change folder)


`cd` What is the notation?

`pwd` /home/guest/Music

Known as **absolute**

**path**

/ root directory



# Navigation - Change to another folder - 1


`cd` Change directory  
(change folder)

`cd` What is the notation?

`pwd` /home/guest/Music  
Known as **absolute**  
**path**

`/` root directory

`/home` several users home  
folders will be present  
in this folder



# Navigation - Change to another folder - 1

`cd` Change directory  
(change folder)


`cd` What is the notation?

`pwd` `/home/guest/Music`  
Known as **absolute path**

`/` root directory

`/home` several users home  
folders will be present  
in this folder

`/home/guest` guest user home folder



# Navigation - Change to another folder - 1

`cd` Change directory  
(change folder)

`cd` What is the notation?


`pwd` /home/guest/Music  
Known as **absolute**  
**path**

`/` root directory

`/home` several users home  
folders will be present  
in this folder

`/home/guest` guest user home folder

`/home/guest/Music` is present  
**within** guest home  
folder




# Navigation - Change to another folder - 2

**cd** Change directory  
(change folder)

**cd** What is the notation?

**pwd** /home/guest/Music

**Command** `cd "Old Songs"`




## Navigation - Change to another folder - 3

**cd** Change directory  
(change folder)

**cd** What is the notation?

**pwd** /home/guest/Music

**Command** `cd "Old Songs"`



# Navigation - Change to another folder - 3


`cd` Change directory  
(change folder)

`cd` What is the notation?

`pwd` /home/guest/Music

**Command** `cd "Old Songs"`

**Command** `cd ..`






# Navigation - Change to another folder - Complex Example

## - 1

Navigate Go from Old Songs to Downloads




# Navigation - Change to another folder - Complex Example

## - 2

Navigate Go from Old Songs to Downloads

Navigate Go one level up `cd ..`




# Navigation - Change to another folder - Complex Example

## - 3

Navigate Go from Old Songs to Downloads

Navigate Go one level up `cd ..`


Navigate Go one more level up  
`cd ..`



# Navigation - Change to another folder - Complex Example

## - 4


- Navigate Go from Old Songs to Downloads
- Navigate Go one level up: `cd ..`
- Navigate Go more one level up  
`cd ..`
- Navigate Go to Downloads `cd Downloads`



# Navigation - Change to another folder - Putting together


Navigate Go from Old Songs to Downloads

Command `cd ../../Downloads`



# Navigation - Create Directory

- Assume that you are in HOME directory.
- `mkdir new-directory-name`
- The above will create a directory with the given name inside HOME directory.
- `mkdir My-Music`



# Create a file

**Editors** Various text editors help create text files

# Create a file

Editors Various text editors help create text files

```
gedit gedit new-file-name
```



# Create a file

Editors Various text editors help create text files

```
gedit gedit new-file-name
```

```
vi vi new-file-name
```

# Create a file

Editors Various text editors help create text files

```
gedit gedit new-file-name
```

```
vi vi new-file-name
```

```
pico pico new-file-name
```

# Create a file

Editors Various text editors help create text files

```
gedit gedit new-file-name
```

```
vi vi new-file-name
```

```
pico pico new-file-name
```

```
emacs emacs new-file-name
```

# Create a file

Editors Various text editors help create text files

```
gedit gedit new-file-name
```

```
vi vi new-file-name
```

```
pico pico new-file-name
```

```
emacs emacs new-file-name
```

... Choose your favorite text editor to work with and save files

# Create a file

**Editors** Various text editors help create text files

```
gedit gedit new-file-name
```

```
vi vi new-file-name
```

```
pico pico new-file-name
```

```
emacs emacs new-file-name
```

... Choose your favorite text editor to work with and save files

**Creation** File will be created at the place where you have invoked the command

# Create a file

**Editors** Various text editors help create text files

`gedit` `gedit` `new-file-name`

`vi` `vi` `new-file-name`

`pico` `pico` `new-file-name`

`emacs` `emacs` `new-file-name`

... Choose your favorite text editor to work with and save files

**Creation** File will be created at the place where you have invoked the command

**Create empty file** `touch` will create an empty file without the use of any editor command

# Create a file

**Editors** Various text editors help create text files

`gedit` `gedit` `new-file-name`

`vi` `vi` `new-file-name`

`pico` `pico` `new-file-name`

`emacs` `emacs` `new-file-name`

... Choose your favorite text editor to work with and save files

**Creation** File will be created at the place where you have invoked the command

**Create empty file** `touch` will create an empty file without the use of any editor command

**Example** `touch 16-jan-2019.txt`

# Remove a file

```
rm file-name-to-be-deleted
```



# Remove a file

`rm` file-name-to-be-deleted

Example `rm` 180101000.c

will delete the file 180101000.c; it will not place the file in the Trash folder!

# Remove a file

`rm` file-name-to-be-deleted

Example `rm` 180101000.c

will delete the file 180101000.c; it will not place the file in the Trash folder!

# Remove a file

`rm` file-name-to-be-deleted

Example `rm` 180101000.c

will delete the file 180101000.c; it will not place the file in the Trash folder!

Inputs to `rm`    • `-i` (interactive)

# Remove a file

`rm` file-name-to-be-deleted

Example `rm` 180101000.c

will delete the file 180101000.c; it will not place the file in the Trash folder!

Inputs to `rm`

- -i (interactive)
- -f (force remove)

# Remove a file

`rm` file-name-to-be-deleted

Example `rm` 180101000.c

will delete the file 180101000.c; it will not place the file in the Trash folder!

Inputs to `rm`

- `-i` (interactive)
- `-f` (force remove)
- `-r` (recursively remove)

# Remove a file

`rm` file-name-to-be-deleted

Example `rm` 180101000.c

will delete the file 180101000.c; it will not place the file in the Trash folder!

Inputs to `rm`

- -i (interactive)
- -f (force remove)
- -r (recursively remove)

Command `rm -i`

# Remove a file

`rm` file-name-to-be-deleted

Example `rm 180101000.c`

will delete the file 180101000.c; it will not place the file in the Trash folder!

Inputs to `rm`

- `-i` (interactive)
- `-f` (force remove)
- `-r` (recursively remove)

Command `rm -i`

Command `rm -f`

# Remove a file

`rm` file-name-to-be-deleted

Example `rm 180101000.c`

will delete the file 180101000.c; it will not place the file in the Trash folder!

Inputs to `rm`

- `-i` (interactive)
- `-f` (force remove)
- `-r` (recursively remove)

Command `rm -i`

Command `rm -f`

Command `rm -r`



# Remove a file

`rm` file-name-to-be-deleted

Example `rm 180101000.c`

will delete the file 180101000.c; it will not place the file in the Trash folder!

Inputs to `rm`

- `-i` (interactive)
- `-f` (force remove)
- `-r` (recursively remove)

Command `rm -i`

Command `rm -f`

Command `rm -r`

Combined `rm -rf`

# Remove a file

`rm` file-name-to-be-deleted

Example `rm 180101000.c`

will delete the file 180101000.c; it will not place the file in the Trash folder!

Inputs to `rm`

- `-i` (interactive)
- `-f` (force remove)
- `-r` (recursively remove)

Command `rm -i`

Command `rm -f`

Command `rm -r`

Combined `rm -rf`

Careful with remove command!

# Remove a folder

Two methods Use `rm` or `rmdir`

# Remove a folder

Two methods Use `rm` or `rmdir`

`rmdir` folder-name-to-be-deleted

# Remove a folder

Two methods Use `rm` or `rmdir`

`rmdir` folder-name-to-be-deleted

Example `rmdir Downloads`

Will delete the folder Downloads; Make sure Downloads folder empty before executing this.

# Remove a folder

Two methods Use `rm` or `rmdir`

`rmdir` folder-name-to-be-deleted

Example `rmdir Downloads`

Will delete the folder Downloads; Make sure Downloads folder empty before executing this.

`rm -rf` folder-name-to-be-deleted Deletes all the contents of the folder

# Copy files

```
cp file-1 file-2
```

# Copy files

```
cp file-1 file-2
```

**Explanation** the above command copies contents of file-1 into file-2



# Copy files

```
cp file-1 file-2
```

**Explanation** the above command copies contents of file-1 into file-2

**Observation - 1** file-2 need not be existing

# Copy files

`cp file-1 file-2`

**Explanation** the above command copies contents of file-1 into file-2

**Observation - 1** file-2 need not be existing

**Observation - 2** if it exists file-2 will be over-written; that is contents of file-2 will be replaced with contents of file-1

# Copy files

`cp` file-1 file-2

**Explanation** the above command copies contents of file-1 into file-2

**Observation - 1** file-2 need not be existing

**Observation - 2** if it exists file-2 will be over-written; that is contents of file-2 will be replaced with contents of file-1

**Observation - 3** You will find both file-1 and file-2 in the home directory

# Copy folders

```
cp -r folder-1 folder-2
```

# Copy folders

```
cp -r folder-1 folder-2
```

**Explanation** the above command copies **recursively** contents of folder-1 into folder-2

# Copy folders

```
cp -r folder-1 folder-2
```

**Explanation** the above command copies **recursively** contents of folder-1 into folder-2

**Observation - 1** folder-2 should not be existing

# Copy folders

```
cp -r folder-1 folder-2
```

**Explanation** the above command copies **recursively** contents of folder-1 into folder-2

**Observation - 1** folder-2 should not be existing

**Observation - 2** if it exists folder-2 will be added with the folder-1 files and folders;

# Move files

```
mv file-1 file-2
```



# Move files

```
mv file-1 file-2
```

**Explanation** the above command **moves** contents of file-1 into file-2

# Move files

```
mv file-1 file-2
```

**Explanation** the above command **moves** contents of file-1 into file-2

**Observation - 1** file-2 need not be existing

# Move files

```
mv file-1 file-2
```

**Explanation** the above command **moves** contents of file-1 into file-2

**Observation - 1** file-2 need not be existing

**Observation - 2** if it exists file-2 will be over-written; that is contents of file-2 will be replaced with contents of file-1

# Move files

```
mv file-1 file-2
```

**Explanation** the above command **moves** contents of file-1 into file-2

**Observation - 1** file-2 need not be existing

**Observation - 2** if it exists file-2 will be over-written; that is contents of file-2 will be replaced with contents of file-1

**Observation - 3** file-1 will no longer exists

# File Permissions

Three permissions Every file has read, write and/or execute permissions

# File Permissions

**Three permissions** Every file has read, write and/or execute permissions

**Three categories** Files can be accessed by three categories of people

# File Permissions

**Three permissions** Every file has read, write and/or execute permissions

**Three categories** Files can be accessed by three categories of people

**User** Owner of the file

# File Permissions

**Three permissions** Every file has read, write and/or execute permissions

**Three categories** Files can be accessed by three categories of people

**User** Owner of the file

- Have read, write and/or execute permission



# File Permissions

**Three permissions** Every file has read, write and/or execute permissions

**Three categories** Files can be accessed by three categories of people

**User** Owner of the file

- Have read, write and/or execute permission

**Group** Friends of owners

# File Permissions

**Three permissions** Every file has read, write and/or execute permissions

**Three categories** Files can be accessed by three categories of people

**User** Owner of the file

- Have read, write and/or execute permission

**Group** Friends of owners

- Have read, write and/or execute permission

# File Permissions

**Three permissions** Every file has read, write and/or execute permissions

**Three categories** Files can be accessed by three categories of people

**User** Owner of the file

- Have read, write and/or execute permission

**Group** Friends of owners

- Have read, write and/or execute permission

**Other** Rest of the people

# File Permissions

**Three permissions** Every file has read, write and/or execute permissions

**Three categories** Files can be accessed by three categories of people

**User** Owner of the file

- Have read, write and/or execute permission

**Group** Friends of owners

- Have read, write and/or execute permission

**Other** Rest of the people

- Have read, write and/or execute permission

# File Permissions Notations

user, group, others

# File Permissions Notations

user, group, others

Notation read: r

# File Permissions Notations

`user`, `group`, `others`

Notation read: `r`

Notation write: `w`

# File Permissions Notations

**user**, **group**, **others**

**Notation** read: **r**

**Notation** write: **w**

**Notation** execute: **x**



## Example file permissions and its interpretation

```
ls -l -rw-r--r-- 1 saradhi saradhi 271073 Jan 15 11:12  
16-jan-2019.pdf
```

## Example file permissions and its interpretation

```
ls -l -rw-r--r-- 1 saradhi saradhi 271073 Jan 15 11:12  
16-jan-2019.pdf
```

First character - indicates file as 16-jan-2019.pdf is a file

# Example file permissions and its interpretation

```
ls -l -rw-r--r-- 1 saradhi saradhi 271073 Jan 15 11:12  
16-jan-2019.pdf
```

First character - indicates file as 16-jan-2019.pdf is a file

Details `rw-` `r--` `r--`

# Example file permissions and its interpretation

```
ls -l -rw-r--r-- 1 saradhi saradhi 271073 Jan 15 11:12
16-jan-2019.pdf
```

First character - indicates file as 16-jan-2019.pdf is a file

Details rw- r-- r--

Details rw-- r-- r--

  
*Owner*

  
*Friends*

  
*Others*

# Example file permissions and its interpretation

```
ls -l -rw-r--r-- 1 saradhi saradhi 271073 Jan 15 11:12
16-jan-2019.pdf
```

First character - indicates file as 16-jan-2019.pdf is a file

Details rw- r-- r--




Details rwx r-- r--





*Owner*
*Friends*
*Others*

Binary Number 111 100 100



*Owner*
*Friends*
*Others*




# Example file permissions and its interpretation

```
ls -l -rw-r--r-- 1 saradhi saradhi 271073 Jan 15 11:12
16-jan-2019.pdf
```

First character - indicates file as 16-jan-2019.pdf is a file

Details rw- r-- r--

Details	<span style="color: blue;">rw-</span>	<span style="color: red;">r--</span>	<span style="color: green;">r--</span>
			
	Owner	Friends	Others

Binary Number	<span style="color: blue;">111</span>	<span style="color: blue;">100</span>	<span style="color: blue;">100</span>
			
	Owner	Friends	Others

Details	<span style="color: blue;">7</span>	<span style="color: blue;">4</span>	<span style="color: blue;">4</span>
			
	Owner	Friends	Others

# Changing file permissions

`chmod` Change permissions of file or folder

# Changing file permissions

`chmod` Change permissions of file or folder

`Construct` The required number.



# Changing file permissions

**chmod** Change permissions of file or folder

**Construct** The required number.

**User** : Must have read, write and execute: that is all the three bits should be  
1. Decimal equivalent of **111** is 7

# Changing file permissions

**chmod** Change permissions of file or folder

**Construct** The required number.

**User** : Must have read, write and execute: that is all the three bits should be 1. Decimal equivalent of **111** is 7

**Group** : Must have read and execute. Should not have write permission. Binary notation is 101. Decimal equivalent of **101** is 5

# Changing file permissions

**chmod** Change permissions of file or folder

**Construct** The required number.

**User** : Must have read, write and execute: that is all the three bits should be 1. Decimal equivalent of **111** is 7

**Group** : Must have read and execute. Should not have write permission. Binary notation is 101. Decimal equivalent of **101** is 5

**Others** : Must have execute. Should not have read and write permissions. Binary notation is 001. Decimal equivalent of **001** is 1.

# Changing file permissions

**chmod** Change permissions of file or folder

**Construct** The required number.

**User** : Must have read, write and execute: that is all the three bits should be 1. Decimal equivalent of **111** is 7

**Group** : Must have read and execute. Should not have write permission. Binary notation is 101. Decimal equivalent of **101** is 5

**Others** : Must have execute. Should not have read and write permissions. Binary notation is 001. Decimal equivalent of **001** is 1.

**Command** `chmod 751 16-jan-2019.pdf`

# Re-directions Commands

Important Very important commands

# Re-directions Commands

**Important** Very important commands

**Output** Every command output is displayed on the shell itself

# Re-directions Commands

**Important** Very important commands

**Output** Every command output is displayed on the shell itself

**File** If the output of a command to be recorded into a file we must use re-direction commands

# Re-directions Commands

**Important** Very important commands

**Output** Every command output is displayed on the shell itself

**File** If the output of a command to be recorded into a file we must use re-direction commands

> **specified-output-file** Store output of a command to **specified-output-file**



# Re-directions Commands

**Important** Very important commands

**Output** Every command output is displayed on the shell itself

**File** If the output of a command to be recorded into a file we must use re-direction commands

> **specified-output-file** Store output of a command to **specified-output-file**

< **specific-input-file** **Input** to a command be read from **specific-input-file**

# Re-directions Commands

**Important** Very important commands

**Output** Every command output is displayed on the shell itself

**File** If the output of a command to be recorded into a file we must use re-direction commands

> **specified-output-file** Store output of a command to **specified-output-file**

< **specific-input-file** **Input** to a command be read from **specific-input-file**

Example 1 `ls -l > ls_output.txt`

# Re-directions Commands

**Important** Very important commands

**Output** Every command output is displayed on the shell itself

**File** If the output of a command to be recorded into a file we must use re-direction commands

> **specified-output-file** Store output of a command to **specified-output-file**

< **specific-input-file** **Input** to a command be read from **specific-input-file**

Example 1 `ls -l > ls_output.txt`

Example 2 `wc < ls_output.txt`

# Compiling a C program

Save file Using gedit save the file hello.c

# Compiling a C program

Save file Using gedit save the file hello.c

Compile `gcc hello.c`

# Compiling a C program

Save file Using gedit save the file hello.c

Compile `gcc hello.c`

a.out The above command result in a file named `a.out`

# Compiling a C program

**Save file** Using gedit save the file hello.c

**Compile** `gcc hello.c`

**a.out** The above command result in a file named `a.out`

**Executable** a.out by default has executable permission

# Compiling a C program

**Save file** Using gedit save the file hello.c

**Compile** `gcc hello.c`

**a.out** The above command result in a file named `a.out`

**Executable** a.out by default has executable permission

**Execute** `./a.out`