

P.MANOJ KUMAR REDDY

192511220

1. Identify and fix the error in the given SQL query that uses incorrect JOIN syntax and returns duplicate results.

```
mysql> SELECT * FROM Student;
+-----+-----+-----+-----+
| student_id | name | age | Department_id |
+-----+-----+-----+-----+
|          101 | Rahul | 20 |          101 |
|          102 | Priya | 21 |          102 |
|          103 | Arun  | 22 |          103 |
|          104 | Kiran | 20 |          104 |
|          105 | Neha  | 21 |          105 |
+-----+-----+-----+-----+
5 rows in set (0.010 sec)
```

2. The following sub-query returns incorrect results due to a missing correlation. Debug and rewrite it correctly.

```
mysql> CREATE TABLE Employee (
  ->     emp_id INT PRIMARY KEY,
  ->     emp_name VARCHAR(30),
  ->     salary INT,
  ->     Department_id INT,
  ->     FOREIGN KEY (Department_id) REFERENCES Department(Department_id)
  -> );
Query OK, 0 rows affected (1.288 sec)

mysql> INSERT INTO Employee VALUES
  -> (1, 'Rahul', 40000, 101),
  -> (2, 'Priya', 50000, 101),
  -> (3, 'Arun', 35000, 102),
  -> (4, 'Neha', 60000, 102),
  -> (5, 'Kiran', 45000, 103);
Query OK, 5 rows affected (0.207 sec)
Records: 5  Duplicates: 0  Warnings: 0

mysql> SELECT * FROM Employee;
+-----+-----+-----+-----+
| emp_id | emp_name | salary | Department_id |
+-----+-----+-----+-----+
|       1 | Rahul    | 40000  |          101 |
|       2 | Priya    | 50000  |          101 |
|       3 | Arun     | 35000  |          102 |
|       4 | Neha     | 60000  |          102 |
|       5 | Kiran    | 45000  |          103 |
+-----+-----+-----+-----+
5 rows in set (0.034 sec)
```

3.A given SQL view definition causes errors when queried. Identify the issue and rewrite a correct and optimized view.

```
mysql> SELECT * FROM Department_View;
+-----+-----+-----+
| Department_id | Departmem_name | block |
+-----+-----+-----+
|          101 | CSE            | AHS   |
|          102 | ECE            | ECE Block |
|          103 | Civil          | SCAD  |
|          104 | IT             | ADMIN |
|          105 | Bio-Tech       | RHS   |
+-----+-----+-----+
5 rows in set (0.044 sec)
```

```
mysql> CREATE OR REPLACE VIEW Department_View AS
-> SELECT
->     Department_id,
->     Departmem_name,
->     block
-> FROM Department;
Query OK, 0 rows affected (0.102 sec)
```

```
mysql> SELECT * FROM Department_View;
+-----+-----+-----+
| Department_id | Departmem_name | block |
+-----+-----+-----+
|          101 | CSE            | AHS   |
|          102 | ECE            | ECE Block |
|          103 | Civil          | SCAD  |
|          104 | IT             | ADMIN |
|          105 | Bio-Tech       | RHS   |
+-----+-----+-----+
5 rows in set (0.015 sec)
```

4. Debug the given relational algebra expression that produces incorrect output for a natural join operation.

```
mysql> SELECT e.student_id,
->         c.course_id,
->         c.course_name
-> FROM Enroll e
-> JOIN Course c
-> ON e.course_id = c.course_id;
```

student_id	course_id	course_name
101	1	DBMS
101	2	Java
102	2	Java
103	3	Python

4 rows in set (0.377 sec)

5. The SQL query below violates referential integrity. Identify the violation and modify the statements to enforce proper constraints

```
mysql> SELECT * FROM Employee;
```

emp_id	emp_name	salary	Department_id
1	Rahul	40000	101
2	Priya	50000	101
3	Arun	35000	102
4	Neha	60000	102
5	Kiran	45000	103
6	Rahul	40000	110

6 rows in set (0.009 sec)

```
mysql> SELECT * FROM Department;
```

Department_id	Department_name	numberofcourses	credits	block
101	CSE	32	192	AHS
102	ECE	32	192	ECE Block
103	Civil	30	190	SCAD
104	IT	32	192	ADMIN
105	Bio-Tech	32	192	RHS
110	Mechanical	30	180	ME Block

6 rows in set (0.010 sec)

```
mysql>
```

6. Given an inefficient SQL query with nested loops, rewrite it using JOIN to optimize performance


```
mysql> SELECT DISTINCT
->      c.customer_id,
->      c.customer_name,
->      c.city
-> FROM Customer c
-> JOIN Orders o
-> ON c.customer_id = o.customer_id;
+-----+-----+-----+
| customer_id | customer_name | city      |
+-----+-----+-----+
|          1 | Rahul         | Chennai  |
|          2 | Priya         | Bangalore|
|          4 | Neha          | Delhi    |
+-----+-----+-----+
3 rows in set (0.398 sec)

mysql> |
```

7. The GROUP BY query below produces wrong aggregation results. Debug the query and explain the error.

```
mysql> SELECT product_name,
->      SUM(quantity) AS Total_Quantity
-> FROM Sales
-> GROUP BY product_name;
+-----+-----+
| product_name | Total_Quantity |
+-----+-----+
| Pen          | 30             |
| Book         | 25             |
| Pencil       | 25             |
+-----+-----+
3 rows in set (0.011 sec)
```

8. Identify and fix the logical error in a given SQL UPDATE statement that unintentionally modifies all rows in the table

```
mysql> SELECT * FROM Student;
+-----+-----+-----+-----+
| student_id | name | age | Department_id |
+-----+-----+-----+-----+
| 101 | Rahul | 23 | 101 |
| 102 | Priya | 21 | 102 |
| 103 | Arun | 22 | 103 |
| 104 | Kiran | 20 | 104 |
| 105 | Neha | 21 | 105 |
+-----+-----+-----+-----+
5 rows in set (0.009 sec)
```

9. Optimize the given multi-table SQL query by restructuring sub-queries into JOINS and using appropriate indexes.

```
mysql> SHOW INDEX FROM Orders;
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| Table | Non_unique | Key_name | Seq_in_index | Column_name | Collation | Cardinality | Sub_part | Packed | Null | Index_type | Comment | Index |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| orders | 0 | PRIMARY | 1 | order_id | A | 4 | NULL | NULL | | BTREE | | |
| orders | 1 | idx_orders_customer | 1 | customer_id | A | 3 | NULL | NULL | YES | BTREE | | |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
2 rows in set (0.546 sec)
```

```
mysql> SHOW INDEX FROM Payment;
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| Table | Non_unique | Key_name | Seq_in_index | Column_name | Collation | Cardinality | Sub_part | Packed | Null | Index_type | Comment | Index |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| payment | 0 | PRIMARY | 1 | payment_id | A | 3 | NULL | NULL | | BTREE | | |
| payment | 1 | idx_payment_order | 1 | order_id | A | 3 | NULL | NULL | YES | BTREE | | |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
2 rows in set (0.182 sec)
```

10. Debug a given relational calculus expression that returns an empty result set due to incorrect quantifier usage.

```
mysql> SELECT * FROM Student;
```

student_id	name	age	Department_id
101	Rahul	23	101
102	Priya	21	102
103	Arun	22	103
104	Kiran	20	104
105	Neha	21	105

```
5 rows in set (0.008 sec)
```

```
mysql> SELECT s.student_id,  
-> s.name,  
-> d.Departmem_name  
-> FROM Student s  
-> JOIN Department d  
-> ON s.Department_id = d.Department_id;
```

student_id	name	Departmem_name
101	Rahul	CSE
102	Priya	ECE
103	Arun	Civil
104	Kiran	IT
105	Neha	Bio-Tech

```
5 rows in set (0.011 sec)
```

```
mysql> |
```