

MITIGATION OF WATER LOGGING IN DISTRICT RAHIMYARKHAN

BOQ

Sr. No	Item	Unit	Total QTY	Rate	Amount (PKR)	Rate		Amount Rupees (PKR)
						Rs. In Figures	Rs. In Words	
1	Earth Work in excavation of drains, irrigation channels through excavator/ drag lines in all kind of soil and conditions (dry, wet slush, daldal and under water) including its disposal and preperation of working pad for operation of machinery. (rates includes 100ft lead)	1000 Cft	69,775,243.96	4,640.70	323,805,974.65			
2	Dressing and levelling of earthwork to designed section etc complete in ii) ordinary or hard soil soil	1000 Cft	26,864,727.17	940.90	25,277,021.79			
3	Transportation of earth all types when the total distance, including the lead covered in the item of work , is more than 1000 ft.		-	-	-			
	a) 500 ft	1000 Cft	546,147.50	1,073.20	586,125.50			
	b) 750 ft	1000 Cft	989,635.00	1,743.95	1,725,873.96			
	c) 1000 ft	1000 Cft	275,885.29	2,414.70	666,180.21			
	d) 1250 ft	1000 Cft	62,477.50	6,677.80	417,212.25			
	e) 1500 ft	1000 Cft	549,295.00	6,751.20	3,708,400.40			
	f) 1750 ft	1000 Cft	555,572.50	6,751.20	3,750,781.06			
	g) 2000 ft	1000 Cft	18,740.00	6,824.60	127,893.00			
	h) 2500 ft	1000 Cft	53,390.00	6,971.40	372,203.05			
	i) 2750 ft	1000 Cft	75,040.00	6,971.40	523,133.86			
	j) 3000 ft	1000 Cft	98,265.75	7,044.80	692,262.56			
	k) 3750 ft	1000 Cft	187,560.00	7,191.60	1,348,856.50			
	l) 4250 ft	1000 Cft	54,772.50	7,338.40	401,942.51			
	m) 4500 ft	1000 Cft	125,720.00	7,411.80	931,811.50			
	n) 5500 ft	1000 Cft	70,367.50	7,558.60	531,879.79			
	o) 6750 ft	1000 Cft	4,869.33	7,934.10	38,633.75			
4	Borrowpit excavation undressed lead upto 100 ft (30 metre) in a) ordinary soil with	1000 Cft	-	-	-			
	a) 250 ft	1000 Cft	140,702.29	10,936.05	1,538,727.22			
	b) 500 ft	1000 Cft	1,887,045.50	11,606.80	21,902,559.71			
	c) 1000 ft	1000 Cft	97,969.47	12,948.30	1,268,538.02			
	d) 1 mile	1000 Cft	159,193.80	18,092.20	2,880,166.07			
5	Rehandling of earthwork lead upto 50ft (35% of excess cutting)	1000 Cft	1,340,460.58	5,266.80	7,059,937.76			
6	Providing and erection at site of work:- iii) R.C.C. boundary pillar. (Complete in all respect including transportation, Cement concrete foundation, fixing, painting and lettering etc)	1 No	1,254.00	1,326.20	1,663,054.80			
7	Making boundary or service roads, including dag-belling, leveling and dressing:ii) in ploughed land: a) from 10.0 ft. to 20.0 ft. (3 to 6 m) wide	1 -Chain	1,740.00	1,935.40	3,367,596.00			
8	Jungle clearance and removing within 100 ft. light	1000 Sft	6,885,050.00	376.20	2,590,155.81			
9	Providing and fixing Enamelled steel plate gauge 4" wide 1/4" thick (including painting and lettering) 10 ft length	1 No	5.00	14,630.00	73,150.00			
10	Excavation in foundation of building bridges and other structures including dagbelling, dressing, refilling around structure with excavated earth, watering and ramming lead upto one chain and lift upto 5 ft. in ordinary soil	1000 Cft	1,617.00	15,824.15	25,587.65			
11	Cement concrete plain including, placing, compacting, finishing and curing complete (including screening and washing of stones aggregate)	100 Cft	-	-	-			
	a) Nominal mix ratio 1:4:8	100 Cft	41,070.55	34,694.30	14,249,141.27			
	b) Nominal mix ratio 1:2:4	100 Cft	12,898.73	47,135.90	6,079,931.59			
12	Pacca brick work in foundation and plinth in cement sand mortar ratio 1:6.	100 Cft	58,371.56	32,675.95	19,073,460.29			
13	Providing and laying damp proof course of cement 1:2:4 (using cement, sand and shingle), including bitumen coating with with 2 coats of bitumen: 1½" thick (40 mm).	100 Sft	643.50	11,851.20	76,262.47			
14	Providing and laying damp proof course of cement 1:2:4 (using cement, sand and shingle), including bitumen coating with one coat of bitumen and one coat polythensheet 500 gauge 1½" thick (40 mm).	100 Sft	11,220.61	11,460.20	1,285,904.28			
15	Providing and laying damp proof course of cement 1:2:4 (using cement, sand and shingle), including bitumen coating with 2 coats of bitumen: 1½" thick (40 mm).	100 Sft	427.50	11,851.60	50,665.59			
16	Pacca brick work other than building upto 10 ft. height in cement sand mortor ratio 1:3	100 Cft	1,348.10	37,620.60	507,163.90			
17	Cement plaster 1:4 upto 20 ft. height, 3/8" thick	100 Sft	3,805.73	4,334.75	164,968.66			

MITIGATION OF WATER LOGGING IN DISTRICT RAHIMYARKHAN

BOQ

Sr. No	Item	Unit	Total QTY	Rate	Amount (PKR)	Rate		Amount Rupees (PKR)
						Rs. In Figures	Rs. In Words	
18	Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect:	100 Sft	61,675.40	7,379.10	4,551,089.76			
19	Writing letter or figures per letter per inch height	1 No	8,250.00	30.50	251,625.00			
20	Carriage of 100 Cf t. (2.83 cu.m) of all materials like stone aggregate, spawl, kankar lime (unslaked), surkhi , etc. or 150 Cf t. (4.25 cu.m) timber, by truck or by any othermeans owned by the contractor from Sakhi Sarwar Quarry to site 275 Km including first 11KM hilly area.	-	-	-	-			
	DPC	100 Cft	70.79	14,042.60	9,940.05			
	PCC 1:2:4	100 Cft	5,036.58	14,042.60	707,267.00			
	PCC 1:4:8	100 Cft	30,772.14	14,042.60	4,321,209.18			
	RCC 1:1.5:3	100 Cft	106,108.06	14,042.60	14,900,329.90			
	Base	100 Cft	2,183.80	14,042.60	306,662.30			
	T.S.T	100 Cft	268.50	14,042.60	37,704.38			
	RCC 1:2.4	100 Cft	24,736.50	14,042.60	3,473,647.08			
	DPC 1:2.4	100 Cft	1,234.27	14,042.60	173,323.18			
	Dry Hand Pack Stone	100 Cft	15,224.76	14,042.60	2,137,952.68			
21	Precast reinforced cement concrete type "C" 1:2:4.	1 Cft	786.04	546.95	429,924.58			
22	Fabrication of mild steel reinforcement for cement concrete including cutting bending laying in position etc. complete in all respect. (deformed bars) Grade 40	100 Kg	1,796.01	30,006.10	538,912.56			
23	Carriage of consignment job upto 5 KMs Average	1 No	457.00	115.40	52,737.80			
24	Placing boundary pillars in position, including digging pits.	1 Each	457.00	141.90	64,848.30			
25	Preparing surface and painting with emulsion paint 3 coat.	100 Sft	1,599.50	4,307.55	68,899.26			
26	Writing letter or figures per letter per inch height (three figure each side).	1 No	4,570.00	30.50	139,385.00			
27	Earthwork excavation undressed lead upto a single throw of Kassi, phaorah or shovel: In ordinary soil.	1000 Cft	245.00	546.95	134.00			
28	Cement concrete plain including placing, compacting, finishing and curing complete (including screening and washing of stone aggregate) Ratio 1: 2: 4	100 Cft	367.50	30,006.10	110,272.42			
29	Providing, laying, cutting, jointing, testing and disinfecting G.I. pipeline in trenches, with socket joints, using G.I. pipes of B.S.S. 1387-1967 complete in all respects, with specials and valves. i) 4" i/d (100 mm) 3.65mm thick	1 Rft	560.00	115.40	64,624.00			
30	Carriage of 100 Cft of all material like stone aggregate, spawl, kankar, lime (unsoaked) surkhi etc by truck or by any other means owned by the contractor, lead 300Km.(From Sakhi Sarwar)	100 Cft	323.40	141.90	458.90			
31	Dismantling brick work in lime or cement mortar	100 Cft	1,823.07	2,633.40	48,008.66			
32	Dismantling and removing road pavement, etc.,including screening and stacking of byproducts upto one chain lead (30 metre).	100 Cft	4,635.00	4,017.80	186,225.03			
33	Dismantling cement concrete reinforced, separating reinforcement from concrete, cleaning and straightening the same.	100 Cft	13,340.27	27,086.40	3,613,398.89			
34	Excavation in foundation of building, bridges and other structures, including dagbelling, dressing, refilling around structure with excavated earth, watering and ramming lead up to one chain and lift upto 5 ft. In ordinary soil (above 5 ft depth)	1000 Cft	588,089.43	12,735.60	7,489,671.70			
35	Providing and Fabrication of mild steel reinforcement for cement concrete, including cutting, bending, laying in position, 13 making joints and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars):- Deformed bars (Grade-60).	100 Kg	1,015,459.21	30,376.90	308,465,028.62			
36	Providing and laying reinforced cement concrete (including prestressed concrete), using Sulphate resisting cement ; coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete 2) Plastering done under soffit of R.C.C. (but excluding the cost of steel reinforcement, its fabrication and placing in position etc.)	-	-	-	-			

MITIGATION OF WATER LOGGING IN DISTRICT RAHIMYARKHAN

BOQ

Sr. No	Item	Unit	Total QTY	Rate	Amount (PKR)	Rate		Amount Rupees (PKR)
						Rs. In Figures	Rs. In Words	
a)	Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects. Type B (nominal mix 1:1.5:3)	1 Cft	174,842.05	817.55	142,942,120.51			
b)	Reinforcement cement concrete in slab of rafts/strip foundation, base slab of column and retaining walls, etc and other structural members not requiring form work(i.e horizontal shuttering) complete in all respect: Type B (Nominal Mix 1:1.5:3)	1 Cft	77,484.51	670.50	51,953,365.16			
37	Providing and embedding 10"(250mm) wide PVC water stopper in expansion joints of RCC structures (Retaining walls, water tanks, Slabs) complete in all respect. 10mm thick	1 Rft	6,423.48	809.40	5,199,164.71			
38	Bitumen coating to plastered or cement concrete surface. 14 lbs per 100 Sft (6.35 Kg. per Sq.m)	100 Sft	99,728.81	1,645.10	1,640,638.71			
39	Providing, laying, cutting, jointing, testing and disinfecting PVC/ uPVC pipe line with `B` Class working pressure complete in all respects:- 4" i/d (100 mm)	1 Rft	11,417.00	514.90	5,878,613.30			
40	Providing and fixing 4" dia P.V.C pipe.	1 Rft	48.00	378.75	18,180.00			
41	Supply and erection PVC pipe for recessed wiring (main and sub-main) purpose, including bends, specials, etc. in floor, wall or trenches:- 80mm dia (3 inch)	1 Rft	169.50	303.80	51,494.10			
41	Providing and laying R.C.C. pipe sewers, moulded with cement concrete 4000 psi conforming to Specification C-76-20, Class II. Wall B, including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing with rubber ring, cutting pipes where necessary, testing, etc., complete. 24 inch internal dia	1 Rft	624.00	2,150.35	1,341,818.40			
43	Providing and laying sub-base course of stone product of approved quality and grade, including placing, mixing, spreading and compaction of sub-base material to required depth, camber, grade to achieve 100% maximum modified AASHTO dry density, including carriage of all material to site of work except gravel and aggregate. Crushed stone aggregate.	100 Cft	4,715.00	10,003.50	471,665.03			
44	Providing and laying base course of crushed stone aggregate of approved quality and grade, and supply and spreading of stone screening, including placing, mixing, spreading and compaction of base course material to required depth, camber and grade to achieve 100% maximum modified AASHTO dry density, including carriage of all materials to site of work except gravel and aggregate.	100 Cft	2,615.00	13,527.40	353,741.51			
45	Providing and laying road edging of 3" (75 mm) wide and 9" (225 mm) deep brick on end, complete in all respects	1 Rft	700.00	64.20	44,940.00			
46	Providing surface treatment of roads, including supply of bitumen and bajri/crushed stone aggregate of approved quality, including cleaning of road surface, heating, spraying bitumen, spreading bajri and rolling etc. complete including carriage of all material to site of work except bajri/crushed stone aggregate for which supply within 5 miles (5.0km) is included in the rate.		-					
a	1st coat 35 lbs. bitumen, and 4 Cft. bajri of nominal size 1" (25 mm) per 100 sq. feet or 1.72 Kg bitumen and 0.017 cu. metre bajri per square metre.	100 Sft	5,230.00	4,549.95	237,962.39			
b	2nd coat 18 lbs. bitumen, and 2 Cft. bajri of nominal size ½" (13 mm) per %sft or 1.23 Kg bitumen and 0.008 cu. metre bajri per sq. metre.	100 Sft	5,230.00	2,639.45	138,043.24			
c	3rd coat 14 lbs. bitumen, and 1.5 Cft. bajri of nominal size ¼" (6 mm) per %sft or 0.69 Kg bitumen and 0.005 cubic metre bajri per sq. metre.	100 Sft	5,230.00	1,960.75	102,547.23			
47	Borrow pit excavation undressed lead up to 100 ft in ordinary soil.	1000 Cft	123,165.00	10,533.60	1,297,370.84			
48	Cement plaster 1:3 upto 20' (6.00 m) height 1/2" (13 mm) thick.	100 Sft	15,594.50	4,850.40	756,395.63			
49	Providing and laying base course.	100 Cft	2,100.00	13,527.40	284,075.40			

MITIGATION OF WATER LOGGING IN DISTRICT RAHIMYARKHAN

BOQ

Sr. No	Item	Unit	Total QTY	Rate	Amount (PKR)	Rate		Amount Rupees (PKR)
						Rs. In Figures	Rs. In Words	
50	Providing surface treatment to roads, including supply of bitumen and bujri /crushed stone aggregate of approved quality, including cleaning of road surface, heating and spraying bitumen, spreading bajri and rolling with road roller (including its operation cost, fuel and hire charges, etc.) etc. complete including carriage of all materials to site of work except bajri/crushed stone aggregate.	100 Sft	2,800.00	4,549.95	127,398.60			
51	Providing and fixing Neoprene bearing pad with laminated steel plate top and bottom. Size (14" x 9" x 1.75")	Cu. Inch	304.64	72.00	21,934.08			
52	Plain wood work for regulation karries or needles, etc. including sawing, planning, wroughting wood and providing and fixing steel parts of karries i.e. end strip and rods, etc. b) Shisham wood	1 Cft	202.95	17,752.20	3,602,808.99			
53	Credit old material - steel	1 Kg	(26,974.04)	170.00	(4,585,586.80)			
54	Credit old material - brick batts	100 Kg	(1,823.07)	4,100.00	(74,745.87)			
55	Extra for slush or Daldal including dewatering.	1000 Cft	333,466.17	12,038.40	4,014,399.13			
56	Pacca brick work other than buildings upto 10 feet height. Cement sand mortar ratio 1:4	100 Cft	13,799.15	35,727.00	4,930,022.32			
57	Providing and placing poly sulphide joint sealent 1" wide and 1" deep.	1 Rft	1,670.00	1,381.00	2,306,270.00			
58	Dismantling stone or spawl pitching and apron in silted condition.	100 Cft	93,240.00	3,762.00	3,507,688.80			
59	Supply and dumping at site, without boat, including handling of materials within three chains (90 m)	100 Cft	126,000.00	4,743.75	5,977,125.00			
60	Providing and laying stone pitching/filling, dry hand packed, as filling behind retaining walls or in pitching and aprons.	100 Cft	50,517.80	6,849.00	3,459,964.12			
61	Formation dressing and preparing subgrade, on slope	100 Sft	94,646.55	2,265.10	2,143,838.93			
62	Formation dressing and preparing subgrade, in bed.	100 Sft	15,600.14	1,660.50	259,040.32			
63	Providing and laying graded bajri 1/8" to 1/2" size on slope.	100 Cft	32,048.50	18,564.10	5,949,516.49			
64	Providing and laying graded bajri 1/2" to 2" size on slope.	100 Cft	32,048.50	18,564.10	5,949,516.49			
65	Providing and laying graded bajri 1/8" to 1/2" size on level.	100 Cft	5,305.09	18,017.60	955,849.72			
66	Providing and laying graded bajri 1/2" to 2" size on level.	100 Cft	5,305.09	18,017.60	955,849.72			
67	Providing and laying stone for top layer only, on slope.	100 Cft	97,109.84	11,511.00	11,178,314.01			
68	Providing and laying stone for top layer only, on Level	100 Cft	15,372.42	10,570.50	1,624,941.66			
69	Carriage of 100 Cft of all material like stone aggregate, spawl, kankar, lime (unsoaked) surkhi etc or 150 Cft of timber by truck or by any other means owned by the contractor, lead 275 Km.	100 Cft	364,527.73	14,042.60	51,189,171.57			
70	Credit to old material		-					
	Steel	1 Kg	2,535.00	(170.00)	(430,950.00)			
	Brick batts	100 Cft	1,819.13	(4,100.00)	(74,584.33)			
71	Excavation in foundation of building, bridges, and other structures, including dag belling, dressing refilling around structure with excavated earth, watering and ramming lead upto one chain (30m)and lift upto 5' (1.5 m) (b) in ordinary soil.1)By Manual	1000 Cft	20,161.00	15,824.15	319,030.70			
72	Spraying termite proofing by using liquid FMC / Biflex/ Terminex Exin/Ms Hextaror equivalent@specified suspension concentrate (SC), MixingAbility-HEXTAR with Ratio (1:250)= 540 Sft or equivalent approved liquid applying with shower and certificate will be provided by the contractor for10-years complete in all respect.as approved by the Engineer Incharge.	1 Sft	18,814.50	12.55	236,121.98			
73	Providing and laying vertical damp proof course with cement sand plaster and bitumen coating with one coat of bitumen and one coat of polythene sheet 500 gauge-Ratio 1:3 a) ½ " thick (13 mm)	100 Sft	13,211.49	7,607.35	1,005,044.28			
74	Filling watering ramming earth under floors with surplus earth from foundation etc.	1000 Cft	37,224.37	7,547.75	280,960.24			
75	Pacca brick work in ground floor. Cement sand mortar Ratio 1:4.	100 Cft	10,763.30	35,830.60	3,856,554.97			
76	Providing and laying reinforced cement concrete (including prestressed concrete), using Sulphate resisting cement ; coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete 2) Plastering done under soffit of R.C.C. (but excluding the cost of steel reinforcement, its fabrication and placing in position etc.)		-	-	-			

MITIGATION OF WATER LOGGING IN DISTRICT RAHIMYARKHAN

BOQ

Sr. No	Item	Unit	Total QTY	Rate	Amount (PKR)	Rate		Amount Rupees (PKR)
						Rs. In Figures	Rs. In Words	
a)	Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects. Type B (nominal mix 1:2:4)	1 Cft	5,704.13	741.85	4,231,612.25			
b)	Reinforcement cement concrete in slab of rafts/strip foundation, base slab of column and retaining walls, etc and other structural members not requiring form work(i.e horizontal shuttering) complete in all respect: Type B (Nominal Mix 1:2:4)	1 Cft	681.09	595.00	405,247.99			
77	Providing and fixing windows consisting of M.S box section frame 2" x 1½" (50 x 40mm) Leaves frame 1½" x 1" (40 x 25 mm) box section frame for glazing 3/8" x 3/8" (10 x 10 mm) using 16 SWG sheet 'U' shaped rubber supported with 1" x 1/8" (25 x 3 mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section 1/2" x 1/2" (13 x 13 mm) of 16 SWG for fixing 24 SWG wire gauge on outer side by means of 3/4" x 1/8" (20 x 3 mm) M.S. flat and screws including grill of M.S. flat 1/2" x 1/8" (13 x 3 mm) or 1/4" x 1/4" (6 x 6 mm) square bar with independent frame of 1/2" x 1/2" (13 x 13 mm) box section of 16 SWG i/c all C.P fitting and painting 3 coats complete in all respect.	1 Sft	1,184.00	2,180.70	2,581,948.80			
78	Providing and fixing mild steel chowkat of doors windows C. windows etc. including holdfast making and threading 18 holes for hinges etc. complete 1½" x 1½" x 1/4" (40 x 40 x 6 mm) welded with M.S. flat 2" x 1/4" (50 m M.S. angle iron).	1 Sft	5,302.00	457.10	2,423,544.20			
79	Making and fixing steel grated door with 1/16" thick sheeting, including angle iron frame 2" x 2" x 3/8" and 3/4" square bars 4" centre to centre. with locking arrangement (Two No.).	1 Sft	1,813.00	2,767.00	5,016,571.00			
80	Providing and laying single layer of tile 9" x 4½" x 1½" laid over 4" earth and 1" thick mud plaster without bhoosa, grouted with cement mud (1:3) on top of R.C.C. roof, slab, provided with 34 lbs. per % Sft. Or 1.72 Kg./Sq.m. bitumen coating sand blinded.	100 Sft	3,535.81	13,179.60	466,005.94			
81	Providing and laying polythene sheet under floor or roof complete 500 gauge.	1 Sft	43,350.19	11.00	476,852.08			
82	Supplying and filling sand under floor or plugging in wells.	100 Cft	8,934.83	3,987.00	356,231.57			
83	Providing and laying watering and ramming brick ballast 1½" to 2" (40 mm to 50 mm) mixed with 25% sand for floor foundation complete in all respect.	100 Cft	10,919.79	12,801.20	1,397,863.84			
84	Cement plaster 1:4 upto 20' (6.00 m) height 1/2" (13 mm) thick.	100 Sft	140,437.42	4,614.10	6,479,922.82			
85	Cement plaster 3/8" (10 mm thick under soffit of R.C.C. roof slabs only, upto 20' height (Ratio 1:3).	100 Sft	4,237.24	5,264.65	223,075.86			
86	Cement pointing struck joints on wall upto 20' (6m) height (a) Ratio 1:2 including extra cost of labour and material for red oxide pigment in cement pointing to match with the colour of bricks.	100 Sft	83,405.59	5,012.65	4,180,830.31			
87	Providing and installing P.V.C. bends, of B.S.S.b) 4" i/d (100 mm)	1 No	658.00	849.70	559,102.60			
88	Making top khurra on roof 2' x 2' x 6".	1 No	154.00	1,159.65	178,586.10			
89	Distempering:- 3 coat	100 Sft	118,808.23	1,548.20	1,839,388.98			
90	Preparing surface and painting of doors and windows any type (including edges):-	100 Sft	12,309.00	3,052.40	375,719.92			
91	Fabrication of heavy steel work, with angle, tees, flat iron round iron and sheet iron for making trusses, girders, tanks, etc., including cutting, drilling, revitting, handling, assembling and fixing, but excluding erection in position.	100 Kg	12,393.47	37,098.85	4,597,835.86			
92	Supply and erection of PVC pipe for wiring recessed in walls, including inspection boxes, pull boxes, hooks, cutting jharries and repairing surface, etc. complete with all specials.		-					
	a) 20mm (3/4") i/d.	1 Rft	12,520.00	112.25	1,405,370.00			
	b) 25 mm (1") i/d	1 Rft	6,560.00	133.60	876,416.00			
	c) 50 mm (2") i/d	1 Rft	555.00	231.55	128,510.25			
93	Supply and erection of single core PVC insulated copper conductor cables, in prepaid P.V.C. pile/M.S. conduit/G.I. pipe/wooden strip batten/wooden casing and capping/G.I. wire/trenches (rate for cables only) (a) 250/440 volts, P.V.C. insulated.		-					
	a) 3/0.74mm (3/0.029").	1 Rft	36,960.00	35.70	1,319,472.00			
	b) 7/0.74mm (7/0.029").	1 Rft	13,020.00	56.30	733,026.00			

MITIGATION OF WATER LOGGING IN DISTRICT RAHIMYARKHAN

BOQ

Sr. No	Item	Unit	Total QTY	Rate	Amount (PKR)	Rate		Amount Rupees (PKR)
						Rs. In Figures	Rs. In Words	
94	Supply and erection of copper conductor cable for service connection in prepaid pipe/G.I. wire/trenches, etc. (rate for cable only) (a) PVC insulated, PVC sheathed, twin core, 250/440 volts 7/0.44" (7/1.12mm).	1 Rft	19,680.00	237.65	4,676,952.00			
95	Supply and connection of M.S. sheet box of 16 SWG, 10 cm (4") deep with 4.75 mm thick (3/16") bakelite sheet top, for recessed wiring, including making holes for regulators switches, plugs etc. a) 10 x 10 cm (4" x 4"). b) 17.5 x 10 cm (7" x 4"). c) 22.5 x 10 cm (9" x 4").	1 Each 1 Each 1 Each	219.00 432.00 128.00	382.30 522.75 668.80	83,723.70 225,828.00 85,606.40			
96	Supply and erection of switches 5 amp. Piano Type.	1 Each	4,100.00	102.70	421,070.00			
97	Supply and erection of ceiling rose, bakelite.	1 Each	744.00	96.30	71,647.20			
98	Supply and erection of 3 pin switch and plug combined recessed type (ii) 10/15 amp.	1 Each	37.00	213.10	7,884.70			
99	P/F wall mounted DB (Distribution Board) made with 16SWG Sheet (Recessded/Surface mounted Type), Powder coated Paint, i/c the cost of Lock, Indication lights,Thimble, Copper Comb, Wiring, Netural & Earth Bar, Door Earthing, Digital Voltmeter,Digital Ammeter,Volt Selector Switch,Ammeter selector switch,Current Transformers and Controles Complete in all respect as approved and directed by the Engineer Incharge (Breakers will be Paid Separately)(a) 6" deep (i) 20~60A	1 No	37.00	24,422.65	903,638.05			
100	Suppling,Installation and comissioning of MCB (Miniature Circuit Breaker) of specified rating made of LEGRAND FRANCE/ GE U.S.A / SCHNEIDER GERMANY /SIEMEN GERMAN/TERASAKI JAPAN/ ABB SWITZERLAND in prelaid DBs and Panels i/c the cost of screws,necessary wire complet Single Pole(iii) 6-63 Amp (10 KA)	1 No	222.00	1,453.75	322,732.50			
101	Supplying, Installation and commissioning of MCCB (Moulded Case Circuit Breaker)of specified rating made of LEGRAND FRANCE /GEU.S.A/ SCHNEIDER GERMANY/ TERASAKI JAPAN/ SIEMEN/ ABBSWITZERLAND or approved equivalent manufacturer (withfixedThermal-MagneticTrip)in prelaid DB sand Panels i/c the cost of screws, necessary wire complete in all respect as approved and directed by the EngineerIncharge. a) Triple Pole (ii) 15-100 Amp (10 KA,15KA)	1 No	74.00	13,796.30	1,020,926.20			
102	Supplying, Installation and commissioning of MCCB (Moulded Case Circuit Breaker)of specified rating made of LEGRAND FRANCE /GEU.S.A/ SCHNEIDER GERMANY/ TERASAKI JAPAN/ SIEMEN/ ABBS WITZERLAND or approved equivalent manufacturer (withfixedThermal-MagneticTrip)in prelaid DB sand Panels i/c the cost of screws, necessary wire complete in all respect as approved and directed by the EngineerIncharge. a) Triple Pole With Adjustable Thermal-Magnetic Trip /Electronic Trip (60-100%) (i) 25-100 Amp	1 No	37.00	19,859.40	734,797.80			
103	Supply and erection of tube light, including rod, choke, starter with frame, flexible wire, including connection from ceiling rose, etc., complete ii)single rod (40 watts) with one choke and one starter.	1 No	707.00	1,995.30	1,410,677.10			
104	Supply and erection of bakelite button holder shade, large size	1 No	111.00	178.75	19,841.25			
105	Single layer of tiles 9"x4½"x1½" (225x113x40 mm) laid over 4"(100 mm) earth and 1" (25 mm) mud plaster without Bhoosa, grouted with cement sand 1:3 on top of RCC roof slab, provided with 34 lbs. per %Sft. or 1.72 Kg/Sq.m bitumen coating sand blinded.	100 Sft	5,447.53	13,179.60	717,963.01			
106	Providing and fixing windows consisting of M.S. box section frame 2"x1½", (50x40mm) leaves frame 1½"x1" (40x25mm) box section frame for glazing 3/8"x3/8" (10x10mm) using 16 SWG sheet 'U' shaped rubber supported with 1"x1/8" (25x3mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section ½"x½" (13x13mm) of 16 SWG for fixing 24 SWG wire gauze on outer side by means of ¾"x1/8" (20x3mm) M.S. flat and screws including grill of M.S. flat ½"x1/8" (13x3mm) or ¼"x¼" (6x6mm) square bar with independent frame of ½"x½" (13x13mm) box section of 16 SWG i/c all C.P. fitting and painting 3 coats complete in all respect.	1	1,983.60	2,180.70	4,325,636.52			
107	Making and fixing steel grated door with 1/16" thick 1.5mm) sheeting, including angle iron frame 2"x2"x3/8" (50x50x10 mm) and ¾" (20 mm) square bars 4" (100 mm)	1 Sft	908.00	2,767.00	2,512,436.00			

MITIGATION OF WATER LOGGING IN DISTRICT RAHIMYARKHAN

BOQ

Sr. No	Item	Unit	Total QTY	Rate	Amount (PKR)	Rate		Amount Rupees (PKR)
						Rs. In Figures	Rs. In Words	
108	Distempering:- 2 coats	100 Sft	19,399.65	1,212.35	235,191.62			
109	Providing and fixing 1½"x1¼"x3/16" (31x31x5 mm) angle" iron step, in manhole chambers, including carriage and setting the same in work to correct lines and levels.	1 No	369.00	680.75	251,196.75			
110	Providing/fixing stair railing consisting of M.S. Box section size 1-1/2"x3" of 16 SWG welded with M.S. flat 1"x1/8" continuously and welded over M.S. square bars 5/8"x5/8"punched in M.S. flat 2 ¾" high @ 5½" c/c fixed in steps of stair I/C painting 3 coats complete.	1 Rft	111.86	1,125.20	125,864.87			
111	Providing and fixing trash rack as per drawing	1 Sft	2,800.00	603.00	1,688,400.00			
112	Providing and layingTuff Pavers, having 7000PSI ,crushing strength of approved manufa cturer, over2"to3" sand cushion i/c grouting withsand in joints i/c finishing to require slope . complete in all respect. (50% Grey / 50% Coloured) 60-mm thick	1 Sft	9,477.06	205.40	1,946,587.84			
113	Providing & laying graded bajri ½" to 2" gauge on level (including carriage).	100 Cft	2,287.97	18,017.60	412,237.28			
114	1½"(40 mm) thick mosaic flooring, consisting of ½ " mosaic topping of one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over 1"(25 mm) thick floor of 1:2:4 cement concrete, including rubbing and polishing complete with finishing :-using grey cement	100 Sft	5,447.53	29,658.50	1,615,656.46			
115	Mosaic dado or skirting with one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over ½"(13 mm) thick cement plaster 1:3, including rubbing and polishing, complete with finishing:(a) using grey cement: i) 1/2"(13 mm) thick	100 Sft	385.13	19,146.85	73,740.26			
116	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels(a) Size 1½" x 3/8" (40 x 10 mm)	1 Rft	2,922.31	39.60	115,723.48			
117	Supply and erection of backlite button holder shade, large size.	1 Each	596.00	178.75	106,535.00			
118	Suppling,Installation and comissioning of MCB (Miniature Circuit Breaker) of specified rating made of LEGRAND FRANCE/ GE U.S.A / SCHNEIDER GERMANY /SIEMEN GERMAN/TERASAKI JAPAN/ ABB SWITZERLAND in prelaid DBs and Panels i/c the cost of screwes,necessary wire completb) Double Pole(iii) 6-63 Amp (10 KA)	1 No	5.00	5,616.25	28,081.25			
119	Suppling,Installation and comissioning of MCB (Miniature Circuit Breaker) of specified rating made of LEGRAND FRANCE/ GE U.S.A / SCHNEIDER GERMANY /SIEMEN GERMAN/TERASAKI JAPAN/ ABB SWITZERLAND in prelaid DBs and Panels i/c the cost of screwes,necessary wire complet Single Pole(iii) 6-63 Amp (10 KA)	1 No	29.00	1,453.75	42,158.75			
120	Providing and fixing Pakistan Energy Label NEECA approved Copper winded wall bracket Fan i/c the cost of necessary cable and hardware for connection as approved and directed by Engineer Incharge.ii) 24" Sweep dia	1 Each	34.00	11,398.45	387,547.30			
121	Barrow pit excavation undressed lead up to 100 ft in ordinary soil.	1000 Cft	58,871.79	10,533.60	620,131.89			
122	Compaction of earth work with power Road Roller, i.c ploughing mixing, moistening earth to optimum moisture content in layer etc; complete 90 % maximum modified AASHO dry denisty	1000 Cft	58,871.79	1,437.50	84,628.20			
123	Earthwork excavation in irrigation channels, drains, etc. to designed section, grades and profiles, excavated material disposed off undressed within 50 ft. (15 m) lead:- ordinary Soil	1000 Cft	14,550.01	5,033.70	73,240.39			
	Cement plaster 1.5" (40 mm) thick ratio 1:6:-							
	a) In bed	100 Sft	2,500.00	6,512.05	162,801.25			
	b) On slope	100 Sft	3,876.00	7,363.45	285,407.32			
124	Cement concrete lining, using washed screened and graded stone aggregate:-							
	a) In bed, ratio 1:2:4	100 Cft	856.25	49,016.90	419,707.21			
	b) On slope, ratio 1:2:4	100 Cft	1,327.53	51,301.80	681,046.79			
125	Providing and placing cement, sand and bituminous joint sealant in ratio 1:2:3, 1/2" wide, 1" deep.	1 Rft	637.60	17.30	11,030.48			
126	Bitumen coating to plastered or cement concrete surface:- 10 lbs. per 100 Sft.	100 Sft	318.80	1,539.80	4,908.88			
127	Excavation in foundation of building, bridges, and other structures, including dag belling, dressing refilling around structure with excavated earth, watering and ramming lead upto one chain (30m)and lift upto 5' (1.5 m) (b) in ordinary soil. By Manual	1000 Cft	46,483.39	15,824.15	735,560.18			

MITIGATION OF WATER LOGGING IN DISTRICT RAHIMYARKHAN

BOQ

Sr. No	Item	Unit	Total QTY	Rate	Amount (PKR)	Rate		Amount Rupees (PKR)
						Rs. In Figures	Rs. In Words	
128	Providing and laying reinforced cement concrete (including prestressed concrete), using Sulphate resisting cement; coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete 2) Plastering done under soffit of R.C.C. (but excluding the cost of steel reinforcement, its fabrication and placing in position etc.)	-	-	-	-			
129	Providing and laying dry, hand packed stone apron as per drawing	100 Cft	11,277.60	6,849.00	772,403.02			
130	Excavation in foundation of building, bridges, and other structures, including dag belling, dressing refilling around structure with excavated earth, watering and ramming lead upto one chain (30m)and lift upto 5' (1.5 m) (b) in ordinary soil. By Manual	1000 Cft	72,531.66	15,824.15	1,147,751.93			
131	Spraying antitermite liquid mixed with water ratio 1:40	1 Sft	88,776.19	12.55	1,114,141.15			
132	Pacca brick work in ground floor. Cement sand mortar Ratio 1:4	100 Cft	47,794.11	35,830.60	17,124,916.38			
133	Providing and laying reinforced cement concrete (including prestressed concrete), using Sulphate resisting cement ; coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete 2) Plastering done under soffit of R.C.C. (but excluding the cost of steel reinforcement, its fabrication and placing in position etc.) - a) Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects. Type C (nominal mix 1:2:4)	1 Cft	21,724.43	741.85	16,116,268.40			
134	Providing and fixing windows consisting of M.S box section frame 2" x 1½" (50 x 40mm) Leaves frame 1½" x 1" (40 x 25 mm) box section frame for glazing 3/8" x 3/8" (10 x 10 mm) using 16 SWG sheet 'U' shaped rubber supported with 1" x 1/8" (25 x 3 mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section 1/2" x 1/2" (13 x 13 mm) of 16 SWG for fixing 24 SWG wire gauge on outer side by means of 3/4" x 1/8" (20 x 3 mm) M.S. flat and screws including grill of M.S. flat 1/2" x 1/8" (13 x 3 mm) or 1/4" x 1/4" (6 x 6 mm) square bar with independent frame of 1/2" x 1/2" (13 x 13 mm) box section of 16 SWG i/c all C.P fitting and painting 3 coats complete in all respect.	1 Sft	3,276.00	2,180.70	7,143,973.20			
135	Providing and fixing 1½" (40 mm) thick solid flush door shutter sterling or equivalent with commercial ply (5mm thick) on both sides double pressed and deodar wood lapping 1½" x 3/8" (40 mm x 10 mm) around shutter including chromium plated fitting, iron hinges with aluminum kick plate 22 SWG on both sides and finger plate complete in all respect.	1 Sft	3,822.00	638.85	2,441,684.70			
136	Providing and laying single layer of tile 9" x 4½" x 1½" laid over 4" earth and 1" thick mud plaster without bhoosa, grouted with cement mud (1:3) on top of R.C.C. roof, slab, provided with 34 lbs. per % Sft. Or 1.72 Kg./Sq.m. bitumen coating sand blinded.	100 Sft	33,854.84	13,179.60	4,461,932.99			
137	1½"(40 mm) thick mosaic flooring, consisting of ½ " mosaic topping of one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over 1"(25 mm) thick floor of 1:2:4 cement concrete, including rubbing and polishing complete with finishing :-using grey cement	100 Sft	22,325.37	29,658.50	6,621,370.23			
138	Mosaic dado or skirting with one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over ½"(13 mm) thick cement plaster 1:3, including rubbing and polishing, complete with finishing:(a) using grey cement: i) 1/2"(13 mm) thick	100 Sft	14,054.04	19,146.85	2,690,905.96			
139	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels (a) Size 1½" x 3/8" (40 x 10 mm)	1 Rft	22,750.00	39.60	900,900.00			
140	Cement concrete plain including, placing, compacting, finishing and curing complete (including screening and washing of stones aggregate)	-	-	-	-			
141	Cement plaster 3/8" (10 mm thick under soffit of R.C.C. roof slabs only, upto 20' height (Ratio 1:3).	100 Sft	21,116.55	5,264.65	1,111,712.45			
142	Providing and fixing sliding; bolt to doors iron sliding bolt, 10" (250 mm) long.	1 No	182.00	656.85	119,546.70			
143	Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern) combined with foot rest white.	1 Each	91.00	4,105.05	373,559.55			

MITIGATION OF WATER LOGGING IN DISTRICT RAHIMYARKHAN

BOQ

Sr. No	Item	Unit	Total QTY	Rate	Amount (PKR)	Rate		Amount Rupees (PKR)
						Rs. In Figures	Rs. In Words	
144	Providing and fitting "P" trap 10 cm (4") glazed.	1 Each	273.00	463.15	126,439.95			
145	Providing and Fixing chromium plated bib cock (ii) 1.5 cm (1/2").	1 Each	364.00	1,639.20	596,668.80			
146	Providing & fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete (i) white.	1 Each	91.00	8,069.20	734,297.20			
147	Providing and installing P.V.C. tees, of B.S.S.Class 'B' working pressure:-b) 4" i/d (100 mm)	1 No	364.00	2,374.25	864,227.00			
148	Providing,laying,testing and commissioning of POLYPROPYLENE RANDOM COPOLYMER (PPRC water supply pipe (Dadex/ Popular/ Beta or approved equivalent manufacturer, with specified pressure rating PN (PRESSURE NOMINAL) and conforming to DIN8077-8078 code/cost of solvent, specials, making jharries complete in all respect as approved and directed by Engineer Incharge.(Internal/External Diameters mentioned). a) PN-16 pipe			-				
i	a) 20mm	1 Rft	9,100.00	62.95	572,845.00			
ii	b) 25mm	1 Rft	4,550.00	87.10	396,305.00			
149	Providing and fixing looking glass (mirror) 22" x 16" (55 x 40) cm, and 5 mm thick glass first quality.	1 Each	91.00	1,457.70	132,650.70			
150	Providing and fixing stainless steel sink with drain board, size 120 x 60 cm (48 x 24") including bracket set, waste pipe and waste coupling.	1 Each	91.00	15,209.10	1,384,028.10			
151	Providing and fitting.		-					
	a) Plastic soap dish.	1 Each	91.00	1,380.00	125,580.00			
	b) Plastic towel rail.	1 Each	91.00	1,610.00	146,510.00			
	c) plastic shelf 60x13cm (24" x 5") with bracket and railing.	1 Each	91.00	1,035.00	94,185.00			
152	Providing and fixing chromium plated tee stop cock 15 mm (1/2").	1 Each	91.00	1,999.20	181,927.20			
153	Supply and erection of wall socket with 3 pin 5 amp shoe.	1 Each	256.00	204.70	52,403.20			
154	Supply and erection of 3 pin switch and plug combined recessed type (ii) 10/15 amp.	1 Each	182.00	213.10	38,784.20			
155	P/F wall mounted DB (Distribution Board) made with 16SWG Sheet (Recessed/Surface mounted Type), Powder coated Paint, i/c the cost of Lock, Indication lights,Thimble, Copper Comb, Wiring, Neutral & Earth Bar, Door Earthing, Digital Voltmeter,Digital Ammeter,Volt Selector Switch,Ammeter selector switch,Current Transformers and Controles Complete in all respect as approved and directed by the Engineer Incharge (Breakers will be Paid Separately)(a) 6" deep (i) 20~60A	1 No	91.00	24,422.65	2,222,461.15			
156	Supplying,Installation and commissioning of MCB (Miniature Circuit Breaker) of specified rating made of LEGRAND FRANCE/ GE U.S.A / SCHNEIDER GERMANY /SIEMEN GERMAN/TERASAKI JAPAN/ ABB SWITZERLAND in prelaidd DBs and Panels i/c the cost of screws,necessary wire completb) Double Pole(iii) 6-63 Amp (10 KA)	1 No	91.00	5,616.25	511,078.75			
157	Supplying,Installation and commissioning of MCB (Miniature Circuit Breaker) of specified rating made of LEGRAND FRANCE/ GE U.S.A / SCHNEIDER GERMANY /SIEMEN GERMAN/TERASAKI JAPAN/ ABB SWITZERLAND in prelaidd DBs and Panels i/c the cost of screws,necessary wire complet Single Pole(iii) 6-63 Amp (10 KA)	1 No	364.00	1,453.75	529,165.00			
158	Supply and erection of 3/8" (10mm) dia M.S. bar fan hook, placed at the time of casting of slab.	1 Each	91.00	83.75	7,621.25			
159	Providing and fixing Pakistan Energy Label NEECA approved Copper winded Ceiling Fan i/c the cost of necessary cable and hardware for connection as approved and directed by Engineer Incharge. 56" Sweep	1 Each	91.00	10,815.40	984,201.40			
160	Erecting of ceiling fan along with regulator (all sizes) including carriage local railway station/ store to site of work, electric wire/cable for suspension rod and board connection and cutting, threading on the rod where necessary.	1 Each	91.00	663.65	60,392.15			
161	Provided and installed 1 HP electric water pump with 70 ft bore, and successfully installed a 200-gallon water tank including all accessories and plumbing connections.	1 Each	91.00	99,800.00	9,081,800.00			
162	HT Spun Pole 45'	1 No	25.00	71344	1783600			
163	HT S/STRUCTURE Pole 36'	1 No	700.00	71680	50,176,000.00			
164	Earthing	1 No	840.00	5488	4,609,920.00			
165	Steel -X-ARMS	1 No	1,760.00	8333	14,666,080.00			

MITIGATION OF WATER LOGGING IN DISTRICT RAHIMYARKHAN

BOQ

Sr. No	Item	Unit	Total QTY	Rate	Amount (PKR)	Rate		Amount Rupees (PKR)
						Rs. In Figures	Rs. In Words	
166	11-KV Disc: Insulator	1 No	1,530.00	4250	6,502,500.00			
167	Eye Nut/Anchore Shackle/D.End Clump	1 No	1,200.00	609	730,800.00			
168	11KV Pin Insulator with Pins	1 No	2,415.00	1797	4,339,755.00			
169	D-Shakel + Spool Insulator	1 No	1,000.00	599	599,000.00			
170	DA Bolts	1 No	700.00	358	250,600.00			
171	Nuts & Bolts 14"	1 No	500.00	208	104,000.00			
172	Nuts & Bolts 12"	1 No	500.00	184	92,000.00			
173	Nuts & Bolts 02"	1 No	200.00	49	9,800.00			
174	Stay Rod + stay strips Complete	1 No	150.00	3935	590,250.00			
175	Stay Wire	1 M	1,870.00	399	746,130.00			
176	ACSR Rabbit Conductor	1 No	61,590.00	245	15,089,550.00			
177	Transformer 400-KVA	1 No	2.00	2189000	4,378,000.00			
178	Transformer 100-KVA	1 No	5.00	506760	2,533,800.00			
179	Transformer 50-KVA	1 No	5.00	400567	2,002,835.00			
180	Transformer 25-KVA	1 No	46.00	286340	13,171,640.00			
181	Plate form D/Edge	1 No	60.00	24290	1,457,400.00			
182	Nuts & Bolts	1 No	1,283.00	198	254,034.00			
183	D-Fues Fitting Set	1 No	183.00	18250	3,339,750.00			
184	Steel Crass arm for D fuse Mounting	1 No	50.00	4770	238,500.00			
185	LT Capacitor	1 No	50.00	10900	545,000.00			
186	LT Spun / PCC Pole 31'	1 No	527.00	23650	12,463,550.00			
187	street light pole bracket 30 mm (1¼") G.I. pipe 2 metre long, complete with 2 No. pole clamp. (Ch-24) [Pump station + Tubewell Rooms)	1 No	200.00	3378.5	675,700.00			
188	Supply and erection of pole mounted street light, holders, shade and glass, etc., for fitting 125/250 watts mercury vapour lamp (excluding cost of lamps): ii) Philips design (Ch 24) [Pump station + Tubewell Rooms)	1 No	200.00	6949.8	1,389,960.00			
189	Supply and fitting of mercury vapour lamp, complete with choke set ii) 250 watt lamp (Ch 24) [Pump station + Tubewell Rooms)	1 No	200.00	4113.3	822,660.00			
190	PVC 4/C Cable 19.083 (70mm Armoured	1 No	6,300.00	975	6,142,500.00			
191	AMR METER HT/LT Type (bi-directional)	1 No	50.00	48900	2,445,000.00			
192	ATB A-Type 100/5	1 No	17.00	31300	532,100.00			
193	CTs 100/5 Amp	1 No	108.00	10530	1,137,240.00			
194	(A)Installation Charges of 11 KV Line material Complete in all respect	1 No	-	16263340	16,263,340.00			
195	(B)Installation Charges of Sub Station material Complete in all respect	1 No	-	5598490	5,598,490.00			
196	(c.)Installation Charges of service and Metering material complete in all respect	1 No	-	1034832	1,034,832.00			
197	Earthing Pit & Material Complete in all respect	1 No	-	8,064,000	8,064,000.00			
198	Foundation Charges complete in all respect	1 No	-	42,000,000	42,000,000.00			
199	630 KVA TRANSFORMER	1 Ea	2.00	2375000	4,750,000.00			
200	200 KVA TRANSFORMER	1 Ea	2.00	904422	1,808,844.00			
201	D/STRUCTURE PLATEFORM	1 Ea	7.00	24290	170,030.00			
202	S/STRUCTURE PLATEFORM	1 Ea	6.00	15786	94,716.00			
203	HT PCC POLE	1 Ea	12.00	33000	396,000.00			
204	AMR METER	1 Ea	9.00	35200	316,800.00			
205	Stay Rods	1 Ea	14.00	3591	50,274.00			
206	Earth Rods	1 Ea	58.00	1498	86,884.00			
207	PVC 4/C 19/.052	1 M	420.00	435	182,700.00			
208	Providing and fixing barbed wire fencing, with 4 horizontal and two cross wires, with R.C.C. 1:2:4 posts, 5.5"x6"x9" (1.68mx150mmx225 mm) at 8 ft. (2.45 m) center to center, reinforced with 4 No. 3/8" (10 mm) dia vertical bars and 1/8" (3 mm) dia stirrups 12" (300 mm) center to center, complete in all respects. in cement concrete 1:4:8 base of size 12"x12"x21"	100 Rft	49,390.00	69347.90	34,250,927.81			

MITIGATION OF WATER LOGGING IN DISTRICT RAHIMYARKHAN

BOQ

Sr. No	Item	Unit	Total QTY	Rate	Amount (PKR)	Rate		Amount Rupees (PKR)
						Rs. In Figures	Rs. In Words	
209	Excavation in foundation of building, bridges, and other structures, including dag belling, dressing refilling around structure with excavated earth, watering and ramming lead upto one chain (30m)and lift upto 5' (1.5 m) (b) in ordinary soil.	1000 Cft	2,062.98	15824.15	32,644.94			
210	Providing and fixing collapsible gate made of 2"x2"x1/4" (50x50x6 mm) tee iron at top and bottom, channel iron verticals 3/4"x1/4"x1/8" (20x6x3 mm) at 3" (75 mm) to 5" (125 mm) centre to centre (approximate) and flat iron crosses 3"x3/16" (75x5 mm), and best quality rollers at bottom of 3" (75 mm) diameter including holdfasts, handles 12" (300 mm) long of 3/4"x1/4"x1/8" (20x6x3 mm) channel iron, locking arrangement inside and outside, painting 3 coats of black Japan enameled, complete in working order.	1 Sft	6,650.00	1985.95	13,206,567.50			
211	Supply and erection PVC pipe for recessed wiring (main and sub-main) purpose, including bends, specials, etc. in floor,wall or trenches:- 50mm i/d	1 Rft	14,250.00	234.95	3,348,037.50			
212	Supply and erection of single core PVC insulated copper conductor cables, in prelaidd PVC pipe/M.S. conduit/G.I pipe/wooden strip batten/wooden casing an capping/G.I. wire/trenches (rate for cables only):7/0.74 mm (7/0.029")	1 Rft	28,500.00	56.30	1,604,550.00			
213	Providing installation, testing, and commissioning of a vertical deep well turbine tubewell pump with discharge 2 cusec against 70 ft head , including bowl assembly, vertical column pipe with shaft, motor, pre-lubrication tank, foundation fixing and alignment, MCCB/control panel with all electrical connections, cables and accessories from transformer to tubewell including earthing and protection devices, complete suction and delivery piping up to 25 ft outlet basin of approved material (MS/CI) with bends, flanges, valves, gaskets, supports and accessories, carrying out all works for energizing, testing, and full-load commissioning; pump casing in Gray Cast Iron EN-GJL-250, impeller in Stainless Steel grade 1.4408, column pipe coated internally and externally with epoxy paint, materials verified per EN 10204-3.1, minimum 80% efficiency per ISO 9906-1B; motor of reputed manufacturer, vertical solid shaft, IE3 efficiency class, 15 kW (20 HP, 1450 rpm), 4-pole, 3-phase, 50 Hz, 380/400 V, manufacturer to have in-house hydraulic and metallurgical testing facility, complete in all respects suitable for tubewell application. [including transportation and all overhead charges]	1 No	37.00	4,350,150	160,955,550.00			
214	Providing installation, testing and commissioning of horizontal centrifugal pump having discharge capacity of 10 cusec against 30 ft - 35 ft head including pump, motor, bowl assembly, column set, pre-lubrication tank, foundation fixing and alignment, MCCB/control panel with all electrical cables and connections from transformer to pump including earthing and protection devices, complete suction piping inside the chamber (SS/MS/CI) and delivery piping up to the outlet basin (40–50 ft) of approved material (Fibre reinforced cement/upvc of suitable internal diameter size as approved by E-in-C) with all bends, flanges, gaskets, supports and accessories, and carrying out all works necessary for energizing, testing and full-load commissioning of the complete pump set in all respects.. Pump shall have min. 81% efficiency which should be verified according to ISO 9906-1B standard. Material of pump casing shall be Gray cast iron EN-GJL-250 having impeller in Stainless Steel grade 1.4408. Pump shall be coated internally with epoxy paint. Material of pump shall be verified according to material test certificate EN 10204-3.1. Motor shall be of reputed manufacturer having min. IE3 efficiency class. Rating of motor to be 37 KW (50HP, 950 rpm)/6 pole, 3 phase, 50 Hz, 380/400 Volts. Manufacturer shall have its own testing facility to verify pumps hydraulic performance testing. Manufacturer shall have its own material testing lab to verify metallurgical testing. [including transportation and all overhead charges]	1 No	8.00	3886124	31,088,992.00			

MITIGATION OF WATER LOGGING IN DISTRICT RAHIMYARKHAN

BOQ

Sr. No	Item	Unit	Total QTY	Rate	Amount (PKR)	Rate		Amount Rupees (PKR)
						Rs. In Figures	Rs. In Words	
215	Providing installation, testing and commissioning of horizontal centrifugal pump having discharge capacity of 10 cusec against 40 ft - 45 ft head including pump, motor, bowl assembly, column set, pre-lubrication tank, foundation fixing and alignment, MCCB/control panel with all electrical cables, accessories and connections from transformer to pump including earthing and protection devices, complete suction piping inside the chamber (SS/MS/CI) and delivery piping up to the outlet basin (40–50 ft) of approved material (Fibre reinforced cement/upvc of suitable internal diameter size as approved by E-in-C) with all bends, flanges, valves, gaskets, supports and accessories, and carrying out all works necessary for energizing, testing and full-load commissioning of the complete pump set in all respects.. Pump shall have min. 82% efficiency which should be verified according to ISO 9906-1B standard. Material of pump casing shall be Gray cast iron EN-GJL-250 having impeller in Stainless Steel grade 1.4408. Pump shall be coated internally with epoxy paint. Material of pump shall be verified according to material test certificate EN 10204-3.1. Motor shall be of reputed manufacturer having min. IE3 efficiency class. Rating of motor to be 45 KW (60HP, 950 rpm)/6 pole, 3 phase, 50 Hz, 380/400 Volts. Manufacturer shall have its own testing facility to verify pumps hydraulic performance testing. Manufacturer shall have its own material testing lab to verify metallurgical testing. [including transportation and all overhead charges]	1 Job	6.00	4,140,119.00	24,840,714.00			
216	Providing installation, testing and commissioning of horizontal centrifugal pump having discharge capacity of 20 cusec against 30 ft - 35 ft head including pump, motor, bowl assembly, column set, pre-lubrication tank, foundation fixing and alignment, MCCB/control panel with all electrical cables, accessories and connections from transformer to pump including earthing and protection devices, complete suction piping inside the chamber (SS/MS/CI) and delivery piping up to the outlet basin (40 -- 50 ft) of approved material (Fibre reinforced cement/upvc of suitable internal diameter size as approved by E-in-C) with all bends, flanges, valves, gaskets, supports and accessories, and carrying out all works necessary for energizing, testing and full-load commissioning of the complete pump set in all respects.. Pump shall have min. 83% efficiency which should be verified according to ISO 9906-1B standard. Material of pump casing shall be Gray cast iron EN-GJL-250 having impeller in Stainless Steel grade 1.4408. Pump shall be coated internally with epoxy paint. Material of pump shall be verified according to material test certificate EN 10204-3.1. Motor shall be of reputed manufacturer having min. IE3 efficiency class. Rating of motor to be 75 KW (100HP, 950 rpm) /8 pole, 3 phase, 50 Hz, 380/400 Volts. Manufacturer shall have its own testing facility to verify pumps hydraulic performance testing. Manufacturer shall have its own material testing lab to verify metallurgical testing. [including transportation and all overhead charges]	1 No	1.00	8,178,639.0	8,178,639.00			

MITIGATION OF WATER LOGGING IN DISTRICT RAHIMYARKHAN

BOQ

Sr. No	Item	Unit	Total QTY	Rate	Amount (PKR)	Rate		Amount Rupees (PKR)
						Rs. In Figures	Rs. In Words	
217	Providing installation, testing and commissioning of vertical tubular casing pump with ever cleaning blades having discharge capacity of 40 cusec against 16-25 ft head including pump, motor, bowl assembly, column set, pre-lubrication tank, foundation fixing and alignment, MCCB/control panel with all electrical cables, accessories and connections from transformer to pump including earthing and protection devices, complete suction piping inside the chamber (SS/MS/CI) and delivery piping up to the outlet basin (40-50 ft) of approved material (Fibre reinforced cement/upvc of suitable internal diameter size as approved by E-in-C) with all bends, flanges, valves, gaskets, supports and accessories, and carrying out all works necessary for energizing, testing and full-load commissioning of the complete pump set in all respects. . Pump shall have min. 84% efficiency which should be verified according to ISO 9906-1B standard. Material of pump casing shall be Gray cast iron JL-1040 having propeller (ever cleaning blades) in Stainless Steel grade 1.4408. Pump and column pipe shall be coated internally and externally with epoxy paint. Material of pump shall be verified according to material test certificate EN 10204-3.1. Motor shall be of reputed manufacturer having min. IE3 efficiency class. Vertical solid shaft. Rating of motor to be 110 KW (150HP, 450 rpm)/8 pole, 3 phase, 50 Hz, 380/400 Volts. . Manufacturer shall have its own testing facility to verify pumps hydraulic performance testing. Manufacturer shall have its own material testing lab to verify metallurgical testing. [including transportation and all overhead charges]	1 No	8.00	13,004,544.0	104,036,352.00			
218	Providing, installation, testing and comissioning of 5 Ton and more capacity Gantry Craine, with girder bridge type arrangement, fitted with electric motor for its operation and mobility, electric wiring and fixing in position, complete in all respect.	1 No	4.00	1,472,223.0	5,888,892.00			
219	Providing, installation, testing and comissioning of 10 Ton and more capacity Gantry Craine, with girder bridge type arrangement, fitted with electric motor for its operation and mobility, electric wiring and fixing in position, complete in all respect.	1 No	1.00	1,315,342.0	1,315,342.00			
220	Direct Rotary / Reverse Rotary drilling of bore for tubewell in all type of soil except shingle gravel and rock. i). 15 " To 18" (500 to 650 mm)	1 Rft	8,140.00	864.05	7,033,367.00			
221	Collection of lithological samples with sieve analysis at every 5 ft. interval or change of lithology whichever is earlier.	1 No	1,628.00	80	130,240.00			
222	Furnishing sample of water from bore hole.	Per Set of 2 bottles	37.00	232.8	8,613.60			
223	Providing, installations testing and commissioning of 16" dia fiberglass blind pump housing casing with 6mm wall thickness having quick lock mechanical key joints complete in all respect as per specification and approved by the Engineer.	1 Rft	2,590.00	5371	13,910,890.00			
224	Providing and installation of Fibre Glass reducer 16"x10" with wall thickness 5.5 mm. complete in all respect as per specification and approved by the Engineer.	1 No	74.00	35582	2,633,068.00			
225	Providing and installing Fiberglass Reinforced Polypropelene (FRP) strainer of specifid wall thickness having slot size of 0.9 mm to 1.10 mm in Tubewell borehole i/c the cost of male/female coupling with Nylone Strip, studs complete in all respect as approved and directed by the Engineer Incharge vi) 10" inch dia (6.35 mm thickness	1 Rft	4,440.00	3866.45	17,167,038.00			
226	Proving and installation of fiberglass Blank blind casing pipe dia 10" with 5.5" wall thickness. complete in all respect as per specification and approved by the Engineer.	1 Rft	740.00	3583	2,651,420.00			
227	Providing and installing Fiber glass Reinforced Polypropelene (FRP) bail plug of specified wall thickness having slot size of 0.9 mm to 1.10 mm in Tubewell bore hole i/c the cost of male / female coupling with Nylone Strip, studs complete in all respect as approved and directed by the Engineer Incharge.vi) 10"dia (6.35mm thickness)	1 Rft	370.00	3735.5	1,382,135.00			
228	Providing and installation of centralizer complete in all respect as per specification and approved by the Engineer.	1 No	148.00	1148	169,904.00			
229	Shrouding with graded pea gravel 3/8" to 1/8" arround tubewell casing in the bore hole.	1 Cft	6,520.88	186.65	1,217,122.25			

MITIGATION OF WATER LOGGING IN DISTRICT RAHIMYARKHAN

BOQ

Sr. No	Item	Unit	Total QTY	Rate	Amount (PKR)	Rate		Amount Rupees (PKR)
						Rs. In Figures	Rs. In Words	
230	Testing and Development of tubewell of size 6"(150 mm) and above continusly. ii) Above 1.5 cs Discharge	1 hour	2,664.00	3253.1	8,666,258.40			
231	Supply and erection of copper conductor cables for service connection (rate for cable only), PVC insulated, PVC sheathed 4 core , 600/1100 volt non armoured cable. (7/0.064")	1 Rft	1,850.00	924.05	1,709,492.50			
232	Excavation of trenches in all kinds of soil except cutting rock, for watersupply pipelines upto 5 ft. (1.5 m) depth from ground level, including trimming, dressing sides leveling the beds of trenches to correct grade and cutting pits for joints, etc. complete in all respects.	1000 Cft	118,400.00	11293.9	1,337,197.76			
233	Providing,laying,testing and commissioning µPVC (Unplasticized Poly vinyl Chloride Pressure pipe of nominal diameter, conforming to PS-3051/BS-3505, Dadex/ Popular/ Beta or approved equivalent manufacturer,i/c the cost of solvent and specials complete as approved and directed by the Engineer Incharge. a)Class-D 12 inch	1 Rft	14,800.00	3565	52,762,000.00			
234	Providing,laying,testing and commissioning µPVC (Unplasticized Poly vinyl Chloride Pressure pipe of nominal diameter, conforming to PS-3051/BS-3505, Dadex/ Popular/ Beta or approved equivalent manufacturer,i/c the cost of solvent and specials complete as approved and directed by the Engineer Incharge. a)Class-D 3 inch	1 Rft	555.00	500.3	277,666.50			
235	Providing installation, testing, and commissioning of a 22.5kW Solar PV system capable of running a horizontal centrifugal pump with discharge 2 cusec against 70 ft head, pump minimum 81% efficiency, including Tier-1 Bloomberg-certified mono / bi-facial N-type solar panels (JINKO / LONGI / JA / Canadian / AKCome / TW / Trina, 700+W/panel, 23.5% efficiency), solar pump inverter INVT suitably rated for system capacity, mounted on 12 ft high L2/L3/L4 galvanized steel structure (14 gauge) with complete mechanical and civil works, DC and AC cabling with XLPE/PVC insulated tin-coated copper wires, combiner boxes, AC & DC breakers, SPDs (A+ grade), all distribution/protection boxes (12"x18"x18" SWG or equivalent), PVC pipes, flexible pipes (1–1.5"), thimbles (O-type, U-type with shrouds), Rawl bolts, nuts and bolts, complete earthing system, lightning arrestor, all civil works, foundations, and supports, all electrical connections for net metering with meter, transportation of all materials from warehouse to site, testing, commissioning, and manufacturer-provided maintenance/after-sales service for up to 2 years, complete in all respects as directed by the Engineer-in-Charge.	1 No	87.00	1950150	169,663,050.00			
236	GNSS (Topographical) Surveying instrument with Base, Rover, Controller complete in all respect	1 No	1.00	1,829,000.00	1,829,000.00			
237	Providing and supplying a complete aerial topographic survey package consisting of a professional RTK-enabled survey drone, high-resolution photogrammetry camera, licensed processing software, additional 8 batteries with charging hub, Ground Control Point (GCP) sets/markers, High graded RTK base station kit with tripod and pole, and 5 TB rugged NVMe SSD storage, complete in all respects (Equivalent: DJI Matrice 350 RTK Drone, Zenmuse P1c etc)	1 No	1.00	4,250,000.00	4,250,000.00			
238	Providing and supplying a Total Station with angle accuracy ≤5", EDM reflectorless range ≥500 m, prism range ≥1500 m, distance accuracy ±(2 mm + 2 ppm), 30× telescope, dual-axis compensator, rechargeable batteries with charger, prism set with pole, tripod, data storage/USB/Bluetooth interface, carrying case, calibration certificate, and all accessories complete.	1 No	1.00	1475000	1,475,000.00			
239	Providing and supplying an automatic self-leveling Auto-Level with minimum 32× magnification, ±2 mm/km accuracy, dual-axis compensator, tripod, 2.5 m leveling staff, carrying case, calibration certificate, and all accessories complete.	1 No	4.00	129800	519,200.00			

MITIGATION OF WATER LOGGING IN DISTRICT RAHIMYARKHAN

BOQ

Sr. No	Item	Unit	Total QTY	Rate	Amount (PKR)	Rate		Amount Rupees (PKR)
						Rs. In Figures	Rs. In Words	
240	Providing and supplying a high-performance workstation laptop with Intel Core i9-14900HX / AMD Ryzen 9 7940HX or higher, 64GB DDR5 RAM, 2TB NVMe Gen-5 M.2 SSD, dedicated NVIDIA RTX 4080 (12GB) or higher GPU, Windows 11 Pro, full-size keyboard with numeric pad, complete with premium laptop bag, wireless headphones (Sennheiser/Beats/Sony/Anker or equivalent), USB 3.2 Gen-2 (10Gbps) flash drive, and Logitech MX Master 3S wireless mouse or equivalent, complete in all respects.	1 No	2.00	850000	1,700,000.00			
241	Providing installation, testing, and commissioning of a 64 kW Solar PV system capable of operating a horizontal centrifugal pump with discharge 10 cusec against 40 - 45 ft head , pump minimum 82% efficiency verified as per ISO 9906-1B standard, including Tier-1 Bloomberg-certified mono/ bi-facial N-type solar panels (JINKO / LONGI / JA / Canadian / AKCome / TW / Trina, 700+ W/panel, 23.5% efficiency), solar pump inverter INVT suitably rated for system capacity, mounted on 12 ft high L2/L3/L4 galvanized steel structure (14 gauge) with complete mechanical and civil works, DC and AC cabling using XLPE/PVC insulated tin-coated copper wires, combiner boxes, AC & DC breakers, SPDs (A+ grade), all distribution/protection boxes (12"x18"x18" SWG or equivalent), PVC pipes, flexible pipes (1-1.5"), thimbles (O-type, U-type with shrouds), Rawl bolts, nuts and bolts, complete earthing system, lightning arrestor, all civil works, foundations, and supports, electrical connections for net metering with meter, transportation of all materials from warehouse to site, testing, commissioning, and manufacturer-provided maintenance/after-sales service for 2 years, complete in all respects as directed by the Engineer-in-Charge.	1 No	6.00	5,061,388	30,368,325.00			
242	Providing installation, testing, and commissioning of a 53.5 kW Solar PV system capable of running a horizontal centrifugal pump with discharge 10 cusec against 30-35 ft head, pump minimum 81% efficiency, including Tier-1 Bloomberg-certified mono / bi-facial N-type solar panels (JINKO / LONGI / JA / Canadian / AKCome / TW / Trina, 700+ W/panel, 23.5% efficiency), solar pump inverter INVT suitably rated for system capacity, mounted on 12 ft high L2/L3/L4 galvanized steel structure (14 gauge) with complete mechanical and civil works, DC and AC cabling with XLPE/PVC insulated tin-coated copper wires (DC 1-core 6 mm, AC 4-core 6 mm, 25 mm PVC/XLPE), combiner boxes, AC & DC breakers, SPDs (A+ grade), all distribution/protection boxes (12"x18"x18" SWG or equivalent), PVC pipes, flexible pipes (1-1.5"), thimbles (O-type, U-type with shrouds), Rawl bolts, nuts and bolts, complete earthing system, lightning arrestor, all civil works, foundations, supports, electrical connections for net metering with meter, transportation of all materials from warehouse to site, testing, commissioning, and manufacturer-provided maintenance/after-sales service for 2 years, complete in all respects as directed by the Engineer-in-Charge.	1 No	7.00	4,116,450	28,815,150.00			
243	Providing installation, testing, and commissioning of a 107 kW Solar PV system for a horizontal centrifugal pump with discharge 20 cusec against 30 - 35 ft head, pump minimum 83% efficiency, including Tier-1 Bloomberg-certified mono/ bi-facial N-type solar panels (JINKO / LONGI / JA / Canadian / AKCome / TW / Trina, 700+ W/panel, 23.5% efficiency), solar pump inverter INVT suitably rated for system capacity, mounted on 12 ft high L2/L3/L4 galvanized steel structure (14 gauge) with complete mechanical and civil works, DC and AC cabling with XLPE/PVC insulated tin-coated copper wires (DC 1-core 6 mm, AC 4-core 6 mm, 25 mm PVC/XLPE), combiner boxes, AC & DC breakers, SPDs (A+ grade), all distribution/protection boxes (12"x18"x18" SWG or equivalent), PVC pipes, flexible pipes (1-1.5"), thimbles (O-type, U-type with shrouds), Rawl bolts, nuts and bolts, complete earthing system, lightning arrestor, all civil works, foundations, and supports, all electrical connections for net metering with meter, transportation of all materials from warehouse to site, testing, commissioning, and manufacturer-provided maintenance/after-sales service for up to 2 years, complete in all respects as directed by the Engineer-in-Charge.	1 No	1.00	8,787,425	8,787,425.00			
244	Surface water Monitoring for Construction Phase	Lump Sump	-		1,300,000.00			
245	Groundwater Monitoring for Construction Phase	Lump Sump	-		700,000.00			
246	Ambient Air Quality Monitoring for Construction Phase	Lump Sump	-		500,000.00			
247	Surface water MonitoringFor Operational Phase	Lump Sump	-		500,000.00			

MITIGATION OF WATER LOGGING IN DISTRICT RAHIMYARKHAN

BOQ

Sr. No	Item	Unit	Total QTY	Rate	Amount (PKR)	Rate		Amount Rupees (PKR)
						Rs. In Figures	Rs. In Words	
248	Groundwater Monitoring For Operational Phase	Lump Sump	-		500,000.00			
249	Drinking Water Monitoring for Drinking Water & Groundwater Monitoring near disposal Pit	Lump Sump	-		250,000.00			
250	Groundwater Monitoring for Drinking Water & Groundwater Monitoring near disposal Pit	Lump Sump	-		250,000.00			
251	Training Session	Lump Sump	5.00	100,000.00	500,000.00			
252	Emergency Plan	Lump Sump	1.00		1,500,000.00			
253	Environmental Audit Cost	Lump Sump	3.00	500,000.00	1,500,000.00			
254	Site Visits by Regulatory Authorities	Lump Sump	1.00		500,000.00			
255	Sign Board for traffic management cost	Lump Sump	1.00		125,000.00			
256	Barricading Fence along Access Roads for traffic management cost	Lump Sump	1.00		100,000.00			
257	Temporary Speed Breakers for traffic management cost	Lump Sump	1.00		100,000.00			
258	Controlling Dust Pollution for traffic management cost	Lump Sump	1.00		175,000.00			
259	Relocation of amenities and localized widening of road and barrier for traffic management cost	Lump Sump	1.00		500,000.00			
Total Cost (PKR)								

MI

BOQ

Sr. No	Item	Unit	2-L Manthar Drain	3-L Manthar Drain
1	Earthwork			
1	Earth Work in excavation of drains, irrigation channels through excavator/ drag lines in all kind of soil and conditions (dry, wet slush, daladal and under water) including its disposal and preperation of working pad for operation of machinary. (rates includes 100ft lead)	1000 Cft	616,487.50	590,424.88
4	Earth work in excavation of drains in irrigation channels through excavator / draglines in all kind of soil and conditions	1000 Cft		
2	Earth work in excavation of drains in irrigation channels through excavator / draglines in all kind of soil and conditions	1000 Cft	476.44	355.50
2	Dressing and levelling of earthwork to designed section etc complete in ii) ordinary or hard soil soil	1000 Cft	174,315.00	112,011.01
3	Transportation of earth all types when the total distance, including the lead covered in the item of work , is more than 1000 ft.			
	a) 500 ft	1000 Cft	20,640.00	4,055.67
	b) 750 ft	1000 Cft		4,805.00
	b) 1000 ft	1000 Cft	2,970.00	
	c) 1250 ft	1000 Cft	8,792.50	20,505.00
	d) 1500 ft	1000 Cft	1,215.00	
	b) 1750 ft	1000 Cft		
	e) 2000 ft	1000 Cft	18,740.00	
	f) 2500 ft	1000 Cft		
	c) 2750 ft	1000 Cft		
	d) 3000 ft	1000 Cft		1,237.50
	g) 3750 ft	1000 Cft		
	f) 4250 ft	1000 Cft	54,772.50	
	e) 4500 ft	1000 Cft		15,772.50
	d) 5500 ft	1000 Cft		
	f) 6750 ft	1000 Cft		4,869.33
4	Borrowpit excavation undressed lead upto 100 ft (30 metre) in a) ordinary	1000 Cft		
	250 ft	1000 Cft		
	a) 500 ft	1000 Cft		
	a) 1000 ft	1000 Cft		
	a) 1 mile	1000 Cft		
5	Rehandling of earthwork lead upto 50ft (35% of excess cutting)	1000 Cft		
21	Rehandling of earthwork:Upto a lead of 50 ft. (15 m).	1000 Cft	6,480.00	
10	Rehandling of earthwork:Upto a lead of 50 ft. (15 m).	1000 Cft	4,000.00	
7	Rehandling of earthwork:Upto a lead of 50 ft. (15 m).	1000 Cft		
21	Rehandling of earthwork lead upto a lead of 50 ft.	1000 Cft	118400	
6	Providing and erection at site of work:- iii) R.C.C. boundary pillar. (Complete in all respect including transportation, Cement concrete foundation, fixing, painting and lettering etc)	1 No		
7	Making boundary or service roads, including dag-belling, leveling and dressing:ii) in ploughed land: a) from 10.0 ft. to 20.0 ft. (3 to 6 m) wide	1 -Chain	410.00	255.00
8	Jungle clearance and removing within 100 ft. light	1000 Sft	315,680.00	180,070.00
9	Providing and fixing Enamelled steel plate gauge 4" wide 1/4" thick (including painting and lettering) 10 ft length	1 No		
2	Data Board			
1	Excavation in foundation of building bridges and other structures including dagbelling, dressing, refilling around structure with excavated earth, watering and ramming lead upto one chain and lift upto 5 ft. in ordinary soil	1000 Cft	98.00	98.00
2	Cement concrete plain including, placing, compacting, finishing and curing complete (including screening and washing of stones aggregate)	100 Cft		
	a) Nominal mix ratio 1:4:8	100 Cft	24.50	24.50
	a) Nominal mix ratio 1:4:8	100 Cft	361.00	
a)	Nominal mix ratio 1:4:8	100 Cft	257.20	
a)	Nominal mix ratio 1:4:8	100 Cft	422.45	211.22
	a) Nominal mix ratio 1:4:8	100 Cft		
	a) Nominal mix ratio 1:4:8	100 Cft		
	a) Nominal mix ratio 1:4:8	100 Cft	11,548.92	
69	a) Nominal mix ratio 1:4:8	100 Cft	515.7	
	b) Nominal mix ratio 1:2:4	100 Cft	157.90	136.80

	b) Nominal mix ratio 1:2:4	100 Cft	183.44	91.72
	b) Nominal mix ratio 1:2:4	100 Cft		
	b) Nominal mix ratio 1:2:4	100 Cft		
	b) Nominal mix ratio 1:2:4	100 Cft	1,780.19	
3	Pacca brick work in foundation and plinth in cement sand mortar ratio 1:6.	100 Cft	97.50	97.50
4	Pacca brick work in foundation and plinth in cement sand mortar ratio 1:6.	100 Cft	1,260.16	630.08
4	Pacca brick work in foundation and plinth in cement sand mortar ratio 1:6.	100 Cft	44,360.68	
70	Pacca brick work in foundation and plinth in cement sand mortar ratio 1:6.	100 Cft	745.6	
4	Providing and laying damp proof course of cement 1:2:4 (using cement, sand and shingle), including bitumen coating with with 2 coats of bitumen: 1½" thick (40 mm).	100 Sft	39.00	39.00
5	Providing and laying damp proof course of cement 1:2:4 (using cement, sand and shingle), including bitumen coating with one coat of bitumen and one coat polythenesheet 500 gauge 1½" thick (40 mm).	100 Sft	258.00	129.00
5	Providing and laying damp proof course of cement 1:2:4 (using cement, sand and shingle), including bitumen coating with one coat of bitumen and one coat polythenesheet 500 gauge 1½" thick (40 mm).	100 Sft	8,834.11	
71	Providing and laying damp proof course of cement 1:2:4 (using cement, sand and shingle), including bitumen coating with 2 coats of bitumen: 1½" thick (40 mm).	100 Sft	427.5	
5	Pacca brick work other than building upto 10 ft. height in cement sand mortar ratio 1:3	100 Cft	81.70	81.70
6	Cement plaster 1:4 upto 20 ft. height, 3/8" thick	100 Sft	230.65	230.65
7	Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect:	100 Sft	230.65	230.65
26	Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect:	100 Sft	690.22	345.11
15	Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect:	100 Sft		
25	Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect:	100 Sft	31,339.95	
8	Writing letter or figures per letter per inch height	1 No	500.00	500.00
9	Carriage of 100 Cf t. (2.83 cu.m) of all materials like stone aggregate, spawl, kankar lime (unslaked), surkhi , etc. or 150 Cf t. (4.25 cu.m) timber, by truck or by any othermeans owned by the contractor from Sakhi Sarwar Quarry to site 275 Km including first 11KM hilly area.			
	DPC	100 Cft	4.29	4.29
3	RD Marks			
1	Precast reinfoced cement concrete type "C" 1:2:4.	1 Cft	55.04	30.96
2	Fabrication of mild steel reinforcement for cement concrete including cutting bending laying in position etc. complete in all respect. (deformed bars) Grade 40	100 Kg	125.76	70.74
3	Carriage of consignment job upto 5 KMs Average	1 No	32.00	18.00
4	Placing boundary pillars in position, including digging pits.	1 Each	32.00	18.00
5	Preparing surface and painting with emulation paint 3 coat.	100 Sft	112.00	63.00
6	Writing letter or firgures per letter per inch height (three figure each side).	1 No	320.00	180.00
7	Carriage of 100 Cf t. (2.83 cu.m) of all materials like stone aggregate, spawl, kankar lime (unslaked), surkhi , etc. or 150 Cf t. (4.25 cu.m) timber, by truck or by any othermeans owned by the contractor from Sakhi Sarwar Quarry to site 275 Km including first 11KM hilly area.			
ii	PCC 1:2:4	100 Cft	48.44	27.24
4	Road Barier.			
1	Earthwork excavation undressed lead upto a single throw of Kassi, phaorah or shovel: In ordinary soil.	1000 Cft		
2	Cement concrete plain including placing, compacting, finishing and curing complete (including screening and washing of stone aggregate) Ratio 1: 2: 4	100 Cft		
3	Providing, laying, cutting, jointing, testing and disinfecting G.I. pipeline in trenches, with socket joints, using G.I. pipes of B.S.S. 1387-1967 complete in all respects, with specials and valves. i) 4" i/d (100 mm) 3.65mm thick	1 Rft		

4	Carriage of 100 Cft of all material like stone aggregate, spawl, kankar, lime (unsoaked) surkhi etc by truck or by any other means owned by the contractor, lead 300Km.(From Sakhi Sarwar)	100 Cft		
5	Culverts / Bridges			
1	Dismantling brick work in lime or cement mortar	100 Cft		
2	Dismantling and removing road pavement, etc.,including screening and stacking of byproducts upto one chain lead (30 metre).	100 Cft		
19	Dismantling and removing road pavement, etc.,including screening and stacking of byproducts upto one chain lead (30 metre).	100 Cft	960.00	
3	Dismantling cement concrete reinforced, separating reinforcement from concrete, cleaning and straightening the same.	100 Cft	307	

5	Excavation in foundation of building, bridges and other structures, including dagbelling, dressing, refilling around structure with excavated earth, watering and ramming lead up to one chain and lift upto 5 ft. In ordinary soil (above 5 ft depth)	1000 Cft	6,406.12	
6	Cement concrete plain including, placing, compacting, finishing and curing complete (including screening and washing of stones aggregate)			

7	Providing and fabrication of mild steel reinforcement for cement concrete, including cutting , bending, laying in position, making joints and fastening, including cost of binding wire and labour charges for binding of steel reinforcement(also includes removal of rust from bars). Deformed Bars (Grade 60)	100 Kg	13,993.24	
4	Providing and fabrication of mild steel reinforcement for cement concrete, including cutting , bending, laying in position, making joints and fastening, including cost of binding wire and labour charges for binding of steel reinforcement(also includes removal of rust from bars). Deformed Bars (Grade 60)	100 Kg	6,108.98	
10	Providing and Fabrication of mild steel reinforcement for cement concrete, including cutting, bending, laying in position, 13 making joints and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars):- Deformed bars (Grade-60).	100 Kg	4,141.77	2,070.88
4	Providing and fabrication of mild steel reinforcement for cement concrete, including cutting , bending, laying in position, making joints and fastening, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars).Deformed Bars (Grade 60)	100 Kg		
5	Providing and Fabrication of mild steel reinforcement for cement concrete, including cutting, bending, laying in position, making joints and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars):- Deformed bars (Grade-60).	100 Kg		
10	Providing and Fabrication of mild steel reinforcement for cement concrete, including cutting, bending, laying in position, 13 making joints and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars):- Deformed bars (Grade-60).	100 Kg	65,173.29	
8	Providing and laying reinforced cement concrete (including prestressed concrete), using Sulphate resisting cement ; coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete 2) Plastering done under soffit of R.C.C. (but excluding the cost of steel reinforcement, its fabrication and placing in position etc.)			
a)	Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects. Type B (nominal mix 1:1.5:3)	1 Cft	3,056.12	

	a) Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects. Type B (nominal mix 1:1.5:3)	1 Cft		
	a) Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects. Type B (nominal mix 1:1.5:3)	1 Cft		
	a) Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects. Type B (nominal mix 1:1.5:3)	1 Cft	1,266.91	
	b) Reinforcement cement concrete in slab of rafts/strip foundation, base slab of column and retaining walls, etc and other structural members not requiring form work(i.e horizontal shuttering) complete in all respect: Type B (Nominal Mix 1:1.5:3)	1 Cft	1,444.00	
	b) Reinforcement cement concrete in slab of rafts/strip foundation, base slab of column and retaining walls, etc and other structural members not requiring form work(i.e horizontal shuttering) complete in all respect: Type B (Nominal Mix 1:1.5:3)	1 Cft	769.42	
	b) Reinforcement cement concrete in slab of rafts/strip foundation, base slab of column and retaining walls, etc and other structural members not requiring form work(i.e horizontal shuttering) complete in all respect: Type B (Nominal Mix 1:1.5:3)	1 Cft		
	b) Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects. Type B (nominal mix 1:1.5:3)	1 Cft		
9	Providing and embedding 10"(250mm) wide PVC water stopper in expansion joints of RCC structures (Retaining walls, water tanks, Slabs) complete in all respect. 10mm thick	1 Rft	190.00	
10	Bitumen coating to plastered or cement concrete surface. 14 lbs per 100 Sft (6.35 Kg. per Sq.m)	100 Sft	2,739.76	
11	Providing, laying, cutting, jointing, testing and disinfecting PVC/ uPVC pipe line with 'B' Class working pressure complete in all respects:- 4" i/d (100 mm)	1 Rft		
12	Providing and fixing 4" dia P.V.C pipe.	1 Rft	12.00	
13	Supply and erection PVC pipe for recessed wiring (main and sub-main) purpose, including bends, specials, etc. in floor, wall or trenches:- 80mm dia (3 inch)	1 Rft	13.50	
14	Providing and laying R.C.C. pipe sewers, moulded with cement concrete 4000 psi conforming to Specification C-76-20, Class II. Wall B, including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing with rubber ring, cutting pipes where necessary, testing, etc., complete. 24 inch internal dia	1 Rft	96.00	
15	Providing and laying sub-base course of stone product of approved quality and grade, including placing, mixing, spreading and compaction of sub-base material to required depth, camber, grade to achieve 100% maximum modified AASHTO dry density, including carriage of all material to site of work except gravel and aggregate. Crushed stone aggregate.	100 Cft	480.00	
16	Providing and laying base course of crushed stone aggregate of approved quality and grade, and supply and spreading of stone screening, including placing, mixing, spreading and compaction of base course material to required depth, camber and grade to achieve 100% maximum modified AASHTO dry density, including carriage of all materials to site of work except gravel and aggregate.	100 Cft	480.00	
17	Providing and laying road edging of 3" (75 mm) wide and 9" (225 mm) deep brick on end, complete in all respects	1 Rft	120.00	

18	Providing surface treatment of roads,including supply of bitumen and bajri/crushed stone aggregate of approved quality,including cleaning of road urface,heating,spraying bitumen,spreading bajri and rollingetc.complete including carriageof all material stosite of work excep tbajri/crushed stone aggregate for which supply with in miles (5.0km) is included in the rate.			
a	1st coat 35 lbs. bitumen, and 4 Cft. bajri of nominal size 1" (25 mm) per 100 sq. feet or 1.72 Kg bitumen and 0.017 cu.metre bajri per square metre..	100 Sft	960.00	
b	2nd coat 18 lbs. bitumen, and 2 Cft. bajri of nominal size ½" (13 mm) per %sft or 1.23 Kg bitumen and 0.008 cu. metre bajri per sq.metre.	100 Sft	960.00	
c	3rd coat 14 lbs. bitumen, and 1.5 Cft. bajri of nominal size ¼" (6 mm) per %sft or 0.69 Kg bitumen and 0.005 cubic metre bajri per sq.metre.	100 Sft	960.00	
20	Borrow pit excavation undressed lead up to 100 ft in ordinary soil.	1000 Cft	10,190.00	

22	Carriage of 100 Cf t. (2.83 cu.m) of all materials like stone aggregate, spawl, kankar lime (unslaked), surkhi , etc. or 150 Cf t. (4.25 cu.m) timber, by truck or by any othermeans owned by the contractor from Sakhi Sarwar Quarry to site 275 Km including first 11KM hilly area.			
i	PCC 1:4:8	100 Cft	346.56	
ii	RCC 1:1.5:3	100 Cft	3,360.20	
iii	Base	100 Cft	585.60	
iii	T.S.T	100 Cft	72.00	
23	Cement plaster 1:3 upto 20' (6.00 m) height 1/2" (13 mm) thick.	100 Sft	694.50	848.00
24	Providing and laying sub base course.	100 Cft		
25	Providing and laying base course.	100 Cft		
26	Providing surface treatment to roads, including supply of bitumen and bujri /crushed stone aggregate of approved quality, including cleaning of road surface, heating and spraying bitumen, spreading bajri and rolling with road roller (including its operation cost, fuel and hire charges, etc.) etc. complete including carriage of all materials to site of work except bajri/crushed stone aggregate.	100 Sft		
27	Providing and fixing Neoprene bearing pad with laminated steel plate top and bottom. Size (14" x 9" x 1.75")	Cu. Inch		
28	Plain wood work for regulation karries or needles, etc. including sawing, planning, wroughting wood and providing and fixing steel parts of karries i.e. end strip and rods, etc. b) Shisham wood	1 Cft		
29	Credit old material - steel	1 Kg	(82.00)	
30	Credit old material - brick batts	100 Cft		
6	Water Course			
1	Excavation in foundation of building, bridges and other structures, including dagbelling, dressing, refilling around structure with excavated earth, watering and ramming lead up to one chain and lift upto 5 ft. In ordinary soil (above 5 ft depth)	1000 Cft	1,867.65	
2	Extra for slush or Daldal including dewatering.	1000 Cft	1,867.65	
3	Cement concrete plain including, placing, compacting, finishing and curing complete (including screening and washing of stones aggregate)			

b)	Nominal mix ratio 1:2:4	100 Cft	34.00	
----	-------------------------	---------	-------	--

5	Providing and laying reinforced cement concrete (including prestressed concrete), using Sulphate resisting cement ; coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete 2) Plastering done under soffit of R.C.C. (but excluding the cost of steel reinforcement, its fabrication and placing in position etc.)			
---	--	--	--	--

6	Bitumen coating to plastered or cement concrete surface. 14 lbs per 100 Sft (6.35 Kg. per Sq.m)	100 Sft	751.28	
7	Pacca brick work other than buildings upto 10 feet height. Cement sand mortar ratio 1:4	100 Cft	80.00	
8	Providing and embedding 10"(250mm) wide PVC water stopper in expansion joints of RCC structures (Retaining walls, water tanks, Slabs) complete in all respect. 10mm thick	1 Lft	189.50	
9	Providing and placing poly sulphide joint sealent 1" wide and 1" deep.	1 Lft	70.00	

11	Carriage of 100 Cf t. (2.83 cu.m) of all materials like stone aggregate, spawl, kankar lime (unslaked), surkhi, etc. or 150 Cf t. (4.25 cu.m) timber, by truck or by any other means owned by the contractor from Sakhi Sarwar Quarry to site 275 Km including first 11KM hilly area.			
i	PCC 1:4:8	100 Cft	246.91	
ii	PCC 1:2:4	100 Cft	29.92	
iii	RCC 1.1.5.3	100 Cft	1,710.52	
7	Stone Pitching			
1	Dismantling stone or spawl pitching and apron in silted condition.	100 Cft		

3	Supply and dumping at site, without boat, including handling of materials within three chains (90 m)	100 Cft		
4	Providing and laying stone pitching/filling, dry hand packed, as filling behind retaining walls or in pitching and aprons.	100 Cft	476.44	355.50
5	Formation dressing and preparing subgrade, on slope	100 Sft	735.37	681.66
6	Formation dressing and preparing subgrade, in bed.	100 Sft	130.50	126.00
7	Providing and laying graded bajri 1/8" to 1/2" size on slope.	100 Cft	242.67	224.94
8	Providing and laying graded bajri 1/2" to 2" size on slope.	100 Cft	242.67	224.94
9	Providing and laying graded bajri 1/8" to 1/2" size on level.	100 Cft	43.07	41.58
10	Providing and laying graded bajri 1/2" to 2" size on level.	100 Cft	43.07	41.58
11	Providing and laying stone for top layer only, on slope.	100 Cft	735.37	681.66
12	Providing and laying stone for top layer only, on Level	100 Cft	130.50	126.00
13	Carriage of 100 Cft of all material like stone aggregate, spawl, kankar, lime (unsoaked) surkhi etc or 150 Cft of timber by truck or by any other means owned by the contractor, lead 275 Km.	100 Cft	1,682.24	1,449.12
14	Credit to old material			
	Steel	1 Kg		
	Brick batts	100 Cft		
8	Tube Well room			
1	Excavation in foundation of building, bridges, and other structures, including dag belling, dressing refilling around structure with excavated earth, watering and ramming lead upto one chain (30m) and lift upto 5' (1.5 m) (b) in ordinary soil. 1) By Manual	1000 Cft	2,179.57	1,089.78
2	Spraying termite proofing by using liquid FMC / Biflex/ Terminex Exin/ Ms Hextar or equivalent @ specified suspension concentrate (SC), Mixing Ability-HEXTAR with Ratio (1:250)= 540 Sft or equivalent approved liquid applying with shower and certificate will be provided by the contractor for 10-years complete in all respect as approved by the Engineer Incharge.	1 Sft	2,034.00	1,017.00
3	Cement concrete plain including, placing, compacting, finishing and curing complete (including screening and washing of stones aggregate)			

6	Providing and laying vertical damp proof course with cement sand plaster and bitumen coating with one coat of bitumen and one coat of polythene sheet 500 gauge-Ratio 1:3 a) ½ " thick (13 mm)	100 Sft	480.00	240.00
7	Filling watering ramming earth under floors with surplus earth from foundation etc.	1000 Cft	600.00	300.00
8	Pacca brick work in ground floor. Cement sand mortar Ratio 1:4.	100 Cft	1,163.60	581.80
9	Providing and laying reinforced cement concrete (including prestressed concrete), using Sulphate resisting cement ; coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete 2) Plastering done under soffit of R.C.C. (but excluding the cost of steel reinforcement, its fabrication and placing in position etc.)			
a)	Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects. Type B (nominal mix 1:2:4)	1 Cft	616.66	308.33
b)	Reinforcement cement concrete in slab of rafts/strip foundation, base slab of column and retaining walls, etc and other structural members not requiring form work (i.e horizontal shuttering) complete in all respect: Type B (Nominal Mix 1:2:4)	1 Cft	73.63	36.82

11	Providing and fixing windows consisting of M.S box section frame 2" x 1½" (50 x 40mm) Leaves frame 1½" x 1" (40 x 25 mm) box section frame for glazing 3/8" x 3/8" (10 x 10 mm) using 16 SWG sheet 'U' shaped rubber supported with 1" x 1/8" (25 x 3 mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section 1/2" x 1/2" (13 x 13 mm) of 16 SWG for fixing 24 SWG wire gauge on outer side by means of 3/4" x 1/8" (20 x 3 mm) M.S. flat and screws including grill of M.S. flat 1/2" x 1/8" (13 x 3 mm) or 1/4" x 1/4" (6 x 6 mm) square bar with independent frame of 1/2" x 1/2" (13 x 13 mm) box section of 16 SWG i/c all C.P fitting and painting 3 coats complete in all respect.	1 Sft	128.00	64.00
12	Providing and fixing mild steel chowkat of doors windows C. windows etc. including holdfast making and threading 18 holes for hinges etc. complete 1½" x 1½" x 1/4" (40 x 40 x 6 mm) welded with M.S. flat 2" x 1/4" (50 m M.S. angle iron).	1 Sft	160.00	80.00
13	Making and fixing steel grated door with 1/16" thick sheeting, including angle iron frame 2" x 2" x 3/8" and 3/4" square bars 4" centre to centre. with locking arrangement (Two No.).	1 Sft	196.00	98.00
14	Providing and laying single layer of tile 9" x 4½" x 1½" laid over 4" earth and 1" thick mud plaster without bhoosa, grouted with cement mud (1:3) on top of R.C.C. roof, slab, provided with 34 lbs. per % Sft. Or 1.72 Kg./Sq.m. bitumen coating sand blinded.	100 Sft	382.25	191.13
15	Providing and laying polythene sheet under floor or roof complete 500 gauge.	1 Sft	398.25	199.13
16	Supplying and filling sand under floor or plugging in wells.	100 Cft	163.75	81.88
17	Providing and laying watering and ramming brick ballast 1½" to 2" (40 mm to 50 mm) mixed with 25% sand for floor foundation complete in all respect.	100 Cft	195.75	97.88
18	Cement concrete plain including, placing, compacting, finishing and curing complete (including screening and washing of stones aggregate)			

19	Cement plaster 1:4 upto 20' (6.00 m) height 1/2" (13 mm) thick.	100 Sft	2,273.22	1,136.61
20	Cement plaster 3/8" (10 mm thick under soffit of R.C.C. roof slabs only, upto 20' height (Ratio 1:3).	100 Sft	458.08	229.04
21	Cement pointing struck joints on wall upto 20' (6m) height (a) Ratio 1:2 including extra cost of labour and material for red oxide pigment in cement pointing to match with the colour of bricks.	100 Sft	1,959.50	979.75
22	Providing, laying, cutting, jointing, testing and disinfecting PVC/ uPVC pipe line with 'B' Class working pressure complete in all respects:- 4" i/d (100 mm)	1 Rft	52.00	26.00
23	Providing and installing P.V.C. bends, of B.S.S.b) 4" i/d (100 mm)	1 No	8.00	4.00
24	Making top khurra on roof 2' x 2' x 6".	1 No	4.00	2.00
25	Distempering:- 3 coat	100 Sft	2,041.08	1,020.54

27	Preparing surface and painting of doors and windows any type (including edges):-	100 Sft	356.00	178.00
28	Fabrication of heavy steel work, with angle, tees, flat iron round iron and sheet iron for making trusses, girders, tanks, etc., including cutting, drilling, revitting, handling, assembling and fixing, but excluding erection in position.	100 Kg	1,339.83	669.92
29	Supply and erection of PVC pipe for wiring recessed in walls, including inspection boxes, pull boxes, hooks, cutting jharries and repairing surface, etc. complete with all specials.			
a)	20mm (3/4") i/d.	1 Rft	240.00	120.00
b)	25 mm (1") i/d	1 Rft	120.00	60.00
c)	50 mm (2") i/d	1 Rft	60.00	30.00
30	Supply and erection of single core PVC insulated copper conductor cables, in prepaid P.V.C. pile/M.S. conduit/G.I. pipe/wooden strip batten/wooden casing and capping/G.I. wire/trenches (rate for cables only) (a) 250/440 volts, P.V.C. insulated.			
a)	3/0.74mm (3/0.029").	1 Rft	720.00	360.00
b)	7/0.74mm (7/0.029").	1 Rft	240.00	120.00
31	Supply and erection of copper conductor cable for service connection in prepaid pipe/G.I. wire/trenches, etc. (rate for cable only) (a) PVC insulated, PVC sheathed, twin core, 250/440 volts 7/0.44" (7/1.12mm).	1 Rft	160.00	80.00
32	Supply and connection of M.S. sheet box of 16 SWG, 10 cm (4") deep with 4.75 mm thick (3/16") bakelite sheet top, for recessed wiring, including making holes for regulators switches, plugs etc.			
a)	10 x 10 cm (4" x 4").	1 Each	4.00	2.00
b)	17.5 x 10 cm (7" x 4").	1 Each	4.00	2.00

c)	22.5 x 10 cm (9" x 4").	1 Each	4.00	2.00
33	Supply and erection of switches 5 amp. Piano Type.	1 Each	80.00	40.00
34	Supply and erection of ceiling rose, bakelite.	1 Each	16.00	8.00
35	Supply and erection of wall socket with 3 pin 5 amp shoe.	1 Each	8.00	4.00
36	Supply and erection of 3 pin switch and plug combined recessed type (ii) 10/15 amp.	1 Each	4.00	2.00
37	P/F wall mounted DB (Distribution Board) made with 16SWG Sheet (Recessed/Surface mounted Type), Powder coated Paint, i/c the cost of Lock, Indication lights, Thimble, Copper Comb, Wiring, Neutral & Earth Bar, Door Earthing, Digital Voltmeter, Digital Ammeter, Volt Selector Switch, Ammeter selector switch, Current Transformers and Controls Complete in all respect as approved and directed by the Engineer Incharge (Breakers will be Paid Separately)(a) 6" deep (i) 20-60A	1 No	4.00	2.00
38	Supplying, Installation and commissioning of MCB (Miniature Circuit Breaker) of specified rating made of LEGRAND FRANCE/ GE U.S.A / SCHNEIDER GERMANY /SIEMEN GERMANY/TERASAKI JAPAN/ ABB SWITZERLAND in pre-laid DBs and Panels i/c the cost of screws, necessary wire complete Single Pole (iii) 6-63 Amp (10 KA)	1 No	24.00	12.00
39	Supplying, Installation and commissioning of MCCB (Moulded Case Circuit Breaker) of specified rating made of LEGRAND FRANCE /GEU.S.A/ SCHNEIDER GERMANY/ TERASAKI JAPAN/ SIEMEN/ ABBSWITZERLAND or approved equivalent manufacturer (with fixed Thermal-Magnetic Trip) in pre-laid DB and Panels i/c the cost of screws, necessary wire complete in all respect as approved and directed by the Engineer Incharge. a) Triple Pole (ii) 15-100 Amp (10 KA, 15KA)	1 No	8.00	4.00
40	Supplying, Installation and commissioning of MCCB (Moulded Case Circuit Breaker) of specified rating made of LEGRAND FRANCE /GEU.S.A/ SCHNEIDER GERMANY/ TERASAKI JAPAN/ SIEMEN/ ABBSWITZERLAND or approved equivalent manufacturer (with fixed Thermal-Magnetic Trip) in pre-laid DB and Panels i/c the cost of screws, necessary wire complete in all respect as approved and directed by the Engineer Incharge. a) Triple Pole With Adjustable Thermal-Magnetic Trip /Electronic Trip (60-100%) (i) 25-100 Amp	1 No	4.00	2.00
41	Supply and erection of tube light, including rod, choke, starter with frame, flexible wire, including connection from ceiling rose, etc., complete ii) single rod (40 watts) with one choke and one starter.	1 No	12.00	6.00
42	Supply and erection of bakelite button holder shade, large size	1 No	12.00	6.00
43	Carriage of 100 Cf t. (2.83 cu.m) of all materials like stone aggregate, spawl, kankar lime (unslaked), surkhi, etc. or 150 Cf t. (4.25 cu.m) timber, by truck or by any other means owned by the contractor from Sakhi Sarwar Quarry to site 275 Km including first 11KM hilly area.			
i	PCC 1:4:8	100 Cft	405.55	202.78
ii	PCC 1:2:4	100 Cft	161.43	80.71
iii	RCC 1:2:4	100 Cft	607.46	303.73
iv	DPC 1:2:4	100 Cft	28.38	14.19
9	Pump House			
1	Excavation in foundation of building, bridges and other structures, including dagbelling, dressing, refilling around structure with excavated earth, watering and ramming lead up to one chain and lift upto 5 ft. In ordinary soil (above 5 ft depth)	1000 Cft		
2	Extra for slush or Daldal including dewatering.	1000 Cft		

5	Providing and laying reinforced cement concrete (including prestressed concrete), using Sulphate resisting cement ; coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete 2) Plastering done under soffit of R.C.C. (but excluding the cost of steel reinforcement, its fabrication and placing in position etc.)			
---	--	--	--	--

6	Bitumen coating to plastered or cement concrete surface. 14 lbs per 100 Sft (6.35 Kg. per Sq.m)	100 Sft		
7	Single layer of tiles 9"x4½"x1½" (225x113x40 mm) laid over 4"(100 mm) earth and 1" (25 mm) mud plaster without Bhoosa, grouted with cement sand 1:3 on top of RCC roof slab, provided with 34 lbs. per %Sft. or 1.72 Kg/Sq.m bitumen coating sand blinded.	100 Sft		
8	Providing and laying polythene sheet under floor or roof complete 500 gauge.	1 Sft		
9	Providing, laying, cutting, jointing, testing and disinfecting PVC/ uPVC pipe line with 'B' Class working pressure complete in all respects:- 4" i/d (100 mm)	1 Rft		
10	Providing and installing P.V.C. bends, of B.S.S.b) 4" i/d (100 mm)	1 No		
11	Making top khurra on roof 2' x 2' x 6".	1 No		
12	Providing and fixing windows consisting of M.S. box section frame 2"x1½", (50x40mm) leaves frame 1½"x1" (40x25mm) box section frame for glazing 3/8"x3/8" (10x10mm) using 16 SWG sheet 'U' shaped rubber supported with 1"x1/8" (25x3mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section ½"x½" (13x13mm) of 16 SWG for fixing 24 SWG wire gauze on outer side by means of ¾"x1/8" (20x3mm) M.S. flat and screws including grill of M.S. flat ½"x1/8" (13x3mm) or ¼"x¼" (6x6mm) square bar with independent frame of ½"x½" (13x13mm) box section of 16 SWG i/c all C.P. fitting and painting 3 coats complete in all respect.	1		
13	Making and fixing steel grated door with 1/16" thick 1.5mm) sheeting, including angle iron frame 2"x2"x3/8" (50x50x10 mm) and ¾" (20 mm) square bars 4" (100 mm)	1 Sft		
14	Distemping:- 2 coats	100 Sft		

16	Preparing surface and painting of doors and windows any type (including edges):-	100 Sft		
17	Providing and fixing 1¼x1¼"x3/16" (31x31x5 mm) angle" iron step, in manhole chambers, including carriage and setting the same in work to correct lines and levels.	1 No		
18	Providing/fixing stair railing consisting of M.S. Box section size 1-1/2"x3" of 16 SWG welded with M.S. flat 1"x1/8" continuously and welded over M.S. square bars 5/8"x5/8" punched in M.S. flat 2 ¾' high @ 5½" c/c fixed in steps of stair I/C painting 3 coats complete.	1 Rft		
19	Providing and fixing trash rack as per drawing	1 Sft		
20	Providing and laying Tuff Pavers, having 7000PSI ,crushing strength of approved manufa cturer, over2"to3" sand cushion i/c grouting withsand in joints i/c finishing to require slope . complete in all respect. (50% Grey / 50% Coloured) 60-mm thick	1 Sft		
21	Providing & laying graded bajri ½" to 2" gauge on level (including carriage).	100 Cft		
22	1½"(40 mm) thick mosaic flooring, consisting of ½ " mosaic topping of one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over 1"(25 mm) thick floor of 1:2:4 cement concrete, including rubbing and polishing complete with finishing :-using grey cement	100 Sft		
23	Mosaic dado or skirting with one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over ½"(13 mm) thick cement plaster 1:3, including rubbing and polishing, complete with finishing:(a) using grey cement: i) 1/2"(13 mm) thick	100 Sft		
24	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels(a) Size 1½" x 3/8" (40 x 10 mm)	1 Rft		
25	Providing and embedding 10"(250mm) wide PVC water stopper in expansion joints of RCC structures (Retaining walls, water tanks, Slabs) complete in all respect. 10mm thick	1 Rft		
26	Supply and erection of PVC pipe for wiring recessed in walls, including inspection boxes, pull boxes, hooks, cutting jharries and repairing surface, etc. complete with all specials.			

	a) 20mm (3/4") i/d.	1 Rft		
	b) 25 mm (1") i/d	1 Rft		
27	Supply and erection of single core PVC insulated copper conductor cables, in prepaid P.V.C. pile/M.S. conduit/G.I. pipe/wooden strip batten/wooden casing and capping/G.I. wire/trenches (rate for cables only) (a) 250/440 volts, P.V.C. insulated.			
	a) 3/0.74mm (3/0.029").	1 Rft		
	b) 7/0.74mm (7/0.029").	1 Rft		
28	Supply and connection of M.S. sheet box of 16 SWG, 10 cm (4") deep with 4.75 mm thick (3/16") bakelite sheet top, for recessed wiring, including making holes for regulators switches, plugs etc.			
	b) 17.5 x 10 cm (7" x 4").	1 Each		
29	Supply and erection of switches 5 amp. Piano Type.	1 Each		
30	Supply and erection of backlite button holder shade, large size.	1 Each		
31	Supply and erection of ceiling rose, bakelite.	1 Each		
32	Suppling,Installation and comissioning of MCB (Miniature Circuit Breaker) of specified rating made of LEGRAND FRANCE/ GE U.S.A / SCHNEIDER GERMANY /SIEMEN GERMAN/TERASAKI JAPAN/ ABB SWITZERLAND in prelaid DBs and Panels i/c the cost of screws,necessary wire completb) Double Pole(iii) 6-63 Amp (10 KA)	1 No		
33	Suppling,Installation and comissioning of MCB (Miniature Circuit Breaker) of specified rating made of LEGRAND FRANCE/ GE U.S.A / SCHNEIDER GERMANY /SIEMEN GERMAN/TERASAKI JAPAN/ ABB SWITZERLAND in prelaid DBs and Panels i/c the cost of screws,necessary wire complet Single Pole(iii) 6-63 Amp (10 KA)	1 No		
34	Providing and fixing Pakistan Energy Label NEECA approved Copper winded wall bracket Fan i/c the cost of necessary cable and hardware for connection as approved and directed by Engineer Incharge.ii) 24" Sweep dia	1 Each		
35	Supply and erection of tube light, including rod, choke, starter with frame, flexible wire, including connection from ceiling rose, etc., complete ii)single rod (40 watts) with one choke and one starter.	1 No		
	Lining Portion			
36	Barrow pit excavation undressed lead up to 100 ft in ordinary soil.	1000 Cft		
37	Compaction of earth work with power Road Roller, i.c ploughing mixing, moistening earth to optimum moisture content in layer etc; complete 90 % maximum modified AASHO dry denisty	1000 Cft		
38	Earthwork excavation in irrigation channels, drains, etc. to designed section, grades and profiles, excavated material disposed off undressed within 50 ft. (15 m) lead:- ordinary Soil	1000 Cft		
	Cement plaster 1.5" (40 mm) thick ratio 1:6:-			
	a) In bed	100 Sft		
	b) On slope	100 Sft		
39	Cement concrete lining, using washed screened and graded stone aggregate:-			
	a) In bed, ratio 1:2:4	100 Cft		
	b) On slope, ratio 1:2:4	100 Cft		
40	Providing and placing cement, sand and bituminous joint sealant in ratio 1:2:3, 1/2" wide, 1" deep.	1 Rft		
41	Bitumen coating to plastered or cement concrete surface:- 10 lbs. per 100 Sft.	100 Sft		
10	Inlets			
1	Excavation in foundation of building, bridges, and other structures, including dag belling, dressing refilling around structure with excavated earth, watering and ramming lead upto one chain (30m)and lift upto 5' (1.5 m) (b) in ordinary soil. By Manual	1000 Cft		
2	Cement concrete plain including, placing, compacting, finishing and curing complete (including screening and washing of stones aggregate)			
3	Pacca brick work other than buildings upto 10 feet height. Cement sand mortar ratio 1:4	100 Cft		

4	Providing and laying reinforced cement concrete (including prestressed concrete), using Sulphate resisting cement; coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete 2) Plastering done under soffit of R.C.C. (but excluding the cost of steel reinforcement, its fabrication and placing in position etc.)			
---	--	--	--	--

6	Providing and laying dry, hand packed stone apron as per drawing	100 Cft		

8	Carriage of 100 Cf t. (2.83 cu.m) of all materials like stone aggregate, spawl, kankar lime (unslaked), surkhi, etc. or 150 Cf t. (4.25 cu.m) timber, by truck or by any other means owned by the contractor from Sakhi Sarwar Quarry to site 275 Km including first 11KM hilly area.			
i	PCC 1:4:8	100 Cft		
i	PCC 1:2:4	100 Cft		
ii	RCC 1:1.5:3	100 Cft		
iii	Dry Hand Pack Stone	100 Cft		
11	Construction of New Quarter for Tube well Operator			
1	Excavation in foundation of building, bridges, and other structures, including dag belling, dressing refilling around structure with excavated earth, watering and ramming lead upto one chain (30m) and lift upto 5' (1.5 m) (b) in ordinary soil. By Manual	1000 Cft	72,531.66	
2	Spraying antitermite liquid mixed with water ratio 1:40	1 Sft	88,776.19	
3	Cement concrete plain including, placing, compacting, finishing and curing complete (including screening and washing of stones aggregate)			

6	Providing and laying vertical damp proof course with cement sand plaster and bitumen coating with one coat of bitumen and one coat of polythene sheet 500 gauge-Ratio 1:3 a) ½ " thick (13 mm)	100 Sft	8,771.49	
7	Filling watering ramming earth under floors with surplus earth from foundation etc.	1000 Cft	31,674.37	
8	Pacca brick work in ground floor. Cement sand mortar Ratio 1:4	100 Cft	47,794.11	
9	Providing and laying reinforced cement concrete (including prestressed concrete), using Sulphate resisting cement ; coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete 2) Plastering done under soffit of R.C.C. (but excluding the cost of steel reinforcement, its fabrication and placing in position etc.) - a) Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects. Type C (nominal mix 1:2:4)	1 Cft	21,724.43	

11	Providing and fixing windows consisting of M.S box section frame 2" x 1½" (50 x 40mm) Leaves frame 1½" x 1" (40 x 25 mm) box section frame for glazing 3/8" x 3/8" (10 x 10 mm) using 16 SWG sheet 'U' shaped rubber supported with 1" x 1/8" (25 x 3 mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section 1/2" x 1/2" (13 x 13 mm) of 16 SWG for fixing 24 SWG wire gauge on outer side by means of 3/4" x 1/8" (20 x 3 mm) M.S. flat and screws including grill of M.S. flat 1/2" x 1/8" (13 x 3 mm) or 1/4" x 1/4" (6 x 6 mm) square bar with independent frame of 1/2" x 1/2" (13 x 13 mm) box section of 16 SWG i/c all C.P fitting and painting 3 coats complete in all respect.	1 Sft	3,276.00	
----	---	-------	----------	--

12	Providing and fixing mild steel chowkat of doors windows C. windows etc. including holdfast making and threading 18 holes for hinges etc. complete 1½" x 1½" x 1/4" (40 x 40 x 6 mm) welded with M.S. flat 2" x 1/4" (50 m M.S. angle iron).	1 Sft	3,822.00	
13	Providing and fixing 1½" (40 mm) thick solid flush door shutter sterling or equivalent with commercial ply (5mm thick) on both sides double pressed and deodar wood lapping 1½" x 3/8" (40 mm x 10 mm) around shutter including chromium plated fitting, iron hinges with aluminum kick plate 22 SWG on both sides and finger plate complete in all respect.	1 Sft	3,822.00	
14	Providing and laying single layer of tile 9" x 4½" x 1½" laid over 4" earth and 1" thick mud plaster without bhoosa, grouted with cement mud (1:3) on top of R.C.C. roof, slab, provided with 34 lbs. per % Sft. Or 1.72 Kg./Sq.m. bitumen coating sand blinded.	100 Sft	33,854.84	
15	Providing and laying polythene sheet under floor or roof complete 500 gauge.	1 Sft	34,218.84	
16	Supplying and filling sand under floor or plugging in wells.	100 Cft	7,420.14	
17	Providing and laying watering and ramming brick ballast 1½" to 2" (40 mm to 50 mm) mixed with 25% sand for floor foundation complete in all respect.	100 Cft	9,109.10	
18	1½"(40 mm) thick mosaic flooring, consisting of ½ " mosaic topping of one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over 1"(25 mm) thick floor of 1:2:4 cement concrete, including rubbing and polishing complete with finishing :-using grey cement	100 Sft	22,325.37	
19	Mosaic dado or skirting with one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over ½"(13 mm) thick cement plaster 1:3, including rubbing and polishing, complete with finishing:(a) using grey cement: i) 1/2"(13 mm) thick	100 Sft	14,054.04	
20	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels(a) Size 1½" x 3/8" (40 x 10 mm)	1 Rft	22,750.00	
21	Cement concrete plain including, placing, compacting, finishing and curing complete (including screening and washing of stones aggregate)			

22	Cement plaster 1:4 upto 20' (6.00 m) height 1/2" (13 mm) thick.	100 Sft	113,184.66	
23	Cement plaster 3/8" (10 mm thick under soffit of R.C.C. roof slabs only, upto 20' height (Ratio 1:3).	100 Sft	21,116.55	
24	Distempering:- 3 coat	100 Sft	99,928.24	
26	Cement pointing struck joints on wall upto 20' (6m) height (a) Ratio 1:2 including extra cost of labour and material for red oxide pigment in cement pointing to match with the colour of bricks.	100 Sft	65,280.22	
27	Providing, laying, cutting, jointing, testing and disinfecting PVC/ uPVC pipe line with 'B' Class working pressure complete in all respects:- 4" i/d (100 mm)	1 Rft	1,183.00	
28	Providing and installing P.V.C. bends, of B.S.S.b) 4" i/d (100 mm)	1 No	182.00	
29	Making top khurra on roof 2' x 2' x 6".	1 No	91.00	
30	Providing and fixing sliding; bolt to doors iron sliding bolt, 10" (250 mm) long.	1 No	182.00	
31	Painting new surface (c) preparing surface and painting of doors and windows any type (including edges) priming coat and 2 subsequent coats of paint.	100 Sft	7,644.00	
32	Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern) combined with foot rest white.	1 Each	91.00	
33	Providing and fitting "P" trap 10 cm (4") glazed.	1 Each	273.00	
34	Providing and Fixing chromium plated bib cock (ii)1.5 cm (1/2").	1 Each	364.00	
35	Providing & fitting plastic made low down flushing cistern 13.63 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete (i) white.	1 Each	91.00	
36	Providing, laying, cutting, jointing, testing and disinfecting PVC/ uPVC pipe line with 'B' Class working pressure complete in all respects:- 4" i/d (100 mm)	1 Rft	9,100.00	
37	Providing and installing P.V.C. bends, of B.S.S.b) 4" i/d (100 mm)	1 No	364.00	
38	Providing and installing P.V.C. tees, of B.S.S.Class 'B' working pressure:- b) 4" i/d (100 mm)	1 No	364.00	

39	Providing,laying,testing and commissioning of POLYPROPYLENE RANDOM COPOLYMER (PPRC water supply pipe (Dadex/ Popular/ Beta or approved equivalent manufacturer, withs pecified pressure rating PN (PRESSURE NOMINAL) and conforming to DIN8077-8078 codei/ccost of solvent,specials,making jharries complete in all respect as approved and directed by Engineer Incharge.(Internal/ExternalDiametersmentioned). a) PN-16 pipe			
i	a) 20mm	1 Rft	9,100.00	
ii	b) 25mm	1 Rft	4,550.00	
40	Providing and fixing looking glass (mirror) 22" x 16" (55 x 40) cm, and 5 mm thick glass first quality.	1 Each	91.00	
41	Providing and fixing stainless steel sink with drain board, size 120 x 60 cm (48 x 24") including bracket set, waste pipe and waste coupling.	1 Each	91.00	
42	Providing and fitting.			
	a) Plastic soap dish.	1 Each	91.00	
	b) Plastic towel rail.	1 Each	91.00	
	c) plastic shelf 60x13cm (24" x 5") with bracket and railing.	1 Each	91.00	
43	Providing and fixing chromium plated tee stop cock 15 mm (1/2").	1 Each	91.00	
44	Supply and erection of PVC pipe for wiring recessed in walls, including inspection boxes, pull boxes, hooks, cutting jharries and repairing surface, etc. complete with all specials.			
	a) 20mm (3/4") i/d.	1 Rft	9,100.00	
	b) 25 mm (1") i/d	1 Rft	4,550.00	
45	Supply and erection of single core PVC insulated copper conductor cables, in prepaid P.V.C. pile/M.S. conduit/G.I. pipe/wooden strip batten/wooden casing and caping/G.I. wire/trenches (rate for cables only) (a) 250/440 volts, P.V.C. insulated.			
	a) 3/0.74mm (3/0.029").	1 Rft	27,300.00	
	b) 7/0.74mm (7/0.029").	1 Rft	9,100.00	
46	Supply and erection of copper conductor cable for service connection in prepaid pipe/G.I. wire/trenches, etc. (rate for cable only) (a) PVC insulated, PVC sheathed, twin core, 250/440 volts 7/0.44" (7/1.12mm).	1 Rft	18,200.00	
47	Supply and connection of M.S. sheet box of 16 SWG, 10 cm (4") deep with 4.75 mm thick (3/16") bakelite sheet top, for recessed wiring, including making holes for regulators switches, plugs etc.			
	a) 10 x 10 cm (4" x 4").	1 Each	182.00	
	b) 17.5 x 10 cm (7" x 4").	1 Each	364.00	
	c) 22.5 x 10 cm (9" x 4").	1 Each	91.00	
48	Supply and erection of switches 5 amp. Piano Type.	1 Each	3,185.00	
49	Supply and erection of backlite button holder shade, large size.	1 Each	546.00	
50	Supply and erection of ceiling rose, bakelite.	1 Each	546.00	
51	Supply and erection of wall socket with 3 pin 5 amp shoe.	1 Each	182.00	
52	Supply and erection of 3 pin switch and plug combined recessed type (ii) 10/15 amp.	1 Each	182.00	
53	P/F wall mounted DB (Distribution Board) made with 16SWG Sheet (Recessded/Surface mounted Type), Powder coated Paint, i/c the cost of Lock, Indication lights,Thimble, Copper Comb, Wiring, Netural & Earth Bar, Door Earthing, Digital Voltmeter,Digital Ammeter,Volt Selector Switch,Ammeter selector switch,Current Transformers and Controles Complete in all respect as approved and directed by the Engineer Incharge (Breakers will be Paid Separately)(a) 6" deep (i) 20~60A	1 No	91.00	
54	Suppling,Installation and comissioning of MCB (Miniature Circuit Breaker) of specified rating made of LEGRAND FRANCE/ GE U.S.A / SCHNEIDER GERMANY /SIEMEN GERMAN/TERASAKI JAPAN/ ABB SWITZERLAND in prelaidd DBs and Panels i/c the cost of screws,necessary wire completb) Double Pole(iii) 6-63 Amp (10 KA)	1 No	91.00	
55	Suppling,Installation and comissioning of MCB (Miniature Circuit Breaker) of specified rating made of LEGRAND FRANCE/ GE U.S.A / SCHNEIDER GERMANY /SIEMEN GERMAN/TERASAKI JAPAN/ ABB SWITZERLAND in prelaidd DBs and Panels i/c the cost of screws,necessary wire complet Single Pole(iii) 6-63 Amp (10 KA)	1 No	364.00	
56	Supply and erection of 3/8" (10mm) dia M.S. bar fan hook, placed at the time of casting of slab.	1 Each	91.00	

57	Providing and fixing Pakistan Energy Label NEECA approved Copper winded Ceiling Fan i/c the cost of necessary cable and hardware for connection as approved and directed by Engineer Incharge. 56" Sweep	1 Each	91.00	
58	Erecting of ceiling fan along with regulator (all sizes) including carriage local railway station/ store to site of work, electric wire/cable for suspension rod and board connection and cutting, threading on the rod where necessary.	1 Each	91.00	
59	Supply and erection of tube light, including rod, choke, starter with frame, flexible wire, including connection from ceiling rose, etc., complete ii)single rod (40 watts) with one choke and one starter.	1 No	546.00	
60	Provided and installed 1 HP electric water pump with 70 ft bore, and successfully installed a 200-gallon water tank including all accessories and plumbing connections.	1 Each	91.00	
61	Carriage of 100 Cf t. (2.83 cu.m) of all materials like stone aggregate, spawl, kankar lime (unslaked), surkhi, etc. or 150 Cf t. (4.25 cu.m) timber, by truck or by any other means owned by the contractor from Sakhi Sarwar Quarry to site 275 Km including first 11KM hilly area.			
i	PCC 1:4:8	100 Cft	11,086.97	
ii	PCC 1:2:4	100 Cft	1,566.57	
iii	RCC 1.2.4	100 Cft	19,117.50	
iv	DPC 1.2.4	100 Cft	971.75	
12	Electrical Work			
1	HT Spun Pole 45'	1 No	25	
2	HT S/STRUCTURE Pole 36'	1 No	700	
3	Earthing	1 No	840	
4	Steel -X-ARMS	1 No	1760	
5	11-KV Disc: Insulator	1 No	1500	
6	Eye Nut/Ahchore Shackle/D.End Clump	1 No	1200	
7	11KV Pin Insulator with Pins	1 No	2415	
8	D-Shackle + Spool Insulator	1 No	1000	
9	DA Bolts	1 No	700	
10	Nuts & Bolts 14"	1 No	500	
11	Nuts & Bolts 12"	1 No	500	
12	Nuts & Bolts 02"	1 No	200	
13	Stay Rod + stay strips Complete	1 No	150	
14	Stay Wire	1 M	1870	
15	ACSR Rabbit Conductor	1 No	61590	
16	Transformer 400-KVA	1 No	2	
17	Transformer 100-KVA	1 No	5	
18	Transformer 50-KVA	1 No	5	
19	Transformer 25-KVA	1 No	40	
23	Plate form D/Edge	1 No	60	
25	Nuts & Bolts	1 No	500	
26	D-Fuses Fitting Set	1 No	183	
27	Steel Cross arm for D fuse Mounting	1 No	50	
28	LT Capacitor	1 No	50	
29	LT Spun Pole 31'	1 No	500	
30	street light pole bracket 30 mm (1¼") G.I. pipe 2 metre long, complete with 2 No. pole clamp. (Ch-24) [Pump station + Tubewell Rooms]	1 No	200	
31	Supply and erection of pole mounted street light, holders, shade and glass, etc., for fitting 125/250 watts mercury vapour lamp (excluding cost of lamps): ii) Philips design (Ch 24) [Pump station + Tubewell Rooms]	1 No	200	
32	Supply and fitting of mercury vapour lamp, complete with choke set ii) 250 watt lamp (Ch 24) [Pump station + Tubewell Rooms]	1 No	200	
33	PVC 4/C Cable 19.083 (70mm Armoured	1 No	5000	
34	AMR METER HT/LT Type (bi-directional)	1 No	50	
35	ATB A-Type 100/5	1 No	10	
36	Earthing	1 No	20	
37	CTs 100/5 Amp	1 No	80	
38	(A) Cost of 11 KV Line material	1 No		
39	(B) Cost of Sub Station material	1 No		
40	(c.) Cost of service and Metering material	1 No		
41	Earthing Pit & Material will be provided by consumer	1 No		
42	Contractor Charges/ Foundation Charges 60000 x 700	1 No		
43	Feeder Rehabilitation Charges / Security	1 No		
44	630 KVA TRANSFORMER	1 Ea		

45	200 KVA TRANSFORMER	1 Ea		
46	D/STRUCTURE PLATFORM	1 Ea		
48	LT PCC POLE	1 Ea		
49	ATB A TYPE	1 Ea		
50	CTS 100/5	1 Ea		
51	25 KVATransformer	1 Ea	1	1
52	S/STRUCTURE PLATFORM	1 Ea	1	1
53	HT PCC POLE	1 Ea	3	1
55	D-Fuse Fitting	1 Ea	3	3
56	ACSR RABBIT	1 M	930	30
57	AMR METER	1 Ea	1	1
58	Pin Insulator with Pins	1 Ea	9	6
59	11 KV Disc	1 Ea	6	
60	Stay Rods	1 Ea	4	
62	Earth Rods	1 Ea	7	3
63	PVC 4/C 19/.052	1 M	30	30
64	PVC 4/C 19/.083	1 M		
65	Nuts & Bolts	L/S	1	1
66	Civil Work Charges (Contactor Charges)	1 Ea	3	1
67	Providing and fixing barbed wire fencing, with 4 horizontal and two cross wires, with R.C.C. 1:2:4 posts, 5.5'x6"x9" (1.68mx150mmx225 mm) at 8 ft. (2.45 m) center to center, reinforced with 4 No. 3/8" (10 mm) dia vertical bars and 1/8" (3 mm) dia stirrups 12" (300 mm) center to center, complete in all respects. in cement concrete 1:4:8 base of size 12"x12"x21"	100 Rft	49390.0	
68	Excavation in foundation of building, bridges, and other structures, including dag belling, dressing refilling around structure with excavated earth, watering and ramming lead upto one chain (30m)and lift upto 5' (1.5 m) (b) in ordinary soil.	1000 Cft	2063.0	

72	Pacca brick work other than building upto 10ft. (3 m) Ratio 1:4	100 Cft	1656.6	
73	Cement plaster 1:4 upto 20' (6.00 m) height 1/2" (13 mm) thick.	100 Sft	6225.5	
74	Providing and fixing collapsible gate made of 2"x2"x1/4" (50x50x6 mm) tee iron at top and bottom, channel iron verticals 3/4"x1/4"x1/8" (20x6x6x3 mm) at 3" (75 mm) to 5" (125 mm) centre to centre (approximate) and flat iron crosses 3"x3/16" (75x5 mm), and best quality rollers at bottom of 3" (75 mm) diameter including holdfasts, handles 12" (300 mm) long of 3/4"x1/4"x1/8" (20x6x6x3 mm) channel iron, locking arrangement inside and outside, painting 3 coats of black Japan enameled, complete in working order.	1 Sft	6650.0	
75	Supply and erection PVC pipe for recessed wiring (main and sub-main) purpose, including bends, specials, etc. in floor, wall or trenches:- 50mm i/d	1 Rft	14250.0	
76	Supply and erection of single core PVC insulated copper conductor cables, in prelaidd PVC pipe/M.S. conduit/G.I pipe/wooden strip batten/wooden casing an capping/G.I. wire/trenches (rate for cables only):7/0.74 mm (7/0.029")	1 Rft	28500.0	
13.	Installation of Tubewells			
1	Providing installation, testing, and commissioning of a vertical deep well turbine tubewell pump with discharge 2 cusec against 70 ft head , including bowl assembly, vertical column pipe with shaft, motor, pre-lubrication tank, foundation fixing and alignment, MCCB/control panel with all electrical connections, cables and accessories from transformer to tubewell including earthing and protection devices, complete suction and delivery piping up to 25 ft outlet basin of approved material (MS/CI) with bends, flanges, valves, gaskets, supports and accessories, carrying out all works for energizing, testing, and full-load commissioning; pump casing in Gray Cast Iron EN-GJL-250, impeller in Stainless Steel grade 1.4408, column pipe coated internally and externally with epoxy paint, materials verified per EN 10204-3.1, minimum 80% efficiency per ISO 9906-1B; motor of reputed manufacturer, vertical solid shaft, IE3 efficiency class, 15 kW (20 HP, 1450 rpm), 4-pole, 3-phase, 50 Hz, 380/400 V, manufacturer to have in-house hydraulic and metallurgical testing facility, complete in all respects suitable for tubewell application. [including transportation and all overhead charges]	1 No	37	

2	Providing installation, testing and commissioning of horizontal centrifugal pump having discharge capacity of 10 cusec against 30 ft - 35 ft head including pump, motor, bowl assembly, column set, pre-lubrication tank, foundation fixing and alignment, MCCB/control panel with all electrical cables and connections from transformer to pump including earthing and protection devices, complete suction piping inside the chamber (SS/MS/CI) and delivery piping up to the outlet basin (40–50 ft) of approved material (Fibre reinforced cement/upvc of suitable internal diameter size as approved by E-in-C) with all bends, flanges, gaskets, supports and accessories, and carrying out all works necessary for energizing, testing and full-load commissioning of the complete pump set in all respects.. Pump shall have min. 81% efficiency which should be verified according to ISO 9906-1B standard. Material of pump casing shall be Gray cast iron EN-GJL-250 having impeller in Stainless Steel grade 1.4408. Pump shall be coated internally with epoxy paint. Material of pump shall be verified according to material test certificate EN 10204-3.1. Motor shall be of reputed manufacturer having min. IE3 efficiency class. Rating of motor to be 37 KW (50HP, 950 rpm)/6 pole, 3 phase, 50 Hz, 380/400 Volts. Manufacturer shall have its own testing facility to verify pumps hydraulic performance testing. Manufacturer shall have its own material testing lab to verify metallurgical testing. [including transportation and all overhead charges]	1 No	8	
3	Providing installation, testing and commissioning of horizontal centrifugal pump having discharge capacity of 10 cusec against 40 ft - 45 ft head including pump, motor, bowl assembly, column set, pre-lubrication tank, foundation fixing and alignment, MCCB/control panel with all electrical cables, accessories and connections from transformer to pump including earthing and protection devices, complete suction piping inside the chamber (SS/MS/CI) and delivery piping up to the outlet basin (40–50 ft) of approved material (Fibre reinforced cement/upvc of suitable internal diameter size as approved by E-in-C) with all bends, flanges, valves, gaskets, supports and accessories, and carrying out all works necessary for energizing, testing and full-load commissioning of the complete pump set in all respects.. Pump shall have min. 82% efficiency which should be verified according to ISO 9906-1B standard. Material of pump casing shall be Gray cast iron EN-GJL-250 having impeller in Stainless Steel grade 1.4408. Pump shall be coated internally with epoxy paint. Material of pump shall be verified according to material test certificate EN 10204-3.1. Motor shall be of reputed manufacturer having min. IE3 efficiency class. Rating of motor to be 45 KW (60HP, 950 rpm)/6 pole, 3 phase, 50 Hz, 380/400 Volts. Manufacturer shall have its own testing facility to verify pumps hydraulic performance testing. Manufacturer shall have its own material testing lab to verify metallurgical testing. [including transportation and all overhead charges]	1 Job	6.00	
4	Providing installation, testing and commissioning of horizontal centrifugal pump having discharge capacity of 20 cusec against 30 ft - 35 ft head including pump, motor, bowl assembly, column set, pre-lubrication tank, foundation fixing and alignment, MCCB/control panel with all electrical cables, accessories and connections from transformer to pump including earthing and protection devices, complete suction piping inside the chamber (SS/MS/CI) and delivery piping up to the outlet basin (40 -- 50 ft) of approved material (Fibre reinforced cement/upvc of suitable internal diameter size as approved by E-in-C) with all bends, flanges, valves, gaskets, supports and accessories, and carrying out all works necessary for energizing, testing and full-load commissioning of the complete pump set in all respects.. Pump shall have min. 83% efficiency which should be verified according to ISO 9906-1B standard. Material of pump casing shall be Gray cast iron EN-GJL-250 having impeller in Stainless Steel grade 1.4408. Pump shall be coated internally with epoxy paint. Material of pump shall be verified according to material test certificate EN 10204-3.1. Motor shall be of reputed manufacturer having min. IE3 efficiency class. Rating of motor to be 75 KW (100HP, 950 rpm)/8 pole, 3 phase, 50 Hz, 380/400 Volts. Manufacturer shall have its own testing facility to verify pumps hydraulic performance testing. Manufacturer shall have its own material testing lab to verify metallurgical testing. [including transportation and all overhead charges]	1 No	1	

5	Providing installation, testing and commissioning of vertical tubular casing pump with ever cleaning blades having discharge capacity of 40 cusec against 16-25 ft head including pump, motor, bowl assembly, column set, pre-lubrication tank, foundation fixing and alignment, MCCB/control panel with all electrical cables, accessories and connections from transformer to pump including earthing and protection devices, complete suction piping inside the chamber (SS/MS/CI) and delivery piping up to the outlet basin (40–50 ft) of approved material (Fibre reinforced cement/upvc of suitable internal diameter size as approved by E-in-C) with all bends, flanges, valves, gaskets, supports and accessories, and carrying out all works necessary for energizing, testing and full-load commissioning of the complete pump set in all respects. . Pump shall have min. 84% efficiency which should be verified according to ISO 9906-1B standard. Material of pump casing shall be Gray cast iron JL-1040 having propeller (ever cleaning blades) in Stainless Steel grade 1.4408. Pump and column pipe shall be coated internally and externally with epoxy paint. Material of pump shall be verified according to material test certificate EN 10204-3.1. Motor shall be of reputed manufacturer having min. IE3 efficiency class. Vertical solid shaft. Rating of motor to be 110 KW (150HP, 450 rpm)/8 pole, 3 phase, 50 Hz, 380/400 Volts. . Manufacturer shall have its own testing facility to verify pumps hydraulic performance testing. Manufacturer shall have its own material testing lab to verify metallurgical testing. [including transportation and all overhead charges]	1 No	8	
6	Providing, installation, testing and comissioning of 5 Ton and more capacity Gantry Craine, with girder bridge type arrangement, fitted with electric motor for its operation and mobility, electric wiring and fixing in position, complete in all respect.	1 No	3	
	Providing, installation, testing and comissioning of 5 Ton and more capacity Gantry Craine, with girder bridge type arrangement, fitted with electric motor for its operation and mobility, electric wiring and fixing in position, complete in all respect.	1 No	1	
7	Providing, installation, testing and comissioning of 10 Ton and more capacity Gantry Craine, with girder bridge type arrangement, fitted with electric motor for its operation and mobility, electric wiring and fixing in position, complete in all respect.	1 No	1	
8	Direct Rotary / Reverse Rotary drilling of bore for tubewell in all type of soil except shingle gravel and rock. i). 15 " To 18" (500 to 650 mm)	Rft	8140	
9	Collection of lithological samples with sieve analysis at every 5 ft. interval or change of lithology whichever is earlier.	1 No	1628	
10	Furnishing sample of water from bore hole.	Per Set of 2 bottles	37	
11	Providing, installations testing and commissioning of 16" dia fiberglass blind pump housing casing with 6mm wall thickness having quick lock mechanical key joints complete in all respect as per specification and approved by the Engineer.	Rft	2590	
12	Providing and installation of Fibre Glass reducer 16"x10" with wall thickness 5.5 mm. complete in all respect as per specification and approved by the Engineer.	1 No	74	
13	Providing and installing Fiberglass Reinforced Polypropelene (FRP) strainer of specifid wall thickness having slot size of 0.9 mm to 1.10 mm in Tubewell borehole i/c the cost of male/female coupling with Nylone Strip, studs complete in all respect as approved and directed by the Engineer Incharge vi) 10" inch dia (6.35 mm thickness	Rft	4440	
14	Proving and installation of fiberglass Blank blind casing pipe dia 10" with 5.5" wall thickness. complete in all respect as per specification and approved by the Engineer.	Rft	740	
15	Providing and installing Fiber glass Reinforced Polypropelene (FRP) bail plug of specified wall thickness having slot size of 0.9 mm to 1.10 mm in Tubewell bore hole i/c the cost of male / female coupling with Nylone Strip, studs complete in all respect as approved and directed by the Engineer Incharge.vi) 10"dia (6.35mm thickness)	Rft	370	
16	Providing and installation of centralizer complete in all respect as per specification and approved by the Engineer.	1 No	148	
17	Shrouding with graded pea gravel 3/8" to 1/8" around tubewell casing in the bore hole.	Cft	6520.88	
18	Testing and Development of tubewell of size 6"(150 mm) and above continusly. ii) Above 1.5 cs Discharge	Hours	2664	

19	Supply and erection of copper conductor cables for service connection (rate for cable only), PVC insulated, PVC sheathed 4 core , 600/1100 volt non armoured cable. (7/0.064")	Rft	1850	
20	Excavation of trenches in all kinds of soil except cutting rock, for watersupply pipelines upto 5 ft. (1.5 m) depth from ground level, including trimming, dressing sides leveling the beds of trenches to correct grade and cutting pits for joints, etc. complete in all respects.	1000 Cft	118400	
22	Providing,laying,testing and commissioning µPVC (Unplasticized Poly vinyl Chloride Pressure pipe of nominal diameter, conforming to PS-3051/BS-3505, Dadex/ Popular/ Beta or approved equivalent manufacturer,i/c the cost of solvent and specials complete as approved and directed by the Engineer Incharge. a)Class-D 12 inch	Lft	14800	
23	Providing,laying,testing and commissioning µPVC (Unplasticized Poly vinyl Chloride Pressure pipe of nominal diameter, conforming to PS-3051/BS-3505, Dadex/ Popular/ Beta or approved equivalent manufacturer,i/c the cost of solvent and specials complete as approved and directed by the Engineer Incharge. a)Class-D 3 inch	Lft	555	
14	Solarization of Tubewells			
1	Providing installation, testing, and commissioning of a 22.5 kW Solar PV system capable of running a horizontal centrifugal pump with discharge 2 cusec against 70 ft head, pump minimum 81% efficiency, including Tier-1 Bloomberg-certified mono / bi-facial N-type solar panels (JINKO / LONGI / JA / Canadian / AKCome / TW / Trina, 700+ W/panel, 23.5% efficiency), solar pump inverter INVT suitably rated for system capacity, mounted on 12 ft high L2/L3/L4 galvanized steel structure (14 gauge) with complete mechanical and civil works, DC and AC cabling with XLPE/PVC insulated tin-coated copper wires, combiner boxes, AC & DC breakers, SPDs (A+ grade), all distribution/protection boxes (12"x18"x18" SWG or equivalent), PVC pipes, flexible pipes (1–1.5"), thimbles (O-type, U-type with shrouds), Rawl bolts, nuts and bolts, complete earthing system, lightning arrestor, all civil works, foundations, and supports, all electrical connections for net metering with meter, transportation of all materials from warehouse to site, testing, commissioning, and manufacturer-provided maintenance/after-sales service for up to 2 years, complete in all respects as directed by the Engineer-in-Charge.	1 No	87	
3	GNSS (Topographical) Surveying instrument with Base, Rover, Controller complete in all respect	1 No	1	
4	Providing and supplying a complete aerial topographic survey package consisting of a professional RTK-enabled survey drone, high-resolution photogrammetry camera, licensed processing software, additional 8 batteries with charging hub, Ground Control Point (GCP) sets/markers, High graded RTK base station kit with tripod and pole, and 5 TB rugged NVMe SSD storage, complete in all respects (Equivalent: DJI Matrice 350 RTK Drone, Zenmuse P1c etc)	1 No	1	
5	Providing and supplying a Total Station with angle accuracy ≤5", EDM reflectorless range ≥500 m, prism range ≥1500 m, distance accuracy ±(2 mm + 2 ppm), 30× telescope, dual-axis compensator, rechargeable batteries with charger, prism set with pole, tripod, data storage/USB/Bluetooth interface, carrying case, calibration certificate, and all accessories complete.	1 No	1	
6	Providing and supplying an automatic self-leveling Auto-Level with minimum 32× magnification, ±2 mm/km accuracy, dual-axis compensator, tripod, 2.5 m leveling staff, carrying case, calibration certificate, and all accessories complete.	1 No	4	
7	Providing and supplying a high-performance workstation laptop with Intel Core i9-14900HX / AMD Ryzen 9 7940HX or higher, 64GB DDR5 RAM, 2TB NVMe Gen-5 M.2 SSD, dedicated NVIDIA RTX 4080 (12GB) or higher GPU, Windows 11 Pro, full-size keyboard with numeric pad, complete with premium laptop bag, wireless headphones (Sennheiser/Beats/Sony/Anker or equivalent), USB 3.2 Gen-2 (10Gbps) flash drive, and Logitech MX Master 3S wireless mouse or equivalent, complete in all respects.	1 No	2	

8	Providing installation, testing, and commissioning of a 64 kW Solar PV system capable of operating a horizontal centrifugal pump with discharge 10 cusec against 40 - 45 ft head , pump minimum 82% efficiency verified as per ISO 9906-1B standard, including Tier-1 Bloomberg-certified mono/ bi-facial N-type solar panels (JINKO / LONGI / JA / Canadian / AKCome / TW / Trina, 700+ W/panel, 23.5% efficiency), solar pump inverter INVT suitably rated for system capacity, mounted on 12 ft high L2/L3/L4 galvanized steel structure (14 gauge) with complete mechanical and civil works, DC and AC cabling using XLPE/PVC insulated tin-coated copper wires, combiner boxes, AC & DC breakers, SPDs (A+ grade), all distribution/protection boxes (12"x18"x18" SWG or equivalent), PVC pipes, flexible pipes (1–1.5"), thimbles (O-type, U-type with shrouds), Rawl bolts, nuts and bolts, complete earthing system, lightning arrestor, all civil works, foundations, and supports, electrical connections for net metering with meter, transportation of all materials from warehouse to site, testing, commissioning, and manufacturer-provided maintenance/after-sales service for 2 years, complete in all respects as directed by the Engineer-in-Charge.	1 No	6	
	Providing installation, testing, and commissioning of a 53.5 kW Solar PV system capable of running a horizontal centrifugal pump with discharge 10 cusec against 30–35 ft head, pump minimum 81% efficiency, including Tier-1 Bloomberg-certified mono / bi-facial N-type solar panels (JINKO / LONGI / JA / Canadian / AKCome / TW / Trina, 700+ W/panel, 23.5% efficiency), solar pump inverter INVT suitably rated for system capacity, mounted on 12 ft high L2/L3/L4 galvanized steel structure (14 gauge) with complete mechanical and civil works, DC and AC cabling with XLPE/PVC insulated tin-coated copper wires (DC 1-core 6 mm, AC 4-core 6 mm, 25 mm PVC/XLPE), combiner boxes, AC & DC breakers, SPDs (A+ grade), all distribution/protection boxes (12"x18"x18" SWG or equivalent), PVC pipes, flexible pipes (1–1.5"), thimbles (O-type, U-type with shrouds), Rawl bolts, nuts and bolts, complete earthing system, lightning arrestor, all civil works, foundations, supports, electrical connections for net metering with meter, transportation of all materials from warehouse to site, testing, commissioning, and manufacturer-provided maintenance/after-sales service for 2 years, complete in all respects as directed by the Engineer-in-Charge.	1 No	7	
	Providing installation, testing, and commissioning of a 107 kW Solar PV system for a horizontal centrifugal pump with discharge 20 cusec against 30 - 35 ft head, pump minimum 83% efficiency, including Tier-1 Bloomberg-certified mono/ bi-facial N-type solar panels (JINKO / LONGI / JA / Canadian / AKCome / TW / Trina, 700+ W/panel, 23.5% efficiency), solar pump inverter INVT suitably rated for system capacity, mounted on 12 ft high L2/L3/L4 galvanized steel structure (14 gauge) with complete mechanical and civil works, DC and AC cabling with XLPE/PVC insulated tin-coated copper wires (DC 1-core 6 mm, AC 4-core 6 mm, 25 mm PVC/XLPE), combiner boxes, AC & DC breakers, SPDs (A+ grade), all distribution/protection boxes (12"x18"x18" SWG or equivalent), PVC pipes, flexible pipes (1–1.5"), thimbles (O-type, U-type with shrouds), Rawl bolts, nuts and bolts, complete earthing system, lightning arrestor, all civil works, foundations, and supports, all electrical connections for net metering with meter, transportation of all materials from warehouse to site, testing, commissioning, and manufacturer-provided maintenance/after-sales service for up to 2 years, complete in all respects as directed by the Engineer-in-Charge.	1 No	1	
a	Surface water Monitoring for Construction Phase	Lump Sump		
b	Groundwater Monitoring for Construction Phase	Lump Sump		
c	Ambient Air Quality Monitoring for Construction Phase	Lump Sump		
a	Surface water MonitoringFor Operational Phase	Lump Sump		
b	Groundwater Monitoring For Operational Phase	Lump Sump		
a	Drinking Water Monitoring for Drinking Water & Groundwater Monitoring near disposal Pit	Lump Sump		
b	Groundwater Monitoring for Drinking Water & Groundwater Monitoring near disposal Pit	Lump Sump		
a	Training Session	Lump Sump	5.00	
13	Emergency Plan	Lump Sump	1.00	
14	Environmental Audit Cost	Lump Sump	3.00	
15	Site Visits by Regulatory Authorities	Lump Sump	1.00	
a	Sign Board for traffic management cost	Lump Sump	1.00	
b	Barricading Fence along Access Roads for traffic management cost	Lump Sump	1.00	
c	Temporary Speed Breakers for traffic management cost	Lump Sump	1.00	

d	Controlling Dust Pollution for traffic management cost	Lump Sump	1.00	
e	Relocation of amenities and localized widening of road and barrier for traffic management cost	Lump Sump	1.00	

[illegible]

	321.02	229.30		550.32	45.86	
		1,164.38		501.68		432.54
				180.37	48.10	180.37
97.50	97.50	97.50	97.50	97.50	97.50	97.50
	2,205.28	1,575.20		3,780.48	315.04	
39.00	39.00	39.00	39.00	39.00	39.00	39.00
	451.50	322.50		774.00	64.50	
81.70	81.70	81.70	81.70	81.70	81.70	81.70
230.65	230.65	230.65	230.65	230.65	230.65	230.65
230.65	230.65	230.65	230.65	230.65	230.65	230.65
	1,207.89	862.78		2,070.66	172.56	
		5,355.00		3,896.51		2,362.25
500.00	500.00	500.00	500.00	500.00	500.00	500.00
4.29	4.29	4.29	4.29	4.29	4.29	4.29
30.96	39.56	242.52	146.20	67.08	22.36	22.36
70.74	90.39	554.13	334.05	153.27	51.09	51.09
18.00	23.00	141.00	85.00	39.00	13.00	13.00
18.00	23.00	141.00	85.00	39.00	13.00	13.00
63.00	80.50	493.50	297.50	136.50	45.50	45.50
180.00	230.00	1,410.00	850.00	390.00	130.00	130.00
27.24	34.81	213.42	128.66	59.03	19.68	19.68

				960.00	360.00	600.00
	384	11823.77				

		3,265.60		91,276.02	36,435.20	29,517.98

	2,080.00	65,893.96		71,071.98	26,990.40	29,348.94
	4,515.81			44,509.40	16,212.10	35,906.24
	7,248.09	5,177.21		12,425.30	1,035.44	
		117,054.47		63,787.43		40,723.13
				9,601.88	2,524.50	9,331.88
	520.00	14,816.27		17,924.66	6,956.80	6,710.98

		16,160.05		9,101.68		5,753.34
				2,377.13	625.50	2,314.13
	1,063.04			10,355.41	3,788.50	7,756.14
		720.00		5,766.00	2,040.00	3,072.00
	442.23			4,481.06	1,615.53	4,212.61
				823.50	216.00	796.50
		9,852.05		5,073.31		3,296.24
	180.00					
		944.00		16,855.64	7,707.60	6,537.28
	6.00	30.00				
		6.00		60.00	22.50	31.50
	48.00	368.00				
				480.00	180.00	300.00
				480.00	180.00	300.00
				160.00	60.00	60.00

				960.00	360.00	600.00
				960.00	360.00	600.00
				960.00	360.00	600.00
	8,490.00	35,745.00		9,600.00	3,200.00	4,000.00

		126.72		1,383.84	489.60	737.28
		1,344.84		19,900.15	7,557.31	8,217.70
				585.60	219.60	366.00
				72.00	27.00	45.00
	3,936.00	5,976.00	4,140.00			
		2,100.00				
		2,100.00				
		2,800.00				
		304.64				
	(768.00)	(23,647.54)				
	1,417.95			17,227.97	6,436.05	12,395.41
	1,417.95			17,227.97	6,436.05	12,395.41

	17.00			187.00	68.00	187.00
--	-------	--	--	--------	-------	--------

--	--	--	--	--	--	--

	551.01			6,197.88	2,288.87	4,687.73
	40.00			440.00	160.00	440.00
	180.20			1,425.38	518.00	1,098.74
	50.00			450.00	160.00	380.00

	134.50			1,405.85	508.54	1,354.31
	14.96			164.56	59.84	164.56
	1,264.43			12,462.63	4,539.39	10,053.75
	93,240.00					

	126,000.00					
312.56	3,745.50	10,945.44		10,137.19	269.25	6,208.72
525.12	72,754.37	6,058.72		3,737.05	480.69	2,589.88
129.50	12,167.00	594.66		631.16	126.00	524.66
173.29	24,008.94	2,001.64		1,233.60	158.63	854.71
173.29	24,008.94	2,001.64		1,233.60	158.63	854.71
42.74	4,015.11	196.42		208.28	41.58	173.14
42.74	4,015.11	196.42		208.28	41.58	173.14
525.12	72,754.37	6,058.72		3,738.19	480.69	2,590.02
129.50	12,167.00	594.66		631.16	126.00	173.14
1,207.50	152,322.07	47,639.45		33,005.50	1,091.52	20,947.18
	3,814.24	2,724.46		6,538.70	544.89	
	3,559.50	2,542.50		6,102.00	508.50	

	840.00	600.00		1,440.00	120.00	
	1,050.00	750.00		1,800.00	150.00	
	2,036.30	1,454.50		3,490.80	290.90	
				-		
	1,079.16	770.83		1,849.99	154.17	
	128.85	92.04		220.89	18.41	

	224.00	160.00		384.00	32.00	
	280.00	200.00		480.00	40.00	
	343.00	245.00		588.00	49.00	
	668.94	477.81		1,146.75	95.56	
	696.94	497.81		1,194.75	99.56	
	286.56	204.69		491.25	40.94	
	342.56	244.69		587.25	48.94	

	3,978.14	2,841.53		6,819.66	568.31	
	801.64	572.60		1,374.24	114.52	
	3,429.13	2,449.38		5,878.50	489.88	
	91.00	65.00		156.00	13.00	
	14.00	10.00		24.00	2.00	
	7.00	5.00		12.00	1.00	
	3,571.89	2,551.35		6,123.24	510.27	

	623.00	445.00		1,068.00	89.00	
	2,344.71	1,674.79		4,019.50	334.96	
	420.00	300.00		720.00	60.00	
	210.00	150.00		360.00	30.00	
	105.00	75.00		180.00	15.00	
	1,260.00	900.00		2,160.00	180.00	
	420.00	300.00		720.00	60.00	
	280.00	200.00		480.00	40.00	
	7.00	5.00		12.00	1.00	
	7.00	5.00		12.00	1.00	

	7.00	5.00		12.00	1.00	
	140.00	100.00		240.00	20.00	
	28.00	20.00		48.00	4.00	
	14.00	10.00		24.00	2.00	
	7.00	5.00		12.00	1.00	
	7.00	5.00		12.00	1.00	
	42.00	30.00		72.00	6.00	
	14.00	10.00		24.00	2.00	
	7.00	5.00		12.00	1.00	
	21.00	15.00		61.00	3.00	5.00
	21.00	15.00		36.00	3.00	
	709.72	506.94		1,216.66	101.39	
	282.50	201.78		484.28	40.36	
	1,063.05	759.32		1,822.38	151.86	
	49.67	35.48		85.14	7.10	
		60,639.35		44,596.77		25,000.75
		60,639.35		44,596.77		25,000.75

--	--	--	--	--	--	--

		6,041.91		5,294.22		3,466.04
		1,758.15		997.54		648.78
		1,758.15		997.54		648.78
		144.00		111.00		46.00
		12.00		6.00		4.00
		6.00		6.00		4.00
		607.92		367.92		271.92
		196.00		176.00		176.00
		5,921.95		3,581.60		2,528.60

		356.00		336.00		168.00
		99.00		64.00		28.00
				71.86		
		1,368.00		368.00		184.00
		2,738.75		1,682.75		1,417.67
		738.42		418.97		272.49
		1,758.15		997.54		648.78
		112.84		72.10		53.42
		900.26		519.15		389.75
		473.50		236.66		173.29

		500.00		150.00		100.00
		300.00		150.00		100.00
		1,000.00		500.00		250.00
		500.00		300.00		200.00
		10.00		5.00		3.00
		50.00		35.00		20.00
		15.00		10.00		5.00
		15.00		10.00		5.00
		1.00		1.00		1.00
		10.00		5.00		2.00
		10.00		6.00		4.00
		15.00		10.00		5.00
				34,138.38		10,698.49
				34,138.38		10,698.49
				5,910.30		4,319.86
				1,100.00		700.00
				1,540.00		1,168.00
				376.75		239.75
				527.45		400.04
				264.00		186.80
				132.00		93.40
				14,140.76	3,514.66	12,209.00

				2,798.89	746.37	2,798.89
--	--	--	--	----------	--------	----------

--	--	--	--	--	--	--

				4,464.84	949.99	2,649.90

				1,674.74	444.85	1,661.64
				158.72	42.33	158.72
				2,688.53	706.86	2,612.93
				6,027.53	1,282.48	3,577.37

--	--	--	--	--	--	--

[illegible]

[illegible]

[illegible]

[illegible]

D-3 Drain	1-L of D-1 Drain	Jarewala Drain	New 1-L / Jarewala	Existing 1-L / Jarewala Drain	Link Channels of Jarewala	New 1-L / Jarewala
1,671,902.14	307,260.39	4,234,073.10	3,676,695.00	15,402.50	4,410,982.06	
		35,774.04		8,700.00		
6,208.72	148.50	967.13		2,700.32	967.13	967.13
1,638,852.06	392,780.15	1,712,983.98	4,402,362.50	51,770.00	1,949,662.13	
10,467.50		70,005.00	137,177.50	1,360.00	147,378.58	
23,965.00		29,937.50	898,790.00			
5,747.50	11,732.79				224,897.50	
					468,525.00	
			496,885.00			
					140,702.29	
			1,780,642.50	45,770.00		
	97,969.47					
159,193.80						
					910,707.78	
24,812.80	11,520.00	45,540.00				
28,000.00	8,000.00					
4,720.00	1,920.00					
130.00	30.00	260.00	170.00	40.00		
		1,272,300.00				
		5.00				
98.00	98.00	98.00	98.00	49.00	294.00	
24.50	24.50	24.50	24.50	12.25	73.50	
564.50	252.00	689.56	717.78	435.94		
1,785.03	458.78					
	105.61		528.06			
736.13			1,808.13			
1,730.87	695.08					
			200.62			

	45.86		229.30			
432.54			577.90			
180.37	72.15					
97.50	97.50	97.50	97.50	48.75	292.50	
	315.04		1,575.20			
39.00	39.00	39.00	39.00	19.50	117.00	
	64.50		322.50			
81.70	81.70	81.70	81.70	40.85	245.11	
230.65	230.65	230.65	230.65	115.33	691.95	
230.65	230.65	230.65	230.65	115.33	691.95	
	172.56		862.78			
2,362.25			6,169.19			
500.00	500.00	500.00	500.00	250.00	1,500.00	
4.29	4.29	4.29	4.29	2.15	12.87	
22.36	5.16	44.72	29.24	6.88	20.64	
51.09	11.79	102.18	66.81	15.72	47.16	
13.00	3.00	26.00	17.00	4.00	12.00	
13.00	3.00	26.00	17.00	4.00	12.00	
45.50	10.50	91.00	59.50	14.00	42.00	
130.00	30.00	260.00	170.00	40.00	120.00	
19.68	4.54	39.35	25.73	6.05	18.16	
		245.00				
		367.50				
		560.00				

		323.40				
		1,019.82		803.25		
		1,155.00				
600.00						
		825.50				

21,204.33	11,161.16	5,932.14	42,881.70	6,543.01		

22,179.12	10,673.28	33,901.50	27,833.97	20,607.39		
45,010.33	9,117.49					
	1,035.44		5,177.21			
40,760.53			129,118.01			
9,331.88	3,786.75					
5,135.04	2,549.76	7,356.22	5,287.91	4,517.97		

5,794.46			18,946.31			
2,314.13	938.25					
9,694.24	1,761.11					
2,258.00	1,008.00	3,429.92	3,478.20	1,972.18		
5,309.21	1,278.05					
796.50	324.00					
3,263.43			9,746.58			
		51.34				
4,909.28	2,884.80	3,165.04	2,449.60	2,183.81		
		6.00	12.00	6.00		
22.50	13.50					
		112.00				
350.00		825.00				
350.00		825.00				
100.00		200.00				

700.00		1,650.00				
700.00		1,650.00				
700.00		1,650.00				
6,400.00		45,540.00				

541.92	241.92	151.68				
6,210.15	2,988.52	1,661.15				
427.00						
52.50						
		59.40		143.55		
		(2,476.50)				
		(1,019.82)		(803.25)		
15,395.30	1,949.33					
15,395.30	1,949.33					

238.00	68.00					
--------	-------	--	--	--	--	--

--	--	--	--	--	--	--

5,822.75	986.24					
560.00	160.00					
1,373.78	213.58					
470.00	90.00					

1,713.62	440.43					
209.44	59.84					
12,602.89	2,552.90					

6,208.72	148.50	967.13	5,141.14	2,700.32	967.13	967.13
3,457.11	422.73	614.72		785.33	614.72	594.53
524.66	126.00	96.00		136.00	96.00	96.00
1,140.89	139.50	202.86	812.42	259.16	202.86	196.20
1,140.89	139.50	202.86	812.42	259.16	202.86	196.20
173.14	41.58	31.68	147.40	54.33	31.68	31.68
173.14	41.58	31.68	147.40	54.33	31.68	31.68
3,457.25	422.73	614.72	2,461.88	785.33	614.72	594.53
173.14	126.00	96.00	446.68	164.64	96.00	96.00
21,997.20	858.95	11,198.25	36,777.20	10,655.63	11,198.25	5,817.78
		1,267.50			1,267.50	
		507.94		803.25	507.94	
	544.89		2,724.46			
	508.50		2,542.50			

	120.00		600.00			
	150.00		750.00			
	290.90		1,454.50			
			-			
	154.17		770.83			
	18.41		92.04			

	32.00		160.00			
	40.00		200.00			
	49.00		245.00			
	95.56		477.81			
	99.56		497.81			
	40.94		204.69			
	48.94		244.69			

	568.31		2,841.53			
	114.52		572.60			
	489.88		2,449.38			
	13.00		65.00			
	2.00		10.00			
	1.00		5.00			
	510.27		2,551.35			

	89.00		445.00			
	334.96		1,674.79			
	60.00		300.00			
	30.00		150.00			
	15.00		75.00			
	180.00		900.00			
	60.00		300.00			
	40.00		200.00			
	1.00		5.00			
	1.00		5.00			

	1.00		5.00			
	20.00		100.00			
	4.00		20.00			
	2.00		10.00			
	1.00		5.00			
	1.00		5.00			
	6.00		30.00			
	2.00		10.00			
	1.00		5.00			
5.00	3.00	15.00	15.00			
	3.00		15.00			
	101.39		506.94			
	40.36		201.78			
	151.86		759.32			
	7.10		35.48			
21,403.79			125,135.85			
21,403.79			125,135.85			

--	--	--	--	--	--	--

3,489.50			9,774.58			
648.78			1,394.28			
648.78			1,394.28			
46.00			282.00			
4.00			12.00			
4.00			6.00			
271.92			463.92			
176.00			184.00			
2,528.60			4,838.90			

168.00			344.00			
28.00			150.00			
			40.00			
184.00			696.00			
1,417.67			2,220.23			
272.49			585.60			
648.78			1,394.28			
53.42			93.35			
389.75			723.40			
176.57			312.94			

100.00			350.00			
100.00			250.00			
250.00			1,000.00			
200.00			500.00			
3.00			10.00			
20.00			50.00			
5.00			15.00			
5.00			15.00			
1.00			1.00			
2.00			10.00			
4.00			10.00			
5.00			15.00			
14,034.93						
14,034.93						
4,319.86						
700.00						
1,168.00						
239.75						
400.04						
186.80						
93.40						
11,890.33	4,728.65					

2,798.89	1,119.56					
----------	----------	--	--	--	--	--

--	--	--	--	--	--	--

2,331.23	881.65					

1,661.64	667.28					
158.72	63.49					
2,612.93	1,060.29					
3,147.16	1,190.22					

--	--	--	--	--	--	--

[illegible]

[illegible]

[illegible]

[illegible]

Add QTY	Total QTY	
	69,294,444.52	2,528,567.51
	44,474.04	
967.13	436,325.40	
	26,864,727.17	
	-	
	546,147.50	
	989,635.00	
	275,885.29	
	62,477.50	
	549,295.00	
	555,572.50	
	18,740.00	
	53,390.00	
	75,040.00	
	98,265.75	
	187,560.00	
	54,772.50	
	125,720.00	
	70,367.50	
	4,869.33	
	-	
	140,702.29	
	1,887,045.50	
	97,969.47	
	159,193.80	
	910,707.78	
	199,832.80	
	94,000.00	
	17,520.00	
	118,400.00	
	1,254.00	
	1,740.00	
	6,885,050.00	
	5.00	
	1,617.00	
	-	3,907.66 - 23,362,466.85
	404.25	
	5,945.78	
	6,046.00	
	3,907.66	
	6,337.46	
	6,364.73	
	11,548.92	
	515.75	
	4,852.36	

	1,696.82	1,696.82	-	
	3,109.02			69,970,747
	661.34			
	1,780.19			
	1,608.75			
	11,656.48	11,656.48	-	
	44,360.68			
	745.65			
	643.50			
	2,386.50	2,386.50	-	
	8,834.11			
	427.50			
	1,348.10			
	3,805.73			
	3,805.73			
	6,384.54	6,384.54	-	
	20,145.20			
	31,339.95			
	8,250.00			
	-			
	70.79			
	786.04			
	1,796.01			
	457.00			
	457.00			
	1,599.50			
	4,570.00			
	-			
	691.72			
	245.00			
	367.50			
	560.00			

	323.40
	1,823.07
	1,155.00
	3,480.00
	13,340.27

	254,623.26
	-

	324,573.79	
	161,380.35	
	38,311.34	
	391,443.57	
	34,576.88	
	65,173.29	
	-	
	74,831.73	

	55,755.85	
	8,569.13	
	35,685.35	
	25,188.30	
	18,108.10	
	2,956.50	
	31,231.61	
	421.34	
	50,376.82	
	24.00	
	48.00	
	169.50	
	624.00	
	2,615.00	
	2,615.00	
	700.00	

	-
	5,230.00
	5,230.00
	5,230.00
	123,165.00

	-
	4,019.52
	51,240.03
	2,183.80
	268.50
	15,594.50
	2,100.00
	2,100.00
	2,800.00
	304.64
	202.95
	(26,974.04)
	(1,823.07)
	56,689.66
	56,689.66
	-

	799.00
--	--------

	-
--	---

	21,285.75
	1,880.00
	4,999.18
	1,670.00

523,927,353.66

208,561,226.00

-

315,366,127.66

-

315,366,127.66

-

318,400,148.15

16,414,641.53

109345724

	1,184.00
	1,480.00
	1,813.00
	3,535.81
	3,683.81
	1,514.69
	1,810.69
	-

1,184.00	-
1,480.00	-
1,813.00	-
3,535.81	-
3,683.81	-
1,514.69	-
1,810.69	-
-	-

	21,027.29
	4,237.24
	18,125.38
	481.00
	74.00
	37.00
	18,879.99

21,027.29	-
4,237.24	-
18,125.38	-
481.00	-
74.00	-
37.00	-
18,879.99	-

	3,293.00
	12,393.47
	-
	2,220.00
	1,110.00
	555.00
	-
	6,660.00
	2,220.00
	1,480.00
	-
	37.00
	37.00

3,293.00	-
12,393.47	-
-	-
2,220.00	-
1,110.00	-
555.00	-
-	-
6,660.00	-
2,220.00	-
1,480.00	-
-	-
37.00	-
37.00	-

	37.00
	740.00
	148.00
	74.00
	37.00
	37.00
	37.00
	222.00
	74.00
	37.00
6.00	707.00
	111.00
	-
	3,751.35
	1,493.20
	5,619.00
	262.52
	276,776.51
	276,776.51

37.00	-
740.00	-
148.00	-
74.00	-
37.00	-
37.00	-
37.00	-
222.00	-
74.00	-
37.00	-
167.00	#REF!
111.00	-
-	-
3,751.35	-
1,493.20	-
5,619.00	-
262.52	-

26,344,735.31	63,826,446.62
	36,383,456.57

	-
--	---

	28,066.25
	5,447.53
	5,447.53
	629.00
	38.00
	26.00
	1,983.60
	908.00
	19,399.65

	1,372.00
	369.00
	111.86
	2,800.00
	9,477.06
	2,287.97
	5,447.53
	385.13
	2,922.31
	1,372.96
	-

	1,200.00
	900.00
	-
	3,000.00
	1,700.00
	-
	31.00
	175.00
	50.00
	50.00
	5.00
	29.00
	34.00
	50.00
	-
	58,871.79
	58,871.79
	14,550.01
	-
	2,500.00
	3,876.00
	-
	856.25
	1,327.53
	637.60
	318.80
	46,483.39
	-

9,611,716.48

31715324

22,103,607.52

	10,262.59
--	-----------

	-
--	---

	11,277.60

	-
	6,110.14
	581.98
	9,681.53
	15,224.76
	72,531.66
	88,776.19
	-

115,067,561.50

	8,771.49
	31,674.37
	47,794.11
	21,724.43

	3,276.00
--	----------

	3,822.00
	3,822.00
	33,854.84
	34,218.84
	7,420.14
	9,109.10
	22,325.37
	14,054.04
	22,750.00
	-

	113,184.66
	21,116.55
	99,928.24
	65,280.22
	1,183.00
	182.00
	91.00
	182.00
	7,644.00
	91.00
	273.00
	364.00
	91.00
	9,100.00
	364.00
	364.00

	-
	9,100.00
	4,550.00
	91.00
	91.00
	-
	91.00
	91.00
	91.00
	91.00
	-
	9,100.00
	4,550.00
	-
	27,300.00
	9,100.00
	18,200.00
	-
	182.00
	364.00
	91.00
	3,185.00
	546.00
	546.00
	182.00
	182.00
	91.00
	91.00
	579.00
	91.00

	91.00
	91.00
	546.00
	91.00
	-
	11,086.97
	1,566.57
	19,117.50
	971.75
	25.00
	700.00
	820.00
	1,760.00
	1,500.00
	1,200.00
	2,350.00
	1,000.00
	700.00
	500.00
	500.00
	200.00
	150.00
	1,870.00
	58,200.00
	2.00
	5.00
	5.00
	40.00
	60.00
	500.00
	183.00
	50.00
	50.00
	500.00
	200.00
	200.00
	200.00
	5,000.00
	50.00
	10.00
	20.00
	80.00
	-
	-
	-
	-
	-
	-
	2.00

115,067,561.50

99163570
40,761,205.00

223475597
13,826,383.00

14594316

	2.00
	7.00
	27.00
	7.00
	28.00
	6.00
	6.00
	12.00
	33.00
	3,390.00
	9.00
	65.00
	30.00
	14.00
	58.00
	420.00
	1,300.00
	9.00
	15.00
	49,390.00
	2,062.98

767,933.00

237526980

3629203

241156183

601627

	1,656.56
	6,225.47
	6,650.00
	14,250.00
	28,500.00
	37.00

53,321,817.18

	8.00
	6.00
	1.00

	8.00
	3.00
	1.00
	1.00
	8,140.00
	1,628.00
	37.00
	2,590.00
	74.00
	4,440.00
	740.00
	370.00
	148.00
	6,520.88
	2,664.00

	1,850.00
	118,400.00

	14,800.00
	555.00
	87.00
	1.00
	1.00
	1.00
	4.00
	2.00

111,056,413.01

	6.00
	7.00
	1.00
	-
	-
	-
	-
	-
	-
	-
	-
	5.00
	1.00
	3.00
	1.00
	1.00
	1.00
	1.00
	1.00


	1.00
	1.00

9,000,000.00


16069459
4726644
11342815
3629203
623

-









- 3,034,020.49

101544.2	40000	141544.2
134924	40000	174924
207719.6	40000	247719.6
274993.6	156780	431773.6
141014	40000	181014
301093.6	156780	457873.6
143304	40000	183304
1426668.4	156780	1583448
		3629203