

Exp No: 6

ARDUINO TO 16x2 LCD DISPLAY USING PROTEUS

PROGRAM:

Arduino to 16x2 LCD Display using Proteus

```
#include <LiquidCrystal.h>
```

```
LiquidCrystal lcd (7, 8, 9, 10, 11, 12);
```

```
// your PWM numbers may be different
```

```
void setup()
```

```
{ lcd.begin(16, 2);
```

```
lcd.print("put your message here");
```

```
}
```

```
void loop () {
```

```
for (int i=0; i<13; i++)
```

```
}
```

```
lcd.scrollDisplayLeft();
```

```
delay(700);
```

```
}
```

```
}
```

The screenshot shows the Proteus 8 Professional Schematic Capture window. The main workspace displays a schematic diagram of an Arduino Uno R3 microcontroller board connected to an LCD1601 module. The Arduino board is labeled 'ARD1' and 'ARDUINO UNO R3'. The LCD module is labeled 'LCD1' and 'LM016L'. The LCD screen displays the text 'ello world!'. The connection between the two components is made using I2C: the Arduino's A4 pin is connected to the LCD's SDA pin, and the Arduino's A5 pin is connected to the LCD's SCL pin. The Proteus 8 Professional interface is visible, including the top menu bar, the left-hand toolbar, and the bottom status bar.

