



SQLite Left Join

Summary: in this tutorial, you will learn how to use SQLite `LEFT JOIN` clause to query data from multiple tables.

Introduction to SQLite LEFT JOIN clause

Similar to the [INNER JOIN](https://www.sqlitetutorial.net/sqlite-inner-join/) (<https://www.sqlitetutorial.net/sqlite-inner-join/>) clause, the `LEFT JOIN` clause is an optional clause of the [SELECT](https://www.sqlitetutorial.net/sqlite-select/) (<https://www.sqlitetutorial.net/sqlite-select/>) statement. You use the `LEFT JOIN` clause to query data from multiple related tables.

Suppose we have two tables: A and B.

A has m and f columns.

B has n and f columns.

To perform join between A and B using `LEFT JOIN` clause, you use the following statement:

```
SELECT
    a,
    b
FROM
    A
LEFT JOIN B ON A.f = B.f
WHERE search_condition;
```

The expression `A.f = B.f` is a conditional expression. Besides the equality (=) operator, you can use other comparison operators such as greater than (>), less than (<), etc.


The statement returns a result set that includes:

1. Rows in table A (left table) that have corresponding rows in table B.
2. Rows in the table A table and the rows in the table B filled with NULL values in case the row from table A does not have any corresponding rows in table B.

In other words, all rows in table A are included in the result set whether there are matching rows in table B or not.

In case you have a [WHERE](https://www.sqlitetutorial.net/sqlite-where/) clause in the statement, the `search_condition` in the `WHERE` clause is applied after the matching of the `LEFT JOIN` clause completes.


See the following illustration of the `LEFT JOIN` clause between the A and B tables.



All rows in the table A are included in the result set.

Because the second row (a2, 2) does not have a corresponding row in table B, the `LEFT JOIN` clause creates a *fake row* filled with `NULL`.


The following Venn Diagram illustrates the `LEFT JOIN` clause.



It is noted that `LEFT OUTER JOIN` is the same as `LEFT JOIN`.

SQLite LEFT JOIN examples

We will use the `artists` and `albums` tables in the [sample database](https://www.sqlitetutorial.net/sqlite-sample-database/) (<https://www.sqlitetutorial.net/sqlite-sample-database/>) for demonstration.



One album belongs to one artist. However, one artist may have zero or more albums.

To find artists who do not have any albums by using the `LEFT JOIN` clause, we select artists and their corresponding albums. If an artist does not have any albums, the value of the `AlbumId` column is `NULL`.

To display the artists who do not have any albums first, we have two choices:

First, use `ORDER BY` (<https://www.sqlitetutorial.net/sqlite-order-by/>) clause to list the rows whose `AlbumId` is `NULL` values first.

Second, use `WHERE` (<https://www.sqlitetutorial.net/sqlite-where/>) clause and `IS NULL` (<https://www.sqlitetutorial.net/sqlite-is-null/>) operator to list only artists who do not have any albums.

The following statement uses the `LEFT JOIN` clause with the `ORDER BY` clause.

```
SELECT
    artists.ArtistId,
    AlbumId
FROM
    artists
LEFT JOIN albums ON
    albums.ArtistId = artists.ArtistId
ORDER BY
    AlbumId;
```

The following statement uses the `LEFT JOIN` clause with the [WHERE](https://www.sqlitetutorial.net/sqlite-where/) [\(https://www.sqlitetutorial.net/sqlite-where/\)](https://www.sqlitetutorial.net/sqlite-where/) clause.

```
SELECT
    artists.ArtistId
    , AlbumId
FROM
    artists
LEFT JOIN albums ON
    albums.ArtistId = artists.ArtistId
WHERE
    AlbumId IS NULL;
```

In this tutorial, you have learned how to use SQLite `LEFT JOIN` clause to query data from multiple tables.

Copyright © 2020 [SQLite Tutorial](https://www.sqlitetutorial.net/). All Rights Reserved.