AZENTIO HACKATHON · DIGITAL FRAUD INVESTIGATION SYSTEM

FinShield

Fraud investigation you can defend: deterministic rules decide, a learned model advises, three AI agents explain and suggest, and the analyst owns every decision.

93%
of 56 planted fraud incidents caught at Medium or High on held-out data

0%
of 48 legitimate lookalikes raised to High

0.78 → 0.95
ranking quality after learning rule weights (3 unseen datasets)

399
automated tests passing on the submitted code

Level 1 · detect, score, explain, case queue | Level 2 · correlate, network, consolidate, investigate, audit | All data is synthetic

EXECUTIVE SUMMARY

A system an auditor can read, not a model they have to trust

Rules decide

23 active risk indicators and 6 mitigations, weighted in one versioned file, produce every score and band. Same data and same rules always give the same alerts.

ML advises

A sign-constrained model learned from labelled scenarios re-weighs the rule evidence. It is shown beside the score and never sets a band or a case.

Agents explain

Pattern Scout, Ask FinShield and Reviewer memory suggest and explain. Every ID they cite is checked against the data. They work with the LLM off.

Humans decide

Eight analyst actions, each with a reviewer and a reason. Holds are recommendations. Alerts are immutable; every correction is appended.

What it covers

- **Level 1.** Ingest CSV/Excel/JSON with validation; detect 13 fraud scenarios, including the four required; score 0–100 with named contributions; dashboard, filters, case queue.
- **Level 2.** Cross-system correlation (loan → payout → mule → insurance claim), relationship network, consolidated investigations with split, analyst workspace, audit trail, report, prioritisation.


Why it reads as production-minded

- One evidence chain from file row to case report; every number traces to record IDs.
- Failure modes designed in: LLM outage, hallucinated IDs, double counting, rule drift, hub false links.
- Honest evaluation on seeds we never tuned on, including what we miss.



Source: one evidence chain: every step keeps the record IDs behind it

One deterministic path, with advisory layers kept outside it



Source: backend/app (ingest, features, detect, score, graph, api, ai), evals/

Explainable first

Who may decide what

The central design rule: every component has a clearly bounded power. Anything probabilistic or generative sits on the advisory side of the line.


Capability	Rules engine	ML shadow	AI agents	Analyst
Set the risk score and band	**Decides**	Shown beside it	No	Reclassify only; original band kept
Open a case from an alert	**Decides (Medium/High)**	No	No	No
Group alerts into one investigation	**Proposes, with the reason**	No	No	Can split; split is pinned
Change case status, record a decision	No	No	No	**Decides, with reviewer + note**
Touch an account or payment	No	No	No	Recommends only; nothing executed
Write to the audit trail	System events	No	AI assessment, only when saved by the analyst, labelled	**Decisions, actions, corrections**
Propose a new rule	No	No	Pattern Scout suggests	Approve / dismiss recorded; rules unchanged

Proof, not promise. A test runs the full golden set with and without the ML model installed and asserts that rule scores, bands and categories are identical. The golden scorecard (34/34) is byte-identical after the ML step.

Source: backend/app/api/cases.py (ACTIONS), backend/tests/test_ml_shadow.py, evals/reports/golden_scorecard.md


Level 1

Same engine, opposite verdicts, and it shows why



Account takeover · High 85

6 failed logins, success from a never-seen device, a large transfer. Corroborated, so mitigations are suspended.



Family tablet · Low 18

Three customers share one device (+45) but share surname and address, so the household mitigation applies (−27).

How a score is built

1. **Signals.** Each indicator fires with a weight and a strength, and lists its record IDs.
2. **No double counting.** Rules that measure the same fact form a family; only the strongest counts.
3. **Noisy-OR.** risk = 1 − ∏(1 − w·s). No weight reaches 0.70, so no single indicator is High alone.
4. **Mitigations.** Known payee, tenure, recurrence, household, own-account lower risk, and switch off when a login attack is active.
5. **Chain floors.** Ordered attack patterns lift the score: takeover 85 / 70 / 55 (capped below High), loan-to-mule 80.
6. **Bands.** Medium ≥ 40, High ≥ 70. Contributions add up exactly to the score.

Source: backend/app/score/scoring.py, backend/app/detect/rules.yaml, evals/reports/golden_scorecard.md

Level 2

From four loose records to one defensible investigation

1 Records

3 loan applications on device **DEV-RING** with one phone; payout to **A-C011**; outflows to MULE-0/1/2; claims **CLM-1**, **CLM-2** paid into A-C011.

2 Indicators

Shared-device applications, phone reuse, loan-to-mule cash-out. Four alerts, each with named contributions and record IDs.

3 Linked group


Customers joined only by device, phone, email or payout account. Reason stored: *device DEV-RING and phone 9000000001 shared by C010–C013*.

4 One case


CASE-7085d89848, High, priority 87, evidence strong. Why grouped is shown; any alert can be split out.

5 Decision + record

Reviewer + note for each action. Hold is a recommendation. AI assessments are labelled and rejectable. Report downloads as JSON or Markdown.



Network around C011: every edge is a shared identifier, and hovering shows the record IDs that prove it.



Case workspace: why these alerts are grouped, split, eight analyst actions with a reviewer and note, report download.

Source: live demo dataset, case CASE-7085d89848; backend/app/graph, backend/app/api/cases.py

Trained models


Trained models calibrate the weights; they do not replace the rules

What was trained, and on what

- **Features.** Per scoring unit: each rule's evidence (weight × strength) plus whether an attack-chain floor applied. **Primary parameters** are the risk indicators; **derived parameters** are the mitigations and the chain floor.
- **Labels.** Planted incidents in a seeded synthetic generator, with labelled lookalikes.
- **Model A (selected).** Logistic regression with sign bounds (risk ≥ 0, mitigation ≤ 0) and a pull toward the hand weights. Output: a multiplier per rule.
- **Model B (rejected).** Gradient-boosted trees with monotonic constraints, explained by permutation importance. Higher recall but lookalike false positives rose to 25% at Medium+ (8% at High).
- **Protocol.** Train on pooled seeds 2, 6, 7 (3,097 units, 512 fraud); test on unseen seeds 4, 5, 8 at matched alert volume; 50 bootstrap resamples by incident for 90% intervals.

Unseen datasets, mean of 3	Hand	Learned
Ranking quality (average precision)	0.78	**0.95**
Precision of Medium+ alerts	76%	**88%**
Background false alarms	35	**17**
Lookalikes wrongly at Medium+	10%	**8%**
Fraud caught at Medium+ (unchanged)	89%	89%

What the model says about our hand weights



Dot = learned multiplier on the hand weight; whisker = 90% bootstrap interval. Known-payee, tenure, new-payee and amount rules deserve more weight; network convergence (NW-01) deserves much less. The rare rules stay near 1.0: not enough evidence to move them.

Shadow first, promote on evidence. The learned score runs on every alert and is labelled comparison-only. It earns promotion to the official score only after analyst feedback confirms it on real data.

Source: evals/reports/ml_stability.md, learned_weights.md; backend/app/detect/ml.py, ml_model.json (rules version d88c05508daf). Unit-level metrics on synthetic data.

AI that assists the system and the analyst, and never decides

Assists the **system**

Pattern Scout

Finds linked behaviour that no rule alerted on: customers sharing a device, phone or payout account with no Medium/High alert; several customers starting to pay the same new account.

- Deterministic mining finds candidates and their record IDs.
- The LLM only words a hypothesis (with an innocent explanation) and a suggested rule.
- Approve / dismiss needs a note; approving never changes a rule or score. Decisions survive re-scans.

Assists the **analyst and evaluator**

Ask FinShield

Answers questions about what is on screen: why a case is High, what links these customers, what to verify first.

- The browser sends only the route and IDs; the backend loads the data from the store.
- Every cited ID must exist in that data, otherwise it is dropped and shown as dropped.
- Record text is data, never instructions. Context is bounded in size.
- An answer can be saved to the case as a labelled AI assessment, and rejected later.

Assists **continuity**

Reviewer memory

Brings earlier reviewers' decisions, actions and notes on this case, and on cases sharing its customer or account, into the investigation.

- Reads the append-only case history; nothing is rewritten.
- Shown as "What earlier reviewers found" and passed to Ask FinShield as context.
- System events are excluded; only human and AI-labelled entries count.

1 · Screen
Browser sends the route and IDs only

›

2 · Load
Backend reads the data from the store

›

3 · LLM
Words an answer or hypothesis; no tools, no writes

›

4 · Check
Every cited ID must exist; others are dropped

›

5 · Label
Marked AI-generated; saved only by the analyst

›

6 · Review
Analyst accepts, rejects or ignores; rules and scores untouched

Shared guardrails Never decide · Real IDs only · Data, not orders · Labelled and rejectable · Works with AI off

Model: openai/gpt-oss-120b on Groq (GROQ_MODEL). The ML shadow score is a classifier, not an agent.

Source: backend/app/graph/scout.py, backend/app/ai/assistant.py, backend/app/graph/store.py

Built and measured today, and the production path we would take

Built and measured

- **6× faster detection** with identical output: 123 s → 19 s on 17k transactions and 11k logins, by removing quadratic hot spots (binary-search windows, sorted per-customer history).
- **Idempotent runs.** Run ID is derived from data and rules; re-running the same inputs reuses the stored run with no new rows.
- **Stable incident keys.** A case follows the same incident across runs; pinned splits are never undone.
- **Rules as versioned config.** One file, hashed to a version; a change creates a new version and old alerts stay as history.
- **Separable stages.** Signal collection and scoring are separate functions, so variants can be re-scored without recomputation.
- **State in the database.** Pagination on lists; storage chosen by DATABASE_URL (SQLite or Postgres); alerts and audit events locked by database triggers.
- **Bounded graph and AI cost.** Hub nodes capped; assistant context capped; LLM calls time-limited with a deterministic fallback.

Production path (designed, not built)

- **Storage.** Postgres URLs and immutability triggers are already supported; next: validate at volume and add indexes on entity and time.
- **Workers.** Run detection as background jobs per tenant and per window instead of in the request.
- **Streaming.** Incremental ingestion with windowed re-scoring for real-time alerts.
- **Identity.** Login, roles and four-eyes approval before any account-affecting action is allowed.
- **Feedback loop.** Analyst outcomes retrain the shadow model; approved Pattern Scout suggestions become tested rules through a rule editor.
- **Observability.** Per-stage timings, alert-volume and drift dashboards.

Not yet tested: Postgres under load, multi-user concurrency, or volumes beyond the synthetic sets.

Source: git history (perf commit d666d6a), backend/app/api/alert_store.py, backend/app/config.py, backend/app/detect/config.py

Enterprise controls

Failure modes we designed for, and where to check each one

Risk	Mitigation	Where
LLM invents an entity or ID	Citations checked against the loaded data; unverifiable IDs dropped and shown	`ai/assistant.py`
Instructions hidden in record text	Record text passed as data; model has no tools and no write path	`ai/assistant.py`
LLM is down or slow	Time-limited calls; templates and quoted evidence take over	`graph/scout.py`
Model overreach	ML shadow only; test asserts identical rule output with and without it	`tests/test_ml_shadow.py`
Double counting one fact	Indicator families: only the strongest counts	`score/scoring.py`
False links from popular IDs	Hub cap; only device, phone, email, payout account group customers	`graph/builder.py`
Rule drift hides history	Rules hashed to a version; old alerts stay as snapshots	`detect/config.py`
Wrongful account action	Hold and verification are recorded recommendations, not executed	`api/cases.py`
Re-run undoes an analyst split	Split incidents are pinned across runs	`api/cases.py`
Mixed currencies summed	Exposure kept per currency, never added across	`graph/priority.py`
Weak evidence ranked first	Single-fact cases capped below top and labelled needs review	`graph/priority.py`
Tuning on the data we report	Reported on seeds never used for tuning	`evals/`

Source: backend/app (paths shown), evals/reports


Measured on held-out synthetic data we did not tune on

93%
of 56 fraud incidents caught at Medium+

57%
caught at High

0%
of 48 lookalikes at High (8% at Medium)

100%
recall on 16 brand-new customers



Read these numbers honestly

- Synthetic data with planted, labelled scenarios. It measures the rules against what we can simulate, not real-world fraud rates.
- **Open gap:** slow drain (small amounts over a long time) stays below Medium: 0 of 4.
- All 4 lookalike false positives are one scenario, loan_paid_to_supplier: 4 of 4 reach Medium, none reach High.
- Held-out workload: 9.5 Medium/High alerts per 1,000 events; 36 background false alarms.
- Precision of Medium/High alerts is 50% on this held-out set, counted per alert. The learned-weights table counts per scoring unit on three other seeds (76% to 88%), so the two are not directly comparable.
- 34 of 34 hand-built calibration scenarios behave as designed; 399 backend tests pass.

Source: evals/reports/d3_heldout.md (seed 3), golden_scorecard.md, ml_stability.md. Rules version d88c05508daf.

Honest limits

What we did not claim, and what comes next

Limits today

- Synthetic data only; metrics are on simulated scenarios, not production fraud rates.
- Reviewer identity is a typed name; no login or role-based approval yet.
- Slow-drain fraud is not caught at Medium.
- Hold and verification are recommendations; no payment system is connected.
- AI wording depends on the LLM service; when off, the app falls back to quoted evidence.
- Learned weights are calibrated on synthetic scenarios and shown only as a shadow score.

Next steps

- Analyst feedback (confirmed fraud / false positive) retrains the shadow model; promote it only on real-data evidence.
- Login, roles and four-eyes approval for account-affecting actions.
- Streaming ingestion and windowed re-scoring.
- Approved Pattern Scout suggestions become tested rules through the rule editor.
- Long-window indicators for slow-drain and collusion patterns.

VERIFY IT YOURSELF

Reproducible

Run it, click it, check the numbers

Run

```
python -m venv .venv
.venv/Scripts/python -m pip install -r backend/requirements.txt
./run.ps1                       # backend on :8000
cd frontend && npm run dev    # UI on :5173
# UI: Data sources → Load demo dataset → Run detection

cd backend && ../.venv/Scripts/python -m pytest -q    # 399 tests
```

Demo click path

1. **Overview.** Filter, open *T-C002-ATO* (High 85); include Low and open *DEV-HOME* (Low 18).
2. **Cases.** Open *CASE-7085d89848*: why grouped, priority factors, split, actions, report download.
3. **Network.** View network, click *DEV-RING* and *A-C011*; Run Pattern Scout; approve one with a note.
4. **Ask FinShield.** "What links these customers?"; save to the case as an AI assessment.

Where each claim is evidenced

Held-out detection results	`evals/reports/d3_heldout.md`
34 calibration scenarios	`evals/reports/golden_scorecard.md`
Learned weights, intervals	`evals/reports/ml_stability.md`
Rule weights and floors	`backend/app/detect/rules.yaml`
Scoring logic	`backend/app/score/scoring.py`
Relationship graph	`backend/app/graph/builder.py`
Case actions, split, report	`backend/app/api/cases.py`
Agents	`graph/scout.py · ai/assistant.py`
Trust boundary test	`backend/tests/test_ml_shadow.py`

Demo data is synthetic and shipped with the repo. Reviewer names are typed text until login exists.