

```

#include <stdio.h>

#include <stdlib.h>

typedef struct node {
    int data;
    struct node *prev, *next;
} node;

node* create() {
    node *head = NULL, *p, *q = NULL;
    int i, n;
    printf("Enter number of nodes:\n");
    scanf("%d", &n);
    printf("Enter data:\n");
    for (i = 0; i < n; i++) {
        p = (node*)malloc(sizeof(node));
        scanf("%d", &p->data);
        p->next = NULL;
        p->prev = q;
        if (head == NULL) {
            head = p;
        } else {
            q->next = p;
        }
        q = p;
    }
    return head;
}

void display(node* head) {
    node* p;
    if (head == NULL) {
        printf("List is empty\n");
        return;
    }

```

```

    }

    printf("Elements in the list:\n");

    for (p = head; p != NULL; p = p->next) {
        printf("%d\t", p->data);
    }

    printf("\n");
}

node* insert_front(node* head, int x) {
    node* p = (node*)malloc(sizeof(node));

    p->data = x;

    p->prev = NULL;

    p->next = head;

    if (head != NULL)
        head->prev = p;

    return p;
}

node* insert_rear(node* head, int x) {
    node *p = (node*)malloc(sizeof(node)), *q;

    p->data = x;

    p->next = NULL;

    if (head == NULL) {
        p->prev = NULL;

        return p;
    }

    q = head;

    while (q->next != NULL)
        q = q->next;

    q->next = p;

```

```
p->prev = q;  
return head;  
}
```

```
node* delete_front(node* head) {  
    if (head == NULL) {  
        printf("List is empty\n");  
        return head;  
    }  
    printf("Item deleted: %d\n", head->data);  
    node* temp = head;  
    head = head->next;  
    if (head != NULL)  
        head->prev = NULL;  
    free(temp);  
    return head;  
}
```

```
node* delete_rear(node* head) {  
    if (head == NULL) {  
        printf("List is empty\n");  
        return head;  
    }  
    node* p = head;  
    if (p->next == NULL) {  
        printf("Item deleted: %d\n", p->data);  
        free(p);  
        return NULL;  
    }  
    while (p->next != NULL)  
        p = p->next;
```

```
    printf("Item deleted: %d\n", p->data);  
    p->prev->next = NULL;  
    free(p);  
    return head;  
}
```

```
int main() {  
    node* head = NULL;  
    head = create();  
    display(head);  
    head = insert_front(head, 10);  
    display(head);  
    head = insert_rear(head, 20);  
    display(head);  
    head = delete_front(head);  
    display(head);  
    head = delete_rear(head);  
    display(head);  
    return 0;  
}
```