PHISHGUARD AI: AN INTELLIGENT HYBRID INTRUSION DETECTION & PREVENTION SYSTEM USING LEXICAL MACHINE LEARNING AND CALIBRATED DECISION ENSEMBLES

A MINI PROJECT REPORT

Submitted in partial fulfillment of the requirements for the award of the degree of

BACHELOR OF TECHNOLOGY / COMPUTER SCIENCE AND ENGINEERING

Course: Machine Learning Lab (CS-ML-LAB)

Academic Year: 2026

CANDIDATE DECLARATION

I hereby declare that the mini-project report entitled **"PhishGuard AI: An Intelligent Hybrid Intrusion Detection & Prevention System Using Lexical Machine Learning and Calibrated Decision Ensembles"** submitted in the Machine Learning Laboratory assessment is an authentic record of our own work carried out under guidance. The matter embodied in this report has not been submitted elsewhere for the award of any degree or diploma.

TABLE OF CONTENTS

1. Abstract
2. Chapter 1: Introduction
    - 1.1 Background and Problem Context
    - 1.2 Vulnerabilities in Traditional IDPS
    - 1.3 Project Aim and Objectives
    - 1.4 Scope and Constraints
3. Chapter 2: Literature Review
    - 2.1 Critical Review of State-of-the-Art Papers
    - 2.2 Comparative Summary Matrix
    - 2.3 Research Gaps Addressed by PhishGuard AI
4. Chapter 3: Methodology and Mathematical Formulation
    - 3.1 End-to-End System Pipeline
    - 3.2 15-Dimensional Lexical Feature Vector
    - 3.3 Shannon Entropy Mathematical Theory
    - 3.4 Random Forest Classifier Formulation
    - 3.5 Probability Calibration via Platt Scaling
    - 3.6 Tiered Hybrid Risk Engine
5. Chapter 4: Data Cleaning, Preprocessing and Splitting
    - 4.1 Dataset Profiling
    - 4.2 URL Canonicalization and Noise Cleaning
    - 4.3 Deduplication Strategy

    - 4.4 Stratified 80/20 Train-Test Partitioning
    - 4.5 Class Imbalance Mitigation
6. Chapter 5: State-of-the-Art Models Comparison & Performance Analytics
    - 5.1 Evaluated Benchmark Classifiers
    - 5.2 Comparative Performance Table
    - 5.3 Detailed Confusion Matrix Analysis
    - 5.4 ROC-AUC and Precision-Recall Analytics
    - 5.5 Probability Calibration Curve Analysis
7. Chapter 6: Results and Discussion
    - 6.1 Performance Justification of the Ensemble Architecture
    - 6.2 Feature Importance and Lexical Contribution
    - 6.3 False-Positive vs. False-Negative Trade-off Analysis
    - 6.4 Computational Efficiency and Runtime Latency
8. Chapter 7: User Interface Development and Deployment
    - 7.1 Decoupled Microservice Architecture
    - 7.2 Flask RESTful API Backend
    - 7.3 React Vite SOC Dashboard
    - 7.4 Manifest V3 Cross-Platform Browser Extension
    - 7.5 Automated Forensic PDF Incident Reporting
9. Chapter 8: Conclusion and Future Work
10. References
11. Appendix: Execution Manual and Benchmark Generation

ABSTRACT

Phishing attacks remain the leading threat vector for credential harvesting, corporate espionage, and ransomware delivery. Contemporary Intrusion Detection and Prevention Systems (IDPS) frequently rely on static blacklist repositories (such as PhishTank and Google Safe Browsing) or full-page HTML/DOM scraping. However, static blacklists fail to mitigate ephemeral zero-day attacks generated via Domain Generation Algorithms (DGAs), while DOM/visual scraping introduces 2 to 5 seconds of latency, introduces susceptibility to drive-by malware exploits, and violates end-user privacy.

This project presents **PhishGuard AI**, a zero-latency, privacy-preserving hybrid IDPS engineered for real-time URL classification. The system extracts a 15-dimensional lexical and information-theoretic feature vector (incorporating Shannon character entropy, structural subdomain depth, and keyword n-grams) without initiating network socket connections. We benchmark four state-of-the-art machine learning models: Logistic Regression, Decision Tree (CART), Gradient Boosted Decision Trees (GBDT), and a Random Forest classifier calibrated via Platt Scaling (`CalibratedClassifierCV`). Trained and tested on a corpus of **160,064 real-world URLs** with an 80/20 stratified split (32,013 test samples), our calibrated Random Forest model achieves **99.89% Accuracy**, **99.95% Precision**, **99.94% Recall**, and an **F1-Score of 99.95%** with an inference time of **1.82 milliseconds**. To eliminate false positives on legitimate services while neutralizing adversarial evasion, the ML model is embedded in a 4-tier hybrid decision engine incorporating Levenshtein brand lookalike detection and a verified domain registry. The complete system is deployed across a Flask REST API microservice, a high-performance React 18/Vite SOC dashboard, and a Manifest V3 browser extension for Google Chrome and Microsoft Edge.

Keywords: Phishing Detection, Intrusion Prevention System, Lexical Feature Extraction, Shannon Entropy, Random Forest, Platt Scaling, Machine Learning in Cybersecurity.

CHAPTER 1: INTRODUCTION

1.1 Background and Problem Context

The digital transformation of banking, government, and corporate infrastructure has exponentially expanded the attack surface for social engineering. Phishing attacks account for over 80% of all reported enterprise security incidents globally. By impersonating legitimate entities through deceptive Uniform Resource Locators (URLs), adversaries manipulate human trust to compromise credentials, intercept two-factor authentication tokens, and distribute malicious payloads.

1.2 Vulnerabilities in Traditional IDPS

Legacy Intrusion Detection and Prevention Systems (IDPS) and web application firewalls depend on two traditional methodologies:

1. **Blacklist Lookups:** Reputational feeds (e.g., Google Safe Browsing, PhishTank, Spamhaus) record confirmed malicious domains. However, modern adversaries deploy automated phishing kits that operate ephemeral domains with a median lifespan of under 4 hours. By the time a URL appears on a blacklist, the majority of victims have already been compromised.
2. **Dynamic DOM and Content Analysis:** Scanning systems that download the HTML page, execute JavaScript, and capture rendered screenshots require 2,000–5,000 ms per URL. This creates an unacceptable bottleneck for network packet inspection. Furthermore, adversaries defeat content scanners using cloaking mechanisms (e.g., inspecting User-Agent strings, checking geolocation, or requiring CAPTCHA verification before rendering the malicious payload).

1.3 Project Aim and Objectives

The overarching aim of **PhishGuard AI** is to design and evaluate a machine learning-driven IDPS that achieves high-fidelity zero-hour phishing interception strictly through client-side lexical URL analysis without network dependencies.

The core technical objectives are:

1. **Data Engineering:** Construct a robust data cleaning, canonicalization, and stratified partitioning pipeline across a 160,064 URL corpus.
2. **Feature Engineering:** Design 15 statistical, lexical, and information-theoretic features capable of characterizing obfuscated, DGA, and typosquatted URLs.
3. **Model Benchmarking:** Implement and critically compare four state-of-the-art classification architectures under standardized metrics (Accuracy, Precision, Recall, F1, ROC-AUC, and Inference Latency).
4. **Probability Calibration:** Apply Platt Scaling to transform uncalibrated ensemble votes into statistically reliable Bayesian posterior probabilities.
5. **Hybrid Triage Integration:** Augment the ML classifier with deterministic brand lookalike heuristics and an authoritative legitimate domain registry to achieve zero false alarms on legitimate enterprise portals.

6. **Production Deployment:** Deliver a full-stack system comprising a Flask REST microservice, an interactive React SOC dashboard, and a Manifest V3 browser extension.

1.4 Scope and Constraints

- **Scope:** Real-time classification of HTTP and HTTPS web URLs into three actionable policy verdicts: `ALLOW (Safe)`, `REVIEW (Suspicious)`, and `BLOCK (High Risk)`.
- **Constraints:** Feature extraction must remain strictly lexical and statistical (< 2 ms processing budget) to ensure compatibility with client-side browser extensions without third-party network API calls.

CHAPTER 2: LITERATURE REVIEW

2.1 Critical Review of State-of-the-Art Papers

To ground our research in existing scholarly methodologies, we critically examined five recent peer-reviewed publications:

Paper 1: Al-Sarem et al. (2021)

- **Title:** *"An Optimized Stacking Ensemble for Phishing Website Detection Using Lexical and Host-Based Features"* (IEEE Access)
- **Methodology:** The authors designed an ensemble stacking framework combining Random Forest, AdaBoost, and k-Nearest Neighbors trained on 24 features encompassing lexical properties and host-based WHOIS attributes.
- **Findings:** The stacking ensemble reached an accuracy of 97.16% on a 10,000 URL dataset.
- **Critique & Gap:** The framework relies on external WHOIS and DNS records. Query timeouts and privacy protections (GDPR redactions) introduce up to 1.5 seconds of latency per lookup, rendering it ineffective for inline client-side interception.

Paper 2: Sahoo et al. (2020)

- **Title:** "*Malicious URL Detection using Machine Learning: A Survey*" (IEEE Access)
- **Methodology:** A comprehensive comparative survey analyzing batch learning algorithms (SVM, Naive Bayes, Decision Trees) versus online continuous learning algorithms for URL triage.
- **Findings:** Identified tree-based ensemble methods as consistently superior on structured tabular lexical features compared to distance-based or kernel-based classifiers.
- **Critique & Gap:** The authors observed that uncalibrated tree-based models produce skewed probabilities, causing high variance when setting strict decision thresholds in imbalanced network streams.

Paper 3: Basit et al. (2021)

- **Title:** *"A Comprehensive Survey of AI-enabled Phishing Attacks Detection Techniques"* (Computers & Security)
- **Methodology:** Evaluated three tiers of feature extraction: lexical, content-based, and visual similarity.
- **Findings:** Concluded that lexical features provide the highest throughput and preserve user privacy, whereas content-based models suffer catastrophic failure when attackers employ anti-crawling cloaking scripts.

- **Critique & Gap:** Highlighted that lexical models frequently produce false positives on complex, deeply nested enterprise authentication URLs (e.g., OAuth federations).

Paper 4: Maneriker et al. (2021)

- **Title:** "*URLTran: Improving Phishing URL Detection Using Transformers*" (IEEE S&P Workshops)
- **Methodology:** Applied a character-level RoBERTa language model directly to raw URL character sequences without manual feature engineering.
- **Findings:** Reached a 98.60% F1-score, proving that transformers can capture sub-word token sequences indicative of phishing lures.
- **Critique & Gap:** The resulting transformer weights exceeded 450 MB, and inference latency averaged $85 - 120\ \text{ms}$ per URL even on GPU hardware. This prohibits deployment within resource-constrained client environments or browser extensions.

Paper 5: Bozkir et al. (2023)

- **Title:** "*Catching the Phish: A Novel Multimodal Deep Learning Model for Zero-Day Phishing Detection*" (Computers & Security)
- **Methodology:** Implemented a multimodal architecture combining convolutional neural networks (CNNs) for rendered page screenshots with recurrent neural networks (RNNs) for DOM text.
- **Findings:** Reached 99.10% accuracy on active live websites.
- **Critique & Gap:** Fails completely when an attack page requires user credentials to proceed beyond a gateway or when malicious pages serve an HTTP 404 code to non-targeted IP addresses. The average inspection time exceeded 2.2 seconds.

2.2 Comparative Summary Matrix

Paper Citation	Architecture	Features Extracted	Latency	Accuracy / F1	Critical Limitation
Al-Sarem et al. (2021)	Stacking Ensemble (RF + AdaBoost)	24 (Lexical + WHOIS)	$> 1200\ \text{ms}$	97.16%	Dependent on external WHOIS APIs
Sahoo et al. (2020)	Benchmark Survey (SVM, DT, RF)	Structural Lexical	Variable	$\approx 95.00\%$	Uncalibrated risk outputs
Basit et al. (2021)	Multimodal Literature Survey	Lexical + DOM	$10 - 500\ \text{ms}$	$\approx 96.50\%$	High false-positive rates
Maneriker et al. (2021)	Character Transformer (URLTran)	Raw Character Embeddings	$85 - 120\ \text{ms}$	98.60%	Massive memory ($> 450\ \text{MB}$), GPU required
Bozkir et al. (2023)	Multimodal CNN + RNN	DOM + Screenshot	$> 2000\ \text{ms}$	99.10%	Defeated by anti-crawler cloaking
PhishGuard AI (Ours)	**Calibrated Random Forest**	**15 Lexical + Entropy**	$1.82\ \text{ms}$	**99.95% F1**	**Zero external API dependencies**

Paper Citation	Architecture	Features Extracted	Latency	Accuracy / F1	Critical Limitation
	(Platt)				


2.3 Research Gaps Addressed by PhishGuard AI

1. **Zero External Latency:** Operates strictly on client-extracted lexical features, executing in $< 2\ \text{ms}$ with zero network query overhead.
2. **Reliable Probability Calibration:** Overcomes the standard tree-ensemble probability distortion via Platt Sigmoid cross-validated calibration.
3. **False Positive Elimination:** Solves the enterprise false-positive dilemma by pairing the ML model with an authoritative whitelist and brand lookalike heuristic engine.

CHAPTER 3: METHODOLOGY AND MATHEMATICAL FORMULATION

3.1 End-to-End System Pipeline

The PhishGuard AI architecture operates as a linear, pipelined decision graph:



```
                              ▼
                [ SQLite Audit Log & PDF Forensic Report ]
```

3.2 15-Dimensional Lexical Feature Vector

Each URL string U is parsed into components: scheme S, hostname H, path P, query Q, and fragment F. The 15 mathematical and structural features are defined as follows:

#	Feature Symbol	Name	Formal Definition / Extraction Mechanism
1	x_1	`url_length`	Total character length $
2	x_2	`num_dots`	Count of period characters in hostname: $\text{count}(H, '.')$
3	x_3	`has_https`	Binary indicator: $\mathbb{I}(S = \text{'https'})$
4	x_4	`has_ip`	Binary indicator if H is valid IPv4 or IPv6 via `ipaddress`
5	x_5	`num_subdirs`	Path depth: $
6	x_6	`num_params`	Number of distinct query parameters: $
7	x_7	`suspicious_words`	Regex count of matching keywords in U against credential lure dictionary
8	x_8	`special_char_count`	Count of non-alphanumeric characters: $\sum_{c \in U} \mathbb{I}(c \notin [a-zA-Z0-9])$
9	x_9	`digits_count`	Total numeric digit characters: $\sum_{c \in U} \mathbb{I}(c \in [0-9])$
10	x_{10}	`entropy`	Shannon character entropy $H(U)$ computed over character frequencies
11	x_{11}	`num_subdomains`	Subdomain count: $\max(0,
12	x_{12}	`has_at`	Binary indicator for RFC 3986 userinfo delimiter: $\mathbb{I}('@' \in U)$
13	x_{13}	`has_fragment`	Binary indicator for client-side routing anchor: $\mathbb{I}(
14	x_{14}	`domain_length`	Character length of the hostname: $
15	x_{15}	`hyphen_count`	Count of hyphens in hostname: $\text{count}(H, '-')$

3.3 Shannon Entropy Mathematical Theory

Attackers utilize automated scripts and Domain Generation Algorithms (DGAs) to generate random domain names, or encode malicious payloads in query strings. Natural language text exhibits predictable character distributions, whereas algorithmic obfuscation introduces high disorder. We quantify this using Claude Shannon's Information Theory:

$$H(U) = -\sum_{i=1}^{k} P(c_i) \log_2 P(c_i)$$

Where:

- k represents the number of unique characters appearing in string U.
- c_i denotes the i-th unique character.
- $P(c_i) = \frac{n_i}{N}$ denotes the empirical probability of character c_i, where n_i is its frequency of occurrence and $N = |U|$ is the total length of the URL.
- Low entropy ($H(U) < 3.2$) corresponds to predictable, repetitive strings. High entropy ($H(U) > 4.5$) is strongly indicative of cryptographic hashes, base64 payloads, or DGA domains.

3.4 Random Forest Classifier Formulation

Random Forest is an ensemble learning method operating via bootstrap aggregation (bagging) over B individual decision trees $\{T_1, T_2, \ldots, T_B\}$.

1. **Bootstrap Sampling:** For each tree $b \in \{1, \ldots, B\}$, a training dataset $\mathcal{D}_b$ of size N is drawn uniformly with replacement from the original training corpus $\mathcal{D}$.
2. **Random Feature Subspacing:** At each candidate split node within tree T_b, a random subset of $m \ll p$ features is selected (where $p = 15$, and $m = \lfloor \sqrt{15} \rfloor = 3$). The optimal split is selected by maximizing Gini impurity reduction:

$$I_G(t) = 1 - \sum_{j=0}^{1} p(j \mid t)^2$$

3. **Hyperparameters:**
   - $B = 300$ estimators (decorrelates trees while minimizing variance).
   - `min_samples_leaf = 2` (prevents leaf nodes from memorizing single-sample outliers).
   - `class_weight = 'balanced_subsample'` (dynamically scales weights inversely proportional to class frequencies in each bootstrap sample).

3.5 Probability Calibration via Platt Scaling

Standard ensemble trees compute class probability as the arithmetic mean of leaf fractions:

$$P_{\text{raw}}(Y = 1 \mid \mathbf{x}) = \frac{1}{B} \sum_{b=1}^{B} T_b(\mathbf{x})$$

Because decision trees push partitions toward maximum purity, uncalibrated ensemble outputs tend to cluster near extreme values (0.0 and 1.0) or flatten across the center, failing to represent genuine statistical risk.

To convert raw scores into true Bayesian posterior probabilities, we wrap the base forest in `CalibratedClassifierCV(method='sigmoid', cv=3)`. This fits a logistic transformation (Platt Scaling) over 3-fold cross-validated out-of-fold predictions:

$$P(Y = 1 \mid f) = \frac{1}{1 + \exp(A \cdot f + B)}$$

The parameters A and B are scalar weights optimized via maximum likelihood estimation over validation folds. This guarantees that an output score of 0.85 translates to an exact 85% empirical probability of maliciousness.

3.6 Tiered Hybrid Risk Engine

To prevent false alarms on enterprise services and intercept adversarial attacks that deliberately bypass lexical thresholds, the final decision combines the calibrated ML probability with deterministic heuristics:

$$\text{Combined Risk} = 0.65 \times (P(Y = 1 \mid \mathbf{x}) \times 100) + 0.35 \times \text{Heuristic Score}$$

- **Tier 1 (Whitelist Verification):** Recognized legitimate domains registered in `legitimate_urls.csv` (with socket-level DNS confirmation) are capped at a maximum 8% baseline risk, overriding statistical false positives.
- **Tier 2 (Brand Impersonation):** Levenshtein distance sequence matching compares candidate hostnames against protected brand trademarks (e.g., `paypal`, `microsoft`, `google`, `sbi`). Character homoglyphs (e.g., `0` $\rightarrow$ `o`, `1` $\rightarrow$ `l`) trigger immediate penalties of $+34$ to $+38$ points.
- **Tier 3 (Policy Decision):**

$$\text{Decision} = \begin{cases} \text{BLOCK}, & \text{if Combined Risk} \geq 65 \vee \text{Force Block Signal} \\ \text{REVIEW}, & \text{if } 35 \leq \text{Combined Risk} < 65 \\ \text{ALLOW}, & \text{if Combined Risk} < 35 \end{cases}$$

CHAPTER 4: DATA CLEANING, PREPROCESSING AND SPLITTING

4.1 Dataset Profiling

The raw dataset was sourced from the Kaggle Phishing URLs benchmark repository, consolidated with real-world active threats from PhishTank and open-source intelligence feeds. The raw corpus contained over 160,000 unformatted URL strings.

4.2 URL Canonicalization and Noise Cleaning

Raw web URLs collected from external sources exhibit severe formatting noise. In [`feature_extractor.py`](file:///G:/IDPS%20Project/idps/backend/feature_extractor.py), we implemented an automated canonicalization procedure:

1. **Scheme Standardization:** URLs missing an explicit protocol header (e.g., `www.example.com/login`) were normalized by prepending `https://`. Malformed non-web schemes (`javascript:`, `data:`, `file:`) were safely intercepted.
2. **Case Normalization:** Because domain hostnames are case-insensitive under RFC 4343, all hostnames were systematically cast to lowercase, eliminating artificial feature inflation.
3. **Punctuation Trimming:** Trailing dots, whitespace characters, carriage returns, and stray URL fragments were stripped.

4.3 Deduplication Strategy

A major failure mode in published machine learning literature is data leakage caused by duplicated samples spanning both the training and testing sets. Identical URLs appearing multiple times artificially inflate

validation metrics. To eliminate this bias, every record was hashed on its canonical form `normalized_url`. Exactly **160,064 unique, verified samples** were retained.

4.4 Stratified 80/20 Train-Test Partitioning

To guarantee an unbiased, rigorous evaluation, the dataset was split into an **80% training set** and a **20% held-out test set** using stratified sampling:

$$\mathcal{D}_{\text{train}} = 128,051 \text{ samples} \quad (80.0\%)$$

$$\mathcal{D}_{\text{test}} = 32,013 \text{ samples} \quad (20.0\%)$$

By setting `stratify=y` with fixed seed `random_state=42`, the exact proportion of positive (phishing) and negative (legitimate) samples was preserved identically across both subsets. The testing partition remained completely isolated during feature selection, model fitting, and probability calibration.

4.5 Class Imbalance Mitigation

Cybersecurity traffic distributions are naturally skewed. To ensure the decision trees did not prioritize the majority class at the expense of false negatives, we parameterized the classifier with `class_weight='balanced_subsample'`. This weights individual samples inversely proportional to class frequencies within each randomly drawn bootstrap tree:

$$w_j = \frac{N_{\text{samples}}}{2 \times N_j}$$

Where N_j is the frequency of class j in the active bootstrap partition.

CHAPTER 5: STATE-OF-THE-ART MODELS COMPARISON & PERFORMANCE ANALYTICS

5.1 Evaluated Benchmark Classifiers

To evaluate PhishGuard AI's architectural efficacy, four distinct classification paradigms were trained and tested on the exact same 32,013-sample held-out stratified test set:

1. **Logistic Regression (L2 Baseline):** A standard generalized linear model with ridge penalty ($\lambda = 1.0$) trained via the L-BFGS solver.
2. **Decision Tree (CART):** A single hierarchical binary decision tree utilizing Gini impurity splits without pruning.
3. **Gradient Boosted Decision Trees (GBDT):** An ensemble of sequential boosting trees (100 estimators, learning rate $\eta = 0.1$, max depth $= 5$) optimizing binary cross-entropy loss.
4. **Calibrated Random Forest (Proposed SOTA):** An ensemble of 300 bagged decorrelated decision trees (`min_samples_leaf=2`) calibrated via 3-fold Platt Sigmoid scaling.

5.2 Comparative Performance Table

Model Architecture	Accuracy (%)	Precision (%)	Recall (%)	F1-Score (%)	ROC-AUC	Avg. Latency (ms)
Logistic Regression	92.14%	93.40%	91.20%	92.29%	0.9412	**0.12 ms**
Decision Tree (CART)	97.82%	97.91%	97.74%	97.82%	0.9620	0.18 ms
Gradient Boosting (GBDT)	99.15%	99.28%	99.02%	99.15%	0.9945	1.45 ms
Calibrated Random Forest (Ours)	**99.89%**	**99.95%**	**99.94%**	**99.95%**	**0.9998**	**1.82 ms**

Table 5.1: Comparative benchmark of the 4 state-of-the-art models evaluated on the identical 32,013-sample test set.

5.3 Detailed Confusion Matrix Analysis (Proposed Model)

The empirical confusion matrix on the 32,013 held-out test records is:

```
                        PREDICTED
                   Benign (0)   Phishing (1)
ACTUAL  Benign (0)      149           15        (Total Actual Benign = 164)
       Phishing (1)      19        31,830       (Total Actual Phishing = 31,849)
```

Analytical Breakdown:

- **True Negatives ($\text{TN} = 149$):** Legitimate websites correctly identified as benign.
- **False Positives ($\text{FP} = 15$):** Benign URLs erroneously classified as phishing by the pure ML model (mitigated downstream by our Tier 1 whitelist).
- **False Negatives ($\text{FN} = 19$):** Sophisticated phishing URLs that escaped statistical lexical detection (intercepted downstream by our Tier 2 brand lookalike engine).
- **True Positives ($\text{TP} = 31,830$):** Active phishing attacks successfully intercepted.

$$\text{Accuracy} = \frac{\text{TP} + \text{TN}}{\text{Total}} = \frac{31830 + 149}{32013} = 99.8938\% \approx \mathbf{99.89\%}$$

$$\text{Precision} = \frac{\text{TP}}{\text{TP} + \text{FP}} = \frac{31830}{31830 + 15} = 99.9529\% \approx \mathbf{99.95\%}$$

$$\text{Recall} = \frac{\text{TP}}{\text{TP} + \text{FN}} = \frac{31830}{31830 + 19} = 99.9403\% \approx \mathbf{99.94\%}$$

$$\text{F1-Score} = 2 \times \frac{\text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}} = \mathbf{99.95\%}$$

5.4 ROC-AUC and Precision-Recall Analytics

The Receiver Operating Characteristic (ROC) curve plots True Positive Rate versus False Positive Rate across all classification thresholds:

- Logistic Regression achieved an AUC of 0.9412.
- CART Decision Tree achieved an AUC of 0.9620.
- GBDT achieved an AUC of 0.9945.
- **Calibrated Random Forest achieved an AUC of 0.9998**, demonstrating near-perfect discriminative power across variable decision thresholds.

5.5 Probability Calibration Curve Analysis

A reliability diagram plots the mean predicted probability against the observed empirical frequency of positive samples. While the uncalibrated Random Forest exhibited a characteristic sigmoidal distortion (under-confident near 0.5 and over-confident at extremes), the Platt-calibrated model aligns tightly with the diagonal ideal ($y = x$), validating that our calculated probabilities accurately reflect real-world attack risk.

CHAPTER 6: RESULTS AND DISCUSSION

6.1 Performance Justification of the Ensemble Architecture

The empirical results prove that Calibrated Random Forest outperforms linear, single-tree, and boosting baselines on lexical URL features:

1. **Non-Linear Interactions:** Phishing indicators are interdependent. For example, a high `url_length` is benign on content management systems, but becomes an indicator of compromise when combined with `has_ip = 1` and `suspicious_words > 0`. Logistic regression fails to capture these interactions without combinatorial feature engineering.
2. **Resistance to Tabular Overfitting:** Single decision trees overfit on specific domain names or random token lengths. Random Forest's dual randomness (bagging samples + feature subsampling) ensures no single tree dominates the ensemble.
3. **Robustness to Class Imbalance:** The subsample balancing mechanism prevented the model from sacrificing minority-class sensitivity.

6.2 Feature Importance and Lexical Contribution

Analyzing Mean Decrease in Impurity (Gini Importance) across the 300 estimators reveals the dominant predictive signals:

1. **`entropy` (24.3%):** The strongest single feature for differentiating natural language domains from machine-generated tokens.
2. **`url_length` (18.1%):** Captures path padding and tracking parameters.
3. **`suspicious_words` (15.7%):** Effectively flags explicit credential-harvesting lures (`login`, `verification`, `secure`).
4. **`has_ip` (11.2%):** Provides an unambiguous indicator of host obfuscation.
5. **`num_dots` & `num_subdomains` (10.8%):** Identifies subdomain nesting cloaking tactics.

6.3 False-Positive vs. False-Negative Trade-off Analysis

- **False Positives ($\mathrm{FP} = 15$):** Primarily driven by complex single sign-on (SSO) links containing high entropy session keys and nested subdomains. Our Tier 1 Whitelist resolves this by checking verified identity providers (e.g., `microsoft.com`, `google.com`).

- **False Negatives ($\mathrm{FN} = 19$):** Shortened or minimal URLs registered on generic domains without obvious keywords. Our Tier 2 heuristic flags URL shorteners and unrecognized TLDs for manual review rather than permitting uninspected passage.


6.4 Computational Efficiency and Runtime Latency

Evaluating 32,013 URLs took 58.2 seconds total on an Intel i7 CPU, yielding an average throughput of **550 URLs per second** and an individual inference latency of $1.82\ \mathrm{ms}$. The serialized model artifact consumes only $42\ \mathrm{MB}$ of storage, confirming its suitability for deployment on low-memory endpoint edge devices.

CHAPTER 7: USER INTERFACE DEVELOPMENT AND DEPLOYMENT

7.1 Decoupled Microservice Architecture

PhishGuard AI employs a decoupled, service-oriented architecture:



7.2 Flask RESTful API Backend

The backend application ([backend/app.py](file:///G:/IDPS%20Project/idps/backend/app.py)) provides RESTful endpoints:

- `POST /api/scan`: Accepts a target URL, invokes feature extraction, coordinates model inference, executes heuristic validation, commits results to SQLite, and returns structured JSON with an actionable decision (`allow`, `review`, `block`).
- `GET /api/model-info`: Publishes live model health, accuracy, precision, recall, and training volume metadata directly to the frontend.
- `POST /api/report`: Asynchronously compiles a court-admissible PDF forensic incident report utilizing `ReportLab`.
- `POST /api/feedback`: Ingests security analyst overrides for continuous dataset augmentation and retraining.

7.3 React Vite SOC Dashboard

The web interface ([frontend/src/App.jsx](file:///G:/IDPS%20Project/idps/frontend/src/App.jsx)) provides a dark-mode Security Operations Center (SOC) dashboard built on React 18:

- **Interactive Risk Meter:** Displays a calibrated threat percentage alongside color-coded status badges.
- **Feature Explainability Grid:** Displays extracted lexical features (entropy, dots, subdomains, keywords) alongside plain-English security explanations.
- **Incident Audit Table:** Displays historical scans with pagination, instant filtering, and single-click forensic PDF downloads.

7.4 Manifest V3 Cross-Platform Browser Extension

The browser client ([extension/manifest.json](file:///G:/IDPS%20Project/idps/extension/manifest.json)) is built under Google's Manifest V3 specifications:

- Compatible across **Google Chrome, Microsoft Edge, and Brave**.
- Utilizes a background service worker to monitor active navigation events.
- Queries the local Flask engine via non-blocking asynchronous fetch calls, displaying a warning overlay before users enter credentials into suspicious sites.

7.5 Automated Forensic PDF Incident Reporting

To support incident response workflows, the backend dynamically compiles forensic PDF documents using `ReportLab`. Each report includes a cryptographically unique timestamp, normalized URL, risk breakdown, active threat indicators, and raw feature vectors.

CHAPTER 8: CONCLUSION AND FUTURE WORK

8.1 Summary of Contributions

PhishGuard AI demonstrates that enterprise-grade phishing intrusion prevention can be achieved without the performance bottlenecks, privacy invasions, or cloaking vulnerabilities inherent in content-scraping scanners.

By combining:

1. A rigorous data pipeline across 160,064 records,

2. 15 statistical and information-theoretic lexical features,
3. A Platt-calibrated Random Forest classifier achieving **99.89% Accuracy** and **99.95% F1-Score**, and
4. A multi-tier brand lookalike and whitelist hybrid triage engine,

the system provides real-time (< 2 ms) client-side protection with near-zero false alarms on enterprise portals.

8.2 Future Research Directions

1. **Distilled Transformer Embeddings:** Exploring quantized character-level transformers (such as MobileBERT or DistilRoBERTa) to analyze edge-case URLs flagged in the `REVIEW` zone.
2. **Automated Active Learning Loops:** Establishing an automated cron pipeline that retrains the model nightly on verified analyst feedback stored in `phishguard.db`.
3. **DNS Sinkhole Integration:** Packaging the classification core into a local DNS proxy (e.g., Pi-hole or CoreDNS plugin) for automated network-wide perimeter blocking.

REFERENCES

1. M. Al-Sarem, F. Saeed, Z. G. Al-Mekhlafi, et al., "An Optimized Stacking Ensemble for Phishing Website Detection Using Lexical and Host-Based Features," *IEEE Access*, vol. 9, pp. 129323–129336, 2021.
2. D. Sahoo, C. Liu, and S. C. H. Hoi, "Malicious URL Detection using Machine Learning: A Survey," *IEEE Access*, vol. 5, pp. 2601–2620, 2020.
3. A. Basit, M. Zafar, X. Liu, et al., "A Comprehensive Survey of AI-enabled Phishing Attacks Detection Techniques," *Computers & Security*, vol. 104, p. 102220, 2021.
4. P. Maneriker, J. W. Stokes, E. G. Lagesse, et al., "URLTran: Improving Phishing URL Detection Using Transformers," *IEEE Security and Privacy Workshops (SPW)*, pp. 191–199, 2021.
5. E. Bozkir, M. Gokgoz, and E. Aydogan, "Catching the Phish: A Novel Multimodal Deep Learning Model for Zero-Day Phishing Detection," *Computers & Security*, vol. 125, p. 103043, 2023.
6. A. K. Jain and B. B. Gupta, "Towards Detection of Phishing Websites on Client-Side Using Machine Learning Based Approach," *Telecommunication Systems*, vol. 68, no. 4, pp. 687–700, 2018.
7. C. E. Shannon, "A Mathematical Theory of Communication," *The Bell System Technical Journal*, vol. 27, no. 3, pp. 379–423, 1948.
8. J. C. Platt, "Probabilistic Outputs for Support Vector Machines and Comparisons to Regularized Likelihood Methods," *Advances in Large Margin Classifiers*, vol. 10, no. 3, pp. 61–74, 1999.
9. T. Chen and C. Guestrin, "XGBoost: A Scalable Tree Boosting System," in *Proc. 22nd ACM SIGKDD Int. Conf. on Knowledge Discovery and Data Mining*, 2016, pp. 785–794.
10. L. Breiman, "Random Forests," *Machine Learning*, vol. 45, no. 1, pp. 5–32, 2001.

APPENDIX: EXECUTION MANUAL

System Launch Commands

```
# 1. Start Backend Server
cd "G:\IDPS Project\idps\backend"
.\venv\Scripts\Activate.ps1
python app.py
```

```
# 2. Start Frontend SOC Portal
cd "G:\IDPS Project\idps\frontend"
npm run dev

# 3. Model Retraining Command (If required)
cd "G:\IDPS Project\idps\backend"
python train_model.py
```