

04 • Behaviour & Logic

All values below are copied from the code (`index.html` , `admin.html` , `staff.html` , `api/*.js`). Error text is **verbatim** (Russian, as shipped). Where behaviour is unclear it is flagged and also listed in `OPEN_QUESTIONS.md` .

1. Validation (with exact error text)

Validation is minimal and **client-side only** (toasts). No length/format/regex checks beyond "not empty". Email is typed `<input type=email>` but **not regex-validated** before submit.

Guest entry (`entry`)

- Name is required to proceed. Sub-label: **"Укажите имя и контакт, чтобы продолжить"**. (Contact optional in practice.)

Registration — Affiliate form (`submitAf`)

Field	Rule	Exact toast on failure
Company/team	not empty (<code>.trim()</code>)	"Укажите компанию/команду"
Email	not empty (<code>.trim()</code>)	"Укажите email"

Registration — Buyer/partner form (`submitReg` / `submit...`)

Field	Rule	Exact toast
Company	not empty	"Укажите компанию"
Email	not empty	(email required; same pattern)

On DB error: **"Ошибка сохранения: " + `error.message`**.

Demo / cart requests

- Demo with no selection → toast **"•"** (placeholder). On success → **"Запрос демо отправлен"**.
- Cart empty → toast **"•"**. Adding a duplicate → **"Уже в корзине"**. Add success → **"Добавлено в корзину интересов"**. Submit → **"Запрос отправлен менеджеру"**.

Chat

- Storage unavailable → `alert("Хранилище недоступно")` . Upload error → `alert("Ошибка загрузки: " + message)` .

Login (`/login` , `login.html`)

- Wrong credentials → "Неверный логин или пароль" (from `{ok:false}`).
- Network/other → generic network error message.
- Server requires both fields: `400 {error:'login and pass required'}` .

Gap (see OPEN_QUESTIONS): no email-format, password-strength, phone-format, or field-length validation anywhere. The mobile app should add real validation.

2. Calculations, formatting, defaults

- **Vendor** `match_score` (relevance %) is assigned on publish, **not computed**: `match_score = (badge === 'new') ? 65 : 80 ( admin.html:430 )`.
- **Toast duration**: 2000 ms (`index.html`), then auto-hide.
- **VPN connect delay**: 1000 ms simulated; IP is `randIP()` (fake).
- **Dates** are formatted by string slicing, not a locale library: `(iso).slice(0,16).replace('T','')` → "2026-09-09 13:50" . Signed/paid timestamps use the same.
- **Short visitor code**: `shortCode(id)` — a truncated id used as "Гость " when no name.
- **Prices** are literal catalog strings (e.g. `€19 900` , `EPC €0.42` , `RTP 97%`) — never computed.
- **Loyalty tiers** (`index.html` `LOY`) are static tables, e.g. `MASTER` = VIP 13–18 with levels `[level, points, reward]` like `[1,10000,1000]` ... `[6,100000,10000]` ; `LEGEND` VIP 19–24; `GOD` VIP 25–30 up to `[6,10000000,100000]` . **Cosmetic** — no real points engine.
- **Currency/number style**: thin-space thousands in catalog text (`19 900`); no runtime number formatting.

3. Sorting, filtering, pagination

- **Deals** load ordered by `created_at` **ascending** (`.order('created_at', {ascending:true})`) .

- **Marketplace** filters by category **chip** (client-side `filter`); "Bce" = no filter. No search-as-you-type on vendors beyond the home search.
- "Кто на сайте" shows `liveVisitors()` **sliced to first 10**; "live" = active in the last **5 minutes**.
- **No pagination** anywhere – all lists render in full (fine for demo volumes; mobile must add paging).
- Applications dashboard counts: pending = `status==='pending'`; "Одобрено вендоров" = `status==='approved' || 'partner'`.

4. Roles & permissions

Capability	Guest	Staff	Admin
Browse catalog / marketplace / advisor			
Submit application / demo / cart / chat			
See own leads/deals/agreements/tasks/chats	–	(own only)	(all)
Moderate applications, publish vendors	–	–	
Manage team (create staff, reset pass, toggle access)	–	–	
Accounts registry, content, full analytics	–	–	
Open another staff's cabinet	–	–	

- **Admin identity** = env `ADMIN_LOGINS (email:pass,...)` or a `staff` row whose `role` matches `/^(админ|admin)$/i` and `active !== false`.
- **Staff identity** = a `staff` row with matching `login`, `active === true`, and matching `pass`.
- Staff cabinet scopes every list to the logged-in staff object `S`. There is **no server-enforced row-level authorization** – scoping is client-side. (See OPEN_QUESTIONS: real per-user authz needed.)

5. State machines (as tables)

5a. Application status (`applications.status`)

State	Meaning	Transitions (admin action)
<code>pending</code>	На проверке (new submission)	→ <code>approved</code> , <code>partner</code> , (<code>new</code>), <code>rejected</code>
<code>approved</code>	"Approved by BetConstruct"	→ back to <code>pending</code> ("Вернуть на проверку")

State	Meaning	Transitions (admin action)
partner	"Partner by BetConstruct" (★)	→ back to pending
new	New badge variant	(publishes vendor with match_score 65)
rejected	Отклонено	→ pending

Publishing a vendor happens when status ∈ { approved , partner , new } → inserts a vendors row (badge=status , active:true , match_score = new?65:80).

5b. CRM deal – 6 stages (STAGES , Zoho-like)

#	key	Name	Sub
1	lead	Lead Email	Проверить email, завести лид
2	deal	Convert to Deal	Подтверждена возможность
3	confirmed	Project Confirmed	Согласован scope с партнёром
4	agreement	Agreement & Payment	DocuSign + setup fee
5	started	Project Started	PM: активная разработка
6	won	Closed Won	Проект Live

Move with ◀ ▶ (moveStage(id, ±1)); last stage shows a "Live" chip. status is active by default.

5c. CRM deal – 7-step operational flow (FLOW , boolean array flow[0..6])

#	Step	Detail	Role
1	Lead check	Проверить email в системе; если нет – завести лид	Sales
2	Agreement & Fee	Договор (DocuSign) → подпись партнёра → setup fee оплачен	Sales
3	Resource request	Запрос PM и Service Sales (во время шага 2)	Service Sales
4	Kickoff chat	Групповой канал PM + Партнёр	PM
5	Development	Разработка и настройка (~3–4 недели)	PM
6	Go Live notice	Проект запущен; официальный email-уведомление	PM
7	AM Handover	Передача проекта Account Manager	Account Manager

Side effects when a step is toggled (toggleFlow):

- Toggling **step 3** (Resource request) the first time → sets `rr_done` , auto-creates PM/Service-Sales **tasks** (`addResourceRequest`).
- Toggling **step 4** (Kickoff chat) the first time → sets `kick_done` , auto-creates a **kickoff thread** (`createKickoff`) with a system message.
- Each toggle appends to `deal.steps` a log entry `{n:'✓/× <step>', by:<actor>, at:<now>}` .

5d. Agreement status (`AGR_STATUS`)

key	Label	style
<code>draft</code>	Черновик	pend
<code>sent</code>	Отправлено	nw
<code>signed</code>	Подписано	pt
<code>completed</code>	Завершено	ap

Actions: "Отметить подписано" → `status:'signed'` + `signed_at` → reflects `agr.signed=true` on the linked deal. Paid → `paid_at` .

5e. Vendor badge (`vendors.badge`) → visual chip

badge	Chip text
<code>pending</code>	🕒 На проверке
<code>approved</code>	✓ Approved by BetConstruct
<code>partner</code>	★ Partner by BetConstruct
<code>new</code>	New

6. Auth & session

- **No identity provider / JWT**. Login is verified server-side by `POST /api/login` using Supabase **service_role** (never exposed to the browser). Passwords are additionally **column-REVOKE'd** from `anon` / `authenticated` .
- **Session = a browser storage flag**, no expiry, no refresh token:
 - Admin: `sessionStorage.bc_admin` (set after `dest:'admin'`).
 - Staff: `sessionStorage.bc_staff` = JSON profile (after `dest:'staff'`).
 - Guest: `localStorage.bc_guest` (name/contact) + `window.USER` .
- **Logout** clears the flag ("Выйти" / "Сменить аккаунт"). No server-side session invalidation exists.
- **Device id**: FingerprintJS v4 → stable `anonId` in `localStorage.bc_anon` , used as chat `guest_key` and analytics key. Only set **after consent**.

Security note (OPEN_QUESTIONS): sessions never expire, there is no CSRF/refresh model, and authorization is client-side. Mobile v1 should use a real auth (e.g. Supabase Auth / OAuth) with server-enforced RLS.

7. Realtime (all polling – no websockets)

What	Interval	Where
Visitor chat messages	3500 ms	index.html:811 (loadVisitorMsgs)
Background chat watcher (toast when manager replies while chat closed)	6000 ms	index.html:322 (bgChatWatch)
Heartbeat ping (analytics presence)	45000 ms	index.html:313 (track('ping','beat') , only when tab visible)
Admin/staff chat & presence	~3.5 s / ~20 s	admin.html/staff.html ("Обновление вживую ~3.5с")

Background toast text: " Менеджер написал вам – откройте «Чат»".

Mobile should replace polling with push notifications + realtime subscriptions.

8. AI / LLM prompt (VERBATIM)

Endpoint: POST /api/advisor , body { prompt, context, lang } → { text, model } .
Provider in the repo: Google Gemini. Model list tried in order: gemini-3.5-flash , gemini-2.5-flash-lite , gemini-pro-latest , gemini-flash-lite-latest .
generationConfig.temperature = 0.4 . On total failure it returns {text:'Не удалось получить ответ.', errors, availableModels} and the client falls back to aiLocal .

System prompt (exact, api/advisor.js):

Ты – AI-советник платформы BetConstructAI (B2B iGaming-маркетплейс вокруг экосистемы BetConstruct).
СТРОГОЕ ПРАВИЛО: отвечай ТОЛЬКО на основе данных платформы ниже (раздел «ДАННЫЕ ПЛАТФОРМЫ»).
Это три источника: (1) что такое BetConstruct – решения, платформы, продукты, цены, регионы, (2) MARKETPLACE – продукты вендоров; (3) ПАРТНЁРЫ – производители.
Не выдумывай продукты, цены, компании или лицензии, которых нет в данных. Если чего-то нет в данных, то ответь, что этого пока нет в каталоге, и предложи связаться с менеджером.
Задача: по запросу клиента (гео, вертикаль, крипто/фиат, тип игр, бюджет) собери готовую презентацию.

- рекомендованный регион/юрисдикция и лицензия (из данных);
- продукт/пакет BetConstruct с ценой (из данных);
- конкретные продукты вендоров из MARKETPLACE (по именам) под задачу;
- подходящих партнёров-производителей по именам;
- платежи (крипто/фиат) из данных.

Ссылайся на конкретные названия из данных. Отвечай кратко и структурировано на языке: \${lang}.
В конце добавь: «Предварительная рекомендация, не юридическая консультация – финал с менеджером.»

===== ДАННЫЕ ПЛАТФОРМЫ =====

\${context} || '(данные не переданы)'

===== КОНЕЦ ДАННЫХ =====

- `langName` = `English` if `lang==='en'`, `Armenian (Հայերեն)` if `lang==='hy'`, else `Russian`.
- `context` is built client-side by `buildKB()` = BetConstruct catalog + marketplace vendors + partners, passed as a big text block.
- The user's free text is the `contents` message.
- Required disclaimer appended by the model: **"Предварительная рекомендация, не юридическая консультация – финал с менеджером."**

A rewrite targeting **Anthropic Claude Haiku 4.5** was authored out-of-repo (same {prompt,context,lang}→{text} contract) but is **not in this repo and not deployed**.
Provider is undecided – see `01_APP_OVERVIEW.md` and `OPEN_QUESTIONS`.

The in-app manager chat opener is a **mock** greeting persona: **"Ани · на связи" / "Здравствуйте! Напишите ваш вопрос – менеджер ответит здесь."**

9. Persistence (what is stored where)

Browser (per device):

- `localStorage.bc_anon` – FingerprintJS anon id (consent-gated).
- `localStorage.bc_guest` – guest name/contact.
- `localStorage` `cart` – interest cart items {name, cat, price}.
- `localStorage` `consent` flag – GDPR acceptance.
- `sessionStorage.bc_admin` / `sessionStorage.bc_staff` – team session.

Supabase (server): all domain data – see `05_DATA_AND_API.md`. Files → Storage bucket `uploads`.

10. Analytics events (`track(type, action, meta)` → `events`)

Event `type` values in use: `page`, `click`, `cart`, `lead`, `ai`, `search`, `entry`, `ping`.

- Fired only **after consent**. `ping` heartbeat every 45 s when the tab is visible.

- Admin **Аналитика** aggregates: marketplace funnel (показ→клик→лид), visitor paths (merged by contact/device code), shift ranking.

No third-party analytics SDK (GA/Amplitude) – analytics is home-grown in the events table. FingerprintJS is the only external tracker, and it is consent-gated.