

06 · Integrations & Platform

Everything third-party this demo touches, plus device/platform notes for the native rebuild. **No secrets are printed here** — key values are shown only as their env-var names.

1. Third-party services

Service	Role in the app	How it's wired	State
Supabase (smddtvaewmmpuyvtuscb.supabase.co)	Primary backend: Postgres DB, REST (PostgREST), Storage bucket uploads	Browser uses anon/publishable key (in-page); server functions use <code>SB_SERVICE_KEY</code> (service_role). <code>supabase-js</code> UMD from <code>cdn.jsdelivr.net/npm/@supabase/supabase-js</code> .	Real, in use
Google Gemini	AI advisor LLM	<code>api/advisor.js</code> , <code>GEMINI_API_KEY</code> , REST <code>generativelanguage.googleapis.com/v1beta</code> . Models tried: gemini-3.5-flash, 2.5-flash-lite, pro-latest, flash-lite-latest.	Coded, currently failing (model/access) → client falls back to <code>aiLocal</code> . Provider undecided (Claude Haiku 4.5 rewrite exists out-of-repo).
FingerprintJS v4	Device fingerprint → stable <code>anonId</code>	<code>openfpcdn.io/fingerprintjs/v4</code> (CDN).	Real, consent-gated (off until "Принять").
Resend	Transactional email (notifications)	<code>api/notify.js</code> , <code>RESEND_API_KEY</code> , <code>NOTIFY_FROM</code> , <code>NOTIFY_ADMIN</code> .	Coded; depends on key being set.
Gmail API (Google OAuth)	Two-way email sync into CRM comms	<code>api/gmail-*.js</code> , <code>GOOGLE_CLIENT_ID/SECRET/REDIRECT</code> ; inbound <code>api/email-inbound.js</code> ; <code>api/comm-ingest.js</code> (<code>COMM_INGEST_SECRET</code>).	Coded, NOT connected — corporate Google blocks the OAuth app.
Vercel	Hosting + serverless	ESM handlers, auto-deploy from GitHub <code>mantarlyani/betconstructAI</code> .	Real (live site).

Service	Role in the app	How it's wired	State
	functions (api/*.js)		
GitHub	Source + deploy trigger	Repo <code>mantarlyani/betconstructAI</code> ; push → Vercel deploy.	Real (dev workflow).

CDNs loaded in the browser (must be replaced by native deps)

- `cdn.jsdelivr.net/npm/@supabase/supabase-js` — Supabase client.
- `openfpcdn.io/fingerprintjs/v4` — FingerprintJS.
- No CSS/icon/font CDNs — fonts are system, icons are inline SVG (see `assets/`).

Environment variables (server) — names only, values are secret

`SB_URL` , `SB_ANON_KEY` , `SB_SERVICE_KEY` , `ADMIN_LOGINS` , `GEMINI_API_KEY` , `RESEND_API_KEY` , `NOTIFY_FROM` ,
`NOTIFY_ADMIN` , `GOOGLE_CLIENT_ID` , `GOOGLE_CLIENT_SECRET` , `GOOGLE_REDIRECT` , `COMM_INGEST_SECRET` .

All real values must be provisioned fresh for mobile; never copy secrets from a running deployment into the repo. The anon key is embedded in the client HTML by design (it is a public key) — but the mobile app should still fetch config at runtime, not hardcode.

2. Device capabilities used

Capability	Used?	Notes for mobile
File upload (chat attachments, documents)		Chat + Documents upload to Storage <code>uploads</code> . Mobile needs image/file picker + camera.
Camera / photo	Indirect	Only via the file picker today; no direct camera API.
Local storage / device id		FingerprintJS anon id + localStorage. Mobile: use a device-stable id + secure storage; respect ATT/privacy.
Geolocation	(faked)	The "VPN bar" and IPs are simulated , not real geolocation/VPN.
Push notifications		None — replaced by polling + in-app toasts. Add real push (APNs/FCM) for chat + lead alerts.
Biometric auth		None. Consider Face/Touch ID for the team login.
Clipboard / share		Not used.
Deep links	(one)	<code>index.html?sign=<agreementId></code> for agreement signing. Map to a mobile deep link / universal link.
Realtime/websockets		Polling only (see <code>04</code>).

3. Environments

- **Single environment** in practice: one Supabase project (`smddtvaewmmpuyvtuscb`) + one Vercel deployment. No separate staging/prod split is defined in the repo.
- **Hosts:** `betconstruct-ai.vercel.app` and the custom domain `betconstructai.com` .
- **Routing:** `vercel.json` rewrites `/login` → `/login.html` . Everything else is static file + `/api/*` functions.
- **Config:** secrets live in Vercel env vars (above). The client HTML embeds the Supabase URL + anon key inline.

Recommendation (OPEN_QUESTIONS): define real **dev / staging / prod** Supabase projects and separate keys before building the native app.

4. Accessibility

Current state (web demo) — **minimal**; mobile should treat these as requirements, not the baseline:

- **Language:** RU (primary), EN, HY — switchable in-app (`translatedOM()`), all LTR. Good multilingual base to carry over.
- **Contrast:** brand magenta on white and dark consent banner — verify WCAG AA on native.
- **Semantics:** icons are decorative inline SVG (`stroke="currentColor"`), mostly without text alternatives — **add labels / semantics** for screen readers.
- **Touch targets:** designed for ~390px width; verify 44×44pt minimums natively.
- **No** explicit ARIA roles, focus management, dynamic-type scaling, or reduced-motion handling in the web code — all to be built properly in Flutter (Semantics widgets, text scaling, high-contrast).
- **Theme:** single **light** theme only (no dark mode / `prefers-color-scheme`). Add a dark theme for mobile if desired (tokens in `design/tokens.json`).

5. Platform notes for the native rebuild

- **Auth:** replace storage-flag sessions with real auth (Supabase Auth / OAuth) + server-enforced RLS; never ship `service_role` to the client.
- **Realtime:** Supabase Realtime channels or push instead of 3.5 s polling.
- **LLM:** finalize the advisor provider (Gemini vs Claude Haiku 4.5) and keep the `{prompt, context, lang}` → `{text}` contract behind your own proxy so the key stays server-side.
- **Payments:** none exist; if real payments are ever added, App Store / Play gambling & payment policies apply — but today this is a **B2B catalog/CRM**, not a real-money app.
- **Email/Gmail:** the two-way email feature is unfinished; decide whether mobile needs it at all for v1.