

BetConstructAI — Design Token Reference (for native mobile rebuild)

Extracted verbatim from the `<style>` blocks of `index.html`, `admin.html`, `staff.html`, `login.html`, `privacy.html`. Every value below appears in the source CSS or inline styles — nothing is invented. Companion machine file: `tokens.json`.

1. Theme model — light only

There is a single light theme. No dark theme exists. None of the five files contain `prefers-color-scheme`, a `data-theme` attribute, `color-scheme`, or a light/dark toggle. The only place the string "dark/light mode" appears is inside a Russian marketing description of a product feature (`index.html` product copy), not a CSS mechanism. Accordingly every color's `dark` value in `tokens.json` is `null`.

- `admin.html` has a **language switcher** (RU / EN / HY), persisted to `localStorage['bc_alang']` and applied by re-translating the DOM — it changes text, never colors.
- `index.html`, `login.html`, `privacy.html` also have RU/EN(/HY) language toggles. Again text-only.
- So: build one light palette; there is no dark variant to mirror.

Per-file variable drift (important)

The brand system is consistent, but a few CSS variables were given different values per file. Treat `index.html` / `admin.html` as the canonical desktop/app palette; `staff.html` and the auth pages drift slightly.

Variable	index.html	admin.html	staff.html	login.html	privacy.html
<code>--mag</code>	<code>#A60063</code>	<code>#A60063</code>	<code>#d6006c</code>	<code>#A60063</code>	<code>#A60063</code>
<code>--mag-dk</code>	<code>#7a0049</code>	<code>#7a0049</code>	<code>—</code>	<code>#7a0049</code>	<code>#7a0049</code>
<code>--bg</code>	<code>#f3f4f6</code> → <code>#f5f6fa</code> (overridden)	<code>#f3f4f6</code>	<code>#f6f7fb</code>	<code>#f6f2f5</code>	<code>#f6f2f5</code>
<code>--card</code>	<code>#ffffff</code>	<code>#fff</code>	<code>#fff</code>	<code>#fff</code>	<code>#fff</code>

Variable	index.html	admin.html	staff.html	login.html	privacy.html
<code>--line</code>	<code>#e7e9ee</code> → <code>#eceedf4</code> (overridden)	<code>#e7e9ee</code>	<code>#e7e9f2</code>	<code>#e7e2e8</code>	<code>#e7e2e8</code>
<code>--text</code>	<code>#1d1f25</code>	<code>#1d1f25</code>	<code>#141631</code>	<code>#1b191d</code>	<code>#1b191d</code>
<code>--muted</code>	<code>#8b909b</code>	<code>#8b909b</code>	<code>#8b8fa7</code>	<code>#7d7280</code>	<code>#726a76</code>
<code>--blue</code>	<code>#2f6bd6</code>	<code>#2f6bd6</code>	<code>#4a44b8</code> (indigo)	<code>#2f6bd6</code>	<code>#2f6bd6</code>
<code>--green</code>	<code>#2fb877</code>	<code>#2fb877</code>	<code>#12a150</code>	—	—
<code>--amber</code>	— (uses <code>#c8901f</code> / <code>#c8860a</code> literals)	<code>#c8860a</code>	<code>#c98a00</code>	—	—
<code>--red</code> / <code>--live</code>	<code>--live #e2453f</code>	<code>--red #e2453f</code>	<code>#e5484d</code>	<code>#d63d38</code>	—

Note: `index.html` redefines `--bg` and `--line` a second time inside a "Premium light polish" block (`--bg:#f5f6fa; --line:#eceedf4;`), plus new tokens `--soft` , `--soft-h` , `--glow` . The later declaration wins. It also sets a redundant `--line:#ecdef0` then immediately `--line:#eceedf4` on the same line — `#eceedf4` is the effective value.

2. Color palette

2.1 Named brand / semantic colors (from CSS variables)

Token	Hex	Role	Used for
<code>mag</code>	<code>#A60063</code>	primary	Brand magenta. Buttons, active tabs/chips, icons, focus border, avatars.
<code>mag-staff</code>	<code>#d6006c</code>	primary	<code>--mag</code> in <code>staff.html</code> only (brighter).
<code>mag-dk</code>	<code>#7a0049</code>	primary	Dark brand shade; loyalty-card gradient end; privacy links.
<code>mag-grad-a</code>	<code>#c40073</code>	primary	Premium button/brand-card gradient start (<code>index</code> polish).
<code>mag-grad-b</code>	<code>#8a004f</code>	primary	Premium button/brand-card gradient end.
<code>bg</code>	<code>#f3f4f6</code>	background	Base app background (<code>admin</code>).

Token	Hex	Role	Used for
bg-index	#f5f6fa	background	index <code>--bg</code> override.
bg-staff	#f6f7fb	background	staff background.
bg-auth	#f6f2f5	background	login + privacy background (warm tint).
body-outer	#d9dce3 → #dcdfe8	background	The ground behind the 412px phone frame (index).
phone-bg	#f6f7fb	background	<code>.phone</code> surface (index).
card	#ffffff	surface	Cards, inputs, top/bottom bars.
line	#e7e9ee	border	Default 1px borders & dividers.
line-index	#eceedf4	border	index override.
line-staff	#e7e9f2	border	staff.
line-auth	#e7e2e8	border	login/privacy.
text	#1d1f25	text	Primary text (index/admin).
text-staff	#141631	text	staff text (also its toast bg).
text-auth	#1b191d	text	login/privacy text.
text-prose	#2f2a33	text	privacy body paragraphs/lists.
muted	#8b909b	muted	Secondary text, placeholders, inactive nav/tab.
muted-staff	#8b8fa7	muted	staff.
muted-login	#7d7280	muted	login.
muted-privacy	#726a76	muted	privacy.
blue	#2f6bd6	accent	Wordmark "AI", links, chevrons, secondary CTA (<code>.btn.b</code>).
green	#2fb877	success	Toggle ON, online status.
green-staff	#12a150	success	staff <code>--green</code> .
green-dk	#0f7a52	success	Success text on green tint (approved badge, done-step).

Token	Hex	Role	Used for
red	#e2453f	error	--live / --red ; live dots, rejected, danger button.
red-staff	#e5484d	error	staff.
red-login	#d63d38	error	login .err .
amber	#c8860a	warning	Pending status text, VPN connecting.
amber-staff	#c98a00	warning	staff.
amber-vpn	#c8901f	warning	index VPN connecting label.
indigo	#4a44b8	accent	Partner badge / step / resource-tag text; staff --blue .
orange-text	#b5700d	warning	"New offer" badge text.
icon-grey	#555555	muted	Header hamburger icon (.hbtn).

2.2 Literal (unnamed) colors used in CSS / inline styles

These have **no CSS variable** but recur across components. Names below are ours; hex values are exact.

Token	Hex	Where it appears
mag-tint	#faf2f6	Magenta ~6% tint: avatars, icon chips (.vlogo , .appc .lg , .acctav , .kpi .ic), active tiles/rows :active , .chip-admin , .rolec.on , .langopt.on , progress-bar track .bar , privacy .note /lang-active. Most-used tint in the system.
green-tint	#e3f6ee	Success chip/badge bg: .st.ap , .vchip , .vb.ap , .vicon.on , .stp.on , staff .btn.g .
indigo-tint	#eef0ff	Partner/step chip bg: .st.pt , .vb.pt , .rtag , .apx.on , .stp.cur .
amber-tint	#fdf3dc	Pending chip bg (.st.pend); VPN connecting icon chip.
orange-tint	#fff0e0	"New offer" chip bg (.st.nw , .vb.nw).
red-tint	#fdecea	Rejected chip / danger button bg (.st.rej , staff .btn.r).
toggle-off	#cfd3db	Switch/toggle OFF track (.tgl , .sw).

Token	Hex	Where it appears
<code>toggle-busy</code>	<code>#f2c14e</code>	Toggle busy track (<code>.tgl.busy</code>).
<code>toast-dark</code>	<code>#222222</code>	Toast bg (index & admin). staff toast bg = <code>#141631</code> .
<code>vpn-grad-a</code>	<code>#fbf1f7</code>	VPN bar gradient start (<code>.vpnbar</code> , <code>→ #fff</code>).
<code>vicon-bg</code>	<code>#ecef2</code>	Inactive VPN icon chip bg (<code>.vicon</code>).
<code>border-green</code>	<code>#b7e6d3</code>	Active VPN card border (<code>.vpncard.act</code>).
<code>border-green2</code>	<code>#bfe9d5</code>	Completed stepper border (<code>.stp.on</code>).
<code>border-indigo</code>	<code>#cdd2ff</code>	Current stepper / active resource-pill border (<code>.stp.cur</code> , <code>.apx.on</code>).
<code>note-border</code>	<code>#f0d8e6</code>	privacy note-box border.
<code>code-bg</code>	<code>#f0eaf0</code>	privacy inline <code>code</code> bg.
<code>border-soft1</code>	<code>#edeff5</code>	index premium soft-card border.
<code>border-soft2</code>	<code>#eef0f6</code>	index premium topbar/nav border.
<code>f2f4f8</code>	<code>#f2f4f8</code>	<code>.langopt:active</code> bg (index).
GDPR banner (index inline JS)		Dark consent banner injected at runtime:
<code>gdpr-bg</code>	<code>#1c1420</code>	Banner background.
<code>gdpr-text</code>	<code>#efe7ef</code>	Banner text.
<code>gdpr-border</code>	<code>#3a2c38</code>	Banner top border.
<code>gdpr-btn-border</code>	<code>#574a56</code>	"Essential only" button border.
<code>gdpr-link</code>	<code>#ff9ecb</code>	Privacy-policy link (pink on dark).

3. Typography

Font families (only two):

- **System stack** — `-apple-system,BlinkMacSystemFont,"Segoe UI",Roboto,Helvetica,Arial,sans-serif` — everything except code. (staff.html omits Helvetica/Arial: `..., 'Segoe UI',Roboto,sans-serif`.)
- **Monospace** — `ui-monospace,Menlo,monospace` (admin `.mono`) / `ui-monospace,monospace` (`.agrbody` in index/admin/staff).

Base body: index unspecified size (default 16 via components), admin `14px`, staff `15px/1.5`, login/privacy `15px`. Global smoothing on index body: `-webkit-font-smoothing:antialiased; font-weight:400; letter-spacing:.1px`.

Weight ladder (as authored): 400 body · 600 `b/strong`, labels, most emphasized UI (index "refined typography" block deliberately steps 800→600 for headings/buttons) · 700 semibold titles/pills/buttons in admin/staff · 800 brand wordmark, big headlines, KPI numbers, primary buttons in index.

Type scale & where each style is used

Style	Size (px)	Weight	Line-height	Letter-spacing	Used for
<code>displayBrand</code>	30	800	~36	0	Gate/splash wordmark <code>.gwm</code> .
<code>h1Legal</code>	27	700	1.15 (~31)	-.01em (-0.27)	Privacy page title <code>h1</code> .
<code>kpiNumber</code>	26	800	—	0	Admin KPI number <code>.kpi .n</code> (staff = 22).
<code>h1</code>	25	800	—	0	Home greeting <code>.welcome h1</code> .
<code>wordmarkAuth</code>	24	800	—	0	Login wordmark <code>.wm</code> .
<code>h2Page</code>	22	700	—	0	Detail-page titles <code>.page h2</code> (staff h2 = 20).
<code>h2</code>	20	800	—	-.3px	Section headers <code>.h2</code> , <code>.promo .t</code> ; admin <code>h2 =19</code> ; index polish → weight 600.
<code>title</code>	19	800	—	0	Top wordmark <code>.wm</code> , AI/promo card title <code>.aicard .t</code> .
<code>subtitleBar</code>	18	800	—	0	Admin wordmark, loyalty level <code>.loylv</code> , login logo mark.
<code>cardTitle</code>	17	600	—	0	Row card label <code>.rowcard .lft</code> .

Style	Size (px)	Weight	Line-height	Letter-spacing	Used for
<code>cardName</code>	16	700	—	0	Vendor/match names, <code>.search</code> , <code>.vtitle</code> , <code>.kcl</code> ; <code>card h3 =15</code> .
<code>body</code>	15	400	1.5 (~22)	.1px	Default text, inputs, textareas, list rows.
<code>bodySm</code>	14	400/600	—	0	Links <code>.h2 a</code> , <code>.lnk</code> rows; admin base body.
<code>sub</code>	13	400	—	0	Muted subtitles <code>.sub</code> , <code>.gsub</code> , <code>.gtag</code> .
<code>chip</code>	13	600	—	0	Filter chips <code>.chip</code> , tabs <code>.tab</code> (13.5), lang buttons.
<code>label</code>	12	600	—	0	Form labels <code>label</code> , <code>.page label</code> .
<code>button</code>	15	800	—	.2px	index <code>.btn</code> ; admin/staff <code>.btn</code> = 700 / 13.5–14.
<code>badge</code>	11	700	—	0	Status pills <code>.st</code> , <code>.vb</code> , <code>.pill</code> , <code>.kn</code> .
<code>overline</code>	11	700	—	.4px, UPPERCASE	<code>.loyhdr</code> , table <code>th</code> , <code>.fsec</code> .
<code>micro</code>	10.5	600	—	0	Bottom-nav labels <code>.nav div</code> , stepper captions, tiny meta.
<code>mono</code>	12.5	400	1.5–1.55	0	Agreement text <code>.agrbdy</code> , admin <code>.mono</code> .

Other discrete sizes present in source that fold into the above: 13.5, 12.5, 11.5, 10 (used for micro-meta, `.mt2` timestamps at 10.5, `.cbadge` at 10).

4. Spacing, radii, shadows, borders, motion

Spacing (recurring px paddings/gaps): 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 16, 18, 20, 22, 26. No formal 4- or 8-pt grid — values are hand-tuned; 8/10/11/12/14/16 dominate.

Radii (px): 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 18, 20; `20` doubles as the pill radius; `50%` / `9999` = full round (toggle knobs, avatars, FAB, `.fchk`). Cards cluster at 12–16; inputs 10–12; chips/badges 20 (pill).

Shadows (box-shadow):

Token	Value
<code>soft</code>	<code>0 1px 2px rgba(24,26,48,.04), 0 8px 22px rgba(24,26,60,.055)</code>
<code>soft-h (hover)</code>	<code>0 4px 10px rgba(24,26,48,.07), 0 16px 34px rgba(24,26,64,.10)</code>
<code>glow</code>	<code>0 10px 26px rgba(166,0,99,.28)</code>
<code>glowStrong</code>	<code>0 14px 32px rgba(166,0,99,.34)</code>
<code>fab</code>	<code>0 8px 22px rgba(166,0,99,.42), 0 2px 6px rgba(166,0,99,.3)</code>
<code>focusRing</code>	<code>0 0 0 3px rgba(166,0,99,.12)</code>
<code>topbar / navbar</code>	<code>0 6px 18px rgba(24,26,55,.05) / 0 -6px 18px ...</code>
<code>acctpop</code>	<code>0 8px 24px rgba(20,22,50,.13)</code>
<code>kcard</code>	<code>0 1px 3px rgba(20,22,50,.05)</code>
<code>authCard</code>	<code>0 8px 30px rgba(90,20,60,.07)</code>
<code>gdprBanner</code>	<code>0 -6px 24px rgba(0,0,0,.28)</code>
(see <code>tokens.json</code> for the full 22 shadows)	

Brand shadows are all magenta-tinted `rgba(166,0,99,...)` ; neutral elevation uses cool blue-grey `rgba(24,26,...)` / `rgba(20,22,50,...)` .

Borders: default `1px solid var(--line)` (hairline) everywhere. `2px` used for: active tab underline (`.tab.on border-bottom:2px solid var(--mag)`), check rings (`.fchk 2px`), current stepper. Dashed 1px only on `.step` divider (admin). Focus = `border-color:var(--mag)` + focus ring.

Motion / durations (transition & animation): 120ms (`.btn press`), 150ms (nav/input color), 180ms (premium hover), **200ms (default — toggles, most transitions)**, 300ms (toast fade), 400ms (loyalty progress width). Easing: mostly `ease` / default; index polish uses `ease` .

Opacity: 0.6 disabled button, 0.7 `.mt2` timestamp, 0.9 `.promo .d` , 0.92 `.loypts` , 0.96 `.loynext` , 0.45 inactive lang link, 0 hidden toast.

Icon sizes: icons are inline SVG (`svg.i{width:1em;height:1em}`) sized by `font-size` . Recurring em→px: 13/15 (small inline), 18/20 (list/nav), 21–22 (card leading icons, `.nav =21`), 26 (FAB), 28 (quick-access tile `.qtile`). All icons: `viewBox 0 0 24 24` , `fill:none`; `stroke:currentColor`;

`stroke-width:1.7; stroke-linecap:round; stroke-linejoin:round` (admin IC set) — a consistent 1.7-weight outline icon style.

5. Component inventory

Every reusable UI component found in the CSS/markup. "Tokens" lists the design tokens each leans on.

Buttons — `.btn` (+ variants `.sec .g .b .r .sm`, plus `.btn2`, `.pbtn`, `.kbtn`, `.acctbtn`, `.langbtn`)

- **Anatomy:** full-width (index: `height:46px`, `radius:13`) or inline (admin: `padding:10px 15px`, `radius:10`) flex row, centered, `gap 6–7`, optional leading SVG. Bold label.
- **Variants:** default = solid `mag` (index uses `linear-gradient(135deg,#c40073,#8a004f) + glow`); `.sec` = white/ card bg + line border + text color; `.g` = green (admin `--green`; staff `green-tint / green-dk`); `.b` = blue; `.r` = red (admin `--red`; staff `red-tint`); `.sm` = compact (`padding 7px 11px`, `12.5px`). `.btn2` = small magenta gradient pill (`radius 10`). `.pbtn` = borderless bottom-bar text button in `mag`.
- **States:** `:active` → `transform:scale(.98–.99)` (index gradient btn → `translateY(1px)` + reduced shadow); `[disabled]` → `opacity .6` (login).
- **Tokens:** `mag / gradient`, `card`, `line`, `text`, radii 10–13, button type, `glow / btnActive` shadow, duration `fast`.

Inputs / forms — `input[type=text|email|password]`, `textarea`, `select`, `label`, `label.chk`, `.pw`

- **Anatomy:** `1px solid var(--line)`, radius 10–12, padding 10–12, `font:inherit`, bg `card`. Label above: `12px/600 muted`. `select` strips native chrome (`appearance:none`). `.pw` wraps password input with an absolute eye toggle. `label.chk` = inline checkbox row (`accent-color:var(--mag)`, `18px box`).
- **States:** `:focus` → `outline:none; border-color:var(--mag)`; index adds `focusRing (0 0 0 3px rgba(166,0,99,.12))` and a 150ms transition.
- **Tokens:** `line`, `card`, `text`, `muted`, radii 10–12, `body / label` type, `focusRing`, `mag`.

Cards — `.card`, `.rowcard`, `.kpi`, `.appc`, `.kcard`, `.vcard`, `.lcard`, `.lmatch`, `.rec`, `.gcard`, `.doccard`, `.pcat`

- **Base card:** bg `card`, `1px solid line`, radius 12–16, padding 13–22, `margin-bottom ~12–14`. index premium adds `soft shadow` + hover `soft-h` + `translateY(-1px)`.

- `.kpi` (metric tile): radius 13, icon chip `.ic` (34px, `mag-tint` bg, `mag` icon, radius 9) + big number (`kpiNumber`) + muted label. Laid out in `.kpis` responsive grid `repeat(auto-fit,minmax(150px,1fr))` (staff 130px).
- `.appc` (application card): header row with 42px logo chip (`mag-tint`), name/meta, expandable `.det` detail block.
- `.kcard` (kanban card): white, radius 11, `kcard` shadow, id/client/responsible/last-msg + `.krow` footer; lives in `.kcol` columns (min 230px, `bg` fill) inside `.kanban` horizontal scroller with `.kn` count badge.
- `.lmatch` (live match card, index): min-width 258 horizontal-scroll card; league line with live dot, score in `green`, odds pill `.od`.
- `.lcard` / `.qtile` (grid tiles): 2-col / 4-col grids, leading `mag` icon, `:active` → `mag-tint`.
- `.pcat` (collapsible category, index): header `.hd` + hidden `.body`, chevron rotates 180° on `.open`.
- `.gcard` (gate/login card): max 360, radius 18, padding 22.
- **Tokens:** `card`, `line`, `mag` / `mag-tint`, `muted`, radii 11–18, `soft` / `soft-h`, `cardName` / `cardTitle` type.

Chips / pills / badges — `.chip`, `.st` (`.pend` `.ap` `.pt` `.rej` `.nw`), `.vb` (`.ap` `.pt` `.nw` `.geo`), `.pill`, `.tag`, `.rtag`, `.apx`, `.vchip`, `.chip-admin`, `.kn`, `.cbadge`

- `.chip` (filter): pill (radius 20), `card` bg + `line` border, 13/600 muted; `.on` = `mag` fill (index: gradient) white text; horizontal-scroll `.chips` row.
- `.st` / `.vb` (status badge): tiny pill radius 20, 11/700, colored tint bg + dark text — `pend` =amber-tint/amber, `ap` =green-tint/green-dk, `pt` =indigo-tint/indigo, `rej` =red-tint/red, `nw` =orange-tint/orange-text, `geo` = `bg` /muted. Optional leading 13px icon.
- `.pill` / `.tag`: neutral outline pill/tag on `bg` fill (roles, path steps).
- `.rtag` / `.apx`: resource/pipeline tags — indigo-tint/indigo when active (`.apx.on` adds `border-indigo`).
- `.vchip`: green "connected" chip (green-tint bg, green text, radius 9).
- `.cbadge`: absolute count bubble, `mag` bg, white, min-16px, shadow.
- **Tokens:** tint colors, `badge` / `chip` type, radius 20 (pill) / 9, `mag`.

Tabs — `.tabs` / `.tab` (admin), `.tabs button` (staff)

- **Anatomy:** horizontal-scroll bar on `card`, hidden scrollbar, sticky (`top:57px` admin). Each tab: padding 13×14, 13.5/700 muted, `border-bottom:2px solid transparent`, leading 17px icon.
- **States:** `.on` → `mag` text + `border-bottom-color:mag` (admin) / white bg + `line` border, top-rounded (staff).
- **Tokens:** `card`, `line`, `mag`, `muted`, `tabActive` border, `chip` type.

Toggles / switches — `.tgl` (index), `.sw` (admin)

- **Anatomy:** track 52×30 (`.tgl`) / 44×26 (`.sw`), radius 20, knob `b` white circle radius 50% with `toggleKnob` shadow, 200ms slide.
- **States:** OFF = `toggle-off` `#cfd3db` ; ON = `green` (knob slides right +22/+18px); `.busy` = `toggle-busy` `#f2c14e` (index only).
- **Tokens:** `toggle-off` , `green` , `toggle-busy` , `card` , `toggleKnob` shadow, duration `base` .

Tables — `.mtab` , **plain** `table / th / td` , **responsive** `table.cardtab` (**admin**)

- **Anatomy:** full-width `border-collapse` , 12.5–13px, `th` muted 11px (uppercase for plain `table`), `td` padding 8–10 with `1px` `line` bottom border, last row borderless.
- **Responsive** (`≤640px` , `.cardtab`): each `<tr>` becomes a bordered card (radius 12, `card` `bg`); header row hidden; each `td` becomes a label/value flex row using `td::before{content:attr(data-label)}` ; first cell is the card title (16px, 2px bottom border).
- **Tokens:** `line` , `muted` , `text` , `overline / sub` type, radius 12.

List rows — `.fbar` , `.lnk` , `.jrow` , `.step` , `.flowrow` , `.krow`

- `.fbar` (stat/list row): flex row, label + optional `.bar` progress + trailing value/button; `margin-bottom` 9 .
- `.lnk` (nav link row, index): space-between, `1px` `line` top divider, leading `mag` icon `.nm` , trailing blue chevron `.go` ; `:active` → `mag-tint` ; first child no top border.
- `.jrow` (journey row) & `.step` (dashed timeline): small 12.5px rows with muted timestamps; `.step` uses `border-bottom:1px` dashed `line` + green check icon.
- `.flowrow` (checklist row): 26px circular `.fchk` (2px `line` ring) + label; `.done` → check filled `green-dk` , label struck-through muted.
- **Tokens:** `line` , `mag / mag-tint` , `blue` , `green-dk` , `muted` , `bodySm` type.

Progress / meters — `.bar` , `.kprog` , `.loybar` , `.stepper / .stp` , `.apipe`

- `.bar / .kprog` : thin track (5–9px) radius 4–20 on `mag-tint / line / bg` , inner `span` fill `mag` .
- `.loybar` (loyalty): 9px translucent white track on brand gradient, white fill, 400ms width transition.
- `.stepper / .stp` : horizontal step boxes (min 92px) on `bg` ; `.on` = `green-tint` + `border-green2` , number badge `green-dk` ; `.cur` = `indigo-tint` + `border-indigo` , badge `mag` .
- `.apipe` : inline pipeline of `.apx` pills joined by `i` separators.
- **Tokens:** `mag` , `mag-tint` , `bg` , `line` , tint/border colors, radii 4–20, duration `progress` .

Toasts — `.toast`

- **Anatomy:** fixed, centered (`left:50%; translateX(-50%)`), bottom 20–90px, dark `bg` (`toast-dark` `#222` , staff `text-staff` `#141631`), white 13.5px, radius 11–12, `opacity` 0 → `.show/.on` =1 over 300ms; `pointer-events:none` ; auto-hides after ~2000–2200ms (JS).

- **Tokens:** `toast-dark` , radius 11–12, duration `toast` .

Chat bubbles — `.msg` (index), `.msg` (admin/staff) + `.cimg` / `.chatimg` , `.chatbox` , `.cmgr`

- **Anatomy:** `.chatbox` scroll container (`bg` fill, `line` border, radius 11–12, column flex, gap 9). Bubbles max 78–80% width, padding 9×12, radius 13, 13.5–14px.
- **Variants:** incoming (`.b` / `.v`) = `card` `bg` + `line` border, left-aligned; outgoing (`.c` / `.s`) = `mag` `bg`, white, right-aligned. `.mt2` = 10.5px timestamp, opacity .7. Images `.cimg` / `.chatimg` capped ~210px, radius 10. `.cmgr` = manager header row with 42px avatar (`mag-tint`) + online dot (`green`).
- **Tokens:** `card` , `line` , `mag` , `bg` , radius 10–13, `body` type.

Avatars & icon chips — `.acctav` , `.cmgr .av` , `.vlogo` , `.vicon` , `.loybadge` , `.appc .lg` , `.kpi .ic` , `.bloglo`

- Rounded squares (radius 9–13) or circles (50%), `mag-tint` `bg` + `mag` icon/initial (or brand-gradient logo). Sizes 23 → 56px. `.vicon` toggles state colors: neutral `vicon-bg` , on `green-tint` / `green` , connecting `amber-tint` / `amber-vpn` . `.bloglo` in index gets a subtle magenta shadow badge.

Loyalty card — `.loycard` (+ `.loytop` `.loybadge` `.loylv` `.loypts` `.loyxp` `.loybar` `.loynext` , table `.loyhdr` / `.loyrow`)

- **Anatomy:** hero card, `linear-gradient(135deg,var(--mag),var(--mag-dk))` , white text, radius 16, `glow` -style shadow `0 8px 22px rgba(166,0,99,.28)` . Badge tile (translucent white .18), level title (`subtitleBar`), points, XP pill (translucent white .2), progress bar, next-tier row. Inner white `.btn` (magenta text). Tier table: `.loyhdr` overline header, `.loyrow` grid rows with `.on` highlight (`rgba(166,0,99,.09)`) and a magenta ● marker.
- **Tokens:** `mag` / `mag-dk` gradient, white alphas, radius 16, `overline` / `subtitleBar` type.

Loaders / progress states

- No spinner component in CSS. "Loading/animation" is limited to width-transition progress bars (`.loybar` , `.bar`) and opacity/transform transitions. Online status shown via colored ● text + `green` .

Bottom nav & bars — `.nav` , `.botbar` , `.topbar` , `.vpnbar` , `.top` , **FAB** `.fab`

- `.nav` (bottom tab bar, index): `card` `bg`, `1px line` / `border-soft2` top + `navbar` shadow, `space-around` , safe-area bottom padding; each item column icon(21px)+ `micro` label, muted, `.on` → `mag` .
- `.botbar` : secondary bottom action bar (`pbtn` magenta text buttons), `card` `bg`, top border.

- `.topbar (index)` / `.top (admin/staff/privacy)`: sticky header on `card /white`, `1px line` bottom (index adds `topbar` shadow), holds wordmark + lang switch + account menu; safe-area top padding (index).
- `.vpnbar (index)`: sticky sub-header, `linear-gradient(90deg,#fbf1f7,#fff)`, left status label (`mag` icon) + right status text `.vst2` colored by state (`.on` green, `.cn` amber-vpn, `.off` muted).
- `.fab`: fixed circular 54px action button, `mag` bg, white 26px icon, `fab` glow shadow, anchored to phone right edge; `right:max(16px,calc(50vw - 190px))`.
- **Tokens:** `card`, `line / border-soft2`, `mag / mag-tint`, `muted`, `green`, `vpn-grad-a`, `micro` type, `topbar / navbar / fab` shadows.

Wordmark — `.wm` / `.gwm` / `.blogo`

- **"BetConstructAI"**: `.b` span = `mag`, plain "Construct" = `text`, `.a` span = `blue`. Sizes 17 (privacy) → 30 (gate). staff/login render `.blogo` as a magenta rounded-square badge with white "B".

Account menu — `.acctwrap` / `.acctbtn` / `.acctpop (admin)`

- Trigger button (`card` bg, `line` border, radius 10, 23px `mag-tint` avatar). Popover `.acctpop` (radius 12, `acctpop` shadow, min 214px) toggled `.on`; header block + link rows (`:hover` bg), `.danger` link in `red`.

Language switcher — `.langseg / .lg`, `.langdd / .langbtn / .langlist / .langopt (index)`, `.langsw a (admin)`, `.lang a (login/privacy)`

- Segmented (`langseg`: `card` bg, `line` border, radius 10; `.lg.active` → `mag` bg white) or dropdown (`langbtn` + absolute `langlist`, radius 12, elevated shadow, flag + label `langopt` rows, `.on` → `mag / mag-tint`). Plain-text RU/EN/HY links elsewhere (active = `mag` + `mag-tint`, or opacity 1 vs .45).

Banners — `.banner` / `.banner.mag (admin)`

- Bordered strip (radius 12) with title/sub + trailing switch; `.mag` variant = full `mag` bg, white text.

GDPR consent banner (index, injected via JS)

- Fixed bottom dark bar (`gdpr-bg` `#1c1420`, `gdpr-text`, `gdpr-border` top, `gdprBanner` shadow), text + pink policy link (`gdpr-link`), two buttons: "Essential only" (transparent, `gdpr-btn-border`) and "Accept" (`#A60063` solid). Safe-area bottom padding. The only dark-surfaced component in the app.

6. Quick guidance for the native rebuild

- Ship **one light theme**. Map `mag #A60063` = primary, `blue #2f6bd6` = secondary accent, `green #2fb877 / #0f7a52` = success, `red #e2453f` = error, `amber #c8860a` = warning, `indigo #4a44b8` = partner/info.
- Normalize the per-file drift: pick canonical `--mag #A60063` (note staff's `#d6006c`), `--bg #f5f6fa`, `--line #ecef4`, `--text #1d1f25`, `--muted #8b909b`.
- Status system is a fixed 5-tint set: tint bg + darker text (green/indigo/amber/orange/red). Reuse `mag-tint #faf2f6` as the universal "brand-selected/hover" surface.
- Elevation: `soft / soft-h` neutral shadows for cards, magenta `glow` for brand CTAs. Corner radii cluster: inputs 10–12, cards 12–16, pills 20, circles full.
- Icons: 1.7-weight, round-cap, 24-grid outline SVGs sized 13–28px.