Tellus Power Green

TELLUS POWER GREEN ADVERTISEMENT AC CHARGER

7.2 kW and 22 kW

FEATURES

- CE Certified
- RFID Reader
- Supports OCPP 1.6J
- Full HD LED 55'' Video Display
- Wide range of power capacities
- Integrated High Output Speakers
- Sleek, Carbon Steel IP55 Enclosure
- HD Digital Signage Multi-Media Display
- Simultaneous display of images and videos

Tellus Power Green
AC Charger
Specifications

Rated Power	2 x 7.2kW	2 x 22kW
Product #	TP-EVVA-220-2D	TP-EVVA-380-2B
Input / Output voltage	208/240VAC Or 415VAC(3P) || 50 - 60 Hz	
Power Connections	Requires (2) Independent 40A branch circuits per port	Requires (2) Independent 3x40A branch circuits per port
Output Current	(2) 1 x 32A Continuous	(2) 3 x 32A Continuous
Weight	440.92 lbs. (200Kg)	
Working Temperature	4°F to +50°F (-20°C to +55°C)	
Relative Humidity	5% to 95% Non-Condensing	
Altitude	<9,842' (<3000m)	
IP Rating	IP54	
Connector Standard	Dual Type2 Dual J1772	
RFID system	Active Multi-Standard	
Communication Protocol	OCPP 1.6J	
Internet	Ethernet	
Charging Cable	(2) 18' Charging cables	
User interface	(2) 3.5" Back-lit monochrome, non-reflective, heated, UV-coated with ambient light sensor	
Installation Type	Pedestal	
Material	Housing: Carbon steel	
Dimensions	77.16" H x 43.62" W x 16.85" D (1960 x 1108 x 428mm)	
Compliance standard	EN 61851-1:2011, EN 61000-6-1:2007, EN 61000-6-3:2007/A1:2011/AC:2012	
Certification	CE || GB	
Safety	Over Current, Short Circuit , Surge Protection, Leakage Current Protection	

CE