CITYPULSE 360°
A Data-Driven 360° View of Vellore City for Smarter Urban Planning

Manthena Sri Adithya
School of Computer Science and Engineering
Vellore Institute of Technology Vellore, India
manthena.sriadithya2024@vitstudent.ac.in

Yuvaraj N
School of Computer Science and Engineering
Vellore Institute of Technology
Vellore, India
yuvaraj.n@vit.ac.in

***Abstract*—Urban areas generate information related to transportation, waste management, water services, environmental conditions, public facilities, and infrastructure development. Analyzing these dimensions separately can make it difficult to understand the overall condition of a city and identify differences between locations. CityPulse 360 is an interactive urban analytics dashboard developed using R and Shiny to demonstrate how multidimensional data visualization can support the exploration of urban indicators.**

The project focuses on eight demonstration locations in Vellore, Tamil Nadu, and six urban dimensions: Mobility, Cleanliness, Water, Environment, Public Facilities, and Development. The dashboard combines interactive charts, geographical maps, heatmaps, location comparisons, statistical summaries, and data-quality validation. It supports the exploration of indicator values across locations and dates, with several spatial visualization methods and selectable map styles.

The current implementation uses reproducible synthetic demonstration data rather than verified municipal observations. Consequently, the project demonstrates the analytical workflow, visualization design, and interactive functionality that could be applied to real urban data. It does not claim to measure actual city performance. The project highlights the importance of data quality, geographical context, suitable visual encodings, and responsible interpretation in advanced data visualization.

Keywords: Urban analytics, R, Shiny, interactive visualization, geospatial analysis, Leaflet, Plotly, data quality, smart cities.

1 . INTRODUCTION

Smart-city planning involves the collection and interpretation of information about transportation, environmental conditions, sanitation, water supply, public services, and infrastructure. These areas are interconnected. For example, traffic congestion may affect travel time and air quality, while the availability of public facilities may influence accessibility and the quality of urban life.

Traditional reports and static charts often provide only a limited view of such information. They may not allow users to compare multiple locations, change analytical indicators, examine temporal patterns, or explore the geographical distribution of values interactively.

Advanced data visualization provides methods for converting structured observations into meaningful visual representations. Interactive dashboards allow users to filter information, compare indicators, investigate unusual observations, and move between statistical and geographical views.

2. PROBLEM STATEMENT

Urban information can be distributed across different categories, locations, and reporting periods. Without an integrated analytical interface, it can be difficult to compare indicators, identify spatial differences, explore trends, and assess whether the underlying dataset is sufficiently reliable for interpretation.

The problem addressed by this case study is the design and implementation of an interactive visualization system that brings multiple urban dimensions into a unified dashboard. The system should support geographical exploration, comparison of locations, examination of indicator distributions, temporal analysis, and basic data-quality validation.

3 . OBJECTIVES

The primary objective is to develop an interactive urban analytics dashboard that demonstrates advanced statistical and geospatial visualization techniques.

The specific objectives are:

1. To develop an interactive R Shiny application for urban data exploration.
2. To organize urban indicators into meaningful analytical dimensions.
3. To visualize spatial differences between selected locations.
4. To analyze temporal patterns using historical observations.
5. To implement multiple statistical and geospatial visualization techniques.
6. To identify data-quality problems before visualization.
7. To provide interactive filters for locations, indicators, dimensions, and dates.
8. To improve the interpretation of urban data through visual summaries.
9. To support the export of selected data and analytical outputs where implemented.
10. To establish a foundation for future real-time monitoring and predictive analysis.

4 . Data Description

CityPulse 360 focuses on interactive exploration of urban indicators rather than automated decision-making or official municipal monitoring.

The project covers the following areas:

Mobility: Traffic counts, travel times, and other transportation-related indicators where available.

Cleanliness: Cleanliness scores, waste-related indicators, and related observations where available.


Water: Water-related measurements and service indicators where available.

Environment: Environmental measurements such as air-quality indicators, where included in the dataset.

Public Facilities: Indicators related to the availability or condition of public facilities.

Development: Indicators representing infrastructure or urban development.

The dashboard can compare locations, analyze changes over time, and display spatial patterns. Its conclusions depend on the quality, coverage, and representativeness of the supplied data.



5 . Dataset Description

The project uses a structured urban dataset organized by analytical dimension, location, indicator, date, value, unit, and source.

5.1 Dataset structure

Attribute	Description
dimension	Urban category such as Mobility or Environment
location	Name of the location associated with the observation
indicator	The measurement or variable being recorded
date	Date of the observation
value	Numerical value of the indicator
unit	Measurement unit associated with the value
source	Origin or description of the data source

5.2 Illustrative and Demonstration

The demonstration dataset may contain 1,008 records, representing six dimensions, eight locations, and 21 monthly observation periods.

The record count follows:

Number of records = 6 × 8 × 21 = 1,008.

This count is valid when each dimension-location-month combination has exactly one record. If multiple indicators are stored for each combination, the dataset structure and expected record count must be adjusted accordingly.

The locations may include Katpadi Junction, VIT Area, Gandhi Nagar, Sathuvachari, Bagayam, Thorapadi, Town Centre, and CMC Area.

The demonstration data should be explicitly identified as synthetic unless each observation has been obtained from a verifiable source. Approximate coordinates should not be treated as surveyed or official geographical boundaries.

5.3 Data source and reliability

For the demonstration version, the dataset can be generated synthetically to test filtering, charting, mapping, and validation functionality. For real-world analysis, the dataset should be replaced or supplemented with verified information from appropriate municipal departments, official open-data portals, monitoring systems, or documented surveys.

Each source should be recorded so that users can understand where the information originated and whether it is suitable for decision-making.

6 . Data Cleaning and Processing

Data preparation is necessary to ensure that visualizations are meaningful and consistent.

6.1 Missing-value detection

The system should identify missing values in important fields such as location, dimension, indicator, date, value, and unit. Missing numerical values should not automatically be replaced with zero because zero may represent a valid observation.

6.2 Duplicate-record detection

Records with identical identifying fields should be checked for duplication. The system should distinguish accidental duplicates from legitimate repeated measurements.

6.3 Date validation

Date values should be converted into a consistent date format. Invalid dates, unsupported formats, and observations outside the intended time range should be reported.

6.4 Value validation

Numerical values should be checked for non-numeric entries, impossible values, and values outside defined indicator ranges. Validation rules should be specific to each indicator.

6.5 Unit consistency

Measurements using different units should be identified before comparison. For example, travel times recorded in seconds and minutes should be converted to a common unit when appropriate.

6.6 File compatibility

Uploaded files should be checked for required columns, supported formats, valid data types, and readable contents. Informative error messages should explain what needs to be corrected when a file is incompatible.

6.7 Data-quality reporting

A data-quality summary should display the number of missing values, duplicate records, invalid dates, unexpected values, inconsistent units, and records requiring review. Correcting an issue should not silently alter the original data without informing the user.

7 . Technologies used

7.1 R programming language

R provides the programming environment for data processing, statistical summaries, validation, and visualization.

7.2 Shiny

Shiny supports the creation of an interactive web application using R. It connects user inputs, data processing, and output components.

7.3 Plotly

Plotly provides interactive charts with hover information, zooming, and other exploration features.

7.4 Leaflet

Leaflet supports interactive geographical maps with markers, popups, map layers, and spatial navigation. Suitable tile providers can be used to present different map styles.

7.5 DT

DT provides interactive tables for searching, sorting, paging, and examining records.

7.6 HTML, CSS and JavaScript

These technologies support the dashboard's layout, appearance, responsive design, and additional browser-side interactions.

8 . Dashboard Architecture

The proposed system follows a modular workflow.

1. **Data input:** Load the dataset from a CSV file or another supported source.
2. **Validation:** Check the structure, data types, dates, values, units, and duplicate records.
3. **Preprocessing:** Standardize fields and prepare data for analysis.
4. **Filtering:** Apply selected dimensions, locations, indicators, and date ranges.
5. **Analysis:** Calculate summaries, comparisons, trends, and other required statistics.
6. **Visualization:** Display charts, maps, summary indicators, and data tables.
7. **Interpretation:** Allow users to explore patterns and identify observations requiring further investigation.
8. **Reporting:** Export selected data or analytical outputs when the relevant functionality is implemented.

The modular structure makes it easier to maintain the application and add new analytical features.

9 . Visualization Techniques

9.1 Summary cards

Summary cards present selected totals, averages, record counts, or data-quality statistics. They provide a quick overview before detailed analysis.



Figure ~ 1 : This fig. displays the summary of the dashboard

9.2 Bar charts

Bar charts compare values across locations, dimensions, or indicators. They are useful for identifying differences between categories.




Figure ~ 2 : This fig. displays the vertical bar chart




Figure ~ 3 : This fig. displays the horizontal bar graph

9.3 Time-series charts

Time-series charts show changes in an indicator over time. They can help identify increases, decreases, recurring patterns, and unusual observations.





Figure ~ 4 : This fig. displays the time line series with trends and anamolies



9.4 Scatter plots


Scatter plots display relationships between two numerical variables. They can help identify possible associations and outliers, but a visible relationship does not establish causation.



Figure ~ 5 : This fig. displays the scatter plot chart of the cities

9.5 Heatmaps

Heatmaps use color intensity to represent numerical values across locations, indicators, or time periods. They are useful for recognizing patterns in multidimensional data.



9.6 Correlation analysis

A correlation matrix can summarize the strength and direction of linear relationships between selected numerical variables. Correlations should be interpreted carefully, especially when variables measure different concepts.

9.7 Interactive data tables

Tables allow users to inspect individual records, search for particular locations, and verify values underlying a chart.


9.8 Proportional-symbol maps

Proportional-symbol maps represent numerical values through marker sizes. Larger or smaller markers can communicate differences between locations, provided the scale is clearly explained.



9.9 Marker clustering


Marker clustering combines nearby map markers at wider zoom levels to reduce overlap. Users can zoom in to examine individual locations.



9.10 Spatial heatmaps


Spatial heatmaps display areas of concentrated

observations or weighted values. They should not be interpreted as exact geographical boundaries or proof of causation.



9.11 Hexagonal binning

Hexagonal binning groups spatial observations into hexagonal cells and summarizes the values in each cell. It can reveal spatial concentration while reducing the visual clutter associated with large numbers of individual points.



9.12 Multiple basemap styles


The geospatial module can offer street, satellite, terrain, light, dark, or hybrid map styles where supported by the configured tile providers. Attribution, usage restrictions, and network availability should be considered.






9.13 Full-screen map viewing

A full-screen map option can provide more space for geographical exploration. Users should be able to return to the normal dashboard layout without losing their selected filters.



9.14 Additional spatial visualizations

Depending on the implemented code and available data, the dashboard may include distance matrices, flow maps, spider or radar charts, temporal trajectories, and other comparative visualizations. Each technique should be used only when its input data and analytical purpose are appropriate.




9.15 Box Plot

A box plot is a statistical visualization used to summarize the distribution of numerical data and identify potential outliers. In the CityPulse 360 dashboard, box plots can be used to compare urban indicators such as traffic counts, travel times, environmental measurements, and cleanliness scores

across different locations.

A box plot consists of five important statistical values: minimum, first quartile (Q1), median, third quartile (Q3), and maximum, excluding separately identified outliers where applicable. The box represents the interquartile range (IQR), which is the difference between Q3 and Q1. The line inside the box indicates the median, while the whiskers represent the range defined by the selected box-plot convention. Individual points beyond the whiskers may indicate potential outliers.



10 . Interactive Features

The main interactive features of CityPulse 360 are designed to let users investigate the dataset from different perspectives.

Location selection: Users can choose a location and examine its available indicators.

Dimension filtering: Users can focus on a particular urban category, such as Mobility or Environment.

Indicator selection: Users can select a numerical variable for comparison or temporal analysis.

Date filtering: Users can restrict the analysis to a selected period.

Interactive charts: Hover details, zooming, and selection tools can help users examine individual values.

Map exploration: Users can zoom, pan, inspect markers, and change the basemap style where supported.

Data inspection: A table can display the filtered records used for analysis.

Data-quality feedback: Validation messages should identify problems and suggest corrective actions.



11. Analytical Questions

CityPulse 360 is designed to help users explore questions such as:

1. How do selected urban indicators differ across locations?
2. How does a particular indicator change over the observation period?
3. Which locations have comparatively high or low recorded values?
4. Are there visible relationships between selected numerical indicators?
5. Where are spatial observations concentrated?
6. Are unusual values associated with particular locations or dates?
7. How many records contain missing values, duplicate entries, or invalid fields?
8. How does the selection of a date range affect location-wise comparisons?
9. Which observations require further verification before interpretation?
10. How can interactive maps complement statistical charts?

12. Results and Interpretation

The dashboard is intended to demonstrate how interactive visualizations can support the exploration of multidimensional urban data.

Bar charts enable comparisons between locations. Time-series charts reveal changes across the observation period. Heatmaps provide an overview of multiple indicators, while scatter plots help explore relationships between numerical variables.

Geospatial views connect numerical observations with locations. Proportional symbols can show differences in recorded magnitude, clustering can reduce marker overlap, and hexagonal binning can summarize spatial concentrations. Multiple basemap styles can help users interpret the geographical context.

Data-quality summaries are equally important because a visualization may appear convincing even when the underlying records contain errors. The validation module therefore supports responsible interpretation by identifying issues that require correction or review.

For a synthetic demonstration dataset, the results should be described as observations about the generated data and the application's functionality. They should not be interpreted as evidence of actual traffic conditions, environmental quality, water availability, or municipal service performance in Vellore.

13 .Key Findings

The design of CityPulse 360 supports the following methodological observations:

- Combining statistical and geographical views provides complementary perspectives on the same dataset.
- Interactive filters allow users to focus on specific indicators and time periods.
- Time-series visualization makes temporal changes easier to examine than a large raw table.
- Heatmaps and comparative charts help users explore patterns across multiple dimensions.
- Data-quality checks are necessary before interpreting unusual values or drawing conclusions.
- Map accuracy depends on the quality of coordinates and the suitability of the basemap.
- Synthetic data is useful for testing application functionality but cannot establish real-world urban conditions.

14 . Recommendations

Based on the design and analytical capabilities of the CityPulse 360 dashboard, the following recommendations are proposed to improve urban data analysis, visualization quality, and decision-making for Vellore city.

1. Integrate Verified and Real-Time Data

The dashboard should be connected to reliable data sources such as municipal records, traffic monitoring systems, environmental sensors, water supply departments, and public facility databases. Real-time or regularly updated information would improve the accuracy and usefulness of urban monitoring. Until such sources are integrated, the existing synthetic dataset should be treated only as demonstration data.

2. Improve Data Quality and Validation

A comprehensive data validation module should be maintained to identify duplicate records, missing observations, invalid dates, unexpected indicator values, inconsistent measurement units, and incompatible uploaded files. The system should provide clear error messages and data-quality summaries so that users can correct problems before generating visualizations.

3. Enhance Geospatial Analysis

The dashboard should provide multiple basemap options, including street maps, satellite imagery, terrain maps, and dark-themed maps. Features such as location search, zoom controls, full-screen map viewing, location labels, marker clustering, heatmaps, and hexagonal binning can help users identify spatial patterns and areas requiring attention. All displayed coordinates and location boundaries should be verified before operational use.

4. Support Early Identification of Urban Issues

Analytical rules can be developed to flag locations with unusually high traffic counts, low cleanliness scores, water-related concerns, or poor environmental indicators. Thresholds should be established using verified standards or approved municipal guidelines rather than arbitrary values. Alerts should be interpreted as indicators for further investigation, not as confirmed evidence of a problem.

5. Strengthen Comparative and Temporal Analysis

The dashboard should support comparisons between locations, urban dimensions, and time periods. Monthly trends, percentage changes, moving averages, and historical comparisons can help users identify recurring patterns and determine whether conditions are improving or deteriorating. The date range and measurement units should remain consistent during comparisons.

6. Improve User Interaction and Accessibility

The interface should include clear navigation, readable

labels, high-contrast text, responsive layouts, meaningful tooltips, and simple filters. Users should be able to select a location, indicator, date range, and visualization type without navigating through complicated menus. Color should not be the only way to communicate important information; labels and symbols should also be provided.

7. Enable Data Export and Reporting

Users should be able to export filtered datasets, data-quality reports, charts, and summary statistics in suitable formats such as CSV and PDF. A report-generation feature could summarize the selected location, time period, indicators, key observations, and data limitations to support academic analysis and municipal planning.

8. Incorporate Predictive Analytics Carefully

Future versions could incorporate forecasting methods to estimate traffic demand, environmental trends, or other urban indicators. Predictive outputs should be evaluated using appropriate validation methods and historical observations. Predictions should clearly indicate their uncertainty and should not be presented as reliable forecasts until tested on verified data.

9. Establish Privacy and Security Measures

If the dashboard later processes sensitive information or data from individual users, suitable access controls, secure data handling, and privacy protection should be implemented. Public-facing dashboards should display aggregated information wherever possible and avoid exposing personally identifiable information.

10. Evaluate the Dashboard with Real Users

The application should be tested with students, researchers, urban planners, and relevant municipal stakeholders. Feedback should be collected on usability, map performance, clarity of visualizations, loading time, and the usefulness of analytical summaries. The results can guide improvements to the dashboard's functionality and presentation.

Overall, these recommendations can help transform CityPulse 360 from a demonstration-oriented visualization application into a more reliable urban analytics platform. The most important initial priorities are integrating verified data, maintaining strong data-quality checks, validating geospatial information, and presenting analytical findings clearly and responsibly.

15. Limitations and Future Work

The project has the following limitations:

1. The demonstration observations are synthetic and do not represent verified municipal measurements.
2. The eight geographical coordinates are approximate and require verification before real-world use.
3. Some spatial methods are illustrative models rather than analyses based on official geographical boundaries or measured movement networks.
4. Generated observations do not capture the full complexity of urban systems, including population, weather, land use, road networks, and seasonal effects.
5. Indicator-specific ranges are generation parameters and are not necessarily official operational thresholds.
6. A monthly demonstration timeline cannot establish the frequency or completeness of real municipal monitoring.
7. External map tiles require an internet connection and remain subject to provider availability and usage policies.
8. Data-quality checks detect configured problems but cannot independently establish the truthfulness of source records.
9. Averages across indicators with different units can be mathematically computable but conceptually misleading.
10. The dashboard is a prototype and has not been established as a validated municipal decision-support system.

Future Work:

- Replace synthetic observations with verified municipal or government open data.
- Add documented data provenance, source URLs, collection dates, and update frequency.
- Validate coordinates and use official geographical boundaries where available.
- Add real road-network analysis and routing data for travel-time and accessibility studies.
- Improve missing-observation detection according to the expected reporting frequency of each indicator.
- Add statistical summaries, correlation analysis, and appropriate normalization methods.
- Include uncertainty indicators and confidence intervals where the data supports them.
- Develop indicator-specific thresholds based on credible standards.
- Add downloadable analytical reports and filtered datasets.
- Improve performance for larger datasets and document

external map-tile dependencies.

- Evaluate the dashboard with real users to assess usability, readability, and interpretability.

16 . CONCLUSION

CityPulse 360 demonstrates the application of advanced data visualization techniques to a multidimensional urban analytics problem. Developed using R, Shiny, Plotly, Leaflet, and DT, the dashboard integrates interactive charts, geospatial exploration, temporal views, distribution analysis, heatmaps, ranking tables, and data-quality validation.

The project illustrates how different visual encodings can help users explore urban indicators from multiple perspectives. It also demonstrates the importance of appropriate scales, readable labels, geographical context, consistent units, and transparent data preparation.

The most important conclusion is that effective urban visualization requires both suitable visual design and reliable underlying data. Although the current implementation uses synthetic demonstration observations, it provides a foundation that can be extended using verified municipal datasets. With appropriate validation and real geographical information, the approach could support exploratory analysis of urban services, mobility, environmental conditions, and infrastructure.

17 .REFERENCES AND TOOLS

[1] *R Core Team. R: A Language and Environment for Statistical Computing. R Foundation for Statistical Computing.*

[2] *Posit. Shiny: Web Application Framework for R.*

[3] *Plotly Technologies Inc. Plotly R Open Source Graphing Library Documentation.*

[4] *Leaflet. Leaflet: An Open-Source JavaScript Library for Interactive Maps.*

[5] *DataTables. DataTables Documentation.*

[6] *OpenStreetMap contributors. OpenStreetMap.*

[7] *Esri. ArcGIS Basemap and World Imagery Services Documentation.*

[8] *CityPulse 360 project source code: CityPulse360_Geospatial_Styles_Enhanced(1).R.*