




SBMS Introduction








4

--Full project re-deployment: Any small change requires re-deploying the entire application.

Microservices Architecture


- > Microservices is not a programming language, framework, or an API.
- > Microservices is an architectural design pattern.
- > Microservices suggests developing an application by breaking down its functionalities into loosely coupled, independently deployable units.
- > Instead of a single monolithic application, a Microservices architecture uses multiple REST APIs, where each REST - API is considered as one Microservice.
- Note: One REST API is called one Microservice.
- > Microservices can be used with any programming language or technology, not just Java.


	<p>Advantages:</p> <ul style="list-style-type: none">--> Loosely Coupled: Microservices are independent of each other, making it easy to modify or replace.--> Easy to maintain: Each service can be managed separately.--> Faster development: Development teams can work on different services simultaneously.--> Quick deployment: Services can be deployed independently.--> Faster releases: New features can be rolled out faster.--> Less downtime: Service failures do not affect the entire system.--> Technology independence: Different services can be developed using different technologies. <p>Disadvantages:</p> <ul style="list-style-type: none">--> Bounded Context: Deciding how to divide the system into services can be challenging.--> Complex configuration: Microservices require a lot of configuration and management.--> Visibility: It may be harder to trace and monitor issues across many services.--> Pack of cards: Multiple services may complicate the system's overall structure.
	




7

- Service Registry: acts as a database that keeps track of all the available services in the system.
- It registers each service, allowing the discovery of available services by number of instances.
- Eureka Server is commonly used as service registry.







The primary responsibilities of the API Gateway include:

- Routing: The API Gateway routes the incoming requests to the appropriate REST API (Microservice) based on the request URL, method, and other parameters.


Filters:

- Authentication and authorization checks
- Logging

Note: Zuul Proxy is no longer supported by the latest versions of Spring Boot. Spring Cloud Gateway is the recommended and actively supported solution for creating API Gateways

Cloud Config Server:
--> Cloud Config Server is used to separate the application code and its configuration properties. This helps in externalizing the configuration of your application so that it can be centrally managed and updated without modifying the application code.

--> Externalizing Configuration: With Config Server, we can externalize the configuration properties into YAML files (e.g., application.yml) which can be managed outside the main application, typically in a version-controlled



--> Cloud Config Server is used to separate the application code and its configuration properties. This helps in externalizing the configuration of your application so that it can be centrally managed and updated without modifying the application code.

--> Externalizing Configuration: With Config Server, we can externalize the configuration properties into YAML files (e.g., application.yml) which can be managed outside the main application, typically in a version-controlled repository like GitHub.

Kafka: Kafka is a distributed messaging platform that is used to manage real-time data feeds. In a microservices architecture, Kafka is ideal for real-time streaming of data.