

Carrier / method	Exact / attempted; 95% interval	Exact goodput; 95% interval	Encode phase (s)	Decode phase (s)	Charged pair (s)	Failure
UTF-8 / Fixed	20/20 [83.16, 100.00]%	3.3247 [3.3247, 3.3247]	45.63	45.31	123.33	None
UTF-8 / Gated	20/20 [83.16, 100.00]%	3.1246 [3.1054, 3.1441]	57.31	57.30	147.29	None
UTF-8 / A1	0/20 [0.00, 16.84]%	0.0000 [0.0000, 0.0000]	398.15	396.01	826.57	Token-cap capacity
PNG / Fixed	20/20 [83.16, 100.00]%	0.2505 [0.2473, 0.2535]	85.27	85.31	178.18	None
PNG / Gated	20/20 [83.16, 100.00]%	0.2505 [0.2473, 0.2535]	85.29	85.65	178.53	None
PNG / A1	20/20 [83.16, 100.00]%	0.2505 [0.2473, 0.2535]	85.59	85.77	179.01	None

V2 recovery, useful rate and original runtime. Original held-out V2 timings, including unsuccessful attempts; later graph timings are not substituted. Goodput units are bits/token for UTF-8 and bits/channel value for PNG; PNG rates multiply by three to obtain bits/pixel. Recovery uses accepted 95% Clopper–Pearson bounds; goodput uses accepted 2,000-draw stratified payload-group percentile intervals, $n = 20$ groups per direction. Incomplete/unauthenticated outcomes have zero exact goodput. Encode/decode phases exclude cold loading and other occupied time; the charged pair includes both full fresh processes, loading and teardown. These nested measurements are not additive charges. All 20 failures are A1 text capacity outcomes, with no authenticated payload.