```
mysql> use manuu;
Database changed
mysql> create table marks( name varchar(15),dept varchar(6),marks int);
Query OK, 0 rows affected (0.01 sec)

mysql> INSERT INTO marks VALUES('rahul','CSE',98),('harish','ECE',87),('fadil','EEE',72),('kavin','IT',80);
Query OK, 4 rows affected (0.01 sec)
Records: 4  Duplicates: 0  Warnings: 0

mysql> select * from marks;
+--------+------+-------+
| name   | dept | marks |
+--------+------+-------+
| rahul  | CSE  |    98 |
| harish | ECE  |    87 |
| fadil  | EEE  |    72 |
| kavin  | IT   |    80 |
+--------+------+-------+
4 rows in set (0.00 sec)
```

```
mysql> SELECT dept, COUNT(*)
    -> FROM marks
    -> GROUP BY dept;
+------+----------+
| dept | COUNT(*) |
+------+----------+
| CSE  |        2 |
| ECE  |        1 |
| EEE  |        2 |
| IT   |        4 |
+------+----------+
4 rows in set (0.00 sec)

mysql> SELECT dept, AVG(marks)
    -> FROM marks
    -> GROUP BY dept
    -> HAVING AVG(marks) > 80;
+------+------------+
| dept | AVG(marks) |
+------+------------+
| CSE  |    83.0000 |
| ECE  |    87.0000 |
| IT   |    89.7500 |
+------+------------+
3 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM marks
    -> ORDER BY marks ASC;
+--------+------+-------+
| name   | dept | marks |
+--------+------+-------+
| balaji | CSE  |    68 |
| fadil  | EEE  |    72 |
| kavin  | IT   |    80 |
| surya  | EEE  |    83 |
| harish | ECE  |    87 |
| manu   | IT   |    90 |
| arsath | IT   |    92 |
| gokul  | IT   |    97 |
| rahul  | CSE  |    98 |
+--------+------+-------+
9 rows in set (0.00 sec)
```

name	dept	marks
rahul	CSE	98
gokul	IT	97
arsath	IT	92
manu	IT	90
harish	ECE	87
surya	EEE	83
kavin	IT	80
fadil	EEE	72
balaji	CSE	68

9 rows in set (0.00 sec)