```
mysql> use manu;
Database changed
mysql> create table mark1 ( name varchar(15),dept varchar(6),marks int);
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> INSERT INTO mark1 VALUES('rahul','CSE',98),('harish','ECE',87),('fadil','EEE',72),('kavin','IT',80),('balaji','CSE',68),('gokul','IT',97),('surya','EEE',83),('manu','IT',90),('arsath','IT',92);
Query OK, 9 rows affected (0.00 sec)
Records: 9  Duplicates: 0  Warnings: 0
```

```
mysql> select * from mark1;
+--------+------+-------+
| name   | dept | marks |
+--------+------+-------+
| rahul  | CSE  |    98 |
| harish | ECE  |    87 |
| fadil  | EEE  |    72 |
| kavin  | IT   |    80 |
| balaji | CSE  |    68 |
| gokul  | IT   |    97 |
| surya  | EEE  |    83 |
| manu   | IT   |    90 |
| arsath | IT   |    92 |
+--------+------+-------+
9 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM mark1
    -> WHERE marks > (SELECT AVG(marks) FROM mark1);
+--------+------+-------+
| name   | dept | marks |
+--------+------+-------+
| rahul  | CSE  |    98 |
| harish | ECE  |    87 |
| gokul  | IT   |    97 |
| manu   | IT   |    90 |
| arsath | IT   |    92 |
+--------+------+-------+
5 rows in set (0.00 sec)
```

```
mysql> SELECT name FROM mark1 WHERE (dept,marks) IN (SELECT dept,MAX(marks) FROM mark1 GROUP BY dept);
+--------+
| name   |
+--------+
| rahul  |
| harish |
| gokul  |
| surya  |
+--------+
```