

BASIC FRONTEND DEVELOPMENT INTERVIEW CHEATSHEET(FRESHERS)

Quetsion-1 What are Variables? In how many ways they can be declared? - Containers that stores values - Automatically declared, var, let, const - Till 2015 there was only var declaration type	Quetsion-2 Difference between var, let and const. - DASH
Quetsion-3 Difference between Static typing and Dynamic Typing. - Explicitly Declaration - JS determines the Data Type at Runtime based on the value it is currently holding, In Statically Types languages there is Type Check at Compile Time, if mismatched	Quetsion-4 What are different Primitive Data Types in JavaScript? - There are 7 Primitive Data Types - String, Numbers, Boolean, BigInt, Null, undefined, Symbol - Undefined represents the absence of a value to a variable whereas Null represents the absence of reference of an Object
Quetsion-5 Difference between == and === . - Compares Value and one Compares Value + Datatype	Question-6 What is a Debugger in JavaScript? - The Debugger in browser must be activated in order to debug the code - The remaining section of the code should stop executing while we go to the next line while debugging
Question-7 Explain Implicit Type Coercion.	Quetsion-8 What are Numbers in JS? Explain NaN Property. - Primitive Datatype, with or without decimal, Extra Large and Extra Small number are represented by Exponential Notation - 64 Bit Floating Point - NaN represents a number which is not legal, like "Apple" – 2, typeof is Number, to check whether a number is legal or not, we can use isNaN()
Quetsion-9 What are IIFE? - IIFE stands for Immediately Invoking Function Expression are self-invoking functions - It should be followed with () - It's an anonymous function - Why the two parenthesis are important	Question-10 What are BOM's in JavaScript? - Allows JS talk to the Browser, Consists many objects that represents various aspects of the browser, not tied to specific site - Created at the time of Browser Initialisation in the Memory by BRE - No Hierarchy like DOM, all the objects are independently created - Types- Window, Screen, Location, History, Navigator
Quetsion-11 What is Strict Mode in JavaScript? - The purpose of Strict Mode - It can be either added at the top of script or function - All the Errors will be thrown, including Silent Errors, Debug Easy - Variables can't be used without declaring, Duplicating a parameter is not allowed, Octal Numeric, Escape Character, JS keywords can't be used	Quetsion-12 What is Currying in JavaScript? - Represent Data/Properties of Component that changes over time - We change data using Hooks - When State Changes the React Component Re-renders - useState Hook used for managing the state object, it has property called initialValue and a function that changes the initialValue
Quetsion-13 What are advantages of using External JavaScript. - Introduces in React 16.8 to provide and manage state object and side effects in functional components without class comp - Before hooks, functional components were called stateless - Examples	Quetsion-14 What is DOM in JavaScript? - When HTML Document is parsed, the Browser Rendering Engine creates DOM Objects in Heap based on the structure and content - These DOM Object represents Elements, Attributes, Text Nodes, Comment Nodes - Once DOM Objects are created, developers use Dom API to access, modify, add or remove these objects dynamically using JS.
Quetsion-15	Quetsion-16

Quetsion-17	Question-18
Question-19 What is an Execution Context in JS? - Everything in JavaScript is wrapped inside Execution Context, which is an abstract concept (can be treated as a container) that holds the whole information about the environment within which the current JavaScript code is being executed. - When a programme is run a Global Execution Context gets created. Now, an Execution Context has two components and JavaScript code gets executed in two phases: Memory Allocation and Code Execution.	Question-20 What is Hoisting in JS? - Hoisting in JavaScript is a mechanism in which Variables and Function Declaration is moved to top of their scopes before moving to second phase of Code Execution. This phase is known as Memory Allocation Phase. - The Variables declared with var are assigned undefined and functions declared as Classical Functions are assigned with Function Definition in JS Object whereas Function declared as Function Expression and Arrow Function are assigned with value undefined if they are declared with var.
Question-21 What are Scopes in JS? - Scopes refers to the accessibility of variables, functions and objects in the particular part of the code during runtime. - JS have two types of Scopes: Global Scope and Local Scope. - Global Scope Variables are declared outside any function and block, whereas Local Scope Variables are declared within a Function or Block like if statement Block.	Question-22 Why Block are used in JS? - Blocks are used in JS where it expects one statement at the place of multiple statements.
Quetsion-23 What is Shadowing? - Shadowing in JS occurs when a variable declared in a particular scope has the same name as the variable in any of its outer scope. - As a result the variable in the inner scope shadows the variable in the outer scope.	Question-24 What is Lexical Environment? - Lexical Environment is a structure that holds identifier-variable mapping. It is created when an Execution Context is created. It provides access to the variable and functions of the current function, and the variables and functions of the parent scopes as well creating the scope chain. - It has two components: A Reference of the Lexical Environment of Parent and the Current Environment Record. - It is created in the Code Execution Phase.
Question-25 Explain Scope Chain in JS? - The scope chain is a series of nested lexical environments, each linked to its outer lexical environment. - When a function is invoked, the JavaScript engine looks up the scope chain to resolve the value of a variable. - This chain allows the JavaScript engine to look for variables or functions in the current scope and then in the outer scopes, if necessary, until it finds the identifier being accessed.	Question-26 What is a Temporal Dead Zone? - When variables are declared using let and const, they are also hoisted just like var in the but they are not given value "undefined" in the place holder. They are given values when the Code Execution takes place. - For a time being they are in TDZ. The temporal dead zone is the time between the declaration of a variable(hoisted in the MA(P1) and its assignment in CE(P2).
Question-27 Explain Closures in JavaScript?	Question-28 Explain First Class Function.
