1. **Java is a ..... language.**

A. weakly typed

B. strongly typed ✔

C. moderate typed

D. None of these

Answer & Solution | Discuss in Board | Save for Later

2. How many primitive data types are there in Java?

A. 6

B. 7

C. 8 ✔

D. 9

Answer & Solution | Discuss in Board | Save for Later

3. In Java byte, short, int and long all of these are

A. signed ✔

B. unsigned ✘

C. Both of the above

D. None of these

Answer & Solution | Discuss in Board | Save for Later

4. Size of int in Java is

A. 16 bit

B. 32 bit ✔

C. 64 bit

D. Depends on execution environment

Answer & Solution | Discuss in Board | Save for Later

5. **The smallest integer type is ..... and its size is ..... bits.**

A. short, 8

B. byte, 8 ✔

C. short, 16

D. short, 16

Answer & Solution | Discuss in Board | Save for Later

6. **Size of float and double in Java is**

A. ◉ **32 and 64** ✔

B. ○ 64 and 64

C. ○ 32 and 32

D. ○ 64 and 32

Answer & Solution | Discuss in Board | Save for Later

7. **Determine output:**

```
class A{
        public static void main(String args[]){
                int x;
                x = 10;
                if(x == 10){
                        int y = 20;
                        System.out.print("x and y: "+ x + "
" + y);
                        y = x*2;
                }
                y = 100;
                System.out.print("x and y: " + x + " " +
y);
        }
}
```

A. ○ 10 20 10 100

B. ○ 10 20 10 20

C. ○ 10 20 10 10

D. ◉ **Error** ✔

8. **Automatic type conversion in Java takes place when**

A. Two type are compatible and size of destination type is shorter than source type.

B. Two type are compatible and size of destination type is equal of source type.

C. **Two type are compatible and size of destination type is larger than source type.**

D. All of the above

Answer & Solution | Discuss in Board | Save for Later

9. **Which of the following automatic type conversion will be possible?**

A. short to int

B. byte to int

C. int to long

D. long to int

Answer & Solution | Discuss in Board | Save for Later

10. What is the output of the following program?

```
class A{
        public static void main(String args[]){
                byte b;
                int i = 258;
                double d = 325.59;

                b = (byte) i;
                System.out.print(b);

                i = (int) d;
                System.out.print(i);

                b = (byte) d;
                System.out.print(b);
        }
}
```

A. 258 325 325

B. 258 326 326

C. **2 325 69** ✔

D. Error

11. Determine output:

```
public class Test {
        static void test(float x){
                System.out.print("float");
        }

        static void test(double x){
                System.out.print("double");
        }

        public static void main(String[] args){
                test(99.9);
        }
}
```

A. ○ float

B. ◉ double ✔

C. ○ Compilation Error

D. ○ Exception is thrown at runtime

12. The following fraction of code

```
double STATIC = 2.5 ;
System.out.println( STATIC );
```

A. Prints 2.5 ✔

B. Rraises an error as STATIC is used as a variable which is a keyword

C. Raises an exception

D. None of these

Answer & Solution | Discuss in Board | Save for Later

13. What would be the output of the following fraction of code ?

```
int Integer = 34 ;
char String = 'S' ;
System.out.print( Integer ) ;
System.out.print( String ) ;
```

A. Does not compile as Integer and String are API class names.

B. Throws exception.

C. 34

D. S

E. 34 S ✔

Answer & Solution | Discuss in Board | Save for Later

14. What is the output of the following program?

```
public class Test{
        static int x  = 10 ;
        public static void main(String[] a){
                Test test = new Test( ) ;
                Test test1 = new Test( ) ;
                test.x  +=  1 ;
                System.out.println(  test.x + test1.x ) ;
        }
}
```

A. 20

B. 21

C. 22 ✔

D. Compilation Error

E. Throws Exception

Answer & Solution | Discuss in Board | Save for Later

15. What will be output of the following program code?

```
public class Test{
        public static void main(String[] a){
                short x = 10;
                x = x*5;
                System.out.print(x);
        }
}
```

A. 50

B. 10

C. Compilation Error ✔

D. None of these

Answer & Solution | Discuss in Board | Save for Later

16. Determine output:

```
public class Test{
        int i = 34;
        public static void main(String args[]){
                Test t1 = new Test();
                Test t2 = new Test();
                t1.i = 65;
                System.out.print(t1.i);
                System.out.print(t2.i);
        }
}
```

A. 34 34

B. 65 34 ✔

C. 65 65

D. 34 65

Answer & Solution | Discuss in Board | Save for Later

17. The following program:

```
public class Test{
        static boolean isOK;
        public static void main(String args[]){
                System.out.print(isOK);
        }
}
```

A. Prints true

B. Prints false ✔

C. Will not compile as boolean is not initialized

D. Will not compile as boolean can never be static

Answer & Solution | Discuss in Board | Save for Later

18. In Java, the word true is .....

A. A Java keyword

B. A Boolean literal ✔

C. Same as value 1

D. Same as value 0

Answer & Solution | Discuss in Board | Save for Later

19. What will the output of the following program?

```
public class Test{
      public static void main(String args[]){
            float f = (1 / 4) * 10;
            int i = Math.round(f);
            System.out.println(i);
      }
}
```

A. 2

B. 0 ✔

C. 3

D. 2.5

E. 25

Answer & Solution | Discuss in Board | Save for Later

20. What is the output for the below code ?

```
class A{
      int k;
      boolean istrue;
      static int p;
      public void printValue(){
            System.out.print(k);
            System.out.print(istrue);
            System.out.print(p);
      }
}

public class Test{
      public static void main(String argv[]){
            A a = new A();
            a.printValue();
      }
}
```

A. ◉ **0 false 0** ✔

B. ○ 0 true 0

C. ○ 0 0 0