1. **Determine output:**

```
public class Test{
        public static void main(String args[]){
                int i;
                for(i = 1; i < 6; i++){
                        if(i > 3) continue ;
                }
                System.out.println(i);
        }
}
```

A. 2

B. 3

C. 4

D. 5 ✗

E. 6 ✓

2. **In java, ... can only test for equality, where as ..... can evaluate any type of the Boolean expression.**

A. ◉ **switch, if** ✔

B. ○ **if, switch**

C. ○ **if, break**

D. ○ **continue, if**

```java
int i = 0, j = 5;
for (; (j++<10 && i<3); i++) {
    System.out.println(i + " " + j);
}
System.out.println(i + " " + j);
```

```java
public class Test{
        public static void main(String args[]){
                int i = 0, j = 5 ;
                for( ; (i < 3) && (j++ < 10) ; i++ ){
                        System.out.print(" " + i + " " + j
);
                }
                System.out.print(" " + i + " " + j );
        }
}
```

- ◉ 0 6 1 7 2 8 3 8
- ○ 0 6 1 7 2 8 3 9
- ○ 0 6 1 5 2 5 3 5

4. **Consider the following program written in Java.**

```java
class Test{
        public static void main(String args[]){
                int x=7;
                if(x==2); // Note the semicolon
                System.out.println("NumberSeven");
                System.out.println("NotSeven");
        }
}
```

What would the output of the program be?

A. ◉ **NumberSeven NotSeven** ✔

B. ○ NumberSeven

C. ○ NotSeven

D. ○ Error

E. ○ 7

5. **Determine output:**

```
public class Test{
        public static void main(String args[]){
                int i, j;
                for(i=1, j=0;i<10;i++) j += i;
                System.out.println(i);
        }
}
```

A. ○ 10 ✔

B. ○ 11

C. ○ 9

D. ○ 20

E. ○ None of these

6. **What will be the output?**

```
public class Test{
        public static void main(String[] args){
                int x=10, y=0;
                if(x && y){
                        System.out.print("TRUE");
                }
                else{
                        System.out.print("FALSE");
                }
        }
}
```

A. FALSE

B. TRUE

C. **Compilation Error** ✔

D. Runtime Error

7. **What will be the value of y after execution of switch statement?**

```
public class Test{
        public static void main(String[] args){
                int x = 3, y = 4;
                switch(x + 3){
                        case 6: y = 0;
                        case 7: y = 1;
                        default: y += 1;
                }
        }
}
```

A. 1

B. 2 ✔

C. 3

D. 4

E. 0

8. **What is the printout of the following switch statement?**

```
char ch = 'a';
switch (ch){
      case 'a':
      case 'A': System.out.print(ch); break;
      case 'b':
      case 'B': System.out.print(ch); break;
      case 'c':
      case 'C': System.out.print(ch); break;
      case 'd':
      case 'D': System.out.print(ch);
}
```

A. ○ abcd

B. ○ aa ✗

C. ◉ a ✓

D. ○ ab

E. ○ abc

9. How many times will the following code print "Welcome to Examveda"?

```
int count = 0;
do {
      System.out.println("Welcome to Examveda");
      count++;
} while (count < 10);
```

A. 8

B. 9

C. 10 ✔

D. 11

E. 0

10. Choose the correct statement in context of the following program code.

```
public class Test{
      public static void main(String[] args){
            double sum = 0;
            for(double d = 0; d < 10;){
                  d += 0.1;
                  sum += sum + d;
            }
      }
}
```

A. ○ The program has a compile error because the adjustment is missing in the for loop.

B. ○ The program has a compile error because the control variable in the for loop cannot be of the double type.

C. ○ The program runs in an infinite loop because d<10 would always be true.

D. ◉ **The program compiles and runs fine.** ✔

11. Which of the following for loops will be an infinite loop?

A. ○ for(; ;)

B. ○ for(i=0 ; i<1; i--)

C. ○ for(i=0; ; i++)

D. ◉ All of the above ✔

12. What will be the result of the following code?

```
public class Test{
      static public void main(String args[]){ //line 2
            int i, j;
            for(i=0; i<3; i++){
                  for(j=1; j<4; j++){
                        i%=j;
                        System.out.println(j);
                  }
            }
      }
}
```

A. 1 2 3 1

B. 1 2 3 2

C. **Repeatedly print 1 2 3 and cause infinite loop.** ✔

D. Compilation fails because of line 2

E. None of these

13. What is the value of a[1] after the following code is executed?

```
int[] a = {0, 2, 4, 1, 3};
for(int i = 0; i < a.length; i++)
      a[i] = a[(a[i] + 3) % a.length];
```

A. 0

B. 1

C. 2

D. 3

E. 4

Answer & Solution | Discuss in Board | Save for Later

15. What all gets printed when the following program is compiled and run.

```
public class Test{
      public static void main(String args[]){
            int i, j=1;
            i = (j>1)?2:1;
            switch(i){
                  case 0: System.out.println(0); break;
                  case 1: System.out.println(1);
                  case 2: System.out.println(2); break;
                  case 3: System.out.println(3); break;
            }
      }
}
```

A. ○ 0

B. ○ 1

C. ○ 2

D. ○ 3

E. ◉ 1 2 ✔

16. What all gets printed when the following program is compiled and run?

```
public class Test{
      public static void main(String args[]){
            int i=0, j=2;
            do{
                  i=++i;
                  j--;
            }while(j>0);
            System.out.println(i);
      }
}
```

A. 0

B. 1

C. 2 ✔

D. The program does not compile because of statement "i=++i;"

E. None of these

17. What will be the output?

```
public class Test{
      public static void main(String args[]){
            int i = 1;
            do{
                  i--;
            }while(i > 2);
            System.out.println(i);
      }
}
```

A. 1

B. 2

C. -1

D. 0 ✓

E. None of these

18.

```
1. public class Test{
2.       public static void main(String [] args){
3.             int x = 0;
4.             // insert code here
5.             do{ } while(x++ < y);
6.             System.out.println(x);
7.       }
8. }
```

Which option, inserted at line 4, produces the output 12?

A. int y = x;

B. int y = 10;

C. **int y = 11;** ✔

D. int y = 12; ✘

E. None of the above will allow compilation to succeed.

19. What will be the result?

```
1.  int i = 10;
2.  while(i++ <= 10){
3.          i++;
4.  }
5.  System.out.print(i);
```

A. 10 ✗

B. 11 ✗

C. 12 ✗

D. 13 ✓

E. Line 5 will be never reached. ✗

Answer & Solution | Discuss in Board | Save for Later