

Model	Variables		Results											
			Day-ahead Forecasting of Total Daily Load											
			24h - Daily Aggregation					Horizon = 1 Day						
			MAPE (%)	MAE (kWh)	RMSE (kWh)	R2	Params (k)	MAPE (%)	MAE (kWh)	RMSE (kWh)	R2	Params (k)		
MLP	y		6.46 ± 0.19	308 ± 13	546 ± 9	0.864	172.72	6.87 ± 0.23	323 ± 12	580 ± 16	0.846	11.32		
	y + H		6.63 ± 0.13	315 ± 6	554 ± 8	0.859	124.07	-	-	-	-	-		
	y + DT		4.45 ± 0.05	231 ± 3	370 ± 5	0.937	126.70	4.80 ± 0.23	246 ± 12	373 ± 14	0.936	110.78		
	y + AC		6.56 ± 0.35	314 ± 24	565 ± 20	0.854	349.59	7.02 ± 0.12	323 ± 5	608 ± 13	0.831	421.19		
	y + H + DT		4.48 ± 0.11	234 ± 6	377 ± 9	0.935	144.99	-	-	-	-	-		
	y + H + AC		6.56 ± 0.21	310 ± 12	560 ± 16	0.856	137.82	-	-	-	-	-		
	y + DT + AC		4.38 ± 0.11	228 ± 6	350 ± 10	0.944	238.70	4.6 ± 0.07	236 ± 3	355 ± 5	0.942	41.47		
	y + H + DT + AC		4.56 ± 0.27	236 ± 16	373 ± 19	0.936	228.95	-	-	-	-	-		
	y + Profile-1		4.01 ± 0.12	210 ± 7	311 ± 8	0.956	86.59	4.55 ± 0.15	232 ± 7	333 ± 9	0.949	33.63		
	y + Profile-2		4.10 ± 0.10	214 ± 5	317 ± 6	0.954	240.23	4.41 ± 0.05	226 ± 2	329 ± 4	0.950	21.90		
NBEATsx	y		6.60 ± 0.17	314 ± 12	547 ± 8	0.863	2772.26	6.44 ± 0.08	302 ± 4	560 ± 6	0.856	810.52		
	y + H		6.81 ± 0.25	327 ± 17	539 ± 12	0.867	3945.39	-	-	-	-	-		
	y + DT		4.86 ± 0.21	252 ± 12	375 ± 12	0.936	4041.00	4.94 ± 0.16	251 ± 6	376 ± 7	0.935	1633.31		
	y + AC		6.44 ± 0.21	306 ± 10	529 ± 13	0.872	4041.00	6.29 ± 0.17	294 ± 7	525 ± 7	0.874	1651.23		
	y + H + DT		5.27 ± 0.23	271 ± 13	393 ± 14	0.929	4283.70	-	-	-	-	-		
	y + H + AC		6.80 ± 0.18	326 ± 11	556 ± 11	0.858	3369.89	-	-	-	-	-		
	y + DT + AC		4.63 ± 0.17	240 ± 9	353 ± 12	0.943	3955.94	4.85 ± 0.14	245 ± 6	363 ± 7	0.940	1699.88		
	y + H + DT + AC		4.93 ± 0.29	254 ± 15	370 ± 17	0.937	4418.70	-	-	-	-	-		
	y + Profile-1		4.42 ± 0.10	227 ± 5	316 ± 6	0.954	2812.52	4.61 ± 0.2	234 ± 9	338 ± 9	0.948	1648.67		
	y + Profile-2		4.28 ± 0.12	224 ± 6	343 ± 6	0.946	3107.04	4.45 ± 0.1	227 ± 4	326 ± 5	0.951	1648.67		
NHITS	y		6.63 ± 0.16	313 ± 9	554 ± 10	0.859	2817.57	6.46 ± 0.13	302 ± 6	552 ± 8	0.860	2423.37		
	y + H		6.55 ± 0.23	313 ± 12	544 ± 12	0.864	3702.88	-	-	-	-	-		
	y + DT		4.80 ± 0.16	249 ± 9	373 ± 10	0.936	3014.18	4.60 ± 0.09	236 ± 4	369 ± 5	0.938	2397.21		
	y + AC		6.66 ± 0.35	316 ± 17	535 ± 21	0.869	3100.27	6.33 ± 0.08	297 ± 4	535 ± 5	0.869	2468.95		
	y + H + DT		4.68 ± 0.11	240 ± 5	364 ± 7	0.939	3100.12	-	-	-	-	-		
	y + H + AC		6.65 ± 0.22	322 ± 13	539 ± 12	0.867	4206.77	-	-	-	-	-		
	y + DT + AC		4.85 ± 0.18	250 ± 10	382 ± 9	0.933	3321.45	4.84 ± 0.12	247 ± 5	372 ± 7	0.937	2512.48		
	y + H + DT + AC		4.98 ± 0.27	257 ± 14	372 ± 17	0.937	3136.92	-	-	-	-	-		
	y + Profile-1		4.37 ± 0.16	227 ± 9	321 ± 11	0.953	3272.45	4.42 ± 0.10	227 ± 4	329 ± 4	0.950	2472.54		
	y + Profile-2		4.26 ± 0.12	223 ± 6	330 ± 7	0.950	3014.18	4.31 ± 0.09	223 ± 4	325 ± 6	0.952	2472.54		
TIDE	y		8.18 ± 0.04	398 ± 2	662 ± 2	0.800	1335.14	8.97 ± 0.05	427 ± 2	684 ± 4	0.786	290.63		
	y + H		8.17 ± 0.03	398 ± 2	662 ± 2	0.800	4517.37	-	-	-	-	-		
	y + DT		8.17 ± 0.03	398 ± 2	662 ± 2	0.800	4517.37	8.96 ± 0.10	429 ± 3	690 ± 4	0.782	315.18		
	y + AC		8.18 ± 0.04	399 ± 2	659 ± 2	0.801	3665.60	8.95 ± 0.07	429 ± 2	689 ± 4	0.783	737.32		
	y + H + DT		8.17 ± 0.04	398 ± 2	661 ± 2	0.800	2764.67	-	-	-	-	-		
	y + H + AC		8.17 ± 0.04	398 ± 2	661 ± 2	0.800	2764.67	-	-	-	-	-		
	y + DT + AC		8.17 ± 0.04	398 ± 2	661 ± 2	0.800	2764.67	8.97 ± 0.10	429 ± 3	690 ± 4	0.782	209.53		
	y + H + DT + AC		8.14 ± 0.04	398 ± 2	662 ± 2	0.799	3368.08	-	-	-	-	-		
	y + Profile-1		8.17 ± 0.03	398 ± 2	662 ± 2	0.800	4517.37	8.96 ± 0.10	429 ± 3	690 ± 4	0.782	315.18		
	y + Profile-2		8.18 ± 0.04	399 ± 2	659 ± 2	0.801	3665.60	8.95 ± 0.05	427 ± 2	684 ± 4	0.786	2603.19		
KAN	y		6.52 ± 0.23	303 ± 11	563 ± 15	0.855	35773.60	6.66 ± 0.16	311 ± 7	579 ± 12	0.847	136.00		
	y + H		6.39 ± 0.28	301 ± 16	551 ± 12	0.861	10180.98	-	-	-	-	-		
	y + DT		4.42 ± 0.07	229 ± 3	378 ± 7	0.935	850.08	4.90 ± 0.15	248 ± 6	384 ± 9	0.933	39.90		
	y + AC		6.27 ± 0.19	290 ± 9	535 ± 13	0.869	24903.68	6.55 ± 0.12	305 ± 5	542 ± 8	0.865	190.44		
	y + H + DT		4.60 ± 0.05	238 ± 3	385 ± 4	0.932	1926.81	-	-	-	-	-		
	y + H + AC		6.25 ± 0.12	292 ± 6	531 ± 6	0.871	1261.44	-	-	-	-	-		
	y + DT + AC		4.41 ± 0.21	230 ± 12	358 ± 16	0.941	0.00	4.90 ± 0.27	248 ± 12	364 ± 17	0.939	2355.32		
	y + H + DT + AC		4.46 ± 0.08	229 ± 4	356 ± 6	0.942	4017.60	-	-	-	-	-		
	y + Profile-1		4.30 ± 0.18	224 ± 10	318 ± 9	0.954	17600.66	4.77 ± 0.25	242 ± 13	343 ± 13	0.946	431.34		
	y + Profile-2		3.96 ± 0.13	207 ± 7	311 ± 6	0.956	7027.36	4.47 ± 0.12	230 ± 5	335 ± 8	0.949	79.12		
TCN	y		9.57 ± 5.99	458 ± 306	682 ± 288	0.750	1558.23	8.05 ± 1.13	377 ± 56	634 ± 71	0.814	750.03		
	y + H		6.37 ± 0.27	300 ± 13	547 ± 13	0.863	703.39	-	-	-	-	-		
	y + DT		4.80 ± 0.18	250 ± 9	405 ± 12	0.925	204.72	8.07 ± 7.18	369 ± 267	556 ± 375	0.795	3.51		
	y + AC		7.00 ± 0.57	333 ± 29	560 ± 29	0.856	4077.16	9.17 ± 4.7	497 ± 183	755 ± 206	0.720	2509.87		
	y + H + DT		4.70 ± 0.17	243 ± 8	396 ± 11	0.928	254.61	-	-	-	-	-		
	y + H + AC		7.14 ± 3.08	335 ± 122	562 ± 143	0.846	1938.64	-	-	-	-	-		
	y + DT + AC		4.70 ± 0.17	243 ± 8	396 ± 11	0.928	254.61	5.04 ± 0.23	255 ± 12	388 ± 15	0.931	297.02		
	y + H + DT + AC		4.94 ± 0.54	254 ± 27	402 ± 72	0.924	4092.06	-	-	-	-	-		
	y + Profile-1		4.27 ± 0.21	222 ± 11	338 ± 11	0.948	132.13	4.56 ± 0.14	228 ± 6	327 ± 8	0.951	1294.67		
	y + Profile-2		4.26 ± 0.21	222 ± 10	338 ± 10	0.948	132.11	4.80 ± 0.19	244 ± 10	355 ± 11	0.942	25.49		
RNN	y		10.14 ± 1.33	478 ± 71	809 ± 83	0.697	225.09	7.46 ± 0.73	348 ± 31	593 ± 37	0.839	140.66		
	y + H		13.83 ± 2.00	612 ± 80	982 ± 110	0.553	452.67	-	-	-	-	-		
	y + DT		5.13 ± 0.21	265 ± 11	436 ± 13	0.913	84.80	5.01 ± 0.13	252 ± 6	392 ± 7	0.930	91.94		
	y + AC		16.85 ± 1.20	771 ± 70	1139 ± 74	0.403	292.71	7.02 ± 0.31	328 ± 15	575 ± 18	0.849	205.23		
	y + H + DT		5.16 ± 0.10	266 ± 5	431 ± 4	0.915	66.87	-	-	-	-	-		
	y + H + AC		12.75 ± 1.82	586 ± 84	919 ± 93	0.610	252.96	-	-	-	-	-		
	y + DT + AC		5.34 ± 0.18	276 ± 10	431 ± 11	0.915	74.00	5.28 ± 0.22	265 ± 10	380 ± 11	0.934	36.96		
	y + H + DT + AC (1)		-	-	-	-	-	-	-	-	-	-		
	y + Profile-1		4.55 ± 0.12	233 ± 7	347 ± 6	0.945	60.67	4.77 ± 0.06	240 ± 3	355 ± 4	0.942	243.45		
	y + Profile-2		4.42 ± 0.05	227 ± 2	343 ± 3	0.946	1.03	4.58 ± 0.11	232 ± 5	342 ± 6	0.947	14.25		
GRU	y		28.51 ± 25.8	1446 ± 1388	1745 ± 1349	-1.222	741.97	7.20 ± 0.42	332 ± 18	573 ± 22	0.849	10.26		
	y + H		8.87 ± 2.74	407 ± 125	691 ± 133	0.774	120.61	-	-	-	-	-		
	y + DT		5.08 ± 0.20	263 ± 10	437 ± 10	0.913	113.66	5.25 ± 0.31	264 ± 13	403 ± 14	0.926	343.10		
	y + AC		11.64 ± 4.69	557 ± 230	871 ± 260	0.622	167.50	6.82 ± 0.36	315 ± 17	558 ± 19	0.857	348.78		
	y + H + DT		5.18 ± 0.28	262 ± 14	414 ± 17	0.921	121.40	-	-	-	-	-		
	y + H + AC		7.19 ± 0.68	338 ± 29	601 ± 42	0.834	449.01	-	-	-	-	-		
	y + DT + AC		5.36 ± 0.40	276 ± 21	435 ± 30	0.913	215.99	5.29 ± 0.18	266 ± 8	382 ± 8	0.933	44.03		
	y + H + DT + AC		15.4 ± 22.8	801 ± 1211	960 ± 1229	-0.111	198.00	-	-	-	-	-		
	y + Profile-1		4.62 ± 0.20	236 ± 9	349 ± 8	0.944	247.33	5.09 ± 1.51	256 ± 59	371 ± 76	0.934	50.69		
	y + Profile-2		4.62 ± 0.23	239 ± 12	346 ± 11	0.945	208.68	4.62 ± 0.19	233 ± 10	339 ± 9	0.947	529.96		
LSTM	y		9.50 ± 2.60	456 ± 129	753 ± 137	0.732	1194.09	8.85 ± 1.93	404 ± 73	694 ± 89	0.776	150.69		
	y + H		9.40 ± 2.25	429 ± 97	741 ± 122	0.742	487.05	-	-	-	-	-		
	y + DT		5.01 ± 0.14	259 ± 7	435 ± 5	0.913	839.26	6.40 ± 1.3	321 ± 62	492 ± 114	0.883	44.18		
	y + AC		14.39 ± 7.91	721 ± 430	970 ± 362	0.510	1124.15	8.79 ± 2.24	407 ± 91	682 ± 151	0.777	375.46		
	y + H + DT		5.12 ± 0.16	264 ± 7	429 ± 5	0.916	75.00	-	-	-	-	-		
	y + H + AC		10.36 ± 3.81	483 ± 178	784 ± 188	0.702	696.81	-	-	-	-	-		
	y + DT + AC		5.32 ± 0.51	274 ± 28	478 ± 214	0.875	179.04	5.30 ± 0.23	262 ± 11	386 ± 12	0.932	296.04		
	y + H + DT + AC		5.34 ± 0.53	274 ± 29	452 ± 224	0.884	470.73	-	-	-	-	-		
	y + Profile-1		4.63 ± 0											