

Hardware / PLC_2 [CPU 1214FC DC/DC/DC] / Programmbausteine

Comparing_p3_s1_s2 [FB5]

Comparing_p3_s1_s2 Eigenschaften							
Allgemein							
Name	Comparing_p3_s1_s2	Nummer	5	Typ	FB	Sprache	SCL
Nummerierung	Automatisch						
Information							
Titel		Autor		Kommentar		Familie	
Version	0.1	Anwenderdefinierte ID					

Comparing_p3_s1_s2									
Name	Datentyp	Defaultwert	Remanenz	Erreichbar aus HMI/OPC UA	Schreibbar aus HMI/OPC UA	Sichtbar in HMI Engineering	Einstellwert	Überwachung	Kommentar
▼ Input									
h_from_pressure130	Real	0.0	Nicht remanent	True	True	True	False		
h_from_high128	Real	0.0	Nicht remanent	True	True	True	False		
h_from_high132	Real	0.0	Nicht remanent	True	True	True	False		
▼ Output									
difference1_mm_130_132	Real	0.0	Nicht remanent	True	True	True	False		
difference1_percentage_130_132	Real	0.0	Nicht remanent	True	True	True	False		
difference2_mm_132_128	Real	0.0	Nicht remanent	True	True	True	False		
difference2_percentage_132_128	Real	0.0	Nicht remanent	True	True	True	False		
InOut									
Static									
Temp									
Constant									

```
0001 IF #h_from_pressure130 <> 0 THEN
0002     #difference1_mm_130_132 := #h_from_pressure130 - #h_from_high132;
0003     #difference1_percentage_130_132 := 100 * (#h_from_pressure130 - #h_from_high132) / #h_from_pressure130;
0004 END_IF;
0005
0006 IF #h_from_high132 <> 0 THEN
0007     #difference2_mm_132_128 := #h_from_high132 - #h_from_high128;
0008     #difference2_percentage_132_128 := 100 * (#h_from_high132 - #h_from_high128) / #h_from_high132;
0009 END_IF;
```

Symbol	Adresse	Typ	Kommentar
#difference1_mm_130_132		Real	
#difference1_percentage_130_132		Real	
#difference2_mm_132_128		Real	
#difference2_percentage_132_128		Real	
#h_from_high128		Real	
#h_from_high132		Real	
#h_from_pressure130		Real	