

SESSION 4: PROGRAMMING IN DO-FILES (II)

Manuel V. Montesinos

Computation Brush-Up Course
Competition and EPP Master Programs

Fall 2021



Macros

What are they?: a name associated with a text (contents).
Everywhere a punctuated macro appears in a command, the macro contents are substituted for the macro name.

Why do we use them?: to avoid repetitive commands and typing.

Which macros are there?: local (valid for the current text) and global (valid for the current Stata session):

- ▶ `local localmacroname associatedtext` (evaluate using 'localmacroname').
- ▶ `global globalmacroname associatedtext` (evaluate using \$globalmacroname).

Conditional Execution

Use the command **if** followed by a **condition**, with the following structure:

```
if expression {  
    commands to be executed if expression is true  
}  
else {  
    optional block to be executed if expression  
        is not true  
}
```

Note that the opening bracket { must be the last thing on a line, and the closing bracket } must be on a new line by itself.

The expression is only one value (i.e. can't have variables here).

Loops

While loop

```
while expression {  
    commands to be executed repeatedly until  
    expression is false  
}
```

The condition is an expression. The loop executes as long as the condition is true (nonzero).

Example:

```
local i=5  
while 'i'>0 {  
    display 'i'+1  
    local i='i'-1  
}
```

Loops

foreach and forvalues

`foreach` loops over elements of a local or global macro or variables in a list:

```
foreach i in 1 2 3 4 5 {  
    display "'i' + 1 = "  
    display 'i' + 1  
    display ""  
}
```

`forvalues` loops over series or lists of numbers:

```
forvalues i=1/5 {  
    display "'i' + 1 = "  
    display 'i' + 1  
    display ""  
}
```

Loops

Nested loops

A loop inside another loop:

```
for values i=43/45 {  
  for values j=0/1 {  
    display "-----"  
    display "AGE=='i' & MARRIED=='j'"  
    display "-----"  
    if 'i'==45 {  
      summarize EARNINGS if AGE=='i'  
        & MARRIED=='j'  
    }  
    else {  
      summarize HOURS EARNINGS if AGE=='i' \&  
        MARRIED=='j'  
    }  
  }  
}
```

Programs

Stata allows you to write **your own** commands.

Make sure a program with the **same name** does not exist:
`capture drop program programname.`

Define the new program:

```
program programname
    ...
    ...
end
```

Use **positional arguments**: '1', '2', '3'...

Type the program name and the arguments to **execute** it:
`programname A B C.`

Exercises

1. Write a loop to create 10 new variables: `var1`, ..., `var10` with `var1=10`, `var2=20`, ..., `var10=100`.
2. Use the *uslifeexp* dataset. For each life expectancy variable:
 - Create a two-way graph (year on the x-axis).
 - Save the graph in your working directory.
3. Download [this dataset](#). It contains artificial data of people and their incomes for twelve months. Create a set of dummy variables for whether the person had any income in that month.
4. **If bored:** write a program of your choice with three arguments at least.