AIM, Explained From Scratch

How a differentially private synthetic-data mechanism chooses, measures and fits marginals

Manuel V. Loureiro

Version 2026-11-04

AIM is an algorithm for releasing a synthetic copy of a table of personal records under differential privacy. This note explains it for a reader who knows basic probability but not privacy or graphical models. It traces AIM on a toy dataset of a thousand people, computes every number with a script, and proves that AIM keeps its privacy promise.

Table of contents

1 The task: synthetic data that gets the marginals right 3
1.1 Records, attributes and the full table . . . 3
1.2 Marginals . . . 4
1.3 The workload and the error . . . 4

2 Differential privacy, as much as AIM needs 5
2.1 Neighbouring datasets and the promise . . . 5
2.2 Counting the cost in concentrated form . . . 5
2.3 The two building blocks . . . 6

3 Select, measure, generate 7

4 Private-PGM, without graphical models 8
4.1 One table that explains every measurement . . . 8
4.2 Why the table never has to be built . . . 9
4.3 From the table to records . . . 10

5 AIM, round by round 10
5.1 The schedule . . . 10
5.2 Initialization . . . 11
5.3 The candidates . . . 11
5.4 Selection: the score . . . 12
5.5 Measurement and estimation . . . 14
5.6 Annealing: when a round teaches too little . . . 14
5.7 The run on the toy dataset . . . 15

6 Why AIM keeps its promise 17

7 What AIM says about its own error **18**

8 How well it works **19**

9 Sources **20**

An organization holds a table of records about people, with attributes such as age group, occupation and a medical condition. Researchers want to study the table, but it cannot leave the building. One answer is **synthetic data**, a new table of made-up rows that gives nearly the same answers to the statistical questions that matter, but reveals almost nothing about any one real person. AIM, by McKenna, Mullins, Sheldon and Miklau (2022), is a way to build such a table, and in the paper's experiments it beat every competitor on most settings.

The name stands for *adaptive and iterative mechanism*. AIM builds its model from noisy statistics, choosing each new statistic using earlier measurements. This note explains its privacy guarantee and how AIM accounts for it, how noisy statistics become a dataset, and how AIM selects and measures each statistic. You need only expectations, the normal distribution and basic calculus. Table 1 lists each section's question, and Table 2 defines the notation. A script carries the running example and computes every number in the note:

```
uv run python code/notes/aim.py
```

Table 1: The question each section answers.

Section	The question it answers
Section 1	What does synthetic data have to get right, and how is its error measured?
Section 2	What does the privacy promise say, and how are its costs counted?
Section 3	Why not measure every statistic directly, and what three problems that leaves?
Section 4	How does one dataset come out of many noisy, inconsistent statistics?
Section 5	What does AIM do in each round, and why?
Section 6	Why does AIM keep its privacy promise?
Section 7	How does AIM know how wrong its answers are?
Section 8	How well does it work, and which of its ideas matter most?

Table 2: The symbols the note uses. Each is also explained where it first appears.

Symbol	Meaning
D, D'; $D \sim D'$	a dataset of n records, and a neighbouring one, which has one record more or one fewer
d	the number of attributes

Symbol	Meaning
r, s	sets of attributes
$\mu_r(D)$, m_r	the marginal of D over the attributes in r, a vector of counts, and its number of cells
$\mathcal{Q}$, c_s	the workload, a list of attribute sets whose marginals the synthetic data should get right, with their weights
$\mathcal{Q}_+$	the downward closure of the workload, the marginals AIM may measure
w_r	the weight AIM gives a candidate marginal r
$\tilde{y}_i$, σ_i	the i-th noisy measurement, and its noise level
$\hat{p}$, $\hat{p}_t$	the model's table of counts, and the model after round t
$\hat{D}$	the synthetic dataset
ε, δ	the parameters of a differential-privacy guarantee
ρ, ρ_{used}	the privacy budget in zero-concentrated form, and the part of it spent so far
σ_t, ε_t	the noise level and the selection budget of round t; σ_0 is the starting noise level
T	the number of rounds AIM plans for
$u(D, r)$, Δu	the score AIM gives candidate r, and the most one record can change it
$D_\alpha(P\|Q)$	the Rényi divergence of order α between two distributions
θ	the parameters of the model

1 The task: synthetic data that gets the marginals right

Before privacy enters, we need to say what a good synthetic dataset is, because every later choice of AIM tries to make its error small.

1.1 Records, attributes and the full table

A dataset D is a list of n records, and each record gives a value for each of d attributes. AIM requires every attribute to be **discrete**, with a fixed, finite list of values, so income, for example, must first be cut into bands.

The running example is a toy dataset of $n = 1{,}000$ people with four attributes. *Smoker* has the values no and yes, and *exercise* has the values rarely and often. *Age* has three bands, under 40, 40 to 64, and 65 and over. *Condition* records whether the person has a certain medical condition. In the population that the script draws from, smoking, exercise and the condition depend on age, and the condition also depends on smoking.

A record is one combination of values, and the number of possible combinations is the product of the attributes' sizes, $2 \times 3 \times 2 \times 2 = 24$ for the toy dataset. The **full table** of a dataset counts the records on each combination, so it holds everything about the dataset except the order of the rows. But for real data it is far too big to release or even to store, because the product of fifteen attribute sizes runs into the billions. So AIM works with marginals instead.

1.2 Marginals

A marginal looks at a few attributes at a time and ignores the rest.

Definition 1.1 (Marginal)**.** Let r be a set of attributes. The **marginal** of D over r, written $\mu_r(D)$, is the vector that gives, for every combination of values of the attributes in r, the number of records of D with that combination. Its number of entries, or **cells**, is written m_r. A marginal over one attribute is a **one-way** marginal, over two attributes a **two-way** marginal, and so on.

So a marginal is a contingency table, flattened into a vector. Table 3 shows the toy dataset's marginal over smoker and condition, which has $m_r = 4$ cells.

Table 3: The marginal of the toy dataset over smoker and condition: how many of its 1,000 people fall in each of the four cells. Its one-way marginals are the row and column sums.

smoker	condition	no	yes
no		627	98
yes		181	94

A marginal over a set r determines the marginal over every subset of r: add the relevant cells, as the row sums of Table 3 do to produce the one-way marginal of smoker. Every marginal is also a sum over the full table. Summing over the attributes outside r gives $\mu_r(D)$. This sum is linear in the table, which lets Section 4 fit a table to noisy marginals.

1.3 The workload and the error

The user of the synthetic data says which marginals matter. The **workload** $\mathcal{Q}$ is a list of attribute sets, and each set s in it has a weight c_s that says how much its marginal matters. In the toy example the workload is all six two-way marginals, with equal weights. In the paper's experiments it is typically every three-way marginal of a dataset, several hundred of them.

The quality of the synthetic dataset $\hat{D}$ is the weighted distance between its workload marginals and the true ones. The paper measures distance by the L_1 norm, the sum of the absolute differences of the cells, and divides by the number of marginals and by n:

$$\text{Error}(D, \hat{D}) = \frac{1}{|\mathcal{Q}|\, n} \sum_{s \in \mathcal{Q}} c_s \left\| \mu_s(D) - \mu_s(\hat{D}) \right\|_1. \tag{1}$$

The division by n turns counts into shares, so an error of 0.05 means that a typical workload marginal is off by five percent of the records in total, spread over its cells. The toy run in Section 5 starts at about 0.14 and ends at about 0.05.

2 Differential privacy, as much as AIM needs

AIM promises that the synthetic data reveal almost nothing about any one person, a promise called differential privacy (DP). AIM touches the data with only two noisy operations. So once we have the exact promise, a way to count its cost and the cost of each operation, the privacy of the whole algorithm comes from adding up costs.

2.1 Neighbouring datasets and the promise

The promise compares two datasets that differ in one person.

Definition 2.1 (Neighbouring datasets)**.** Two datasets D and D' are **neighbouring**, written $D \sim D'$, if one can be obtained from the other by adding or removing a single record.

Some papers instead let neighbours differ by one replaced record. AIM uses the add-or-remove version, and the choice matters for the noise, because adding a record changes a marginal in one cell, while replacing one changes two cells.

A **mechanism** M is a randomized algorithm that takes a dataset and returns an output, here a synthetic dataset. Its output on D is random, and the promise is that this distribution barely changes when D is replaced by a neighbour.

Definition 2.2 (Differential privacy)**.** Let $\varepsilon \geq 0$ and $\delta \in [0, 1]$. A mechanism M is (ε, δ)-**differentially private**, or (ε, δ)-DP, if for every pair of neighbouring datasets $D \sim D'$ and every set S of possible outputs,

$$\Pr[M(D) \in S] \leq e^{\varepsilon} \Pr[M(D') \in S] + \delta. \tag{2}$$

In words, no outcome becomes much more likely because one person's record is in the data. For example, $\varepsilon = 1$ lets an outcome become at most $e \approx 2.7$ times more likely, and δ is a small probability of exceptions, typically far below one in a million. The definition covers both orders of the pair. So an observer who sees the output cannot tell with any confidence whether a given person's record was used, whatever else they know.

2.2 Counting the cost in concentrated form

AIM performs many noisy operations, and if you add up their (ε, δ) pairs directly, the total is weak. So AIM counts in a different currency, called zero-concentrated differential privacy, in which costs simply add and convert to an (ε, δ) pair at the end. Its definition uses a distance between two distributions.

Definition 2.3 (Rényi divergence)**.** Let P and Q be two distributions on the same outputs, and write p and q for their densities, or their mass functions if the outputs are discrete. Let the order α be a number greater than 1. Their **Rényi divergence of order** α is

$$D_{\alpha}(P \| Q) = \frac{1}{\alpha - 1} \ln \mathbb{E}_{Y \sim Q} \left[\left(\frac{p(Y)}{q(Y)} \right)^{\alpha} \right]. \tag{3}$$

The ratio $p(y)/q(y)$ says how much more likely an output is under P than under Q, and the divergence averages a power of that ratio, on a logarithmic scale. So it is zero when the distributions are equal and grows as they separate.

Definition 2.4 (Zero-concentrated differential privacy)**.** Let $\rho \geq 0$. A mechanism M is **ρ-zero-concentrated differentially private**, or ρ-zCDP, if for every pair of neighbouring datasets $D \sim D'$ and every order $\alpha > 1$,

$$D_\alpha(M(D) \,\|\, M(D')) \leq \rho\,\alpha. \tag{4}$$

The number ρ is the **privacy budget** in this currency. AIM needs three standard facts about it.

Proposition 2.1 (Three properties of zCDP)**.**

(a) Composition. *If M_1 is ρ_1-zCDP and M_2 is ρ_2-zCDP, where M_2 may be chosen after seeing the output of M_1, then releasing both outputs is $(\rho_1 + \rho_2)$-zCDP.*

(b) Post-processing. *Any computation on the output of a ρ-zCDP mechanism, which does not look at the data again, is still ρ-zCDP.*

(c) Conversion. *A ρ-zCDP mechanism is (ε, δ)-DP for every $\varepsilon \geq 0$ with*

$$\delta = \min_{\alpha > 1} \frac{\exp\big((\alpha - 1)(\alpha\rho - \varepsilon)\big)}{\alpha - 1} \left(1 - \frac{1}{\alpha}\right)^{\alpha}. \tag{5}$$

Bun and Steinke (2016) prove parts (a) and (b), and Canonne, Kamath and Steinke (2020) prove part (c). In AIM, part (a) lets the costs of the rounds add even though each round depends on earlier outputs. Part (b) makes most of AIM free, because the model fit, the choice of what to measure next and the rounding to a dataset look only at released values. Part (c) sets the budget. The user picks ε and δ, and the script finds the largest ρ whose conversion gives them. For $\varepsilon = 1$ and $\delta = 10^{-6}$, the values of the toy run, the budget is $\rho = 0.0244$.

2.3 The two building blocks

The first building block releases a vector of counts with Gaussian noise. Its cost depends on how much one person can change the vector.

Definition 2.5 (Sensitivity)**.** Let f map datasets to vectors. Its L_2 **sensitivity** is the largest Euclidean distance between its values on two neighbouring datasets,

$$\Delta_2 f = \max_{D \sim D'} \big\| f(D) - f(D') \big\|_2. \tag{6}$$

A marginal has the smallest sensitivity a count can have.

Lemma 2.1 (A marginal has sensitivity one)**.** *For every attribute set r, the marginal μ_r has L_2 sensitivity* 1.

Proof. Adding one record to D adds one to exactly one cell of $\mu_r(D)$, the cell of that record's values on the attributes in r, and leaves every other cell unchanged. Removing a record subtracts one from one cell. In both cases the difference vector has a single entry of ± 1, whose Euclidean length is 1. □

Proposition 2.2 (The Gaussian mechanism)**.** *Let f have L_2 sensitivity $\Delta_2 f$, and let $\sigma > 0$. The mechanism that releases $f(D) + Z$, where Z is a vector of independent $\mathcal{N}(0, \sigma^2)$ noise, one entry per coordinate, is ρ-zCDP with*

$$\rho = \frac{(\Delta_2 f)^2}{2\sigma^2}. \tag{7}$$

Bun and Steinke (2016) prove this result. Their proof uses the Rényi divergence between two normal distributions with the same variance, which is α times the squared distance of their means over $2\sigma^2$. A marginal has sensitivity one by Lemma 2.1, so a measurement with noise level σ costs $1/(2\sigma^2)$, whatever the marginal's size. But a marginal with many cells spreads the same n records thinly, so each cell's count is small next to the noise. That is why Section 5 prefers smaller marginals when the budget is tight.

The second building block chooses one option from a list. It favours options with a high score, but it does not reveal the scores.

Proposition 2.3 (The exponential mechanism)**.** *Let $\mathcal{R}$ be a finite set of candidates, and let $u(D, r)$ be a score for each candidate r, whose **sensitivity** Δu is the most that adding or removing one record can change any candidate's score. The mechanism that chooses candidate r with probability proportional to $\exp(\varepsilon\, u(D, r)/(2\Delta u))$ is ε-DP, and it is ρ-zCDP with*

$$\rho = \frac{\varepsilon^2}{8}. \tag{8}$$

The ε-DP claim is the theorem of McSherry and Talwar (2007), and Cesar and Rogers (2021) prove the zCDP cost. The exponent sets how sharp the choice is, because a candidate whose score is higher by $2\Delta u/\varepsilon$ is e times more likely to be chosen. So with a large ε the mechanism almost always picks the best candidate, and with a tiny ε it picks nearly at random.

3 Select, measure, generate

With the two building blocks, the obvious method is to measure every workload marginal with Gaussian noise and release the results. Its failure names the three problems that AIM must solve.

Suppose the workload has k marginals, each measured once with the same noise level σ. By Proposition 2.2 and Proposition 2.1 (a), the total cost is $k/(2\sigma^2)$, so if you spend the whole budget, $\sigma = \sqrt{k/(2\rho)}$. On the toy workload, with $k = 6$ and $\rho = 0.0244$, that gives $\sigma = 11.1$, which is small next to counts in the hundreds. But all three-way marginals of fifteen attributes make $k = 455$, and then $\sigma = 96.6$. A three-way marginal of fifty thousand records might have a hundred cells of about five hundred records each, so the noise would be a fifth of a typical count. That is the first problem, **selection**: measure only the marginals that matter, and infer the rest from them.

The second problem appears even on the toy workload, because six noisy marginals are not a dataset. Two of them that share an attribute disagree about its one-way marginal, because each carries its own noise. Some cells are negative, and a marginal that was never measured gets no answer at all. This is the problem of **generation**: turn the noisy measurements into one dataset whose marginals are consistent, non-negative, and close to the measurements.

The third problem is the **budget split**. A measurement with little noise costs a great deal, and one with much noise may be worthless, so an even split ignores that some marginals are far from what the model already knows and others are not.

The *select-measure-generate* family, as the paper calls it, answers the three problems in a loop. It selects a marginal, measures it with noise, updates a model of the data to agree with every measurement so far, and repeats, and at the end it generates a dataset from the model. The ancestor of AIM in this family is the multiplicative weights exponential mechanism (MWEM). It uses the exponential mechanism to pick the marginal on which the current model is most wrong. AIM keeps the loop and changes every step in it, but both share the generation step, which comes first.

4 Private-PGM, without graphical models

The generation step must turn noisy, inconsistent marginals into one dataset. Private-PGM (McKenna, Sheldon and Miklau, 2019) does this. Its name promises probabilistic graphical models, but what it computes is simple to state without them, and AIM takes only one number from that machinery, the size of the model.

4.1 One table that explains every measurement

Suppose that a sequence of marginals has been measured. The i-th measurement is a noisy vector $\tilde{y}_i$, equal to $\mu_{r_i}(D)$ plus Gaussian noise of level σ_i in each cell. Private-PGM looks for a full table p, which counts the records on every combination of values, as in Section 1, with non-negative entries that sum to the number of records. Its marginals $\mu_r(p)$ are sums over the attributes outside r, as for a dataset. Private-PGM asks them to be as close to the measurements as possible, in squared error, with less weight on noisier measurements:

$$\hat{p} = \arg\min_{p} \sum_{i} \frac{1}{\sigma_i} \left\| \mu_{r_i}(p) - \tilde{y}_i \right\|_2^2. \tag{9}$$

Squared error matches the Gaussian noise model. Weights of $1/\sigma_i^2$ would give the maximum-likelihood table, but the paper reports better results in its experiments with weights of $1/\sigma_i$.

Fitting one table resolves two problems from Section 3. Its marginals are consistent because they sum the same table, and they are nonnegative because the table's entries are nonnegative. The fitted table also estimates marginals that AIM did not measure by combining the measured marginals. For example, after the toy run measures only the four one-way marginals, its estimate over smoker and condition preserves the measured row and column totals (Table 4). It treats the attributes as independent because no measurement captures their dependence.

Table 4: The true marginal over smoker and condition, and what the model fitted to the noisy one-way marginals alone gives for it. The model keeps the row and column sums, within the noise, but it spreads each row in the same proportions, because nothing it has measured says that smoking and the condition go together.

smoker	true: no condition	true: condition	model: no condition	model: condition
no	627	98	584.8	140.4
yes	181	94	236.6	56.8

The number of records n changes between add-or-remove neighbours, so it is private, and the table's total cannot simply be set to n. Instead, each noisy one-way marginal sums to a noisy copy of n, and the script uses the average of these sums, which is free post-processing. The toy run estimates 1,019 records.

4.2 Why the table never has to be built

The difficulty is size. On the toy domain, p has 24 entries, but no computer can hold p on a real domain with billions of combinations. The way out is that the objective of Equation 9 depends on p only through its marginals over the measured sets $r_1, r_2, ...$, and that fact forces the shape of the solution.

Theorem 4.1 (The solution is a product of small tables)**.** *Write x_{r_i} for the combination of values that a record x takes on the attributes in r_i. Among the minimizers of Equation 9 there is a table of the form*

$$p_\theta(x) \propto \exp\Big(\sum_i \theta_i[x_{r_i}]\Big), \tag{10}$$

where each θ_i is a table of numbers with one entry per cell of the i-th measured marginal.

McKenna, Sheldon and Miklau (2019) prove this by a convex duality argument. The objective depends on the table only through its marginals, which are linear in it, and the maximum-entropy table with given marginals has this exponential form. So the model has as many parameters as the measurements have cells, however large the domain. To fit it, the script's optimizer adjusts the parameter tables θ_i until the model's marginals match the measurements, and Private-PGM does the same with a more careful algorithm.

This form explains Table 4. With only one-way marginals measured, the model is proportional to $\exp(\theta_1[x_1])\exp(\theta_2[x_2])\cdots$, one factor per attribute, which is the definition of independent attributes. A measured marginal over smoker and condition adds a factor that depends on both, and only that pair becomes dependent. So the model carries exactly the dependencies that were measured.

Graphical models compute the marginals of p_θ without the full table, because they sum out one attribute at a time. The largest intermediate table sets the cost. It stays small when the measured sets form chains and small clusters, and grows enormous when the sets overlap in a tangled way. The paper calls the memory this needs the **junction tree size**, written JT-SIZE$(r_1, \dots, r_t)$ for the measured sets, in megabytes, and AIM keeps it below a limit.

4.3 From the table to records

The fitted table $\hat{p}$ has fractional entries, but a dataset needs whole records, so Private-PGM produces the synthetic dataset $\hat{D}$ by rounding. It rounds each cell's count down and gives the records lost to rounding to the cells with the largest fractional parts. By Proposition 2.1 (b) this step is free. In the toy run, the model's workload error is 0.0529 and the rounded dataset's is 0.0537.

5 AIM, round by round

The generation method in Section 4 leaves two questions: which marginals should AIM measure, and how much budget should it spend on each? AIM takes a dataset D, a workload $\mathcal{Q}$ of attribute sets with weights c_s, and a budget ρ, then returns a synthetic dataset. It uses three fixed settings. It plans for $T = 16d$ rounds, where d is the number of attributes, allocates nine tenths of each round's budget to measurement and one tenth to selection, and caps the model's junction tree size at 80 megabytes.

5.1 The schedule

Each round t selects a marginal with the exponential mechanism at a budget ε_t, then measures it with Gaussian noise at a level σ_t. By Proposition 2.3, Proposition 2.2 and Lemma 2.1, the round costs

$$\rho_t = \frac{\varepsilon_t^2}{8} + \frac{1}{2\sigma_t^2}. \tag{11}$$

AIM chooses the starting values so that T rounds at those values would spend the budget in the planned split. Nine tenths of ρ over T measurements means $T/(2\sigma_0^2) = 0.9\rho$, and one tenth over T selections means $T\varepsilon_1^2/8 = 0.1\rho$. Each equation solves for its unknown:

$$\sigma_0 = \sqrt{\frac{T}{2 \cdot 0.9\,\rho}}, \qquad \varepsilon_1 = \sqrt{\frac{8 \cdot 0.1\,\rho}{T}}. \tag{12}$$

With $T = 16d$ the starting noise is large and the starting selection budget is tiny, on purpose. The annealing rule below raises the per-round budget when a round teaches too little, and AIM stops when the budget is gone, not after T rounds. Table 5 gives the schedule for the toy dataset, where $d = 4$.

Table 5: AIM's budget schedule on the toy dataset, with the paper's defaults. Each annealing doubles ε and halves σ, so it multiplies the cost of a round by four.

Quantity	Value
budget ρ, from $(\varepsilon, \delta) = (1, 10^{-6})$	0.0244
rounds planned, $T = 16d$	64
starting noise $\sigma_0 = \sqrt{T/(2 \cdot 0.9\rho)}$	38.2

Quantity	Value
starting selection budget $\varepsilon_1 = \sqrt{8 \cdot 0.1\rho/T}$	0.0174
cost of the initialization, $d/(2\sigma_0^2)$	0.0014
cost of one round at the start, $\varepsilon_1^2/8 + 1/(2\sigma_0^2)$	0.0004
cost of a round after one annealing	0.0015
cost of a round after two annealings	0.0061

5.2 Initialization

Before the loop, AIM measures every one-way marginal that appears in some workload marginal, each with noise level σ_0, and fits the model to them. This saves the selections that MWEM's early rounds spend on one-way marginals anyway. The cost is at most $d/(2\sigma_0^2)$, which by Equation 12 equals $0.9\rho\, d/T$, a sixteenth of the measurement budget when $T = 16d$. The result is the independence model of Table 4.

5.3 The candidates

AIM may measure every marginal over a subset of a workload set, a collection the paper calls the **downward closure** of the workload,

$$\mathcal{Q}_+ = \{\, r : r \subseteq s \text{ for some } s \in \mathcal{Q} \,\}. \tag{13}$$

A large marginal spreads the records over many cells, so noise can swamp each cell's count. A sub-marginal has larger counts, and the model combines sub-marginals to estimate the larger marginal. On the toy workload of six two-way marginals, the closure adds the four one-way marginals, for ten candidates in all.

Each candidate gets a weight that says how much of the workload it serves. It counts the attributes the candidate shares with each workload marginal, times that marginal's weight:

$$w_r = \sum_{s \in \mathcal{Q}} c_s \, |r \cap s|. \tag{14}$$

For example, a two-way candidate on the toy workload shares both attributes with itself and one attribute with four other workload marginals, so its weight is 6. A one-way candidate shares its attribute with three workload marginals, for a weight of 3.

In each round, AIM drops candidates that would make the model too large. A candidate r stays only if the junction tree size of the measured sets plus r is at most $(\rho_{\text{used}}/\rho)$ times the 80-megabyte cap. Early rounds therefore use small models; the full cap becomes available only near the end. Every model on the toy domain is small enough that the script does not need this filter.

5.4 Selection: the score

AIM changes the candidate score used by MWEM. MWEM scores a candidate by the L_1 distance $\|\mu_r(D) - \mu_r(\hat{p}_{t-1})\|_1$ between the true marginal and the current model's estimate. This score favours large marginals because they have more cells and therefore larger errors, even when measurement noise would be larger still. AIM subtracts the expected L_1 norm of the noise; the next lemma gives that quantity.

Lemma 5.1 (Expected size of Gaussian noise)**.** *Let $Z \sim \mathcal{N}(0, \sigma^2)$. Then*

$$\mathbb{E}|Z| = \sigma\sqrt{2/\pi}. \tag{15}$$

Hence a vector of m independent such entries has expected L_1 norm $\sigma m\sqrt{2/\pi}$.

Proof. The density of Z is symmetric about zero, so the expectation of $|Z|$ is twice the integral over the positive half-line:

$$\mathbb{E}|Z| = 2\int_0^\infty \frac{z}{\sigma\sqrt{2\pi}} \exp\left(-\frac{z^2}{2\sigma^2}\right) \mathrm{d}z. \tag{16}$$

Up to the constant in front, the integrand is the derivative of $-\sigma^2 \exp(-z^2/(2\sigma^2))$, which runs from $-\sigma^2$ at zero to 0 at infinity. So the integral equals $\sigma^2/(\sigma\sqrt{2\pi})$, and twice that is $2\sigma/\sqrt{2\pi} = \sigma\sqrt{2/\pi}$. The L_1 norm of a vector is the sum of the absolute values of its entries, and expectation is linear, so m entries give m times the single-entry value. □

The constant $\sqrt{2/\pi}$ is about 0.798. AIM's score for candidate r in round t is then

$$u(D, r) = w_r\Big(\big\|\mu_r(D) - \mu_r(\hat{p}_{t-1})\big\|_1 - \sqrt{2/\pi}\,\sigma_t\, m_r\Big). \tag{17}$$

Read it as a balance in units of records. The first term is how far the model is from the truth on r, and the second is how far the noisy measurement would be from the truth, in expectation. So a candidate scores above zero only when its measurement is expected to bring the model closer to the truth. The script's version is short:

```
def score(
    data: Array,
    model: Array,
    attrs: Attrs,
    weight: float,
    sigma: float,
) -> float:
    """AIM's quality score of a candidate marginal: how far the model is from the data
    on it, minus the L1 error that measuring it with noise of standard deviation sigma
    would add in expectation, times the weight."""
    model_error = float(np.abs(marginal(data, attrs) - marginal(model, attrs)).sum())
    penalty = SQRT_2_OVER_PI * sigma * cells(attrs)
    return weight * (model_error - penalty)
```

The exponential mechanism needs the score's sensitivity, and the weight sets it.

Proposition 5.1 (Sensitivity of the score)**.** *Adding or removing one record changes $u(D, r)$ by at most w_r. So, over a candidate set $\mathcal{R}$, the sensitivity is $\Delta u = \max_{r \in \mathcal{R}} w_r$.*

Proof. The model $\hat{p}_{t-1}$ and the noise level are fixed when the score is computed, so only $\mu_r(D)$ changes between neighbouring datasets, and by the argument of Lemma 2.1 it changes in a single cell by 1. So the L_1 distance to the fixed vector $\mu_r(\hat{p}_{t-1})$ changes by at most 1, by the triangle inequality applied to that one cell. Multiplying by w_r gives the claim, and the sensitivity over the set is the largest of these. □

AIM then chooses r_t with probability proportional to $\exp(\varepsilon_t u(D, r)/(2\Delta u))$, as Proposition 2.3 prescribes. Table 6 and Figure 1 show the first round on the toy dataset. The model is still the independence model, so the pairs with real dependence, such as smoker with condition, have the largest errors, and two of them clear their noise penalty by a wide margin.

Table 6: The first round's selection on the toy dataset. The model error is the L_1 distance between the true marginal and the model's, the noise penalty is $\sqrt{2/\pi}\,\sigma_1$ times the marginal's cells, the score is the weight times their difference, and the last column is the exponential mechanism's probability of choosing that candidate at the first round's ε_1.

Candidate	w_r	Model error on it	Noise penalty	Score	Chance of being chosen
smoker	3	19	61	-127	9%
age	3	104	91	38	11%
exercise	3	38	61	-70	9%
condition	3	19	61	-127	9%
smoker × age	6	114	183	-416	6%
smoker × exercise	6	38	122	-506	5%
smoker × condition	6	177	122	333	17%
age × exercise	6	249	183	396	18%
age × condition	6	181	183	-9	10%
exercise × condition	6	88	122	-203	8%

But the last column of Table 6 shows that a high score barely helps at the start. At the starting budget $\varepsilon_1 = 0.0174$, the best score of 396 gives an exponent of only $0.0174 \times 396/12 \approx 0.57$. So the best candidate is only about $e^{0.57} \approx 1.8$ times as likely as an average one, and the selection is nearly random. In the toy run, round 1 chose the one-way marginal of smoker, which the model already knew. The cautious schedule of Equation 12 causes this, and the annealing rule exists to notice it and raise the stakes.




Figure 1: The first round's balance for each candidate: the model's error on the marginal against the L_1 error that measuring it would add in expectation. Only candidates whose blue bar is taller than their grey bar get a positive score.

5.5 Measurement and estimation

AIM measures the chosen marginal with Gaussian noise at level σ_t, by Proposition 2.2, and appends it to the list of measurements. Then it refits the model to the whole list by Equation 9, which is free by Proposition 2.1 (b). So the model stays consistent with every earlier measurement, weighted by its precision.

5.6 Annealing: when a round teaches too little

AIM's second new idea sets the number of rounds and the per-round budget automatically. After the refit, AIM compares the model's marginal over r_t before and after the measurement. The round taught too little if the measurement moved that marginal by no more than the noise it carried, that is, if

$$\left\|\mu_{r_t}(\hat{p}_t) - \mu_{r_t}(\hat{p}_{t-1})\right\|_1 \leq \sqrt{2/\pi}\,\sigma_t\, m_{r_t}. \tag{18}$$

In that case AIM doubles ε_{t+1} and halves σ_{t+1}, which by Equation 11 makes a round cost four times as much. Both reasons for a weak round are fixed. If no candidate was worth measuring at this noise level, halving σ makes more scores positive, and if the selection missed a good candidate, doubling ε makes it sharper. The comparison looks only at two fitted models, so it is free.

A second rule ends the loop cleanly. If the remaining budget $\rho - \rho_{\text{used}}$ is at most twice the next round's cost, AIM makes the next round the last one and sets its parameters to spend exactly what is left, in the same nine-to-one split:

$$\varepsilon_{t+1} = \sqrt{8 \cdot 0.1\,(\rho - \rho_{\text{used}})}, \qquad \sigma_{t+1} = \sqrt{\frac{1}{2 \cdot 0.9\,(\rho - \rho_{\text{used}})}}. \tag{19}$$

If you put these into Equation 11, you get 0.1 plus 0.9 of the remainder, which is all of it. So the loop's condition $\rho_{\text{used}} < \rho$ fails after that round and AIM stops. The script's version of both rules is short:

```
def anneal(
    eps: float, sigma: float, change: float, penalty: float, remaining: float
) -> tuple[float, float, bool, bool]:
    """The next round's (eps, sigma). If the last measurement moved the model by less
    than the noise it carried, double eps and halve sigma. Then, if what is left cannot
    pay for two such rounds, make the next round the last one and let it spend exactly
    the remaining budget. Also returns whether it annealed and whether it is the
    last."""
    annealed = change <= penalty
    if annealed:
        eps, sigma = 2 * eps, sigma / 2
    last = remaining <= 2 * round_cost(eps, sigma)
    if last:
        eps = math.sqrt(8 * (1 - MEASURE_SHARE) * remaining)
        sigma = math.sqrt(1 / (2 * MEASURE_SHARE * remaining))
    return eps, sigma, annealed, last
```

5.7 The run on the toy dataset

Table 7 lists every round, and Figure 2 plots the workload error of Equation 1 after each. The run is short, because the budget is small and each annealing makes a round cost four times as much.

Table 7: Every round of AIM on the toy dataset. The model error is the L_1 distance between the true marginal and the model's before the measurement, the noise penalty is $\sqrt{2/\pi}\,\sigma_t$ times the marginal's cells, and the change is how far the model moved on that marginal after refitting. A round anneals when the change is at most the penalty. The workload error is the paper's metric, the weighted L_1 error over the workload divided by the number of marginals and by n.

Round	Marginal chosen	σ_t	ε_t	Cost	Model error on it	Noise penalty	Change	Annealed	Workload error after
1	smoker	38.2	0.017	0.0004	19	61	1	yes	0.1412
2	smoker × condition	19.1	0.035	0.0015	178	61	173		0.1153
3	age × exercise	19.1	0.035	0.0015	249	91	247		0.0761

Round	Marginal chosen	σ_t	ε_t	Cost	Model error on it	Noise penalty	Change	Annealed	Workload error after
4	exercise × condition	19.1	0.035	0.0015	79	61	100		0.0722
5	exercise × condition	19.1	0.035	0.0015	22	61	18	yes	0.0726
6	age × condition	9.6	0.070	0.0061	171	46	172		0.0527
7	smoker × condition	7.3	0.091	0.0104	29	23	12	yes	0.0529




Figure 2: The model's workload error after each round of the toy run. Round 0 is the independence model from the one-way marginals. Circled rounds annealed, so the round after each paid four times as much.

Round 1 measured smoker again and moved the model by one record, less than the penalty, so AIM annealed. Rounds 2 and 3 used twice the selection budget and half the noise. They selected the two marginals with the strongest remaining dependencies, and workload error fell by almost half. Round 4 measured exercise with condition and corrected that mismatch. Round 5 selected that pair again, made no new progress, and triggered annealing. Round 6, at four times the original budget, captured the dependence between age and condition, the last large error. Round 7 used Equation 19 to spend the remaining budget and refined a marginal that was already close.

Error fell from 0.141 to 0.053, and Table 8 shows the final smoker-and-condition marginal.

Table 8: The marginal over smoker and condition in the toy dataset and in AIM's final model. Compare Table 4, the model before any two-way marginal was measured.

smoker	true: no condition	true: condition	final model: no condition	final model: condition
no	627	98	626.3	103.0
yes	181	94	185.4	104.0

On this toy workload, directly measuring all six marginals and fitting the model gives lower error than AIM: 0.035 rather than 0.053, using the whole budget at noise level $\sigma = 11.1$. None of the six marginals is redundant, so spending part of the budget on selection provides no benefit. AIM is designed for real workloads, where hundreds of marginals compete for the budget and a few can nearly determine many others.

6 Why AIM keeps its promise

AIM must not spend more than its budget ρ, although its rounds choose their own costs as the run goes. AIM touches the data only through Gaussian measurements and exponential-mechanism selections. So the proof must show that each round costs Equation 11, and that the costs never add up to more than ρ. The second part needs a budget filter, because the costs depend on earlier outputs and plain composition assumes that they are fixed in advance.

Lemma 6.1 (Budget filter)**.** *Consider a sequence of mechanisms in which the t-th is ρ_t-zCDP, where ρ_t may be chosen after seeing the outputs of the earlier mechanisms. If, for every choice the earlier outputs can lead to, the sum of the ρ_t over the rounds that run is at most ρ, then releasing all the outputs is ρ-zCDP.*

This is Theorem 3.1 of Feldman and Zrnic (2021). They prove it for Rényi differential privacy, which contains zCDP as the case of all orders at once, by a supermartingale argument over the rounds.

Theorem 6.1 (AIM is ρ-zCDP)**.** *With the paper's settings, $T = 16d$ and a nine-to-one split, AIM is ρ-zCDP. By Proposition 2.1 (c) it is therefore (ε, δ)-DP for every pair that the conversion gives.*

Proof. The plan is to list every access to the data with its cost, confirm that nothing else touches the data, and then show that the loop's bookkeeping keeps the total at ρ, so that Lemma 6.1 applies.

Step 1: the accesses and their costs. The initialization measures at most d one-way marginals, each at noise level σ_0. By Lemma 2.1 and Proposition 2.2 each costs $1/(2\sigma_0^2)$. So by Equation 12 the initialization costs at most $d/(2\sigma_0^2) = 0.9\rho\, d/T$, which is $0.9\rho/16$ for $T = 16d$. Round t makes two accesses. The selection is the exponential mechanism with the score of Equation 17 at budget

ε_t, whose sensitivity Proposition 5.1 gives, so by Proposition 2.3 it costs $\varepsilon_t^2/8$. The measurement is a Gaussian release at level σ_t, which costs $1/(2\sigma_t^2)$. Together they are Equation 11, which is exactly what the algorithm adds to ρ_{used}.

Step 2: nothing else touches the data. The model fits of Equation 9 use only the released measurements. The candidate weights depend on the workload alone, and the candidate filter depends on the sets already selected and on ρ_{used}, both of which are released. The annealing test of Equation 18 compares two fitted models, and the final-round rule of Equation 19 reads ρ_{used}. The rounding to records uses the final model. By Proposition 2.1 (b), none of this adds to the cost. In particular, the next round's ε_{t+1} and σ_{t+1} are functions of earlier outputs, which is exactly the situation Lemma 6.1 allows.

Step 3: the total never exceeds ρ. After the initialization, by Step 1, the remaining budget is at least $\rho(1 - 0.9/16)$, and by Equation 12 the first round costs $\rho/T = \rho/(16d)$, which is smaller. So the first round fits. Now consider any later round $t+1$, and look at the decision taken at the end of round t. If the final-round rule fired, round $t+1$ costs exactly the remainder, by the arithmetic below Equation 19, so after it $\rho_{\text{used}} = \rho$ and the loop stops. If the rule did not fire, the remainder was more than twice the cost of round $t+1$, so that round fits with budget to spare, and the argument repeats at the end of it. Either way ρ_{used} never exceeds ρ, on every path the random choices can take.

By Steps 1 to 3, AIM is a sequence of mechanisms with adaptively chosen costs whose sum is at most ρ on every path, and Lemma 6.1 makes it ρ-zCDP. □

So the final-round rule is not a detail. Without it, a round could start with less budget left than it costs, and AIM would have to overspend or waste the rest. The script checks the rule at the end of every run, where ρ_{used} equals ρ to floating-point precision.

7 What AIM says about its own error

A synthetic dataset is more useful when it comes with a bound on how far its marginals may be from the truth. AIM gives one at no extra privacy cost, because it computes the bound from values it has already released. Here is the simpler of the paper's two bounds.

Consider a marginal r that lies inside one or more of the measured sets. If you add up the cells of each such measurement $\tilde{y}_i$, the noisy marginal of the i-th measured set, you get a noisy copy of $\mu_r(D)$, the true marginal over r. A weighted average of the copies gives one estimate $\bar{y}_r$, which is the truth plus Gaussian noise of a known level $\bar{\sigma}_r$. The question is how large the L_1 norm of that noise can be.

Theorem 7.1 (A confidence bound for a measured marginal)**.** *Let $\bar{y}_r = \mu_r(D) + Z$, where Z has m_r independent $\mathcal{N}(0, \bar{\sigma}_r^2)$ entries. For every $\lambda \geq 0$, with probability at least $1 - e^{-\lambda^2}$,*

$$\left\|\mu_r(D) - \bar{y}_r\right\|_1 \leq \sqrt{2\ln 2}\;\bar{\sigma}_r\, m_r + \lambda\,\bar{\sigma}_r\sqrt{2m_r}. \tag{20}$$

This is Theorem 3 of the AIM paper. Its proof bounds the expected L_1 norm by Jensen's inequality, which gives the first term, slightly looser than Lemma 5.1. Then a concentration inequality for the L_1 norm, a Lipschitz function of the Gaussian vector, gives the second term, in which λ sets

the confidence. The bound on the synthetic dataset then follows by the triangle inequality. The distance from $\mu_r(\hat{D})$ to the truth is at most its known distance to $\bar{y}_r$, plus the bound above. For a marginal that no measured set contains, the paper gives a weaker bound built from the selection scores. In the paper's experiments, with λ set for 95% confidence, the bounds held. They were within a factor of about four of the true error for measured marginals, and eight for the others.

8 How well it works

The toy run cannot show whether AIM beats other methods on real data. The paper tests that on six public datasets with nine to sixteen attributes and about a thousand to a million records, each on three workloads of three-way marginals, at nine privacy budgets from $\varepsilon = 0.01$ to $\varepsilon = 100$, with $\delta = 10^{-9}$. Three competitors ignore the workload, among them MST, the winner of a NIST synthetic-data competition. Three use it, among them MWEM with Private-PGM as its model.

AIM had the lowest workload error in 76% of all settings, and in every setting with $\varepsilon \geq 1$. On average it beat the next best method in each setting by a factor of 1.6. On the workloads that concentrate on a few attributes, where the choice of what to measure matters most, the factor was up to 5.7. The paper also removes AIM's ideas one at a time and measures how much the error grows, as Table 9 reports.

Table 9: The paper's ablation, as geometric means over the datasets and budgets of the ratio of the error without the idea to the error with it.

Idea removed	Error grows by a factor of
Private-PGM, replaced by a relaxed table that need not be a distribution	2.36
adaptive rounds and the annealed budget split, replaced by fixed rounds	1.48
the noise-aware score of Equation 17, replaced by the model error alone	1.37
Gaussian noise, replaced by Laplace noise	1.18
add-or-remove neighbours, replaced by replace-one	1.13
the nine-to-one split, replaced by an even split	1.08
the initialization on one-way marginals	1.03

So generation from a real distribution, which Private-PGM gives, matters most, and the adaptive budget comes second. AIM's own two ideas, the annealing and the noise-aware score, together account for a factor of about two.

The method has three limits. Every attribute must be discrete, so the user must bin numeric attributes before any privacy is spent. The model's size is capped, so AIM cannot measure every marginal of a workload whose marginals overlap in a tangled way, however large the budget. And the running time grows with the model, because every round refits it. The paper ran AIM on one processor core with four gigabytes of memory, which the 80 megabyte cap keeps possible.

9 Sources

1. R. McKenna, B. Mullins, D. Sheldon and G. Miklau (2022), *AIM: An Adaptive and Iterative Mechanism for Differentially Private Synthetic Data*, PVLDB 15(11). The algorithm, its privacy theorem, the error bounds and the experiments. https://arxiv.org/abs/2201.12677
2. R. McKenna, D. Sheldon and G. Miklau (2019), *Graphical-model based estimation and inference for differential privacy*, ICML. Private-PGM: the objective of Equation 9, the form of its solution (Theorem 4.1) and the algorithms that fit it without building the full table. https://arxiv.org/abs/1901.09436
3. M. Bun and T. Steinke (2016), *Concentrated Differential Privacy: Simplifications, Extensions, and Lower Bounds*. The definition of zCDP, its composition and post-processing, and the Gaussian mechanism's cost. https://arxiv.org/abs/1605.02065
4. C. Canonne, G. Kamath and T. Steinke (2020), *The Discrete Gaussian for Differential Privacy*. The conversion from zCDP to (ε, δ)-DP in Proposition 2.1 (c). https://arxiv.org/abs/2004.00010
5. F. McSherry and K. Talwar (2007), *Mechanism Design via Differential Privacy*, FOCS. The exponential mechanism and its ε-DP guarantee.
6. M. Cesar and R. Rogers (2021), *Bounding, Concentrating, and Truncating: Unifying Privacy Loss Composition for Data Analytics*, ALT. The $\varepsilon^2/8$ zCDP cost of the exponential mechanism. https://arxiv.org/abs/2004.07223
7. V. Feldman and T. Zrnic (2021), *Individual Privacy Accounting via a Rényi Filter*, NeurIPS. The budget filter of Lemma 6.1. https://arxiv.org/abs/2008.11193
8. M. Hardt, K. Ligett and F. McSherry (2012), *A Simple and Practical Algorithm for Differentially Private Data Release*, NeurIPS. MWEM, the ancestor of AIM's select-measure-generate loop. https://arxiv.org/abs/1012.4763