



API Documentation

SentinelOne Api Documentation Version swagger.2_1.json

Get Accounts	28
Create Account	34
Get Account by ID	52
Update Account	58
Revert Policy	79
Reactivate Account	82
Expire an Account	84
Get Uninstall Password Metadata	88
Get Uninstall Password	90
Generate/Regenerate Uninstall Password	91
Revoke Uninstall Password	93
Export Accounts	94
Get Activities	95
Get Activity Types	99
Last activity as Syslog message	100
Export Activities	103
Broadcast Message	105

Connect to Network	117
Fetch Logs	129
Initiate Scan	141
Abort Scan	153
Disconnect from Network	165
Decommission	177
Uninstall	189
Restart	201
Shutdown	213
Approve Uninstall	225
Reject uninstall	237
Update Software	249
Reset Local Config	262
Set Persistent Configuration Overrides	275
Set External ID	287
Fetch Files	299
Move between Sites	301
Fetch Firewall Rules	313
Move to Console	325
Get Applications	338
Start Remote Shell	351
Can run Remote Shell	363
Terminate Remote Shell	376
Fetch Firewall Logs	388
Randomize UUID	400
Mark as up-to-date	412
Enable Network Discovery	424
Disable Network Discovery	436
Edit local upgrade/downgrade Site authorization	448
Reset Passphrases	460
Disable Agent	472
Enable Agent	484

Start Remote Profiling	496
Stop Remote Profiling	508
Approve Stateless Upgrades	520
Manage endpoint tags: add, remove, override	532
Clear Remote Shell	544
Get Agents	556
Count Agents	574
Get Passphrase	586
Export Agent Logs	599
Applications	599
Processes	601
Get local upgrade/downgrade Agent authorization	602
Export Agents	603
Enable Agent PNA for Hyperautomation	613
Disable PNA for Hyperautomation	626
Export Agents - Passphrases	638
Export Agents - Light	648
Get the endpoint tags that match the filters.	659
Endpoint tags count by Filters	663
List Access Tokens	665
Create Access Token	667
Delete Access Token	669
Get alerts	669
Update Threat Incident	679
Update Alert Analyst Verdict	683
Get a single NAC rule	687
Update NAC rule	689
Create or update NAC rule	692
Delete NAC rules	695
Get paginated NAC rules	698
Create presigned CSV upload URL	701
Import CSV file uploaded	704

Export NAC rules to CSV	707
Get rule change log	710
Get column metadata	712
Get CSV processing status	713
Get CSV export status	715
Download sample CSV file	717
Get NAC settings	718
Update NAC settings	720
Get all NAC labels	722
Get CVE data	724
Risks Data Export	729
Initiate scan	732
Get Application Inventory	734
Inventory Data Export	736
Get App Inventory Endpoints	737
Inventory Endpoints Data Export	741
Get Application CVEs	742
Application CVE Data Export	746
Get Aggregated Applications With Risk	747
Aggregated Application Risk Data Export	752
Get Applications With Risk	754
Application Risk Data Export	758
Get Endpoints For Vulnerable App	760
Risk Endpoint Data Export	765
Get Endpoint Apps	767
Update Application Management Settings	768
Get Application Management Settings	770
Export Applications	772
[DEPRECATED] Get Applications	774
[DEPRECATED] Get CVEs	778
All Policies OS Count	780
Get Available Packages	782

Has Policy	783
Get Parent Policies	785
Get Policies	786
Deactivate Policies	788
Policies OS Count	789
Create Policy	790
Update Policy	792
Policy Action	794
Reset Policy Retry Counter	796
Reorder Policies	797
Set Scope Inheriting	799
Validate Bucket	801
Get cloud funnel rule	803
Delete cloud funnel rule	805
Post onboarding cloud funnel	808
Validate Query	810
Create Estimator ID	813
Get estimate size of events	815
Get AWS assume role external ID.	816
Get cloud rogue resources	817
Export cloud rogue resources to csv (default) or json	820
Get Config Overrides	821
Create Config Override	825
Delete Config Overrides	830
Delete Config Override	832
Update Config Override	834
Get Rules	838
Create Rule	847
Delete Rules	857
Update Rule	861
Activate Rules	871
Disable Rules	875

Get Entity Mapping Options	879
Get Available Actions by Asset/Entity Type	880
Perform an Action on selected assets/entities	883
Fetch surface ids in case of select all with filters	884
Internal api only to notify action was triggered without actually performing it	885
[DEPRECATED] Create Query and Get QueryId	886
[DEPRECATED] Cancel Running Query	888
[DEPRECATED] Get Query Status	890
[DEPRECATED] Get Events	891
[DEPRECATED] Get Process State	896
[DEPRECATED] Get Events By Type	897
[DEPRECATED] Create a Power Query and Get QueryId	902
[DEPRECATED] Ping a Power Query if results haven't been retrieved	905
Download source process file	906
S1 RSS Feed	908
Get Default Reports	909
Get Default Report Tasks	912
Create Default Report Task	915
Update Default Report Task	917
Delete Default Reports	920
Delete Default Report Tasks	921
Download Default Report	923
Get Default Insight Reports	924
Get Device Rules	925
Create Device Control Rule	929
Delete Rules	934
Update Device Rule	937
Copy Rules	942
Move rules	945
Reorder Rules	949
Get Configuration	952
Update Configuration	954

Export Rules	957
Get Device Control Events	959
Enable/Disable Rules	963
Get all tags rules	966
Create new tag rule	969
Delete tag rules	973
Update tag rule	975
Check how many assets this tag rule matches	979
Import Exclusions	983
Get Exclusion Import Validation Report	986
Import Blocklist Items	986
Get Blocklist Import Validation Report	989
Get Exclusions	989
Create Exclusion	994
Update Exclusions	998
Delete Exclusions	1002
Get Blocklist	1005
Create Blocklist Item	1009
Update Blocklist Item	1012
Delete Blocklist Item	1016
Validate Exclusion Item	1019
Validate Blocklist Item	1021
Export Exclusions	1023
Export Blocklist	1025
Get Exclusions	1027
Delete Exclusions	1033
Create Unified Exclusion	1035
Update Exclusions	1037
Create Bulk Unified Exclusion	1038
Import Unified Exclusions	1040
Export Unified Exclusions	1042
Get Exclusion Actions	1045

Get Filters	1052
Save Filter	1061
Update Filter	1078
Delete Filter	1093
[DEPRECATED] Get Deep Visibility Filters	1095
[DEPRECATED] Save Deep Visibility Filter	1096
[DEPRECATED] Delete Deep Visibility Filter	1098
[DEPRECATED] Update Deep Visibility Filter	1099
Upload CSV file	1102
Get Filters	1104
Save Filter	1106
Filters with Metadata	1109
Update Filter	1111
Delete Filter	1113
Get Firewall Rules	1114
Create Firewall Rule	1119
Delete Rules	1126
Copy Rules	1130
Move Rules	1133
Set Location	1137
Reorder Rules	1141
Get Configuration	1144
Update Configuration	1146
Export Rules	1149
Import Rules	1151
Enable/Disable Rules	1153
Get Protocols	1156
Add Rule Tags	1158
Remove Rule Tags	1162
Get Tag Firewall Rules	1166
Update Firewall Rule	1171
Application Forensics	1178

Application Forensics - Detailed	1181
Application Connections	1185
Export Application	1187
Get Gateways	1188
Update Gateways	1194
Update Gateway	1199
Query the graph based on query builder filters	1203
Query the graph based on query builder filters	1205
Query the sub graph of an asset type and id	1208
Get Graph Query Builder Initial Metadata	1211
Get Graph Query Builder Initial Metadata	1212
Get Query Builder metadata For Requested Resource Types	1213
Auto Complete	1214
Auto Complete	1216
Tag Auto Complete	1218
Get all of the feature toggles for graph services.	1220
Get the available relations	1221
Get graph recent query list	1222
Get graph query list	1223
Save graph query	1225
Get graph query counts by type	1227
Update graph query	1228
Delete graph query	1231
Get Groups	1232
Create Group	1236
Regenerate Group Token	1252
Delete Group	1253
Update Group	1254
Get Group by ID	1270
Revert Policy	1271
Move Agents	1274
Update Ranks	1285

Get Site registration token by ID	1286
Hash Reputation verdict	1288
List all workflow executions	1289
Get a workflow execution by its ID	1291
Trigger a workflow that uses a manual trigger or a scheduled trigger	1293
Get workflow execution output	1294
List workflow versions	1296
List all workflows	1297
Activate a workflow version	1299
Deactivate The active workflow	1300
Export workflow	1302
Batch export workflows	1303
Import workflow	1303
Batch import workflows	1307
Import custom integration from OpenAPI/Swagger spec file	1308
Export custom integration	1310
Batch export custom custom integrations	1311
Import custom integration	1311
Batch import custom integrations	1314
Expression Breakdown	1316
Evaluate Expression	1318
Get Assessment Status	1321
Get Exposures	1324
Get Affected Objects	1327
Trigger Assessment	1333
Set Skipped Exposures	1336
Set Acknowledged Status	1339
Delete AD configuration	1341
Add complete AD configuration	1343
Get timezones	1347
Get AD domains	1348
Get available features	1349

Get AD configurations	1350
Get AD configuration features	1351
Replace AD Connector	1352
Check if IDR is enabled on endpoint	1354
Get Windows Unified Agents	1356
Get Cloudlink Configurations	1358
Get onboarding status	1359
Get Policy List	1360
Get Inheritance Status	1361
Activate Policy	1362
Get Identity Policy Details	1364
Delete Policies	1366
Detach Policy Inheritance	1367
Revert Policy Inheritance	1369
Deactivate Policies	1371
Get Policy Info for Agent	1373
Create Policy	1375
Update Policy	1378
Duplicate Policy	1381
Get Privileged Admins	1383
Get Service Accounts	1385
Get Domain Controllers	1386
Get Delegated Admins	1387
Categories and counts	1388
Counts per subcategory for categories	1389
Get inventory counts for menu items	1395
Export Cloud Tags to CSV or JSON	1402
Assets	1403
Assets using POST	1408
Export assets to CSV or JSON	1413
Perform action	1417
Available actions	1422

Assets	1427
Assets using POST	1431
Perform action	1436
Export assets to CSV or JSON	1441
Available actions	1444
Filter counts	1450
Free text filters	1454
Auto Complete	1455
Assets	1459
Assets using POST	1464
Perform action	1469
Export assets to CSV or JSON	1474
Available actions	1477
Filter counts	1483
Free text filters	1487
Auto Complete	1488
Assets	1492
Assets using POST	1497
Perform action	1502
Export assets to CSV or JSON	1507
Available actions	1510
Filter counts	1516
Free text filters	1520
Auto Complete	1521
Assets	1525
Assets using POST	1530
Perform action	1535
Export assets to CSV or JSON	1540
Available actions	1543
Filter counts	1549
Free text filters	1553
Auto Complete	1554

Assets	1558
Export assets to CSV or JSON	1566
Perform action	1573
Available actions	1580
Filter counts	1588
Free text filters	1595
Auto Complete	1596
Assets	1603
Assets using POST	1614
Perform action	1625
Export assets to CSV or JSON	1636
Available actions	1646
Filter counts	1658
Free text filters	1669
Auto Complete	1670
Assets	1681
Assets using POST	1686
Perform action	1691
Export assets to CSV or JSON	1696
Available actions	1699
Filter counts	1705
Free text filters	1709
Auto Complete	1710
Assets	1714
Assets using POST	1720
Perform action	1726
Export assets to CSV or JSON	1731
Available actions	1735
Filter counts	1742
Free text filters	1747
Auto Complete	1748
Assets	1753

Assets using POST	1758
Perform action	1763
Export assets to CSV or JSON	1768
Available actions	1771
Filter counts	1777
Free text filters	1781
Auto Complete	1782
Assets	1786
Assets using POST	1792
Export assets to CSV or JSON	1798
Perform action	1803
Available actions	1808
Filter counts	1814
Free text filters	1819
Auto Complete	1820
Assets	1825
Assets using POST	1833
Export assets to CSV or JSON	1841
Perform action	1849
Available actions	1857
Filter counts	1866
Free text filters	1874
Auto Complete	1875
Filter counts	1883
Free text filters	1888
Auto Complete	1889
Upload CSV file	1893
Assets	1895
Assets using POST	1900
Perform action	1905
Export assets to CSV or JSON	1910
Available actions	1913

Filter counts	1919
Free text filters	1923
Auto Complete	1924
Assets	1928
Assets using POST	1933
Export assets to CSV or JSON	1938
Perform action	1942
Available actions	1946
Filter counts	1951
Free text filters	1955
Auto Complete	1956
Assets	1960
Assets using POST	1967
Export assets to CSV or JSON	1974
Perform action	1979
Available actions	1986
Filter counts	1993
Free text filters	1999
Auto Complete	2000
Assets	2006
Export assets to CSV or JSON	2013
Perform action	2019
Available actions	2025
Filter counts	2032
Free text filters	2038
Auto Complete	2039
Assets	2045
Assets using POST	2050
Export assets to CSV or JSON	2055
Perform action	2059
Available actions	2063
Assets	2068

Export assets to CSV or JSON	2073
Perform action	2077
Available actions	2083
Filter counts	2089
Free text filters	2094
Auto Complete	2095
Filter counts	2100
Free text filters	2104
Auto Complete	2105
Create or update note against asset	2109
Delete note	2110
Assets	2111
Assets using POST	2122
Export assets to CSV or JSON	2133
Perform action	2144
Available actions	2155
Filter counts	2167
Free text filters	2178
Auto Complete	2179
Assets	2190
Assets using POST	2196
Export assets to CSV or JSON	2202
Available actions	2207
Perform action	2213
Filter counts	2218
Free text filters	2223
Auto Complete	2224
Get asset tags filters count	2229
Fetch all Unique Tags	2231
Get count of assets by tag id	2233
Get tags info of assets by asset id	2235
Get Available Actions by Asset/Entity Type	2241

Perform an Action on selected assets/entities	2256
Loads all agent ids for the unified actions	2270
Filter counts	2285
Free text filters	2294
Auto Complete	2295
Assets	2304
Assets using POST	2313
Export assets to CSV or JSON	2322
Perform action	2330
Available actions	2339
Update sites add-ons	2349
Get Agent Merged Updates	2352
Create Location	2354
Get Locations	2362
Delete Locations	2368
Update Location	2371
Get Log Collection rules	2378
Create a log collection rule	2384
Delete log collection rules	2388
Get Log Collection rules by agent type	2392
Get Agent type count	2398
Update a log collection rule	2400
Change activation status of log collection rules	2403
Export log collection rules	2408
Export log collection rules	2410
Launch a query	2412
Poll query	2422
Delete query	2424
Delete Application	2425
Get Installed Applications	2427
Install Applications	2429
Update Application Configuration	2431

Get Applications Catalog	2433
Get Configuration Fields	2435
Get Configuration Fields For Installed Application	2436
Enable Or Disable Application	2438
Get application log	2440
Provision - Persist MSSP partner key	2441
Provision - Update MSSP partner key	2442
Provision - Get MSSP partner key	2444
Deletes MSSP partner key by client ID	2446
Provision - Provision tenant with admin user	2447
Provision - Get tenant with users	2448
Provision - Check if tenant can be provisioned	2451
Provision - Provision MSSP partner with admin user	2453
Provision - Get MSSP partner with admin user	2455
Devices - Get list of devices for specific scope	2457
Incidents - Get list of incidents	2462
Get Network Discovery Table	2466
Export Network Discovery Data	2472
JSON Raw Data	2475
Export JSON Raw Data	2476
Get Network Discovery Settings	2476
Update Network Discovery Settings	2479
Change Device Review in Bulk	2485
Change Device Review	2489
Change Device Tags	2493
Get Self Enablement	2497
Change Network Discovery or Unprotected Endpoints Discovery Features	2499
Change the Self-Enablement for Accounts	2501
Features Configuration for New Sites	2502
Change Feature Defaults for New Sites	2502
Get Firewall Rules	2505
Create Firewall Rule	2510

Delete Rules	2517
Copy Rules	2521
Move Rules	2524
Set Location	2528
Reorder Rules	2532
Get Configuration	2535
Update Configuration	2537
Export Rules	2540
Import Rules	2542
Enable/Disable Rules	2544
Get Protocols	2547
Add Rule Tags	2549
Remove Rule Tags	2553
Cloud Inventory resource overview	2557
Get Managed Detection Rules	2560
Get Managed Detection Rules	2567
Get Template Detection Rules	2573
Enable a Managed Detection Rule	2578
Disable a Managed Detection Rule	2582
Free-Text Filters	2585
Update settings for Managed Detection Rules	2586
Get settings for Managed Detection Rules	2588
Get Surfaces	2590
Get Severities	2590
Get Data Sources	2590
Get Statuses	2590
Group Policy	2591
Update Group Policy	2605
Site Policy	2634
Update Site Policy	2649
Account Policy	2678
Update Account Policy	2693

Global Policy	2722
Update Global Policy	2737
Get All Roles	2766
Get Specific Role Definition	2769
Update role	2773
Delete role	2776
Create new role	2779
Get template for new role	2782
Create new Destination profile.	2785
Get available Destination profiles	2787
Delete multiple Destination profiles by ID	2788
Delete Destination profile by ID	2791
Update existing Destination profile	2791
Get Destination profile by ID	2794
Set profile as default profile of the scope	2796
Get results sent to data exporter	2798
Schedule remote script for future run.	2800
Schedule forensics for future run.	2804
Delete multiple scheduled tasks by ID	2808
Get available Scheduled Tasks	2810
Update existing Scheduled task	2815
Start collection of Forensics artifacts according to specified profile	2818
Return result of collection task	2829
Returns collection file download pre-signed url	2833
Check if collection file exists for given storyline	2834
Get list of supported artifact types	2835
Get Collection profile by ID	2836
Update Collection profile by ID	2839
Delete Collection profiles	2842
Create new Collection profile	2846
Get list of available Collection profiles	2849
Run Remote Script	2852

Get Remote Scripts Tasks Status	2864
Get Script Results	2868
Get upload limit for Package	2870
Get script content	2870
Get Scripts	2872
Upload New Script	2876
Delete Scripts	2880
Update a Script	2884
Update a Script	2887
Get paginated pending executions	2891
Approve/decline pending execution	2896
Gets a guardrails configuration for a given scope	2899
Updates or inserts (if record does not exist) a guardrails configuration	2900
Deletes a specific guardrails configuration	2902
Check whether guardrail applies to an execution	2904
List saved searches	2906
Create or update saved searches	2908
Delete saved searches	2910
Create Cred Group	2912
Get Cred groups	2914
Delete Cred Group	2916
Add cred details	2918
Get Cred group details	2920
Delete Cred Group Detail	2922
Update Cred Group Details	2924
Get Service Users	2926
Create Service User	2929
Get Service User	2933
Update Service User	2936
Delete Service User	2940
Export Service Users	2942
Generate API Token for Service User	2942

Bulk Delete Service Users	2945
Get SSO Settings	2947
Set SSO Settings	2950
Get SSO Service Provider Certificate	2954
Download SSO Service Provider Certificate	2955
Test SSO Settings	2955
Get Notification Settings	2959
Set Notification Settings	2961
Clear Pending Emails	2966
Get SMTP Settings	2969
Set SMTP Settings	2970
Test SMTP Settings	2973
Get Syslog Settings	2976
Set Syslog Settings	2978
Test Syslog Settings	2981
Get SMS Settings	2984
Set SMS Settings	2986
Get Notification Recipients	2988
Set Notification Recipients	2990
Delete Notification Recipient	2993
Get AD Settings	2995
Set AD Settings	2996
Test AD Settings	2998
Get AD FQDNs	3000
Set AD FQDNs	3002
Get Microsoft Settings	3004
Set Microsoft Settings	3006
Test Microsoft Settings	3008
Get Sites	3011
Create Site	3018
Export Sites	3039
Get Site by ID	3040

Update Site	3045
Delete Site	3066
Get Site registration token by ID	3067
Revert Policy	3068
Create duplicate site	3070
Create Site and User	3088
Regenerate Site Key	3110
Reactivate Site	3112
Expire Site	3114
Update Sites	3118
Get local upgrade/downgrade Site authorization	3122
Edit local upgrade/downgrade Site authorization	3123
Get a CSV file of local upgrade/downgrade Site authorization data	3125
System Info	3126
System Status	3127
Database Status	3128
Cache Status	3129
Get System Config	3130
Set System Config	3134
System Environment	3141
Create a new endpoint tag	3142
Delete tags	3144
Edit an existing tag	3147
Get Tags	3149
Create Tags	3152
Delete Tags	3154
Delete Tag by ID	3157
Edit Tag	3159
Get Task Configuration	3161
Create Task	3163
Get Task Configuration (Flexible MW)	3166
Update Task Configuration (Flexible MW)	3168

Has Child Scopes	3173
Get Child Scope Task Configuration	3175
Export Maintenance Windows as CSV	3177
Get IOCs	3178
Create IOCs	3184
Delete IOCs	3188
Create IOCs from STIX bundle	3192
Get Threat Intelligence user config	3196
Create Threat Intelligence user config	3198
Delete Threat Intelligence user config	3201
Get Threat Notes	3204
Add Note to Multiple	3206
Update Threat Note	3214
Delete Threat Note	3217
Get Threats	3218
Mitigate Threats	3233
Add to Blocklist	3241
Fetch Threat File	3249
Disable Engines	3257
Exclusion Options	3260
Get Events	3261
Add to Exclusions	3266
Export Threats	3275
Add to Blocklist (Deep Visibility)	3280
Mark as Threat (Deep Visibility)	3283
Mitigate Alerts	3285
Export Mitigation Report	3288
Updated Threat Incident	3288
Update Threat Analyst Verdict	3296
Update Threat External Ticket ID	3304
Download from cloud	3312
Disconnect Container	3314

Reconnect Container	3321
Get Quarantined Files	3329
Delete Quarantined Files	3331
Get Threat Timeline	3339
Export Threat Timeline	3341
Export Events	3342
Get Unprotected Endpoints Discovery Table	3343
Export Unprotected Endpoints Discovery Data	3347
Get Unprotected Endpoints Discovery Settings	3349
Update Unprotected Endpoints Discovery Settings	3352
Latest Packages by OS	3356
Get Latest Packages	3363
Delete Packages	3367
Update package	3370
Upload Agent Package	3373
Upload System Package	3377
Deploy System Package	3380
Download Agent Package	3381
Download Package	3381
User by token	3382
List users	3385
Create User	3391
Export Users	3397
Get User	3399
Delete User	3404
Update User	3405
Bulk Delete Users	3410
Generate iFrame Token	3412
Enable 2FA	3415
Disable 2FA	3417
Generate API Token	3419
Revoke API Token	3421

API Token by User ID	3423
API Token Details	3424
Enable 2FA App	3426
Request 2FA App	3428
Change Password	3430
Auth Elevate	3432
Sign EULA	3434
Check Global User	3435
Check Remote Shell Permissions	3436
Check Viewer	3437
Email Verification	3438
Validate Verification Token	3440
Send Verification Email	3441
Reset 2FA	3444
Delete 2FA	3447
Enroll 2FA	3449
Redirect to SSO	3451
Redirect to SSO for re-authentication	3451
Auth by SSO	3452
Login	3452
Logout	3455
Login by API Token	3456
Login by Token	3458
Continue with login due to upcoming password expiration or SSO 2FA setup	3458
Set a New Password	3461
Prompt reset password	3463
Reset password on next login	3466
Auth App	3470
Fetch filter count	3473
Delete a VCS Integration	3474
Disable scanning for repositories in a VCS integration	3475
Edit tags for repositories in a VCS integration	3477

Enable scanning for repositories in a VCS integration	3479
Fetch repository tags	3481
Delete a VCS integration	3483
Update a VCS integration	3484
List VCS integration repositories	3486
Resync VCS Integration Repositories	3488
List VCS integrations	3489
Edit tags for a VCS integration	3490
Onboard a new VCS integration	3492
List VCS and CICD scanner policies	3494
Create a VCS and CICD scanner policy	3496
Get max allowed priority	3498
Delete a VCS and CICD scanner policy	3500
Get a VCS and CICD scanner policy	3501
Update a VCS and CICD scanner policy	3502
Register Tunnel User	3506

Accounts

Get Accounts

GET /web/api/v2.1/accounts

Get the Accounts, and their data, that match the filter. This command gives the Account IDs, which other commands require. Accounts are created by a Global User or by SentinelOne. Each Account contains Sites, which can inherit assets and settings. Each Account has one or more SKUs, that you assign to the Sites. To have both Core and Complete Sites in an Account, the Account must have both SKUs.

Parameters

accountids	optional	List of Account IDs to search for. Example: "225494730938493804,225494730938493915".
accounttype	optional	Account type. Example: "Trial".
activelicenses	optional	Active licenses
billingmode	optional	Billing mode. Example: "subscription".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat	optional	Timestamp of Account creation. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
expiration	optional	Expiration. Example: "2018-02-27T04:49:26.257525Z".
features	optional	Filter the list of Accounts for those that support this feature. Example: "firewall-control".
ids	optional	A list of Account IDs. Example: "225494730938493804,225494730938493915".
isdefault	optional	Is default
limit	optional	Limit number of returned items (1-1000). Example: "10".
module	optional	Module. Example: "star,rso".
name	optional	Name. Example: "My Account".

name__contains	optional	Free-text filter by account name (supports multiple values)
query	optional	Full text search for fields: name. (Note: on single-Account Consoles, the Account name will not be matched)
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sku	optional	Sku. Example: "core".
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
state	optional	Account state. Example: "active".
states	optional	Filter by state, such as active or expired.
statesnin	optional	List of states to not filter
totallicenses	optional	Total licenses
updatedat	optional	Timestamp of last update. Example: "2018-02-27T04:49:26.257525Z".
usagetype	optional	Usage type. Example: "customer".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Accounts - response - pagination table
data	Response data	false	see Get Accounts - response - data table
errors	Errors	false	array

Get Accounts - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Accounts - response - data

Name	Description	Required	Value
accountType	Account type	false	string
activeAgents	Total Agents in the Account	false	integer
agentsInCompleteSku	[DEPRECATED] Number of Agents connected to a Complete site	false	integer
agentsInControlSku	[DEPRECATED] Number of Agents connected to a Control site	false	integer
agentsInCoreSku	[DEPRECATED] Number of Agents connected to a Core site	false	integer
billingMode	Billing mode	false	enum
completeSites	[DEPRECATED] Number of Sites in suite Complete	false	integer
controlSites	[DEPRECATED] Number of Sites in suite Control	false	integer
coreSites	[DEPRECATED] Number of Sites in suite Core	false	integer
createdAt	Timestamp of Account creation	false	string
creator	The user that created the group	false	string
creatorId	The ID of the user that created the group	false	string
expiration	Expiration	false	string

externalId	ID of CRM external system	false	string
id	Account ID	false	string
irFields	Ir fields	false	see Get Accounts - response - irFields table
isDefault	Is default	false	boolean
licenses	The account licenses.	false	see Get Accounts - response - licenses table
makeSocDefaultUi	True if SOC is to be enabled by default	false	boolean
name	Name	false	string
numberOfSites	Total number of Sites in this Account	false	integer
promptFields	Prompt fields	false	see Get Accounts - response - promptFields table
salesforceId		false	string
skus	[DEPRECATED] The list of SKUs for the Account.	false	see Get Accounts - response - skus table
state	Account state	false	enum
totalComplete	[DEPRECATED] Total Number of Complete licenses	false	integer
totalControl	[DEPRECATED] Total Number of Control licenses	false	integer
totalCore	[DEPRECATED] Total Number of Core licenses	false	integer
totalLicenses	The total number of licenses on all Surfaces for all Bundles.	false	integer
unlimitedComplete	[DEPRECATED] True if Complete licenses count is unlimited	false	boolean
unlimitedControl	[DEPRECATED] True if Control licenses count is unlimited	false	boolean
unlimitedCore	[DEPRECATED] True if Core licenses count is unlimited	false	boolean
unlimitedExpiration	The Account does not expire	false	boolean
updatedAt	Timestamp of last update	false	string
usageType	Usage type	false	enum

Get Accounts - response - irFields

Name	Description	Required	Value
companyName	The customer's company name	true	string
contactEmail	Business email of the customer contact. Must not match the IR partner domain, the submitter's own domain, or a free/personal email provider (e.g. Gmail, Yahoo, Hotmail)	true	string
contactFirstName	First name of the customer contact	true	string
contactLastName	Last name of the customer contact	true	string
country	Country of the customer	true	string
industry	Industry vertical of the customer	true	enum
numberOfEmployeesEndpoints	Estimated number of employees or endpoints at the customer	true	integer
city	City of the customer	false	string
postal	Postal / ZIP code of the customer	false	string
region	State or region within the country	false	string

Get Accounts - response - licenses

Name	Description	Required	Value
bundles	The licenses Bundles	false	see Get Accounts - response - bundles table
modules	The licenses Add-ons	false	see Get Accounts - response - modules table
settings	The licenses Settings	false	see Get Accounts - response - settings table

Get Accounts - response - bundles

Name	Description	Required	Value
displayName	The Bundle display name	false	string
majorVersion	The Bundle major version	false	integer
minorVersion	The Bundle minor version	false	integer
name	The Bundle internal api name	false	string
surfaces	The Surfaces in the Bundle	false	see Get Accounts - response - surfaces table

totalSurfaces	The total number of Surfaces in this Bundle. -1 indicates unlimited count.	false	integer
---------------	--	-------	---------

Get Accounts - response - surfaces

Name	Description	Required	Value
count	The Surface count. -1 indicates unlimited count	false	integer
name	The Surface name.	false	string

Get Accounts - response - modules

Name	Description	Required	Value
displayName	The Add-on display name	false	string
majorVersion	The Add-on major version	false	integer
name	The Add-on internal api name	false	string

Get Accounts - response - settings

Name	Description	Required	Value
displayName	[DEPRECATED] The Setting display name	false	string
groupName	The Setting group name	false	
setting	The Setting display name	false	
settingGroup	[DEPRECATED] The Setting group name	false	string
settingGroupDisplayName	The Setting group display name	false	string

Get Accounts - response - promptFields

Name	Description	Required	Value
------	-------------	----------	-------

promptRegion	Region associated with the prompt	false	enum
promptTenantName	Tenant name associated with the prompt	false	string
promptUserEmail	Email of the user associated with the prompt	false	string
promptUserName	Name of the user associated with the prompt	false	string

Get Accounts - response - skus

Name	Description	Required	Value
agentsInSku	Total agents commissioned in this SKU.	false	integer
totalLicenses	Number of licenses for this specific SKU. Applicable only if unlimited is False	false	integer
type	The suite of product features active for this account	false	enum
unlimited	True if this is an unlimited SKU.	false	boolean

Create Account

POST /web/api/v2.1/accounts

Create a new Account. This command requires Global permissions and an MSSP deployment. Consult with your SE before you run this command. An Account is a logical segment with permissions to configure features for specific Sites. Multiple Accounts can be useful for deployments with multiple Sites for third-parties (such as MSSP). Each Account has one or more SKUs, that you assign to Sites. If an Account has the Complete SKU, and you create a new Site in the Account, it will automatically have the Complete SKU. Best practice: Run "name-available" first, to make sure the name is unique in your deployment.

BEST PRACTICE

Run "name-available" first, to make sure the name is unique in your deployment.

Response Messages

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Account - body - data table

Create Account - body - data

Name	Description	Required	Value
name	Name	true	string
accountType	Account type: Trial or Paid	false	enum
billingMode	Billing mode	false	enum
expiration	Expiration	false	string
externalId	ID of CRM external system	false	string
inherits	True if the policy is inherited from Global, False if the Account has its own edited policy	false	boolean
irFields	IR related fields	false	see Create Account - body - irFields table
licenses	The license configuration for the Account	false	see Create Account - body - licenses table
makeSocDefaultUi	True if SOC is to be enabled by default	false	boolean
policy	Policy is mandatory if it was edited (inherits = false), otherwise ignored.	false	see Create Account - body - policy table
promptFields	Prompt related fields	false	see Create Account - body - promptFields table
skus	[DEPRECATED] The list of allowed SKUs for the Account	false	see Create Account - body - skus table
unlimitedExpiration	If expiration is not unlimited, enter the expiration date	false	boolean
usageType	Usage type	false	enum

Create Account - body - irFields

Name	Description	Required	Value
companyName	The customer's company name	true	string
contactEmail	Business email of the customer contact. Must not match the IR partner domain, the submitter's own domain, or a free/personal email	true	string

	provider (e.g. Gmail, Yahoo, Hotmail)		
contactFirstName	First name of the customer contact	true	string
contactLastName	Last name of the customer contact	true	string
country	Country of the customer	true	string
industry	Industry vertical of the customer	true	enum
numberOfEmployeesEndpoints	Estimated number of employees or endpoints at the customer	true	integer
city	City of the customer	false	string
postal	Postal / ZIP code of the customer	false	string
region	State or region within the country	false	string

Create Account - body - licenses

Name	Description	Required	Value
bundles	The list of Bundles selected	false	see Create Account - body - bundles table
modules	The list of Add-ons selected	false	see Create Account - body - modules table
settings	The list of Settings selected for the Bundle and Add-ons. If a Bundle or Add-on requires a Setting that is not defined, the default Setting is used.	false	see Create Account - body - settings table

Create Account - body - bundles

Name	Description	Required	Value
name		true	string
majorVersion		false	integer
surfaces		false	see Create Account - body - surfaces table

Create Account - body - surfaces

Name	Description	Required	Value
------	-------------	----------	-------

name		true	string
count	The number of licenses per Surface. -1 indicates unlimited count.	false	integer

Create Account - body - modules

Name	Description	Required	Value
name		true	string

Create Account - body - settings

Name	Description	Required	Value
groupName		true	string
setting		true	string

Create Account - body - policy

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Create Account - body - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer

autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Create Account - body - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Create Account - body - dvAttributesPerEventType table
engines	The engines statuses	false	see Create Account - body - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Create Account - body - forensicsAutoTriggering table
identityConfigurationSettings	Identity configuration	false	see Create Account - body - identityConfigurationSettings table
identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Create Account - body - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean

mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Create Account - body - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Create Account - body - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean
researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first registration	false	boolean
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Create Account - body - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string

contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Create Account - body - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Create Account - body - dvAttributesPerEventType

Name	Description	Required	Value
------	-------------	----------	-------

autoInstallBrowserExtensions	Auto install browser extensions	false	see Create Account - body - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Create Account - body - behavioralIndicators table
commandScripts	Command scripts event	false	see Create Account - body - commandScripts table
crossProcess	Cross process event	false	see Create Account - body - crossProcess table
dataMasking	Data masking	false	see Create Account - body - dataMasking table
dllModuleLoad	DLL module load event	false	see Create Account - body - dllModuleLoad table
dns	Network event - DNS	false	see Create Account - body - dns table
driver	Driver	false	see Create Account - body - driver table
externalDeviceActivity	External Device Activity	false	see Create Account - body - externalDeviceActivity table
file	File event	false	see Create Account - body - file table
ip	Network event - IP	false	see Create Account - body - ip table
login	User login/logout event	false	see Create Account - body - login table
namedPipe	Named Pipe	false	see Create Account - body - namedPipe table
namedPipeExtended	Named Pipe Extended	false	see Create Account - body - namedPipeExtended table
openDirectoryActivity	Open Directory Activity	false	see Create Account - body - openDirectoryActivity table
process	Process event	false	see Create Account - body - process table
profileActivity	Profile Activity	false	see Create Account - body - profileActivity table
registry	Registry event	false	see Create Account - body - registry table
scheduledTask	Scheduled task event	false	see Create Account - body - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Create Account - body - smartFileMonitoring table
url	URL Actions event	false	see Create Account - body - url table
userSubstitution	User Substitution	false	see Create Account - body - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Create Account - body - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Create Account - body - windowsEventLogsExtended table

Create Account - body - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Create Account - body - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Create Account - body - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Create Account - body - crossProcess

Name	Description	Required	Value
dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Create Account - body - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Create Account - body - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Create Account - body - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Create Account - body - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Create Account - body - externalDeviceActivity

Name	Description	Required	Value
dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Create Account - body - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Create Account - body - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Create Account - body - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Create Account - body - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean
dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean

Create Account - body - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Create Account - body - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean

r			
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean
dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean

Create Account - body - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Create Account - body - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Create Account - body - registry

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Create Account - body - scheduledTask

Name	Description	Required	Value
dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Create Account - body - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Create Account - body - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Create Account - body - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Create Account - body - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Create Account - body - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Create Account - body - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum

preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Create Account - body - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean
macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Create Account - body - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer

identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean
-----------------------------	--	-------	---------

Create Account - body - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean
externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Create Account - body - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Create Account - body - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Create Account - body - promptFields

Name	Description	Required	Value
promptRegion	Region associated with the prompt	false	enum
promptTenantName	Tenant name associated with the prompt	false	string
promptUserEmail	Email of the user associated with the prompt	false	string
promptUserName	Name of the user associated with the prompt	false	string

Create Account - body - skus

Name	Description	Required	Value
totalLicenses	Number of licenses for this specific SKU. Applicable only if unlimited is False	false	integer
type	The suite of product features active for this Account	false	enum
unlimited	True if this is an unlimited SKU. Total licenses will be ignored if unlimited is True	false	boolean

Get Account by ID

GET /web/api/v2.1/accounts/{account_id}

Get Account data from a given Account ID. To get an Account ID, run "accounts".

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

404 - Account not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Account by ID - response - data table
errors	Errors	false	array

Get Account by ID - response - data

Name	Description	Required	Value
accountType	Account type	false	string
activeAgents	Total Agents in the Account	false	integer
agentsInCompleteSku	[DEPRECATED] Number of Agents connected to a Complete site	false	integer
agentsInControlSku	[DEPRECATED] Number of Agents connected to a Control site	false	integer
agentsInCoreSku	[DEPRECATED] Number of Agents connected to a Core site	false	integer
billingMode	Billing mode	false	enum
completeSites	[DEPRECATED] Number of Sites in suite Complete	false	integer
controlSites	[DEPRECATED] Number of Sites in suite Control	false	integer
coreSites	[DEPRECATED] Number of Sites in suite Core	false	integer
createdAt	Timestamp of Account creation	false	string
creator	The user that created the group	false	string
creatorId	The ID of the user that created the group	false	string
expiration	Expiration	false	string
externalId	ID of CRM external system	false	string
id	Account ID	false	string
irFields	Ir fields	false	see Get Account by ID - response - irFields table
isDefault	Is default	false	boolean
licenses	The account licenses.	false	see Get Account by ID - response - licenses table
makeSocDefaultUi	True if SOC is to be enabled by default	false	boolean
name	Name	false	string
numberOfSites	Total number of Sites in this Account	false	integer
promptFields	Prompt fields	false	see Get Account by ID - response - promptFields table

salesforceId		false	string
skus	[DEPRECATED] The list of SKUs for the Account.	false	see Get Account by ID - response - skus table
state	Account state	false	enum
totalComplete	[DEPRECATED] Total Number of Complete licenses	false	integer
totalControl	[DEPRECATED] Total Number of Control licenses	false	integer
totalCore	[DEPRECATED] Total Number of Core licenses	false	integer
totalLicenses	The total number of licenses on all Surfaces for all Bundles.	false	integer
unlimitedComplete	[DEPRECATED] True if Complete licenses count is unlimited	false	boolean
unlimitedControl	[DEPRECATED] True if Control licenses count is unlimited	false	boolean
unlimitedCore	[DEPRECATED] True if Core licenses count is unlimited	false	boolean
unlimitedExpiration	The Account does not expire	false	boolean
updatedAt	Timestamp of last update	false	string
usageType	Usage type	false	enum

Get Account by ID - response - irFields

Name	Description	Required	Value
companyName	The customer's company name	true	string
contactEmail	Business email of the customer contact. Must not match the IR partner domain, the submitter's own domain, or a free/personal email provider (e.g. Gmail, Yahoo, Hotmail)	true	string
contactFirstName	First name of the customer contact	true	string
contactLastName	Last name of the customer contact	true	string
country	Country of the customer	true	string
industry	Industry vertical of the customer	true	enum

numberOfEmployeesEndpoints	Estimated number of employees or endpoints at the customer	true	integer
city	City of the customer	false	string
postal	Postal / ZIP code of the customer	false	string
region	State or region within the country	false	string

Get Account by ID - response - licenses

Name	Description	Required	Value
bundles	The licenses Bundles	false	see Get Account by ID - response - bundles table
modules	The licenses Add-ons	false	see Get Account by ID - response - modules table
settings	The licenses Settings	false	see Get Account by ID - response - settings table

Get Account by ID - response - bundles

Name	Description	Required	Value
displayName	The Bundle display name	false	string
majorVersion	The Bundle major version	false	integer
minorVersion	The Bundle minor version	false	integer
name	The Bundle internal api name	false	string
surfaces	The Surfaces in the Bundle	false	see Get Account by ID - response - surfaces table
totalSurfaces	The total number of Surfaces in this Bundle. -1 indicates unlimited count.	false	integer

Get Account by ID - response - surfaces

Name	Description	Required	Value
count	The Surface count. -1 indicates unlimited count	false	integer
name	The Surface name.	false	string

Get Account by ID - response - modules

Name	Description	Required	Value
displayName	The Add-on display name	false	string
majorVersion	The Add-on major version	false	integer
name	The Add-on internal api name	false	string

Get Account by ID - response - settings

Name	Description	Required	Value
displayName	[DEPRECATED] The Setting display name	false	string
groupName	The Setting group name	false	
setting	The Setting display name	false	
settingGroup	[DEPRECATED] The Setting group name	false	string
settingGroupDisplayName	The Setting group display name	false	string

Get Account by ID - response - promptFields

Name	Description	Required	Value
promptRegion	Region associated with the prompt	false	enum
promptTenantName	Tenant name associated with the prompt	false	string
promptUserEmail	Email of the user associated with the prompt	false	string
promptUserName	Name of the user associated with the prompt	false	string

Get Account by ID - response - skus

Name	Description	Required	Value
------	-------------	----------	-------

agentsInSku	Total agents commissioned in this SKU.	false	integer
totalLicenses	Number of licenses for this specific SKU. Applicable only if unlimited is False	false	integer
type	The suite of product features active for this account	false	enum
unlimited	True if this is an unlimited SKU.	false	boolean

Update Account

PUT /web/api/v2.1/accounts/{account_id}

Change the data of an Account. This command requires a Global user or an Account user and Admin role. Use this command to change the name, ID, SKUs and how they are distributed among Sites and Agents, and more. (See the Body sample.) Best practice: Consult with your SentinelOne SE.

BEST PRACTICE

Consult with your SentinelOne SE.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Account not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Account - response - data table
errors	Errors	false	array

Update Account - response - data

Name	Description	Required	Value
accountType	Account type	false	string
activeAgents	Total Agents in the Account	false	integer
billingMode	Billing mode	false	enum
createdAt	Timestamp of Account creation	false	string
creator	The user that created the group	false	string
creatorId	The ID of the user that created the group	false	string
expiration	Expiration	false	string
externalId	ID of CRM external system	false	string
id	Account ID	false	string
irFields	Ir fields	false	see Update Account - response - irFields table
isDefault	Is default	false	boolean
licenses	The account licenses.	false	see Update Account - response - licenses table
makeSocDefaultUi	True if SOC is to be enabled by default	false	boolean
name	Name	false	string
promptFields	Prompt fields	false	see Update Account - response - promptFields table
salesforceId		false	string
skus	[DEPRECATED] The list of SKUs for the Account.	false	see Update Account - response - skus table
state	Account state	false	enum
totalLicenses	The total number of licenses on all Surfaces for all Bundles.	false	integer
unlimitedExpiration	The Account does not expire	false	
updatedAt	Timestamp of last update	false	string
usageType	Usage type	false	enum

Update Account - response - irFields

Name	Description	Required	Value
companyName	The customer's company name	true	string
contactEmail	Business email of the customer contact. Must not match the IR partner domain, the submitter's own domain, or a free/personal email provider (e.g. Gmail, Yahoo, Hotmail)	true	string
contactFirstName	First name of the customer contact	true	string
contactLastName	Last name of the customer contact	true	string
country	Country of the customer	true	string
industry	Industry vertical of the customer	true	enum
numberOfEmployeesEndpoints	Estimated number of employees or endpoints at the customer	true	integer
city	City of the customer	false	string
postal	Postal / ZIP code of the customer	false	string
region	State or region within the country	false	string

Update Account - response - licenses

Name	Description	Required	Value
bundles	The licenses Bundles	false	see Update Account - response - bundles table
modules	The licenses Add-ons	false	see Update Account - response - modules table
settings	The licenses Settings	false	see Update Account - response - settings table

Update Account - response - bundles

Name	Description	Required	Value
displayName	The Bundle display name	false	string
majorVersion	The Bundle major version	false	integer
minorVersion	The Bundle minor version	false	integer
name	The Bundle internal api name	false	string
surfaces	The Surfaces in the Bundle	false	see Update Account - response - surfaces table

totalSurfaces	The total number of Surfaces in this Bundle. -1 indicates unlimited count.	false	integer
---------------	--	-------	---------

Update Account - response - surfaces

Name	Description	Required	Value
count	The Surface count. -1 indicates unlimited count	false	integer
name	The Surface name.	false	string

Update Account - response - modules

Name	Description	Required	Value
displayName	The Add-on display name	false	string
majorVersion	The Add-on major version	false	integer
name	The Add-on internal api name	false	string

Update Account - response - settings

Name	Description	Required	Value
displayName	[DEPRECATED] The Setting display name	false	string
groupName	The Setting group name	false	
setting	The Setting display name	false	
settingGroup	[DEPRECATED] The Setting group name	false	string
settingGroupDisplayName	The Setting group display name	false	string

Update Account - response - promptFields

Name	Description	Required	Value
------	-------------	----------	-------

promptRegion	Region associated with the prompt	false	enum
promptTenantName	Tenant name associated with the prompt	false	string
promptUserEmail	Email of the user associated with the prompt	false	string
promptUserName	Name of the user associated with the prompt	false	string

Update Account - response - skus

Name	Description	Required	Value
agentsInSku	Total agents commissioned in this SKU.	false	integer
totalLicenses	Number of licenses for this specific SKU. Applicable only if unlimited is False	false	integer
type	The suite of product features active for this account	false	enum
unlimited	True if this is an unlimited SKU.	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Account - body - data table

Update Account - body - data

Name	Description	Required	Value
accountType	Account type	false	enum
billingMode	Billing mode	false	enum
expiration	Expiration	false	string
externalId	ID of CRM external system	false	string
inherits	True if the policy is inherited from Global, False if the Account has its own edited policy	false	boolean
irFields	IR related fields	false	see Update Account - body - irFields table
licenses	The license configuration for the Account	false	see Update Account - body - licenses table
makeSocDefaultUi	True if SOC is to be enabled by default	false	boolean
name	Name	false	string
policy	Policy	false	see Update Account - body - policy table
promptFields	Prompt related fields	false	see Update Account - body - promptFields table
salesforceId		false	string
skus	[DEPRECATED] Use licenses instead	false	see Update Account - body - skus table
unlimitedExpiration	If expiration is not limited, enter the expiration date and time yyyy-mm-ddThh:mm:ss	false	boolean
usageType	Usage type	false	enum

Update Account - body - irFields

Name	Description	Required	Value
companyName	The customer's company name	true	string
contactEmail	Business email of the customer contact. Must not match the IR partner domain, the submitter's own domain, or a free/personal email	true	string

	provider (e.g. Gmail, Yahoo, Hotmail)		
contactFirstName	First name of the customer contact	true	string
contactLastName	Last name of the customer contact	true	string
country	Country of the customer	true	string
industry	Industry vertical of the customer	true	enum
numberOfEmployeesEndpoints	Estimated number of employees or endpoints at the customer	true	integer
city	City of the customer	false	string
postal	Postal / ZIP code of the customer	false	string
region	State or region within the country	false	string

Update Account - body - licenses

Name	Description	Required	Value
bundles	The list of Bundles selected	false	see Update Account - body - bundles table
modules	The list of Add-ons selected	false	see Update Account - body - modules table
settings	The list of Settings selected for the Bundle and Add-ons. If a Bundle or Add-on requires a Setting that is not defined, the default Setting is used.	false	see Update Account - body - settings table

Update Account - body - bundles

Name	Description	Required	Value
name		true	string
majorVersion		false	integer
surfaces		false	see Update Account - body - surfaces table

Update Account - body - surfaces

Name	Description	Required	Value
------	-------------	----------	-------

name		true	string
count	The number of licenses per Surface. -1 indicates unlimited count.	false	integer

Update Account - body - modules

Name	Description	Required	Value
name		true	string

Update Account - body - settings

Name	Description	Required	Value
groupName		true	string
setting		true	string

Update Account - body - policy

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Update Account - body - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer

autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Update Account - body - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Update Account - body - dvAttributesPerEventType table
engines	The engines statuses	false	see Update Account - body - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Update Account - body - forensicsAutoTriggering table
identityConfigurationSettings	Identity configuration	false	see Update Account - body - identityConfigurationSettings table
identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Update Account - body - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean

mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Update Account - body - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Update Account - body - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean
researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first registration	false	boolean
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Update Account - body - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string

contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Update Account - body - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Update Account - body - dvAttributesPerEventType

Name	Description	Required	Value
------	-------------	----------	-------

autoInstallBrowserExtensions	Auto install browser extensions	false	see Update Account - body - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Update Account - body - behavioralIndicators table
commandScripts	Command scripts event	false	see Update Account - body - commandScripts table
crossProcess	Cross process event	false	see Update Account - body - crossProcess table
dataMasking	Data masking	false	see Update Account - body - dataMasking table
dllModuleLoad	DLL module load event	false	see Update Account - body - dllModuleLoad table
dns	Network event - DNS	false	see Update Account - body - dns table
driver	Driver	false	see Update Account - body - driver table
externalDeviceActivity	External Device Activity	false	see Update Account - body - externalDeviceActivity table
file	File event	false	see Update Account - body - file table
ip	Network event - IP	false	see Update Account - body - ip table
login	User login/logout event	false	see Update Account - body - login table
namedPipe	Named Pipe	false	see Update Account - body - namedPipe table
namedPipeExtended	Named Pipe Extended	false	see Update Account - body - namedPipeExtended table
openDirectoryActivity	Open Directory Activity	false	see Update Account - body - openDirectoryActivity table
process	Process event	false	see Update Account - body - process table
profileActivity	Profile Activity	false	see Update Account - body - profileActivity table
registry	Registry event	false	see Update Account - body - registry table
scheduledTask	Scheduled task event	false	see Update Account - body - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Update Account - body - smartFileMonitoring table
url	URL Actions event	false	see Update Account - body - url table
userSubstitution	User Substitution	false	see Update Account - body - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Update Account - body - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Update Account - body - windowsEventLogsExtended table

Update Account - body - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Update Account - body - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Update Account - body - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Update Account - body - crossProcess

Name	Description	Required	Value
dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Update Account - body - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Update Account - body - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Update Account - body - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Update Account - body - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Update Account - body - externalDeviceActivity

Name	Description	Required	Value
dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Update Account - body - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Update Account - body - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Update Account - body - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Update Account - body - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean
dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean

Update Account - body - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Update Account - body - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean

r			
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean
dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean

Update Account - body - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Update Account - body - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Update Account - body - registry

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Update Account - body - scheduledTask

Name	Description	Required	Value
dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Update Account - body - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Update Account - body - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Update Account - body - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Update Account - body - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Update Account - body - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Update Account - body - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum

preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Update Account - body - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean
macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Update Account - body - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer

identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean
-----------------------------	--	-------	---------

Update Account - body - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean
externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Update Account - body - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Update Account - body - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Update Account - body - promptFields

Name	Description	Required	Value
promptRegion	Region associated with the prompt	false	enum
promptTenantName	Tenant name associated with the prompt	false	string
promptUserEmail	Email of the user associated with the prompt	false	string
promptUserName	Name of the user associated with the prompt	false	string

Update Account - body - skus

Name	Description	Required	Value
totalLicenses	Number of licenses for this specific SKU. Applicable only if unlimited is False	false	integer
type	The suite of product features active for this Account	false	enum
unlimited	True if this is an unlimited SKU. Total licenses will be ignored if unlimited is True	false	boolean

Revert Policy

PUT /web/api/v2.1/accounts/{account_id}/revert-policy

The policy of the Account is based on the default Global policy and is enforced by all endpoints in the Sites and Groups of the Account (if you did not change the Site or Group policies). If you change the Account policy, you can use this command to revert it to the default Global policy.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Revert Policy - response - data table
errors	Errors	false	array

Revert Policy - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	false	see Revert Policy - body - data table

Revert Policy - body - data

Name	Description	Required	Value
id	Id	false	string

Reactivate Account

PUT /web/api/v2.1/accounts/{account_id}/reactivate

Reactivate an expired Account. This command requires a Global user or Support. Consult with your SentinelOne SE.

Response Messages

200 - Account reactivated

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Account not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Reactivate Account - response - data table
errors	Errors	false	array

Reactivate Account - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Reactivate Account - body - data table

Reactivate Account - body - data

Name	Description	Required	Value
expiration	New expiration date for the Account	false	string
unlimited	If false enter an expiration date and time (yyyy-mm-ddThh:mm:ss	false	boolean

Expire an Account

POST /web/api/v2.1/accounts/{account_id}/expire-now

Expire an Account immediately. The user must have Global access or Account access with permissions for the Account. Best practice: Consult with Support before you use this command.

BEST PRACTICE

Consult with Support before you use this command.

Response Messages

200 - Expire account now

401 - Unauthorized access - please sign in and retry.

404 - Account not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Expire an Account - response - data table
errors	Errors	false	array

Expire an Account - response - data

Name	Description	Required	Value
accountType	Account type	false	string
activeAgents	Total Agents in the Account	false	integer
billingMode	Billing mode	false	enum
createdAt	Timestamp of Account creation	false	string
creator	The user that created the group	false	string
creatorId	The ID of the user that created the group	false	string
expiration	Expiration	false	string
externalId	ID of CRM external system	false	string
id	Account ID	false	string
irFields	Ir fields	false	see Expire an Account - response - irFields table
isDefault	Is default	false	boolean
licenses	The account licenses.	false	see Expire an Account - response - licenses table
makeSocDefaultUi	True if SOC is to be enabled by default	false	boolean
name	Name	false	string
promptFields	Prompt fields	false	see Expire an Account - response - promptFields table
salesforceId		false	string
skus	[DEPRECATED] The list of SKUs for the Account.	false	see Expire an Account - response - skus table
state	Account state	false	enum
totalLicenses	The total number of licenses on all Surfaces for all Bundles.	false	integer
unlimitedExpiration	The Account does not expire	false	
updatedAt	Timestamp of last update	false	string
usageType	Usage type	false	enum

Expire an Account - response - irFields

Name	Description	Required	Value
companyName	The customer's company name	true	string
contactEmail	Business email of the customer contact. Must not match the IR partner domain, the submitter's own domain, or a free/personal email provider (e.g. Gmail, Yahoo, Hotmail)	true	string
contactFirstName	First name of the customer contact	true	string
contactLastName	Last name of the customer contact	true	string
country	Country of the customer	true	string
industry	Industry vertical of the customer	true	enum
numberOfEmployeesEndpoints	Estimated number of employees or endpoints at the customer	true	integer
city	City of the customer	false	string
postal	Postal / ZIP code of the customer	false	string
region	State or region within the country	false	string

Expire an Account - response - licenses

Name	Description	Required	Value
bundles	The licenses Bundles	false	see Expire an Account - response - bundles table
modules	The licenses Add-ons	false	see Expire an Account - response - modules table
settings	The licenses Settings	false	see Expire an Account - response - settings table

Expire an Account - response - bundles

Name	Description	Required	Value
displayName	The Bundle display name	false	string
majorVersion	The Bundle major version	false	integer
minorVersion	The Bundle minor version	false	integer
name	The Bundle internal api name	false	string
surfaces	The Surfaces in the Bundle	false	see Expire an Account - response - surfaces table

totalSurfaces	The total number of Surfaces in this Bundle. -1 indicates unlimited count.	false	integer
---------------	--	-------	---------

Expire an Account - response - surfaces

Name	Description	Required	Value
count	The Surface count. -1 indicates unlimited count	false	integer
name	The Surface name.	false	string

Expire an Account - response - modules

Name	Description	Required	Value
displayName	The Add-on display name	false	string
majorVersion	The Add-on major version	false	integer
name	The Add-on internal api name	false	string

Expire an Account - response - settings

Name	Description	Required	Value
displayName	[DEPRECATED] The Setting display name	false	string
groupName	The Setting group name	false	
setting	The Setting display name	false	
settingGroup	[DEPRECATED] The Setting group name	false	string
settingGroupDisplayName	The Setting group display name	false	string

Expire an Account - response - promptFields

Name	Description	Required	Value
------	-------------	----------	-------

promptRegion	Region associated with the prompt	false	enum
promptTenantName	Tenant name associated with the prompt	false	string
promptUserEmail	Email of the user associated with the prompt	false	string
promptUserName	Name of the user associated with the prompt	false	string

Expire an Account - response - skus

Name	Description	Required	Value
agentsInSku	Total agents commissioned in this SKU.	false	integer
totalLicenses	Number of licenses for this specific SKU. Applicable only if unlimited is False	false	integer
type	The suite of product features active for this account	false	enum
unlimited	True if this is an unlimited SKU.	false	boolean

Get Uninstall Password Metadata

GET /web/api/v2.1/accounts/{account_id}/uninstall-password/metadata

Get the uninstall password metadata, such as which user created and revoked it and when.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Get Uninstall Password Metadata - response - data table
errors	Errors	false	array

Get Uninstall Password Metadata - response - data

Name	Description	Required	Value
generatedByName	name of the user that generated the uninstall password	true	string
lastRevoked	uninstall password last revoked date	true	string
revokedByName	Revoked by name	true	string
version	Version	true	integer
createdAt	password creation date: yyyy-mm-dd	false	string
expiration	password expiration date format: yyyy-mm-dd	false	string
generatedById	The ID of the user that generated the uninstall password	false	integer
revokedById	The ID of the user that revoked the uninstall password	false	integer

Get Uninstall Password

GET /web/api/v2.1/accounts/{account_id}/uninstall-password/view

Get the uninstall password to uninstall several Agents of one Account with one command.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Uninstall Password - response - data table
errors	Errors	false	array

Get Uninstall Password - response - data

Name	Description	Required	Value
password	msg EC signed with private key: v1.base64(data).base64(ES384(data))	false	string

Generate/Regenerate Uninstall Password

POST /web/api/v2.1/accounts/{account_id}/uninstall-password/generate

You can uninstall all Agents of one Account with one command that requires a password. This command sets a new account-level uninstall password.

To enable this feature, submit a ticket with Support.

Best Practice: After you uninstall the Agents and install again, revoke the passphrase.

Applicable on Windows (versions 4.4+) and Linux (versions 21.7+) Agents.

BEST PRACTICE

After you uninstall the Agents and install again, revoke the passphrase.

Applicable on Windows (versions 4.4+) and Linux (versions 21.7+) Agents.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Generate/Regenerate Uninstall Password - response - data table
errors	Errors	false	array

Generate/Regenerate Uninstall Password - response - data

Name	Description	Required	Value
generatedByName	name of the user that generated the uninstall password	true	string
lastRevoked	uninstall password last revoked date	true	string
revokedByName	Revoked by name	true	string
version	Version	true	integer
createdAt	password creation date: yyyy-mm-dd	false	string
expiration	password expiration date format: yyyy-mm-dd	false	string
generatedById	The ID of the user that generated the uninstall password	false	integer
revokedById	The ID of the user that revoked the uninstall password	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Generate/Regenerate Uninstall Password - body - data table

Generate/Regenerate Uninstall Password - body - data

Name	Description	Required	Value
expiration	password expiration date format: yyyy-mm-dd	true	string

Revoke Uninstall Password

POST /web/api/v2.1/accounts/{account_id}/uninstall-password/revoke

Delete the account-level uninstall password. If you do not delete it, you or another Console user can mistakenly use the Account passphrase (and uninstall all Agents) when you mean to uninstall one Agent.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Revoke Uninstall Password - response - data table
errors	Errors	false	array

Revoke Uninstall Password - response - data

Name	Description	Required	Value
generatedByName	name of the user that generated the uninstall password	true	string
lastRevoked	uninstall password last revoked date	true	string
revokedByName	Revoked by name	true	string
version	Version	true	integer
createdAt	password creation date: yyyy-mm-dd	false	string
expiration	password expiration date format: yyyy-mm-dd	false	string
generatedByld	The ID of the user that generated the uninstall password	false	integer
revokedByld	The ID of the user that revoked the uninstall password	false	integer

Export Accounts

GET /web/api/v2.1/export/accounts

Export Accounts data to a CSV, for Accounts that match the filter.

Parameters

accountids	optional	List of Account IDs to search for. Example: "225494730938493804,225494730938493915".
accounttype	optional	Account type. Example: "Trial".
activelicense	optional	Active licenses
billingmode	optional	Billing mode. Example: "subscription".
createdat	optional	Timestamp of Account creation. Example: "2018-02-27T04:49:26.257525Z".
expiration	optional	Expiration. Example: "2018-02-27T04:49:26.257525Z".
features	optional	Filter the list of Accounts for those that support this feature. Example: "firewall-control".

ids	optional	A list of Account IDs. Example: "225494730938493804,225494730938493915".
isdefault	optional	Is default
module	optional	Module. Example: "star,rso".
name	optional	Name. Example: "My Account".
name__contains	optional	Free-text filter by account name (supports multiple values)
query	optional	Full text search for fields: name. (Note: on single-Account Consoles, the Account name will not be matched)
sku	optional	Sku. Example: "core".
state	optional	Account state. Example: "active".
states	optional	Filter by state, such as active or expired.
statesnin	optional	List of states to not filter
totallicenses	optional	Total licenses
updatedat	optional	Timestamp of last update. Example: "2018-02-27T04:49:26.257525Z".
usagetype	optional	Usage type. Example: "customer".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Activities

Get Activities

GET /web/api/v2.1/activities

Get the activities, and their data, that match the filters.

We recommend that you set some values for the filters. The full list will be too large to be useful.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
activitytypes	optional	Return only these activity codes (comma-separated list). Select a code from the drop-down, or see the id field from the Get activity types command. . Example: "52,53,71,72".
activityuuids	optional	Return activities by specific activity UUIDs. Example: "a2c8037c-e6df-436d-b92b-bc09a418717e,f15b308b-fab9-4c0b-b6f5-17d236a7bf55".
agentids	optional	Return activities related to specified agents. Example: "225494730938493804,225494730938493915".
alertids	optional	Return activities related to specified alerts. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__between	optional	Get activities created in this range (inclusive) of a start timestamp and an end timestamp. Example: "1514978764288-1514978999999".
createdat__gt	optional	Get activities created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Get activities created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Get activities created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Get activities created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	Filter activities by specific activity IDs. Example: "225494730938493804,225494730938493915".
includehidden	optional	Include internal activities hidden from display. Example: "False".
limit	optional	Limit number of returned items (1-1000). Example: "10".

relatedids	optional	Return activities related to specified entities. Example: "56ee72a79c7e5c62dd36e6b1".
ruleids	optional	Return activities related to specified rules. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
threatids	optional	Return activities related to specified threats. Example: "225494730938493804,225494730938493915".
useremails	optional	Email of the user who invoked the activity (If applicable)
userids	optional	The user who invoked the activity (If applicable). Example: "225494730938493804,225494730938493915".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Activities - response - pagination table
data	Response data	false	see Get Activities - response - data table
errors	Errors	false	array

Get Activities - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Activities - response - data

Name	Description	Required	Value
accountId	Related account id (If applicable)	false	string
accountName	Related account name (If applicable)	false	string
activityType	Activity type	false	integer
activityUuid	Activity UUID	false	string
agentId	Related agent (If applicable)	false	string
agentUpdatedVersion	Agent's new version (If applicable)	false	string
comments	Comments	false	string
createdAt	Activity creation time (UTC)	false	string
data	Extra activity specific data	false	object
description	Extra activity information	false	string
groupId	Related group id (If applicable)	false	string
groupName	Related group name (If applicable)	false	string
hash	Threat file hash (If applicable)	false	string
id	Activity ID	false	string
osFamily	Agent's OS type (if applicable)	false	enum
primaryDescription	Primary description	false	string
secondaryDescription	Secondary description	false	string
siteId	Related site id (If applicable)	false	string

siteName	Related site name (If applicable)	false	string
threatId	Related threat (If applicable)	false	string
updatedAt	Activity last updated time (UTC)	false	string
userId	The user who invoked the activity (If applicable)	false	string

Get Activity Types

GET /web/api/v2.1/activities/types

Get a list of activity types. This is useful to see valid values to filter activities in other commands.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Activity Types - response - data table
errors	Errors	false	array

Get Activity Types - response - data

Name	Description	Required	Value
action	Action described in the activity	false	string
descriptionTemplate	Activity description template as seen in activity page	false	string
id	Activity type ID	false	integer

Last activity as Syslog message

GET /web/api/v2.1/last-activity-as-syslog

To see examples of Syslog messages, you can get the Syslog message that corresponds to the last activity that matches the filter. This is not intended for production purposes.

If Syslog messages that you expected to see are not in the response, make sure you selected "Syslog" for the activity type in Console > Settings > Notifications.

To see your Syslog settings, run: "settings/notifications".

To change the settings, run: "settings/notifications" with the changes in the body of the request.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
activitytypes	optional	Return only these activity codes (comma-separated list). Select a code from the drop-down, or see the id field from the Get activity types command. . Example: "52,53,71,72".
activityuuids	optional	Return activities by specific activity UUIDs. Example: "a2c8037c-e6df-436d-b92b-bc09a418717e,f15b308b-fab9-4c0b-b6f5-17d236a7bf55".
agentids	optional	Return activities related to specified agents. Example: "225494730938493804,225494730938493915".
alertids	optional	Return activities related to specified alerts. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__between	optional	Get activities created in this range (inclusive) of a start timestamp and an end timestamp. Example:

		"1514978764288-15149789999999".
createdat__gt	optional	Get activities created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Get activities created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Get activities created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Get activities created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	Filter activities by specific activity IDs. Example: "225494730938493804,225494730938493915".
includehidden	optional	Include internal activities hidden from display. Example: "False".
limit	optional	Limit number of returned items (1-1000). Example: "10".
relatedids	optional	Return activities related to specified entities. Example: "56ee72a79c7e5c62dd36e6b1".
ruleids	optional	Return activities related to specified rules. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
threatids	optional	Return activities related to specified threats. Example: "225494730938493804,225494730938493915".
useremails	optional	Email of the user who invoked the activity (If applicable)
userids	optional	The user who invoked the activity (If applicable). Example:

		"225494730938493804,225494730938493915".
--	--	--

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Last activity as Syslog message - response - pagination table
data	Response data	false	see Last activity as Syslog message - response - data table
errors	Errors	false	array

Last activity as Syslog message - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Last activity as Syslog message - response - data

Name	Description	Required	Value
activityId	ID of the activity	false	string
syslogMessage	Syslog message corresponding to the activity	false	string

Export Activities

GET /web/api/v2.1/export/activities

Export the list of activities.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
activitytypes	optional	Return only these activity codes (comma-separated list). Select a code from the drop-down, or see the id field from the Get activity types command. . Example: "52,53,71,72".
activityuuids	optional	Return activities by specific activity UUIDs. Example: "a2c8037c-e6df-436d-b92b-bc09a418717e,f15b308b-fab9-4c0b-b6f5-17d236a7bf55".
agentids	optional	Return activities related to specified agents. Example: "225494730938493804,225494730938493915".

alertids	optional	Return activities related to specified alerts. Example: "225494730938493804,225494730938493915".
createdat__between	optional	Get activities created in this range (inclusive) of a start timestamp and an end timestamp. Example: "1514978764288-1514978999999".
createdat__gt	optional	Get activities created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Get activities created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Get activities created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Get activities created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	Filter activities by specific activity IDs. Example: "225494730938493804,225494730938493915".
includehidden	optional	Include internal activities hidden from display. Example: "False".
relatedids	optional	Return activities related to specified entities. Example: "56ee72a79c7e5c62dd36e6b1".
rowslimit	optional	Limit number of returned items (1-10000). Example: "100".
ruleids	optional	Return activities related to specified rules. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
threatids	optional	Return activities related to specified threats. Example: "225494730938493804,225494730938493915".
useremails	optional	Email of the user who invoked the activity (If applicable)
userids	optional	The user who invoked the activity (If applicable). Example: "225494730938493804,225494730938493915".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Agent Actions

Broadcast Message

POST /web/api/v2.1/agents/actions/broadcast

You can send a message through the Agents that users can see.

This is useful for endpoints that have human users. This command is supported on Windows and macOS endpoints (not supported on Linux). The message is sent to all endpoints that match the filter.

Put the message in the data parameter: "data":{"message":"<your message>"}

The message must be 140 characters or less.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Broadcast Message - response - data table
errors	Errors	false	array

Broadcast Message - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Broadcast Message - body - data table
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Broadcast Message - body - filter table

Broadcast Message - body - data

Name	Description	Required	Value
message	Message to broadcast to agents.	true	string

Broadcast Message - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []

agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance	false	string []

	id(supports multiple values)		
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Broadcast Message - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer

cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string
createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []

ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraild__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []

isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string

lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []

operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string

remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []
scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean

threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer
totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Broadcast Message - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Connect to Network

POST /web/api/v2.1/agents/actions/connect

After you run "disconnect from network" on endpoints, analyze the issue, and mitigate threats. Use this command to reconnect to the network all endpoints that match the filter. To learn more, see "Disconnect from Network".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Connect to Network - response - data table
errors	Errors	false	array

Connect to Network - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Connect to Network - body - filter table
data	Data	false	see Connect to Network - body - data table

Connect to Network - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Connect to Network - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Connect to Network - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Connect to Network - body - data

Fetch Logs

POST /web/api/v2.1/agents/actions/fetch-logs

Get the Agent and Endpoint logs from Agents that match the filter.

The Agent logs are encrypted and only Support can read them.

The Endpoint logs, for operations on the computers, laptops, or servers that have the Agent installed, are readable. The Endpoint logs are available for Windows endpoints only and require Agent version 3.6 or later. After you run this command, download the fetched logs. You can download the logs from the Console GUI or collect them.

On Windows: C:\ProgramData\Sentinel\logs.

On macOS: Run `sudo sentinelctl logreport` and get the log files on the desktop.

On Linux: Run `sudo /opt/sentinelone/bin/sentinelctl log generate`.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Fetch Logs - response - data table
errors	Errors	false	array

Fetch Logs - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Fetch Logs - body - filter table
data	Data	false	see Fetch Logs - body - data table

Fetch Logs - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Fetch Logs - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Fetch Logs - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Fetch Logs - body - data

Name	Description	Required	Value
agentLogs	Fetch Agent logs	false	boolean
customerFacingLogs	Fetch customer-facing logs	false	boolean
platformLogs	Actively fetch logs from the relevant platform: windows/mac/linux	false	boolean

Initiate Scan

POST /web/api/v2.1/agents/actions/initiate-scan

Use this command to run a Full Disk Scan on Agents that match the filter.

Full Disk Scan finds dormant suspicious activity, threats, and compliance violations, that are then mitigated according to the policy. It scans the local file system.

Full Disk Scan does not inspect drives that require user credentials (such as network drives) or external drives.

Full Disk Scan does not work on hashes. It does not check each file against the blocklist.

If the Static AI determines a file is suspicious, the Agent calculates its hash and sees if the hash is in the blocklist. If a file is executed, all aspects of the process are inspected, including hash-based analysis and blocklist checks. Full Disk Scan can run when the endpoint is offline, but when it is connected to the Management, it can use the most updated Cloud data to improve detection.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Initiate Scan - response - data table
errors	Errors	false	array

Initiate Scan - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Initiate Scan - body - filter table
data	Data	false	see Initiate Scan - body - data table

Initiate Scan - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Initiate Scan - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Initiate Scan - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Initiate Scan - body - data

Abort Scan

POST /web/api/v2.1/agents/actions/abort-scan

Immediately stop a Full Disk Scan on all Agents that match the filter. See "Initiate scan" to learn more about Full Disk Scan.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Abort Scan - response - data table
errors	Errors	false	array

Abort Scan - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Abort Scan - body - filter table
data	Data	false	see Abort Scan - body - data table

Abort Scan - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Abort Scan - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Abort Scan - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Abort Scan - body - data

Disconnect from Network

POST /web/api/v2.1/agents/actions/disconnect

Use this command to isolate (quarantine) endpoints from the network, if the endpoints match the filter.

The Agent can communicate with the Management, which lets you analyze and mitigate threats. Best practice: For Active threats that spread, apply "Disconnect from network" immediately. In the policy, you can set this is to be automatic. When the Agent detects a high-confidence malicious threat, it will mitigate the threat (on Protect) with the action set by the policy. Then the Agent will immediately quarantine the endpoint. To make Disconnect from network automatic in an Account policy, run the "accounts/{id} command (see "Update Account") with: "networkQuarantine":true.

BEST PRACTICE

For Active threats that spread, apply "Disconnect from network" immediately. In the policy, you can set this is to be automatic. When the Agent detects a high-confidence malicious threat, it will mitigate the threat (on Protect) with the action set by the policy. Then the Agent will immediately quarantine the endpoint. To make Disconnect from network automatic in an Account policy, run the "accounts/{id} command (see "Update Account") with: "networkQuarantine":true.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Disconnect from Network - response - data table
errors	Errors	false	array

Disconnect from Network - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Note: One of these filter arguments must be supplied: ids, groupIds, filterId.	true	see Disconnect from Network - body - filter table
data	Data	false	see Disconnect from Network - body - data table

Disconnect from Network - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Disconnect from Network - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of network groups	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Disconnect from Network - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
podsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Disconnect from Network - body - data

Decommission

POST /web/api/v2.1/agents/actions/decommission

If a user is scheduled for time off, or a device is scheduled for maintenance, you can decommission the Agent. This removes the Agent from the Management Console. When the Agent communicates with the Management again, the Management recommissions it and returns it to the Console. Use this command to decommission the Agents that match the filter.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Decommission - response - data table
errors	Errors	false	array

Decommission - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Note: One of these filter arguments must be supplied: ids, groupIds, filterId.	true	see Decommission - body - filter table
data	Data	false	see Decommission - body - data table

Decommission - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Decommission - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of network groups	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Decommission - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Decommission - body - data

Uninstall

POST /web/api/v2.1/agents/actions/uninstall

Use this command to uninstall Agents that match the filter. For Windows and macOS, make sure that all remnants of the Agent are removed: reboot the endpoints after uninstall. Use the "restart" command.

Response Messages

- 200 - Success
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.
- 403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Uninstall - response - data table
errors	Errors	false	array

Uninstall - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Note: One of these filter arguments must be supplied: ids, groupIds, filterId.	true	see Uninstall - body - filter table
data	Data	false	see Uninstall - body - data table

Uninstall - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Uninstall - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of network groups	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Uninstall - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
podsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Uninstall - body - data

Restart

POST /web/api/v2.1/agents/actions/restart-machine

Use this command to restart endpoints that have an Agent installed and that fit the filter. We recommend that you use the "broadcast" command to send a message to users of endpoints before you restart their computers.

Response Messages

- 200 - Success
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.
- 403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Restart - response - data table
errors	Errors	false	array

Restart - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Note: One of these filter arguments must be supplied: ids, groupIds, filterId.	true	see Restart - body - filter table
data	Data	false	see Restart - body - data table

Restart - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Restart - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of network groups	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Restart - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Restart - body - data

Shutdown

POST /web/api/v2.1/agents/actions/shutdown

You can shut down endpoints remotely for performance, maintenance, or security. This command shuts down all endpoints that match the filter. Best Practice: If an endpoint is infected, we recommend the "disconnect" command and not the "shutdown" command. The disconnect command secures the environment from infection while you analyze the cause and best response. If the endpoint is offline, the shutdown command is not available.

BEST PRACTICE

If an endpoint is infected, we recommend the "disconnect" command and not the "shutdown" command. The disconnect command secures the environment from infection while you analyze the cause and best response.

If the endpoint is offline, the shutdown command is not available.

Response Messages

- 200 - Success
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.
- 403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Shutdown - response - data table
errors	Errors	false	array

Shutdown - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Note: One of these filter arguments must be supplied: ids, groupIds, filterId.	true	see Shutdown - body - filter table
data	Data	false	see Shutdown - body - data table

Shutdown - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Shutdown - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of network groups	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Shutdown - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
podsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Shutdown - body - data

Approve Uninstall

POST /web/api/v2.1/agents/actions/approve-uninstall

If a user tries to uninstall the SentinelOne Agent from an endpoint, an uninstall request is sent to the Management. You must approve the request.

After you approve a request, users see a message that the request was approved. They can restart to complete the Agent uninstall.

We recommend that you do not approve these requests until you understand the reason for the request, you agree with the request, and you have alternative security for the endpoint until you install the Agent again.

This command will approve pending uninstall requests for all Agents that match the filter.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Approve Uninstall - response - data table
errors	Errors	false	array

Approve Uninstall - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Approve Uninstall - body - filter table
data	Data	false	see Approve Uninstall - body - data table

Approve Uninstall - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Approve Uninstall - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>--<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Approve Uninstall - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
podsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Approve Uninstall - body - data

Reject uninstall

POST /web/api/v2.1/agents/actions/reject-uninstall

Reject uninstall requests for all Agents that match the filter. To learn more about Uninstall Requests, see "Approve Uninstall".

Response Messages

- 200 - Success
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.
- 403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Reject uninstall - response - data table
errors	Errors	false	array

Reject uninstall - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Reject uninstall - body - filter table
data	Data	false	see Reject uninstall - body - data table

Reject uninstall - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Reject uninstall - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Reject uninstall - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
podsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Reject uninstall - body - data

Update Software

POST /web/api/v2.1/agents/actions/update-software

Use this command to update the Agent version on endpoints that have the Agent installed and that match the filter. For a cloud-based Management, SentinelOne updates your Management Console with the latest Agent versions. For On-Prem environments, or if you need a package that is not in your Management Console, request files from SentinelOne Support.

IMPORTANT: These parameters are required:

packageType - example: "packageType": "AgentAndRanger", osType - example: "osType": "windows", fileName - example: "fileName": "SentinelInstaller-x86_windows_32bit_v4_6_12_241.exe"

Best Practice: Upgrade your SentinelOne Agents by group or OS. Note about macOS endpoints: It is important that you upgrade the Agent before the endpoint operating system is upgraded to a version that the Agent does not support. More best practices: read the Release Notes, review the system requirements, and if you decide to not upgrade Agents yet, review the Agent Lifecycle. Make sure your deployment is in the supportable bounds.

BEST PRACTICE

Upgrade your SentinelOne Agents by group or OS. Note about macOS endpoints: It is important that you upgrade the Agent before the endpoint operating system is upgraded to a version that the Agent does not support. More best practices: read the Release Notes, review the system requirements, and if you decide to not upgrade Agents yet, review the Agent Lifecycle. Make sure your deployment is in the supportable bounds.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permissions to perform the requested action

409 - The Agent is automatically upgraded according to its Upgrade Policy. Manually upgrading the Agent may cause conflicts

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Software - response - data table

errors	Errors	false	array
--------	--------	-------	-------

Update Software - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Software - body - data table
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Update Software - body - filter table

Update Software - body - data

Name	Description	Required	Value
allowDowngrade	Allows or disallows downgrading the Agent version	false	boolean
fileName	Upgrade with a given uploaded package, locate package by its filename	false	string
ignoreConflicts	Ignore conflicts that may arise when you upgrade an Agent that has an active Upgrade Policy	false	boolean
isScheduled	Upgrade according to the defined scheduled in agent upgrade configuration	false	boolean
osType	Filter by specific OS type, can be used in conjunction with "fileName" or "path"	false	enum
packageId	Upgrade with a given uploaded package, located package by its ID	false	string
packageType	Package type	false	enum
path	Upgrade from local path at the endpoint	false	string

Update Software - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []

adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []

agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or	false	string []

	uuid (supports multiple values)		
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Update Software - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string
createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string

decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []

groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []

k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum

missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceLocalnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Excluded network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they	false	string

	start with the search term only (no match if they contain the term).		
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []
scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each	false	string

	value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.		
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer
totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this	false	string

	timestamp		
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Update Software - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
podsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Reset Local Config

POST /web/api/v2.1/agents/actions/reset-local-config

SentinelCtl is the CLI for Agents. It runs commands directly on one Agent at a time. You can use this command to clear the SentinelCtl changes from all Agents that match the filter. Specific SentinelCtl settings are not cleared:

On Windows: proxy address and Management token.

On macOS: Management server address and server site key.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Reset Local Config - response - data table
errors	Errors	false	array

Reset Local Config - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Reset Local Config - body - filter table
data	Data	false	see Reset Local Config - body - data table

Reset Local Config - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Reset Local Config - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Reset Local Config - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Reset Local Config - body - data

Set Persistent Configuration Overrides

POST /web/api/v2.1/agents/actions/set-config

This command requires Global permissions or Support.

The configuration of an Agent can be changed in different ways, such as through Policy settings, Policy Override, SentinelCtl, and changes to the LocalConfig.json file. For Windows, Policy Override overwrites policy settings, and local changes (to the file and from this command) overwrite Policy Override from the Console or with policy updates from the API.

For macOS, the Policy Override has the highest priority. If you run this command and then update a Group policy that affects both Windows and macOS endpoints, the settings of this command are applied to the Windows endpoints. But the macOS endpoints will apply the settings of the policy, for settings that are duplicated in both the policy and this command.

When you use this command, enter the filter values to set which Agents get the change. Then use the data parameter to set the actual changes. Get the JSON settings for data from the Agent Configuration or see the Knowledge Base: <https://support.sentinelone.com/hc/en-us/articles/360022158673-sentinelctl>

Response Messages

- 200 - Success
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.
- 403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set Persistent Configuration Overrides - response - data table
errors	Errors	false	array

Set Persistent Configuration Overrides - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Set Persistent Configuration Overrides - body - data table
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Set Persistent Configuration Overrides - body - filter table

Set Persistent Configuration Overrides - body - data

Name	Description	Required	Value
config	Config	false	object

Set Persistent Configuration Overrides - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []

agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance	false	string []

	id(supports multiple values)		
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Set Persistent Configuration Overrides - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer

cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string
createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []

ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []

isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string

lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []

operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string

remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []
scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean

threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer
totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Set Persistent Configuration Overrides - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Set External ID

POST /web/api/v2.1/agents/actions/set-external-id

You can add a Customer Identifier (a string) to identify each endpoint or to tag sets of endpoints. The string shows in the Endpoint Details of the Management Console. For example, you can tag endpoints based on their state, installed applications, or endpoint status. The identifier is set on all Agents that match the filter.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set External ID - response - data table
errors	Errors	false	array

Set External ID - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Set External ID - body - data table
filter	Applied filter - only matched Agents will be affected by the requested action.	true	see Set External ID - body - filter table

Set External ID - body - data

Name	Description	Required	Value
externalId	New external id for the agent	true	string

Set External ID - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []

agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance	false	string []

	id(supports multiple values)		
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Set External ID - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer

cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string
createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []

ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []

isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string

lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []

operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string

remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []
scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean

threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer
totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Set External ID - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Fetch Files

POST /web/api/v2.1/agents/{agent_id}/actions/fetch-files

Fetch files from endpoints (up to 10 MB for each command) to analyze the root of threats (that come from files - of course, this does not help for fileless threats). Set the pathnames in the body of the request.

Regular expressions and metacharacters are not allowed. Spaces are allowed.

You must enter a new password, which you will use to open the archive of downloaded files. The password must be 10 or more characters with a mix of upper and lower case letters, numbers, and symbols.

This command collects the file and uploads them to the Management. To get the files, download them from the Management.

FedRAMP-compliant and other Managements in GovCloud require a Support ticket to enable this feature.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permissions to perform the requested action

404 - Agent not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Fetch Files - response - data table
errors	Errors	false	array

Fetch Files - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Fetch Files - body - data table

Fetch Files - body - data

Name	Description	Required	Value
password	File encryption password	true	string
files	List of files to fetch (absolute paths, up to 10 files)	false	string []

Move between Sites

POST /web/api/v2.1/agents/actions/move-to-site

This command requires Account or Global level access.

Agents are assigned to a Site when they are first installed with a Site Token. If you have the required access level, a role with permissions (the SOC role does not allow this action), and permission for both Sites, you can move Agents from one Site to a different Site. Agents will be moved to the best matching dynamic group, or to the Default group if no dynamic group matches.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Move between Sites - response - data table
errors	Errors	false	array

Move between Sites - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Move between Sites - body - data table
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Move between Sites - body - filter table

Move between Sites - body - data

Name	Description	Required	Value
targetSiteId	Target site id	true	string

Move between Sites - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []

agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance	false	string []

	id(supports multiple values)		
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Move between Sites - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer

cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string
createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []

ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []

isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string

lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []

operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string

remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []
scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean

threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer
totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Move between Sites - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Fetch Firewall Rules

POST /web/api/v2.1/agents/actions/fetch-firewall-rules

Firewall Control is disabled at the Global level. When it is first enabled, all Sites and Groups inherit the Firewall Control policy from the Global policy. Agents have Firewall Control disabled, until they connect to a Site or Group with an enabled Firewall Control policy.

After Agents get Firewall Control, if you add or change a Firewall rule, you can use this command to make sure all Agents fetch the rules, (though Agents usually update their policies every few seconds). Use the filter parameter to set which Agents will fetch the rules, if you do not want all of them to attempt it.

Firewall Control requires a Control SKU.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Fetch Firewall Rules - response - data table
errors	Errors	false	array

Fetch Firewall Rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Fetch Firewall Rules - body - data table
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Fetch Firewall Rules - body - filter table

Fetch Firewall Rules - body - data

Name	Description	Required	Value
format	Desired firewall configuration format. Use "native" to get configuration file in native format.	false	enum
state	Desired firewall configuration state. Use "initial" to get the firewall configuration that existed before Agent installation. (Note: "initial" requires native format).	false	enum

Fetch Firewall Rules - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []

	values)		
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []

azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Fetch Firewall Rules - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer

coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string
createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []

ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one	false	boolean

	active threat		
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string

lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpNet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address	false	string []

	(supports multiple values)		
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time	false	string

	(format: <from_timestamp>-<to_timestamp>, inclusive)		
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []
scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or	false	string

	at this time		
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer
totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []

windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Fetch Firewall Rules - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
podsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Move to Console

POST /web/api/v2.1/agents/actions/move-to-console

You can move Agents between Management Consoles. This command moves Agents to a target Console, Account, and Site, given the Console URL and Site token.

You must have Global permissions for the source Console and access to the Site token of the target Site.

Resolve all threats on the Agents to move before you run this command.

If the Agents have local configurations, the configurations are maintained.

If the new Management has different blocklists, exclusions, and other assets, these are applied the next time the Agent communicates with the Management.

This command works on these Agent versions: Windows 3.0 and later, macOS 3.0 and later, Linux 3.4 and later.

An Agent tries to connect to the new Management Console for 3 minutes. If the Agent cannot connect (has unresolved threats or other requirements are not met), it stays in the original Management Console.

To get the Site token, run the "sites" command (see Sites list) and take the "registrationToken" value.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Move to Console - response - data table
errors	Errors	false	array

Move to Console - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Move to Console - body - data table
filter	Applied filter - only matched Agents will be affected by the requested action. Note: One of these filter arguments must be supplied: ids, groupIds, filterId.	true	see Move to Console - body - filter table

Move to Console - body - data

Name	Description	Required	Value
token	Site token of the site to which the Agent is to be moved. This is a base-64 string that can be copied from the GUI.	true	string

Move to Console - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []

adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []

cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Move to Console - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer

cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string
createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []

ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of network groups	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these	false	string []

	package types		
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []

lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []

networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string

registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []
scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before	false	string

	or at this time		
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer
totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Move to Console - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Get Applications

POST /web/api/v2.1/agents/actions/fetch-installed-apps

Application Risk Management is an EA feature. Contact your partner or SentinelOne SE to learn how to join the EA program.

If you have this feature, you can use this command to have all Agents update the data of the applications that are installed on the endpoint. Change the filter parameter values to send this command to matching Agents only. The updated data of installed applications shows on the Console.

Some filter fields are required.

Best practice: Enter all fields in the body. Click in the Body sample to get a copy of the fields in the body form.

BEST PRACTICE

Enter all fields in the body. Click in the Body sample to get a copy of the fields in the body form.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Applications - response - data table

errors	Errors	false	array
--------	--------	-------	-------

Get Applications - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Note: One of these filter arguments must be supplied: ids, groupIds, filterId.	true	see Get Applications - body - filter table
data	Data	false	see Get Applications - body - data table

Get Applications - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Get Applications - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of network groups	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Get Applications - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
podsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Get Applications - body - data

Start Remote Shell

POST /web/api/v2.1/agents/actions/start-remote-shell

Remote shell is an opened websocket between the browser and the Agent, with a proprietary communication protocol that requires an unreasonable effort to run from the API. We recommend that you not use this call.

If you do want to use this API, you must have permission through your user role (not IT or Viewer), specific Remote Shell permissions, 2FA enabled on the username with a valid code in the twoFaCode parameter, valid code in the twoFaCode parameter, and permissions for the Account, Site, or Group on whose policy Remote Shell is enabled. To make sure you have permission to start Remote Shell, use the "can-start-remote-shell" command. Best practice: Use the UUID filter to run Remote Shell on a specific endpoint. To get the UUID, run the "agents" command.

In the body of this command, the data parameter set is mandatory.

Remote Shell requires a Control SKU.

BEST PRACTICE

Use the UUID filter to run Remote Shell on a specific endpoint. To get the UUID, run the "agents" command.

In the body of this command, the data parameter set is mandatory.

Remote Shell requires a Control SKU.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Start Remote Shell - response - data table
errors	Errors	false	array

Start Remote Shell - response - data

Name	Description	Required	Value
agentId	Agent that matched the filter	false	string
channelId	Name of the channel that will be used to communicate with the Agent	false	string
supportsResize	Whether the agent supports terminal resize capability	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Start Remote Shell - body - data table
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Start Remote Shell - body - filter table

Start Remote Shell - body - data

Name	Description	Required	Value
columns	Number of columns of the console shell	true	integer
rows	Number of rows of the console shell	true	integer
historyPassword	Password to zip the shell history file at end of session	false	string
passwordFromScope	Used to specify execution where a generic password is used	false	see Start Remote Shell - body - passwordFromScope table
twoFaCode	[DEPRECATED] The 2FA code to authenticate the user. Use only if remote_shell_risky_actions GS is disabled.	false	string

Start Remote Shell - body - passwordFromScope

Name	Description	Required	Value
scopeLevel	User scope	true	enum
scopeId	string repr. of scope id	false	string

Start Remote Shell - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []

adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []

agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or	false	string []

	uuid (supports multiple values)		
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Start Remote Shell - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string
createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string

decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []

groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []

k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum

missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceLocalnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Excluded network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they	false	string

	start with the search term only (no match if they contain the term).		
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []
scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each	false	string

	value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.		
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer
totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this	false	string

	timestamp		
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Start Remote Shell - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
podsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Can run Remote Shell

POST /web/api/v2.1/agents/actions/can-start-remote-shell

Who can run Remote Shell? Remote Shell is a powerful way to respond remotely to events on endpoints. It lets you open full shell capabilities - PowerShell on Windows and Bash on macOS and Linux. To be able to run a Remote Shell session, SentinelOne users require permissions, which are set on different levels. It can be confusing to know who has permission. Use this command to see if a username you created for someone else or the API, or your own name, has permission.

If a user does not have Remote Shell permission, how can you grant it? First, you need the Control SKU. Then, the user must have a role with permission to use Remote Shell: Admin, SOC, IR Team. The IT role does not have Remote Shell permission, and the user must be responsible for the Account, Site, or Group on whose policy Remote Shell is enabled.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Can run Remote Shell - response - data table
errors	Errors	false	array

Can run Remote Shell - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Can run Remote Shell - body - filter table
data	Data	false	see Can run Remote Shell - body - data table

Can run Remote Shell - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Can run Remote Shell - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Can run Remote Shell - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
podsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Can run Remote Shell - body - data

Terminate Remote Shell

POST /web/api/v2.1/agents/actions/terminate-remote-shell

Remote Shell is a powerful, full shell for Windows, macOS, and Linux. It is best practice to terminate Remote Shell sessions when they are not in use. A Remote Shell session terminates when the user closes the session, the session times out, or the session is idle longer than the idle-timeout. Use this command terminate a session immediately.

Response Messages

- 200 - Success
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.
- 403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Terminate Remote Shell - response - data table
errors	Errors	false	array

Terminate Remote Shell - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Terminate Remote Shell - body - data table
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Terminate Remote Shell - body - filter table

Terminate Remote Shell - body - data

Name	Description	Required	Value
channelId	The channel the user is closing	true	string

Terminate Remote Shell - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []

agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance	false	string []

	id(supports multiple values)		
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Terminate Remote Shell - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer

cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string
createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []

ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraild__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []

isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string

lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []

operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string

remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensics feature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []
scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean

threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer
totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Terminate Remote Shell - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Fetch Firewall Logs

POST /web/api/v2.1/agents/actions/firewall-logging

Get Firewall Control events in the local log file, written in clear text, for Firewall Control events of an endpoint with Firewall Control enabled. Enable the logs for Agents that match the filter.

When Firewall Logging is enabled, you can choose if blocked traffic events go only to a local log on the endpoint (reportMgmt: false, reportLog: true), or also to Console > Activity (reportMgmt: true).

Allowed traffic is not logged.

Each Agent with Firewall Control Event Logging enabled keeps five log files, for a total of 100 MB maximum. The logs cycle older lines to maintain the size threshold.

On Windows endpoints, the Firewall Control logs are in C:\ProgramData\Sentinel\logs\. Search for log files with "visible" in the filename.

On macOS, run: sudo sentinelctl log.

On Linux, run: sudo /opt/sentinelone/bin/sentinelctl log generate /output_path.

Make sure the Group and Site of the Agent has Firewall Control enabled. Firewall Control requires a Control SKU.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Fetch Firewall Logs - response - data table
errors	Errors	false	array

Fetch Firewall Logs - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Fetch Firewall Logs - body - data table
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Fetch Firewall Logs - body - filter table

Fetch Firewall Logs - body - data

Name	Description	Required	Value
reportLog	Report blocking activity to log	true	boolean
reportMgmt	Report blocking activity to management	true	boolean

Fetch Firewall Logs - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []

adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []

cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Fetch Firewall Logs - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer

cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string
createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []

ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these	false	string []

	package types		
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []

lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []

networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string

registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []
scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before	false	string

	or at this time		
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer
totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Fetch Firewall Logs - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Randomize UUID

POST /web/api/v2.1/agents/actions/randomize-uuid

IMPORTANT: This action will assign a new UUID to Agents that match the filter.

Run it only when instructed to do so by SentinelOne Support.

If you clone the Agent on a VM or VDI without the /VDI switch, you might need to run this command. It is best to ask for Support assistance. Historical threat and Deep Visibility data will be kept in the Management, but that data will be disassociated from the Agent.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Randomize UUID - response - data table
errors	Errors	false	array

Randomize UUID - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Note: One of these filter arguments must be supplied: ids, groupIds, filterId.	true	see Randomize UUID - body - filter table
data	Data	false	see Randomize UUID - body - data table

Randomize UUID - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Randomize UUID - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of network groups	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Randomize UUID - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Randomize UUID - body - data

Mark as up-to-date

POST /web/api/v2.1/agents/actions/mark-up-to-date

The value of the Agent version as "up-to-date" is a useful filter for many actions. There are scenarios where the Management does not recognize a version as latest. For example, if Agents that were sent a new version with the update-software command did not yet report to their Management.

You can manually mark these Agents as up-to-date.

This command is not available to users with the SOC role.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permissions to perform the requested action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Mark as up-to-date - response - data table
errors	Errors	false	array

Mark as up-to-date - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Mark as up-to-date - body - filter table
data	Data	false	see Mark as up-to-date - body - data table

Mark as up-to-date - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Mark as up-to-date - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Mark as up-to-date - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Enable Network Discovery

POST /web/api/v2.1/agents/actions/ranger-enable

Singularity Network Discovery gives full visibility of all devices connected to your network. Network Discovery scans your corporate environment to identify and manage connected devices, even those not protected by or supported by SentinelOne. Use this command to enable Network Discovery on Agents that match the filter. The Agent adds "Scanner" to its functionality.

If the given Agent cannot support Network Discovery, or if Network Discovery is already enabled, this command does nothing.

Network Discovery requires a special license. Consult with your SentinelOne SE.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Enable Network Discovery - response - data table
errors	Errors	false	array

Enable Network Discovery - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Enable Network Discovery - body - filter table
data	Data	false	see Enable Network Discovery - body - data table

Enable Network Discovery - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Enable Network Discovery - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Enable Network Discovery - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Enable Network Discovery - body - data

Disable Network Discovery

POST /web/api/v2.1/agents/actions/ranger-disable

Disable Network Discovery from the Agents that match the filter.
Singularity Network Discovery gives full visibility of all devices connected to your network. Network Discovery scans your corporate environment to identify and manage connected devices, even those not protected by or supported by SentinelOne. When Network Discovery is enabled on an Agent, the Agent adds "Scanner" to its functionality. It is the starting point for the Network Discovery scans.
Best Practice: Disable Network Discovery on endpoints that are performance-sensitive and on endpoints that often connect to non-corporate networks.

BEST PRACTICE
Disable Network Discovery on endpoints that are performance-sensitive and on endpoints that often connect to non-corporate networks.

Response Messages

- 200 - Success
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.
- 403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Disable Network Discovery - response - data table
errors	Errors	false	array

Disable Network Discovery - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Disable Network Discovery - body - filter table
data	Data	false	see Disable Network Discovery - body - data table

Disable Network Discovery - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Disable Network Discovery - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Disable Network Discovery - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Disable Network Discovery - body - data

Edit local upgrade/downgrade Site authorization

POST /web/api/v2.1/agents/actions/local-upgrade-authorization

Edit when authorization of local upgrades/downgrades expires.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Edit local upgrade/downgrade Site authorization - response - data table
errors	Errors	false	array

Edit local upgrade/downgrade Site authorization - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Edit local upgrade/downgrade Site authorization - body - data table
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Edit local upgrade/downgrade Site authorization - body - filter table

Edit local upgrade/downgrade Site authorization - body - data

Name	Description	Required	Value
agentAuthorization	Agent approval expiration timestamp	true	string

Edit local upgrade/downgrade Site authorization - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []

agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance	false	string []

	id(supports multiple values)		
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Edit local upgrade/downgrade Site authorization - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer

cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string
createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []

ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []

isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string

lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []

operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string

remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []
scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean

threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer
totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Edit local upgrade/downgrade Site authorization - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Reset Passphrases

POST /web/api/v2.1/agents/actions/reset-passphrase

Initiate an Agent passphrase reset for Agents that match the filter.

This action performs eligibility checks (for example: Agent online status, required capabilities, feature toggles, and cooldown period) and returns per-agent results. Historical passphrase records are kept in the Management and are associated with the Agent.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Reset Passphrases - response - data table
errors	Errors	false	array

Reset Passphrases - response - data

Name	Description	Required	Value
summary	Summary	true	
results	Results	false	see Reset Passphrases - response - results table

Reset Passphrases - response - results

Name	Description	Required	Value
agentId		true	string
attempted		true	boolean
status		true	string
reasons		false	see Reset Passphrases - response - reasons table

Reset Passphrases - response - reasons

Name	Description	Required	Value
code		true	string
message		true	string
details		false	

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Reset Passphrases - body - filter table
data	Data	false	see Reset Passphrases - body - data table

Reset Passphrases - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Reset Passphrases - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of network groups	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Reset Passphrases - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Reset Passphrases - body - data

Disable Agent

POST /web/api/v2.1/agents/actions/disable-agent

Use this command to disable Agents that match the filter.
Disabled agents run with minimal footprint and do not detect or mitigate threats, but they maintain connectivity with the Management Console.
If the command returns "Insufficient permissions", make sure you have permissions for the Account, Site, or Group and a role that allows Disable Agent (Admin, IR team or IT).
In the body of this command, the data parameter set is mandatory.

Response Messages

- 200 - Success
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.
- 403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Disable Agent - response - data table
errors	Errors	false	array

Disable Agent - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Disable Agent - body - data table
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Disable Agent - body - filter table

Disable Agent - body - data

Name	Description	Required	Value
shouldReboot	Reboot the endpoint	true	boolean
expiration	Agents will be re-enabled after this timestamp	false	string
expirationTimezone	Timezone for the expiration timestamp	false	string

Disable Agent - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory	false	string []

	username string (supports multiple values)		
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []

cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceid__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Disable Agent - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores	false	string

	(inclusive)		
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string
createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>- <to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []

ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with	false	string []

	these package types		
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string

lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network	false	boolean []

	Quarantine Control and its enabled for the agent's group		
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string

registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []
scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before	false	string

	this time		
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer
totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer

windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer
------------------------	---	-------	---------

Disable Agent - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Enable Agent

POST /web/api/v2.1/agents/actions/enable-agent

Use this command to enable disabled Agents that match the filter.

If the command returns "Insufficient permissions", make sure you have permissions for the Account, Site, or Group and a role that allows Disable Agent (Admin, IR team or IT).

In the body of this command, the data parameter set is mandatory.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Enable Agent - response - data table
errors	Errors	false	array

Enable Agent - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Enable Agent - body - data table
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Enable Agent - body - filter table

Enable Agent - body - data

Name	Description	Required	Value
shouldReboot	Reboot the endpoint	true	boolean

Enable Agent - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []

agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance	false	string []

	id(supports multiple values)		
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Enable Agent - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer

cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string
createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []

ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraild__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []

isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string

lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []

operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string

remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []
scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean

threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer
totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Enable Agent - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Start Remote Profiling

POST /web/api/v2.1/agents/actions/start-profiling

Use this command to start remote profiling on Agents that match the filter.

Remote profiling lets you collect runtime diagnostic information for Agents on containers.

If the command returns "Insufficient permissions", make sure you have permissions for the Account, Site, or Group and a role that allows Start Remote Profiling (Admin or IT).

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Start Remote Profiling - response - data table
errors	Errors	false	array

Start Remote Profiling - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Start Remote Profiling - body - filter table
data	Data	false	see Start Remote Profiling - body - data table

Start Remote Profiling - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Start Remote Profiling - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Start Remote Profiling - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
podsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Start Remote Profiling - body - data

Name	Description	Required	Value
timeout	Profiling will be disabled after that many seconds	false	integer

Stop Remote Profiling

POST /web/api/v2.1/agents/actions/stop-profiling

Use this command to stop remote profiling on Agents that match the filter.

If the command returns "Insufficient permissions", make sure you have permissions for the Account, Site, or Group and a role that allows Stop Remote Profiling (Admin or IT).

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Stop Remote Profiling - response - data table
errors	Errors	false	array

Stop Remote Profiling - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Stop Remote Profiling - body - filter table
data	Data	false	see Stop Remote Profiling - body - data table

Stop Remote Profiling - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Stop Remote Profiling - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Stop Remote Profiling - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Stop Remote Profiling - body - data

Approve Stateless Upgrades

POST /web/api/v2.1/agents/actions/approve-stateless-upgrade

Approve stateless upgrade for agents

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Approve Stateless Upgrades - response - data table
errors	Errors	false	array

Approve Stateless Upgrades - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Approve Stateless Upgrades - body - filter table
data	Data	false	see Approve Stateless Upgrades - body - data table

Approve Stateless Upgrades - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Approve Stateless Upgrades - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Approve Stateless Upgrades - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
podsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Approve Stateless Upgrades - body - data

Name	Description	Required	Value
expiration	Number of days users are authorized to upgrade Agents	true	integer

Manage endpoint tags: add, remove, override

POST /web/api/v2.1/agents/actions/manage-tags

The "add" operation adds the given tags to the endpoints (if not already present), the "remove" operation removes the given tags from endpoints (if present), and the "override" operation overrides already present tag(s) by the same key of the given tags (if multiple same-key tags are provided, they are preserved).

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Manage endpoint tags: add, remove, override - response - data table
errors	Errors	false	array

Manage endpoint tags: add, remove, override - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Manage endpoint tags: add, remove, override - body - filter table
data	Tags to attach	false	see Manage endpoint tags: add, remove, override - body - data table

Manage endpoint tags: add, remove, override - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Manage endpoint tags: add, remove, override - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Manage endpoint tags: add, remove, override - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Manage endpoint tags: add, remove, override - body - data

Name	Description	Required	Value
operation	Operation to perform on tag	true	enum
tagId	Tag ID	true	string

Agent Support Actions

Clear Remote Shell

POST /web/api/v2.1/agents/actions/clear-remote-shell-session

Remote Shell is a powerful way to respond remotely to events on endpoints. It lets you open full shell capabilities - PowerShell on Windows and Bash on macOS and Linux. For best practices, a Remote Shell session can be terminated in many ways: from the UI, from Agent timeouts, from endpoint or connections issues, and so on. If a shell closes at the same time that an Agent goes offline, Remote Shell status is incorrect on the Management.

Use this command to clear the "open shell" flags on the Management.

The IT user role does not have permissions to run this command.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Clear Remote Shell - response - data table
errors	Errors	false	array

Clear Remote Shell - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Clear Remote Shell - body - filter table
data	Data	false	see Clear Remote Shell - body - data table

Clear Remote Shell - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Clear Remote Shell - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Clear Remote Shell - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Agents

Get Agents

GET /web/api/v2.1/agents

Get the Agents, and their data, that match the filter. This command gives the Agent ID, which you can use in other commands. To save the list and data to a CSV file, use "export/agents".

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
activeprotection	optional	Included agent active protections. Example: "edr,idr".
activethreats	optional	Include Agents with this amount of active threats. Example: "3".
activethreats__gt	optional	Include Agents with at least this amount of active threats. Example: "5".
adcomputermember__contains	optional	Free-text filter by Active Directory computer groups string (supports multiple values). Example: "DC=sentinelone".
adcomputername__contains	optional	Free-text filter by Active Directory computer name string (supports multiple values). Example: "DC=sentinelone".
adcomputerquery__contains	optional	Free-text filter by Active Directory computer name or its groups (supports multiple values). Example: "DC=sentinelone,Windows".
adquery	optional	An Active Directory query string. Example: "CN=Managers,DC=sentinelone,DC=com".
adquery__contains	optional	Free-text filter by Active Directory string (supports multiple values). Example: "DC=sentinelone".
adusermember__contains	optional	Free-text filter by Active Directory user groups string (supports multiple values). Example: "DC=sentinelone".
adusername__contains	optional	Free-text filter by Active Directory username string (supports multiple values). Example: "DC=sentinelone".

aduserquery__contains	optional	Free-text filter by Active Directory computer name or its groups (supports multiple values). Example: "DC=sentinelone,John".
agentnamespace__contains	optional	Free-text filter by agent namespace (supports multiple values)
agentoperatingmode__contains	optional	Free-text filter by Agent Operating Mode (supports multiple values)
agentoperatingmodes	optional	Agent operating mode in. Example: "optimized".
agentoperatingmodesnin	optional	Agent operating mode nin. Example: "optimized".
agentpodname__contains	optional	Free-text filter by agent pod name (supports multiple values)
agentversion__between	optional	Version range for agent version (format: <from_version>-<to_version>, inclusive). Example: "2.0.0.0-2.1.5.144".
agentversion__gt	optional	Agents versions greater than given version. Example: "2.5.1.1320".
agentversion__gte	optional	Agents versions greater than or equal to given version. Example: "2.5.1.1320".
agentversion__lt	optional	Agents versions less than given version. Example: "2.5.1.1320".
agentversion__lte	optional	Agents versions less than or equal to given version. Example: "2.5.1.1320".
agentversions	optional	Agent versions to include. Example: "2.0.0.0,2.1.5.144".
agentversionsnin	optional	Agent versions not to include. Example: "2.0.0.0,2.1.5.144".
appsvulnerabilitystatus	optional	Apps vulnerability status in. Example: "patch_required".
appsvulnerabilitystatusnin	optional	Apps vulnerability status nin. Example: "patch_required".
awsrole__contains	optional	Free-text filter by aws role(supports multiple values)
awssecuritygroups__contains	optional	Free-text filter by aws securityGroups(supports multiple values)
awssubnetids__contains	optional	Free-text filter by aws subnet ids (supports multiple values)
azureresourcegroup__contains	optional	Free-text filter by azure resource group(supports multiple values)
cloudaccount__contains	optional	Free-text filter by cloud account (supports multiple values)

cloudimage__contains	optional	Free-text filter by cloud image (supports multiple values)
cloudinstanceid__contains	optional	Free-text filter by cloud instance id(supports multiple values)
cloudinstancesize__contains	optional	Free-text filter by cloud instance size(supports multiple values)
cloudlocation__contains	optional	Free-text filter by cloud location (supports multiple values)
cloudnetwork__contains	optional	Free-text filter by cloud network (supports multiple values)
cloudprovider	optional	Agents from which cloud provider
cloudprovidernin	optional	Exclude Agents from these cloud provider
cloudtags__contains	optional	Free-text filter by cloud tags (supports multiple values)
clustername__contains	optional	Free-text filter by cluster name (supports multiple values)
computername	optional	Computer name. Example: "My Office Desktop".
computername__contains	optional	Free-text filter by computer name (supports multiple values). Example: "john-office,WIN".
computername__like	optional	Match computer name partially (substring). Example: "Lab1".
computernameoruuid__contains	optional	Free-text filter by computer name or uuid (supports multiple values)
consolemigrationstatuses	optional	Migration status in. Example: "N/A".
consolemigrationstatusnin	optional	Migration status nin. Example: "N/A".
containerizedworkloadcounts	optional	Containerized workload counts
corecount__between	optional	Possible number of CPU cores (inclusive). Example: "2-8".
corecount__gt	optional	CPU cores (more than)
corecount__gte	optional	CPU cores (more than or equal)
corecount__lt	optional	CPU cores (less than)
corecount__lte	optional	CPU cores (less than or equal)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cpucount__between	optional	Possible number of CPU cores (inclusive). Example: "2-8".

cpucount__gt	optional	Number of CPUs (more than)
cpucount__gte	optional	Number of CPUs (more than or equal)
cpucount__lt	optional	Number of CPUs (less than)
cpucount__lte	optional	Number of CPUs (less than or equal)
cpuid__contains	optional	Free-text filter by CPU name (supports multiple values). Example: "Intel,AMD".
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdat__gt	optional	Agents created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Agents created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Agents created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Agents created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
csvfilterid	optional	The ID of the CSV file to filter by. Example: "225494730938493804".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
decommissionedat__between	optional	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
decommissionedat__gt	optional	Agents decommissioned after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__gte	optional	Agents decommissioned after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__lt	optional	Agents decommissioned before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__lte	optional	Agents decommissioned before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
domains	optional	Included network domains. Example: "mybusiness.net,workgroup".

domainsnin	optional	Not included network domains. Example: "mybusiness.net,workgroup".
ecsclustername__contains	optional	Free-text filter by ECS cluster name
ecsservicearn__contains	optional	Free-text filter by ECS service arn
ecsservicename__contains	optional	Free-text filter by ECS service name
ecstaskarn__contains	optional	Free-text filter by ECS task arn
ecstaskavailabilityzone__contains	optional	Free-text filter by ECS task availability zone
ecstaskdefinitionarn__contains	optional	Free-text filter by ECS task definition arn
ecstaskdefinitionfamily__contains	optional	Free-text filter by ECS task definition family
ecstaskdefinitionrevision__contains	optional	Free-text filter by ECS task definition revision
ecstype__contains	optional	Free-text filter by ECS type
ecsversion__contains	optional	Free-text filter by ECS version
encryptedapplications	optional	Disk encryption status
entraid__contains	optional	Free-text filter by Entra ID (supports multiple values)
externalid__contains	optional	Free-text filter by external ID (Customer ID). Example: "Tag#1 - monitoring,Performance machine".
externalip__contains	optional	Free-text filter by visible IP (supports multiple values). Example: "205,127.0".
filteredgroupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
filteredsiteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
filterid	optional	Include all Agents matching this saved filter. Example: "225494730938493804".
firewallenabled	optional	The agents supports Firewall Control and it is enabled for the agent's group
gatewayip	optional	Gateway ip. Example: "192.168.0.1".

gcp-service-account__contains	optional	Free-text filter by gcp service account (supports multiple values)
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
has-containerized-workload	optional	Indicates whether the agent protects containerized workload at the moment
has-local-configuration	optional	Agent has a local configuration set
has-tags	optional	Include only Agents that have any tags assigned if True, or none if False
ids	optional	Included Agent IDs. Example: "225494730938493804,225494730938493915".
idsnin	optional	Excluded Agent IDs. Example: "225494730938493804,225494730938493915".
infected	optional	Include only Agents with at least one active threat
installertypes	optional	Include only Agents installed with these package types. Example: ".msi".
installertypesnin	optional	Exclude Agents installed with these package types. Example: ".msi".
is-active	optional	Include only active Agents
is-ad-connector	optional	The agents that are ADConnectors if True, or not if False
is-decommissioned	optional	Include active, decommissioned or both. Example: "True,False".
is-event-search-proxy-enabled	optional	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).
is-hyper-automate	optional	The agents has Hyper Automate PNA enabled if True, or not if False
is-mgmt-proxy-enabled	optional	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).
is-pending-uninstall	optional	Include only Agents with pending uninstall requests
is-uninstalled	optional	Include installed, uninstalled or both. Example: "True,False".
is-up-to-date	optional	Include only Agents with updated software
k8s-node-labels__contains	optional	Free-text filter by K8s node labels (supports multiple values)
k8s-node-name__contains	optional	Free-text filter by K8s node name (supports multiple values)
k8s-type__contains	optional	Free-text filter by K8s type(supports multiple values)

k8sversion__contains	optional	Free-text filter by K8s version (supports multiple values)
lastactivatedate__between	optional	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
lastactivatedate__gt	optional	Agents last active after this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__gte	optional	Agents last active after or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__lt	optional	Agents last active before this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__lte	optional	Agents last active before or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastloggedinusername__contains	optional	Free-text filter by username (supports multiple values). Example: "admin,johnd1".
lastsuccessfulscandate__between	optional	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
lastsuccessfulscandate__gt	optional	Agents last successful full disk scan after this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__gte	optional	Agents last successful full disk scan after or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__lt	optional	Agents last successful full disk scan before this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__lte	optional	Agents last successful full disk scan before or at this time. Example: "2018-02-27T04:49:26.257525Z".
limit	optional	Limit number of returned items (1-1000). Example: "10".
liveupdateid__contains	optional	Free-text filter by live update ID (supports multiple values)
locationenabled	optional	The agents supports Location Awareness and it is enabled for the agent's group
locationids	optional	Include only Agents reporting these locations. Example: "225494730938493804,225494730938493915".
locationidsnin	optional	Do not include only Agents reporting these locations. Example: "225494730938493804,225494730938493915".
machinetypes	optional	Included machine types. Example: "laptop,desktop".

machinetypesnin	optional	Not included machine types. Example: "laptop,desktop".
migrationstatus	optional	Migration status. Example: "N/A".
missingpermissions	optional	Included missing permissions. Example: "user_action_needed_bluetooth_per,user_action_needed_fda_helper".
missingpermissionsnin	optional	Excluded missing permissions. Example: "user_action_needed_bluetooth_per,user_action_needed_fda_helper".
mitigationmode	optional	Agent mitigation mode policy. Example: "detect".
mitigationmodesuspicious	optional	Mitigation mode policy for suspicious activity. Example: "detect".
networkinterfacegatewaymacaddress__contains	optional	Free-text filter by Gateway MAC address (supports multiple values). Example: "aa:0f,:41:".
networkinterfaceip__contains	optional	Free-text filter by local IP (supports multiple values). Example: "192,10.0.0".
networkinterfacephysical__contains	optional	Free-text filter by MAC address (supports multiple values). Example: "aa:0f,:41:".
networkquarantineenabled	optional	The agents supports Network Quarantine Control and its enabled for the agent's group
networkstatuses	optional	Included network statuses. Example: "connected,connecting".
networkstatusesnin	optional	Included network statuses. Example: "connected,connecting".
operationalstates	optional	Agent operational state
operationalstatesnin	optional	Do not include these Agent operational states
osarch	optional	OS architecture. Example: "32 bit".
osarches	optional	OS architectures to include. Example: "32 bit,64 bit".
osarchesnin	optional	OS architectures not to include. Example: "32 bit,64 bit".
ostypes	optional	Included OS types. Example: "linux".
ostypesnin	optional	Not included OS types. Example: "linux".
osversion__contains	optional	Free-text filter by OS full name and version (supports multiple values). Example: "Service Pack 1".
pacfileusage	optional	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).

proxymethod	optional	Include only Agents using these proxy methods. Example: "None,Auto,System,User,Custom".
proxymethodnin	optional	Exclude Agents using these proxy methods. Example: "None,Auto,System,User,Custom".
query	optional	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term). Example: "Linux".
rangerstatus	optional	[DEPRECATED] Use rangerStatuses. Example: "NotApplicable".
rangerstatuses	optional	Status of Network Discovery. Example: "NotApplicable".
rangerstatusesnin	optional	Do not include these Network Scanner Statuses. Example: "NotApplicable".
rangerversions	optional	Network Scanner versions to include. Example: "2.0.0.0,2.1.5.144".
rangerversionsnin	optional	Network Scanner versions not to include. Example: "2.0.0.0,2.1.5.144".
registeredat__between	optional	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
registeredat__gt	optional	Agents registered after this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__gte	optional	Agents registered after or at this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__lt	optional	Agents registered before this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__lte	optional	Agents registered before or at this time. Example: "2018-02-27T04:49:26.257525Z".
remoteopsforensicssupported	optional	Include only agents that has Remote Ops Forensicsfeature supported
remoteprofilingsstates	optional	Agent remote profiling state
remoteprofilingsstatesnin	optional	Do not include these Agent remote profiling states
rsolevel	optional	Supported Remote Script Orchestration level. Example: "none".
rsolevels	optional	A list of included rso_levels. Example: "pro,ars".
scanstatus	optional	Scan status. Example: "none".

scanstatuses	optional	Included scan statuses. Example: "started,aborted".
scanstatusesnin	optional	Not included scan statuses. Example: "started,aborted".
serialnumber__contains	optional	Free-text filter by Serial Number (supports multiple values)
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
storagetypes	optional	Included storage types. Example: "NetApp,Dell,S3".
storagetypesnin	optional	Excluded storage types. Example: "NetApp,Dell,S3".
tagsdata	optional	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key. Example: "{"key1": ["value1_1", "value1_2"], "key2__nin": ["value2"]}".
threatcontenthash	optional	Include only Agents that have at least one threat with this content hash. Example: "cf23df2207d99a74fbe169e3eba035e633b65d94".
threatcreatedat__between	optional	Agents with threats reported in a date range (format: <from_timestamp>--<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
threatcreatedat__gt	optional	Agents with threats reported after this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__gte	optional	Agents with threats reported after or at this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__lt	optional	Agents with threats reported before this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__lte	optional	Agents with threats reported before or at this time. Example: "2018-02-27T04:49:26.257525Z".
threathidden	optional	Include only Agents with at least one hidden threat
threatmitigationstatus	optional	Include only Agents that have threats with this mitigation status.

		Example: "mitigated".
threatrebootrequired	optional	Has at least one threat with at least one mitigation action pending reboot to succeed
threatresolved	optional	Include only Agents with at least one resolved threat
totalmemory__between	optional	Total memory range (GB, inclusive). Example: "4-8".
totalmemory__gt	optional	Memory size (MB, more than)
totalmemory__gte	optional	Memory size (MB, more than or equal)
totalmemory__lt	optional	Memory size (MB, less than)
totalmemory__lte	optional	Memory size (MB, less than or equal)
updatedat__between	optional	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedat__gt	optional	Agents updated after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Agents updated after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Agents updated before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Agents updated before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
useractionsneeded	optional	Included pending user actions. Example: "reboot_needed,upgrade_needed".
useractionsneedednin	optional	Excluded pending user actions. Example: "reboot_needed,upgrade_needed".
uuid	optional	Agent's universally unique identifier. Example: "ff819e70af13be381993075eb0ce5f2f6de05be2".
uuid__contains	optional	Free-text filter by Agent UUID (supports multiple values). Example: "e92-01928,b055".
uuids	optional	A list of included UUIDs. Example: "ff819e70af13be381993075eb0ce5f2f6de05b11,ff819e70af13be381993075eb0ce5f2f6de05c22".
windowsosrevision__gte	optional	Agents os revision than or equal to given version

windowsosrevision__lte	optional	Agents os revision lower than or equal to given version
------------------------	----------	---

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Agents - response - pagination table
data	Response data	false	see Get Agents - response - data table
errors	Errors	false	array

Get Agents - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Agents - response - data

Name	Description	Required	Value
accountId	A reference to the containing account	false	string
accountName	Name of the containing account	false	string
activeDirectory	Active Directory data	false	see Get Agents - response - activeDirectory table
activeProtection	A list of agent active protections. List items possible values: "edr, idr".	false	string []
activeThreats	Current number of active threats	false	integer
agentOperatingMode	Agent operating mode: optimized (lightweight agent, e.g. Linux kernel >= 5.8) or standard (runtime agents that are not lightweight agents). Null when not applicable.	false	enum
agentVersion	Agent version	false	string
allowRemoteShell	Agent is capable and policy enabled for remote shell	false	boolean
appsVulnerabilityStatus	Apps vulnerability status	false	enum
cloudProviders	Cloud providers for this agent	false	object
computerName	Computer name	false	string
consoleMigrationStatus	What step the agent is at in the process of migrating to another console, if any	false	enum
containerizedWorkloadCounts	Containerized workload counts	false	see Get Agents - response - containerizedWorkloadCounts table

coreCount	CPU cores	false	integer
cpuCount	Number of CPUs	false	integer
cpuld	CPU model	false	string
createdAt	Created at	false	string
detectionState	Detection State	false	string
domain	Network domain	false	string
encryptedApplications	Disk encryption status	false	boolean
entraId	Entra ID	false	string
externalId	External id set by customer	false	string
externalIp	External IPv4 address	false	string
firewallEnabled	Firewall enabled	false	boolean
firstFullModeTime	Date of the first time the Agent moved to full or slim detection modes	false	string
fullDiskScanLastUpdatedAt	Last time scan status was updated	false	string
groupId	A reference to the containing network group	false	string
groupIp	IP Address subnet	false	string
groupName	Name of the containing network group	false	string
groupUpdatedAt	Group updated at	false	string
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean
id	Agent ID	false	string
infected	Indicates if the Agent has active threats	false	boolean
inRemoteShellSession	Is the Agent in a remote shell session	false	boolean
installerType	Installer package type (file extension)	false	enum
isActive	Indicates if the agent was recently active	false	boolean
isAdConnector	Indicates if the Agent is ADConnector	false	boolean
isDecommissioned	Is Agent decommissioned	false	boolean
isHyperAutomate	Indicates if PNA for Hyper Automate Enabled	false	boolean
isPendingUninstall	Agent with a pending uninstall	false	boolean

	request		
isUninstalled	Indicates if Agent was removed from the device	false	boolean
isUpToDate	Indicates if the agent version is up to date	false	boolean
lastActiveDate	Last active date	false	string
lastIpToMgmt	The last ip used to connect to the Management console	false	string
lastLoggedInUserName	Last logged in user name	false	string
lastSuccessfulScanDate	Last successful full disc scan time	false	string
licenseKey	License key	false	string
locationEnabled	Location enabled	false	boolean
locations	A list of locations reported by the Agent	false	see Get Agents - response - locations table
locationType	Reported location type	false	enum
machineSid	Machine SID of the endpoint	false	string
machineType	Machine type	false	enum
missingPermissions	A list of missing permissions. List items possible values: "user_action_needed_fda, user_action_needed_rs_fda, user_action_needed_fda_helper, user_action_needed_fda_sentinel, user_action_needed_bluetooth_per, user_action_needed_network, user_action_needed_notifications".	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
modelName	Device model	false	string
networkInterfaces	Device's network interfaces	false	see Get Agents - response - networkInterfaces table
networkQuarantineEnabled	Network quarantine enabled	false	boolean
networkStatus	Agent's network connectivity status	false	enum
operationalState	Agent operational state	false	string
operationalStateExpiration	Agent operational state expiration	false	string
osArch	Os arch	false	enum

osName	Os name	false	string
osRevision	Os revision	false	string
osStartTime	Last boot time	false	string
osType	OS type	false	enum
osUsername	Os username	false	string
policyUpdatedAt	Policy updated at	false	string
proxyStates	Proxy state information	false	see Get Agents - response - proxyStates table
rangerStatus	Is Agent disabled as a Network Discovery	false	enum
rangerVersion	The version of Network Discovery	false	string
registeredAt	Time of first registration to management console (similar to createdAt)	false	string
remoteProfilingState	Agent remote profiling state	false	string
remoteProfilingStateExpiration	Agent remote profiling state expiration inseconds	false	string
scanAbortedAt	Abort time of last scan (If applicable)	false	string
scanFinishedAt	Finish time of last scan (If applicable)	false	string
scanStartedAt	Start time of last scan	false	string
scanStatus	Last scan status	false	enum
serialNumber	Serial Number of the endpoint	false	string
showAlertIcon	Show alert icon in agent view and details	false	boolean
siteId	A reference to the containing site	false	string
siteName	Name of the containing site	false	string
storageName	Storage Name	false	string
storageType	Storage Type	false	string
tags	Agent's attached tags	false	see Get Agents - response - tags table
threatRebootRequired	Has at least one threat with at least one mitigation action that is pending reboot to succeed	false	boolean
totalMemory	Memory size (MB)	false	integer
updatedAt	Updated at	false	string
userActionsNeeded	A list of pending user actions. List items possible values: "none,	false	string []

	user_action_needed, reboot_needed, upgrade_needed, incompatible_os, unprotected, rebootless_without_dynamic_detection, extended_exclusions_partially_accepted, reboot_required, pending_deprecation, ne_not_running, ne_cf_not_active, pending_performance_insights".		
uuid	Agent's universally unique identifier	false	string

Get Agents - response - activeDirectory

Name	Description	Required	Value
computerDistinguishedName	Computer distinguished name	false	string
computerMemberOf	Computer member of	false	string []
lastUserDistinguishedName	Last user distinguished name	false	string
lastUserMemberOf	Last user member of	false	string []
mail	Mail	false	string
userPrincipalName	User principal name	false	string

Get Agents - response - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Get Agents - response - locations

Name	Description	Required	Value
id	Location ID	false	string
name	Location name	false	string
scope	Location scope	false	enum

Get Agents - response - networkInterfaces

Name	Description	Required	Value
gatewayIp	The default gateway ip	false	string
gatewayMacAddress	The default gateway mac address	false	string
id	Id	false	string
inet	IPv4 addresses	false	string []
inet6	IPv6 addresses	false	string []
name	Name	false	string
physical	Interface's MAC address	false	string

Get Agents - response - proxyStates

Name	Description	Required	Value
eventSearchAddress	Event Search Proxy Address	false	string
isEventSearchProxyEnabled	Connected to Event Search using a proxy	false	boolean
isMgmtProxyEnabled	Connected to Management Console using a proxy	false	boolean
mgmtProxyAddress	Management Proxy Address	false	string
pacFileUsage	PAC file usage status	false	boolean
proxyMethod	Proxy method	false	string

Get Agents - response - tags

Name	Description	Required	Value
------	-------------	----------	-------

sentinelone	SentinelOne tags section	false	see Get Agents - response - sentinelone table
-------------	--------------------------	-------	---

Get Agents - response - sentinelone

Name	Description	Required	Value
assignedAt	when tag assigned to the agent	false	string
assignedBy	full user name who assigned the tag to the agent	false	string
assignedById	user ID who assigned the tag to the agent	false	string
id	Tag ID	false	string
key	Tag key	false	string
value	Tag value	false	string

Count Agents

GET /web/api/v2.1/agents/count

Get the count of Agents that match a filter. This command is useful to run before you run other commands. You will be able to manage Agent maintenance better if you know how many Agents will get a command that takes time (such as Update Software).

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
activeprotection	optional	Included agent active protections. Example: "edr,idr".
activethreats	optional	Include Agents with this amount of active threats. Example: "3".
activethreats__gt	optional	Include Agents with at least this amount of active threats. Example: "5".
adcomputermember__contains	optional	Free-text filter by Active Directory computer groups string (supports multiple values). Example: "DC=sentinelone".
adcomputername__contains	optional	Free-text filter by Active Directory computer name string (supports multiple values). Example: "DC=sentinelone".
adcomputerquery__contains	optional	Free-text filter by Active Directory computer name or its groups (supports multiple values). Example: "DC=sentinelone,Windows".

adquery	optional	An Active Directory query string. Example: "CN=Managers,DC=sentinelone,DC=com".
adquery__contains	optional	Free-text filter by Active Directory string (supports multiple values). Example: "DC=sentinelone".
adusermember__contains	optional	Free-text filter by Active Directory user groups string (supports multiple values). Example: "DC=sentinelone".
adusername__contains	optional	Free-text filter by Active Directory username string (supports multiple values). Example: "DC=sentinelone".
aduserquery__contains	optional	Free-text filter by Active Directory computer name or its groups (supports multiple values). Example: "DC=sentinelone,John".
agentnamespace__contains	optional	Free-text filter by agent namespace (supports multiple values)
agentoperatingmode__contains	optional	Free-text filter by Agent Operating Mode (supports multiple values)
agentoperatingmodes	optional	Agent operating mode in. Example: "optimized".
agentoperatingmodesnin	optional	Agent operating mode nin. Example: "optimized".
agentpodname__contains	optional	Free-text filter by agent pod name (supports multiple values)
agentversion__between	optional	Version range for agent version (format: <from_version>-<to_version>, inclusive). Example: "2.0.0.0-2.1.5.144".
agentversion__gt	optional	Agents versions greater than given version. Example: "2.5.1.1320".
agentversion__gte	optional	Agents versions greater than or equal to given version. Example: "2.5.1.1320".
agentversion__lt	optional	Agents versions less than given version. Example: "2.5.1.1320".
agentversion__lte	optional	Agents versions less than or equal to given version. Example: "2.5.1.1320".
agentversions	optional	Agent versions to include. Example: "2.0.0.0,2.1.5.144".
agentversionsnin	optional	Agent versions not to include. Example: "2.0.0.0,2.1.5.144".
appsvulnerabilitystatus	optional	Apps vulnerability status in. Example: "patch_required".
appsvulnerabilitystatusnin	optional	Apps vulnerability status nin. Example: "patch_required".
awsrole__contains	optional	Free-text filter by aws role(supports multiple values)

awssecuritygroups__contains	optional	Free-text filter by aws securityGroups(supports multiple values)
awssubnetids__contains	optional	Free-text filter by aws subnet ids (supports multiple values)
azureresourcegroup__contains	optional	Free-text filter by azure resource group(supports multiple values)
cloudaccount__contains	optional	Free-text filter by cloud account (supports multiple values)
cloudimage__contains	optional	Free-text filter by cloud image (supports multiple values)
cloudinstanceid__contains	optional	Free-text filter by cloud instance id(supports multiple values)
cloudinstancesize__contains	optional	Free-text filter by cloud instance size(supports multiple values)
cloudlocation__contains	optional	Free-text filter by cloud location (supports multiple values)
cloudnetwork__contains	optional	Free-text filter by cloud network (supports multiple values)
cloudprovider	optional	Agents from which cloud provider
cloudprovidernin	optional	Exclude Agents from these cloud provider
cloudtags__contains	optional	Free-text filter by cloud tags (supports multiple values)
clustername__contains	optional	Free-text filter by cluster name (supports multiple values)
computername	optional	Computer name. Example: "My Office Desktop".
computername__contains	optional	Free-text filter by computer name (supports multiple values). Example: "john-office,WIN".
computername__like	optional	Match computer name partially (substring). Example: "Lab1".
computernameoruuid__contains	optional	Free-text filter by computer name or uuid (supports multiple values)
consolemigrationstatus	optional	Migration status in. Example: "N/A".
consolemigrationstatusnin	optional	Migration status nin. Example: "N/A".
containerizedworkloadcounts	optional	Containerized workload counts
corecount__between	optional	Possible number of CPU cores (inclusive). Example: "2-8".

corecount__gt	optional	CPU cores (more than)
corecount__gte	optional	CPU cores (more than or equal)
corecount__lt	optional	CPU cores (less than)
corecount__lte	optional	CPU cores (less than or equal)
cpucount__between	optional	Possible number of CPU cores (inclusive). Example: "2-8".
cpucount__gt	optional	Number of CPUs (more than)
cpucount__gte	optional	Number of CPUs (more than or equal)
cpucount__lt	optional	Number of CPUs (less than)
cpucount__lte	optional	Number of CPUs (less than or equal)
cpuid__contains	optional	Free-text filter by CPU name (supports multiple values). Example: "Intel,AMD".
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdat__gt	optional	Agents created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Agents created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Agents created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Agents created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
csvfilterid	optional	The ID of the CSV file to filter by. Example: "225494730938493804".
decommissionedat__between	optional	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
decommissionedat__gt	optional	Agents decommissioned after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__gte	optional	Agents decommissioned after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__lt	optional	Agents decommissioned before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__lte	optional	Agents decommissioned before this timestamp. Example:

e		"2018-02-27T04:49:26.257525Z".
domains	optional	Included network domains. Example: "mybusiness.net,workgroup".
domainsnin	optional	Not included network domains. Example: "mybusiness.net,workgroup".
ecsclustername__contains	optional	Free-text filter by ECS cluster name
ecsservicearn__contains	optional	Free-text filter by ECS service arn
ecsservicename__contains	optional	Free-text filter by ECS service name
ecstaskarn__contains	optional	Free-text filter by ECS task arn
ecstaskavailabilityzone__contains	optional	Free-text filter by ECS task availability zone
ecstaskdefinitionarn__contains	optional	Free-text filter by ECS task definition arn
ecstaskdefinitionfamily__contains	optional	Free-text filter by ECS task definition family
ecstaskdefinitionrevision__contains	optional	Free-text filter by ECS task definition revision
ecstype__contains	optional	Free-text filter by ECS type
ecsversion__contains	optional	Free-text filter by ECS version
encryptedapplications	optional	Disk encryption status
entraid__contains	optional	Free-text filter by Entra ID (supports multiple values)
externalid__contains	optional	Free-text filter by external ID (Customer ID). Example: "Tag#1 - monitoring,Performance machine".
externalip__contains	optional	Free-text filter by visible IP (supports multiple values). Example: "205,127.0".
filteredgroupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
filteredsiteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
filterid	optional	Include all Agents matching this saved filter. Example: "225494730938493804".

firewallenabled	optional	The agents supports Firewall Control and it is enabled for the agent's group
gatewayip	optional	Gateway ip. Example: "192.168.0.1".
gcpserviceaccount__contains	optional	Free-text filter by gcp service account (supports multiple values)
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
hascontainerizedworkload	optional	Indicates whether the agent protects containerized workload at the moment
haslocalconfiguration	optional	Agent has a local configuration set
hastags	optional	Include only Agents that have any tags assigned if True, or none if False
ids	optional	Included Agent IDs. Example: "225494730938493804,225494730938493915".
idsnin	optional	Excluded Agent IDs. Example: "225494730938493804,225494730938493915".
infected	optional	Include only Agents with at least one active threat
installertypes	optional	Include only Agents installed with these package types. Example: ".msi".
installertypesnin	optional	Exclude Agents installed with these package types. Example: ".msi".
isactive	optional	Include only active Agents
isadconnector	optional	The agents that are ADConnectors if True, or not if False
isdecommissioned	optional	Include active, decommissioned or both. Example: "True,False".
iseventsearchproxyenabled	optional	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).
ishyperautomate	optional	The agents has Hyper Automate PNA enabled if True, or not if False
ismgmtproxyenabled	optional	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).
ispendinguninstall	optional	Include only Agents with pending uninstall requests
isuninstalled	optional	Include installed, uninstalled or both. Example: "True,False".
isuptodate	optional	Include only Agents with updated software
k8snodelabels__contains	optional	Free-text filter by K8s node labels (supports multiple values)

k8snodename__contains	optional	Free-text filter by K8s node name (supports multiple values)
k8stype__contains	optional	Free-text filter by K8s type(supports multiple values)
k8sversion__contains	optional	Free-text filter by K8s version (supports multiple values)
lastactivatedate__between	optional	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
lastactivatedate__gt	optional	Agents last active after this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__gte	optional	Agents last active after or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__lt	optional	Agents last active before this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__lte	optional	Agents last active before or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastloggedinusername__contains	optional	Free-text filter by username (supports multiple values). Example: "admin,johnd1".
lastsuccessfulscandate__between	optional	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
lastsuccessfulscandate__gt	optional	Agents last successful full disk scan after this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__gte	optional	Agents last successful full disk scan after or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__lt	optional	Agents last successful full disk scan before this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__lte	optional	Agents last successful full disk scan before or at this time. Example: "2018-02-27T04:49:26.257525Z".
liveupdateid__contains	optional	Free-text filter by live update ID (supports multiple values)
locationenabled	optional	The agents supports Location Awareness and it is enabled for the agent's group
locationids	optional	Include only Agents reporting these locations. Example: "225494730938493804,225494730938493915".
locationidsnin	optional	Do not include only Agents reporting these locations. Example: "225494730938493804,225494730938493915".

machinetypes	optional	Included machine types. Example: "laptop,desktop".
machinetypesnin	optional	Not included machine types. Example: "laptop,desktop".
migrationstatus	optional	Migration status. Example: "N/A".
missingpermissions	optional	Included missing permissions. Example: "user_action_needed_bluetooth_per,user_action_needed_fda_helper".
missingpermissionsnin	optional	Excluded missing permissions. Example: "user_action_needed_bluetooth_per,user_action_needed_fda_helper".
mitigationmode	optional	Agent mitigation mode policy. Example: "detect".
mitigationmodesuspicious	optional	Mitigation mode policy for suspicious activity. Example: "detect".
networkinterfacegatewaymacaddress__contains	optional	Free-text filter by Gateway MAC address (supports multiple values). Example: "aa:0f,:41:".
networkinterfaceinet__contains	optional	Free-text filter by local IP (supports multiple values). Example: "192,10.0.0".
networkinterfacephysical__contains	optional	Free-text filter by MAC address (supports multiple values). Example: "aa:0f,:41:".
networkquarantineenabled	optional	The agents supports Network Quarantine Control and its enabled for the agent's group
networkstatuses	optional	Included network statuses. Example: "connected,connecting".
networkstatusesnin	optional	Included network statuses. Example: "connected,connecting".
operationalstates	optional	Agent operational state
operationalstatesnin	optional	Do not include these Agent operational states
osarch	optional	OS architecture. Example: "32 bit".
osarches	optional	OS architectures to include. Example: "32 bit,64 bit".
osarchesnin	optional	OS architectures not to include. Example: "32 bit,64 bit".
ostypes	optional	Included OS types. Example: "linux".
ostypesnin	optional	Not included OS types. Example: "linux".
osversion__contains	optional	Free-text filter by OS full name and version (supports multiple values). Example: "Service Pack 1".
pacfileusage	optional	Include only Agents using PAC file for proxy configuration. Accepts

		true, false, or none (for not reported).
proxymethod	optional	Include only Agents using these proxy methods. Example: "None,Auto,System,User,Custom".
proxymethodnin	optional	Exclude Agents using these proxy methods. Example: "None,Auto,System,User,Custom".
query	optional	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term). Example: "Linux".
rangerstatus	optional	[DEPRECATED] Use rangerStatuses. Example: "NotApplicable".
rangerstatuses	optional	Status of Network Discovery. Example: "NotApplicable".
rangerstatusesnin	optional	Do not include these Network Scanner Statuses. Example: "NotApplicable".
rangerversions	optional	Network Scanner versions to include. Example: "2.0.0.0,2.1.5.144".
rangerversionsnin	optional	Network Scanner versions not to include. Example: "2.0.0.0,2.1.5.144".
registeredat__between	optional	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
registeredat__gt	optional	Agents registered after this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__gte	optional	Agents registered after or at this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__lt	optional	Agents registered before this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__lte	optional	Agents registered before or at this time. Example: "2018-02-27T04:49:26.257525Z".
remoteopsforensicsupported	optional	Include only agents that has Remote Ops Forensicsfeature supported
remoteprofilingsstates	optional	Agent remote profiling state
remoteprofilingsstatesnin	optional	Do not include these Agent remote profiling states
rsolevel	optional	Supported Remote Script Orchestration level. Example: "none".
rsolevels	optional	A list of included rso_levels. Example: "pro,ars".

scanstatus	optional	Scan status. Example: "none".
scanstatuses	optional	Included scan statuses. Example: "started,aborted".
scanstatusesnin	optional	Not included scan statuses. Example: "started,aborted".
serialnumber__contains	optional	Free-text filter by Serial Number (supports multiple values)
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
storagetypes	optional	Included storage types. Example: "NetApp,Dell,S3".
storagetypesnin	optional	Excluded storage types. Example: "NetApp,Dell,S3".
tagsdata	optional	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key. Example: '{"key1": ["value1_1", "value1_2"], "key2__nin": ["value2"]}''.
threatcontenthash	optional	Include only Agents that have at least one threat with this content hash. Example: "cf23df2207d99a74fbe169e3eba035e633b65d94".
threatcreatedat__between	optional	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
threatcreatedat__gt	optional	Agents with threats reported after this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__gte	optional	Agents with threats reported after or at this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__lt	optional	Agents with threats reported before this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__lte	optional	Agents with threats reported before or at this time. Example: "2018-02-27T04:49:26.257525Z".
threathidden	optional	Include only Agents with at least one hidden threat
threatmitigationstatus	optional	Include only Agents that have threats with this mitigation status. Example: "mitigated".
threatrebootrequired	optional	Has at least one threat with at least one mitigation action pending reboot to succeed
threatresolved	optional	Include only Agents with at least one resolved threat
totalmemory__between	optional	Total memory range (GB, inclusive). Example: "4-8".

n		
totalmemory__gt	optional	Memory size (MB, more than)
totalmemory__gte	optional	Memory size (MB, more than or equal)
totalmemory__lt	optional	Memory size (MB, less than)
totalmemory__lte	optional	Memory size (MB, less than or equal)
updatedat__between	optional	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedat__gt	optional	Agents updated after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Agents updated after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Agents updated before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Agents updated before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
useractionsneeded	optional	Included pending user actions. Example: "reboot_needed,upgrade_needed".
useractionsneedednin	optional	Excluded pending user actions. Example: "reboot_needed,upgrade_needed".
uuid	optional	Agent's universally unique identifier. Example: "ff819e70af13be381993075eb0ce5f2f6de05be2".
uuid__contains	optional	Free-text filter by Agent UUID (supports multiple values). Example: "e92-01928,b055".
uuids	optional	A list of included UUIDs. Example: "ff819e70af13be381993075eb0ce5f2f6de05b11,ff819e70af13be381993075eb0ce5f2f6de05c22".
windowsosrevision__gte	optional	Agents os revision than or equal to given version
windowsosrevision__lte	optional	Agents os revision lower than or equal to given version

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Count Agents - response - data table
errors	Errors	false	array

Count Agents - response - data

Name	Description	Required	Value
total	Number of Agents matching the input filter	false	integer

Get Passphrase

GET /web/api/v2.1/agents/passphrases

Show the passphrase for the Agents that match the filter. This is an important command. You need the passphrase for most SentinelCtl commands and for different API commands.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
activeprotection	optional	Included agent active protections. Example: "edr,idr".
activethreats	optional	Include Agents with this amount of active threats. Example: "3".
activethreats__gt	optional	Include Agents with at least this amount of active threats. Example: "5".
adcomputermember__contains	optional	Free-text filter by Active Directory computer groups string (supports multiple values). Example: "DC=sentinelone".
adcomputername__contains	optional	Free-text filter by Active Directory computer name string (supports multiple values). Example: "DC=sentinelone".
adcomputerquery__contains	optional	Free-text filter by Active Directory computer name or its groups (supports multiple values). Example: "DC=sentinelone,Windows".
adquery	optional	An Active Directory query string. Example: "CN=Managers,DC=sentinelone,DC=com".
adquery__contains	optional	Free-text filter by Active Directory string (supports multiple values). Example: "DC=sentinelone".
adusermember__contains	optional	Free-text filter by Active Directory user groups string (supports multiple values). Example: "DC=sentinelone".
adusername__contains	optional	Free-text filter by Active Directory username string (supports multiple values). Example: "DC=sentinelone".

aduserquery__contains	optional	Free-text filter by Active Directory computer name or its groups (supports multiple values). Example: "DC=sentinelone,John".
agentnamespace__contains	optional	Free-text filter by agent namespace (supports multiple values)
agentoperatingmode__contains	optional	Free-text filter by Agent Operating Mode (supports multiple values)
agentoperatingmodes	optional	Agent operating mode in. Example: "optimized".
agentoperatingmodesnin	optional	Agent operating mode nin. Example: "optimized".
agentpodname__contains	optional	Free-text filter by agent pod name (supports multiple values)
agentversion__between	optional	Version range for agent version (format: <from_version>-<to_version>, inclusive). Example: "2.0.0.0-2.1.5.144".
agentversion__gt	optional	Agents versions greater than given version. Example: "2.5.1.1320".
agentversion__gte	optional	Agents versions greater than or equal to given version. Example: "2.5.1.1320".
agentversion__lt	optional	Agents versions less than given version. Example: "2.5.1.1320".
agentversion__lte	optional	Agents versions less than or equal to given version. Example: "2.5.1.1320".
agentversions	optional	Agent versions to include. Example: "2.0.0.0,2.1.5.144".
agentversionsnin	optional	Agent versions not to include. Example: "2.0.0.0,2.1.5.144".
appsvulnerabilitystatuses	optional	Apps vulnerability status in. Example: "patch_required".
appsvulnerabilitystatusnin	optional	Apps vulnerability status nin. Example: "patch_required".
awsrole__contains	optional	Free-text filter by aws role(supports multiple values)
awssecuritygroups__contains	optional	Free-text filter by aws securityGroups(supports multiple values)
awssubnetids__contains	optional	Free-text filter by aws subnet ids (supports multiple values)
azureresourcegroup__contains	optional	Free-text filter by azure resource group(supports multiple values)
cloudaccount__contains	optional	Free-text filter by cloud account (supports multiple values)

cloudimage__contains	optional	Free-text filter by cloud image (supports multiple values)
cloudinstanceid__contains	optional	Free-text filter by cloud instance id(supports multiple values)
cloudinstancesize__contains	optional	Free-text filter by cloud instance size(supports multiple values)
cloudlocation__contains	optional	Free-text filter by cloud location (supports multiple values)
cloudnetwork__contains	optional	Free-text filter by cloud network (supports multiple values)
cloudprovider	optional	Agents from which cloud provider
cloudprovidernin	optional	Exclude Agents from these cloud provider
cloudtags__contains	optional	Free-text filter by cloud tags (supports multiple values)
clustername__contains	optional	Free-text filter by cluster name (supports multiple values)
computername	optional	Computer name. Example: "My Office Desktop".
computername__contains	optional	Free-text filter by computer name (supports multiple values). Example: "john-office,WIN".
computername__like	optional	Match computer name partially (substring). Example: "Lab1".
computernameoruuid__contains	optional	Free-text filter by computer name or uuid (supports multiple values)
consolemigrationstatuses	optional	Migration status in. Example: "N/A".
consolemigrationstatusnin	optional	Migration status nin. Example: "N/A".
containerizedworkloadcounts	optional	Containerized workload counts
corecount__between	optional	Possible number of CPU cores (inclusive). Example: "2-8".
corecount__gt	optional	CPU cores (more than)
corecount__gte	optional	CPU cores (more than or equal)
corecount__lt	optional	CPU cores (less than)
corecount__lte	optional	CPU cores (less than or equal)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cpucount__between	optional	Possible number of CPU cores (inclusive). Example: "2-8".

cpucount__gt	optional	Number of CPUs (more than)
cpucount__gte	optional	Number of CPUs (more than or equal)
cpucount__lt	optional	Number of CPUs (less than)
cpucount__lte	optional	Number of CPUs (less than or equal)
cpuid__contains	optional	Free-text filter by CPU name (supports multiple values). Example: "Intel,AMD".
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdat__gt	optional	Agents created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Agents created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Agents created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Agents created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
csvfilterid	optional	The ID of the CSV file to filter by. Example: "225494730938493804".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
decommissionedat__between	optional	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
decommissionedat__gt	optional	Agents decommissioned after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__gte	optional	Agents decommissioned after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__lt	optional	Agents decommissioned before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__lte	optional	Agents decommissioned before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
domains	optional	Included network domains. Example: "mybusiness.net,workgroup".

domainsnin	optional	Not included network domains. Example: "mybusiness.net,workgroup".
ecsclustername__contains	optional	Free-text filter by ECS cluster name
ecsservicearn__contains	optional	Free-text filter by ECS service arn
ecsservicename__contains	optional	Free-text filter by ECS service name
ecstaskarn__contains	optional	Free-text filter by ECS task arn
ecstaskavailabilityzone__contains	optional	Free-text filter by ECS task availability zone
ecstaskdefinitionarn__contains	optional	Free-text filter by ECS task definition arn
ecstaskdefinitionfamily__contains	optional	Free-text filter by ECS task definition family
ecstaskdefinitionrevision__contains	optional	Free-text filter by ECS task definition revision
ecstype__contains	optional	Free-text filter by ECS type
ecsversion__contains	optional	Free-text filter by ECS version
encryptedapplications	optional	Disk encryption status
entraid__contains	optional	Free-text filter by Entra ID (supports multiple values)
externalid__contains	optional	Free-text filter by external ID (Customer ID). Example: "Tag#1 - monitoring,Performance machine".
externalip__contains	optional	Free-text filter by visible IP (supports multiple values). Example: "205,127.0".
filteredgroupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
filteredsiteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
filterid	optional	Include all Agents matching this saved filter. Example: "225494730938493804".
firewallenabled	optional	The agents supports Firewall Control and it is enabled for the agent's group
gatewayip	optional	Gateway ip. Example: "192.168.0.1".

gcpserviceaccount__contains	optional	Free-text filter by gcp service account (supports multiple values)
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
hascontainerizedworkload	optional	Indicates whether the agent protects containerized workload at the moment
haslocalconfiguration	optional	Agent has a local configuration set
hastags	optional	Include only Agents that have any tags assigned if True, or none if False
ids	optional	Included Agent IDs. Example: "225494730938493804,225494730938493915".
idsnin	optional	Excluded Agent IDs. Example: "225494730938493804,225494730938493915".
infected	optional	Include only Agents with at least one active threat
installertypes	optional	Include only Agents installed with these package types. Example: ".msi".
installertypesnin	optional	Exclude Agents installed with these package types. Example: ".msi".
isactive	optional	Include only active Agents
isadconnector	optional	The agents that are ADConnectors if True, or not if False
isdecommissioned	optional	Include active, decommissioned or both. Example: "True,False".
iseventsearchproxyenabled	optional	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).
ishyperautomate	optional	The agents has Hyper Automate PNA enabled if True, or not if False
ismgmtproxyenabled	optional	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).
ispendinguninstall	optional	Include only Agents with pending uninstall requests
isuninstalled	optional	Include installed, uninstalled or both. Example: "True,False".
isuptodate	optional	Include only Agents with updated software
k8snodelabels__contains	optional	Free-text filter by K8s node labels (supports multiple values)
k8snodename__contains	optional	Free-text filter by K8s node name (supports multiple values)
k8stype__contains	optional	Free-text filter by K8s type(supports multiple values)

k8sversion__contains	optional	Free-text filter by K8s version (supports multiple values)
lastactivatedate__between	optional	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
lastactivatedate__gt	optional	Agents last active after this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__gte	optional	Agents last active after or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__lt	optional	Agents last active before this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__lte	optional	Agents last active before or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastloggedinusername__contains	optional	Free-text filter by username (supports multiple values). Example: "admin,johnd1".
lastsuccessfulscandate__between	optional	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
lastsuccessfulscandate__gt	optional	Agents last successful full disk scan after this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__gte	optional	Agents last successful full disk scan after or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__lt	optional	Agents last successful full disk scan before this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__lte	optional	Agents last successful full disk scan before or at this time. Example: "2018-02-27T04:49:26.257525Z".
limit	optional	Limit number of returned items (1-1000). Example: "10".
liveupdateid__contains	optional	Free-text filter by live update ID (supports multiple values)
locationenabled	optional	The agents supports Location Awareness and it is enabled for the agent's group
locationids	optional	Include only Agents reporting these locations. Example: "225494730938493804,225494730938493915".
locationidsnin	optional	Do not include only Agents reporting these locations. Example: "225494730938493804,225494730938493915".
machinetypes	optional	Included machine types. Example: "laptop,desktop".

machinetypesnin	optional	Not included machine types. Example: "laptop,desktop".
migrationstatus	optional	Migration status. Example: "N/A".
missingpermissions	optional	Included missing permissions. Example: "user_action_needed_bluetooth_per,user_action_needed_fda_helper".
missingpermissionsnin	optional	Excluded missing permissions. Example: "user_action_needed_bluetooth_per,user_action_needed_fda_helper".
mitigationmode	optional	Agent mitigation mode policy. Example: "detect".
mitigationmodesuspicious	optional	Mitigation mode policy for suspicious activity. Example: "detect".
networkinterfacegatewaymacaddress__contains	optional	Free-text filter by Gateway MAC address (supports multiple values). Example: "aa:0f,:41:".
networkinterfaceip__contains	optional	Free-text filter by local IP (supports multiple values). Example: "192,10.0.0".
networkinterfacephysical__contains	optional	Free-text filter by MAC address (supports multiple values). Example: "aa:0f,:41:".
networkquarantineenabled	optional	The agents supports Network Quarantine Control and its enabled for the agent's group
networkstatuses	optional	Included network statuses. Example: "connected,connecting".
networkstatusesnin	optional	Included network statuses. Example: "connected,connecting".
operationalstates	optional	Agent operational state
operationalstatesnin	optional	Do not include these Agent operational states
osarch	optional	OS architecture. Example: "32 bit".
osarches	optional	OS architectures to include. Example: "32 bit,64 bit".
osarchesnin	optional	OS architectures not to include. Example: "32 bit,64 bit".
ostypes	optional	Included OS types. Example: "linux".
ostypesnin	optional	Not included OS types. Example: "linux".
osversion__contains	optional	Free-text filter by OS full name and version (supports multiple values). Example: "Service Pack 1".
pacfileusage	optional	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).

proxymethod	optional	Include only Agents using these proxy methods. Example: "None,Auto,System,User,Custom".
proxymethodnin	optional	Exclude Agents using these proxy methods. Example: "None,Auto,System,User,Custom".
query	optional	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term). Example: "Linux".
rangerstatus	optional	[DEPRECATED] Use rangerStatuses. Example: "NotApplicable".
rangerstatuses	optional	Status of Network Discovery. Example: "NotApplicable".
rangerstatusesnin	optional	Do not include these Network Scanner Statuses. Example: "NotApplicable".
rangerversions	optional	Network Scanner versions to include. Example: "2.0.0.0,2.1.5.144".
rangerversionsnin	optional	Network Scanner versions not to include. Example: "2.0.0.0,2.1.5.144".
registeredat__between	optional	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
registeredat__gt	optional	Agents registered after this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__gte	optional	Agents registered after or at this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__lt	optional	Agents registered before this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__lte	optional	Agents registered before or at this time. Example: "2018-02-27T04:49:26.257525Z".
remoteopsforensicssupported	optional	Include only agents that has Remote Ops Forensicsfeature supported
remoteprofilingsstates	optional	Agent remote profiling state
remoteprofilingsstatesnin	optional	Do not include these Agent remote profiling states
rsolevel	optional	Supported Remote Script Orchestration level. Example: "none".
rsolevels	optional	A list of included rso_levels. Example: "pro,ars".
scanstatus	optional	Scan status. Example: "none".

scanstatuses	optional	Included scan statuses. Example: "started,aborted".
scanstatusesnin	optional	Not included scan statuses. Example: "started,aborted".
serialnumber__contains	optional	Free-text filter by Serial Number (supports multiple values)
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
storagetypes	optional	Included storage types. Example: "NetApp,Dell,S3".
storagetypesnin	optional	Excluded storage types. Example: "NetApp,Dell,S3".
tagsdata	optional	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key. Example: '{"key1": ["value1_1", "value1_2"], "key2__nin": ["value2"]}'.
threatcontenthash	optional	Include only Agents that have at least one threat with this content hash. Example: "cf23df2207d99a74fbe169e3eba035e633b65d94".
threatcreatedat__between	optional	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
threatcreatedat__gt	optional	Agents with threats reported after this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__gte	optional	Agents with threats reported after or at this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__lt	optional	Agents with threats reported before this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__lte	optional	Agents with threats reported before or at this time. Example: "2018-02-27T04:49:26.257525Z".
threathidden	optional	Include only Agents with at least one hidden threat
threatmitigationstatus	optional	Include only Agents that have threats with this mitigation status. Example: "mitigated".
threatrebootrequired	optional	Has at least one threat with at least one mitigation action pending reboot to succeed

threatresolved	optional	Include only Agents with at least one resolved threat
totalmemory__between	optional	Total memory range (GB, inclusive). Example: "4-8".
totalmemory__gt	optional	Memory size (MB, more than)
totalmemory__gte	optional	Memory size (MB, more than or equal)
totalmemory__lt	optional	Memory size (MB, less than)
totalmemory__lte	optional	Memory size (MB, less than or equal)
updatedat__between	optional	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedat__gt	optional	Agents updated after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Agents updated after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Agents updated before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Agents updated before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
useractionsneeded	optional	Included pending user actions. Example: "reboot_needed,upgrade_needed".
useractionsneedednin	optional	Excluded pending user actions. Example: "reboot_needed,upgrade_needed".
uuid	optional	Agent's universally unique identifier. Example: "ff819e70af13be381993075eb0ce5f2f6de05be2".
uuid__contains	optional	Free-text filter by Agent UUID (supports multiple values). Example: "e92-01928,b055".
uuids	optional	A list of included UUIDs. Example: "ff819e70af13be381993075eb0ce5f2f6de05b11,ff819e70af13be381993075eb0ce5f2f6de05c22".
windowsosrevision__gte	optional	Agents os revision than or equal to given version
windowsosrevision__lte	optional	Agents os revision lower than or equal to given version

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Passphrase - response - pagination table
data	Response data	false	see Get Passphrase - response - data table
errors	Errors	false	array

Get Passphrase - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Passphrase - response - data

Name	Description	Required	Value
acknowledgedAt	Acknowledged at	false	string
computerName	Computer name	false	string
createdAt	Created at	false	string
createdByUser	Created by user	false	string
domain	Network domain	false	string
id	Agent ID	false	string
lastLoggedInUserName	Last logged in user name	false	string
passphrase	Generated passphrase for the agent	false	string
previousPassphrases	Previous passphrases	false	see Get Passphrase - response - previousPassphrases table
uuid	Agent's universally unique identifier	false	string

Get Passphrase - response - previousPassphrases

Name	Description	Required	Value
createdAt		false	string
createdByUser		false	string
passphrase	Previous passphrase for the agent	false	string

Export Agent Logs

GET /web/api/v2.1/agents/{agent_id}/uploads/{activity_id}

Get Agent logs from Agents that match the filter. You can filter by Agent ID (run "agents" to get the ID) or by Activity ID (run "activities/types" to get the Activity ID). Send the logs to SentinelOne Support for assistance.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

404 - Agent or activity not found

Applications

GET /web/api/v2.1/agents/applications

Get the installed applications for a specific Agent.
To get the Agent ID, run "agents".

Parameters

ids	required	Agent ID list. Example: "225494730938493804,225494730938493915".
-----	----------	---

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Applications - response - data table
errors	Errors	false	array

Applications - response - data

Name	Description	Required	Value
installedDate	Installed date	false	string
name	Name	false	string
publisher	Publisher	false	string
size	Size	false	integer
version	Version	false	string

Processes

GET /web/api/v2.1/agents/processes

[OBSOLETE] Returns empty array. To get processes of an Agent, see Applications.

Parameters

ids	required	Agent ID list. Example: "225494730938493804,225494730938493915".
-----	----------	---

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Processes - response - data table
errors	Errors	false	array

Processes - response - data

Name	Description	Required	Value
cpuUsage	CPU Usage (%)	false	integer
executablePath	Executable path	false	string
memoryUsage	Memory usage (MB)	false	integer
pid	Process ID	false	integer
processName	Process name	false	string
startTime	Start time	false	string

Get local upgrade/downgrade Agent authorization

GET /web/api/v2.1/agents/{agent_id}/local-upgrade-authorization

Get the time when authorization of local upgrades/downgrades expires

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get local upgrade/downgrade Agent authorization - response - data table
errors	Errors	false	array

Get local upgrade/downgrade Agent authorization - response - data

Name	Description	Required	Value
agentAuthorization	Agent authorization	false	string
siteAuthorization	Site authorization	false	string

Export Agents

GET /web/api/v2.1/export/agents

Export Agent data to a CSV, for Agents that match the filter. This command exports up to 50000 items (each datum is an item).

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
activeprotection	optional	Included agent active protections. Example: "edr,idr".
activethreats	optional	Include Agents with this amount of active threats. Example: "3".
activethreats__gt	optional	Include Agents with at least this amount of active threats. Example: "5".
adcomputermember__contains	optional	Free-text filter by Active Directory computer groups string (supports multiple values). Example: "DC=sentinelone".
adcomputername__contains	optional	Free-text filter by Active Directory computer name string (supports multiple values). Example: "DC=sentinelone".
adcomputerquery__contains	optional	Free-text filter by Active Directory computer name or its groups (supports multiple values). Example: "DC=sentinelone,Windows".
adquery	optional	An Active Directory query string. Example: "CN=Managers,DC=sentinelone,DC=com".
adquery__contains	optional	Free-text filter by Active Directory string (supports multiple values). Example: "DC=sentinelone".
adusermember__contains	optional	Free-text filter by Active Directory user groups string (supports multiple values). Example: "DC=sentinelone".
adusername__contains	optional	Free-text filter by Active Directory username string (supports multiple values). Example: "DC=sentinelone".

aduserquery__contains	optional	Free-text filter by Active Directory computer name or its groups (supports multiple values). Example: "DC=sentinelone,John".
agentnamespace__contains	optional	Free-text filter by agent namespace (supports multiple values)
agentoperatingmode__contains	optional	Free-text filter by Agent Operating Mode (supports multiple values)
agentoperatingmodes	optional	Agent operating mode in. Example: "optimized".
agentoperatingmodesnin	optional	Agent operating mode nin. Example: "optimized".
agentpodname__contains	optional	Free-text filter by agent pod name (supports multiple values)
agentversion__between	optional	Version range for agent version (format: <from_version>-<to_version>, inclusive). Example: "2.0.0.0-2.1.5.144".
agentversion__gt	optional	Agents versions greater than given version. Example: "2.5.1.1320".
agentversion__gte	optional	Agents versions greater than or equal to given version. Example: "2.5.1.1320".
agentversion__lt	optional	Agents versions less than given version. Example: "2.5.1.1320".
agentversion__lte	optional	Agents versions less than or equal to given version. Example: "2.5.1.1320".
agentversions	optional	Agent versions to include. Example: "2.0.0.0,2.1.5.144".
agentversionsnin	optional	Agent versions not to include. Example: "2.0.0.0,2.1.5.144".
appsvulnerabilitystatuses	optional	Apps vulnerability status in. Example: "patch_required".
appsvulnerabilitystatusnin	optional	Apps vulnerability status nin. Example: "patch_required".
awsrole__contains	optional	Free-text filter by aws role(supports multiple values)
awssecuritygroups__contains	optional	Free-text filter by aws securityGroups(supports multiple values)
awssubnetids__contains	optional	Free-text filter by aws subnet ids (supports multiple values)
azureresourcegroup__contains	optional	Free-text filter by azure resource group(supports multiple values)
cloudaccount__contains	optional	Free-text filter by cloud account (supports multiple values)

cloudimage__contains	optional	Free-text filter by cloud image (supports multiple values)
cloudinstanceid__contains	optional	Free-text filter by cloud instance id(supports multiple values)
cloudinstancesize__contains	optional	Free-text filter by cloud instance size(supports multiple values)
cloudlocation__contains	optional	Free-text filter by cloud location (supports multiple values)
cloudnetwork__contains	optional	Free-text filter by cloud network (supports multiple values)
cloudprovider	optional	Agents from which cloud provider
cloudprovidernin	optional	Exclude Agents from these cloud provider
cloudtags__contains	optional	Free-text filter by cloud tags (supports multiple values)
clustername__contains	optional	Free-text filter by cluster name (supports multiple values)
computername	optional	Computer name. Example: "My Office Desktop".
computername__contains	optional	Free-text filter by computer name (supports multiple values). Example: "john-office,WIN".
computername__like	optional	Match computer name partially (substring). Example: "Lab1".
computernameoruuid__contains	optional	Free-text filter by computer name or uuid (supports multiple values)
consolemigrationstatuses	optional	Migration status in. Example: "N/A".
consolemigrationstatusnin	optional	Migration status nin. Example: "N/A".
containerizedworkloadcounts	optional	Containerized workload counts
corecount__between	optional	Possible number of CPU cores (inclusive). Example: "2-8".
corecount__gt	optional	CPU cores (more than)
corecount__gte	optional	CPU cores (more than or equal)
corecount__lt	optional	CPU cores (less than)
corecount__lte	optional	CPU cores (less than or equal)
cpucount__between	optional	Possible number of CPU cores (inclusive). Example: "2-8".
cpucount__gt	optional	Number of CPUs (more than)

cpucount__gte	optional	Number of CPUs (more than or equal)
cpucount__lt	optional	Number of CPUs (less than)
cpucount__lte	optional	Number of CPUs (less than or equal)
cpuid__contains	optional	Free-text filter by CPU name (supports multiple values). Example: "Intel,AMD".
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdat__gt	optional	Agents created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Agents created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Agents created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Agents created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
csvfilterid	optional	The ID of the CSV file to filter by. Example: "225494730938493804".
decommissionedat__between	optional	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
decommissionedat__gt	optional	Agents decommissioned after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__gte	optional	Agents decommissioned after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__lt	optional	Agents decommissioned before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__lte	optional	Agents decommissioned before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
domains	optional	Included network domains. Example: "mybusiness.net,workgroup".
domainsnin	optional	Not included network domains. Example: "mybusiness.net,workgroup".
ecsclustername__contains	optional	Free-text filter by ECS cluster name

ecsservicearn__contains	optional	Free-text filter by ECS service arn
ecsservicename__contains	optional	Free-text filter by ECS service name
ecstaskarn__contains	optional	Free-text filter by ECS task arn
ecstaskavailabilityzone__contains	optional	Free-text filter by ECS task availability zone
ecstaskdefinitionarn__contains	optional	Free-text filter by ECS task definition arn
ecstaskdefinitionfamily__contains	optional	Free-text filter by ECS task definition family
ecstaskdefinitionrevision__contains	optional	Free-text filter by ECS task definition revision
ecstype__contains	optional	Free-text filter by ECS type
ecsversion__contains	optional	Free-text filter by ECS version
encryptedapplications	optional	Disk encryption status
entraid__contains	optional	Free-text filter by Entra ID (supports multiple values)
externalid__contains	optional	Free-text filter by external ID (Customer ID). Example: "Tag#1 - monitoring,Performance machine".
externalip__contains	optional	Free-text filter by visible IP (supports multiple values). Example: "205,127.0".
filteredgroupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
filteredsiteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
filterid	optional	Include all Agents matching this saved filter. Example: "225494730938493804".
firewallenabled	optional	The agents supports Firewall Control and it is enabled for the agent's group
gatewayip	optional	Gateway ip. Example: "192.168.0.1".
gcpserviceaccount__contains	optional	Free-text filter by gcp service account (supports multiple values)
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".

hascontainerizedworkload	optional	Indicates whether the agent protects containerized workload at the moment
haslocalconfiguration	optional	Agent has a local configuration set
hastags	optional	Include only Agents that have any tags assigned if True, or none if False
ids	optional	Included Agent IDs. Example: "225494730938493804,225494730938493915".
idsnin	optional	Excluded Agent IDs. Example: "225494730938493804,225494730938493915".
infected	optional	Include only Agents with at least one active threat
installertypes	optional	Include only Agents installed with these package types. Example: ".msi".
installertypesnin	optional	Exclude Agents installed with these package types. Example: ".msi".
isactive	optional	Include only active Agents
isadconnector	optional	The agents that are ADConnectors if True, or not if False
isdecommissioned	optional	Include active, decommissioned or both. Example: "True,False".
iseventsearchproxyenabled	optional	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).
ishyperautomate	optional	The agents has Hyper Automate PNA enabled if True, or not if False
ismgmtproxyenabled	optional	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).
ispendinguninstall	optional	Include only Agents with pending uninstall requests
isuninstalled	optional	Include installed, uninstalled or both. Example: "True,False".
isuptodate	optional	Include only Agents with updated software
k8snodelabels__contains	optional	Free-text filter by K8s node labels (supports multiple values)
k8snodename__contains	optional	Free-text filter by K8s node name (supports multiple values)
k8stype__contains	optional	Free-text filter by K8s type(supports multiple values)
k8sversion__contains	optional	Free-text filter by K8s version (supports multiple values)
lastactivatedate__between	optional	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".

lastactivatedate__gt	optional	Agents last active after this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__gte	optional	Agents last active after or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__lt	optional	Agents last active before this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__lte	optional	Agents last active before or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastloggedinusername__contains	optional	Free-text filter by username (supports multiple values). Example: "admin,johnd1".
lastsuccessfulscandate__between	optional	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
lastsuccessfulscandate__gt	optional	Agents last successful full disk scan after this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__gte	optional	Agents last successful full disk scan after or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__lt	optional	Agents last successful full disk scan before this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__lte	optional	Agents last successful full disk scan before or at this time. Example: "2018-02-27T04:49:26.257525Z".
liveupdateid__contains	optional	Free-text filter by live update ID (supports multiple values)
locationenabled	optional	The agents supports Location Awareness and it is enabled for the agent's group
locationids	optional	Include only Agents reporting these locations. Example: "225494730938493804,225494730938493915".
locationidsnin	optional	Do not include only Agents reporting these locations. Example: "225494730938493804,225494730938493915".
machinetypes	optional	Included machine types. Example: "laptop,desktop".
machinetypesnin	optional	Not included machine types. Example: "laptop,desktop".
migrationstatus	optional	Migration status. Example: "N/A".
missingpermissions	optional	Included missing permissions. Example: "user_action_needed_bluetooth_per,user_action_needed_fda_helper".

missingpermissionsnin	optional	Excluded missing permissions. Example: "user_action_needed_bluetooth_per,user_action_needed_fda_helper".
mitigationmode	optional	Agent mitigation mode policy. Example: "detect".
mitigationmodesuspicious	optional	Mitigation mode policy for suspicious activity. Example: "detect".
networkinterfacegatewaymacaddress__contains	optional	Free-text filter by Gateway MAC address (supports multiple values). Example: "aa:0f;41:".
networkinterfaceinet__contains	optional	Free-text filter by local IP (supports multiple values). Example: "192,10.0.0".
networkinterfacephysical__contains	optional	Free-text filter by MAC address (supports multiple values). Example: "aa:0f;41:".
networkquarantineenabled	optional	The agents supports Network Quarantine Control and its enabled for the agent's group
networkstatuses	optional	Included network statuses. Example: "connected,connecting".
networkstatusesnin	optional	Included network statuses. Example: "connected,connecting".
operationalstates	optional	Agent operational state
operationalstatesnin	optional	Do not include these Agent operational states
osarch	optional	OS architecture. Example: "32 bit".
osarches	optional	OS architectures to include. Example: "32 bit,64 bit".
osarchesnin	optional	OS architectures not to include. Example: "32 bit,64 bit".
ostypes	optional	Included OS types. Example: "linux".
ostypesnin	optional	Not included OS types. Example: "linux".
osversion__contains	optional	Free-text filter by OS full name and version (supports multiple values). Example: "Service Pack 1".
pacfileusage	optional	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).
proxymethod	optional	Include only Agents using these proxy methods. Example: "None,Auto,System,User,Custom".
proxymethodnin	optional	Exclude Agents using these proxy methods. Example: "None,Auto,System,User,Custom".
query	optional	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they

		start with the search term only (no match if they contain the term). Example: "Linux".
rangerstatus	optional	[DEPRECATED] Use rangerStatuses. Example: "NotApplicable".
rangerstatuses	optional	Status of Network Discovery. Example: "NotApplicable".
rangerstatusesnin	optional	Do not include these Network Scanner Statuses. Example: "NotApplicable".
rangerversions	optional	Network Scanner versions to include. Example: "2.0.0.0,2.1.5.144".
rangerversionsnin	optional	Network Scanner versions not to include. Example: "2.0.0.0,2.1.5.144".
registeredat__between	optional	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
registeredat__gt	optional	Agents registered after this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__gte	optional	Agents registered after or at this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__lt	optional	Agents registered before this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__lte	optional	Agents registered before or at this time. Example: "2018-02-27T04:49:26.257525Z".
remoteopsforensicsupported	optional	Include only agents that has Remote Ops Forensicsfeature supported
remoteprofilingsstates	optional	Agent remote profiling state
remoteprofilingsstatesnin	optional	Do not include these Agent remote profiling states
rsolevel	optional	Supported Remote Script Orchestration level. Example: "none".
rsolevels	optional	A list of included rso_levels. Example: "pro,ars".
scanstatus	optional	Scan status. Example: "none".
scanstatuses	optional	Included scan statuses. Example: "started,aborted".
scanstatusesnin	optional	Not included scan statuses. Example: "started,aborted".
serialnumber__contains	optional	Free-text filter by Serial Number (supports multiple values)
siteids	optional	List of Site IDs to filter by. Example:

		"225494730938493804,225494730938493915".
storagetypes	optional	Included storage types. Example: "NetApp,Dell,S3".
storagetypesnin	optional	Excluded storage types. Example: "NetApp,Dell,S3".
tagsdata	optional	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key. Example: '{"key1": ["value1_1", "value1_2"], "key2__nin": ["value2"]}'.
threatcontenthash	optional	Include only Agents that have at least one threat with this content hash. Example: "cf23df2207d99a74fbe169e3eba035e633b65d94".
threatcreatedat__between	optional	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
threatcreatedat__gt	optional	Agents with threats reported after this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__gte	optional	Agents with threats reported after or at this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__lt	optional	Agents with threats reported before this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__lte	optional	Agents with threats reported before or at this time. Example: "2018-02-27T04:49:26.257525Z".
threathidden	optional	Include only Agents with at least one hidden threat
threatmitigationstatus	optional	Include only Agents that have threats with this mitigation status. Example: "mitigated".
threatrebootrequired	optional	Has at least one threat with at least one mitigation action pending reboot to succeed
threatresolved	optional	Include only Agents with at least one resolved threat
totalmemory__between	optional	Total memory range (GB, inclusive). Example: "4-8".
totalmemory__gt	optional	Memory size (MB, more than)
totalmemory__gte	optional	Memory size (MB, more than or equal)
totalmemory__lt	optional	Memory size (MB, less than)
totalmemory__lte	optional	Memory size (MB, less than or equal)
updatedat__between	optional	Date range for update time (format: <from_timestamp>-

		<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedat__gt	optional	Agents updated after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Agents updated after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Agents updated before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Agents updated before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
useractionsneeded	optional	Included pending user actions. Example: "reboot_needed,upgrade_needed".
useractionsneedednin	optional	Excluded pending user actions. Example: "reboot_needed,upgrade_needed".
uuid	optional	Agent's universally unique identifier. Example: "ff819e70af13be381993075eb0ce5f2f6de05be2".
uuid__contains	optional	Free-text filter by Agent UUID (supports multiple values). Example: "e92-01928,b055".
uuids	optional	A list of included UUIDs. Example: "ff819e70af13be381993075eb0ce5f2f6de05b11,ff819e70af13be381993075eb0ce5f2f6de05c22".
windowsosrevision__gte	optional	Agents os revision than or equal to given version
windowsosrevision__lte	optional	Agents os revision lower than or equal to given version

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Enable Agent PNA for Hyperautomation

POST /web/api/v2.1/agents/enable-hyper-automation-pna

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

404 - Agent not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Enable Agent PNA for Hyperautomation - response - data table
errors	Errors	false	array

Enable Agent PNA for Hyperautomation - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Enable Agent PNA for Hyperautomation - body - filter table
data	Data	false	see Enable Agent PNA for Hyperautomation - body - data table

Enable Agent PNA for Hyperautomation - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Enable Agent PNA for Hyperautomation - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Enable Agent PNA for Hyperautomation - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Enable Agent PNA for Hyperautomation - body - data

Disable PNA for Hyperautomation

POST /web/api/v2.1/agents/disable-hyper-automation-pna

Disable Agent PNA for Hyperautomation

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Disable PNA for Hyperautomation - response - data table
errors	Errors	false	array

Disable PNA for Hyperautomation - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Applied filter - only matched Agents will be affected by the requested action. Leave empty to apply the action on all applicable Agents.	true	see Disable PNA for Hyperautomation - body - filter table
data	Data	false	see Disable PNA for Hyperautomation - body - data table

Disable PNA for Hyperautomation - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Disable PNA for Hyperautomation - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer

totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Disable PNA for Hyperautomation - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Disable PNA for Hyperautomation - body - data

Export Agents - Passphrases

GET /web/api/v2.1/export/agents-passphrases

Export Agent passphrases to a CSV, for Agents that match the filter. This command exports up to 2000 items (each datum is an item).

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
activeprotection	optional	Included agent active protections. Example: "edr,idr".
activethreats	optional	Include Agents with this amount of active threats. Example: "3".
activethreats__gt	optional	Include Agents with at least this amount of active threats. Example: "5".
adcomputermember__contains	optional	Free-text filter by Active Directory computer groups string (supports multiple values). Example: "DC=sentinelone".
adcomputername__contains	optional	Free-text filter by Active Directory computer name string (supports multiple values). Example: "DC=sentinelone".
adcomputerquery__contains	optional	Free-text filter by Active Directory computer name or its groups (supports multiple values). Example: "DC=sentinelone,Windows".
adquery	optional	An Active Directory query string. Example: "CN=Managers,DC=sentinelone,DC=com".
adquery__contains	optional	Free-text filter by Active Directory string (supports multiple values). Example: "DC=sentinelone".
adusermember__contains	optional	Free-text filter by Active Directory user groups string (supports multiple values). Example: "DC=sentinelone".
adusername__contains	optional	Free-text filter by Active Directory username string (supports multiple values). Example: "DC=sentinelone".
aduserquery__contains	optional	Free-text filter by Active Directory computer name or its groups (supports multiple values). Example: "DC=sentinelone,John".
agentnamespace__contains	optional	Free-text filter by agent namespace (supports multiple values)
agentoperatingmode__	optional	Free-text filter by Agent Operating Mode (supports multiple values)

contains		
agentoperatingmodes	optional	Agent operating mode in. Example: "optimized".
agentoperatingmodesnin	optional	Agent operating mode nin. Example: "optimized".
agentpodname__contains	optional	Free-text filter by agent pod name (supports multiple values)
agentversion__between	optional	Version range for agent version (format: <from_version>-<to_version>, inclusive). Example: "2.0.0.0-2.1.5.144".
agentversion__gt	optional	Agents versions greater than given version. Example: "2.5.1.1320".
agentversion__gte	optional	Agents versions greater than or equal to given version. Example: "2.5.1.1320".
agentversion__lt	optional	Agents versions less than given version. Example: "2.5.1.1320".
agentversion__lte	optional	Agents versions less than or equal to given version. Example: "2.5.1.1320".
agentversions	optional	Agent versions to include. Example: "2.0.0.0,2.1.5.144".
agentversionsnin	optional	Agent versions not to include. Example: "2.0.0.0,2.1.5.144".
appsvulnerabilitystatuses	optional	Apps vulnerability status in. Example: "patch_required".
appsvulnerabilitystatusnin	optional	Apps vulnerability status nin. Example: "patch_required".
awsrole__contains	optional	Free-text filter by aws role(supports multiple values)
awssecuritygroups__contains	optional	Free-text filter by aws securityGroups(supports multiple values)
awssubnetids__contains	optional	Free-text filter by aws subnet ids (supports multiple values)
azureresourcegroup__contains	optional	Free-text filter by azure resource group(supports multiple values)
cloudaccount__contains	optional	Free-text filter by cloud account (supports multiple values)
cloudimage__contains	optional	Free-text filter by cloud image (supports multiple values)
cloudinstanceid__contains	optional	Free-text filter by cloud instance id(supports multiple values)
cloudinstancesize__contains	optional	Free-text filter by cloud instance size(supports multiple values)

contains		
cloudlocation__contains	optional	Free-text filter by cloud location (supports multiple values)
cloudnetwork__contains	optional	Free-text filter by cloud network (supports multiple values)
cloudprovider	optional	Agents from which cloud provider
cloudprovidernin	optional	Exclude Agents from these cloud provider
cloudtags__contains	optional	Free-text filter by cloud tags (supports multiple values)
clustername__contains	optional	Free-text filter by cluster name (supports multiple values)
computername	optional	Computer name. Example: "My Office Desktop".
computername__contains	optional	Free-text filter by computer name (supports multiple values). Example: "john-office,WIN".
computername__like	optional	Match computer name partially (substring). Example: "Lab1".
computernameoruuid__contains	optional	Free-text filter by computer name or uuid (supports multiple values)
consolemigrationstatus	optional	Migration status in. Example: "N/A".
consolemigrationstatusnin	optional	Migration status nin. Example: "N/A".
containerizedworkloadcounts	optional	Containerized workload counts
corecount__between	optional	Possible number of CPU cores (inclusive). Example: "2-8".
corecount__gt	optional	CPU cores (more than)
corecount__gte	optional	CPU cores (more than or equal)
corecount__lt	optional	CPU cores (less than)
corecount__lte	optional	CPU cores (less than or equal)
cpucount__between	optional	Possible number of CPU cores (inclusive). Example: "2-8".
cpucount__gt	optional	Number of CPUs (more than)
cpucount__gte	optional	Number of CPUs (more than or equal)
cpucount__lt	optional	Number of CPUs (less than)
cpucount__lte	optional	Number of CPUs (less than or equal)
cpuid__contains	optional	Free-text filter by CPU name (supports multiple values). Example:

		"Intel,AMD".
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdat__gt	optional	Agents created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Agents created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Agents created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Agents created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
csvfilterid	optional	The ID of the CSV file to filter by. Example: "225494730938493804".
decommissionedat__between	optional	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
decommissionedat__gt	optional	Agents decommissioned after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__gte	optional	Agents decommissioned after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__lt	optional	Agents decommissioned before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__lte	optional	Agents decommissioned before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
domains	optional	Included network domains. Example: "mybusiness.net,workgroup".
domainsnin	optional	Not included network domains. Example: "mybusiness.net,workgroup".
ecsclustername__contains	optional	Free-text filter by ECS cluster name
ecsservicearn__contains	optional	Free-text filter by ECS service arn
ecsservicename__contains	optional	Free-text filter by ECS service name
ecstaskarn__contains	optional	Free-text filter by ECS task arn

ecstaskavailabilityzone__contains	optional	Free-text filter by ECS task availability zone
ecstaskdefinitionarn__contains	optional	Free-text filter by ECS task definition arn
ecstaskdefinitionfamily__contains	optional	Free-text filter by ECS task definition family
ecstaskdefinitionrevision__contains	optional	Free-text filter by ECS task definition revision
ecstype__contains	optional	Free-text filter by ECS type
ecsversion__contains	optional	Free-text filter by ECS version
encryptedapplications	optional	Disk encryption status
entraid__contains	optional	Free-text filter by Entra ID (supports multiple values)
externalid__contains	optional	Free-text filter by external ID (Customer ID). Example: "Tag#1 - monitoring,Performance machine".
externalip__contains	optional	Free-text filter by visible IP (supports multiple values). Example: "205,127.0".
filteredgroupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
filtersiteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
filterid	optional	Include all Agents matching this saved filter. Example: "225494730938493804".
firewallenabled	optional	The agents supports Firewall Control and it is enabled for the agent's group
gatewayip	optional	Gateway ip. Example: "192.168.0.1".
gcpserviceaccount__contains	optional	Free-text filter by gcp service account (supports multiple values)
groupids	optional	List of network groups. Example: "225494730938493804,225494730938493915".
hascontainerizedworkload	optional	Indicates whether the agent protects containerized workload at the moment
haslocalconfiguration	optional	Agent has a local configuration set
hastags	optional	Include only Agents that have any tags assigned if True, or none if False

ids	optional	Included Agent IDs. Example: "225494730938493804,225494730938493915".
idsnin	optional	Excluded Agent IDs. Example: "225494730938493804,225494730938493915".
infected	optional	Include only Agents with at least one active threat
installertypes	optional	Include only Agents installed with these package types. Example: ".msi".
installertypesnin	optional	Exclude Agents installed with these package types. Example: ".msi".
isactive	optional	Include only active Agents
isadconnector	optional	The agents that are ADConnectors if True, or not if False
isdecommissioned	optional	Include active, decommissioned or both. Example: "True,False".
iseventsearchproxyenabled	optional	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).
ishyperautomate	optional	The agents has Hyper Automate PNA enabled if True, or not if False
ismgmtproxyenabled	optional	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).
ispendinguninstall	optional	Include only Agents with pending uninstall requests
isuninstalled	optional	Include installed, uninstalled or both. Example: "True,False".
isuptodate	optional	Include only Agents with updated software
k8snodelabels__contains	optional	Free-text filter by K8s node labels (supports multiple values)
k8snodename__contains	optional	Free-text filter by K8s node name (supports multiple values)
k8stype__contains	optional	Free-text filter by K8s type(supports multiple values)
k8sversion__contains	optional	Free-text filter by K8s version (supports multiple values)
lastactivatedate__between	optional	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
lastactivatedate__gt	optional	Agents last active after this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__gte	optional	Agents last active after or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__lt	optional	Agents last active before this time. Example:

		"2018-02-27T04:49:26.257525Z".
lastactivedate__lte	optional	Agents last active before or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastloggedinusername__contains	optional	Free-text filter by username (supports multiple values). Example: "admin,johnd1".
lastsuccessfulscandate__between	optional	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
lastsuccessfulscandate__gt	optional	Agents last successful full disk scan after this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__gte	optional	Agents last successful full disk scan after or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__lt	optional	Agents last successful full disk scan before this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__lte	optional	Agents last successful full disk scan before or at this time. Example: "2018-02-27T04:49:26.257525Z".
liveupdateid__contains	optional	Free-text filter by live update ID (supports multiple values)
locationenabled	optional	The agents supports Location Awareness and it is enabled for the agent's group
locationids	optional	Include only Agents reporting these locations. Example: "225494730938493804,225494730938493915".
locationidsnin	optional	Do not include only Agents reporting these locations. Example: "225494730938493804,225494730938493915".
machinetypes	optional	Included machine types. Example: "laptop,desktop".
machinetypesnin	optional	Not included machine types. Example: "laptop,desktop".
migrationstatus	optional	Migration status. Example: "N/A".
missingpermissions	optional	Included missing permissions. Example: "user_action_needed_bluetooth_per,user_action_needed_fda_helper".
missingpermissionsnin	optional	Excluded missing permissions. Example: "user_action_needed_bluetooth_per,user_action_needed_fda_helper".
mitigationmode	optional	Agent mitigation mode policy. Example: "detect".
mitigationmodesuspici	optional	Mitigation mode policy for suspicious activity. Example: "detect".

ous		
networkinterfacegatewaymacaddress__contains	optional	Free-text filter by Gateway MAC address (supports multiple values). Example: "aa:0f,:41:".
networkinterfaceinet__contains	optional	Free-text filter by local IP (supports multiple values). Example: "192,10.0.0".
networkinterfacephysical__contains	optional	Free-text filter by MAC address (supports multiple values). Example: "aa:0f,:41:".
networkquarantineenabled	optional	The agents supports Network Quarantine Control and its enabled for the agent's group
networkstatuses	optional	Included network statuses. Example: "connected,connecting".
networkstatusesnin	optional	Included network statuses. Example: "connected,connecting".
operationalstates	optional	Agent operational state
operationalstatesnin	optional	Do not include these Agent operational states
osarch	optional	OS architecture. Example: "32 bit".
osarches	optional	OS architectures to include. Example: "32 bit,64 bit".
osarchesnin	optional	OS architectures not to include. Example: "32 bit,64 bit".
ostypes	optional	Included OS types. Example: "linux".
ostypesnin	optional	Not included OS types. Example: "linux".
osversion__contains	optional	Free-text filter by OS full name and version (supports multiple values). Example: "Service Pack 1".
pacfileusage	optional	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).
proxymethod	optional	Include only Agents using these proxy methods. Example: "None,Auto,System,User,Custom".
proxymethodnin	optional	Exclude Agents using these proxy methods. Example: "None,Auto,System,User,Custom".
query	optional	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term). Example: "Linux".
rangerstatus	optional	[DEPRECATED] Use rangerStatuses. Example: "NotApplicable".
rangerstatuses	optional	Status of Network Discovery. Example: "NotApplicable".

rangerstatusesnin	optional	Do not include these Network Scanner Statuses. Example: "NotApplicable".
rangerversions	optional	Network Scanner versions to include. Example: "2.0.0.0,2.1.5.144".
rangerversionsnin	optional	Network Scanner versions not to include. Example: "2.0.0.0,2.1.5.144".
registeredat__between	optional	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
registeredat__gt	optional	Agents registered after this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__gte	optional	Agents registered after or at this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__lt	optional	Agents registered before this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__lte	optional	Agents registered before or at this time. Example: "2018-02-27T04:49:26.257525Z".
remoteopsforensicssupported	optional	Include only agents that has Remote Ops Forensicsfeature supported
remoteprofilingsstates	optional	Agent remote profiling state
remoteprofilingsstatesnin	optional	Do not include these Agent remote profiling states
rsolevel	optional	Supported Remote Script Orchestration level. Example: "none".
rsolevels	optional	A list of included rso_levels. Example: "pro,ars".
scanstatus	optional	Scan status. Example: "none".
scanstatuses	optional	Included scan statuses. Example: "started,aborted".
scanstatusesnin	optional	Not included scan statuses. Example: "started,aborted".
serialnumber__contains	optional	Free-text filter by Serial Number (supports multiple values)
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
storagetypes	optional	Included storage types. Example: "NetApp,Dell,S3".
storagetypesnin	optional	Excluded storage types. Example: "NetApp,Dell,S3".
tagsdata	optional	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of

		string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key. Example: '{"key1": ["value1_1", "value1_2"], "key2__nin": ["value2"]}'.
threatcontenthash	optional	Include only Agents that have at least one threat with this content hash. Example: "cf23df2207d99a74fbe169e3eba035e633b65d94".
threatcreatedat__between	optional	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
threatcreatedat__gt	optional	Agents with threats reported after this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__gte	optional	Agents with threats reported after or at this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__lt	optional	Agents with threats reported before this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__lte	optional	Agents with threats reported before or at this time. Example: "2018-02-27T04:49:26.257525Z".
threathidden	optional	Include only Agents with at least one hidden threat
threatmitigationstatus	optional	Include only Agents that have threats with this mitigation status. Example: "mitigated".
threatrebootrequired	optional	Has at least one threat with at least one mitigation action pending reboot to succeed
threatresolved	optional	Include only Agents with at least one resolved threat
totalmemory__between	optional	Total memory range (GB, inclusive). Example: "4-8".
totalmemory__gt	optional	Memory size (MB, more than)
totalmemory__gte	optional	Memory size (MB, more than or equal)
totalmemory__lt	optional	Memory size (MB, less than)
totalmemory__lte	optional	Memory size (MB, less than or equal)
updatedat__between	optional	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedat__gt	optional	Agents updated after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Agents updated after or at this timestamp. Example:

		"2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Agents updated before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Agents updated before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
useractionsneeded	optional	Included pending user actions. Example: "reboot_needed,upgrade_needed".
useractionsneedednin	optional	Excluded pending user actions. Example: "reboot_needed,upgrade_needed".
uuid	optional	Agent's universally unique identifier. Example: "ff819e70af13be381993075eb0ce5f2f6de05be2".
uuid__contains	optional	Free-text filter by Agent UUID (supports multiple values). Example: "e92-01928,b055".
uuids	optional	A list of included UUIDs. Example: "ff819e70af13be381993075eb0ce5f2f6de05b11,ff819e70af13be381993075eb0ce5f2f6de05c22".
windowsosrevision__gte	optional	Agents os revision than or equal to given version
windowsosrevision__lte	optional	Agents os revision lower than or equal to given version

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Export Agents - Light

GET /web/api/v2.1/export/agents-light

Export Agent data to a CSV, for Agents that match the filter. This command exports up to 300000 items (each datum is an item).

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
activeprotection	optional	Included agent active protections. Example: "edr,idr".
activethreats	optional	Include Agents with this amount of active threats. Example: "3".
activethreats__gt	optional	Include Agents with at least this amount of active threats. Example: "5".
adcomputermember__contains	optional	Free-text filter by Active Directory computer groups string (supports multiple values). Example: "DC=sentinelone".
adcomputername__contains	optional	Free-text filter by Active Directory computer name string (supports multiple values). Example: "DC=sentinelone".
adcomputerquery__contains	optional	Free-text filter by Active Directory computer name or its groups (supports multiple values). Example: "DC=sentinelone,Windows".
adquery	optional	An Active Directory query string. Example: "CN=Managers,DC=sentinelone,DC=com".
adquery__contains	optional	Free-text filter by Active Directory string (supports multiple values). Example: "DC=sentinelone".
adusermember__contains	optional	Free-text filter by Active Directory user groups string (supports multiple values). Example: "DC=sentinelone".
adusername__contains	optional	Free-text filter by Active Directory username string (supports multiple values). Example: "DC=sentinelone".
aduserquery__contains	optional	Free-text filter by Active Directory computer name or its groups (supports multiple values). Example: "DC=sentinelone,John".
agentnamespace__contains	optional	Free-text filter by agent namespace (supports multiple values)
agentoperatingmode__contains	optional	Free-text filter by Agent Operating Mode (supports multiple values)
agentoperatingmodes	optional	Agent operating mode in. Example: "optimized".
agentoperatingmodesnin	optional	Agent operating mode nin. Example: "optimized".
agentpodname__contains	optional	Free-text filter by agent pod name (supports multiple values)
agentversion__between	optional	Version range for agent version (format: <from_version>-<to_version>, inclusive). Example: "2.0.0.0-2.1.5.144".

agentversion__gt	optional	Agents versions greater than given version. Example: "2.5.1.1320".
agentversion__gte	optional	Agents versions greater than or equal to given version. Example: "2.5.1.1320".
agentversion__lt	optional	Agents versions less than given version. Example: "2.5.1.1320".
agentversion__lte	optional	Agents versions less than or equal to given version. Example: "2.5.1.1320".
agentversions	optional	Agent versions to include. Example: "2.0.0.0,2.1.5.144".
agentversionsnin	optional	Agent versions not to include. Example: "2.0.0.0,2.1.5.144".
appsvulnerabilitystatus	optional	Apps vulnerability status in. Example: "patch_required".
appsvulnerabilitystatusnin	optional	Apps vulnerability status nin. Example: "patch_required".
awsrole__contains	optional	Free-text filter by aws role(supports multiple values)
awssecuritygroups__contains	optional	Free-text filter by aws securityGroups(supports multiple values)
awssubnetids__contains	optional	Free-text filter by aws subnet ids (supports multiple values)
azureresourcegroup__contains	optional	Free-text filter by azure resource group(supports multiple values)
cloudaccount__contains	optional	Free-text filter by cloud account (supports multiple values)
cloudimage__contains	optional	Free-text filter by cloud image (supports multiple values)
cloudinstanceid__contains	optional	Free-text filter by cloud instance id(supports multiple values)
cloudinstancesize__contains	optional	Free-text filter by cloud instance size(supports multiple values)
cloudlocation__contains	optional	Free-text filter by cloud location (supports multiple values)
cloudnetwork__contains	optional	Free-text filter by cloud network (supports multiple values)
cloudprovider	optional	Agents from which cloud provider
cloudprovidernin	optional	Exclude Agents from these cloud provider
cloudtags__contains	optional	Free-text filter by cloud tags (supports multiple values)

clustername__contains	optional	Free-text filter by cluster name (supports multiple values)
computername	optional	Computer name. Example: "My Office Desktop".
computername__contains	optional	Free-text filter by computer name (supports multiple values). Example: "john-office,WIN".
computername__like	optional	Match computer name partially (substring). Example: "Lab1".
computernameoruuid__contains	optional	Free-text filter by computer name or uuid (supports multiple values)
consolemigrationstatuses	optional	Migration status in. Example: "N/A".
consolemigrationstatusnin	optional	Migration status nin. Example: "N/A".
containerizedworkloadcounts	optional	Containerized workload counts
corecount__between	optional	Possible number of CPU cores (inclusive). Example: "2-8".
corecount__gt	optional	CPU cores (more than)
corecount__gte	optional	CPU cores (more than or equal)
corecount__lt	optional	CPU cores (less than)
corecount__lte	optional	CPU cores (less than or equal)
cpucount__between	optional	Possible number of CPU cores (inclusive). Example: "2-8".
cpucount__gt	optional	Number of CPUs (more than)
cpucount__gte	optional	Number of CPUs (more than or equal)
cpucount__lt	optional	Number of CPUs (less than)
cpucount__lte	optional	Number of CPUs (less than or equal)
cpuid__contains	optional	Free-text filter by CPU name (supports multiple values). Example: "Intel,AMD".
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdat__gt	optional	Agents created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Agents created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Agents created before this timestamp. Example:

		"2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Agents created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
csvfilterid	optional	The ID of the CSV file to filter by. Example: "225494730938493804".
decommissionedat__between	optional	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
decommissionedat__gt	optional	Agents decommissioned after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__gte	optional	Agents decommissioned after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__lt	optional	Agents decommissioned before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
decommissionedat__lte	optional	Agents decommissioned before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
domains	optional	Included network domains. Example: "mybusiness.net,workgroup".
domainsnin	optional	Not included network domains. Example: "mybusiness.net,workgroup".
ecsclustername__contains	optional	Free-text filter by ECS cluster name
ecsservicearn__contains	optional	Free-text filter by ECS service arn
ecsservicename__contains	optional	Free-text filter by ECS service name
ecstaskarn__contains	optional	Free-text filter by ECS task arn
ecstaskavailabilityzone__contains	optional	Free-text filter by ECS task availability zone
ecstaskdefinitionarn__contains	optional	Free-text filter by ECS task definition arn
ecstaskdefinitionfamily__contains	optional	Free-text filter by ECS task definition family
ecstaskdefinitionrevision__contains	optional	Free-text filter by ECS task definition revision

ecstype__contains	optional	Free-text filter by ECS type
ecsversion__contains	optional	Free-text filter by ECS version
encryptedapplications	optional	Disk encryption status
entraid__contains	optional	Free-text filter by Entra ID (supports multiple values)
externalid__contains	optional	Free-text filter by external ID (Customer ID). Example: "Tag#1 - monitoring,Performance machine".
externalip__contains	optional	Free-text filter by visible IP (supports multiple values). Example: "205,127.0".
filteredgroupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
filteredsiteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
filterid	optional	Include all Agents matching this saved filter. Example: "225494730938493804".
firewallenabled	optional	The agents supports Firewall Control and it is enabled for the agent's group
gatewayip	optional	Gateway ip. Example: "192.168.0.1".
gcpserviceaccount__contains	optional	Free-text filter by gcp service account (supports multiple values)
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
hascontainerizedworkload	optional	Indicates whether the agent protects containerized workload at the moment
haslocalconfiguration	optional	Agent has a local configuration set
hastags	optional	Include only Agents that have any tags assigned if True, or none if False
ids	optional	Included Agent IDs. Example: "225494730938493804,225494730938493915".
idsnin	optional	Excluded Agent IDs. Example: "225494730938493804,225494730938493915".
infected	optional	Include only Agents with at least one active threat
installertypes	optional	Include only Agents installed with these package types. Example: ".msi".
installertypesnin	optional	Exclude Agents installed with these package types. Example: ".msi".

isactive	optional	Include only active Agents
isadconnector	optional	The agents that are ADConnectors if True, or not if False
isdecommissioned	optional	Include active, decommissioned or both. Example: "True,False".
iseventsearchproxyenabled	optional	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).
ishyperautomate	optional	The agents has Hyper Automate PNA enabled if True, or not if False
ismgmtproxyenabled	optional	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).
ispendinguninstall	optional	Include only Agents with pending uninstall requests
isuninstalled	optional	Include installed, uninstalled or both. Example: "True,False".
isuptodate	optional	Include only Agents with updated software
k8snodelabels__contains	optional	Free-text filter by K8s node labels (supports multiple values)
k8snodename__contains	optional	Free-text filter by K8s node name (supports multiple values)
k8stype__contains	optional	Free-text filter by K8s type(supports multiple values)
k8sversion__contains	optional	Free-text filter by K8s version (supports multiple values)
lastactivatedate__between	optional	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
lastactivatedate__gt	optional	Agents last active after this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__gte	optional	Agents last active after or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__lt	optional	Agents last active before this time. Example: "2018-02-27T04:49:26.257525Z".
lastactivatedate__lte	optional	Agents last active before or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastloggedinusername__contains	optional	Free-text filter by username (supports multiple values). Example: "admin,johnd1".
lastsuccessfulscandate__between	optional	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
lastsuccessfulscandate	optional	Agents last successful full disk scan after this time. Example:

__gt		"2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__gte	optional	Agents last successful full disk scan after or at this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__lt	optional	Agents last successful full disk scan before this time. Example: "2018-02-27T04:49:26.257525Z".
lastsuccessfulscandate__lte	optional	Agents last successful full disk scan before or at this time. Example: "2018-02-27T04:49:26.257525Z".
liveupdateid__contains	optional	Free-text filter by live update ID (supports multiple values)
locationenabled	optional	The agents supports Location Awareness and it is enabled for the agent's group
locationids	optional	Include only Agents reporting these locations. Example: "225494730938493804,225494730938493915".
locationidsnin	optional	Do not include only Agents reporting these locations. Example: "225494730938493804,225494730938493915".
machinetypes	optional	Included machine types. Example: "laptop,desktop".
machinetypesnin	optional	Not included machine types. Example: "laptop,desktop".
migrationstatus	optional	Migration status. Example: "N/A".
missingpermissions	optional	Included missing permissions. Example: "user_action_needed_bluetooth_per,user_action_needed_fda_helper".
missingpermissionsnin	optional	Excluded missing permissions. Example: "user_action_needed_bluetooth_per,user_action_needed_fda_helper".
mitigationmode	optional	Agent mitigation mode policy. Example: "detect".
mitigationmodesuspicious	optional	Mitigation mode policy for suspicious activity. Example: "detect".
networkinterfacegatewaymacaddress__contains	optional	Free-text filter by Gateway MAC address (supports multiple values). Example: "aa:0f,:41:".
networkinterfaceinet__contains	optional	Free-text filter by local IP (supports multiple values). Example: "192,10.0.0".
networkinterfacephysical__contains	optional	Free-text filter by MAC address (supports multiple values). Example: "aa:0f,:41:".
networkquarantineena	optional	The agents supports Network Quarantine Control and its enabled

bled		for the agent's group
networkstatuses	optional	Included network statuses. Example: "connected,connecting".
networkstatusesnin	optional	Included network statuses. Example: "connected,connecting".
operationalstates	optional	Agent operational state
operationalstatesnin	optional	Do not include these Agent operational states
osarch	optional	OS architecture. Example: "32 bit".
osarches	optional	OS architectures to include. Example: "32 bit,64 bit".
osarchesnin	optional	OS architectures not to include. Example: "32 bit,64 bit".
ostypes	optional	Included OS types. Example: "linux".
ostypesnin	optional	Not included OS types. Example: "linux".
osversion__contains	optional	Free-text filter by OS full name and version (supports multiple values). Example: "Service Pack 1".
pacfileusage	optional	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).
proxymethod	optional	Include only Agents using these proxy methods. Example: "None,Auto,System,User,Custom".
proxymethodnin	optional	Exclude Agents using these proxy methods. Example: "None,Auto,System,User,Custom".
query	optional	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term). Example: "Linux".
rangerstatus	optional	[DEPRECATED] Use rangerStatuses. Example: "NotApplicable".
rangerstatuses	optional	Status of Network Discovery. Example: "NotApplicable".
rangerstatusesnin	optional	Do not include these Network Scanner Statuses. Example: "NotApplicable".
rangerversions	optional	Network Scanner versions to include. Example: "2.0.0.0,2.1.5.144".
rangerversionsnin	optional	Network Scanner versions not to include. Example: "2.0.0.0,2.1.5.144".
registeredat__between	optional	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
registeredat__gt	optional	Agents registered after this time. Example:

		"2018-02-27T04:49:26.257525Z".
registeredat__gte	optional	Agents registered after or at this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__lt	optional	Agents registered before this time. Example: "2018-02-27T04:49:26.257525Z".
registeredat__lte	optional	Agents registered before or at this time. Example: "2018-02-27T04:49:26.257525Z".
remoteopsforensicssupported	optional	Include only agents that has Remote Ops Forensicsfeature supported
remoteprofilingsstates	optional	Agent remote profiling state
remoteprofilingsstatesnotin	optional	Do not include these Agent remote profiling states
rsolevel	optional	Supported Remote Script Orchestration level. Example: "none".
rsolevels	optional	A list of included rso_levels. Example: "pro,ars".
scanstatus	optional	Scan status. Example: "none".
scanstatuses	optional	Included scan statuses. Example: "started,aborted".
scanstatusesnotin	optional	Not included scan statuses. Example: "started,aborted".
serialnumber__contains	optional	Free-text filter by Serial Number (supports multiple values)
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
storagetypes	optional	Included storage types. Example: "NetApp,Dell,S3".
storagetypesnotin	optional	Excluded storage types. Example: "NetApp,Dell,S3".
tagsdata	optional	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key. Example: "{"key1": ["value1_1", "value1_2"], "key2__nin": ["value2"]}".
threatcontenthash	optional	Include only Agents that have at least one threat with this content hash. Example: "cf23df2207d99a74fbe169e3eba035e633b65d94".
threatcreatedat__between	optional	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978764288-1514978999999".
threatcreatedat__gt	optional	Agents with threats reported after this time. Example:

		"2018-02-27T04:49:26.257525Z".
threatcreatedat__gte	optional	Agents with threats reported after or at this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__lt	optional	Agents with threats reported before this time. Example: "2018-02-27T04:49:26.257525Z".
threatcreatedat__lte	optional	Agents with threats reported before or at this time. Example: "2018-02-27T04:49:26.257525Z".
threathidden	optional	Include only Agents with at least one hidden threat
threatmitigationstatus	optional	Include only Agents that have threats with this mitigation status. Example: "mitigated".
threatrebootrequired	optional	Has at least one threat with at least one mitigation action pending reboot to succeed
threatresolved	optional	Include only Agents with at least one resolved threat
totalmemory__between	optional	Total memory range (GB, inclusive). Example: "4-8".
totalmemory__gt	optional	Memory size (MB, more than)
totalmemory__gte	optional	Memory size (MB, more than or equal)
totalmemory__lt	optional	Memory size (MB, less than)
totalmemory__lte	optional	Memory size (MB, less than or equal)
updatedat__between	optional	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedat__gt	optional	Agents updated after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Agents updated after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Agents updated before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Agents updated before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
useractionsneeded	optional	Included pending user actions. Example: "reboot_needed,upgrade_needed".
useractionsneedednin	optional	Excluded pending user actions. Example: "reboot_needed,upgrade_needed".

uuid	optional	Agent's universally unique identifier. Example: "ff819e70af13be381993075eb0ce5f2f6de05be2".
uuid__contains	optional	Free-text filter by Agent UUID (supports multiple values). Example: "e92-01928,b055".
uuids	optional	A list of included UUIDs. Example: "ff819e70af13be381993075eb0ce5f2f6de05b11,ff819e70af13be381993075eb0ce5f2f6de05c22".
windowsosrevision__gte	optional	Agents os revision than or equal to given version
windowsosrevision__lte	optional	Agents os revision lower than or equal to given version

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Get the endpoint tags that match the filters.

GET /web/api/v2.1/agents/tags

Get endpoint Tags.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdby	optional	Created by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
description	optional	Tag description

groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of tag IDs to filter by. Example: "225494730938493804,225494730938493915".
includechildren	optional	Return tags from children scope levels
includeendpointcounters	optional	Include endpoint counters
includeexclusioncounters	optional	Include exclusion counters
includeparents	optional	Return tags from parent scope levels
isdecommissioned	optional	Filter endpoint counts by decommissioned status: [False] for active only, [True] for decommissioned only, [True, False] for both. Example: "True,False".
isuninstalled	optional	Filter endpoint counts by uninstalled status: [False] for installed only, [True] for uninstalled only, [True, False] for both. Example: "True,False".
key	optional	Tag key
key__contains	optional	Free-text filter by tag key. Example: "server".
limit	optional	Limit number of returned items (1-1000). Example: "10".
query	optional	Free text search on fields key, value, description
scopepath	optional	Scope path
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
updatedby	optional	Updated by
value	optional	Tag value
value__contains	optional	Free-text filter by tag value. Example: "server".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get the endpoint tags that match the filters. - response - pagination table
data	Response data	false	see Get the endpoint tags that match the filters. - response - data table
errors	Errors	false	array

Get the endpoint tags that match the filters. - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get the endpoint tags that match the filters. - response - data

Name	Description	Required	Value
allowEdit	indicate if user can/cant edit the tag	false	boolean
createdAt	Timestamp of creation	false	string
createdBy	Tag creator name	false	string
description	Tag description	false	string
endpointsInCurrentScope	The number of endpoints in this scope that have this tag (not present if includeEndpointCounters=false)	false	integer
id	Tag ID	false	string
key	Tag key	false	string
scopeId	Scope id	false	string
scopeLevel	Scope level	false	enum
scopePath	tag scope path	false	string
totalEndpoints	The total number of endpoints that have this tag (not present if includeEndpointCounters=false)	false	integer
totalExclusions	Number of exclusions with this tag.	false	integer
type	Tag type	false	string
updatedAt	Timestamp of last update	false	string
updatedBy	Tag updater name	false	string

value	tag value	false	string
-------	-----------	-------	--------

Endpoint tags count by Filters

GET /web/api/v2.1/agents/tags/filters-count

Get endpoint Tags filter counts.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
createdby	optional	Created by
description	optional	Tag description
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of tag IDs to filter by. Example: "225494730938493804,225494730938493915".
includechildren	optional	Return tags from children scope levels
includeparents	optional	Return tags from parent scope levels
key	optional	Tag key
key__contains	optional	Free-text filter by tag key. Example: "server".
query	optional	Free text search on fields key, value, description
scopepath	optional	Scope path
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
updatedby	optional	Updated by
value	optional	Tag value
value__contains	optional	Free-text filter by tag value. Example: "server".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Endpoint tags count by Filters - response - data table
errors	Errors	false	array

Endpoint tags count by Filters - response - data

Name	Description	Required	Value
disableSorting	A flag to disable the UI filter values sorting by counts, and instead display values in the provided order.	false	boolean
enableNegation	This flag indicates whether the negation query is enabled for this filter key or not	false	boolean
hiddenFilter	This flag indicates whether the filter is hidden in the UI filters but it may remain for grouping.	false	boolean
hiddenGroupBy	This flag indicates whether the filter is hidden in the UI group by but it may remain for filtering.	false	boolean
key	Filter argument key	false	string
title	Filter description	false	string
type	Filter type	false	string
values	A list of filter values with their count	false	see Endpoint tags count by Filters - response - values table

Endpoint tags count by Filters - response - values

Name	Description	Required	Value
count	Number of entities matching this value	false	integer
title	Value description	false	string
value	Value	false	string

Agents Repository (Beta)

List Access Tokens

GET /web/api/v2.1/agent-artifacts/token

Lists valid access tokens for the S1 Agent Artifacts Repository, with the option to filter by scope

Parameters

limit	optional	The number of tokens to return, for example: '10'. Optional
offset	optional	The number of tokens to skip before starting to collect the result, for example: '2'. Optional
scope_id	optional	Scope id to list the tokens for, example: '983604236220743370'
scope_level	optional	Scope level to list the tokens for. Possible values: 'site', 'account', 'tenant'

Response Messages

200 - OK

400 - Invalid request

401 - Unauthorized

500 - Internal error

Response Schema

Name	Description	Required	Value
data	List of existing tokens	false	undefined []
pagination	Pagination information	false	

Create Access Token

POST /web/api/v2.1/agent-artifacts/token

Creates an access token for the S1 Agent Artifacts Repository, which is needed for pulling artifacts

Response Messages

200 - OK

400 - Invalid request

401 - Unauthorized

500 - Internal Error

Response Schema

Name	Description	Required	Value
created_at	Created At timestamp of the token	false	string
description	Token description	false	string
id	Access token ID	false	integer
scope_id	Scope ID	false	string
scope_level	Scope level of the token	false	string
title	Token name	false	string
token	Access token - seen only once	false	string
username	Username of the token	false	string

Body Schema

Name	Description	Required	Value
description	Token description	false	string
scope_id	Scope ID of the specified account or site	false	string
scope_level	Scope Level of the token e.g. `account`, `site`	false	string
title	Token title	false	string

Delete Access Token

DELETE /web/api/v2.1/agent-artifacts/token

Deletes an access token for the S1 Agent Artifacts Repository

Parameters

scope_id	optional	Scope id to list the tokens for, example: '983604236220743370'
scope_level	optional	Scope level to list the tokens for. Possible values: 'site', 'account'
token_id	optional	token id of the token to be deleted, example: '42'

Response Messages

200 - Token deleted

400 - Invalid request

401 - Unauthorized

404 - Not found

500 - Internal error

Alerts

Get alerts

GET /web/api/v2.1/cloud-detection/alerts

Get a list of alerts for a given scope

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
------------	----------	---

analystverdict	optional	Filter threats by a analyst verdict. Example: "TRUE_POSITIVE".
containerimagename__contains	optional	Free-text filter by the endpoint container image name (supports multiple values)
containerlabels__contains	optional	Free-text filter by the endpoint container labels (supports multiple values)
containername__contains	optional	Free-text filter by the endpoint container name (supports multiple values)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__gt	optional	Created at greater than. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Created at greater or equal than. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Created at lesser than. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Created at lesser or equal than. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
disablepagination	optional	If true, all rules for requested scope will be returned
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	A list of Alert IDs. Example: "225494730938493804,225494730938493915".
incidentstatus	optional	Filter threats by a incident status. Example: "IN_PROGRESS".
k8scluster__contains	optional	Free-text filter by the endpoint Kubernetes cluster name (supports multiple values)
k8scontrollerlabels__contains	optional	Free-text filter by the endpoint Kubernetes controller labels (supports multiple values)
k8scontrollername__contains	optional	Free-text filter by the endpoint Kubernetes controller name (supports multiple values)
k8snamespacelabels__contains	optional	Free-text filter by the endpoint Kubernetes namespace labels (supports multiple values)
k8snamespace__contains	optional	Free-text filter by the endpoint Kubernetes namespace name

contains		(supports multiple values)
k8snode__contains	optional	Free-text filter by the endpoint Kubernetes node name (supports multiple values)
k8spod__contains	optional	Free-text filter by the endpoint Kubernetes pod name (supports multiple values)
k8spodlabels__contains	optional	Free-text filter by the endpoint Kubernetes pod labels (supports multiple values)
limit	optional	Limit number of returned items (1-1000). Example: "10".
machinetype	optional	agent machine type
origagentname__contains	optional	Free-text filter by agent name. Example: "ilia".
origagentosrevision__contains	optional	Free-text filter by agent OS revision. Example: "win7".
origagentuuid__contains	optional	Free-text filter by agent UUID. Example: "win7".
origagentversion__contains	optional	Free-text filter by agent OS version. Example: "7.11".
ostype	optional	Included OS types
query	optional	Full text search for all fields
reportedat__gt	optional	Reported at greater than. Example: "2018-02-27T04:49:26.257525Z".
reportedat__gte	optional	Reported at greater or equal than. Example: "2018-02-27T04:49:26.257525Z".
reportedat__lt	optional	Reported at lesser than. Example: "2018-02-27T04:49:26.257525Z".
reportedat__lte	optional	Reported at lesser or equal than. Example: "2018-02-27T04:49:26.257525Z".
rulename__contains	optional	Free-text filter by rule name. Example: "rule1".
scopes	optional	Filter results by scope. Example: "group".
severity	optional	Severity. Example: "Low".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000

		items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
sourceprocesscommandline__contains	optional	Free-text filter by source commandline. Example: "rule1".
sourceprocessfilehashmd5__contains	optional	Free-text filter by source md5. Example: "rule1".
sourceprocessfilehashsha1__contains	optional	Free-text filter by source sha1. Example: "rule1".
sourceprocessfilehashsha256__contains	optional	Free-text filter by source sha256. Example: "rule1".
sourceprocessfilepath__contains	optional	Free-text filter by source file path. Example: "rule1".
sourceprocessname__contains	optional	Free-text filter by source process name. Example: "proc1.exe".
sourceprocessstoryline__contains	optional	Free-text filter by source storyline. Example: "rule1".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get alerts - response - pagination table
data	Response data	false	see Get alerts - response - data table
errors	Errors	false	array

Get alerts - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get alerts - response - data

Name	Description	Required	Value
agentDetectionInfo	Agent detection time information	false	see Get alerts - response - agentDetectionInfo table
alertInfo	Alert information	false	see Get alerts - response - alertInfo table
containerInfo	Alert container information	false	see Get alerts - response - containerInfo table
kubernetesInfo	Alert kubernetes information	false	see Get alerts - response - kubernetesInfo table
ruleInfo	Custom Detection rules like STAR indicators information	false	see Get alerts - response - ruleInfo table
sourceParentProcessInfo	Source parent process info	false	see Get alerts - response - sourceParentProcessInfo table
sourceProcessInfo	Source process info	false	see Get alerts - response - sourceProcessInfo table
targetProcessInfo	Target process info	false	see Get alerts - response - targetProcessInfo table

Get alerts - response - agentDetectionInfo

Name	Description	Required	Value
accountId	Account id	false	string
machineType	Machine type	false	string
name	Name	false	string
osFamily	Os family	false	string
osName	Os name	false	string

osRevision	Os revision	false	string
siteId	Site id	false	string
uuid	UUID of the agent	false	string
version	Version	false	string

Get alerts - response - alertInfo

Name	Description	Required	Value
alertId	Alert ID	false	string
analystVerdict	Analyst verdict	false	enum
createdAt	Timestamp alert sent for detection	false	string
dnsRequest	Get the DNS name.	false	string
dnsResponse	Get the DNS response information (examples: IP address, DNS, data type).	false	string
dstIp	Get the IP address of the destination.	false	string
dstPort	Get the port number of the destination.	false	string
dvEventId	Deep Visibility event ID	false	string
eventType	Event type	false	string
hitType	Type of hit reported from the Agent	false	enum
incidentStatus	Incident status	false	enum
indicatorCategory	Get the Indicator categories for this process.	false	string
indicatorDescription	Get the description of the Indicator.	false	string
indicatorName	Get the Indicator names for this process.	false	string
isEdr	True if the event is edr event	false	boolean
loginAccountDomain	Get the domain or computer name for which the login attempt was performed.	false	string
loginAccountSid	Get the SID of the account that attempted to log in.	false	string
loginIsAdministratorEquivalent	See if the login attempt was	false	string

	performed by an administrator equivalent.		
loginIsSuccessful	Check if the login attempt succeeded.	false	string
loginUserName	Get the login username.	false	string
loginType	Get the type of login that was performed.	false	string
modulePath	Get the paths of modules loaded by this process.	false	string
moduleSha1	Get the SHA1 signatures for modules loaded by this process.	false	string
netEventDirection	Get the direction of the connection attempt (incoming or outgoing).	false	string
registryKeyPath	Get the full paths of registry entries modified by this process.	false	string
registryOldValue	Get the previous registry value if it was modified.	false	string
registryOldValueType	Get the previous registry value type if it was modified.	false	string
registryPath	Get the full path location of the registry key entry.	false	string
registryValue	Get the registry value	false	string
reportedAt	Timestamp of alert creation in STAR	false	string
source	Source reported from the Agent.	false	string
srcIp	Get the IP address of the traffic source.	false	string
srcMachineIp	Get the IP address of the endpoint performing the login attempt.	false	string
srcPort	Get the port number of the traffic source.	false	string
tiIndicatorComparisonMethod	Get the comparison method used by SentinelOne to trigger the event.	false	string
tiIndicatorSource	Get the source of the identified Threat Intelligence indicator.	false	string
tiIndicatorType	Get the type of the identified Threat Intelligence indicator.	false	string
tiIndicatorValue	Get the value of the identified Threat Intelligence indicator.	false	string

updatedAt	Date of alert updated in Star MMS	false	string
-----------	-----------------------------------	-------	--------

Get alerts - response - containerInfo

Name	Description	Required	Value
id	Id	false	string
image	Image	false	string
labels	Labels	false	string
name	Name	false	string

Get alerts - response - kubernetesInfo

Name	Description	Required	Value
cluster	Cluster	false	string
controllerKind	Controller kind	false	string
controllerLabels	Controller labels	false	string
controllerName	Controller name	false	string
namespace	Namespace	false	string
namespaceLabels	Namespace labels	false	string
node	Node	false	string
pod	Pod	false	string
podLabels	Pod labels	false	string

Get alerts - response - ruleInfo

Name	Description	Required	Value
s1ql	The query	true	string
description	Rule description for the STAR alert	false	string
id	Rule ID for the STAR alert	false	string
name	Rule name for the STAR alert	false	string

queryLang	Defines the sql version query language of the rule (1.0/2.0)	false	enum
queryType	The query type	false	enum
scopeLevel	Scope level	false	enum
severity	Rule severity	false	enum
treatAsThreat	Rule treat as threat type	false	enum

Get alerts - response - sourceParentProcessInfo

Name	Description	Required	Value
integrityLevel	Integrity level	true	enum
subsystem	Subsystem	true	enum
commandline	Commandline	false	string
effectiveUser	Effective user	false	string
fileHashMd5	File hash md5	false	string
fileHashSha1	File hash sha1	false	string
fileHashSha256	File hash sha256	false	string
filePath	File path	false	string
fileSignerIdentity	File signer identity	false	string
loginUser	Login user	false	string
name	Name	false	string
pid	Pid	false	string
pidStarttime	Pid starttime	false	string
realUser	Real user	false	string
storyline	Storyline	false	string
uniqueId	Unique id	false	string
user	User	false	string

Get alerts - response - sourceProcessInfo

Name	Description	Required	Value
------	-------------	----------	-------

integrityLevel	Integrity level	true	enum
subsystem	Subsystem	true	enum
commandline	Commandline	false	string
effectiveUser	Effective user	false	string
fileHashMd5	File hash md5	false	string
fileHashSha1	File hash sha1	false	string
fileHashSha256	File hash sha256	false	string
filePath	File path	false	string
fileSignerIdentity	File signer identity	false	string
loginUser	Login user	false	string
name	Name	false	string
pid	Pid	false	string
pidStarttime	Pid starttime	false	string
realUser	Real user	false	string
storyline	Storyline	false	string
uniqueId	Unique id	false	string
user	User	false	string

Get alerts - response - targetProcessInfo

Name	Description	Required	Value
tgtFileCreatedAt	Date and Time of File Creation	false	string
tgtFileHashSha1	SHA1 Signature of File	false	string
tgtFileHashSha256	SHA256 Signature of File	false	string
tgtFileId	Unique ID of file	false	string
tgtFileIsSigned	Is file signed	false	string
tgtFileModifiedAt	Date and time file was modified	false	string
tgtFileOldPath	Old path before 'Rename'	false	string
tgtFilePath	Path and filename	false	string
tgtProcCmdLine	Target Process Command Line	false	string
tgtProcessStartTime	Target Process Start Time	false	string

tgtProcImagePath	Target Process Image path	false	string
tgtProcIntegrityLevel	Integrity level of target process	false	enum
tgtProcName	Target Process Name	false	string
tgtProcPid	Target Process ID (PID)	false	string
tgtProcSignedStatus	Target Process Signed Status	false	string
tgtProcStorylineId	Target Process StoryLine ID	false	string
tgtProcUid	Target Process Unique ID	false	string

Update Threat Incident

POST /web/api/v2.1/cloud-detection/alerts/incident

Update the incident details of an alert.

Response Messages

200 - Threats incident successfully updated

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Threat Incident - response - data table
errors	Errors	false	array

Update Threat Incident - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Threat Incident - body - data table
filter	Filter	true	see Update Threat Incident - body - filter table

Update Threat Incident - body - data

Name	Description	Required	Value
incidentStatus	Incident status	true	enum

Update Threat Incident - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
analystVerdict	Filter threats by a analyst verdict	false	string []
containerImageName__contains	Free-text filter by the endpoint container image name (supports multiple values)	false	string []
containerLabels__contains	Free-text filter by the endpoint container labels (supports multiple values)	false	string []
containerName__contains	Free-text filter by the endpoint container name (supports multiple values)	false	string []
createdAt__gt	Created at greater than.	false	string
createdAt__gte	Created at greater or equal than.	false	string
createdAt__lt	Created at lesser than.	false	string
createdAt__lte	Created at lesser or equal than.	false	string
groupIds	List of Group IDs to filter by	false	string []
ids	A list of Alert IDs	false	string []
incidentStatus	Filter threats by a incident status	false	string []
k8sCluster__contains	Free-text filter by the endpoint Kubernetes cluster name (supports multiple values)	false	string []
k8sControllerLabels__contains	Free-text filter by the endpoint Kubernetes controller labels (supports multiple values)	false	string []
k8sControllerName__contains	Free-text filter by the endpoint	false	string []

	Kubernetes controller name (supports multiple values)		
k8sNamespaceLabels__contains	Free-text filter by the endpoint Kubernetes namespace labels (supports multiple values)	false	string []
k8sNamespaceName__contains	Free-text filter by the endpoint Kubernetes namespace name (supports multiple values)	false	string []
k8sNode__contains	Free-text filter by the endpoint Kubernetes node name (supports multiple values)	false	string []
k8sPod__contains	Free-text filter by the endpoint Kubernetes pod name (supports multiple values)	false	string []
k8sPodLabels__contains	Free-text filter by the endpoint Kubernetes pod labels (supports multiple values)	false	string []
limit	Limit	false	integer
machineType	agent machine type	false	string []
origAgentName__contains	Free-text filter by agent name	false	string []
origAgentOsRevision__contains	Free-text filter by agent OS revision	false	string []
origAgentUuid__contains	Free-text filter by agent UUID	false	string []
origAgentVersion__contains	Free-text filter by agent OS version	false	string []
osType	Included OS types	false	string []
query	Full text search for all fields	false	string
reportedAt__gt	Reported at greater than.	false	string
reportedAt__gte	Reported at greater or equal than.	false	string
reportedAt__lt	Reported at lesser than.	false	string
reportedAt__lte	Reported at lesser or equal than.	false	string
ruleName__contains	Free-text filter by rule name	false	string []
scopes	Filter results by scope	false	string []
severity	Severity	false	string []
sitelds	List of Site IDs to filter by	false	string []
sourceProcessCommandline__contains	Free-text filter by source commandline	false	string []
sourceProcessFileHashMd5__contains	Free-text filter by source md5	false	string []

sourceProcessFileHashSha1__contains	Free-text filter by source sha1	false	string []
sourceProcessFileHashSha256__contains	Free-text filter by source sha255	false	string []
sourceProcessFilePath__contains	Free-text filter by source file path	false	string []
sourceProcessName__contains	Free-text filter by source process name	false	string []
sourceProcessStoryline__contains	Free-text filter by source storyline	false	string []
tenant	Indicates a tenant scope request	false	boolean

Update Alert Analyst Verdict

POST /web/api/v2.1/cloud-detection/alerts/analyst-verdict

Change the verdict of an alert

Response Messages

200 - Threats incident successfully updated

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Alert Analyst Verdict - response - data table
errors	Errors	false	array

Update Alert Analyst Verdict - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Alert Analyst Verdict - body - data table
filter	Filter	true	see Update Alert Analyst Verdict - body - filter table

Update Alert Analyst Verdict - body - data

Name	Description	Required	Value
analystVerdict	Analyst verdict	true	enum

Update Alert Analyst Verdict - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
analystVerdict	Filter threats by a analyst verdict	false	string []
containerImageName__contains	Free-text filter by the endpoint container image name (supports multiple values)	false	string []
containerLabels__contains	Free-text filter by the endpoint container labels (supports multiple values)	false	string []
containerName__contains	Free-text filter by the endpoint container name (supports multiple values)	false	string []
createdAt__gt	Created at greater than.	false	string
createdAt__gte	Created at greater or equal than.	false	string
createdAt__lt	Created at lesser than.	false	string
createdAt__lte	Created at lesser or equal than.	false	string
groupIds	List of Group IDs to filter by	false	string []
ids	A list of Alert IDs	false	string []
incidentStatus	Filter threats by a incident status	false	string []
k8sCluster__contains	Free-text filter by the endpoint Kubernetes cluster name (supports multiple values)	false	string []
k8sControllerLabels__contains	Free-text filter by the endpoint Kubernetes controller labels (supports multiple values)	false	string []
k8sControllerName__contains	Free-text filter by the endpoint	false	string []

	Kubernetes controller name (supports multiple values)		
k8sNamespaceLabels__contains	Free-text filter by the endpoint Kubernetes namespace labels (supports multiple values)	false	string []
k8sNamespaceName__contains	Free-text filter by the endpoint Kubernetes namespace name (supports multiple values)	false	string []
k8sNode__contains	Free-text filter by the endpoint Kubernetes node name (supports multiple values)	false	string []
k8sPod__contains	Free-text filter by the endpoint Kubernetes pod name (supports multiple values)	false	string []
k8sPodLabels__contains	Free-text filter by the endpoint Kubernetes pod labels (supports multiple values)	false	string []
limit	Limit	false	integer
machineType	agent machine type	false	string []
origAgentName__contains	Free-text filter by agent name	false	string []
origAgentOsRevision__contains	Free-text filter by agent OS revision	false	string []
origAgentUuid__contains	Free-text filter by agent UUID	false	string []
origAgentVersion__contains	Free-text filter by agent OS version	false	string []
osType	Included OS types	false	string []
query	Full text search for all fields	false	string
reportedAt__gt	Reported at greater than.	false	string
reportedAt__gte	Reported at greater or equal than.	false	string
reportedAt__lt	Reported at lesser than.	false	string
reportedAt__lte	Reported at lesser or equal than.	false	string
ruleName__contains	Free-text filter by rule name	false	string []
scopes	Filter results by scope	false	string []
severity	Severity	false	string []
sitelds	List of Site IDs to filter by	false	string []
sourceProcessCommandline__contains	Free-text filter by source commandline	false	string []
sourceProcessFileHashMd5__contains	Free-text filter by source md5	false	string []

sourceProcessFileHashSha1__contains	Free-text filter by source sha1	false	string []
sourceProcessFileHashSha256__contains	Free-text filter by source sha255	false	string []
sourceProcessFilePath__contains	Free-text filter by source file path	false	string []
sourceProcessName__contains	Free-text filter by source process name	false	string []
sourceProcessStoryline__contains	Free-text filter by source storyline	false	string []
tenant	Indicates a tenant scope request	false	boolean

Application Control - Rules

Get a single NAC rule

GET /web/api/v2.1/nac/config/api/v1/nac/rules/{id}

Retrieves a single NAC rule by its ID

Parameters

scopeid	optional	Scope ID
scopetype	optional	Scope Type

Response Messages

200 - Rule retrieved successfully

400 - Invalid rule ID format or bad request

401 - Unauthorized

403 - Forbidden

404 - Rule not found or out of scope

405 - Method Not Allowed

409 - Conflict

415 - Unsupported Media Type

422 - Unprocessable Content

429 - Too Many Requests

500 - Internal server error

Response Schema

Name	Description	Required	Value
behavior	Rule behavior	false	enum
createdAt	Timestamp when the rule was created	false	string
createdBy	Created by	false	string
description	Description	false	string
exceptions	Exceptions	false	undefined []
id	Rule ID	false	string
osType	OS types	false	string []
parameters	Rule conditions	false	see Get a single NAC rule - response - parameters table
propagation	Whether propagation is enabled	false	boolean
ruleName	Rule name	false	string
scope	Scope info	false	see Get a single NAC rule - response - scope table

Get a single NAC rule - response - parameters

Name	Description	Required	Value
applicationVersion	Application version	false	string
parentProcess	Parent process	false	string
path	Path	false	string
process	Process name	false	string
publisher	Publisher	false	string
sha256	SHA-256 hash	false	string
signer	Signer	false	string

Get a single NAC rule - response - scope

Name	Description	Required	Value
scopeId	Scope ID	false	string
scopeLevel	Scope level	false	enum
scopeName	Scope name	false	string
scopePath	Scope path	false	string

Update NAC rule

PUT /web/api/v2.1/nac/config/api/v1/nac/rules/{id}

Updates an existing Native Application Control rule by ID

Response Messages

200 - Rule updated successfully

400 - Validation error, invalid request, or rule not found

401 - Unauthorized

403 - Forbidden

404 - Rule not found

405 - Method Not Allowed

409 - Conflict

415 - Unsupported Media Type

422 - Unprocessable Content

429 - Too Many Requests

500 - Internal server error

Response Schema

Name	Description	Required	Value
id	Resource ID	false	string
statusCode	Status code	false	integer
statusMessage	Status message	false	string
success	Whether the request was successful	false	boolean
validationErrors	Validation errors	false	undefined []

Body Schema

Name	Description	Required	Value
behavior	Rule behavior	false	enum
description	Description	false	string
exceptions	Exceptions	false	undefined []
id	Rule ID	false	string
osType	OS types	false	string []
parameters	Rule conditions input	false	see Update NAC rule - body - parameters table
propagation	Whether propagation is enabled	false	boolean
ruleName	Rule name	false	string
scope	Scope selector as JSON	false	see Update NAC rule - body - scope table

Update NAC rule - body - parameters

Name	Description	Required	Value
parentProcess	Parent process	false	string
path	Path	false	string
process	Process name	false	string
publisher	Publisher	false	string
sha256	SHA-256 hash	false	string
signer	Signer	false	string

Update NAC rule - body - scope

Name	Description	Required	Value
scopelds	Scope IDs	false	string []
scopeType	Scope type	false	enum

Create or update NAC rule

POST /web/api/v2.1/nac/config/api/v1/nac/rules

Creates a new NAC rule if id is absent, otherwise updates the existing rule

Response Messages

200 - Rule updated successfully

201 - Rule created successfully

400 - Validation error or invalid request

401 - Unauthorized

403 - Forbidden

404 - Not Found

405 - Method Not Allowed

409 - Conflict

415 - Unsupported Media Type

422 - Unprocessable Content

429 - Too Many Requests

500 - Internal server error

Response Schema

Name	Description	Required	Value
id	Resource ID	false	string
statusCode	Status code	false	integer
statusMessage	Status message	false	string
success	Whether the request was successful	false	boolean
validationErrors	Validation errors	false	undefined []

Body Schema

Name	Description	Required	Value
behavior	Rule behavior	false	enum
description	Description	false	string
exceptions	Exceptions	false	undefined []
id	Rule ID	false	string
osType	OS types	false	string []
parameters	Rule conditions input	false	see Create or update NAC rule - body - parameters table
propagation	Whether propagation is enabled	false	boolean
ruleName	Rule name	false	string
scope	Scope selector as JSON	false	see Create or update NAC rule - body - scope table

Create or update NAC rule - body - parameters

Name	Description	Required	Value
parentProcess	Parent process	false	string
path	Path	false	string
process	Process name	false	string
publisher	Publisher	false	string
sha256	SHA-256 hash	false	string
signer	Signer	false	string

Create or update NAC rule - body - scope

Name	Description	Required	Value
scopelds	Scope IDs	false	string []
scopeType	Scope type	false	enum

Delete NAC rules

DELETE /web/api/v2.1/nac/config/api/v1/nac/rules

Deletes multiple NAC rules by their IDs

Parameters

ids	required	
-----	----------	--

Response Messages

200 - Rules deleted successfully

400 - Validation error or invalid request

401 - Unauthorized

403 - Forbidden

404 - No rules found for the provided IDs

405 - Method Not Allowed

409 - Conflict

415 - Unsupported Media Type

422 - Unprocessable Content

429 - Too Many Requests

500 - Internal server error

Response Schema

Name	Description	Required	Value
id	Resource ID	false	string
statusCode	Status code	false	integer
statusMessage	Status message	false	string
success	Whether the request was successful	false	boolean
validationErrors	Validation errors	false	undefined []

Body Schema

Name	Description	Required	Value
scopes	Scope IDs	false	string []
scopeType	Scope type	false	enum

Get paginated NAC rules

POST /web/api/v2.1/nac/config/api/v1/nac/rules/query

Retrieves a paginated list of NAC rules with optional filtering and sorting

Parameters

cursor	optional	Cursor for pagination
direction	optional	Pagination direction (FORWARD, BACKWARD)
pagesize	optional	Pagination page size

Response Messages

200 - Rules retrieved successfully

400 - Invalid filter, sort, or pagination parameters

401 - Unauthorized

403 - Forbidden

404 - Not Found

405 - Method Not Allowed

409 - Conflict

415 - Unsupported Media Type

422 - Unprocessable Content

429 - Too Many Requests

500 - Internal server error

Response Schema

Name	Description	Required	Value
edges	Rule list with cursors	false	undefined []

pageInfo	Page info	false	see Get paginated NAC rules - response - pageInfo table
totalCount	Total count	false	integer

Get paginated NAC rules - response - pageInfo

Name	Description	Required	Value
endCursor	End cursor	false	string
hasNextPage	Whether there is a next page	false	boolean
hasPreviousPage	Whether there is a previous page	false	boolean
startCursor	Start cursor	false	string

Body Schema

Name	Description	Required	Value
filters	Filters	false	undefined []
includeParents	Include rules from parent scopes	false	boolean
scopeSelector	Scope selector as JSON	false	see Get paginated NAC rules - body - scopeSelector table
sorts	Sorting	false	undefined []

Get paginated NAC rules - body - scopeSelector

Name	Description	Required	Value
scopeIds	Scope IDs	false	string []
scopeType	Scope type	false	enum

Create presigned CSV upload URL

POST /web/api/v2.1/nac/config/api/v1/nac/csv/upload-url

Generates a presigned URL for uploading a CSV file containing NAC rules

Response Messages

200 - Presigned upload URL generated successfully

400 - Validation error or invalid request

401 - Unauthorized

403 - Forbidden

404 - Not Found

405 - Method Not Allowed

409 - Conflict

415 - Unsupported Media Type

422 - Unprocessable Content

429 - Too Many Requests

500 - Internal server error

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

expiresAt	Expiry time in epoch milliseconds	false	integer
fileOperationId	File operation ID	false	string
url	Presigned upload URL	false	string

Body Schema

Name	Description	Required	Value
fileName	File name	false	string
fileSizeInBytes	File size in bytes	false	integer
scope	Scope selector as JSON	false	see Create presigned CSV upload URL - body - scope table

Create presigned CSV upload URL - body - scope

Name	Description	Required	Value
scopeIds	Scope IDs	false	string []
scopeType	Scope type	false	enum

Import CSV file uploaded

POST /web/api/v2.1/nac/config/api/v1/nac/csv/import

Imports the CSV file that has been uploaded

Response Messages

200 - CSV import initiated successfully

400 - Validation error or invalid request

401 - Unauthorized

403 - Forbidden

404 - Not Found

405 - Method Not Allowed

409 - Invalid state transition for import

415 - Unsupported Media Type

422 - Unprocessable Content

429 - Too Many Requests

500 - Internal server error

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

fileOperationId		false	string
status		false	enum
statusMessage		false	string

Body Schema

Name	Description	Required	Value
etag	ETag returned after upload	false	string
fileOperationId	File operation ID	false	string
scope	Scope selector as JSON	false	see Import CSV file uploaded - body - scope table

Import CSV file uploaded - body - scope

Name	Description	Required	Value
scopelds	Scope IDs	false	string []
scopeType	Scope type	false	enum

Export NAC rules to CSV

POST /web/api/v2.1/nac/config/api/v1/nac/csv/export

Triggers an async CSV export of NAC rules based on filters and sorting

Response Messages

200 - CSV export initiated successfully

400 - Validation error or invalid request

401 - Unauthorized

403 - Forbidden

404 - Not Found

405 - Method Not Allowed

409 - Conflict

415 - Unsupported Media Type

422 - Unprocessable Content

429 - Too Many Requests

500 - Internal server error

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

downloadUrl		false	string
expiresAt		false	integer
fileOperationId		false	string
status		false	enum
statusMessage		false	string

Body Schema

Name	Description	Required	Value
filters	Filters	false	undefined []
includeParents	Include rules from parent scopes	false	boolean
scopeSelector	Scope selector as JSON	false	see Export NAC rules to CSV - body - scopeSelector table
sorts	Sorting	false	undefined []

Export NAC rules to CSV - body - scopeSelector

Name	Description	Required	Value
scopeIds	Scope IDs	false	string []
scopeType	Scope type	false	enum

Get rule change log

GET /web/api/v2.1/nac/config/api/v1/nac/rules/{id}/changelog

Retrieves the change history for a specific rule

Parameters

scopeid	optional	Scope ID
scopetype	optional	Scope Type

Response Messages

200 - Change log retrieved successfully

400 - Invalid rule ID format or invalid scope parameters

401 - Unauthorized

403 - Forbidden

404 - Rule not found

405 - Method Not Allowed

409 - Conflict

415 - Unsupported Media Type

422 - Unprocessable Content

429 - Too Many Requests

500 - Internal server error

Response Schema

Name	Description	Required	Value
changeLog	List of change logs	false	undefined []
createdAt	Timestamp when the rule was created	false	string
createdBy	Created by	false	string
ruleId	Rule ID	false	integer

Get column metadata

GET /web/api/v2.1/nac/config/api/v1/nac/rules/metadata/columns

Retrieves metadata about rule table columns

Response Messages

200 - Column metadata retrieved successfully

400 - Bad Request

401 - Unauthorized

403 - Forbidden

404 - Not Found

405 - Method Not Allowed

409 - Conflict

415 - Unsupported Media Type

422 - Unprocessable Content

429 - Too Many Requests

500 - Internal server error

Response Schema

Name	Description	Required	Value
enumValues	Enum values for this column, if applicable	false	string []
fieldId	Field name	false	string
filterTypes	Supported filter types	false	string []
groupable	Whether grouping is supported	false	boolean
sortable	Whether sorting is supported	false	boolean

Get CSV processing status

GET /web/api/v2.1/nac/config/api/v1/nac/csv/status/{fileOperationId}

Retrieves the current status of a CSV file processing request

Parameters

scopeid	optional	Scope ID
scopetype	optional	Scope Type

Response Messages

200 - Processing status retrieved successfully

400 - Invalid request or file operation not found

401 - Unauthorized

403 - Forbidden

404 - Not Found

405 - Method Not Allowed

409 - Import results not yet available

415 - Unsupported Media Type

422 - Unprocessable Content

429 - Too Many Requests

500 - Internal server error

Response Schema

Name	Description	Required	Value
fileOperationId		false	string
status		false	enum

statusMessage		false	string
---------------	--	-------	--------

Get CSV export status

GET /web/api/v2.1/nac/config/api/v1/nac/csv/export/status/{fileOperationId}

Retrieves the current status of a CSV export request

Parameters

scopeid	optional	Scope ID
scopetype	optional	Scope Type

Response Messages

200 - Export status retrieved successfully

400 - Invalid request or file operation not found

401 - Unauthorized

403 - Forbidden

404 - Not Found

405 - Method Not Allowed

409 - Conflict

415 - Unsupported Media Type

422 - Unprocessable Content

429 - Too Many Requests

500 - Internal server error

Response Schema

Name	Description	Required	Value
downloadUrl		false	string
expiresAt		false	integer

fileOperationId		false	string
status		false	enum
statusMessage		false	string

Download sample CSV file

GET /web/api/v2.1/nac/config/api/v1/nac/csv/export/sample

Returns a presigned URL to download a sample NAC rules CSV file for reference

Response Messages

200 - Sample file URL generated successfully

400 - Bad Request

401 - Unauthorized

403 - Forbidden

404 - Not Found

405 - Method Not Allowed

409 - Conflict

415 - Unsupported Media Type

422 - Unprocessable Content

429 - Too Many Requests

500 - Internal server error

Response Schema

Name	Description	Required	Value
expiresAt		false	integer
url		false	string

Application Control - Settings and Labels

Get NAC settings

GET /web/api/v2.1/nac/config/api/v1/nac/settings

Retrieves NAC Application Control settings for the given scope or default settings

Parameters

scopeid	optional	Scope ID
scopetype	optional	Scope type (ACCOUNT, SITE, GROUP)

Response Messages

200 - Settings retrieved successfully

400 - Invalid scope parameters

401 - Unauthorized

403 - Forbidden

404 - Not Found

405 - Method Not Allowed

409 - Conflict

415 - Unsupported Media Type

422 - Unprocessable Content

429 - Too Many Requests

500 - Internal server error

Response Schema

Name	Description	Required	Value
enableApplicationControl	Whether NAC is enabled	false	boolean
fallbackBehavior	Default behavior	false	enum
inheritApplicationControl	Whether settings are inherited	false	boolean

Update NAC settings

PUT /web/api/v2.1/nac/config/api/v1/nac/settings

Updates or creates NAC Application Control settings for the given scope

Response Messages

200 - Settings updated successfully

400 - Validation error or invalid request

401 - Unauthorized

403 - Forbidden

404 - Not Found

405 - Method Not Allowed

409 - Conflict

415 - Unsupported Media Type

422 - Unprocessable Content

429 - Too Many Requests

500 - Internal server error

Response Schema

Name	Description	Required	Value
id	Resource ID	false	string
statusCode	Status code	false	integer
statusMessage	Status message	false	string
success	Whether the request was successful	false	boolean
validationErrors	Validation errors	false	undefined []

Body Schema

Name	Description	Required	Value
enableApplicationControl	Whether NAC is enabled	false	boolean
fallbackBehavior	Default behavior	false	enum
inheritApplicationControl	Whether settings are inherited	false	boolean
scope	Scope selector as JSON	false	see Update NAC settings - body - scope table

Update NAC settings - body - scope

Name	Description	Required	Value
scopelds	Scope IDs	false	string []
scopeType	Scope type	false	enum

Get all NAC labels

GET /web/api/v2.1/nac/config/api/v1/nac/labels

Retrieves all available labels for NAC rules

Response Messages

200 - Labels retrieved successfully

400 - Bad Request

401 - Unauthorized

403 - Forbidden

404 - Not Found

405 - Method Not Allowed

409 - Conflict

415 - Unsupported Media Type

422 - Unprocessable Content

429 - Too Many Requests

500 - Internal server error

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

id	Label ID	false	string
labelName	Label name	false	string

Application Management

Get CVE data

GET /web/api/v2.1/application-management/risks

Get the CVE vulnerability data for each CVE.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
analystverdict	optional	Include Default(not edited)/ False Positives / Added CVEs for Vulnerabilities. Example: "Default,False Positive,Added CVE".
application__contains	optional	Free-text filter by application name and version (supports multiple values). Example: "Office 1.1,Test".
applicationnames	optional	Included application names. Example: "Office 1.1,Test".
applicationvendor__contains	optional	Free-text filter by vendor (supports multiple values). Example: "Microsoft,Apple".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
cveid__contains	optional	Free-text filter by CVE id (supports multiple values). Example: "CVE-1234-5678".
daysfromcvedetection	optional	Days from CVE detection, e.g. 12 days or more. Example: "12".
detectiondate__between	optional	Date range for CVE detection date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
detectiondate__gt	optional	CVE detection date after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__gte	optional	CVE detection date after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".

detectiondate__lt	optional	CVE detection date before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lte	optional	CVE detection date before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
domain__contains	optional	Free-text filter by domain (supports multiple values). Example: "mybusiness,workgroup".
domains	optional	Included network domains. Example: "mybusiness,workgroup".
endpointname__contains	optional	Free-text filter by endpoint name (supports multiple values). Example: "Office,Test".
endpointtypes	optional	Included endpoint types
exploitcodematurity	optional	Included exploit code maturity values. Available for Singularity Vulnerability Management SKU. Example: "FUNCTIONAL,HIGH".
exploitedinthewild	optional	Included exploited in the wild values. Available for Singularity Vulnerability Management SKU. Example: "EXPLOITED_UNKNOWN,YES".
groupids	optional	Single Group ID to filter by. Example: "225494730938493804".
includeremovals	optional	Include also removed CVEs in the results
lastscanresults	optional	Included last scan results. Example: "Succeeded".
limit	optional	Limit number of returned items (1-1000). Example: "10".
mitigationstatus	optional	Filters by the application's mitigation status values. Available for Singularity Vulnerability Management SKU. Example: "Not mitigated,To be patched,On hold".
ostypes	optional	Included OS types
osversions	optional	Included OS versions
publisheddate__between	optional	Date range for CVE publish date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
publisheddate__gt	optional	CVE published date after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
publisheddate__gte	optional	CVE published date after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
publisheddate__lt	optional	CVE published date before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
publisheddate__lte	optional	CVE published date before or at this timestamp. Example:

		"2018-02-27T04:49:26.257525Z".
remediationlevels	optional	Included remediation level values. Available for Singularity Vulnerability Management SKU. Example: "OFFICIAL_FIX,TEMPORARY_FIX".
reportconfidence	optional	Included report confidence values. Available for Singularity Vulnerability Management SKU. Example: "REASONABLE,CONFIRMED".
riskscore__between	optional	Risk score (inclusive). Available for Singularity Vulnerability Management SKU. Example: "5-8.9".
riskupdateddate__between	optional	Significant CVE updates within this date range(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
riskupdateddate__gt	optional	Significant CVE updates after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
riskupdateddate__gte	optional	Significant CVE updates after or at this timestamp. Recommended for fetching delta-changes. Example: "2018-02-27T04:49:26.257525Z".
riskupdateddate__lt	optional	Significant CVE updates before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
riskupdateddate__lte	optional	Significant CVE updates before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
severities	optional	Included severities. Example: "CRITICAL,HIGH".
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
vendors	optional	Included vendors. Example: "Microsoft,Apple".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get CVE data - response - pagination table
data	Response data	false	see Get CVE data - response - data table
errors	Errors	false	array

Get CVE data - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get CVE data - response - data

Name	Description	Required	Value
application	Composed application name	false	string
applicationName	Application name	false	string
applicationVendor	Application vendor	false	string
applicationVersion	Application version	false	string
baseScore	Not available with Singularity Vulnerability Management SKU	false	string
cveId	CVE Id	false	string
cvssVersion	Cvss version	false	string
daysDetected	Days detected	false	integer
detectionDate	Detection date	false	string
endpointId	Endpoint id	false	string
endpointName	Endpoint name	false	string
endpointType	Endpoint type	false	string
exploitCodeMaturity	Available for Singularity Vulnerability Management SKU	false	enum
id	Id	false	string
lastScanDate	Last scan date	false	string
lastScanResult	Last scan result	false	string
markedBy	Marked by	false	string

markedDate	Marked date	false	string
markType	Mark type	false	
mitigationStatus	Risk mitigation status	false	enum
mitigationStatusChangedBy	Mitigation status changer	false	string
mitigationStatusChangeTime	Mitigation status change time	false	string
mitigationStatusReason	Mitigation status reason	false	string
nvdBaseScore	Available for Singularity Vulnerability Management SKU	false	string
nvdCvssVersion	Available for Singularity Vulnerability Management SKU	false	string
osType	OS type	false	enum
publishedDate	Published date	false	string
reason	Reason	false	string
remediationLevel	Available for Singularity Vulnerability Management SKU	false	enum
reportConfidence	Available for Singularity Vulnerability Management SKU	false	enum
riskScore	Available for Singularity Vulnerability Management SKU	false	string
severity	Severity	false	string
status	Risk status	false	enum

Risks Data Export

GET /web/api/v2.1/application-management/risks/export/csv

Export risks data to CSV.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
analystverdict	optional	Include Default(not edited)/ False Positives / Added CVEs for Vulnerabilities. Example: "Default,False Positive,Added CVE".
application__contains	optional	Free-text filter by application name and version (supports multiple values). Example: "Office 1.1,Test".
applicationnames	optional	Included application names. Example: "Office 1.1,Test".

applicationvendor__contains	optional	Free-text filter by vendor (supports multiple values). Example: "Microsoft,Apple".
csvdelimiter	optional	"Optionally specify character to be used as CSV delimiter. Defaults to ";". Example: ";".
cveid__contains	optional	Free-text filter by CVE id (supports multiple values). Example: "CVE-1234-5678".
daysfromcvedetection	optional	Days from CVE detection, e.g. 12 days or more. Example: "12".
detectiondate__between	optional	Date range for CVE detection date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
detectiondate__gt	optional	CVE detection date after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__gte	optional	CVE detection date after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lt	optional	CVE detection date before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lte	optional	CVE detection date before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
domain__contains	optional	Free-text filter by domain (supports multiple values). Example: "mybusiness,workgroup".
domains	optional	Included network domains. Example: "mybusiness,workgroup".
endpointname__contains	optional	Free-text filter by endpoint name (supports multiple values). Example: "Office,Test".
endpointtypes	optional	Included endpoint types
exploitcodematurity	optional	Included exploit code maturity values. Available for Singularity Vulnerability Management SKU. Example: "FUNCTIONAL,HIGH".
exploitedinthewild	optional	Included exploited in the wild values. Available for Singularity Vulnerability Management SKU. Example: "EXPLOITED_UNKNOWN,YES".
groupids	optional	Single Group ID to filter by. Example: "225494730938493804".
includeremovals	optional	Include also removed CVEs in the results
lastscanresults	optional	Included last scan results. Example: "Succeeded".
mitigationstatus	optional	Filters by the application's mitigation status values.Available for Singularity Vulnerability Management SKU. Example: "Not

		mitigated,To be patched,On hold".
ostypes	optional	Included OS types
osversions	optional	Included OS versions
publisheddate__between	optional	Date range for CVE publish date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
publisheddate__gt	optional	CVE published date after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
publisheddate__gte	optional	CVE published date after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
publisheddate__lt	optional	CVE published date before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
publisheddate__lte	optional	CVE published date before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
remediationlevels	optional	Included remediation level values. Available for Singularity Vulnerability Management SKU. Example: "OFFICIAL_FIX,TEMPORARY_FIX".
reportconfidence	optional	Included report confidence values. Available for Singularity Vulnerability Management SKU. Example: "REASONABLE,CONFIRMED".
riskscore__between	optional	Risk score (inclusive). Available for Singularity Vulnerability Management SKU. Example: "5-8.9".
riskupdateddate__between	optional	Significant CVE updates within this date range(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
riskupdateddate__gt	optional	Significant CVE updates after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
riskupdateddate__gte	optional	Significant CVE updates after or at this timestamp. Recommended for fetching delta-changes. Example: "2018-02-27T04:49:26.257525Z".
riskupdateddate__lt	optional	Significant CVE updates before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
riskupdateddate__lte	optional	Significant CVE updates before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
severities	optional	Included severities. Example: "CRITICAL,HIGH".

siteids	optional	Single Site ID to filter by. Example: "225494730938493804".
vendors	optional	Included vendors. Example: "Microsoft,Apple".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Initiate scan

POST /web/api/v2.1/application-management/scan

Initiate application vulnerability scan.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Initiate scan - response - data table
errors	Errors	false	array

Initiate scan - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Initiate scan - body - filter table

Initiate scan - body - filter

Name	Description	Required	Value
accountIds	Single Account ID to filter by	false	string []
siteIds	Single Site ID to filter by	false	string []
tenant	if the entire tenant scope should be filtered	false	boolean

Get Application Inventory

GET /web/api/v2.1/application-management/inventory

Get application inventory data grouped by application name and vendor.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
endpointname__contains	optional	Free-text filter by endpoint name (supports multiple values). Example: "Office,Test".
endpointuuid__contains	optional	Free-text filter by endpoint uuid (supports multiple values)
groupids	optional	Single Group ID to filter by. Example: "225494730938493804".
limit	optional	Limit number of returned items (1-1000). Example: "10".
name__contains	optional	Free-text filter by application name (supports multiple values). Example: "Office,Test".
osarchitectures	optional	Included OS architectures
ostypes	optional	Included OS types
osversion__contains	optional	Free-text filter by os version (supports multiple values). Example: "Windows 7 ServicePack1".

osversions	optional	Included OS versions
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
vendor__contains	optional	Free-text filter by vendor (supports multiple values). Example: "Microsoft,Apple".
vendors	optional	Included vendors. Example: "Microsoft,Apple".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Application Inventory - response - pagination table
data	Response data	false	see Get Application Inventory - response - data table
errors	Errors	false	array

Get Application Inventory - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Application Inventory - response - data

Name	Description	Required	Value
applicationName	Name	false	string
applicationVendor	Vendor	false	string
applicationVersionsCount	Application versions count	false	integer
endpointsCount	Endpoints count	false	integer
estimate	Estimate	false	boolean

Inventory Data Export

GET /web/api/v2.1/application-management/inventory/export/csv

Export application inventory data to CSV.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
csvdelimiter	optional	"Optionally specify character to be used as CSV delimiter. Defaults to ";". Example: ";".
endpointname__contains	optional	Free-text filter by endpoint name (supports multiple values). Example: "Office,Test".
endpointuuid__contains	optional	Free-text filter by endpoint uuid (supports multiple values)

groupids	optional	Single Group ID to filter by. Example: "225494730938493804".
name__contains	optional	Free-text filter by application name (supports multiple values). Example: "Office,Test".
osarchitectures	optional	Included OS architectures
ostypes	optional	Included OS types
osversion__contains	optional	Free-text filter by os version (supports multiple values). Example: "Windows 7 ServicePack1".
osversions	optional	Included OS versions
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".
vendor__contains	optional	Free-text filter by vendor (supports multiple values). Example: "Microsoft,Apple".
vendors	optional	Included vendors. Example: "Microsoft,Apple".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Get App Inventory Endpoints

GET /web/api/v2.1/application-management/inventory/endpoints

Get endpoint data for a specific application.

Parameters

applicationname	required	Name
applicationvendor	required	Vendor
accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.

cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
detectiondate__between	optional	Date range for application detection date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
detectiondate__gt	optional	Application detection date after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__gte	optional	Application detection date after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lt	optional	Application detection date before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lte	optional	Application detection date before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
endpointname__contains	optional	Free-text filter by endpoint name (supports multiple values). Example: "Office,Test".
endpointuuid__contains	optional	Free-text filter by endpoint uuid (supports multiple values)
groupids	optional	Single Group ID to filter by. Example: "225494730938493804".
limit	optional	Limit number of returned items (1-1000). Example: "10".
osarchitectures	optional	Included OS architectures
ostypes	optional	Included OS types
osversions	optional	Included OS versions
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
versions	optional	Included application versions

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get App Inventory Endpoints - response - pagination table
data	Response data	false	see Get App Inventory Endpoints - response - data table
errors	Errors	false	array

Get App Inventory Endpoints - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get App Inventory Endpoints - response - data

Name	Description	Required	Value
accountName	Account name	false	string
applicationInstallationDate	Application installation date	false	string
applicationInstallationPath	Application installation path	false	string
applicationName	Application name	false	string
coreCount	Core count	false	integer
cpe	Cpe	false	
cpuCount	Cpu count	false	integer
detectionDate	Detection date	false	string
endpointId	Endpoint id	false	string
endpointName	Endpoint name	false	string
endpointType	Endpoint type	false	string
endpointUuid	Endpoint uuid	false	string
fileSize	File size	false	integer
groupName	Group name	false	string
id	Id	false	string
osArch	Os arch	false	string
osName	Os name	false	string
osType	OS type	false	enum

osVersion	Os version	false	string
siteName	Site name	false	string
version	Version	false	string

Inventory Endpoints Data Export

GET /web/api/v2.1/application-management/inventory/endpoints/export/csv

Export application inventory endpoints data to CSV.

Parameters

applicationname	required	Name
applicationvendor	required	Vendor
accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
csvdelimiter	optional	"Optionally specify character to be used as CSV delimiter. Defaults to ','. Example: ','.
detectiondate__between	optional	Date range for application detection date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
detectiondate__gt	optional	Application detection date after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__gte	optional	Application detection date after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lt	optional	Application detection date before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lte	optional	Application detection date before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
endpointname__contains	optional	Free-text filter by endpoint name (supports multiple values). Example: "Office,Test".
endpointuuid__contains	optional	Free-text filter by endpoint uuid (supports multiple values)
groupids	optional	Single Group ID to filter by. Example: "225494730938493804".
osarchitectures	optional	Included OS architectures
ostypes	optional	Included OS types

osversions	optional	Included OS versions
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".
versions	optional	Included application versions

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Get Application CVEs

GET /web/api/v2.1/application-management/risks/cves

Get CVE data for a specific application. Use applicationIds query parameter to include a single application id (required). For Ranger Insights license users, either use the applicationIds query parameter that can include multiple application IDs, or the applicationName and applicationVendors query parameters.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
analystverdict	optional	Include Default(not edited)/ False Positives / Added CVEs for Vulnerabilities. Example: "Default,False Positive,Added CVE".
applicationids	optional	Included application versions by id. Example: "225494730938493804,225494730938493915".
applicationname	optional	Application name
applicationvendor	optional	Application vendor
applicationversions	optional	Included application versions
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
cveid__contains	optional	Free-text filter by CVE id (supports multiple values). Example:

		"CVE-1234-5678".
exploitcodematurity	optional	Included exploit code maturity values. Available with Ranger Insights. Example: "FUNCTIONAL,HIGH".
exploitedinthewild	optional	Included exploited in the wild values. Available with Ranger Insights. Example: "EXPLOITED_UNKNOWN,YES".
groupids	optional	Single Group ID to filter by. Example: "225494730938493804".
limit	optional	Limit number of returned items (1-1000). Example: "10".
publisheddate__between	optional	Date range for CVE publish date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
publisheddate__gt	optional	CVE published date after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
publisheddate__gte	optional	CVE published date after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
publisheddate__lt	optional	CVE published date before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
publisheddate__lte	optional	CVE published date before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
remediationlevels	optional	Included remediation level values. Available with Ranger Insights. Example: "OFFICIAL_FIX,TEMPORARY_FIX".
reportconfidence	optional	Included report confidence values. Available with Ranger Insights. Example: "REASONABLE,CONFIRMED".
severities	optional	Included severities. Example: "CRITICAL,HIGH".
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Application CVEs - response - pagination table
data	Response data	false	see Get Application CVEs - response - data table
errors	Errors	false	array

Get Application CVEs - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Application CVEs - response - data

Name	Description	Required	Value
cveId	Cve id	false	string
cvssVersion	Cvss version	false	string
description	Description	false	
exploitCodeMaturity	Available with Ranger Insights	false	enum
exploitedInTheWild	Available with Ranger Insights	false	enum
fpFnMarks	Fp fn marks	false	see Get Application CVEs - response - fpFnMarks table
mitreUrl	Mitre url	false	
nvdBaseScore	Nvd base score	false	string
nvdUrl	Nvd url	false	
publishedDate	Published date	false	string
remediationLevel	Available with Ranger Insights	false	enum
reportConfidence	Available with Ranger Insights	false	enum
riskScore	Available with Ranger Insights	false	string
severity	Severity	false	

Get Application CVEs - response - fpFnMarks

Name	Description	Required	Value
------	-------------	----------	-------

markedOnScope		true	see Get Application CVEs - response - markedOnScope table
markedBy		false	string
markedDate		false	string
reason		false	string
type		false	

Get Application CVEs - response - markedOnScope

Name	Description	Required	Value
id		false	string
name		false	string
type		false	string

Application CVE Data Export

GET /web/api/v2.1/application-management/risks/cves/export/csv

Export CVE data to CSV. Use applicationIds query parameter to include a single application id (required). For Ranger Insights license users, either use the applicationIds query parameter that can include multiple application IDs, or the applicationName and applicationVendors query parameters.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
analystverdict	optional	Include Default(not edited)/ False Positives / Added CVEs for Vulnerabilities. Example: "Default,False Positive,Added CVE".
applicationids	optional	Included application versions by id. Example: "225494730938493804,225494730938493915".
applicationname	optional	Application name
applicationvendor	optional	Application vendor
applicationversions	optional	Included application versions
csvdelimiter	optional	"Optionally specify character to be used as CSV delimiter. Defaults to ",". Example: ",".
cveid__contains	optional	Free-text filter by CVE id (supports multiple values). Example: "CVE-1234-5678".

exploitcodematurity	optional	Included exploit code maturity values. Available with Ranger Insights. Example: "FUNCTIONAL,HIGH".
exploitedinthewild	optional	Included exploited in the wild values. Available with Ranger Insights. Example: "EXPLOITED_UNKNOWN,YES".
groupids	optional	Single Group ID to filter by. Example: "225494730938493804".
publisheddate__between	optional	Date range for CVE publish date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
publisheddate__gt	optional	CVE published date after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
publisheddate__gte	optional	CVE published date after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
publisheddate__lt	optional	CVE published date before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
publisheddate__lte	optional	CVE published date before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
remediationlevels	optional	Included remediation level values. Available with Ranger Insights. Example: "OFFICIAL_FIX,TEMPORARY_FIX".
reportconfidence	optional	Included report confidence values. Available with Ranger Insights. Example: "REASONABLE,CONFIRMED".
severities	optional	Included severities. Example: "CRITICAL,HIGH".
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Get Aggregated Applications With Risk

GET /web/api/v2.1/application-management/risks/aggregated-applications

Get data for all applications. Available with Ranger Insights license.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
applicationtypes	optional	Application type. Available with Ranger Insights. Example: "A,p,p,l,i,c,a,t,i,o,n".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
cveid__contains	optional	Free-text filter by CVE id (supports multiple values). Example: "CVE-1234-5678".
daysfromdetection	optional	Days from application detection, e.g. 12 days or more. Example: "12".
detectiondate__between	optional	Date range for application detection date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
detectiondate__gt	optional	Application detection date after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__gte	optional	Application detection date after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lt	optional	Application detection date before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lte	optional	Application detection date before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
domains	optional	Included domains.
endpointname__contains	optional	Free-text filter by endpoint name (supports multiple values). Example: "Office,Test".
endpointtypes	optional	Included endpoint types. Example: "desktop,laptop".
endpointuuid__contains	optional	Free-text filter by endpoint uuid (supports multiple values)
exploitcodematurity	optional	Included exploit code maturity values. Available with Ranger Insights. Example: "Functional,High".

exploitedinthewild	optional	Included exploited in the wild values. Available with Ranger Insights. Example: "Unknown,Yes".
groupids	optional	Single Group ID to filter by. Example: "225494730938493804".
highestseverities	optional	Included highest severities. Example: "CRITICAL,HIGH".
limit	optional	Limit number of returned items (1-1000). Example: "10".
mostcommonstatuses	optional	Included most common status values. Available with Ranger Insights.
name__contains	optional	Free-text filter by application name (supports multiple values). Example: "Office 1.1,Test".
ostypes	optional	Included OS types. Example: "windows,linux".
remediationlevels	optional	Included remediation level values. Available with Ranger Insights. Example: "Official Fix,Temporary Fix".
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
vendor__contains	optional	Free-text filter by vendor (supports multiple values). Example: "Microsoft,Apple".
vendors	optional	Included vendors. Example: "Microsoft,Apple".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

pagination	Pagination information	true	see Get Aggregated Applications With Risk - response - pagination table
data	Response data	false	see Get Aggregated Applications With Risk - response - data table
errors	Errors	false	array

Get Aggregated Applications With Risk - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Aggregated Applications With Risk - response - data

Name	Description	Required	Value
applicationType	Application type	false	string
cveCount	Cve count	false	integer
daysDetected	Days detected	false	
detectionDate	Detection date	false	string
endpointCount	Endpoint count	false	integer
endpointsWithoutTicket	Number of endpoints that are in an integrated scope, but don't have a ticket created. Available with Ranger Insights.	false	integer
estimate	Estimate	false	boolean
exploitCodeMaturity	Exploit code maturity	false	enum
exploitedInTheWild	Exploited in the wild	false	enum
highestNvdBaseScore	Highest nvd base score	false	string
highestRiskScore	Highest risk score	false	string
highestSeverity	Highest severity	false	string
name	Name	false	string
remediationLevel	Remediation level	false	enum
statuses	Statuses	false	see Get Aggregated Applications With Risk - response - statuses table
vendor	Vendor	false	string

versionCount	Version count	false	integer
--------------	---------------	-------	---------

Get Aggregated Applications With Risk - response - statuses

Name	Description	Required	Value
count	Count	false	integer
key	Key	false	
label	Label	false	
ticketCategory	Ticket category	false	string

Aggregated Application Risk Data Export

GET /web/api/v2.1/application-management/risks/aggregated-applications/export/csv

Export aggregated application data to CSV. Available with Ranger Insights license.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
applicationtypes	optional	Application type. Available with Ranger Insights. Example: "A,p,p,l,i,c,a,t,i,o,n".
csvdelimiter	optional	"Optionally specify character to be used as CSV delimiter. Defaults to ','. Example: ','.
cveid__contains	optional	Free-text filter by CVE id (supports multiple values). Example: "CVE-1234-5678".
daysfromdetection	optional	Days from application detection, e.g. 12 days or more. Example: "12".
detectiondate__between	optional	Date range for application detection date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
detectiondate__gt	optional	Application detection date after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__gte	optional	Application detection date after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lt	optional	Application detection date before this timestamp. Example:

		"2018-02-27T04:49:26.257525Z".
detectiondate__lte	optional	Application detection date before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
domains	optional	Included domains.
endpointname__contains	optional	Free-text filter by endpoint name (supports multiple values). Example: "Office,Test".
endpointtypes	optional	Included endpoint types. Example: "desktop,laptop".
endpointuuid__contains	optional	Free-text filter by endpoint uuid (supports multiple values)
exploitcodematurity	optional	Included exploit code maturity values. Available with Ranger Insights. Example: "Functional,High".
exploitedinthewild	optional	Included exploited in the wild values. Available with Ranger Insights. Example: "Unknown,Yes".
groupids	optional	Single Group ID to filter by. Example: "225494730938493804".
highestseverities	optional	Included highest severities. Example: "CRITICAL,HIGH".
mostcommonstatuses	optional	Included most common status values. Available with Ranger Insights.
name__contains	optional	Free-text filter by application name (supports multiple values). Example: "Office 1.1,Test".
ostypes	optional	Included OS types. Example: "windows,linux".
remediationlevels	optional	Included remediation level values. Available with Ranger Insights. Example: "Official Fix,Temporary Fix".
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".
vendor__contains	optional	Free-text filter by vendor (supports multiple values). Example: "Microsoft,Apple".
vendors	optional	Included vendors. Example: "Microsoft,Apple".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Get Applications With Risk

GET /web/api/v2.1/application-management/risks/applications

Get data for each version of all applications.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
application__contains	optional	Free-text filter by application name and version (supports multiple values). Example: "Office 1.1,Test".
applicationtypes	optional	Application type. Available with Ranger Insights. Example: "A,p,p,l,i,c,a,t,i,o,n".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
cveid__contains	optional	Free-text filter by CVE id (supports multiple values). Example: "CVE-1234-5678".
daysfromdetection	optional	Days from application detection, e.g. 12 days or more. Example: "12".
detectiondate__between	optional	Date range for application detection date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
detectiondate__gt	optional	Application detection date after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__gte	optional	Application detection date after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lt	optional	Application detection date before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lte	optional	Application detection date before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
domains	optional	Included domains.
endpointname__contains	optional	Free-text filter by endpoint name (supports multiple values). Example: "Office,Test".

endpointtypes	optional	Included endpoint types. Example: "desktop,laptop".
endpointuuid__contains	optional	Free-text filter by endpoint uuid (supports multiple values)
exploitcodematurity	optional	Included exploit code maturity values. Available with Ranger Insights. Example: "Functional,High".
exploitedinthewild	optional	Included exploited in the wild values. Available with Ranger Insights. Example: "Unknown,Yes".
groupids	optional	Single Group ID to filter by. Example: "225494730938493804".
highestseverities	optional	Included highest severities. Example: "CRITICAL,HIGH".
limit	optional	Limit number of returned items (1-1000). Example: "10".
mostcommonstatuses	optional	Included most common status values. Available with Ranger Insights.
ostypes	optional	Included OS types. Example: "windows,linux".
remediationlevels	optional	Included remediation level values. Available with Ranger Insights. Example: "Official Fix,Temporary Fix".
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
vendor__contains	optional	Free-text filter by vendor (supports multiple values). Example: "Microsoft,Apple".
vendors	optional	Included vendors. Example: "Microsoft,Apple".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Applications With Risk - response - pagination table
data	Response data	false	see Get Applications With Risk - response - data table
errors	Errors	false	array

Get Applications With Risk - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Applications With Risk - response - data

Name	Description	Required	Value
applicationId	Application id	false	string
applicationType	Available with Ranger Insights.	false	string
cveCount	Cve count	false	integer
daysDetected	Days detected	false	
detectionDate	Detection date	false	string
endpointCount	Endpoint count	false	integer
endpointsWithoutTicket	Number of endpoints that are in an integrated scope, but don't have a ticket created. Available with Ranger Insights.	false	integer
estimate	Estimate	false	boolean
exploitCodeMaturity	Available with Ranger Insights.	false	enum
exploitedInTheWild	Available with Ranger Insights.	false	enum
highestNvdBaseScore	Highest nvd base score	false	string
highestRiskScore	Available with Ranger Insights.	false	string
highestSeverity	Highest severity	false	string
name	Name	false	string
remediationLevel	Available with Ranger Insights.	false	enum
statuses	Statuses	false	see Get Applications With Risk - response - statuses table

vendor	Vendor	false	string
--------	--------	-------	--------

Get Applications With Risk - response - statuses

Name	Description	Required	Value
count	Count	false	integer
key	Key	false	
label	Label	false	
ticketCategory	Ticket category	false	string

Application Risk Data Export

GET /web/api/v2.1/application-management/risks/applications/export/csv

Export application data to CSV.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
application__contains	optional	Free-text filter by application name and version (supports multiple values). Example: "Office 1.1,Test".
applicationtypes	optional	Application type. Available with Ranger Insights. Example: "A,p,p,l,i,c,a,t,i,o,n".
csvdelimiter	optional	"Optionally specify character to be used as CSV delimiter. Defaults to ",". Example: ",".
cveid__contains	optional	Free-text filter by CVE id (supports multiple values). Example: "CVE-1234-5678".
daysfromdetection	optional	Days from application detection, e.g. 12 days or more. Example: "12".
detectiondate__between	optional	Date range for application detection date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
detectiondate__gt	optional	Application detection date after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__gte	optional	Application detection date after or at this timestamp. Example:

		"2018-02-27T04:49:26.257525Z".
detectiondate__lt	optional	Application detection date before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lte	optional	Application detection date before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
domains	optional	Included domains.
endpointname__contains	optional	Free-text filter by endpoint name (supports multiple values). Example: "Office,Test".
endpointtypes	optional	Included endpoint types. Example: "desktop,laptop".
endpointuuid__contains	optional	Free-text filter by endpoint uuid (supports multiple values)
exploitcodematurity	optional	Included exploit code maturity values. Available with Ranger Insights. Example: "Functional,High".
exploitedinthewild	optional	Included exploited in the wild values. Available with Ranger Insights. Example: "Unknown,Yes".
groupids	optional	Single Group ID to filter by. Example: "225494730938493804".
highestseverities	optional	Included highest severities. Example: "CRITICAL,HIGH".
mostcommonstatuses	optional	Included most common status values. Available with Ranger Insights.
ostypes	optional	Included OS types. Example: "windows,linux".
remediationlevels	optional	Included remediation level values. Available with Ranger Insights. Example: "Official Fix,Temporary Fix".
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".
vendor__contains	optional	Free-text filter by vendor (supports multiple values). Example: "Microsoft,Apple".
vendors	optional	Included vendors. Example: "Microsoft,Apple".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Get Endpoints For Vulnerable App

GET /web/api/v2.1/application-management/risks/endpoints

Get a list of all endpoints installed with a specific application that contains vulnerabilities. Use applicationIds query parameter to include a single application id (required). For Ranger Insights license users, either use the applicationIds query parameter that can include multiple application IDs, or the applicationName and applicationVendors query parameters.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
applicationids	optional	Included application versions by id. Example: "225494730938493804,225494730938493915".
applicationname	optional	Application name
applicationvendor	optional	Application vendor
applicationversions	optional	Included application versions
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
daysfromdetection	optional	Days from application detection, e.g. 12 days or more. Example: "12".
daystomitigation__between	optional	Date range for days left to mitigation. Available with Ranger Insights when using ticket integration. Example: "1-30".
detectiondate__between	optional	Date range for application detection date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
detectiondate__gt	optional	Application detection date after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__gte	optional	Application detection date after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lt	optional	Application detection date before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lte	optional	Application detection date before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".

domain__contains	optional	Free-text filter by domain (supports multiple values). Example: "mybusiness,workgroup".
domains	optional	Included endpoint domains
endpointid__contains	optional	Free-text filter by endpoint id (supports multiple values)
endpointname__contains	optional	Free-text filter by endpoint name (supports multiple values). Example: "Office,Test".
endpointtypes	optional	Included endpoint types
endpointuuid__contains	optional	Free-text filter by endpoint uuid (supports multiple values)
groupids	optional	Single Group ID to filter by. Example: "225494730938493804".
lastscandate__between	optional	Date range for last scan date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
lastscandate__gt	optional	Last scan date after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastscandate__gte	optional	Last scan date after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastscandate__lt	optional	Last scan date before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastscandate__lte	optional	Last scan date before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastscanresults	optional	Included last scan results. Example: "Succeeded".
limit	optional	Limit number of returned items (1-1000). Example: "10".
ostypes	optional	Included OS types
osversions	optional	Included OS versions
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
statuses	optional	Included statuses. Available with Ranger Insights.

statusmessage__contains	optional	Free-text filter by status message (supports multiple values). Available with Ranger Insights. Example: "assigned to john,top priority".
ticketid__contains	optional	Free-text filter by ticket id. Available with Ranger Insights when using ticket integration. Example: "ABC-123,ABCD-100".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Endpoints For Vulnerable App - response - pagination table
data	Response data	false	see Get Endpoints For Vulnerable App - response - data table
errors	Errors	false	array

Get Endpoints For Vulnerable App - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Endpoints For Vulnerable App - response - data

Name	Description	Required	Value
accountName	Account name	false	string
applicationDaysDetected	Application days detected	false	
applicationDetectionDate	Detection date	false	string
applicationVersion	Version	false	string
domain	Domain	false	string
endpointId	Endpoint id	false	string
endpointName	Endpoint name	false	string
endpointType	Endpoint type	false	string
endpointUuid	Endpoint uuid	false	string
externalTicketSystem	External ticket system	false	see Get Endpoints For Vulnerable App - response - externalTicketSystem table
groupName	Group name	false	string
lastScanDate	Last scan date	false	string
lastScanResult	Last scan result	false	string
osType	OS type	false	enum
osVersion	Os version	false	string
siteName	Site name	false	string
statusHistory	Available with Ranger Insights	false	see Get Endpoints For Vulnerable App - response - statusHistory table
ticket	Ticket	false	see Get Endpoints For Vulnerable App - response - ticket table

Get Endpoints For Vulnerable App - response - externalTicketSystem

Name	Description	Required	Value
available	Available	false	boolean
type	Type	false	string

Get Endpoints For Vulnerable App - response - statusHistory

Name	Description	Required	Value
changedAt	Changed at	false	string
changedBy	Changed by	false	string
currentKey	Current key	false	string
currentLabel	Current label	false	enum
previousKey	Previous key	false	string
previousLabel	Previous label	false	enum
reason	Reason	false	string

Get Endpoints For Vulnerable App - response - ticket

Name	Description	Required	Value
analystReason	Analyst reason	false	string
assignee	Assignee	false	string
daysToMitigation	Days to mitigation	false	integer
endpointsCount	Endpoints count	false	integer
metaData	Meta data	false	object
name	Name	false	string
projectName	Project name	false	string
reporter	Reporter	false	string
status	Status	false	string
statusCategory	Status category	false	string
title	Title	false	string

url	Url	false	string
-----	-----	-------	--------

Risk Endpoint Data Export

GET /web/api/v2.1/application-management/risks/endpoints/export/csv

Export endpoint data to CSV. Use applicationIds query parameter to include a single application id (required). For Ranger Insights license users, either use the applicationIds query parameter that can include multiple application IDs, or the applicationName and applicationVendors query parameters.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
applicationids	optional	Included application versions by id. Example: "225494730938493804,225494730938493915".
applicationname	optional	Application name
applicationvendor	optional	Application vendor
applicationversions	optional	Included application versions
csvdelimiter	optional	"Optionally specify character to be used as CSV delimiter. Defaults to ','. Example: ','.
daysfromdetection	optional	Days from application detection, e.g. 12 days or more. Example: "12".
daystomitigation__between	optional	Date range for days left to mitigation. Available with Ranger Insights when using ticket integration. Example: "1-30".
detectiondate__between	optional	Date range for application detection date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
detectiondate__gt	optional	Application detection date after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__gte	optional	Application detection date after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lt	optional	Application detection date before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
detectiondate__lte	optional	Application detection date before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
domain__contains	optional	Free-text filter by domain (supports multiple values). Example: "mybusiness,workgroup".

domains	optional	Included endpoint domains
endpointid__contains	optional	Free-text filter by endpoint id (supports multiple values)
endpointname__contains	optional	Free-text filter by endpoint name (supports multiple values). Example: "Office,Test".
endpointtypes	optional	Included endpoint types
endpointuuid__contains	optional	Free-text filter by endpoint uuid (supports multiple values)
groupids	optional	Single Group ID to filter by. Example: "225494730938493804".
lastscandate__between	optional	Date range for last scan date(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
lastscandate__gt	optional	Last scan date after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastscandate__gte	optional	Last scan date after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastscandate__lt	optional	Last scan date before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastscandate__lte	optional	Last scan date before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastscanresults	optional	Included last scan results. Example: "Succeeded".
ostypes	optional	Included OS types
osversions	optional	Included OS versions
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".
statuses	optional	Included statuses. Available with Ranger Insights.
statusmessage__contains	optional	Free-text filter by status message (supports multiple values). Available with Ranger Insights. Example: "assigned to john,top priority".
ticketid__contains	optional	Free-text filter by ticket id. Available with Ranger Insights when using ticket integration. Example: "ABC-123,ABCD-100".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Get Endpoint Apps

GET /web/api/v2.1/application-management/inventory/applications

Get the installed applications for a specific endpoint.

To get the Agent ID, run "agents".

Parameters

ids	required	Agent ID list. Example: "225494730938493804,225494730938493915".
-----	----------	---

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Endpoint Apps - response - data table
errors	Errors	false	array

Get Endpoint Apps - response - data

Name	Description	Required	Value
installedDate	Installed date	false	string
name	Name	false	string
publisher	Publisher	false	string
size	Size	false	integer
version	Version	false	string

Application Management Settings

Update Application Management Settings

POST /web/api/v2.1/application-management/settings

Update Application Management Settings

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Application Management Settings - response - data table
errors	Errors	false	array

Update Application Management Settings - response - data

Name	Description	Required	Value
extensiveLinuxScanEnabled	Extensive linux scan enabled	false	boolean
extensiveScanEnabled	Extensive scan enabled	false	boolean
hasBreakingInheritance	Determines if settings are overridden on any descendant scope.	false	boolean
inheritedFrom	Inherited from	false	string
isDefaultPolicy	Determines if the policy is overridden on the scope level.	false	boolean
scanSchedule	Scan schedule configuration.	false	see Update Application Management Settings - response - scanSchedule table
vulnerabilitiesScanEnabled	Vulnerabilities scan enabled	false	boolean

Update Application Management Settings - response - scanSchedule

Name	Description	Required	Value
repeatOn	A day of the week	true	enum
scanEvery	Number of weeks between scans (must be between 1 and 4)	true	integer
time	Scan start time in 24-hour format	true	string
timezone	Timezone for the scan time	true	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Application Management Settings - body - data table
filter	Filter	true	see Update Application Management Settings - body - filter table

Update Application Management Settings - body - data

Name	Description	Required	Value
extensiveLinuxScanEnabled	Extensive linux scan enabled	false	boolean
extensiveScanEnabled	Extensive scan enabled	false	boolean
isDefaultPolicy	Determines if the policy is overridden on the scope level.	false	boolean
scanSchedule	Scan schedule configuration.	false	see Update Application Management Settings - body - scanSchedule table
vulnerabilitiesScanEnabled	Vulnerabilities scan enabled	false	boolean

Update Application Management Settings - body - scanSchedule

Name	Description	Required	Value
repeatOn	A day of the week	true	enum
scanEvery	Number of weeks between scans (must be between 1 and 4)	true	integer
time	Scan start time in 24-hour format	true	string
timezone	Timezone for the scan time	true	string

Update Application Management Settings - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Get Application Management Settings

GET /web/api/v2.1/application-management/settings

Get Application Management settings.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
groupids	optional	Single Group ID to filter by. Example: "225494730938493804".
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Application Management Settings - response - data table
errors	Errors	false	array

Get Application Management Settings - response - data

Name	Description	Required	Value
extensiveLinuxScanEnabled	Extensive linux scan enabled	false	boolean
extensiveScanEnabled	Extensive scan enabled	false	boolean
hasBreakingInheritance	Determines if settings are overridden on any descendant scope.	false	boolean
inheritedFrom	Inherited from	false	string
isDefaultPolicy	Determines if the policy is overridden on the scope level.	false	boolean
scanSchedule	Scan schedule configuration.	false	see Get Application Management Settings - response - scanSchedule table
vulnerabilitiesScanEnabled	Vulnerabilities scan enabled	false	boolean

Get Application Management Settings - response - scanSchedule

Name	Description	Required	Value
repeatOn	A day of the week	true	enum
scanEvery	Number of weeks between scans (must be between 1 and 4)	true	integer
time	Scan start time in 24-hour format	true	string
timezone	Timezone for the scan time	true	string

Application Risk

Export Applications

GET /web/api/v2.1/export/installed-applications

Export the list of applications installed on endpoints with Application Risk-enabled Agents and their properties, including the CVEs for each application that requires a patch. The CSV file is stored on the Management. Application Risk requires Complete SKU. This feature is in EA. To join the EA program, contact your SentinelOne Sales Rep.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
agentcomputername__contains	optional	Free-text filter by computer name (supports multiple values). Example: "john-office,WIN".
agentisdecommissioned	optional	Include active agents, decommissioned or both. Example: "True,False".
agentmachinetypes	optional	Filter by endpoint machine types. Example: "unknown".
agentmachinetypesnin	optional	Filter not by endpoint machine types. Example: "unknown".
agentosversion__contains	optional	Free-text filter by OS full name and version (supports multiple values). Example: "Service Pack 1".
agentuuid__contains	optional	Free-text filter by agent UUID (supports multiple values). Example: "e92-01928,b055".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	Filter by application IDs. Example: "225494730938493804,225494730938493915".
installedat__between	optional	Filter by installation date range
name__contains	optional	Free-text filter by application name (supports multiple values). Example: "calc".
ostypes	optional	Filter by OS types. Example: "linux".
ostypesnin	optional	Filter not by OS types. Example: "linux".
publisher__contains	optional	Free-text filter by application publisher (supports multiple values). Example: "Sentinel".
risklevels	optional	Filter by risk. Example: "none".
risklevelsnin	optional	Filter not by risk. Example: "none".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
size__between	optional	Filter by application size range (bytes). Example: "1024-104856".
types	optional	Filter by application types. Example: "app".
typesnin	optional	Filter not by application types. Example: "app".
version__contains	optional	Free-text filter by application version (supports multiple values). Example: "1.22.333,build".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Application Risk (Deprecated)

[DEPRECATED] Get Applications

GET /web/api/v2.1/installed-applications

Get the applications, and their data (such as risk level), installed on endpoints with Application Risk-enabled Agents that match the filter. SentinelOne Application Risk lets you monitor applications installed on endpoints. Applications not updated with the latest patches are vulnerable to exploits. With SentinelOne Application Risk you can see all applications to be patched, on all endpoints or on a specific endpoint. The Agent takes a snapshot of the endpoint application data and checks for vulnerabilities in the SentinelOne Cloud. When the Agent detects a change to the application data, it sends a diff to the Management.

Application Risk requires Complete SKU. This feature is in EA. To join the EA program, contact your SentinelOne Sales Rep.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
agentcomputername__contains	optional	Free-text filter by computer name (supports multiple values). Example: "john-office,WIN".
agentisdecommissioned	optional	Include active agents, decommissioned or both. Example: "True,False".
agentmachinetypes	optional	Filter by endpoint machine types. Example: "unknown".
agentmachinetypesnin	optional	Filter not by endpoint machine types. Example: "unknown".
agentosversion__contains	optional	Free-text filter by OS full name and version (supports multiple values). Example: "Service Pack 1".
agentuuid__contains	optional	Free-text filter by agent UUID (supports multiple values). Example: "e92-01928,b055".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.

cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	Filter by application IDs. Example: "225494730938493804,225494730938493915".
installedat__between	optional	Filter by installation date range
limit	optional	Limit number of returned items (1-1000). Example: "10".
name__contains	optional	Free-text filter by application name (supports multiple values). Example: "calc".
ostypes	optional	Filter by OS types. Example: "linux".
ostypesnin	optional	Filter not by OS types. Example: "linux".
publisher__contains	optional	Free-text filter by application publisher (supports multiple values). Example: "Sentinel".
risklevels	optional	Filter by risk. Example: "none".
risklevelsnin	optional	Filter not by risk. Example: "none".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
size__between	optional	Filter by application size range (bytes). Example: "1024-104856".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
types	optional	Filter by application types. Example: "app".
typesnin	optional	Filter not by application types. Example: "app".
version__contains	optional	Free-text filter by application version (supports multiple values). Example: "1.22.333,build".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see [DEPRECATED] Get Applications - response - pagination table
data	Response data	false	see [DEPRECATED] Get Applications - response - data table
errors	Errors	false	array

[DEPRECATED] Get Applications - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

[DEPRECATED] Get Applications - response - data

Name	Description	Required	Value
agentComputerName	Agent computer name	false	string
agentDomain	Agent domain	false	string
agentId	Agent id	false	string
agentInfected	Agent infected	false	boolean
agentIsActive	Agent is active	false	boolean
agentIsDecommissioned	Agent is decommissioned	false	boolean
agentMachineType	Agent machine type	false	enum
agentNetworkStatus	Agent network status	false	enum
agentOperationalState	Agent operational state	false	string
agentOsType	OS type	false	enum
agentUuid	Agent uuid	false	string
agentVersion	Agent version	false	string
createdAt	Created at	false	string
id	Application ID	false	string
installedAt	Installed at	false	string
name	Name	false	string
osType	OS type	false	enum
publisher	Publisher	false	string

riskLevel	Risk level	false	enum
signed	Signed	false	boolean
size	Application size (bytes)	false	integer
type	Type	false	enum
updatedAt	Updated at	false	string
version	Version	false	string

[DEPRECATED] Get CVEs

GET /web/api/v2.1/installed-applications/cves

Get known CVEs for applications that are installed on endpoints with Application Risk-enabled Agents. Application Risk requires Complete SKU. This feature is in EA. To join the EA program, contact your SentinelOne Sales Rep.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
applicationids	optional	Filter by application IDs. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__gt	optional	Created at greater than. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Created at greater or equal than. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Created at lesser than. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Created at lesser or equal than. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
cveids	optional	Filter by global CVE ids. Example: "CVE-2018-3182,CVE-2018-1087".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".

ids	optional	Filter by internal CVE IDs. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
updatedat__gt	optional	Updated at greater than. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Updated at greater or equal than. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Updated at lesser than. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Updated at lesser or equal than. Example: "2018-02-27T04:49:26.257525Z".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see [DEPRECATED] Get CVEs - response - pagination table
data	Response data	false	see [DEPRECATED] Get CVEs - response - data table
errors	Errors	false	array

[DEPRECATED] Get CVEs - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

[DEPRECATED] Get CVEs - response - data

Name	Description	Required	Value
createdAt	Created at	false	string
cveId	Global CVE ID	false	string
description	Description	false	string
id	Id	false	string
link	Link	false	string
publishedAt	Published at	false	string
riskLevel	Risk level	false	enum
score	Score	false	number
updatedAt	Updated at	false	string

Auto Upgrade Policy

All Policies OS Count

GET /web/api/v2.1/upgrade-policy/all-policies-count

Get the number of all policies for each OS from the given scope and the inherited scopes

Parameters

scopelevel	required	Scope level, one of 'account', 'group', 'site' or 'tenant'
scopeid	optional	Scope ID

Response Messages

200 - Success

400 - Bad request

Response Schema

Name	Description	Required	Value
linux		false	integer
macos		false	integer
windows		false	integer

Get Available Packages

GET /web/api/v2.1/upgrade-policy/available-packages

Get Available Packages

Parameters

ostype	required	OS type, one of 'linux', 'macos' or 'windows'
scopelevel	required	Scope level, one of 'account', 'group', 'site' or 'tenant'
displayname__contains	optional	Partially match the name of the package, e.g. '22.1 GA'
scopeid	optional	Scope ID

Response Messages

200 - Success

400 - Bad request

Response Schema

Name	Description	Required	Value
data		false	see Get Available Packages - response - data table

Get Available Packages - response - data

Name	Description	Required	Value
packages		false	undefined []

Has Policy

POST /web/api/v2.1/upgrade-policy/has-policy

Has policy

Response Messages

200 - Success

400 - Bad request

Response Schema

Name	Description	Required	Value
hasPolicies		false	boolean

Body Schema

Name	Description	Required	Value
groups	List of Group IDs to filter by. Example: '225494730938493804,225494730938493915'.	false	string []
osType	OS type, one of 'linux', 'macos' or 'windows'	false	string

Get Parent Policies

GET /web/api/v2.1/upgrade-policy/parent-policies

Get paginated and ordered parent policies by a given scope

Parameters

limit	required	Limit number of returned items. Should be more than 1. Example: '10'.
ostype	required	OS type, one of 'linux', 'macos' or 'windows'
scopelevel	required	Scope level, one of 'account', 'group', 'site' or 'tenant'
skip	required	Skip first number of items. Example: '0'.
sortby	required	The column to sort the results by. Example: 'priority'.
sortorder	required	Sort direction. Could be 'asc' or 'desc'.
scopeid	optional	Scope ID

Response Messages

200 - Success

400 - Bad request

Response Schema

Name	Description	Required	Value
data		false	see Get Parent Policies - response - data table
pagination		false	see Get Parent Policies - response - pagination table

Get Parent Policies - response - data

Name	Description	Required	Value
isInherited		false	boolean
policies		false	undefined []
policiesInChildScope		false	boolean

Get Parent Policies - response - pagination

Name	Description	Required	Value
totalItems		false	integer

Get Policies

GET /web/api/v2.1/upgrade-policy/policies

Get paginated and ordered policies by a given scope

Parameters

limit	required	Limit number of returned items. Should be more than 1. Example: '10'
ostype	required	OS type, one of 'linux', 'macos' or 'windows'
scopelevel	required	Scope level, one of 'account', 'group', 'site' or 'tenant'
skip	required	Skip first number of items. Example: '0'.
sortby	required	The column to sort the results by. Example: 'priority'.
sortorder	required	Sort direction. Could be 'asc' or 'desc'.
scopeid	optional	Scope ID

Response Messages

200 - Success

400 - Bad request

Response Schema

Name	Description	Required	Value
data		false	see Get Policies - response - data table
pagination		false	see Get Policies - response - pagination table

Get Policies - response - data

Name	Description	Required	Value
isInherited		false	boolean
policies		false	undefined []
policiesInChildScope		false	boolean

Get Policies - response - pagination

Name	Description	Required	Value
totalItems		false	integer

Deactivate Policies

POST /web/api/v2.1/upgrade-policy/policies

Deactivate all policies

Parameters

ostype	required	OS type, one of 'linux', 'macos' or 'windows'
scopelevel	required	Scope level, one of 'account', 'group', 'site' or 'tenant'
scopeid	optional	Scope ID

Response Messages

200 - Success

400 - Bad request

Response Schema

Name	Description	Required	Value
response		false	string

Policies OS Count

GET /web/api/v2.1/upgrade-policy/policies-count

Get the number of policies for each OS, for a given scope level and id

Parameters

scopelevel	required	Scope level, one of 'account', 'group', 'site' or 'tenant'
scopeid	optional	Scope ID

Response Messages

200 - Success

400 - Bad request

Response Schema

Name	Description	Required	Value
linux		false	integer
macos		false	integer
windows		false	integer

Create Policy

POST /web/api/v2.1/upgrade-policy/policy

Add policy

Response Messages

200 - Success

400 - Bad request

Response Schema

Name	Description	Required	Value
response		false	string

Body Schema

Name	Description	Required	Value
activatedAt		false	string
allEndpoints		false	boolean
createdAt		false	string
description		false	string
id		false	string
isActive		false	boolean
isScheduled		false	boolean
maxRetries		false	integer
name		false	string
osType		false	string
package		false	see Create Policy - body - package table
priority		false	integer
scopeld		false	string
scopeLevel		false	string
tags		false	string []
updatedAt		false	string

Create Policy - body - package

Name	Description	Required	Value
build		false	string
fileId		false	string
major		false	string
minor		false	string

Update Policy

PUT /web/api/v2.1/upgrade-policy/policy/{policyid}

Update existing policy

Response Messages

200 - Success

400 - Bad request

Response Schema

Name	Description	Required	Value
response		false	string

Body Schema

Name	Description	Required	Value
allEndpoints	Affected endpoints. 'true' if the policy is applied to all endpoints. If 'false', tags must be provided.	false	boolean
description	Policy description	false	string
isActive	'true' if policy is active, 'false' if policy is disabled	false	boolean
isScheduled	In case of maintenance window selected, scheduling an upgrade for maintenance window	false	boolean
maxRetries	Maximum number of upgrade retries for an endpoint in case of retrieable failure. If provided, it should be a positive integer. Defaults to 5.	false	integer
name	Policy name. This name will be used for creating tasks. Should be unique.	false	string
osType	OS type, one of 'linux', 'macos' or 'windows'	false	string
package		false	see Update Policy - body - package table
scopeId	Scope ID	false	string
scopeLevel	Scope level, one of 'account', 'group', 'site' or 'tenant'	false	string
tags	Tags for policy application. If provided, AllEndpoints should be false.	false	string []

Update Policy - body - package

Name	Description	Required	Value
build		false	string
fileId		false	string
major		false	string
minor		false	string

Policy Action

POST /web/api/v2.1/upgrade-policy/policy/{policyid}

Perform action on a certain policy

Response Messages

200 - Success

400 - Bad request

Response Schema

Name	Description	Required	Value
response		false	string

Body Schema

Name	Description	Required	Value
action	Policy action, one of 'delete', 'activate' or 'deactivate'	false	string

Reset Policy Retry Counter

PUT /web/api/v2.1/upgrade-policy/policy/{policyid}/reset-retry-counter

Reset the number of times an Agent upgrade will be retried if the original upgrade attempt fails.

Response Messages

200 - Success

400 - Bad request

Response Schema

Name	Description	Required	Value
response		false	string

Reorder Policies

PUT /web/api/v2.1/upgrade-policy/reorder

Reorder policies

Response Messages

200 - Success

400 - Bad request

Response Schema

Name	Description	Required	Value
response		false	string

Body Schema

Name	Description	Required	Value
policies	List of policy IDs and their new order. Example: { "id": "2ad5fdd3-7f9d-4969-9d52-3560fcb482fb", "order": 0, "id": "b448ed4e-545f-442d-ad20-624876e85e84", "order": 1. }	false	undefined []

Set Scope Inheriting

PUT /web/api/v2.1/upgrade-policy/set-inheriting

Set Scope Inheriting

Response Messages

200 - Success

400 - Bad request

Response Schema

Name	Description	Required	Value
response		false	string

Body Schema

Name	Description	Required	Value
isInheriting	True if policies are inherited from the higher scopes, false otherwise.	false	boolean
scopeId	Scope ID	false	string
scopeLevel	Scope level, one of 'account', 'group', 'site' or 'tenant'	false	string

Cloud Funnel

Validate Bucket

POST /web/api/v2.1/cloud-funnel/validate-bucket-permissions

Validates bucket permissions.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Validate Bucket - response - data table
errors	Errors	false	array

Validate Bucket - response - data

Name	Description	Required	Value
isValid	Bucket permissions is valid or invalid	true	boolean
error	Error message in case the bucket permissions is invalid	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Validate Bucket - body - data table

Validate Bucket - body - data

Name	Description	Required	Value
bucketUrl	Validate bucket permissions	true	string
accessKeyId	Access key id, for S3 compatible storages (e.g. R2)	false	string
accountId	Account id	false	string
cloudProvider	Cloud provider, default is aws	false	string
roleToAssume	The aws role to assume when using assume role functionality.Only applicable if cloud_provider is s3.	false	string
secretAccessKey	Secret access key, for S3 compatible storages (e.g. R2)	false	string
siteId	Site id	false	string
useAssumeRole	If set to true, activates the AWS AssumeRole functionality for accessing S3 buckets or other associated resources. Only applicable if cloud_provider is s3.	false	boolean

Get cloud funnel rule

GET /web/api/v2.1/cloud-funnel/onboarding

Gets cloud funnel onboarding rule details

Parameters

accountId	optional	Account id. Example: "225494730938493804".
siteId	optional	Site id. Example: "225494730938493804".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get cloud funnel rule - response - data table
errors	Errors	false	array

Get cloud funnel rule - response - data

Name	Description	Required	Value
bucketUrl	Bucket url	true	string
disableStream	disable events stream	true	boolean
accessKeyId	Access key id, for S3 compatible storages (e.g. R2)	false	string
accountOnboardingExists	For site scope, is account onboarding exists	false	boolean
assumeRoleExternalId	The AWS assume role external id.	false	string
cloudProvider	Cloud provider, default is aws	false	string
desiredFields	List of desired fields to be included in the output. If not specified, all fields are included.	false	string []
error	Error message in case the bucket permissions is invalid	false	string
globalOnboardingExists	Is global onboarding exists in table	false	boolean
id	log-archive-rule id, default for accounts: cloud-funnel	false	string
isInheriting	Is inheriting global setting	false	boolean
query	Sql query to validate	false	string
roleToAssume	The AWS role to assume when using assume role functionality. Only applicable if cloud_provider is s3.	false	string
secretAccessKey	Secret access key, for S3 compatible storages (e.g. R2)	false	string
useAssumeRole	If set to true, activates the AWS AssumeRole functionality for accessing S3 buckets or other associated resources. Only applicable if cloud_provider is s3.	false	boolean

Delete cloud funnel rule

DELETE /web/api/v2.1/cloud-funnel/onboarding

Deletes cloud funnel onboarding rule.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete cloud funnel rule - response - data table
errors	Errors	false	array

Delete cloud funnel rule - response - data

Name	Description	Required	Value
error	Error message in case the bucket permissions is invalid	true	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Delete cloud funnel rule - body - data table

Delete cloud funnel rule - body - data

Name	Description	Required	Value
accountId	Account id	false	string
siteIds	Site ids	false	string []

Post onboarding cloud funnel

POST /web/api/v2.1/cloud-funnel/onboarding

Post onboarding cloud funnel rule.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Post onboarding cloud funnel - response - data table
errors	Errors	false	array

Post onboarding cloud funnel - response - data

Name	Description	Required	Value
bucketUrl	Bucket url	true	string
disableStream	disable events stream	true	boolean
accessKeyId	Access key id, for S3 compatible storages (e.g. R2)	false	string
accountOnboardingExists	For site scope, is account onboarding exists	false	boolean
assumeRoleExternalId	The AWS assume role external id.	false	string
cloudProvider	Cloud provider, default is aws	false	string
desiredFields	List of desired fields to be included in the output. If not specified, all fields are included.	false	string []
error	Error message in case the bucket permissions is invalid	false	string
globalOnboardingExists	Is global onboarding exists in table	false	boolean
id	log-archive-rule id, default for accounts: cloud-funnel	false	string
isInheriting	Is inheriting global setting	false	boolean
query	Syql query to validate	false	string
roleToAssume	The AWS role to assume when using assume role functionality. Only applicable if cloud_provider is s3.	false	string
secretAccessKey	Secret access key, for S3 compatible storages (e.g. R2)	false	string
useAssumeRole	If set to true, activates the AWS AssumeRole functionality for accessing S3 buckets or other associated resources. Only applicable if cloud_provider is s3.	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Post onboarding cloud funnel - body - data table

Post onboarding cloud funnel - body - data

Name	Description	Required	Value
accessKeyId	Access key id, for S3 compatible storages (e.g. R2)	false	string
accountId	Account id	false	string
bucketUrl	bucket url	false	string
cloudProvider	Cloud provider, default is aws	false	string
desiredFields	List of desired fields to be included in the output. If not specified, all fields are included.	false	string []
disableStream	disable events stream	false	boolean
isInheriting	Is inheriting global setting	false	boolean
query	Syql query to validate	false	string
roleToAssume	The aws role to assume when using assume role functionality.Only applicable if cloud_provider is s3.	false	string
secretAccessKey	Secret access key, for S3 compatible storages (e.g. R2)	false	string
siteIds	Site ids	false	string []
useAssumeRole	If set to true, activates the AWS AssumeRole functionality for accessing S3 buckets or other associated resources. Only applicable if cloud_provider is s3.	false	boolean

Validate Query

POST /web/api/v2.1/cloud-funnel/validate-query

Verifies that a query is valid before using it as filterfor a Cloud Funnel onboarding

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Validate Query - response - data table
errors	Errors	false	array

Validate Query - response - data

Name	Description	Required	Value
error	Error message in case the query is invalid	true	string
isValid	Query is valid or invalid	true	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Validate Query - body - data table

Validate Query - body - data

Name	Description	Required	Value
query	Validate query	true	string

Create Estimator ID

POST /web/api/v2.1/cloud-funnel/estimator

Create estimator ID. This is needed to run the API "Get Estimate Size Of Events".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Estimator ID - response - data table
errors	Errors	false	array

Create Estimator ID - response - data

Name	Description	Required	Value
estimatorId	Estimator query id.	true	string
error	Error message in case the estimator query is invalid	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Estimator ID - body - data table

Create Estimator ID - body - data

Name	Description	Required	Value
accountIds	Account ids	false	string []
desiredFields	List of desired fields to be included in the output. If not specified, all fields are included.	false	string []
query	Query	false	string
siteIds	Site ids	false	string []

Get estimate size of events

GET /web/api/v2.1/cloud-funnel/estimator

Get estimate size of events in the bucket. You need the estimator ID which can be generated by running the API: "Create Estimator ID".

Parameters

estimatorid	required	Estimator query id.
-------------	----------	---------------------

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get estimate size of events - response - data table
errors	Errors	false	array

Get estimate size of events - response - data

Name	Description	Required	Value
isCompleted	Is estimator query status is completed.	true	boolean
compressedBytes	Estimation of compressed size.	false	string
error	Error message in case the estimator query failed	false	string
matchingEvents	Estimation of events number. string to avoid round	false	string
uncompressedBytes	Estimation of uncompressed size.	false	string

Get AWS assume role external ID.

GET /web/api/v2.1/cloud-funnel/assume-role-external-id

Get the AWS assume role external ID.

Parameters

accountid	optional	Account id. Example: "225494730938493804".
siteid	optional	Site id. Example: "225494730938493804".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get AWS assume role external ID. - response - data table
errors	Errors	false	array

Get AWS assume role external ID. - response - data

Name	Description	Required	Value
assumeRoleExternalId	The AWS assume role external id.	true	string

Cloud Resources

Get cloud rogue resources

GET /web/api/v2.1/cloudnative/cloud-rogues

Returns the cloud rogue resources for given filter

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
cloudprovideraccountid__contains	optional	Free-text filter by cloud account id (supports multiple values)
cloudprovideraccountname	optional	Filter by cloud account (supports multiple values)
cloudprovideraccountname__contains	optional	Free-text filter by cloud account (supports multiple values)
cloudprovidername	optional	Filter by cloud provider name (supports multiple values)
concatenatedtags__contains	optional	Free-text filter by tags (supports multiple values)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
id__contains	optional	Free-text filter by id (supports multiple values)

imageid__contains	optional	Free-text filter by image (supports multiple values)
limit	optional	Limit number of returned items (1-1000). Example: "10".
name__contains	optional	Free-text filter by resource name (supports multiple values)
ostypes	optional	Included OS types
region	optional	Filter by region (supports multiple values)
region__contains	optional	Free-text filter by region (supports multiple values)
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
virtualnetworkid__contains	optional	Free-text filter by network id (supports multiple values)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get cloud rogue resources - response - pagination table
data	Response data	false	see Get cloud rogue resources - response - data table
errors	Errors	false	array

Get cloud rogue resources - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get cloud rogue resources - response - data

Name	Description	Required	Value
resources	Resources	false	see Get cloud rogue resources - response - resources table

Get cloud rogue resources - response - resources

Name	Description	Required	Value
cloudProviderAccountId		false	string
cloudProviderAccountName		false	string
cloudProviderName		false	string
cloudProviderOrganization		false	string
concatenatedTags		false	string
createdTime		false	string
id	Cloud Resource ID	false	string
imageId		false	string
internalResourceType		false	string
name		false	string
osType		false	string
osTypeIcon		false	string
region		false	string

resourceType		false	string
tags		false	
virtualNetworkId		false	string

Export cloud rogue resources to csv (default) or json

GET /web/api/v2.1/cloudnative/cloud-rogues/export

Returns the results for given cloud rogues filter in a csv (default) or json format

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
cloudprovideraccountid__contains	optional	Free-text filter by cloud account id (supports multiple values)
cloudprovideraccountname	optional	Filter by cloud account (supports multiple values)
cloudprovideraccountname__contains	optional	Free-text filter by cloud account (supports multiple values)
cloudprovidername	optional	Filter by cloud provider name (supports multiple values)
concatenatedtags__contains	optional	Free-text filter by tags (supports multiple values)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
exportformat	optional	Export format. Example: "csv".
id__contains	optional	Free-text filter by id (supports multiple values)
imageid__contains	optional	Free-text filter by image (supports multiple values)
limit	optional	Limit number of returned items (1-1000). Example: "10".
name__contains	optional	Free-text filter by resource name (supports multiple values)
ostypes	optional	Included OS types
region	optional	Filter by region (supports multiple values)

region__contains	optional	Free-text filter by region (supports multiple values)
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
virtualnetworkid__contains	optional	Free-text filter by network id (supports multiple values)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Config Overrides

Get Config Overrides

GET /web/api/v2.1/config-override

There are different ways to override the configuration of an Agent, and the priority of changes depends on the endpoint OS and the version of the installed Agent. Use this command to see the configuration values that are changed for each Agent that matches the filter.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
agentids	optional	List of Agent IDs to filter by. Example: "225494730938493804,225494730938493915".

agentversions	optional	Included agent versions. Example: "2.5.1.1320".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdat__gt	optional	Config Overrides created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Config Overrides created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Config Overrides created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Config Overrides created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
description__like	optional	Match description partially (substring)
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of ids to filter by. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".
name__like	optional	Match name partially (substring)
ostypes	optional	Included OS types. Example: "linux".
query	optional	Free text search on fields name, description, agent_version, os_type, config
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".

sortorder	optional	Sort direction. Example: "asc".
tenant	optional	Indicates a tenant scope request
versionoption	optional	Version option. Example: "ALL".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Config Overrides - response - pagination table
data	Response data	false	see Get Config Overrides - response - data table
errors	Errors	false	array

Get Config Overrides - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Config Overrides - response - data

Name	Description	Required	Value
description	Description	true	string
name	Name	true	string
account	Account	false	see Get Config Overrides - response - account table
agent	Agent	false	see Get Config Overrides - response - agent table
agentVersion	Agent version	false	string
config	Config	false	object
createdAt	Created at	false	string
group	Group	false	see Get Config Overrides - response - group table
id	Id	false	string
osType	OS type	false	enum
scope	Scope level	false	enum
site	Site	false	see Get Config Overrides - response - site table
updatedAt	Updated at	false	string
versionOption	Version option	false	enum

Get Config Overrides - response - account

Name	Description	Required	Value
------	-------------	----------	-------

id	Id	true	string
name	Name	false	string

Get Config Overrides - response - agent

Name	Description	Required	Value
id	Id	true	string

Get Config Overrides - response - group

Name	Description	Required	Value
id	Id	true	string
name	Name	false	string

Get Config Overrides - response - site

Name	Description	Required	Value
id	Id	true	string
name	Name	false	string

Create Config Override

POST /web/api/v2.1/config-override

Override the configuration of Agents that match the filter. Best practice: Run "support-actions/config" to get the complete syntax. This command requires a Global user or Support.

BEST PRACTICE

Run "support-actions/config" to get the complete syntax. This command requires a Global user or Support.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

404 - Scope not found.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Config Override - response - data table
errors	Errors	false	array

Create Config Override - response - data

Name	Description	Required	Value
description	Description	true	string
name	Name	true	string
account	Account	false	see Create Config Override - response - account table
agent	Agent	false	see Create Config Override - response - agent table
agentVersion	Agent version	false	string
config	Config	false	object
createdAt	Created at	false	string
group	Group	false	see Create Config Override - response - group table
id	Id	false	string
osType	OS type	false	enum
scope	Scope level	false	enum
site	Site	false	see Create Config Override - response - site table
updatedAt	Updated at	false	string
versionOption	Version option	false	enum

Create Config Override - response - account

Name	Description	Required	Value
id	Id	true	string
name	Name	false	string

Create Config Override - response - agent

Name	Description	Required	Value
id	Id	true	string

Create Config Override - response - group

Name	Description	Required	Value
id	Id	true	string
name	Name	false	string

Create Config Override - response - site

Name	Description	Required	Value
id	Id	true	string
name	Name	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Config Override - body - data table
filter	Filter	false	see Create Config Override - body - filter table

Create Config Override - body - data

Name	Description	Required	Value
name	Name	true	string
osType	OS type	true	enum
scope	Scope level	true	enum
account	Config override will apply to all agents in the account. This should be used with scope = 'account'	false	see Create Config Override - body - account table
agentVersion	Agent version	false	string
config	Config	false	object
description	Description	false	string
group	Config override will apply to all agents in the group. This should be used with scope = 'group'	false	see Create Config Override - body - group table
site	Config override will apply to all agents in the site. This should be used with scope = 'site'	false	see Create Config Override - body - site table
versionOption	Version option	false	enum

Create Config Override - body - account

Name	Description	Required	Value
id	Id	true	string
name	Name	false	string

Create Config Override - body - group

Name	Description	Required	Value
id	Id	true	string
name	Name	false	string

Create Config Override - body - site

Name	Description	Required	Value
id	Id	true	string
name	Name	false	string

Create Config Override - body - filter

Delete Config Overrides

DELETE /web/api/v2.1/config-override

Delete overrides value. To get the required IDs, run "config-override".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Config Overrides - response - data table
errors	Errors	false	array

Delete Config Overrides - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Delete Config Overrides - body - filter table

Delete Config Overrides - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
agentIds	List of Agent IDs to filter by	false	string []
agentVersions	Included agent versions	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Config Overrides created after this timestamp	false	string
createdAt__gte	Config Overrides created after or at this timestamp	false	string
createdAt__lt	Config Overrides created before this timestamp	false	string
createdAt__lte	Config Overrides created before or at this timestamp	false	string
description__like	Match description partially (substring)	false	string
groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
name__like	Match name partially (substring)	false	string
osTypes	Included OS types	false	string []
query	Free text search on fields name, description, agent_version, os_type, config	false	string
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean
versionOption	Version option	false	enum

Delete Config Override

DELETE /web/api/v2.1/config-override/{override_id}

Delete an override value. To get the required ID, run "config-override".

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

404 - Override not found.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Config Override - response - data table
errors	Errors	false	array

Delete Config Override - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Update Config Override

PUT /web/api/v2.1/config-override/{override_id}

Use this command to change the value of one configuration value. To get the required ID, run "config-override".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions.

404 - Override not found.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Config Override - response - data table
errors	Errors	false	array

Update Config Override - response - data

Name	Description	Required	Value
description	Description	true	string
name	Name	true	string
account	Account	false	see Update Config Override - response - account table
agent	Agent	false	see Update Config Override - response - agent table
agentVersion	Agent version	false	string
config	Config	false	object
createdAt	Created at	false	string
group	Group	false	see Update Config Override - response - group table
id	Id	false	string
osType	OS type	false	enum
scope	Scope level	false	enum
site	Site	false	see Update Config Override - response - site table
updatedAt	Updated at	false	string
versionOption	Version option	false	enum

Update Config Override - response - account

Name	Description	Required	Value
id	Id	true	string
name	Name	false	string

Update Config Override - response - agent

Name	Description	Required	Value
id	Id	true	string

Update Config Override - response - group

Name	Description	Required	Value
id	Id	true	string
name	Name	false	string

Update Config Override - response - site

Name	Description	Required	Value
id	Id	true	string
name	Name	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Config Override - body - data table
filter	Filter	false	see Update Config Override - body - filter table

Update Config Override - body - data

Name	Description	Required	Value
account	Account	false	see Update Config Override - body - account table
agentVersion	Agent version	false	string
config	Config	false	object
description	Description	false	string
group	Group	false	see Update Config Override - body - group table
name	Name	false	string
osType	OS type	false	enum
scope	Scope level	false	enum
site	Site	false	see Update Config Override - body - site table
versionOption	Version option	false	enum

Update Config Override - body - account

Name	Description	Required	Value
id	Id	true	string
name	Name	false	string

Update Config Override - body - group

Name	Description	Required	Value
id	Id	true	string
name	Name	false	string

Update Config Override - body - site

Name	Description	Required	Value
------	-------------	----------	-------

id	Id	true	string
name	Name	false	string

Update Config Override - body - filter

Custom Detection Rule

Get Rules

GET /web/api/v2.1/cloud-detection/rules

Get a list of Custom Detection Rules for a given scope.

Note: You can create and see rules only for your highest available scope. For example, if your username has an access level of scope Account, you cannot see rules created for the Global scope or rules created for a specific Site.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
activeresponse	optional	The active response status for the rule.
attacksurfaces	optional	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.
categories	optional	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release. Example: "Events".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
creator__contains	optional	Free-text filter by rule creator. You can enter multiple values, separated by commas. Example: "Service Pack 1".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
description__contains	optional	Free-text filter by rule description. You can enter multiple values, separated by commas. Example: "Service Pack 1".

descriptionsubstring	optional	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.
disablepagination	optional	If True, all rules for the requested scope will be returned.
excludeids	optional	List of entity ids to exclude from select_all. Example: "225494730938493804,225494730938493915".
expirationmode	optional	The expiration mode. Example: "Permanent".
expired	optional	Rule expired or not.
filterby	optional	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release. Example: "Template".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
hidequery	optional	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release. Example: "Shown".
ids	optional	To filter by Rule ID, enter one or more Rule IDs, separated by commas. Example: "225494730938493804,225494730938493915".
includehiddenlogicrules	optional	If True and isLegacy is True, include rules whose logic is hidden. The query content will still be masked for non-privileged users.
includescheduledrules	optional	If True, includes scheduled rules. Requires isLegacy=false.
islegacy	optional	If True, alertsCount will be retrieved from Star and not from UAM.
labels	optional	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.
limit	optional	Limit number of returned items (1-1000). Example: "10".
mitretactics	optional	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.
name__contains	optional	Free-text filter by rule name. You can enter multiple values, separated by commas. Example: "Service Pack 1".
namesubstring	optional	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.
platformruleids	optional	platform rule ids. Example: "225494730938493804,225494730938493915".
query	optional	Free-text filter by S1 query. You can enter multiple values, separated by commas. Example: "Service Pack 1".
querytype	optional	Enter a list of query types. Example: "events".

reachedlimit	optional	Rule reached limit or not.
s1ql__contains	optional	Free-text filter by S1 query. You can enter multiple values, separated by commas. Example: "Service Pack 1".
s1qlsubstring	optional	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.
scopeid	optional	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release. Example: "225494730938493804".
scopelevel	optional	To filter by scope, enter one or more scopes, separated by commas. Example: "group".
scopes	optional	To filter by scope, enter one or more scopes, separated by commas. Example: "group".
severities	optional	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release. Example: "Info".
severity	optional	To filter by severity, enter one or more severities, separated by commas. Example: "Info".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
sources	optional	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.
status	optional	To filter by status, enter one or more statuses, separated by commas. Example: "Draft".
statuses	optional	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release. Example: "Activating".
tags	optional	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Rules - response - pagination table
data	Response data	false	see Get Rules - response - data table
errors	Errors	false	array

Get Rules - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Rules - response - data

Name	Description	Required	Value
expirationMode	Whether the rule is Temporary or Permanent.	true	enum
name	The name of the custom detection rule.	true	string
severity	The rule severity in your environment.	true	enum
status	Enabled (Activated and sends alerts if triggered) or Disabled.	true	enum
accountId	The account ID.	false	string
accountName	The name of the account.	false	string
activeResponse	The Active Response status of the Rule.	false	boolean
coolOffSettings	Receive only one alert and suppress additional alerts when a rule is triggered multiple times during the cool-off period. Mitigation actions set in the rule will not be applied to suppressed alerts.	false	see Get Rules - response - coolOffSettings table
correlationParams	Correlation params	false	see Get Rules - response - correlationParams table
createdAt	The date the rule was created.	false	string
creator	The full name of the user that created the rule.	false	string

creatorId	The ID of the user that created the rule.	false	string
description	The description of the custom detection rule.	false	string
editable	True if the rule can be modified at this scope level.	false	boolean
enrichment	Enrichment	false	see Get Rules - response - enrichment table
entityMappings	List of OCSF entity mappings to associate alerts with specific assets.	false	see Get Rules - response - entityMappings table
expiration	If Temporary, the expiration date for the rule.	false	string
expired	True if the Rule has expired.	false	boolean
generatedAlerts	The number of alerts that have been generated for the Rule.	false	integer
hideLogic	If true, this rule's logic is hidden from non-privileged users.	false	boolean
id	Rule ID	false	string
lastAlertTime	The time of the last alert for the Rule.	false	string
networkQuarantine	True if the network quarantine is on.	false	boolean
queryLang	The s1ql version query language of the rule. Can be 1.0 or 2.0.	false	enum
queryType	The query type - Correlation (made of multiple subqueries), Event (single query).	false	enum
reachedLimit	True if the Rule reached the 5k/hour or 10k/day alert limit. If the limit has been reached, the Rule is disabled.	false	boolean
s1ql	The query.	false	string
scheduledParams	Scheduled params	false	see Get Rules - response - scheduledParams table
scope	The scope of the rule. Can be Global, Account, Site, or Group.	false	enum
scopeId	The Account, Site, or Group ID, depending on the scope. Null if the scope is Global.	false	string []
siteId	The site ID.	false	string
siteName	The name of the site.	false	string
source	The source of the rule. Present for	false	enum

	Detection-as-Code managed rules.		
statusReason	The reason why the Rule has its current status.	false	string
templateRuleId	Rule Id of template rule from which this rule was created.	false	
treatAsThreat	The Treat as threat auto response - UNDEFINED/suspicious/malicious	false	enum
updatedAt	The date the rule was last updated.	false	string
updateId	The ID of the user that last updated the rule.	false	string

Get Rules - response - coolOffSettings

Name	Description	Required	Value
renotifyMinutes	The period of time in minutes in which alerts will be suppressed after the rule has been triggered.	true	integer

Get Rules - response - correlationParams

Name	Description	Required	Value
entity	A common entity used to group matching events.	true	enum
matchInOrder	Set to True to require subqueries to match in sequence to trigger an alert.	true	boolean
subQueries	The list of subqueries for the custom detection rule.	false	see Get Rules - response - subQueries table
timeWindow	The period of time in minutes in which subqueries must match to trigger an alert.	false	see Get Rules - response - timeWindow table

Get Rules - response - subQueries

Name	Description	Required	Value
------	-------------	----------	-------

matchesRequired	The number of times a subquery must match.	true	integer
subQuery	A subquery	true	string

Get Rules - response - timeWindow

Name	Description	Required	Value
windowMinutes	The period of time in minutes in which subqueries must match to trigger an alert.	false	enum

Get Rules - response - enrichment

Name	Description	Required	Value
creator	The ID of the user that created the Rule.	false	string
scopeName	scope id	false	string
updater	The ID of the user that last updated the Rule.	false	string

Get Rules - response - entityMappings

Name	Description	Required	Value
assetProperty	Asset unique identifier property (e.g., device_uuid, hostname_fqdn for Endpoint; ad_id, aad_id, sid, domain_username, upn for Identity; aws_arn, azure_resource_id, entra_id_object_id, gcp_resource_name, gcp_iam_user for Cloud)	true	string
assetSurface	Asset surface: Endpoint, Cloud, or Identity	true	enum
columnName	Unique case insensitive column name from PowerQuery table result	false	string

	(required for Scheduled rules)		
--	--------------------------------	--	--

Get Rules - response - scheduledParams

Name	Description	Required	Value
lookbackWindowMinutes	Sets the evaluation lookback window in minutes. For example, set to 5 evaluates the alert over the past five minutes.	true	integer
query	The PowerQuery to run	true	string
runIntervalMinutes	How often the alert is evaluated, in minutes. If used with coolOffSettings then it must be a denominator of renotifyMinutes. If the lookbackWindowMinutes is less than 60 (1 hour), the minimum is 1 minute. For a window between 1 and 360 (6 hours), 5 minutes. For a window between 360 (6 hours) and 10080 (7 days), 15 minutes. For a window between 10080 (7 days) and 43200 (30 days), 60 minutes.	true	integer
alertPerRow	If True, an alert will be generated for each row detected in the defined lookback window. If False (default), get one alert for all detected events matched in the defined lookback window.	false	boolean
disableStreaksLogic	If True (default), disables streak counting logic for scheduled rules. If False, streak counting logic is enabled.	false	boolean
threshold	Receive an alert only if the number of rows in the result of the query matches the condition in the threshold	false	see Get Rules - response - threshold table

Get Rules - response - threshold

Name	Description	Required	Value
operator	Defines the operator to use in combination with the query and thresholdValue to set the threshold condition for an alert to trigger The default value is Greater	false	enum
value	Defines the threshold value that in combination with operator and the query sets the threshold condition for an alert to be triggered. The default value is 0	false	integer

Create Rule

POST /web/api/v2.1/cloud-detection/rules

Create a Custom Detection Rule for a scope specified by ID. To get the ID, run "accounts", "sites", "groups", or set "tenant" to "true" for Global.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Rule - response - data table
errors	Errors	false	array

Create Rule - response - data

Name	Description	Required	Value
expirationMode	Whether the rule is Temporary or Permanent.	true	enum
name	The name of the custom detection rule.	true	string
severity	The rule severity in your environment.	true	enum
status	Enabled (Activated and sends alerts if triggered) or Disabled.	true	enum
coolOffSettings	Receive only one alert and suppress additional alerts when a rule is triggered multiple times during the cool-off period. Mitigation actions set in the rule will not be applied to suppressed alerts.	false	see Create Rule - response - coolOffSettings table
correlationParams	Correlation params	false	see Create Rule - response - correlationParams table
createdAt	The date the rule was created.	false	string
creator	The full name of the user that created the rule.	false	string
creatorId	The ID of the user that created the rule.	false	string
description	The description of the custom detection rule.	false	string
editable	True if the rule can be modified at this scope level.	false	boolean
entityMappings	List of OCSF entity mappings to associate alerts with specific assets.	false	see Create Rule - response - entityMappings table
expiration	If Temporary, the expiration date for the rule.	false	string
expired	True if the Rule has expired.	false	boolean
hideLogic	If true, this rule's logic is hidden from non-privileged users.	false	boolean
id	Rule ID	false	string
networkQuarantine	True if the network quarantine is on.	false	boolean

queryLang	The s1ql version query language of the rule. Can be 1.0 or 2.0.	false	enum
queryType	The query type - Correlation (made of multiple subqueries), Event (single query).	false	enum
reachedLimit	True if the Rule reached the 5k/hour or 10k/day alert limit. If the limit has been reached, the Rule is disabled.	false	boolean
s1ql	The query.	false	string
scheduledParams	Scheduled params	false	see Create Rule - response - scheduledParams table
scope	The scope of the rule. Can be Global, Account, Site, or Group.	false	enum
scopeId	The Account, Site, or Group ID, depending on the scope. Null if the scope is Global.	false	string []
statusReason	The reason why the Rule has its current status.	false	string
templateRuleId	Rule Id of template rule from which this rule was created.	false	
treatAsThreat	The Treat as threat auto response - UNDEFINED/suspicious/malicious	false	enum
updatedAt	The date the rule was last updated.	false	string
updaterId	The ID of the user that last updated the rule.	false	string

Create Rule - response - coolOffSettings

Name	Description	Required	Value
renotifyMinutes	The period of time in minutes in which alerts will be suppressed after the rule has been triggered.	true	integer

Create Rule - response - correlationParams

Name	Description	Required	Value
------	-------------	----------	-------

entity	A common entity used to group matching events.	true	enum
matchInOrder	Set to True to require subqueries to match in sequence to trigger an alert.	true	boolean
subQueries	The list of subqueries for the custom detection rule.	false	see Create Rule - response - subQueries table
timeWindow	The period of time in minutes in which subqueries must match to trigger an alert.	false	see Create Rule - response - timeWindow table

Create Rule - response - subQueries

Name	Description	Required	Value
matchesRequired	The number of times a subquery must match.	true	integer
subQuery	A subquery	true	string

Create Rule - response - timeWindow

Name	Description	Required	Value
windowMinutes	The period of time in minutes in which subqueries must match to trigger an alert.	false	enum

Create Rule - response - entityMappings

Name	Description	Required	Value
assetProperty	Asset unique identifier property (e.g., device_uuid, hostname_fqdn for Endpoint; ad_id, aad_id, sid, domain_username, upn for Identity; aws_arn, azure_resource_id, entra_id_object_id, gcp_resource_name, gcp_iam_user for Cloud)	true	string

assetSurface	Asset surface: Endpoint, Cloud, or Identity	true	enum
columnName	Unique case insensitive column name from PowerQuery table result (required for Scheduled rules)	false	string

Create Rule - response - scheduledParams

Name	Description	Required	Value
lookbackWindowMinutes	Sets the evaluation lookback window in minutes. For example, set to 5 evaluates the alert over the past five minutes.	true	integer
query	The PowerQuery to run	true	string
runIntervalMinutes	How often the alert is evaluated, in minutes. If used with coolOffSettings then it must be a denominator of renotifyMinutes. If the lookbackWindowMinutes is less than 60 (1 hour), the minimum is 1 minute. For a window between 1 and 360 (6 hours), 5 minutes. For a window between 360 (6 hours) and 10080 (7 days), 15 minutes. For a window between 10080 (7 days) and 43200 (30 days), 60 minutes.	true	integer
alertPerRow	If True, an alert will be generated for each row detected in the defined lookback window. If False (default), get one alert for all detected events matched in the defined lookback window.	false	boolean
disableStreaksLogic	If True (default), disables streak counting logic for scheduled rules. If False, streak counting logic is enabled.	false	boolean
threshold	Receive an alert only if the number of rows in the result of the query matches the condition in the threshold	false	see Create Rule - response - threshold table

Create Rule - response - threshold

Name	Description	Required	Value
operator	Defines the operator to use in combination with the query and thresholdValue to set the threshold condition for an alert to trigger The default value is Greater	false	enum
value	Defines the threshold value that in combination with operator and the query sets the threshold condition for an alert to be triggered. The default value is 0	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Rule - body - data table
filter	Filter	true	see Create Rule - body - filter table

Create Rule - body - data

Name	Description	Required	Value
expirationMode	Defines the rule as Permanent or Temporary.	true	enum
name	The name of the custom detection rule.	true	string
queryType	Define the query type: Correlation (made of multiple subqueries), Event (single query).	true	enum
severity	The rule severity in your environment.	true	enum
status	Defines the rule is Enabled (Activated and sends alerts if triggered) or Disabled.	true	enum
coolOffSettings	Receive only one alert and suppress additional alerts when a rule is triggered multiple times during the cool-off period. Mitigation actions set in the rule will not be applied to suppressed alerts.	false	see Create Rule - body - coolOffSettings table
correlationParams	Correlation params	false	see Create Rule - body - correlationParams table
description	A description of the custom detection rule.	false	string
entityMappings	List of OCSF entity mappings to associate alerts with specific assets.	false	see Create Rule - body - entityMappings table
expiration	If the rule is Temporary, enter the expiration date for the rule.	false	string
hideLogic	If true, hide this rule logic from non-privileged users.	false	boolean
id	Rule ID	false	string
networkQuarantine	Set to True to automatically quarantine the alerted endpoints.	false	boolean
queryLang	Defines the s1ql version query language of the rule - 1.0 or 2.0.	false	enum
s1ql	The query	false	string
scheduledParams	Scheduled params	false	see Create Rule - body - scheduledParams table

templateRuleId	Rule Id of template rule from which this rule was created.	false	string
treatAsThreat	Defines the Treat as a threat auto response. Undefined, Suspicious, or Malicious.	false	enum

Create Rule - body - coolOffSettings

Name	Description	Required	Value
renotifyMinutes	The period of time in minutes in which alerts will be suppressed after the rule has been triggered.	true	integer

Create Rule - body - correlationParams

Name	Description	Required	Value
entity	A common entity used to group matching events.	true	enum
matchInOrder	Set to True to require subqueries to match in sequence to trigger an alert.	true	boolean
subQueries	The list of subqueries for the custom detection rule.	false	see Create Rule - body - subQueries table
timeWindow	The period of time in minutes in which subqueries must match to trigger an alert.	false	see Create Rule - body - timeWindow table

Create Rule - body - subQueries

Name	Description	Required	Value
matchesRequired	The number of times a subquery must match.	true	integer
subQuery	A subquery	true	string

Create Rule - body - timeWindow

Name	Description	Required	Value
windowMinutes	The period of time in minutes in which subqueries must match to trigger an alert.	false	enum

Create Rule - body - entityMappings

Name	Description	Required	Value
assetProperty	Asset unique identifier property (e.g., device_uuid, hostname_fqdn for Endpoint; ad_id, aad_id, sid, domain_username, upn for Identity; aws_arn, azure_resource_id, entra_id_object_id, gcp_resource_name, gcp_iam_user for Cloud)	true	string
assetSurface	Asset surface: Endpoint, Cloud, or Identity	true	enum
columnName	Unique case insensitive column name from PowerQuery table result (required for Scheduled rules)	false	string

Create Rule - body - scheduledParams

Name	Description	Required	Value
lookbackWindowMinutes	Sets the evaluation lookback window in minutes. For example, set to 5 evaluates the alert over the past five minutes.	true	integer
query	The PowerQuery to run	true	string
runIntervalMinutes	How often the alert is evaluated, in minutes. If used with coolOffSettings then it must be a denominator of renotifyMinutes. If the lookbackWindowMinutes is less than 60 (1 hour), the minimum is 1 minute. For a window between 1 and 360 (6 hours), 5 minutes. For a window	true	integer

	between 360 (6 hours) and 10080 (7 days), 15 minutes. For a window between 10080 (7 days) and 43200 (30 days), 60 minutes.		
alertPerRow	If True, an alert will be generated for each row detected in the defined lookback window. If False (default), get one alert for all detected events matched in the defined lookback window.	false	boolean
disableStreaksLogic	If True (default), disables streak counting logic for scheduled rules. If False, streak counting logic is enabled.	false	boolean
threshold	Receive an alert only if the number of rows in the result of the query matches the condition in the threshold	false	see Create Rule - body - threshold table

Create Rule - body - threshold

Name	Description	Required	Value
operator	Defines the operator to use in combination with the query and thresholdValue to set the threshold condition for an alert to trigger The default value is Greater	false	enum
value	Defines the threshold value that in combination with operator and the query sets the threshold condition for an alert to be triggered. The default value is 0	false	integer

Create Rule - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []

sitelds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Delete Rules

DELETE /web/api/v2.1/cloud-detection/rules

Deletes Custom Detection Rules that match a filter.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Rules - response - data table
errors	Errors	false	array

Delete Rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Delete Rules - body - filter table

Delete Rules - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeResponse	The active response status for the rule.	false	boolean
attackSurfaces	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
categories	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
creator__contains	Free-text filter by rule creator. You can enter multiple values, separated by commas.	false	string []
description__contains	Free-text filter by rule description. You can enter multiple values, separated by commas.	false	string []
descriptionSubstring	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string
excludeIds	List of entity ids to exclude from select_all	false	string []
expirationMode	The expiration mode.	false	enum
expired	Rule expired or not.	false	boolean
filterBy	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	enum
groupIds	List of Group IDs to filter by	false	string []
hideQuery	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	enum
ids	To filter by Rule ID, enter one or more Rule IDs, separated by commas.	false	string []
labels	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []

mitreTactics	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
name__contains	Free-text filter by rule name. You can enter multiple values, separated by commas.	false	string []
nameSubstring	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string
platformRuleIds	platform rule ids	false	string []
query	Free-text filter by S1 query. You can enter multiple values, separated by commas.	false	string []
queryType	Enter a list of query types.	false	string []
reachedLimit	Rule reached limit or not.	false	boolean
s1ql__contains	Free-text filter by S1 query. You can enter multiple values, separated by commas.	false	string []
s1qlSubstring	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string
scopeId	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string
scopeLevel	To filter by scope, enter one or more scopes, separated by commas.	false	enum
scopes	To filter by scope, enter one or more scopes, separated by commas.	false	string []
severities	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
severity	To filter by severity, enter one or more severities, separated by commas.	false	string []
sitelds	List of Site IDs to filter by	false	string []
sources	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
status	To filter by status, enter one or more	false	string []

	statuses, separated by commas.		
statuses	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
tags	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []

Update Rule

PUT /web/api/v2.1/cloud-detection/rules/{rule_id}

Change a Custom Detection rule.

This command requires the rule ID. (See Get Rules).

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Custom Detection rule not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Rule - response - data table
errors	Errors	false	array

Update Rule - response - data

Name	Description	Required	Value
expirationMode	Whether the rule is Temporary or Permanent.	true	enum
name	The name of the custom detection rule.	true	string
severity	The rule severity in your environment.	true	enum
status	Enabled (Activated and sends alerts if triggered) or Disabled.	true	enum
coolOffSettings	Receive only one alert and suppress additional alerts when a rule is triggered multiple times during the cool-off period. Mitigation actions set in the rule will not be applied to suppressed alerts.	false	see Update Rule - response - coolOffSettings table
correlationParams	Correlation params	false	see Update Rule - response - correlationParams table
createdAt	The date the rule was created.	false	string
creator	The full name of the user that created the rule.	false	string
creatorId	The ID of the user that created the rule.	false	string
description	The description of the custom detection rule.	false	string
editable	True if the rule can be modified at this scope level.	false	boolean
entityMappings	List of OCSF entity mappings to associate alerts with specific assets.	false	see Update Rule - response - entityMappings table
expiration	If Temporary, the expiration date for the rule.	false	string
expired	True if the Rule has expired.	false	boolean
hideLogic	If true, this rule's logic is hidden from non-privileged users.	false	boolean
id	Rule ID	false	string
networkQuarantine	True if the network quarantine is on.	false	boolean

queryLang	The s1ql version query language of the rule. Can be 1.0 or 2.0.	false	enum
queryType	The query type - Correlation (made of multiple subqueries), Event (single query).	false	enum
reachedLimit	True if the Rule reached the 5k/hour or 10k/day alert limit. If the limit has been reached, the Rule is disabled.	false	boolean
s1ql	The query.	false	string
scheduledParams	Scheduled params	false	see Update Rule - response - scheduledParams table
scope	The scope of the rule. Can be Global, Account, Site, or Group.	false	enum
scopeId	The Account, Site, or Group ID, depending on the scope. Null if the scope is Global.	false	string []
statusReason	The reason why the Rule has its current status.	false	string
templateRuleId	Rule Id of template rule from which this rule was created.	false	
treatAsThreat	The Treat as threat auto response - UNDEFINED/suspicious/malicious	false	enum
updatedAt	The date the rule was last updated.	false	string
updaterId	The ID of the user that last updated the rule.	false	string

Update Rule - response - coolOffSettings

Name	Description	Required	Value
renotifyMinutes	The period of time in minutes in which alerts will be suppressed after the rule has been triggered.	true	integer

Update Rule - response - correlationParams

Name	Description	Required	Value
------	-------------	----------	-------

entity	A common entity used to group matching events.	true	enum
matchInOrder	Set to True to require subqueries to match in sequence to trigger an alert.	true	boolean
subQueries	The list of subqueries for the custom detection rule.	false	see Update Rule - response - subQueries table
timeWindow	The period of time in minutes in which subqueries must match to trigger an alert.	false	see Update Rule - response - timeWindow table

Update Rule - response - subQueries

Name	Description	Required	Value
matchesRequired	The number of times a subquery must match.	true	integer
subQuery	A subquery	true	string

Update Rule - response - timeWindow

Name	Description	Required	Value
windowMinutes	The period of time in minutes in which subqueries must match to trigger an alert.	false	enum

Update Rule - response - entityMappings

Name	Description	Required	Value
assetProperty	Asset unique identifier property (e.g., device_uuid, hostname_fqdn for Endpoint; ad_id, aad_id, sid, domain_username, upn for Identity; aws_arn, azure_resource_id, entra_id_object_id, gcp_resource_name, gcp_iam_user for Cloud)	true	string

assetSurface	Asset surface: Endpoint, Cloud, or Identity	true	enum
columnName	Unique case insensitive column name from PowerQuery table result (required for Scheduled rules)	false	string

Update Rule - response - scheduledParams

Name	Description	Required	Value
lookbackWindowMinutes	Sets the evaluation lookback window in minutes. For example, set to 5 evaluates the alert over the past five minutes.	true	integer
query	The PowerQuery to run	true	string
runIntervalMinutes	How often the alert is evaluated, in minutes. If used with coolOffSettings then it must be a denominator of renotifyMinutes. If the lookbackWindowMinutes is less than 60 (1 hour), the minimum is 1 minute. For a window between 1 and 360 (6 hours), 5 minutes. For a window between 360 (6 hours) and 10080 (7 days), 15 minutes. For a window between 10080 (7 days) and 43200 (30 days), 60 minutes.	true	integer
alertPerRow	If True, an alert will be generated for each row detected in the defined lookback window. If False (default), get one alert for all detected events matched in the defined lookback window.	false	boolean
disableStreaksLogic	If True (default), disables streak counting logic for scheduled rules. If False, streak counting logic is enabled.	false	boolean
threshold	Receive an alert only if the number of rows in the result of the query matches the condition in the threshold	false	see Update Rule - response - threshold table

Update Rule - response - threshold

Name	Description	Required	Value
operator	Defines the operator to use in combination with the query and thresholdValue to set the threshold condition for an alert to trigger The default value is Greater	false	enum
value	Defines the threshold value that in combination with operator and the query sets the threshold condition for an alert to be triggered. The default value is 0	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Rule - body - data table
filter	Filter	true	see Update Rule - body - filter table

Update Rule - body - data

Name	Description	Required	Value
expirationMode	Defines the rule as Permanent or Temporary.	true	enum
name	The name of the custom detection rule.	true	string
queryType	Define the query type: Correlation (made of multiple subqueries), Event (single query).	true	enum
severity	The rule severity in your environment.	true	enum
status	Defines the rule is Enabled (Activated and sends alerts if triggered) or Disabled.	true	enum
coolOffSettings	Receive only one alert and suppress additional alerts when a rule is triggered multiple times during the cool-off period. Mitigation actions set in the rule will not be applied to suppressed alerts.	false	see Update Rule - body - coolOffSettings table
correlationParams	Correlation params	false	see Update Rule - body - correlationParams table
description	A description of the custom detection rule.	false	string
entityMappings	List of OCSF entity mappings to associate alerts with specific assets.	false	see Update Rule - body - entityMappings table
expiration	If the rule is Temporary, enter the expiration date for the rule.	false	string
hideLogic	If true, hide this rule logic from non-privileged users.	false	boolean
id	Rule ID	false	string
networkQuarantine	Set to True to automatically quarantine the alerted endpoints.	false	boolean
queryLang	Defines the s1ql version query language of the rule - 1.0 or 2.0.	false	enum
s1ql	The query	false	string
scheduledParams	Scheduled params	false	see Update Rule - body - scheduledParams table

templateRuleId	Rule Id of template rule from which this rule was created.	false	string
treatAsThreat	Defines the Treat as a threat auto response. Undefined, Suspicious, or Malicious.	false	enum

Update Rule - body - coolOffSettings

Name	Description	Required	Value
renotifyMinutes	The period of time in minutes in which alerts will be suppressed after the rule has been triggered.	true	integer

Update Rule - body - correlationParams

Name	Description	Required	Value
entity	A common entity used to group matching events.	true	enum
matchInOrder	Set to True to require subqueries to match in sequence to trigger an alert.	true	boolean
subQueries	The list of subqueries for the custom detection rule.	false	see Update Rule - body - subQueries table
timeWindow	The period of time in minutes in which subqueries must match to trigger an alert.	false	see Update Rule - body - timeWindow table

Update Rule - body - subQueries

Name	Description	Required	Value
matchesRequired	The number of times a subquery must match.	true	integer
subQuery	A subquery	true	string

Update Rule - body - timeWindow

Name	Description	Required	Value
windowMinutes	The period of time in minutes in which subqueries must match to trigger an alert.	false	enum

Update Rule - body - entityMappings

Name	Description	Required	Value
assetProperty	Asset unique identifier property (e.g., device_uuid, hostname_fqdn for Endpoint; ad_id, aad_id, sid, domain_username, upn for Identity; aws_arn, azure_resource_id, entra_id_object_id, gcp_resource_name, gcp_iam_user for Cloud)	true	string
assetSurface	Asset surface: Endpoint, Cloud, or Identity	true	enum
columnName	Unique case insensitive column name from PowerQuery table result (required for Scheduled rules)	false	string

Update Rule - body - scheduledParams

Name	Description	Required	Value
lookbackWindowMinutes	Sets the evaluation lookback window in minutes. For example, set to 5 evaluates the alert over the past five minutes.	true	integer
query	The PowerQuery to run	true	string
runIntervalMinutes	How often the alert is evaluated, in minutes. If used with coolOffSettings then it must be a denominator of renotifyMinutes. If the lookbackWindowMinutes is less than 60 (1 hour), the minimum is 1 minute. For a window between 1 and 360 (6 hours), 5 minutes. For a window	true	integer

	between 360 (6 hours) and 10080 (7 days), 15 minutes. For a window between 10080 (7 days) and 43200 (30 days), 60 minutes.		
alertPerRow	If True, an alert will be generated for each row detected in the defined lookback window. If False (default), get one alert for all detected events matched in the defined lookback window.	false	boolean
disableStreaksLogic	If True (default), disables streak counting logic for scheduled rules. If False, streak counting logic is enabled.	false	boolean
threshold	Receive an alert only if the number of rows in the result of the query matches the condition in the threshold	false	see Update Rule - body - threshold table

Update Rule - body - threshold

Name	Description	Required	Value
operator	Defines the operator to use in combination with the query and thresholdValue to set the threshold condition for an alert to trigger The default value is Greater	false	enum
value	Defines the threshold value that in combination with operator and the query sets the threshold condition for an alert to be triggered. The default value is 0	false	integer

Update Rule - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []

sitelds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Activate Rules

PUT /web/api/v2.1/cloud-detection/rules/enable

Activate Custom Detection Rules based on a filter.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Activate Rules - response - data table
errors	Errors	false	array

Activate Rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Activate Rules - body - filter table

Activate Rules - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeResponse	The active response status for the rule.	false	boolean
attackSurfaces	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
categories	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
creator__contains	Free-text filter by rule creator. You can enter multiple values, separated by commas.	false	string []
description__contains	Free-text filter by rule description. You can enter multiple values, separated by commas.	false	string []
descriptionSubstring	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string
excludeIds	List of entity ids to exclude from select_all	false	string []
expirationMode	The expiration mode.	false	enum
expired	Rule expired or not.	false	boolean
filterBy	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	enum
groupIds	List of Group IDs to filter by	false	string []
hideQuery	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	enum
ids	To filter by Rule ID, enter one or more Rule IDs, separated by commas.	false	string []
labels	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []

mitreTactics	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
name__contains	Free-text filter by rule name. You can enter multiple values, separated by commas.	false	string []
nameSubstring	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string
platformRuleIds	platform rule ids	false	string []
query	Free-text filter by S1 query. You can enter multiple values, separated by commas.	false	string []
queryType	Enter a list of query types.	false	string []
reachedLimit	Rule reached limit or not.	false	boolean
s1ql__contains	Free-text filter by S1 query. You can enter multiple values, separated by commas.	false	string []
s1qlSubstring	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string
scopeId	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string
scopeLevel	To filter by scope, enter one or more scopes, separated by commas.	false	enum
scopes	To filter by scope, enter one or more scopes, separated by commas.	false	string []
severities	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
severity	To filter by severity, enter one or more severities, separated by commas.	false	string []
sitelds	List of Site IDs to filter by	false	string []
sources	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
status	To filter by status, enter one or more	false	string []

	statuses, separated by commas.		
statuses	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
tags	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []

Disable Rules

PUT /web/api/v2.1/cloud-detection/rules/disable

Disable Custom Detection Rules based on a filter.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Disable Rules - response - data table
errors	Errors	false	array

Disable Rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Disable Rules - body - filter table

Disable Rules - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeResponse	The active response status for the rule.	false	boolean
attackSurfaces	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
categories	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
creator__contains	Free-text filter by rule creator. You can enter multiple values, separated by commas.	false	string []
description__contains	Free-text filter by rule description. You can enter multiple values, separated by commas.	false	string []
descriptionSubstring	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string
excludeIds	List of entity ids to exclude from select_all	false	string []
expirationMode	The expiration mode.	false	enum
expired	Rule expired or not.	false	boolean
filterBy	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	enum
groupIds	List of Group IDs to filter by	false	string []
hideQuery	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	enum
ids	To filter by Rule ID, enter one or more Rule IDs, separated by commas.	false	string []
labels	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []

mitreTactics	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
name__contains	Free-text filter by rule name. You can enter multiple values, separated by commas.	false	string []
nameSubstring	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string
platformRuleIds	platform rule ids	false	string []
query	Free-text filter by S1 query. You can enter multiple values, separated by commas.	false	string []
queryType	Enter a list of query types.	false	string []
reachedLimit	Rule reached limit or not.	false	boolean
s1ql__contains	Free-text filter by S1 query. You can enter multiple values, separated by commas.	false	string []
s1qlSubstring	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string
scopeId	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string
scopeLevel	To filter by scope, enter one or more scopes, separated by commas.	false	enum
scopes	To filter by scope, enter one or more scopes, separated by commas.	false	string []
severities	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
severity	To filter by severity, enter one or more severities, separated by commas.	false	string []
siteIds	List of Site IDs to filter by	false	string []
sources	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
status	To filter by status, enter one or more	false	string []

	statuses, separated by commas.		
statuses	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []
tags	The API ignores this field. It's kept for backward compatibility only, and will be removed in a future release.	false	string []

Get Entity Mapping Options

GET /web/api/v2.1/cloud-detection/rules/entity-mapping-options

Get available entity mapping options. Returns valid asset surfaces, their properties, and limits.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Entity Mapping Options - response - data table
errors	Errors	false	array

Get Entity Mapping Options - response - data

Name	Description	Required	Value
assetProperties	Map of asset surface to list of valid properties. When creating an entity mapping, select one surface and one property from that surface.	false	object
assetSurfaces	List of valid asset surfaces	false	string []
maxEntityMappings	Maximum number of entity mappings allowed per rule	false	integer

Datalake Unified Actions

Get Available Actions by Asset/Entity Type

POST /web/api/v2.1/xdr/action-controller/fetch-unified-actions

Get Available Actions by Asset/Entity Type

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Get Available Actions by Asset/Entity Type - response - data table
errors	Errors	false	array

Get Available Actions by Asset/Entity Type - response - data

Name	Description	Required	Value
unifiedActions	Unifiedactions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected entity ids	false	object
id__nin	List of entity ids to exclude from select_all	false	object

Perform an Action on selected assets/entities

POST /web/api/v2.1/xdr/action-controller/perform-unified-action

Perform an Action on selected assets/entities

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionPath	Action path	true	string
id__in	List of selected entity ids	false	object
id__nin	List of entity ids to exclude from select_all	false	object
payload	Payload	false	

Fetch surface ids in case of select all with filters

POST /web/api/v2.1/xdr/action-controller/fetch-surface-ids

Fetch surface ids in case of select all with filters

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionPath	Action path	false	string
id__in	List of selected entity ids	false	object
id__nin	List of entity ids to exclude from select_all	false	object
payload	Payload	false	

Internal api only to notify action was triggered without actually performing it

POST /web/api/v2.1/xdr/action-controller/perform-unified-action/notify

Internal api only to notify action was triggered without actually performing it

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionPath	Action path	true	string
notifyOnly	Notify only	true	enum
id__in	List of selected entity ids	false	object
id__nin	List of entity ids to exclude from select_all	false	object
payload	Payload	false	

Deep Visibility

[DEPRECATED] Create Query and Get QueryId

POST /web/api/v2.1/dv/init-query

Start a Deep Visibility Query and get the queryId. You can use the queryId for other commands, such as Get Events and Get Query Status. For complete query syntax, see Query Syntax in the Knowledge Base (community.sentinelone.com) or the Console Help. Only SentinelOne Deep Visibility Query Language (S1QL 1.0) syntax is supported. SentinelOne Deep Visibility extends the ActiveEDR capabilities, with full visibility into endpoint data and threat hunting. Its kernel-based monitoring searches across endpoints for all indicators of compromise (IOC).
Note: From Management version Rio (February 2022) the default of "isVerbose" is "false" instead of "true".
Deep Visibility requires Complete SKU.

Response Messages

- 200 - Success
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see [DEPRECATED] Create Query and Get QueryId - response - data table
errors	Errors	false	array

[DEPRECATED] Create Query and Get QueryId - response - data

Name	Description	Required	Value
queryId	A query unique identifier	true	string
queryModelInfo	Query mode info	false	see [DEPRECATED] Create Query and Get QueryId - response - queryModelInfo table

[DEPRECATED] Create Query and Get QueryId - response - queryModelInfo

Name	Description	Required	Value
mode	The query mode	true	string
lastActivatedAt	The query mode last_activated_at date	false	string

Body Schema

Name	Description	Required	Value
fromDate	Events created after this timestamp	true	string
query	Events matching the query search term will be returned	true	string
toDate	Events created before or at this timestamp	true	string
accountIds	List of Account IDs to filter by	false	string []
isVerbose	Show all fields or just priority fields	false	boolean
limit	Limit number of returned items (1-100000)	false	integer
queryType	Query Search Type - only one is allowed	false	string []
siteIds	List of Site IDs to filter by	false	string []
timeFrame	Time frame that the query was performed on, when omitted defaults to "Last 48 Hours"	false	string

[DEPRECATED] Cancel Running Query

POST /web/api/v2.1/dv/cancel-query

Stop a Deep Visibility Query by queryId. The body is {"queryID":"string_ID"}. Get the ID of the Deep Visibility query or Power Query from "init-query". See "Create Query and get QueryId".

Deep Visibility requires Complete SKU.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see [DEPRECATED] Cancel Running Query - response - data table
errors	Errors	false	array

[DEPRECATED] Cancel Running Query - response - data

Name	Description	Required	Value
success	request success status	true	string

Body Schema

Name	Description	Required	Value
queryId	QueryId obtained when creating a query under Create Query	true	string

[DEPRECATED] Get Query Status

GET /web/api/v2.1/dv/query-status

Get that status of a Deep Visibility Query. When the status is FINISHED, you can get the results with the queryId in "Get Events".

Deep Visibility requires Complete SKU.

Rate limit: 1 call per second for each different user token.

responseState can return these values: EMPTY_RESULTS, EVENTS_RUNNING, FAILED, FAILED_CLIENT, FINISHED, PLANNING, PROCESS_RUNNING, QUERY_CANCEL, QUERY_EXPIRED, QUERY_NOT_FOUND, QUERY_RUNNING, RUNNING, TIMED_OUT.

Parameters

queryId	required	QueryId obtained when creating a query under Create Query. Example: "q1xx2xx3".
---------	----------	--

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see [DEPRECATED] Get Query Status - response - data table
errors	Errors	false	array

[DEPRECATED] Get Query Status - response - data

Name	Description	Required	Value
progressStatus	Query loading status in percentage	true	integer
responseState	Response state	true	enum
queryModelInfo	Query mode info	false	see [DEPRECATED] Get Query Status - response - queryModelInfo table
responseError	Relevant only for FAILED and FAILED_CLIENT DV errors	false	string
warnings	Warnings	false	string

[DEPRECATED] Get Query Status - response - queryModelInfo

Name	Description	Required	Value
mode	The query mode	true	string
lastActivatedAt	The query mode last_activated_at date	false	string

[DEPRECATED] Get Events

GET /web/api/v2.1/dv/events

Get all Deep Visibility events from a queryId. You can use this command to send a sub-query, a new query to run on these events. Get the ID from "init-query". See "Create Query and get QueryId".

For complete documentation, see Query Syntax in the Knowledge Base (support.sentinelone.com) or the Console Help.

Parameters

queryid	required	QueryId obtained when creating a query under Create Query. Example: "q1xx2xx3".
cursor	optional	Cursor position returned by the last request. Should be used instead of skip. cursor currently supports sort by with createdAt, pid, processStartTime
limit	optional	Limit number of returned items (1-1000). Example: "10".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000

		items, use "cursor". Example: "150".
sortby	optional	Events sorted by field. Example: "createdAt".
sortorder	optional	Event sorting order. Example: "asc".
subquery	optional	Create a sub query to run on the data that was already pulled

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see [DEPRECATED] Get Events - response - pagination table
data	Response data	false	see [DEPRECATED] Get Events - response - data table
errors	Errors	false	array

[DEPRECATED] Get Events - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

[DEPRECATED] Get Events - response - data

Name	Description	Required	Value
agentDomain	Agent domain	true	string
agentGroupld	Agent group id	true	string
agentld	Agent id	true	string
agentInfected	Agent infected	true	boolean
agentIp	Agent ip	true	string
agentIsActive	Agent is active	true	boolean
agentIsDecommissioned	Agent is decommissioned	true	boolean
agentMachineType	Agent machine type	true	string
agentName	Agent name	true	string
agentNetworkStatus	Agent network status	true	string
agentOs	OS type	true	enum
agentUuid	Agent uuid	true	string
agentVersion	Agent version	true	string
createdAt	Created at	true	string
id	Id	true	string
objectType	Object type	true	string
processName	Process name	true	string
siteName	Site name	true	string

user	User	true	string
connectionStatus	Connection status	false	string
direction	Direction	false	string
dnsRequest	Dns request	false	string
dnsResponse	Dns response	false	string
dstIp	Dst ip	false	string
dstPort	Dst port	false	integer
eventType	Event type	false	string
fileFullName	File full name	false	string
fileId	File id	false	string
fileMd5	File md5	false	string
fileSha1	File sha1	false	string
fileSha256	File sha256	false	string
fileSize	File size	false	string
fileType	File type	false	string
forensicUrl	Forensic url	false	string
indicatorCategory	Indicator category	false	string
indicatorDescription	Indicator description	false	string
indicatorMetadata	Indicator metadata	false	string
indicatorName	Indicator name	false	string
isAgentVersionFullySupportedForPg	Is agent version fully supported for pg	false	boolean
isAgentVersionFullySupportedForPgMessage	Is agent version fully supported for pg message	false	string
loginsBaseType	Logins base type	false	string
loginsUserName	Logins user name	false	string
md5	Md5	false	string
networkMethod	Network method	false	string
networkSource	Network source	false	string
networkUrl	Network url	false	string
oldFileMd5	Old file md5	false	string
oldFileName	Old file name	false	string
oldFileSha1	Old file sha1	false	string

oldFileSha256	Old file sha256	false	string
parentPid	Parent pid	false	string
parentProcessGroupId	Parent process group id	false	string
parentProcessIsMalicious	Parent process is malicious	false	boolean
parentProcessName	Parent process name	false	string
parentProcessStartTime	Parent process start time	false	string
parentProcessUniqueKey	Parent process unique key	false	string
pid	Pid	false	string
processCmd	Process cmd	false	string
processDisplayName	Process display name	false	string
processGroupId	Process group id	false	string
processImagePath	Process image path	false	string
processImageSha1Hash	Process image sha1 hash	false	string
processIntegrityLevel	Process integrity level	false	string
processIsMalicious	Process is malicious	false	boolean
processIsRedirectedCommandProcess or	Process is redirected command processor	false	string
processIsWow64	Process is wow64	false	string
processRoot	Process root	false	string
processSessionId	Process session id	false	string
processStartTime	Process start time	false	string
processSubSystem	Process sub system	false	string
processUniqueKey	Process unique key	false	string
processUserName	Process user name	false	string
publisher	Publisher	false	string
registryId	Registry id	false	string
registryPath	Registry path	false	string
relatedToThreat	Related to threat	false	string
rpId	Rpid	false	string
sha1	Sha1	false	string
sha256	Sha256	false	string
signatureSignedInvalidReason	Signature signed invalid reason	false	string

signedStatus	Signed status	false	string
srcIp	Src ip	false	string
srcPort	Src port	false	integer
srcProcDownloadToken	Src proc download token	false	string
taskName	Task name	false	string
taskPath	Task path	false	string
threatStatus	Threat status	false	string
tid	Tid	false	string
trueContext	True context	false	string
verifiedStatus	Verified status	false	string

[DEPRECATED] Get Process State

GET /web/api/v2.1/dv/process-state

Get details of all Deep Visibility processes from a queryId. To get the ID from "init-query". See "Create Query and get QueryId".

Parameters

queryid	required	QueryId obtained when creating a query under Create Query. Example: "q1xx2xx3".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
limit	optional	Limit number of returned items (1-1000). Example: "10".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
sortBy	optional	Events sorted by field. Example: "SrcProcStartTime".
sortorder	optional	Event sorting order. Example: "asc".

Response Messages

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

[DEPRECATED] Get Events By Type

GET /web/api/v2.1/dv/events/{event_type}

Get Deep Visibility results from the query that matches the given event type. Valid event_type values below shown as "event_type - (objectTypes)":

process - (Process Exit, Process Modification, Process Creation, Duplicate Process Handle, Duplicate Thread Handle, Open Remote Process Handle, Remote Thread Creation, Remote Process Termination, Command Script)

ip - (IP Connect, IP Listen)

file - (File Modification, File Creation, File Scan, File Deletion, File Rename, Pre Execution Detection)

logins - (Login, Logout)

url - (GET, OPTIONS, POST, PUT, DELETE, CONNECT, HEAD)

dns - (DNS Resolved, DNS Unresolved)

scheduled_task - (Task Register, Task Update, Task Start, Task Trigger, Task Delete)

registry - (Registry Key Create, Registry Key Rename, Registry Key Delete, Registry Key Export, Registry Key Security Changed, Registry Key Import, Registry Value Modified, Registry Value Create, Registry Value Delete)

indicators - (Behavioral Indicators)

module - (Module Load)

Parameters

queryid	required	QueryId obtained when creating a query under Create Query. Example: "q1xx2xx3".
cursor	optional	Cursor position returned by the last request. Should be used instead of skip. cursor currently supports sort by with createdAt, pid, processStartTime
limit	optional	Limit number of returned items (1-1000). Example: "10".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
sortby	optional	Events sorted by field. Example: "createdAt".
sortorder	optional	Event sorting order. Example: "asc".
subquery	optional	Create a sub query to run on the data that was already pulled

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see [DEPRECATED] Get Events By Type - response - pagination table
data	Response data	false	see [DEPRECATED] Get Events By Type - response - data table
errors	Errors	false	array

[DEPRECATED] Get Events By Type - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

[DEPRECATED] Get Events By Type - response - data

Name	Description	Required	Value
agentDomain	Agent domain	true	string
agentGroupId	Agent group id	true	string
agentId	Agent id	true	string
agentInfected	Agent infected	true	boolean
agentIp	Agent ip	true	string
agentIsActive	Agent is active	true	boolean
agentIsDecommissioned	Agent is decommissioned	true	boolean
agentMachineType	Agent machine type	true	string
agentName	Agent name	true	string
agentNetworkStatus	Agent network status	true	string
agentOs	OS type	true	enum
agentUuid	Agent uuid	true	string
agentVersion	Agent version	true	string
createdAt	Created at	true	string
id	Id	true	string
objectType	Object type	true	string
processName	Process name	true	string
siteName	Site name	true	string

user	User	true	string
connectionStatus	Connection status	false	string
direction	Direction	false	string
dnsRequest	Dns request	false	string
dnsResponse	Dns response	false	string
dstIp	Dst ip	false	string
dstPort	Dst port	false	integer
eventType	Event type	false	string
fileFullName	File full name	false	string
fileId	File id	false	string
fileMd5	File md5	false	string
fileSha1	File sha1	false	string
fileSha256	File sha256	false	string
fileSize	File size	false	string
fileType	File type	false	string
forensicUrl	Forensic url	false	string
indicatorCategory	Indicator category	false	string
indicatorDescription	Indicator description	false	string
indicatorMetadata	Indicator metadata	false	string
indicatorName	Indicator name	false	string
isAgentVersionFullySupportedForPg	Is agent version fully supported for pg	false	boolean
isAgentVersionFullySupportedForPgMessage	Is agent version fully supported for pg message	false	string
loginsBaseType	Logins base type	false	string
loginsUserName	Logins user name	false	string
md5	Md5	false	string
networkMethod	Network method	false	string
networkSource	Network source	false	string
networkUrl	Network url	false	string
oldFileMd5	Old file md5	false	string
oldFileName	Old file name	false	string
oldFileSha1	Old file sha1	false	string

oldFileSha256	Old file sha256	false	string
parentPid	Parent pid	false	string
parentProcessGroupId	Parent process group id	false	string
parentProcessIsMalicious	Parent process is malicious	false	boolean
parentProcessName	Parent process name	false	string
parentProcessStartTime	Parent process start time	false	string
parentProcessUniqueKey	Parent process unique key	false	string
pid	Pid	false	string
processCmd	Process cmd	false	string
processDisplayName	Process display name	false	string
processGroupId	Process group id	false	string
processImagePath	Process image path	false	string
processImageSha1Hash	Process image sha1 hash	false	string
processIntegrityLevel	Process integrity level	false	string
processIsMalicious	Process is malicious	false	boolean
processIsRedirectedCommandProcess or	Process is redirected command processor	false	string
processIsWow64	Process is wow64	false	string
processRoot	Process root	false	string
processSessionId	Process session id	false	string
processStartTime	Process start time	false	string
processSubSystem	Process sub system	false	string
processUniqueKey	Process unique key	false	string
processUserName	Process user name	false	string
publisher	Publisher	false	string
registryId	Registry id	false	string
registryPath	Registry path	false	string
relatedToThreat	Related to threat	false	string
rpId	Rpid	false	string
sha1	Sha1	false	string
sha256	Sha256	false	string
signatureSignedInvalidReason	Signature signed invalid reason	false	string

signedStatus	Signed status	false	string
srcIp	Src ip	false	string
srcPort	Src port	false	integer
srcProcDownloadToken	Src proc download token	false	string
taskName	Task name	false	string
taskPath	Task path	false	string
threatStatus	Threat status	false	string
tid	Tid	false	string
trueContext	True context	false	string
verifiedStatus	Verified status	false	string

[DEPRECATED] Create a Power Query and Get QueryId

POST /web/api/v2.1/dv/events/pq

Start a Deep Visibility Power Query, get back status and potential results (ping afterwards using the queryId if query has not finished)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see [DEPRECATED] Create a Power Query and Get QueryId - response - data table
errors	Errors	false	array

[DEPRECATED] Create a Power Query and Get QueryId - response - data

Name	Description	Required	Value
progress	Query loading status in percentage	true	integer
queryId	Query Id	true	string
status	Status	true	enum
columns	includes the name of the column and its type	false	see [DEPRECATED] Create a Power Query and Get QueryId - response - columns table
data	Includes actual searched data	false	see [DEPRECATED] Create a Power Query and Get QueryId - response - data table
externalId	External Query Id	false	string
recommendations	possible action items to improve query results	false	string []

[DEPRECATED] Create a Power Query and Get QueryId - response - columns

Name	Description	Required	Value
		false	object

[DEPRECATED] Create a Power Query and Get QueryId - response - data

Name	Description	Required	Value
		false	undefined []

Body Schema

Name	Description	Required	Value
fromDate	Events created after this timestamp	true	string
query	Events matching the query search term will be returned	true	string
toDate	Events created before or at this timestamp	true	string
accountIds	List of Account IDs to filter by	false	string []

limit	Limit number of returned items (1-100000)	false	integer
sitelds	List of Site IDs to filter by	false	string []

[DEPRECATED] Ping a Power Query if results haven't been retrieved

GET /web/api/v2.1/dv/events/pq-ping

Ping a Deep Visibility Power Query using the queryId if results have not returned from an initial Power Query or a previous ping.

Use pq-ping soon after initiating a Power Query via the /web/api/v2.1/dv/events/pq endpoint.

It is recommended to create a script that initiates the Power Query and then pings the query every few seconds to check the status and retrieve results when they are ready.

If the ping is run after a significant delay, it may result in a 503 Service Unavailable response. This indicates that the results are no longer available due to cache eviction.

Parameters

queryid	optional	QueryId query param
---------	----------	---------------------

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see [DEPRECATED] Ping a Power Query if results haven't been retrieved - response - data table
errors	Errors	false	array

[DEPRECATED] Ping a Power Query if results haven't been retrieved - response - data

Name	Description	Required	Value
progress	Query loading status in percentage	true	integer
queryId	Query Id	true	string
status	Status	true	enum
columns	includes the name of the column and its type	false	see [DEPRECATED] Ping a Power Query if results haven't been retrieved - response - columns table
data	Includes actual searched data	false	see [DEPRECATED] Ping a Power Query if results haven't been retrieved - response - data table
externalId	External Query Id	false	string
recommendations	possible action items to improve query results	false	string []

[DEPRECATED] Ping a Power Query if results haven't been retrieved - response - columns

Name	Description	Required	Value
		false	object

[DEPRECATED] Ping a Power Query if results haven't been retrieved - response - data

Name	Description	Required	Value
		false	undefined []

Download source process file

GET /web/api/v2.1/dv/fetch-file

Download the source process file associated with a Deep Visibility event.

Parameters

downloadtoken	required	Download token
---------------	----------	----------------

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - File not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Download source process file - response - data table
errors	Errors	false	array

Download source process file - response - data

Name	Description	Required	Value
downloadUrl	Download link	false	string
fileName	File name	false	string

Default Reports

S1 RSS Feed

GET /web/api/v2.1/sentinelonerss

Get the SentinelOne RSS feed. In the SentinelOne Management Console, we show the feed contents in the Dashboard.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

404 - Site not found

Response Schema

Name	Description	Required	Value
data	Response data	false	
errors	Errors	false	array

Get Default Reports

GET /web/api/v2.1/reports

Get the default reports that match the filter and the data of the reports. Default Reports require Reports permission and appropriate license. Use this command to get the ID of reports to use in other commands. Other data in the response: schedule, Insight Type, name and ID of the user who created the report, the date range, and more.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__gte	optional	Created at gte. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Created at lte. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
frequency	optional	Frequency. Example: "manually".
fromdate	optional	From date. Example: "2018-02-27T04:49:26.257525Z".
id	optional	Id. Example: "225494730938493804".
ids	optional	Id in. Example: "225494730938493804,225494730938493915".
interval	optional	Interval
limit	optional	Limit number of returned items (1-1000). Example: "10".
name	optional	Name
query	optional	Query
scheduletype	optional	Report type. Example: "manually".
scope	optional	Scope. Example: "group".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.

sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
taskid	optional	Task id. Example: "225494730938493804".
todate	optional	To date. Example: "2018-02-27T04:49:26.257525Z".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Default Reports - response - pagination table
data	Response data	false	see Get Default Reports - response - data table
errors	Errors	false	array

Get Default Reports - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Default Reports - response - data

Name	Description	Required	Value
attachmentTypes	Type of documents for the report	false	string []
createdAt	Creation date	false	string
creatorId	Id of the creator	false	string
creatorName	Name of the creator	false	string
frequency	Report frequency	false	string
fromDate	From date	false	string
id	Id	false	string
insightTypes	Report data	false	see Get Default Reports - response - insightTypes table
interval	Interval of the report	false	
name	Name of the report	false	string
scheduleType	Report type	false	enum
scope	Scope of the report	false	string
sites	Report sites	false	string
status	Status of the reports	false	string
toDate	To date	false	string

Get Default Reports - response - insightTypes

Name	Description	Required	Value
		false	object

Get Default Report Tasks

GET /web/api/v2.1/report-tasks

Get the tasks that were done to generate default reports and to schedule future default reports. Default Reports require Reports permission and appropriate license. Best Practice: Use a filter. Each task includes many lines of data and can quickly fill the page limit. Use this command to get the ID of a report task to use in other commands.

BEST PRACTICE

Use a filter. Each task includes many lines of data and can quickly fill the page limit. Use this command to get the ID of a report task to use in other commands.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__gte	optional	Created at gte. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Created at lte. Example: "2018-02-27T04:49:26.257525Z".
creatorid	optional	Creator id. Example: "225494730938493804".
creatorname	optional	Creator name
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
day	optional	Day
frequency	optional	Frequency. Example: "manually".
id	optional	Id. Example: "225494730938493804".
ids	optional	Id in. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".
name	optional	Name
query	optional	Query
scheduletype	optional	Report type. Example: "manually".

scope	optional	Scope. Example: "group".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Default Report Tasks - response - pagination table
data	Response data	false	see Get Default Report Tasks - response - data table
errors	Errors	false	array

Get Default Report Tasks - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Default Report Tasks - response - data

Name	Description	Required	Value
attachmentTypes	Type of documents for the report	false	string []
creatorId	Creator id	false	string
creatorName	Creator name	false	string
day	Day	false	
frequency	Frequency	false	enum
fromDate	From date	false	string
id	Id	false	string
insightTypes	Insight types	false	see Get Default Report Tasks - response - insightTypes table
isTrend	Is trend	false	boolean
name	Name	false	string
recipients	Recipients	false	string []
scheduleType	Report type	false	enum
scope	Scope	false	enum
sites	Sites associated to the report	false	string
toDate	To date	false	string

Get Default Report Tasks - response - insightTypes

Name	Description	Required	Value
		false	object

Create Default Report Task

POST /web/api/v2.1/report-tasks

Create a task to generate a default report immediately, one time in the future, or on a schedule. Default Reports require Reports permission and appropriate license. Best Practice: Get Default Report Tasks first, to have a basis for a new task.

BEST PRACTICE

Get Default Report Tasks first, to have a basis for a new task.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Validation errors

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Default Report Task - response - data table
errors	Errors	false	array

Create Default Report Task - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Default Report Task - body - data table
filter	Filter	true	see Create Default Report Task - body - filter table

Create Default Report Task - body - data

Name	Description	Required	Value
name	Name of the report	true	string
scheduleType	Schedule type	true	enum
attachmentTypes	Type of attachments for the report. Must be supplied if recipients are added	false	string []
day	Day of the week for Weekly report.	false	enum
frequency	Report Period	false	enum
fromDate	From date	false	string
insightTypes	List of reports.	false	see Create Default Report Task - body - insightTypes table
isTrend	If is trend is true then the period will be last month	false	boolean
recipients	List of recipients for the report	false	string []
toDate	To date	false	string

Create Default Report Task - body - insightTypes

Name	Description	Required	Value
		false	object

Create Default Report Task - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
scope		false	string
siteIds	List of Site IDs to filter by	false	string []

Update Default Report Task

PUT /web/api/v2.1/report-tasks/{task_id}

Update the default report task of the given ID. Default Reports require Reports permission and appropriate license. To get the task ID, and the data to change, run Get Default Report Tasks.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Validation errors

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Default Report Task - response - data table
errors	Errors	false	array

Update Default Report Task - response - data

Name	Description	Required	Value
attachmentTypes	Type of documents for the report	false	string []
creatorId	Creator id	false	string
creatorName	Creator name	false	string
day	Day	false	
frequency	Frequency	false	enum
fromDate	From date	false	string
id	Id	false	string
insightTypes	Insight types	false	see Update Default Report Task - response - insightTypes table
isTrend	Is trend	false	boolean
name	Name	false	string
recipients	Recipients	false	string []
scheduleType	Report type	false	enum
scope	Scope	false	enum
sites	Sites associated to the report	false	string
toDate	To date	false	string

Update Default Report Task - response - insightTypes

Name	Description	Required	Value
		false	object

Body Schema

Name	Description	Required	Value
data	Data	false	see Update Default Report Task - body - data table

Update Default Report Task - body - data

Name	Description	Required	Value
name	Name of the report	true	string
attachmentTypes	Type of documents for the report	false	string []
id	Database id of the task	false	string
recipients	List of recipients for the report	false	string []

Delete Default Reports

POST /web/api/v2.1/reports/delete-reports

Delete the default reports that match the filter. Default Reports require Reports permission and appropriate license. To delete a specific report, use its ID (see Get Default Reports).

Response Messages

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
data	Data	false	see Delete Default Reports - body - data table
filter	Filter	false	see Delete Default Reports - body - filter table

Delete Default Reports - body - data

Delete Default Reports - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
createdAt__gte	Created at gte	false	string
createdAt__lte	Created at lte	false	string
frequency	Frequency	false	enum
fromDate	From date	false	string
groupIds	List of Group IDs to filter by	false	string []
id	Id	false	string
ids	Id in	false	string []
interval	Interval	false	string
name	Name	false	string
query	Query	false	string
scheduleType	Report type	false	enum
scope	Scope	false	enum
siteIds	List of Site IDs to filter by	false	string []
toDate	To date	false	string

Delete Default Report Tasks

POST /web/api/v2.1/reports/delete-tasks

You can schedule a default report to be generated on a routine. Default Reports require Reports permission and appropriate license. Use this command to remove a task to generate a report in the future. To get an ID to delete a specific task, see Get Default Report Tasks.

Response Messages

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
data	Data	false	see Delete Default Report Tasks - body - data table
filter	Filter	false	see Delete Default Report Tasks - body - filter table

Delete Default Report Tasks - body - data

Delete Default Report Tasks - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
createdAt__gte	Created at gte	false	string
createdAt__lte	Created at lte	false	string
frequency	Frequency	false	enum
groupIds	List of Group IDs to filter by	false	string []
id	Id	false	string
ids	Id in	false	string []
interval	Interval	false	string
isTrend	Is trend	false	boolean
name	Name	false	string
query	Query	false	string
scheduleType	Report type	false	enum
scope	Scope	false	enum
siteIds	List of Site IDs to filter by	false	string []
sites	Sites	false	string

Download Default Report

GET /web/api/v2.1/reports/{report_id}/{report_format}

When the Management generates a default report, it is uploaded to the Management Console. Default Reports require Reports permission and appropriate license. Use this command to get the report as a PDF or HTML file. To get the ID of the report, see Get Default Reports.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

404 - Report not found

Get Default Insight Reports

GET /web/api/v2.1/reports/insights/types

Get the Insight Report types for Default Reports. Default Reports require Reports permission and appropriate license. These reports show high-level and detailed information on the state of your endpoint security. Reports include statistics, trends, and summaries with easy to read and actionable information about your network. Use this command to see the predefined reports. This command does not give data for specific reports.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
forceupdate	optional	Force update
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Package not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Default Insight Reports - response - data table
errors	Errors	false	array

Get Default Insight Reports - response - data

Name	Description	Required	Value
insightTypes	List of reports	false	see Get Default Insight Reports - response - insightTypes table

Get Default Insight Reports - response - insightTypes

Name	Description	Required	Value
		false	object

Device Control

Get Device Rules

GET /web/api/v2.1/device-control

Get the Device Control rules of a specified Account, Site, Group or Global (tenant) that match the filter.

Parameters

accesspermissions	optional	Access permission in. Example: "Read-Only".
accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
actions	optional	Return device rules with the filtered action. Example: "Allow".
bluetoothaddresses	optional	Return device rules with the filtered bluetooth addresses.
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__between	optional	Return device rules created within this range (inclusive). Example: "1514978764288-1514978999999".
createdat__gt	optional	Return device rules created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".

createdat__gte	optional	Return device rules created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Return device rules created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Return device rules created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
deviceclasses	optional	Return device rules with the filtered device class. Example: "02h".
deviceids	optional	Return device rules with the filtered device id. Example: "02".
deviceinformationserviceinfokeys	optional	Return device rules with the filtered device information service info keys.
devicenames	optional	Return device rules with the filtered device names.
disablepagination	optional	If true, all rules for requested scope will be returned
gattservices	optional	Return device rules with the filtered GATT services.
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of ids to filter by. Example: "225494730938493804,225494730938493915".
interfaces	optional	Return device rules with the filtered interface. Example: "USB".
limit	optional	Limit number of returned items (1-1000). Example: "10".
manufacturernames	optional	Return device rules with the filtered manufacturer names.
minorclasses	optional	Return device rules with the filtered minor classes.
productids	optional	Return device rules with the filtered product id. Example: "02".
query	optional	A free-text search term, will match applicable attributes.
rulename	optional	Return device rules with the filtered rule name.
scopes	optional	Return only device rules in this scope. Example: "account".
serviceclasses	optional	Return device rules with the filtered service class. Example: "02".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".

skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
statuses	optional	Return device rules with the filtered status. Example: "Enabled".
tenant	optional	Indicates a tenant scope request
uids	optional	Return device rules with the filtered uid.
vendorids	optional	Return device rules with the filtered vendor id.
versions	optional	Return device rules with the filtered versions.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Device Rules - response - pagination table
data	Response data	false	see Get Device Rules - response - data table
errors	Errors	false	array

Get Device Rules - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Device Rules - response - data

Name	Description	Required	Value
accessPermission	Access permission	false	enum
action	Defines if agent shall Block or Allow use of devices which matches the rule parameters.	false	enum
bluetoothAddress	Bluetooth Address	false	string
createdAt	Date of rule creation	false	string
creator	Full name of the creating user	false	string
creatorId	Id of the creating user	false	string
deviceClass	The Device Class key. Valid for all rule types.	false	string
deviceClassName	The Device Class name. Valid for all rule types.	false	
deviceId	The id of the physical device connected to the interface.	false	string
deviceInformationServiceInfoKey	Device Information Service Info Key	false	string
deviceInformationServiceInfoValue	Device Information Service Info Value	false	string
deviceName	Device Name	false	string
editable	True if the rule can be modified at this scope level	false	boolean
gattService	GATT Service IDs	false	string []

id	Rule ID	false	string
interface	The physical bus type of the device.	false	enum
manufacturerName	Manufacturer Name	false	string
minorClasses	List of Bluetooth minor classes	false	string []
order	Position in the list of rules	false	integer
productId	Product identifier. Unique for a specific product module, per vendor ID, Interface.	false	string
ruleName	The name of the device rule.	false	string
ruleType	Defines a set of fields that are mandatory.	false	enum
scope	Scope of the rule	false	enum
scopeId	The id representing a group or a site dependent on the scope	false	string
scopeName	Extended name of the scope	false	string
status	Defines if rule is Enabled or Disabled.	false	enum
uid	Relevant USB Mass storage devices only (Interface=USB, Class=mass storage).	false	string
updatedAt	Date of last update	false	string
vendorId	Vendor identifier. Mandatory when rule type is vendor id or product id.	false	string
version	Vendor identifier. Mandatory when rule type is vendor id or product id.	false	string

Create Device Control Rule

POST /web/api/v2.1/device-control

Use this command to create a new Device Control rule. These rules allow or block devices, based on device identifiers. Rules apply to a scope: Global (tenant), Account, Site, or Group. To learn details of the fields, see <https://support.sentinelone.com/hc/en-us/articles/360023338494>.

Recommended: Before you begin, see Device Control Known Limitations: <https://support.sentinelone.com/hc/en-us/articles/360021104114>.

Device Control requires Control SKU. Linux Agents do not support Device Control.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Device Control Rule - response - data table
errors	Errors	false	array

Create Device Control Rule - response - data

Name	Description	Required	Value
accessPermission	Access permission	false	enum
action	Defines if agent shall Block or Allow use of devices which matches the rule parameters.	false	enum
bluetoothAddress	Bluetooth Address	false	string
createdAt	Date of rule creation	false	string
creator	Full name of the creating user	false	string
creatorId	Id of the creating user	false	string
deviceClass	The Device Class key. Valid for all rule types.	false	string
deviceClassName	The Device Class name. Valid for all rule types.	false	
deviceId	The id of the physical device connected to the interface.	false	string
deviceInformationServiceInfoKey	Device Information Service Info Key	false	string
deviceInformationServiceInfoValue	Device Information Service Info Value	false	string
deviceName	Device Name	false	string
editable	True if the rule can be modified at this scope level	false	boolean
gattService	GATT Service IDs	false	string []
id	Rule ID	false	string
interface	The physical bus type of the device.	false	enum
manufacturerName	Manufacturer Name	false	string
minorClasses	List of Bluetooth minor classes	false	string []
order	Position in the list of rules	false	integer
productId	Product identifier. Unique for a specific product module, per vendor ID, Interface.	false	string
ruleName	The name of the device rule.	false	string
ruleType	Defines a set of fields that are	false	enum

	mandatory.		
scope	Scope of the rule	false	enum
scopeId	The id representing a group or a site dependent on the scope	false	string
scopeName	Extended name of the scope	false	string
status	Defines if rule is Enabled or Disabled.	false	enum
uid	Relevant USB Mass storage devices only (Interface=USB, Class=mass storage).	false	string
updatedAt	Date of last update	false	string
vendorId	Vendor identifier. Mandatory when rule type is vendor id or product id.	false	string
version	Vendor identifier. Mandatory when rule type is vendor id or product id.	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Device Control Rule - body - data table
filter	Filter	true	see Create Device Control Rule - body - filter table

Create Device Control Rule - body - data

Name	Description	Required	Value
action	Defines if agent shall Block or Allow use of devices which matches the rule parameters.	true	enum
interface	The physical bus type of the device.	true	enum
ruleName	The name of the device rule.	true	string
ruleType	Rule type. Depending on the type, each rule requires different parameters.	true	enum
status	Defines if rule is Enabled or Disabled.	true	enum
accessPermission	Access permission	false	enum
bluetoothAddress	Bluetooth Address	false	string
deviceClass	The Device Class	false	string
deviceId	Physical device identifier. Mandatory when rule type is device id.	false	string
deviceInformationServiceInfoKey	Device Information Service Info Key	false	string
deviceInformationServiceInfoValue	Device Information Service Info Value	false	string
deviceName	Device Name	false	string
gattService	Gatt service	false	string []
manufacturerName	Manufacturer Name	false	string
minorClasses	Minor classes	false	string []
productId	Product identifier. Unique for a specific product module, per vendor ID, Interface.	false	string
serviceClass	Relevant for Bluetooth devices only	false	string
uid	Relevant USB Mass storage devices only (Interface=USB, Class=mass storage).	false	string
vendorId	Vendor identifier. Mandatory when rule type is vendor id or product id.	false	string
version	The version of the device.	false	string

Create Device Control Rule - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Delete Rules

DELETE /web/api/v2.1/device-control

Delete Device Control rules that match the filter.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Rules - response - data table
errors	Errors	false	array

Delete Rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Delete Rules - body - filter table

Delete Rules - body - filter

Name	Description	Required	Value
accessPermissions	Access permission in	false	string []
accountIds	List of Account IDs to filter by	false	string []
actions	Return device rules with the filtered action.	false	string []
bluetoothAddresses	Return device rules with the filtered bluetooth addresses.	false	string []
createdAt__between	Return device rules created within this range (inclusive)	false	string
createdAt__gt	Return device rules created after this timestamp.	false	string
createdAt__gte	Return device rules created after or at this timestamp.	false	string
createdAt__lt	Return device rules created before this timestamp.	false	string
createdAt__lte	Return device rules created before or at this timestamp.	false	string
deviceClasses	Return device rules with the filtered device class.	false	string []
deviceIds	Return device rules with the filtered device id.	false	string []
deviceInformationServiceInfoKeys	Return device rules with the filtered device information service info keys.	false	string []
deviceNames	Return device rules with the filtered device names.	false	string []
gattServices	Return device rules with the filtered GATT services.	false	string []
groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
interfaces	Return device rules with the filtered interface.	false	string []
manufacturerNames	Return device rules with the filtered manufacturer names.	false	string []

minorClasses	Return device rules with the filtered minor classes.	false	string []
productIds	Return device rules with the filtered product id.	false	string []
query	A free-text search term, will match applicable attributes.	false	string
ruleName	Return device rules with the filtered rule name.	false	string
scopes	Return only device rules in this scope	false	string []
serviceClasses	Return device rules with the filtered service class.	false	string []
sitelds	List of Site IDs to filter by	false	string []
statuses	Return device rules with the filtered status.	false	string []
tenant	Indicates a tenant scope request	false	boolean
uids	Return device rules with the filtered uid.	false	string []
vendorIds	Return device rules with the filtered vendor id.	false	string []
versions	Return device rules with the filtered versions.	false	string []

Update Device Rule

PUT /web/api/v2.1/device-control/{rule_id}

Change the Device Control rule that matches the filter. To learn more about the fields, see <https://support.sentinelone.com/hc/en-us/articles/360023338494>.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Device rule not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Device Rule - response - data table
errors	Errors	false	array

Update Device Rule - response - data

Name	Description	Required	Value
accessPermission	Access permission	false	enum
action	Defines if agent shall Block or Allow use of devices which matches the rule parameters.	false	enum
bluetoothAddress	Bluetooth Address	false	string
createdAt	Date of rule creation	false	string
creator	Full name of the creating user	false	string
creatorId	Id of the creating user	false	string
deviceClass	The Device Class key. Valid for all rule types.	false	string
deviceClassName	The Device Class name. Valid for all rule types.	false	
deviceId	The id of the physical device connected to the interface.	false	string
deviceInformationServiceInfoKey	Device Information Service Info Key	false	string
deviceInformationServiceInfoValue	Device Information Service Info Value	false	string
deviceName	Device Name	false	string
editable	True if the rule can be modified at this scope level	false	boolean
gattService	GATT Service IDs	false	string []
id	Rule ID	false	string
interface	The physical bus type of the device.	false	enum
manufacturerName	Manufacturer Name	false	string
minorClasses	List of Bluetooth minor classes	false	string []
order	Position in the list of rules	false	integer
productId	Product identifier. Unique for a specific product module, per vendor ID, Interface.	false	string
ruleName	The name of the device rule.	false	string
ruleType	Defines a set of fields that are	false	enum

	mandatory.		
scope	Scope of the rule	false	enum
scopeId	The id representing a group or a site dependent on the scope	false	string
scopeName	Extended name of the scope	false	string
status	Defines if rule is Enabled or Disabled.	false	enum
uid	Relevant USB Mass storage devices only (Interface=USB, Class=mass storage).	false	string
updatedAt	Date of last update	false	string
vendorId	Vendor identifier. Mandatory when rule type is vendor id or product id.	false	string
version	Vendor identifier. Mandatory when rule type is vendor id or product id.	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Device Rule - body - data table

Update Device Rule - body - data

Name	Description	Required	Value
accessPermission	Access permission	false	enum
action	Defines if agent shall Block or Allow use of devices which matches the rule parameters.	false	enum
bluetoothAddress	Bluetooth Address	false	string
deviceClass	The Device Class	false	string
deviceId	Physical device identifier. Mandatory when rule type is device id.	false	string
deviceInformationServiceInfoKey	Device Information Service Info Key	false	string
deviceInformationServiceInfoValue	Device Information Service Info Value	false	string
deviceName	Device Name	false	string
gattService	Gatt service	false	string []
interface	Defines the Physical bus type of the Device.	false	enum
manufacturerName	Manufacturer Name	false	string
minorClasses	Minor classes	false	string []
productId	Product identifier. Unique for a specific product module, per vendor ID, Interface.	false	string
ruleName	The name of the device rule.	false	string
ruleType	Rule type. Depending on the type, each rule requires different parameters.	false	enum
serviceClass	Relevant for Bluetooth devices only	false	string
status	Defines if rule is Enabled or Disabled.	false	enum
uid	Relevant USB Mass storage devices only (Interface=USB, Class=mass storage).	false	string
vendorId	Vendor identifier. Mandatory when rule type is vendor id or product id.	false	string
version	The version of the device.	false	string

Copy Rules

POST /web/api/v2.1/device-control/copy-rules

You can copy a set of Device Control rules to use in other Accounts, Sites, or Groups. Copy the rules from a source Group, Site, or Account to target Groups, Sites, or Accounts.

Define the rules to copy with the filters. To get the values for devices, run "unscoped". To get Account IDs, run "accounts". To get Site IDs, run "sites".

Device Control requires Control SKU. Linux Agents do not support Device Control.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Copy Rules - response - data table
errors	Errors	false	array

Copy Rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Copy Rules - body - filter table
data	Data	false	see Copy Rules - body - data table

Copy Rules - body - filter

Name	Description	Required	Value
accessPermissions	Access permission in	false	string []
accountIds	List of Account IDs to filter by	false	string []
actions	Return device rules with the filtered action.	false	string []
bluetoothAddresses	Return device rules with the filtered bluetooth addresses.	false	string []
createdAt__between	Return device rules created within this range (inclusive)	false	string
createdAt__gt	Return device rules created after this timestamp.	false	string
createdAt__gte	Return device rules created after or at this timestamp.	false	string
createdAt__lt	Return device rules created before this timestamp.	false	string
createdAt__lte	Return device rules created before or at this timestamp.	false	string
deviceClasses	Return device rules with the filtered device class.	false	string []
deviceIds	Return device rules with the filtered device id.	false	string []
deviceInformationServiceInfoKeys	Return device rules with the filtered device information service info keys.	false	string []
deviceNames	Return device rules with the filtered device names.	false	string []
gattServices	Return device rules with the filtered GATT services.	false	string []
groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
interfaces	Return device rules with the filtered interface.	false	string []
manufacturerNames	Return device rules with the filtered manufacturer names.	false	string []

minorClasses	Return device rules with the filtered minor classes.	false	string []
productIds	Return device rules with the filtered product id.	false	string []
query	A free-text search term, will match applicable attributes.	false	string
ruleName	Return device rules with the filtered rule name.	false	string
scopes	Return only device rules in this scope	false	string []
serviceClasses	Return device rules with the filtered service class.	false	string []
sitelds	List of Site IDs to filter by	false	string []
statuses	Return device rules with the filtered status.	false	string []
tenant	Indicates a tenant scope request	false	boolean
uids	Return device rules with the filtered uid.	false	string []
vendorIds	Return device rules with the filtered vendor id.	false	string []
versions	Return device rules with the filtered versions.	false	string []

Copy Rules - body - data

Name	Description	Required	Value
accountId	Target account (or "null" for global scope)	false	string
groupId	Target group(s)	false	string []
siteld	Target site (or "null" for global scope)	false	string

Move rules

POST /web/api/v2.1/device-control/move-rules

You can move a set of Device Control rules to other Accounts, Sites, or Groups. This command removes the rule from the source and copies to the targets. Define the rules to copy with the filters. To get the values for devices, run "unscoped". To get Account IDs, run "accounts". To get Site IDs, run "sites". Device Control requires Control SKU. Linux Agents do not support Device Control.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Move rules - response - data table
errors	Errors	false	array

Move rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Move rules - body - filter table
data	Data	false	see Move rules - body - data table

Move rules - body - filter

Name	Description	Required	Value
accessPermissions	Access permission in	false	string []
accountIds	List of Account IDs to filter by	false	string []
actions	Return device rules with the filtered action.	false	string []
bluetoothAddresses	Return device rules with the filtered bluetooth addresses.	false	string []
createdAt__between	Return device rules created within this range (inclusive)	false	string
createdAt__gt	Return device rules created after this timestamp.	false	string
createdAt__gte	Return device rules created after or at this timestamp.	false	string
createdAt__lt	Return device rules created before this timestamp.	false	string
createdAt__lte	Return device rules created before or at this timestamp.	false	string
deviceClasses	Return device rules with the filtered device class.	false	string []
deviceIds	Return device rules with the filtered device id.	false	string []
deviceInformationServiceInfoKeys	Return device rules with the filtered device information service info keys.	false	string []
deviceNames	Return device rules with the filtered device names.	false	string []
gattServices	Return device rules with the filtered GATT services.	false	string []
groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
interfaces	Return device rules with the filtered interface.	false	string []
manufacturerNames	Return device rules with the filtered manufacturer names.	false	string []

minorClasses	Return device rules with the filtered minor classes.	false	string []
productIds	Return device rules with the filtered product id.	false	string []
query	A free-text search term, will match applicable attributes.	false	string
ruleName	Return device rules with the filtered rule name.	false	string
scopes	Return only device rules in this scope	false	string []
serviceClasses	Return device rules with the filtered service class.	false	string []
sitelds	List of Site IDs to filter by	false	string []
statuses	Return device rules with the filtered status.	false	string []
tenant	Indicates a tenant scope request	false	boolean
uids	Return device rules with the filtered uid.	false	string []
vendorIds	Return device rules with the filtered vendor id.	false	string []
versions	Return device rules with the filtered versions.	false	string []

Move rules - body - data

Name	Description	Required	Value
accountId	Target account (or "null" for global scope)	false	string
groupId	Target group(s)	false	string []
siteld	Target site (or "null" for global scope)	false	string

Reorder Rules

PUT /web/api/v2.1/device-control/reorder

When an external device connects to an endpoint, the SentinelOne Agent looks at the rules based on their order in the Device Control policy, from the top to the bottom. When the Agent finds a rule that matches the device identifiers of a connected device, that rule is applied. The Agent does not continue to the lower rules in the list. Use this command to change the order of rules for a specific scope.

Device Control requires Control SKU. Linux Agents do not support Device Control.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Reorder Rules - response - data table
errors	Errors	false	array

Reorder Rules - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Reorder Rules - body - filter table
data	Data	false	see Reorder Rules - body - data table

Reorder Rules - body - filter

Name	Description	Required	Value
interface	The physical bus type of the device.	true	enum
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Reorder Rules - body - data

Name	Description	Required	Value
id	Rule ID	true	string
order	Desired position in the list of rules	true	integer

Get Configuration

GET /web/api/v2.1/device-control/configuration

Get Device Control configuration for a given scope.

To filter the results for a scope:

* Global - Make sure "tenant" is "true" and no other scope ID is given.

* Account - Make sure "tenant" is "false" and at least one Account ID is given.

* Site - Make sure "tenant" is "false" and at least one Site ID is given.
Device Control requires Control SKU. It is not supported on Linux.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

tenant	optional	Indicates a tenant scope request
--------	----------	----------------------------------

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Configuration - response - data table
errors	Errors	false	array

Get Configuration - response - data

Name	Description	Required	Value
disableBleCommunication	Disable Bluetooth LE Communication	false	boolean
disableRfcomm	Disable RFCOMM for Bluetooth devices	false	boolean
disallowAccessPermissionControl	Disallow access permission control (i.e. treat Read-Only rules as Read-Write)	false	boolean
enabled	Device control enabled for the scope	false	boolean
inheritedFrom	If null it means it is own policy else it will be site or global to state which policy is being inherited.	false	string
inherits	True if rules are decoupled from parent rules	false	boolean
reportApproved	Agent should report connected/disconnected events	false	boolean
reportBlocked	Agent should report blocked events	false	boolean
reportReadOnly	Agent should report 'connected as read-only' events	false	boolean

Update Configuration

PUT /web/api/v2.1/device-control/configuration

Use this command to change the Device Control configuration. Enter a Group ID, Site ID, Account ID, or "tenant = true". If you select only tenant, and the other scopes are empty, the change is applied to the Global policy.

Device Control requires Control SKU. It is not supported on Linux.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Configuration - response - data table
errors	Errors	false	array

Update Configuration - response - data

Name	Description	Required	Value
disableBleCommunication	Disable Bluetooth LE Communication	false	boolean
disableRfcomm	Disable RFCOMM for Bluetooth devices	false	boolean
disallowAccessPermissionControl	Disallow access permission control (i.e. treat Read-Only rules as Read-Write)	false	boolean
enabled	Device control enabled for the scope	false	boolean
inheritedFrom	If null it means it is own policy else it will be site or global to state which policy is being inherited.	false	string
inherits	True if rules are decoupled from parent rules	false	boolean
reportApproved	Agent should report connected/disconnected events	false	boolean
reportBlocked	Agent should report blocked events	false	boolean
reportReadOnly	Agent should report 'connected as read-only' events	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Configuration - body - data table
filter	Filter	true	see Update Configuration - body - filter table

Update Configuration - body - data

Name	Description	Required	Value
disableBleCommunication	Disable Bluetooth LE Communication	false	boolean
disableRfcomm	Disable RFCOMM for Bluetooth devices	false	boolean
disallowAccessPermissionControl	Disallow access permission control (i.e. treat Read-Only rules as Read-Write)	false	boolean
enabled	Device control enabled for the scope	false	boolean
inheritedFrom	If null it means it is own policy else it will be site or global to state which policy is being inherited.	false	string
inherits	True if rules are decoupled from parent rules	false	boolean
reportApproved	Agent should report connected/disconnected events	false	boolean
reportBlocked	Agent should report blocked events	false	boolean
reportReadOnly	Agent should report 'connected as read-only' events	false	boolean

Update Configuration - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Export Rules

GET /web/api/v2.1/device-control/export

Export Device Control rules to a CSV file.

Parameters

accesspermissions	optional	Access permission in. Example: "Read-Only".
accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
actions	optional	Return device rules with the filtered action. Example: "Allow".
bluetoothaddresses	optional	Return device rules with the filtered bluetooth addresses.
createdat__between	optional	Return device rules created within this range (inclusive). Example: "1514978764288-1514978999999".
createdat__gt	optional	Return device rules created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Return device rules created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Return device rules created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Return device rules created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
deviceclasses	optional	Return device rules with the filtered device class. Example: "02h".
deviceids	optional	Return device rules with the filtered device id. Example: "02".
deviceinformationserviceinfokeys	optional	Return device rules with the filtered device information service info keys.
devicenames	optional	Return device rules with the filtered device names.
gattservices	optional	Return device rules with the filtered GATT services.
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of ids to filter by. Example: "225494730938493804,225494730938493915".
interfaces	optional	Return device rules with the filtered interface. Example: "USB".
manufacturernames	optional	Return device rules with the filtered manufacturer names.
minorclasses	optional	Return device rules with the filtered minor classes.
productids	optional	Return device rules with the filtered product id. Example: "02".
query	optional	A free-text search term, will match applicable attributes.
rulename	optional	Return device rules with the filtered rule name.

scopes	optional	Return only device rules in this scope. Example: "account".
serviceclasses	optional	Return device rules with the filtered service class. Example: "02".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
statuses	optional	Return device rules with the filtered status. Example: "Enabled".
tenant	optional	Indicates a tenant scope request
uids	optional	Return device rules with the filtered uid.
vendorids	optional	Return device rules with the filtered vendor id.
versions	optional	Return device rules with the filtered versions.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Get Device Control Events

GET /web/api/v2.1/device-control/events

Get the data of Device Control events on Windows and macOS endpoints with Device Control-enabled Agents that match the filter. Device Control requires Control SKU. Linux Agents do not support Device Control.

Parameters

accesspermissions	optional	Access permission in. Example: "Read-Only".
accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
agentids	optional	List of agent ids to filter by
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".

deviceclasses	optional	List of device classes to filter by. Example: "02h".
deviceids	optional	List of device IDs to filter by
eventids	optional	List of event IDs to filter by
eventtime__between	optional	Return events created within this range (inclusive). Example: "1514978764288-1514978999999".
eventtime__gt	optional	Return events generated after this time. Example: "2018-02-27T04:49:26.257525Z".
eventtime__gte	optional	Return events generated after or at this time. Example: "2018-02-27T04:49:26.257525Z".
eventtime__lt	optional	Return events generated before this time. Example: "2018-02-27T04:49:26.257525Z".
eventtime__lte	optional	Return events generated before or at this time. Example: "2018-02-27T04:49:26.257525Z".
eventtypes	optional	List of event types to filter by.
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of IDs to filter by. Example: "225494730938493804,225494730938493915".
interfaces	optional	List of interfaces to filter by. Example: "USB".
limit	optional	Limit number of returned items (1-1000). Example: "10".
productids	optional	List of product IDs to filter by. Example: "02".
query	optional	A free-text search term, will match applicable attributes.
serviceclasses	optional	List of service classes to filter by. Example: "02".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
tenant	optional	Indicates a tenant scope request
uids	optional	List of uids to filter by.

vendorids	optional	List of vendor IDs to filter by.
-----------	----------	----------------------------------

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Device Control Events - response - pagination table
data	Response data	false	see Get Device Control Events - response - data table
errors	Errors	false	array

Get Device Control Events - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Device Control Events - response - data

Name	Description	Required	Value
accessPermission	Access permission	false	enum
agentId	Agent id	false	string
computerName	Computer name	false	string
createdAt	Created at	false	string
deviceClass	Device class	false	string
deviceId	Device id	false	string
deviceName	Device name	false	string
eventId	Event id	false	string
eventTime	Event time	false	string
eventType	Event type	false	string
id	Id	false	string
interface	Interface	false	enum
lastLoggedInUserName	Last logged in user name	false	string
impVersion	Lmp version	false	string
minorClass	Minor class	false	string
productId	Product id	false	string
profileUuids	Profile uuids	false	string
ruleId	Rule id	false	string

serviceClass	Service class	false	string
uld	U id	false	string
updatedAt	Updated at	false	string
vendorId	Vendor id	false	string

Enable/Disable Rules

PUT /web/api/v2.1/device-control/enable

It is best practice to disable a rule rather than delete it. Use this command to change the status of a rule between Enabled and Disabled.

Note: On Windows, if a USB device is already connected to an endpoint, new rules and rule changes do not affect it. USB rules will apply the next time the device connects to the endpoint. For Windows Bluetooth rules, the device and endpoint must be paired after the SentinelOne Agent that supports Bluetooth is installed or upgraded. If the endpoint and device were already paired before the Agent supported bluetooth, reboot the endpoint to activate the rule, or re-pair the endpoint and device.

On macOS, changes apply to devices that are already connected to an endpoint.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Enable/Disable Rules - response - data table
errors	Errors	false	array

Enable/Disable Rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Enable/Disable Rules - body - data table
filter	Filter	true	see Enable/Disable Rules - body - filter table

Enable/Disable Rules - body - data

Name	Description	Required	Value
status	should the rules be enabled/disabled	true	enum

Enable/Disable Rules - body - filter

Name	Description	Required	Value
accessPermissions	Access permission in	false	string []
accountIds	List of Account IDs to filter by	false	string []
actions	Return device rules with the filtered action.	false	string []
bluetoothAddresses	Return device rules with the filtered bluetooth addresses.	false	string []
createdAt__between	Return device rules created within this range (inclusive)	false	string
createdAt__gt	Return device rules created after this timestamp.	false	string
createdAt__gte	Return device rules created after or at this timestamp.	false	string
createdAt__lt	Return device rules created before this timestamp.	false	string
createdAt__lte	Return device rules created before or at this timestamp.	false	string
deviceClasses	Return device rules with the filtered device class.	false	string []
deviceIds	Return device rules with the filtered device id.	false	string []
deviceInformationServiceInfoKeys	Return device rules with the filtered device information service info keys.	false	string []
deviceNames	Return device rules with the filtered device names.	false	string []
gattServices	Return device rules with the filtered GATT services.	false	string []

groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
interfaces	Return device rules with the filtered interface.	false	string []
manufacturerNames	Return device rules with the filtered manufacturer names.	false	string []
minorClasses	Return device rules with the filtered minor classes.	false	string []
productIds	Return device rules with the filtered product id.	false	string []
query	A free-text search term, will match applicable attributes.	false	string
ruleName	Return device rules with the filtered rule name.	false	string
scopes	Return only device rules in this scope	false	string []
serviceClasses	Return device rules with the filtered service class.	false	string []
sitIds	List of Site IDs to filter by	false	string []
statuses	Return device rules with the filtered status.	false	string []
tenant	Indicates a tenant scope request	false	boolean
uids	Return device rules with the filtered uid.	false	string []
vendorIds	Return device rules with the filtered vendor id.	false	string []
versions	Return device rules with the filtered versions.	false	string []

Dynamic tag rules

Get all tags rules

GET /web/api/v2.1/xdr/assets/tags/rules

Get all tags rules

Parameters

accountids	optional	List of Account IDs to filter by
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdbyemail	optional	Filter by created by emails of the tag rules.
createdbyemail__nin	optional	Negative filter by created by emails of the tag rules.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
description	optional	Filter by description of the tag rules.
description__nin	optional	Negative filter by descriptions of the tag rules.
groupids	optional	List of Group IDs to filter by
ids	optional	The list of tag rule ID identifiers.
limit	optional	Limit number of returned items (1-1000)
name	optional	Filter by names of the tag rules.
name__nin	optional	Negative filter by names of the tag rules.
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
status	optional	Status
tagids	optional	The list of tag identifiers that the rule is associated with.
updatedbyemail	optional	Filter by updated by emails of the tag rules.
updatedbyemail__nin	optional	Negative filter by updated by emails of the tag rules.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Get all tags rules - response - pagination table

Get all tags rules - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Create new tag rule

POST /web/api/v2.1/xdr/assets/tags/rules

Create new tag rule

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
name	The name of the tag rule.	true	string
accountId	The account ID of the tag rule.	false	string
conditions		false	see Create new tag rule - response - conditions table

createdAt	The date and time when the tag rule was created.	false	string
createdByEmail	The email of the user who created the tag rule.	false	string
createdById	The ID of the user who created the tag rule.	false	string
description	The description of the tag rule.	false	string
excludedAssets	The list of excluded asset IDs.	false	string []
id	The ID of the tag rule.	false	string
mgmtId	The management ID of the tag rule.	false	string
scopes		false	see Create new tag rule - response - scopes table
siteId	The site ID of the tag rule.	false	string
status	The status of the tag rule (enabled or disabled).	false	string
tags	The list of tags associated with the rule.	false	undefined []
updatedAt	The date and time when the tag rule was last updated.	false	string
updatedByEmail	The email of the user who last updated the tag rule.	false	string
updatedById	The ID of the user who last updated the tag rule.	false	string

Create new tag rule - response - conditions

Name	Description	Required	Value
operand	The operand to apply to the asset properties.	false	enum
properties	Properties	false	undefined []

Create new tag rule - response - scopes

Name	Description	Required	Value
scopelds		false	see Create new tag rule - response - scopelds table
scopeType	The type of the scope (account or site).	false	string

Create new tag rule - response - scopelds

Name	Description	Required	Value
accounts	The list of account IDs.	false	string []
sites	The list of site IDs. Can be empty. When not empty, the account IDs must contain only one account ID.	false	string []

Body Schema

Name	Description	Required	Value
name	The name of the tag rule.	true	string
accountId	The account ID of the tag rule.	false	string
conditions		false	see Create new tag rule - body - conditions table
createdAt	The date and time when the tag rule was created.	false	string
createdByEmail	The email of the user who created the tag rule.	false	string

createdById	The ID of the user who created the tag rule.	false	string
description	The description of the tag rule.	false	string
excludedAssets	The list of excluded asset IDs.	false	string []
id	The ID of the tag rule.	false	string
mgmtId	The management ID of the tag rule.	false	string
scopes		false	see Create new tag rule - body - scopes table
siteId	The site ID of the tag rule.	false	string
status	The status of the tag rule (enabled or disabled).	false	string
tags	The list of tags associated with the rule.	false	undefined []
updatedAt	The date and time when the tag rule was last updated.	false	string
updatedByEmail	The email of the user who last updated the tag rule.	false	string
updatedById	The ID of the user who last updated the tag rule.	false	string

Create new tag rule - body - conditions

Name	Description	Required	Value
operand	The operand to apply to the asset properties.	false	enum
properties	Properties	false	undefined []

Create new tag rule - body - scopes

Name	Description	Required	Value
scopelds		false	see Create new tag rule - body - scopelds table
scopeType	The type of the scope (account or site).	false	string

Create new tag rule - body - scopelds

Name	Description	Required	Value
accounts	The list of account IDs.	false	string []
sites	The list of site IDs. Can be empty. When not empty, the account IDs must contain only one account ID.	false	string []

Delete tag rules

DELETE /web/api/v2.1/xdr/assets/tags/rules

Delete tag rules

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
ids	optional	The list of tag rule ID identifiers to be removed.

siteids	optional	List of Site IDs to filter by
---------	----------	-------------------------------

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Delete tag rules - response - data table
errors	Errors	false	array

Delete tag rules - response - data

Name	Description	Required	Value
affected	Affected	false	integer

Update tag rule

PUT /web/api/v2.1/xdr/assets/tags/rules

Update tag rule

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
name	The name of the tag rule.	true	string
accountId	The account ID of the tag rule.	false	string
conditions		false	see Update tag rule - response - conditions table
createdAt	The date and time when the tag rule was created.	false	string
createdByEmail	The email of the user who created the tag rule.	false	string

createdById	The ID of the user who created the tag rule.	false	string
description	The description of the tag rule.	false	string
excludedAssets	The list of excluded asset IDs.	false	string []
id	The ID of the tag rule.	false	string
mgmtId	The management ID of the tag rule.	false	string
scopes		false	see Update tag rule - response - scopes table
siteId	The site ID of the tag rule.	false	string
status	The status of the tag rule (enabled or disabled).	false	string
tags	The list of tags associated with the rule.	false	undefined []
updatedAt	The date and time when the tag rule was last updated.	false	string
updatedByEmail	The email of the user who last updated the tag rule.	false	string
updatedById	The ID of the user who last updated the tag rule.	false	string

Update tag rule - response - conditions

Name	Description	Required	Value
operand	The operand to apply to the asset properties.	false	enum
properties	Properties	false	undefined []

Update tag rule - response - scopes

Name	Description	Required	Value
scopelds		false	see Update tag rule - response - scopelds table
scopeType	The type of the scope (account or site).	false	string

Update tag rule - response - scopelds

Name	Description	Required	Value
accounts	The list of account IDs.	false	string []
sites	The list of site IDs. Can be empty. When not empty, the account IDs must contain only one account ID.	false	string []

Body Schema

Name	Description	Required	Value
name	The name of the tag rule.	true	string
accountId	The account ID of the tag rule.	false	string
conditions		false	see Update tag rule - body - conditions table
createdAt	The date and time when the tag rule was created.	false	string
createdByEmail	The email of the user who created the tag rule.	false	string

createdById	The ID of the user who created the tag rule.	false	string
description	The description of the tag rule.	false	string
excludedAssets	The list of excluded asset IDs.	false	string []
id	The ID of the tag rule.	false	string
mgmtId	The management ID of the tag rule.	false	string
scopes		false	see Update tag rule - body - scopes table
siteId	The site ID of the tag rule.	false	string
status	The status of the tag rule (enabled or disabled).	false	string
tags	The list of tags associated with the rule.	false	undefined []
updatedAt	The date and time when the tag rule was last updated.	false	string
updatedByEmail	The email of the user who last updated the tag rule.	false	string
updatedById	The ID of the user who last updated the tag rule.	false	string

Update tag rule - body - conditions

Name	Description	Required	Value
operand	The operand to apply to the asset properties.	false	enum
properties	Properties	false	undefined []

Update tag rule - body - scopes

Name	Description	Required	Value
scopelds		false	see Update tag rule - body - scopelds table
scopeType	The type of the scope (account or site).	false	string []

Update tag rule - body - scopelds

Name	Description	Required	Value
accounts	The list of account IDs.	false	string []
sites	The list of site IDs. Can be empty. When not empty, the account IDs must contain only one account ID.	false	string []

Check how many assets this tag rule matches

POST /web/api/v2.1/xdr/assets/tags/rules/test

Check how many assets this tag rule matches

Parameters

accountids	optional	List of Account IDs to filter by
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.

cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
groupids	optional	List of Group IDs to filter by
limit	optional	Limit number of returned items (1-1000)
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Check how many assets this tag rule matches - response - pagination table

Check how many assets this tag rule matches - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
name	The name of the tag rule.	true	string
accountId	The account ID of the tag rule.	false	string
conditions		false	see Check how many assets this tag rule matches - body - conditions table
createdAt	The date and time when the tag rule was created.	false	string
createdByEmail	The email of the user who created the tag rule.	false	string
createdById	The ID of the user who created the tag rule.	false	string
description	The description of the tag rule.	false	string
excludedAssets	The list of excluded asset IDs.	false	string []
id	The ID of the tag rule.	false	string
mgmtId	The management ID of the tag rule.	false	string
scopes		false	see Check how many assets this tag rule matches - body - scopes table
siteId	The site ID of the tag rule.	false	string
status	The status of the tag rule (enabled or disabled).	false	string
tags	The list of tags associated with the rule.	false	undefined []
updatedAt	The date and time when the tag rule was last updated.	false	string
updatedByEmail	The email of the user who last	false	string

	updated the tag rule.		
updatedById	The ID of the user who last updated the tag rule.	false	string

Check how many assets this tag rule matches - body - conditions

Name	Description	Required	Value
operand	The operand to apply to the asset properties.	false	enum
properties	Properties	false	undefined []

Check how many assets this tag rule matches - body - scopes

Name	Description	Required	Value
scopelds		false	see Check how many assets this tag rule matches - body - scopelds table
scopeType	The type of the scope (account or site).	false	string

Check how many assets this tag rule matches - body - scopelds

Name	Description	Required	Value
accounts	The list of account IDs.	false	string []
sites	The list of site IDs. Can be empty. When not empty, the account IDs must contain only one account ID.	false	string []

Exclusions and Blocklist

Import Exclusions

POST /web/api/v2.1/exclusions/import

Upload a CSV file that contains exclusion entries to import to a scope in your Management

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Import Exclusions - response - data table
errors	Errors	false	array

Import Exclusions - response - data

Name	Description	Required	Value
reportId	The ID of the Validation Report generated for the import. It can help you fix entries that did not import successfully.	false	string
succeeded	The number of entries that imported successfully	false	integer
total	The number of rows in the file	false	integer

Body Schema

Name	Description	Required	Value
formData		false	see Import Exclusions - body - formData table

Import Exclusions - body - formData

Name	Description	Required	Value
file	The input CSV file	true	file
filter	The details of the scope where the entities will be imported, for example: For Global - '{"tenant":true}' For an Account - '{"accountIds":["225494730938493804"]}' For a Site - '{"siteIds":["225494730938493804"]}' For a Group - '{"groupIds":["225494730938493804"]}'	false	string

Get Exclusion Import Validation Report

GET /web/api/v2.1/exclusions/report/{report_id}

Get the Validation Report generated for the import to help you fix entries that did not import successfully

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Import Blocklist Items

POST /web/api/v2.1/restrictions/import

Upload a CSV file that contains blocklist entries to import to a scope in your Management

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Import Blocklist Items - response - data table
errors	Errors	false	array

Import Blocklist Items - response - data

Name	Description	Required	Value
reportId	The ID of the Validation Report generated for the import. It can help you fix entries that did not import successfully.	false	string
succeeded	The number of entries that imported successfully	false	integer
total	The number of rows in the file	false	integer

Body Schema

Name	Description	Required	Value
formData		false	see Import Blocklist Items - body - formData table

Import Blocklist Items - body - formData

Name	Description	Required	Value
file	The input CSV file	true	file
filter	The details of the scope where the entities will be imported, for example: For Global - '{"tenant":true}' For an Account - '{"accountIds":["225494730938493804"]}' For a Site - '{"siteIds":["225494730938493804"]}' For a Group - '{"groupIds":["225494730938493804"]}'	false	string

Get Blocklist Import Validation Report

GET /web/api/v2.1/restrictions/report/{report_id}

Get the Validation Report generated for the import to help you fix entries that did not import successfully

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Get Exclusions

GET /web/api/v2.1/exclusions

Get a list of all the Exclusions that match the filter.

Note: To filter the results for a scope:

- * Global - Make sure "tenant" is "true" and no other scope ID is given.
- * Account - Make sure "tenant" is "false" and at least one Account ID is given.
- * Site - Make sure "tenant" is "false" and at least one Site ID is given.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
applicationname__contains	optional	Free-text filter by application name
childprocess	optional	Child process
conditions	optional	Conditions in. Example: "white_hash".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdat__gt	optional	Created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
description__contains	optional	Free-text filter by description
engines	optional	Engine in. Example: "suppress".
exclusionname__contains	optional	Exclusion name like any
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of IDs to filter by. Example: "225494730938493804,225494730938493915".
imported	optional	Filter by import status: true (imported), false (not imported), or both for multiselect
inappinventory	optional	Found or Not found - indicates if this exclusion is related to an application found in the scope's Application Inventory.

includechildren	optional	Return filters from children scope levels (Default: false)
includeparents	optional	Return filters from parent scope levels (Default: false)
interactionlevel	optional	Interaction level in. Example: "disable_all_monitors".
limit	optional	Limit number of returned items (1-1000). Example: "10".
modes	optional	List of modes to filter by (Path exclusions only). Example: "suppress".
modetype	optional	Mode type. Example: "all".
notrecommended	optional	Not recommended in. Example: "Not recommended".
ostypes	optional	List of Os types to filter by. Example: "linux".
pathexclusiontypes	optional	List of excluded paths in an exclusion (Path exclusions only). Example: "file".
query	optional	A free-text search term, will match applicable attributes
recommendations	optional	List of recommendations to filter by. Example: "Not recommended".
scopepath__contains	optional	Scope path like any
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
source	optional	List sources to filter by. Example: "user".
tenant	optional	Indicates a tenant scope request
threatype	optional	Threat type in. Example: "EDR".
type	optional	Type. Example: "path".
types	optional	Type in. Example: "path".
unified	optional	Unified
updatedat__between	optional	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedat__gt	optional	Updated after this timestamp. Example: "2018-02-27T04:49:26.257525Z".

updatedat__gte	optional	Updated after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Updated before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Updated before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
user__contains	optional	Free-text filter by user name
userids	optional	List of user ids to filter by. Example: "225494730938493804,225494730938493915".
value	optional	Value
value__contains	optional	Free-text filter by value

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Exclusions - response - pagination table
data	Response data	false	see Get Exclusions - response - data table
errors	Errors	false	array

Get Exclusions - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Exclusions - response - data

Name	Description	Required	Value
actions	Actions to perform	false	string []
applicationName	The Application name of exclusions created from the Exclusion Catalog.	false	string
createdAt	Timestamp of item creation	false	string
description	Description	false	string
id	The ID of the exclusion	false	string
imported	indication whether the exclusion was imported by a bulk operation or not	false	boolean
inAppInventory	Found or Not found - indicates if this exclusion is related to an application found in the scope's Application Inventory.	false	boolean
includeChildren	Return filters from children scope levels (Default: false)	false	boolean
includeParents	Return filters from parent scope levels (Default: false)	false	boolean
inject	[DEPRECATED] Path exclusion monitor mode	false	boolean
mode	Exclusion mode (path exclusion only)	false	enum
notRecommended	Not recommended	false	string
osType	os_type	false	enum

pathExclusionType	Excluded path for a path exclusion list	false	enum
scope	Scope	false	see Get Exclusions - response - scope table
scopeName	Scope name	false	string
scopePath	Scope path	false	string
source	Source: cloud, user, action_from_threat, catalog, or performance_insight	false	enum
type	type	false	string
updatedAt	Timestamp of item update	false	string
userId	ID of the creating user	false	string
userName	Name of the creating user	false	string
value	Sha1 if hash type or value according to the exclusion list type	false	string

Get Exclusions - response - scope

Name	Description	Required	Value
accountIds	Account ids	false	string []
groupIds	Group ids	false	string []
siteIds	Site ids	false	string []
tenant	Tenant	false	boolean

Create Exclusion

POST /web/api/v2.1/exclusions

Create Exclusions to make your Agents suppress alerts and mitigation for items that you consider to be benign or which you require for interoperability.

IMPORTANT! Every Exclusion is a possible security hole. Do not create Exclusions unless you are sure this hash, path, certificate signer, file type, or browser is always benign.

Of course, if you can make the Exclusion by its hash or path, that is much more secure than excluding all detections of a specific signer, file type, or browser. We do not recommend the last types for Exclusions on production endpoints. These Exclusions might be helpful in a lab or pentester group. When you create an Exclusion, make sure you set the filter to the smallest possible scope. For example, if you can exclude security for this item on a group, do not enter values for siteIds or accountIds.

We recommend that you read "Not Recommended Exclusions: <https://support.sentinelone.com/hc/en-us/articles/360007532894>

and Best Practices for Exclusions: <https://support.sentinelone.com/hc/en-us/articles/360008709014>

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Exclusion - response - data table
errors	Errors	false	array

Create Exclusion - response - data

Name	Description	Required	Value
scope	Scope	true	see Create Exclusion - response - scope table
actions	Actions to perform	false	string []
createdAt	Timestamp of exclusion item creation	false	string
description	Description	false	string
id	The ID of the exclusion	false	
inject	[DEPRECATED] Path exclusion monitor mode	false	boolean
mode	Exclusion mode (path exclusion only)	false	enum
notRecommended	Not recommended	false	string
osType	OS type	false	enum
pathExclusionType	Excluded path for a path exclusion list	false	enum
scopeName	Scope name	false	string
source	Source: cloud, user, action_from_threat, catalog, or performance_insight	false	enum
type	Type	false	string
updatedAt	Timestamp of exclusion item update	false	string
userId	ID of the creating user	false	string
userName	Name of the creating user	false	string
value	Sha1 if hash type or value according to the exclusion list type	false	string

Create Exclusion - response - scope

Name	Description	Required	Value
accountIds	Account ids	false	string []
groupIds	Group ids	false	string []
siteIds	Site ids	false	string []

tenant	Tenant	false	boolean
--------	--------	-------	---------

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Exclusion - body - data table
filter	Filter	true	see Create Exclusion - body - filter table

Create Exclusion - body - data

Name	Description	Required	Value
osType	OS type	true	enum
type	Exclusion item type	true	enum
value	Valid values depend on the item type	true	
actions	Actions to perform	false	string []
description	Description	false	string
inject	[DEPRECATED] Path exclusion monitor mode	false	boolean
mode	Exclusion mode (path exclusion only)	false	enum
pathExclusionType	Excluded path for a path exclusion list	false	string
source	Source	false	string

Create Exclusion - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Update Exclusions

PUT /web/api/v2.1/exclusions

Change the properties of an Exclusion through the data fields. To get the original data, run "exclusions" with a filter to give the item you want.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Exclusion not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Exclusions - response - data table
errors	Errors	false	array

Update Exclusions - response - data

Name	Description	Required	Value
scope	Scope	true	see Update Exclusions - response - scope table
actions	Actions to perform	false	string []
createdAt	Timestamp of exclusion item creation	false	string
description	Description	false	string
id	The ID of the exclusion	false	
inject	[DEPRECATED] Path exclusion monitor mode	false	boolean
mode	Exclusion mode (path exclusion only)	false	enum
notRecommended	Not recommended	false	string
osType	OS type	false	enum
pathExclusionType	Excluded path for a path exclusion list	false	enum
scopeName	Scope name	false	string
source	Source: cloud, user, action_from_threat, catalog, or performance_insight	false	enum
type	Type	false	string
updatedAt	Timestamp of exclusion item update	false	string
userId	ID of the creating user	false	string
userName	Name of the creating user	false	string
value	Sha1 if hash type or value according to the exclusion list type	false	string

Update Exclusions - response - scope

Name	Description	Required	Value
accountIds	Account ids	false	string []
groupIds	Group ids	false	string []
siteIds	Site ids	false	string []

tenant	Tenant	false	boolean
--------	--------	-------	---------

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Exclusions - body - data table

Update Exclusions - body - data

Name	Description	Required	Value
id	Id	true	string
osType	OS type	true	enum
type	Exclusion item type	true	enum
actions	Actions to perform	false	string []
description	Description	false	string
inject	[DEPRECATED] Path exclusion monitor mode	false	boolean
mode	Exclusion mode (path exclusion only)	false	enum
pathExclusionType	Excluded path for a path exclusion list	false	string
sha256Value	Sha256 value	false	string
source	Source	false	string
value	Value	false	

Delete Exclusions

DELETE /web/api/v2.1/exclusions

Every Exclusion opens a possible security hole. If you decide that an Exclusion (or multiple Exclusions) is not required, use this command to delete it. To get the ID of the Exclusion to delete, run the "exclusions" command.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Delete Exclusions - response - data table
errors	Errors	false	array

Delete Exclusions - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Delete Exclusions - body - data table

Delete Exclusions - body - data

Name	Description	Required	Value
ids	Ids	false	string []
type	Type	false	enum

Get Blocklist

GET /web/api/v2.1/restrictions

Get a list of all the items in the Blocklist that match the filter.

To filter the results for a scope:

- * Global - Make sure "tenant" is "true" and no other scope ID is given.
- * Account - Make sure "tenant" is "false" and at least one Account ID is given.
- * Site - Make sure "tenant" is "false" and at least one Site ID is given.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdat__gt	optional	Created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example:

		"YWdlbnRfaWQ6NTgwMjkzODE=".
description__contains	optional	Free-text filter by description
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of IDs to filter by. Example: "225494730938493804,225494730938493915".
imported	optional	Filter by import status: true (imported), false (not imported), or both for multiselect
includechildren	optional	Return filters from children scope levels (Default: false)
includeparents	optional	Return filters from parent scope levels (Default: false)
limit	optional	Limit number of returned items (1-1000). Example: "10".
modes	optional	List of modes to filter by (Path exclusions only). Example: "suppress".
ostypes	optional	List of Os types to filter by. Example: "linux".
query	optional	A free-text search term, will match applicable attributes
recommendations	optional	List of recommendations to filter by. Example: "Not recommended".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
source	optional	List sources to filter by. Example: "user".
tenant	optional	Indicates a tenant scope request
type	optional	Type. Example: "black_hash".
types	optional	Type in. Example: "black_hash".
unified	optional	Unified
updatedat__between	optional	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedat__gt	optional	Updated after this timestamp. Example:

		"2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Updated after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Updated before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Updated before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
user__contains	optional	Free-text filter by user name
userids	optional	List of user ids to filter by. Example: "225494730938493804,225494730938493915".
value	optional	Value
value__contains	optional	Free-text filter by value

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Blocklist - response - pagination table
data	Response data	false	see Get Blocklist - response - data table
errors	Errors	false	array

Get Blocklist - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Blocklist - response - data

Name	Description	Required	Value
createdAt	Timestamp of item creation	false	string
description	Description	false	string
id	The ID of the restriction	false	string
imported	indication whether the exclusion was imported by a bulk operation or not	false	boolean
includeChildren	Return filters from children scope levels (Default: false)	false	boolean
includeParents	Return filters from parent scope levels (Default: false)	false	boolean
notRecommended	Not recommended	false	string
osType	os_type	false	enum
scope	Scope	false	see Get Blocklist - response - scope table
scopeName	Scope name	false	string
scopePath	Scope path	false	string
sha256Value	SHA256 hash value	false	string
source	Source: cloud, user, action_from_threat, catalog, or performance_insight	false	enum
type	type	false	string
updatedAt	Timestamp of item update	false	string

userId	ID of the creating user	false	string
userName	Name of the creating user	false	string
value	SHA1 hash	false	string

Get Blocklist - response - scope

Name	Description	Required	Value
accountIds	Account ids	false	string []
groupIds	Group ids	false	string []
siteIds	Site ids	false	string []
tenant	Tenant	false	boolean

Create Blocklist Item

POST /web/api/v2.1/restrictions

Create a blocklist item for a SHA1 or SHA256 hash or both, for the scopes you enter in the filter fields. You can add the hash to multiple Groups, Sites, Accounts, and to the Global list.

IMPORTANT: The type must be "black_hash" - any other value will create an Exclusion rather than a Blocklist item.

Users with the IT role do not have permissions to run this.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Blocklist Item - response - data table
errors	Errors	false	array

Create Blocklist Item - response - data

Name	Description	Required	Value
createdAt	Timestamp of item creation	false	string
description	Description	false	string
hashId	Hash id	false	string
id	The ID of the restriction	false	string
notRecommended	Not recommended	false	string
osType	os_type	false	enum
scope	Scope	false	see Create Blocklist Item - response - scope table
scopeName	Scope name	false	string
sha256Value	SHA256 hash value	false	string
source	Source: cloud, user, action_from_threat, catalog, or performance_insight	false	enum
type	type	false	string
updatedAt	Timestamp of item update	false	string
userId	ID of the creating user	false	string
userName	Name of the creating user	false	string
value	SHA1 hash	false	string

Create Blocklist Item - response - scope

Name	Description	Required	Value
accountIds	Account ids	false	string []
groupIds	Group ids	false	string []
siteIds	Site ids	false	string []
tenant	Tenant	false	boolean

Body Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Data	true	see Create Blocklist Item - body - data table
filter	Filter	true	see Create Blocklist Item - body - filter table

Create Blocklist Item - body - data

Name	Description	Required	Value
osType	OS type	true	enum
type	Restriction type	true	enum
description	Description	false	string
sha256Value	SHA256 of the file to add to the blocklist	false	string
source	Source	false	string
value	SHA1 of the file to add to the blocklist	false	

Create Blocklist Item - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Update Blocklist Item

PUT /web/api/v2.1/restrictions

Change the properties of a Blocklist item through the data fields. To get the original data, run "restrictions" with a filter to give the item you want.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Blocklist not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Blocklist Item - response - data table
errors	Errors	false	array

Update Blocklist Item - response - data

Name	Description	Required	Value
createdAt	Timestamp of item creation	false	string
description	Description	false	string
hashId	Hash id	false	string
id	The ID of the restriction	false	string
notRecommended	Not recommended	false	string
osType	os_type	false	enum
scope	Scope	false	see Update Blocklist Item - response - scope table
scopeName	Scope name	false	string
sha256Value	SHA256 hash value	false	string
source	Source: cloud, user, action_from_threat, catalog, or performance_insight	false	enum
type	type	false	string
updatedAt	Timestamp of item update	false	string
userId	ID of the creating user	false	string
userName	Name of the creating user	false	string
value	SHA1 hash	false	string

Update Blocklist Item - response - scope

Name	Description	Required	Value
accountIds	Account ids	false	string []
groupIds	Group ids	false	string []
siteIds	Site ids	false	string []
tenant	Tenant	false	boolean

Body Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Data	true	see Update Blocklist Item - body - data table
filter	Filter	false	see Update Blocklist Item - body - filter table

Update Blocklist Item - body - data

Name	Description	Required	Value
id	Id	true	string
osType	OS type	true	enum
type	Restrictions type (black_hash)	true	enum
description	Description	false	string
sha256Value	Sha256 value	false	string
source	Source	false	string
value	Value	false	

Update Blocklist Item - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Delete Blocklist Item

DELETE /web/api/v2.1/restrictions

Agents immediately identify files on the blocklist and block them from executing. Agents identify files on the blocklist before they look at exclusions. If there is a conflict - for example, if a hash is blocklisted from the Cloud Intelligence, and you have an exclusion to run an application that requires this hash - you can delete the hash from the Blocklist. Users with the IT role do not have permissions to run this command.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Blocklist Item - response - data table
errors	Errors	false	array

Delete Blocklist Item - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Delete Blocklist Item - body - data table

Delete Blocklist Item - body - data

Name	Description	Required	Value
ids	Ids	false	string []
type	Type	false	enum

Validate Exclusion Item

POST /web/api/v2.1/exclusions/validate

Check if an exclusion is on the list of SentinelOne items that are "Not Allowed" or "Not Recommended". This API returns one of the following statuses:

- * Not Recommended: This item is not recommended by SentinelOne because it decreases security. For example, If you accidentally exclude a path that is too broad, malware can enter your environment.
- * Not Allowed: This exclusion can harm the product and lead to unexpected functionality. From version North Pole SP3 you are prevented from creating Not Allowed exclusions.
- * None: This item is not on the list of SentinelOne items that are "Not Allowed" or "Not Recommended".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Validate Exclusion Item - response - data table
errors	Errors	false	array

Validate Exclusion Item - response - data

Name	Description	Required	Value
details	Details	false	see Validate Exclusion Item - response - details table
status	Recommendation for the exclusion/ blocklist item	false	enum

Validate Exclusion Item - response - details

Name	Description	Required	Value
error	Error	true	string
field	Field	true	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Validate Exclusion Item - body - data table

Validate Exclusion Item - body - data

Name	Description	Required	Value
exclusionType	Exclusion type	false	enum
osType	OS type	false	enum
value	Value	false	string

Validate Blocklist Item

POST /web/api/v2.1/restrictions/validate

Check if a hash is on the list of SentinelOne items that are "Not Allowed" or "Not Recommended". This API returns one of the following statuses:

* Not Recommended: This item is not recommended by SentinelOne because it decreases security.

* Not Allowed: This item can harm the product and lead to unexpected functionality. From version North Pole SP3 you are prevented from creating Not Allowed blocklist item. * None: This item is not on the list of SentinelOne items that are "Not Allowed" or "Not Recommended".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Validate Blocklist Item - response - data table
errors	Errors	false	array

Validate Blocklist Item - response - data

Name	Description	Required	Value
details	Details	false	see Validate Blocklist Item - response - details table
status	Recommendation for the exclusion/ blocklist item	false	enum

Validate Blocklist Item - response - details

Name	Description	Required	Value
error	Error	true	string
field	Field	true	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Validate Blocklist Item - body - data table
filter	Filter	false	see Validate Blocklist Item - body - filter table

Validate Blocklist Item - body - data

Name	Description	Required	Value
osType	OS type	false	enum
sha256Value	Sha256 value	false	string
value	Value	false	string

Validate Blocklist Item - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Export Exclusions

GET /web/api/v2.1/export/exclusions

Get a csv of all the items in the Exclusions that match the filter.

Note: To see items from the Global Exclusion scope, make sure "tenant" is "true" and no other scope ID is given.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
applicationname__contains	optional	Free-text filter by application name
childprocess	optional	Child process
conditions	optional	Conditions in. Example: "white_hash".
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".

createdat__gt	optional	Created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
description__contains	optional	Free-text filter by description
engines	optional	Engine in. Example: "suppress".
exclusionname__contains	optional	Exclusion name like any
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of IDs to filter by. Example: "225494730938493804,225494730938493915".
imported	optional	Filter by import status: true (imported), false (not imported), or both for multiselect
inappinventory	optional	Found or Not found - indicates if this exclusion is related to an application found in the scope's Application Inventory.
includechildren	optional	Return filters from children scope levels (Default: false)
includeparents	optional	Return filters from parent scope levels (Default: false)
interactionlevel	optional	Interaction level in. Example: "disable_all_monitors".
modes	optional	List of modes to filter by (Path exclusions only). Example: "suppress".
modetype	optional	Mode type. Example: "all".
notrecommended	optional	Not recommended in. Example: "Not recommended".
ostypes	optional	List of Os types to filter by. Example: "linux".
pathexclusiontypes	optional	List of excluded paths in an exclusion (Path exclusions only). Example: "file".
query	optional	A free-text search term, will match applicable attributes
recommendations	optional	List of recommendations to filter by. Example: "Not recommended".
scopepath__contains	optional	Scope path like any
siteids	optional	List of Site IDs to filter by. Example:

		"225494730938493804,225494730938493915".
source	optional	List sources to filter by. Example: "user".
tenant	optional	Indicates a tenant scope request
threattype	optional	Threat type in. Example: "EDR".
type	optional	Type. Example: "path".
types	optional	Type in. Example: "path".
unified	optional	Unified
updatedat__between	optional	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedat__gt	optional	Updated after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Updated after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Updated before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Updated before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
user__contains	optional	Free-text filter by user name
userids	optional	List of user ids to filter by. Example: "225494730938493804,225494730938493915".
value	optional	Value
value__contains	optional	Free-text filter by value

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Export Blocklist

GET /web/api/v2.1/export/restrictions

Get a csv of all the items in the Blocklist that match the filter.

Note: To see items from the Global Blocklist, make sure "tenant" is "true" and no other scope ID is given.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdat__gt	optional	Created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
description__contains	optional	Free-text filter by description
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of IDs to filter by. Example: "225494730938493804,225494730938493915".
imported	optional	Filter by import status: true (imported), false (not imported), or both for multiselect
includechildren	optional	Return filters from children scope levels (Default: false)
includeparents	optional	Return filters from parent scope levels (Default: false)
ostypes	optional	List of Os types to filter by. Example: "linux".
query	optional	A free-text search term, will match applicable attributes
recommendations	optional	List of recommendations to filter by. Example: "Not recommended".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
source	optional	List sources to filter by. Example: "user".
tenant	optional	Indicates a tenant scope request

type	optional	Type. Example: "black_hash".
types	optional	Type in. Example: "black_hash".
unified	optional	Unified
updatedat__between	optional	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedat__gt	optional	Updated after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Updated after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Updated before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Updated before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
user__contains	optional	Free-text filter by user name
userids	optional	List of user ids to filter by. Example: "225494730938493804,225494730938493915".
value	optional	Value
value__contains	optional	Free-text filter by value

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Exclusions v2.1

Get Exclusions

GET /web/api/v2.1/unified-exclusions

Get a list of all the Exclusions that match the filter.

Note: To filter the results for a scope:

* Global - Make sure "tenant" is "true" and no other scope ID is given.

* Account - Make sure "tenant" is "false" and at least one Account ID is given.

* Site - Make sure "tenant" is "false" and at least one Site ID is given.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
applicationname__contains	optional	Free-text filter by application name.
childprocess	optional	Indicates if the exclusion applies to child processes or not. You can filter by this.
cmdlinevalue__contains	optional	Free-text filter by nested cmdline value.
conditions	optional	List of conditions to filter by. Example: "white_hash".
containername__contains	optional	Free-text filter by container name.
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	comma-separated list of fields to be shown. Example: "threatType,interactionLevel".
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdat__gt	optional	Created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
creator__contains	optional	Free-text filter by creator name.
cursor	optional	Cursor position returned by the last request. Use to iterate over

		more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
description__contains	optional	Free-text filter by description.
engines	optional	List of engines to filter by. Example: "suppress".
exclusionidentifier	optional	Filter by the stable exclusion identifier.
exclusionname__contains	optional	Free-text filter by exclusion name.
fullimagename__contains	optional	Free-text filter by full image URI.
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
hashtags	optional	Include only Exclusions that have any tags assigned if True, or none if False
hashtagsbygroup	optional	Include Exclusions that have any tags assigned if True, or none if False
hits30d__between	optional	Inclusive range for number of hits within the past 30 days. Example: "6-9".
hits90d__between	optional	Inclusive range for number of hits within the past 90 days. Example: "13-37".
hitsalltime__between	optional	Inclusive range for all-time number of hits. Example: "678-9998212".
ids	optional	List of IDs to filter by. Example: "225494730938493804,225494730938493915".
idsnin	optional	List of IDs to exclude from filter. Example: "225494730938493804,225494730938493915".
imported	optional	Indicates if the exclusion was imported by a bulk operation or not. You can filter by this.
inappinventory	optional	Indicates if the exclusion is related to an application found in the scope's Application Inventory or not. You can filter by this.
includechildren	optional	Return filters from children scope levels (Default: false).
includeparents	optional	Return filters from parent scope levels (Default: false).
interactionlevel	optional	List of interaction levels to filter by. Example: "disable_all_monitors".
labelskey__contains	optional	Free-text filter by label key.
labelsvalue__contains	optional	Free-text filter by label value.

lasthit__between	optional	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1775676749738-1775676848156".
lasthit__lt	optional	Last hit before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lasthit__lte	optional	Last hit before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
limit	optional	Limit number of returned items (1-1000). Example: "10".
menutype	optional	Page-scope (left-menu) exclusion grouping, e.g. 'endpoint' (which covers suppression + agent_interoperability). Combined with modeType (the in-table filter) by intersection. Sending modeType alone keeps the previous behaviour. Example: "all".
modetype	optional	List of Exclusion Type to filter by: suppression, agent_interoperability, or binary_vault . Example: "all".
namespace__contains	optional	Free-text filter by namespace.
notrecommended	optional	List of recommendations to filter by. Example: "Not recommended".
ostypes	optional	List of OS types to filter by. Example: "linux".
pathexclusiontypes	optional	List of excluded paths in an exclusion to filter by. Applies only to EDR exclusions of type path. Example: "file".
pathvalue__contains	optional	Free-text filter by nested path value.
podname__contains	optional	Free-text filter by pod name.
scopepath__contains	optional	Free-text filter by scope path.
sha256image__contains	optional	Free-text filter by SHA-256 of an image.
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
source	optional	List sources to filter by. Example: "user".
tagids	optional	List of tag IDs to filter by. Example:

		"225494730938493804,225494730938493915".
tags	optional	Filter exclusions by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key. Example: '{"key1": ["value1_1", "value1_2"], "key2__nin": ["value2"]}'.
tagsbygroup	optional	Group exclusions by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. . Example: '{"key1": ["value1_1", "value1_2"], "key2": ["value2"]}'.
tenant	optional	Indicates a tenant scope request
threattype	optional	List of threat types to filter by. Example: "EDR".
updatedat__between	optional	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedat__gt	optional	Updated after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Updated after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Updated before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Updated before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
user__contains	optional	Free-text filter by username.
userids	optional	List of user IDs to filter by. Example: "225494730938493804,225494730938493915".
value__contains	optional	Free-text filter by value.
warnings	optional	List of warnings to filter by. Example: "Not allowed".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Exclusions - response - pagination table
data	Response data	false	see Get Exclusions - response - data table
errors	Errors	false	array

Get Exclusions - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Exclusions - response - data

Delete Exclusions

DELETE /web/api/v2.1/unified-exclusions

Response Messages

200 - Exclusions successfully deleted.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed to perform this operation.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Exclusions - response - data table
errors	Errors	false	array

Delete Exclusions - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Delete Exclusions - body - data table

Delete Exclusions - body - data

Name	Description	Required	Value
exclusions	Exclusions	false	see Delete Exclusions - body - exclusions table

Delete Exclusions - body - exclusions

Name	Description	Required	Value
id	Id	true	string
type	Type	true	enum

Create Unified Exclusion

POST /web/api/v2.1/unified-exclusions

Create Exclusions to make your Agents suppress alerts and mitigation for items that you consider to be benign or which you require for interoperability. **IMPORTANT!** Every Exclusion is a possible security hole. Do not create Exclusions unless you are sure this hash, path, certificate signer, file type, or browser is always benign. Of course, if you can make the Exclusion by its hash or path, that is much more secure than excluding all detections of a specific signer, file type, or browser. We do not recommend the last types for Exclusions on production endpoints. These Exclusions might be helpful in a lab or pentester group. When you create an Exclusion, make sure you set the filter to the smallest possible scope. For example, if you can exclude security for this item on a group, do not enter values for sitelds or accountlds. We recommend that you read "Not Recommended Exclusions and Best Practices for Exclusions. See the Help from the Console for more details.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Create Unified Exclusion - response - pagination table

data	Response data	false	see Create Unified Exclusion - response - data table
errors	Errors	false	array

Create Unified Exclusion - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Create Unified Exclusion - response - data

Update Exclusions

PUT /web/api/v2.1/unified-exclusions

Change the properties of an Exclusion through the data fields. To get the original data, run "exclusions" with a filter to give the item you want.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Exclusion not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Exclusions - response - data table
errors	Errors	false	array

Update Exclusions - response - data

Create Bulk Unified Exclusion

POST /web/api/v2.1/unified-exclusions/bulk

Create Bulk Exclusions to make your Agents suppress alerts and mitigation for items that you consider to be benign or which you require for interoperability. **IMPORTANT!** Every Exclusion is a possible security hole. Do not create Exclusions unless you are sure this hash, path, certificate signer, file type, or browser is always benign.

Of course, if you can make the Exclusion by its hash or path, that is much more secure than excluding all detections of a specific signer, file type, or browser. We do not recommend the last types for Exclusions on production endpoints. These Exclusions might be helpful in a lab or pentester group. When you create an Exclusion, make sure you set the filter to the smallest possible scope. For example, if you can exclude security for this item on a group, do not enter values for sitelds or accountIds.

We recommend that you read "Not Recommended Exclusions and Best Practices for Exclusions."

See the Help from the Console for more details.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Create Bulk Unified Exclusion - response - pagination table
data	Response data	false	see Create Bulk Unified Exclusion - response - data table
errors	Errors	false	array

Create Bulk Unified Exclusion - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Create Bulk Unified Exclusion - response - data

Body Schema

Name	Description	Required	Value
data	Data	true	
filter	Filter	true	see Create Bulk Unified Exclusion - body - filter table

Create Bulk Unified Exclusion - body - filter

Name	Description	Required	Value
scopeLevel	The scope level of the exclusion.	true	enum
scopeLevelId	The identifier of the scope level.	false	integer

Import Unified Exclusions

POST /web/api/v2.1/unified-exclusions/import

Import exclusions to a specified scope in the Console. Use an exclusion JSON file exported from a different scope. Exported exclusion CSV files are also supported.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed to perform this operation.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Import Unified Exclusions - response - data table
errors	Errors	false	array

Import Unified Exclusions - response - data

Name	Description	Required	Value
reportId	The ID of the Validation Report generated for the import. It can help you fix entries that did not import successfully.	false	string
succeeded	The number of entries that imported successfully	false	integer
total	The number of rows in the file	false	integer

Body Schema

Name	Description	Required	Value
formData		false	see Import Unified Exclusions - body - formData table

Import Unified Exclusions - body - formData

Name	Description	Required	Value
file	The input JSON or CSV file	true	file
filter	Filter	false	object

Export Unified Exclusions

GET /web/api/v2.1/unified-exclusions/export

Export the currently filtered exclusions to a JSON file. You can use the export file to import the exclusions to a different scope.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
applicationname__contains	optional	Free-text filter by application name.
childprocess	optional	Indicates if the exclusion applies to child processes or not. You can filter by this.
cmdlinevalue__contains	optional	Free-text filter by nested cmdline value.
conditions	optional	List of conditions to filter by. Example: "white_hash".
containername__contains	optional	Free-text filter by container name.
countsfor	optional	comma-separated list of fields to be shown. Example: "threatType,interactionLevel".
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdat__gt	optional	Created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".

createdat__lt	optional	Created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
creator__contains	optional	Free-text filter by creator name.
description__contains	optional	Free-text filter by description.
engines	optional	List of engines to filter by. Example: "suppress".
exclusionidentifier	optional	Filter by the stable exclusion identifier.
exclusionname__contains	optional	Free-text filter by exclusion name.
fullimagename__contains	optional	Free-text filter by full image URI.
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
hashtags	optional	Include only Exclusions that have any tags assigned if True, or none if False
hashtagsbygroup	optional	Include Exclusions that have any tags assigned if True, or none if False
hits30d__between	optional	Inclusive range for number of hits within the past 30 days. Example: "6-9".
hits90d__between	optional	Inclusive range for number of hits within the past 90 days. Example: "13-37".
hitsalltime__between	optional	Inclusive range for all-time number of hits. Example: "678-9998212".
ids	optional	List of IDs to filter by. Example: "225494730938493804,225494730938493915".
idsnin	optional	List of IDs to exclude from filter. Example: "225494730938493804,225494730938493915".
imported	optional	Indicates if the exclusion was imported by a bulk operation or not. You can filter by this.
inappinventory	optional	Indicates if the exclusion is related to an application found in the scope's Application Inventory or not. You can filter by this.
includechildren	optional	Return filters from children scope levels (Default: false).
includeparents	optional	Return filters from parent scope levels (Default: false).
interactionlevel	optional	List of interaction levels to filter by. Example: "disable_all_monitors".

labelskey__contains	optional	Free-text filter by label key.
labelsvalue__contains	optional	Free-text filter by label value.
lasthit__between	optional	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1775676749738-1775676848156".
lasthit__lt	optional	Last hit before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lasthit__lte	optional	Last hit before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
menutype	optional	Page-scope (left-menu) exclusion grouping, e.g. 'endpoint' (which covers suppression + agent_interoperability). Combined with modeType (the in-table filter) by intersection. Sending modeType alone keeps the previous behaviour. Example: "all".
modetype	optional	List of Exclusion Type to filter by: suppression, agent_interoperability, or binary_vault . Example: "all".
namespace__contains	optional	Free-text filter by namespace.
notrecommended	optional	List of recommendations to filter by. Example: "Not recommended".
ostypes	optional	List of OS types to filter by. Example: "linux".
pathexclusiontypes	optional	List of excluded paths in an exclusion to filter by. Applies only to EDR exclusions of type path. Example: "file".
pathvalue__contains	optional	Free-text filter by nested path value.
podname__contains	optional	Free-text filter by pod name.
scopepath__contains	optional	Free-text filter by scope path.
sha256image__contains	optional	Free-text filter by SHA-256 of an image.
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
source	optional	List sources to filter by. Example: "user".
tagids	optional	List of tag IDs to filter by. Example: "225494730938493804,225494730938493915".
tags	optional	Filter exclusions by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key. Example: "{"key1": ["value1_1",

		"value1_2"], "key2__nin": ["value2"]}]".
tagsbygroup	optional	Group exclusions by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. . Example: {"key1": ["value1_1", "value1_2"], "key2": ["value2"]}]".
tenant	optional	Indicates a tenant scope request
threatype	optional	List of threat types to filter by. Example: "EDR".
updatedat__between	optional	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedat__gt	optional	Updated after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Updated after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Updated before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Updated before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
user__contains	optional	Free-text filter by username.
userids	optional	List of user IDs to filter by. Example: "225494730938493804,225494730938493915".
value__contains	optional	Free-text filter by value.
warnings	optional	List of warnings to filter by. Example: "Not allowed".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed to perform this operation.

Get Exclusion Actions

GET /web/api/v2.1/unified-exclusions/available-actions

Get a list of available actions for exclusions that match the filter criteria.

Parameters

create	required	Create
accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
applicationname__contains	optional	Free-text filter by application name.
childprocess	optional	Indicates if the exclusion applies to child processes or not. You can filter by this.
cmdlinevalue__contains	optional	Free-text filter by nested cmdline value.
conditions	optional	List of conditions to filter by. Example: "white_hash".
containername__contains	optional	Free-text filter by container name.
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	comma-separated list of fields to be shown. Example: "threatType,interactionLevel".
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdat__gt	optional	Created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
creator__contains	optional	Free-text filter by creator name.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example:

		"YWdlbnRfaWQ6NTgwMjkzODE=".
description__contains	optional	Free-text filter by description.
engines	optional	List of engines to filter by. Example: "suppress".
exclusionidentifier	optional	Filter by the stable exclusion identifier.
exclusionname__contains	optional	Free-text filter by exclusion name.
fullimagename__contains	optional	Free-text filter by full image URI.
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
hashtags	optional	Include only Exclusions that have any tags assigned if True, or none if False
hashtagsbygroup	optional	Include Exclusions that have any tags assigned if True, or none if False
hits30d__between	optional	Inclusive range for number of hits within the past 30 days. Example: "6-9".
hits90d__between	optional	Inclusive range for number of hits within the past 90 days. Example: "13-37".
hitsalltime__between	optional	Inclusive range for all-time number of hits. Example: "678-9998212".
ids	optional	List of IDs to filter by. Example: "225494730938493804,225494730938493915".
idsnin	optional	List of IDs to exclude from filter. Example: "225494730938493804,225494730938493915".
imported	optional	Indicates if the exclusion was imported by a bulk operation or not. You can filter by this.
inappinventory	optional	Indicates if the exclusion is related to an application found in the scope's Application Inventory or not. You can filter by this.
includechildren	optional	Return filters from children scope levels (Default: false).
includeparents	optional	Return filters from parent scope levels (Default: false).
interactionlevel	optional	List of interaction levels to filter by. Example: "disable_all_monitors".
labelskey__contains	optional	Free-text filter by label key.
labelsvalue__contains	optional	Free-text filter by label value.
lasthit__between	optional	Date range for update time (format: <from_timestamp>-

		<to_timestamp>, inclusive). Example: "1775676749738-1775676848156".
lasthit__lt	optional	Last hit before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lasthit__lte	optional	Last hit before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
limit	optional	Limit number of returned items (1-1000). Example: "10".
menutype	optional	Page-scope (left-menu) exclusion grouping, e.g. 'endpoint' (which covers suppression + agent_interoperability). Combined with modeType (the in-table filter) by intersection. Sending modeType alone keeps the previous behaviour. Example: "all".
modetype	optional	List of Exclusion Type to filter by: suppression, agent_interoperability, or binary_vault . Example: "all".
namespace__contains	optional	Free-text filter by namespace.
notrecommended	optional	List of recommendations to filter by. Example: "Not recommended".
ostypes	optional	List of OS types to filter by. Example: "linux".
pathexclusiontypes	optional	List of excluded paths in an exclusion to filter by. Applies only to EDR exclusions of type path. Example: "file".
pathvalue__contains	optional	Free-text filter by nested path value.
podname__contains	optional	Free-text filter by pod name.
scopepath__contains	optional	Free-text filter by scope path.
selectall	optional	When true, calculate actions for all exclusions matching filters (not just selected IDs).
sha256image__contains	optional	Free-text filter by SHA-256 of an image.
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

source	optional	List sources to filter by. Example: "user".
tagids	optional	List of tag IDs to filter by. Example: "225494730938493804,225494730938493915".
tags	optional	Filter exclusions by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key. Example: '{"key1": ["value1_1", "value1_2"], "key2__nin": ["value2"]}'.
tagsbygroup	optional	Group exclusions by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. . Example: '{"key1": ["value1_1", "value1_2"], "key2": ["value2"]}'.
tenant	optional	Indicates a tenant scope request
threattype	optional	List of threat types to filter by. Example: "EDR".
updatedat__between	optional	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedat__gt	optional	Updated after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Updated after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Updated before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Updated before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
user__contains	optional	Free-text filter by username.
userids	optional	List of user IDs to filter by. Example: "225494730938493804,225494730938493915".
value__contains	optional	Free-text filter by value.
warnings	optional	List of warnings to filter by. Example: "Not allowed".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Exclusion Actions - response - pagination table
data	Response data	false	see Get Exclusion Actions - response - data table
errors	Errors	false	array

Get Exclusion Actions - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Exclusion Actions - response - data

Name	Description	Required	Value
actions	Actions	false	see Get Exclusion Actions - response - actions table
exclusions	Exclusions	false	see Get Exclusion Actions - response - exclusions table

Get Exclusion Actions - response - actions

Name	Description	Required	Value
isDisabled		true	boolean
name		true	string
order		true	integer
title		true	string
children		false	see Get Exclusion Actions - response - children table
disabledReason		false	string

Get Exclusion Actions - response - children

Name	Description	Required	Value
isDisabled		true	boolean

name		true	string
order		true	integer
title		true	string
disabledReason		false	string

Get Exclusion Actions - response - exclusions

Filters

Get Filters

GET /web/api/v2.1/filters

Get the list of saved filters. See Save Filter. The response includes the ID of the filter, which you can use in other commands.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
ids	optional	A list of Filter IDs. Example: "225494730938493804,225494730938493915".
includechildren	optional	Return filters from children scope levels (Default: false)
includeglobal	optional	[DEPRECATED] Return global filters even when specific sites are selected
includeparents	optional	Return filters from parent scope levels (Default: false)
limit	optional	Limit number of returned items (1-1000). Example: "10".
query	optional	Text query for filter's name. Example: "MyFilter".

siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Filters - response - pagination table
data	Response data	false	see Get Filters - response - data table
errors	Errors	false	array

Get Filters - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Filters - response - data

Name	Description	Required	Value
createdAt	Created at	true	string
id	Id	true	string
name	Name	true	string
scopeLevel	Filter scope	true	enum
updatedAt	Updated at	true	string
filterFields	A set of arguments composing the filter	false	see Get Filters - response - filterFields table
scopeld	Associated site/account	false	string
siteld	[DEPRECATED] Use scopeld instead	false	string

Get Filters - response - filterFields

Name	Description	Required	Value
activeProtection	Included agent active protections	false	string []
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports	false	string []

	multiple values)		
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []

cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceid__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Get Filters - response - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []

ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []

isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []

locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []

query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
totalMemory__between	Total memory range (GB, inclusive)	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid__contains	Free-text filter by Agent UUID	false	string []

	(supports multiple values)		
--	----------------------------	--	--

Get Filters - response - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Save Filter

POST /web/api/v2.1/filters

Save a new filter to get a list of matching endpoints. When you save a filter, you can run actions on the Agents as a set of objects or create a dynamic group (automatically adds new Agents that match the filter and drops Agents if they change to not match).

For example, you can save a filter with `{"data":{"filterFields":{"infected":true}}}` to run kill and quarantine commands on all the Agents at once, or to create a group that holds currently infected endpoints. Best Practice: Set a scope for the new Saved Filter. Run "accounts", "sites", or "groups" to get the IDs for the scope.

BEST PRACTICE

Set a scope for the new Saved Filter. Run "accounts", "sites", or "groups" to get the IDs for the scope.

Response Messages

200 - Filter successfully saved. Returns created object.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed to perform this operation.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Save Filter - response - data table
errors	Errors	false	array

Save Filter - response - data

Name	Description	Required	Value
createdAt	Created at	true	string
id	Id	true	string
name	Name	true	string
scopeLevel	Filter scope	true	enum
updatedAt	Updated at	true	string
filterFields	A set of arguments composing the filter	false	see Save Filter - response - filterFields table
scopeld	Associated site/account	false	string
siteld	[DEPRECATED] Use scopeld instead	false	string

Save Filter - response - filterFields

Name	Description	Required	Value
activeProtection	Included agent active protections	false	string []
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory	false	string []

	username string (supports multiple values)		
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network	false	string []

	(supports multiple values)		
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Save Filter - response - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []

ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt	false	string []

	proxy. Accepts true, false, or none (for not reported).		
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []

networkInterfaceNet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []

rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
totalMemory__between	Total memory range (GB, inclusive)	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []

Save Filter - response - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer

tasksCount	Number of tasks the agent is currently protecting	false	integer
------------	---	-------	---------

Body Schema

Name	Description	Required	Value
data	Data	true	see Save Filter - body - data table
filter	Target scope for the new filter	false	see Save Filter - body - filter table

Save Filter - body - data

Name	Description	Required	Value
filterFields	A set of parameters to filter by	true	see Save Filter - body - filterFields table
name	New filter name	true	string
scopeLevel	[DEPRECATED] Use the "filter" object instead.	false	enum
siteId	[DEPRECATED] Use the "filter" object instead.	false	string

Save Filter - body - filterFields

Name	Description	Required	Value
activeProtection	Included agent active protections	false	string []
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []

agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags	false	string []

	(supports multiple values)		
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Save Filter - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []

isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network	false	boolean []

	Quarantine Control and its enabled for the agent's group		
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string

remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
totalMemory__between	Total memory range (GB, inclusive)	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []

Save Filter - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Save Filter - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Update Filter

PUT /web/api/v2.1/filters/{filter_id}

Update an existing filter

Response Messages

200 - Filter successfully updated. Returns updated object.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed to perform this operation.

404 - Filter not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Filter - response - data table
errors	Errors	false	array

Update Filter - response - data

Name	Description	Required	Value
createdAt	Created at	true	string
id	Id	true	string
name	Name	true	string
scopeLevel	Filter scope	true	enum
updatedAt	Updated at	true	string
filterFields	A set of arguments composing the filter	false	see Update Filter - response - filterFields table
scopeld	Associated site/account	false	string
siteld	[DEPRECATED] Use scopeld instead	false	string

Update Filter - response - filterFields

Name	Description	Required	Value
activeProtection	Included agent active protections	false	string []
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory	false	string []

	username string (supports multiple values)		
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network	false	string []

	(supports multiple values)		
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Update Filter - response - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []

ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt	false	string []

	proxy. Accepts true, false, or none (for not reported).		
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []

networkInterfaceNet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []

rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
totalMemory__between	Total memory range (GB, inclusive)	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []

Update Filter - response - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer

tasksCount	Number of tasks the agent is currently protecting	false	integer
------------	---	-------	---------

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Filter - body - data table

Update Filter - body - data

Name	Description	Required	Value
filterFields	A set of parameters to filter by (If supplied, replaces existing parameter set)	false	see Update Filter - body - filterFields table
name	Updated filter name	false	string

Update Filter - body - filterFields

Name	Description	Required	Value
activeProtection	Included agent active protections	false	string []
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []

agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name	false	string []

	(supports multiple values)		
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Update Filter - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []

externallp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []

k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceLocalnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []

networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote	false	string []

	profiling states		
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
totalMemory__between	Total memory range (GB, inclusive)	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []

Update Filter - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
podsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Delete Filter

DELETE /web/api/v2.1/filters/{filter_id}

Delete a saved filter.

Response Messages

200 - Filter successfully deleted.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed to perform this operation.

404 - Filter not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Filter - response - data table
errors	Errors	false	array

Delete Filter - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

[DEPRECATED] Get Deep Visibility Filters

GET /web/api/v2.1/filters/dv

Get saved Deep Visibility queries with full data. See Save Deep Visibility Filters.The response includes the ID of the filter, which you can use in other commands.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	A list of Filter IDs. Example: "225494730938493804,225494730938493915".
includechildren	optional	Return filters from children scope levels (Default: false)
includeglobal	optional	[DEPRECATED] Return global filters even when specific sites are selected
includeparents	optional	Return filters from parent scope levels (Default: false)
limit	optional	Limit number of returned items (1-1000). Example: "10".
query	optional	Text query for filter's name. Example: "MyFilter".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".

skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

Response Messages

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

[DEPRECATED] Save Deep Visibility Filter

POST /web/api/v2.1/filters/dv

Save a Deep Visibility query with data as a filter, to get notifications of specific events sent to named recipients on a given frequency. The recipients must be Console users with permissions on the scope of the query. Notifications are sent through email: you must have an SMTP server configured in the SentinelOne solution (/settings/smtp see Set SMTP Settings).

Deep Visibility requires a Complete SKU.

Response Messages

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
data	Data	true	see [DEPRECATED] Save Deep Visibility Filter - body - data table
filter	Filter	true	see [DEPRECATED] Save Deep Visibility Filter - body - filter table

[DEPRECATED] Save Deep Visibility Filter - body - data

Name	Description	Required	Value
filterFields	A set of parameters to filter by	true	see [DEPRECATED] Save Deep Visibility Filter - body - filterFields table
name	New filter name	true	string
frequency	Frequency	false	integer
notifications	Notifications	false	boolean
recipients	List of recipients	false	string []

[DEPRECATED] Save Deep Visibility Filter - body - filterFields

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
migratedToSdl	Whether the saved search was migrated to SDL	false	boolean
query	The query to be saved	false	string
queryType	Query Search Type	false	string
siteIds	List of Site IDs to filter by	false	string []
timeRange	The timeframe in which events occurred	false	string

[DEPRECATED] Save Deep Visibility Filter - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
scope_level	Filter scope	false	enum
siteIds	List of Site IDs to filter by	false	string []

[DEPRECATED] Delete Deep Visibility Filter

DELETE /web/api/v2.1/filters/dv/{filter_id}

Delete a saved Deep Visibility query.

Response Messages

- 200 - Filter successfully deleted.
- 401 - Unauthorized access - please sign in and retry.
- 403 - User is not allowed to perform this operation.
- 404 - Filter not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see [DEPRECATED] Delete Deep Visibility Filter - response - data table
errors	Errors	false	array

[DEPRECATED] Delete Deep Visibility Filter - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

[DEPRECATED] Update Deep Visibility Filter

PUT /web/api/v2.1/filters/dv/{filter_id}

Change a saved Deep Visibility filter. To get the ID and fields to change, run Get Deep Visibility Filters.

Response Messages

200 - Filter successfully updated. Returns updated object.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed to perform this operation.

404 - Filter not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see [DEPRECATED] Update Deep Visibility Filter - response - data table
errors	Errors	false	array

[DEPRECATED] Update Deep Visibility Filter - response - data

Name	Description	Required	Value
createdAt	Created at	true	string
id	Id	true	string
name	Name	true	string
scopeLevel	Filter scope	true	enum
updatedAt	Updated at	true	string
filterFields	A set of parameters to filter by	false	see [DEPRECATED] Update Deep Visibility Filter - response - filterFields table
frequency	Frequency	false	integer
notifications	Notifications	false	boolean
recipients	List of recipients	false	string []
scopeld	Associated site/account	false	string
scopeLevelName	Filter scope name	false	string
siteld	[DEPRECATED] Use scopeld instead	false	string

[DEPRECATED] Update Deep Visibility Filter - response - filterFields

Name	Description	Required	Value
migratedToSdl	Whether this saved query was migrated to SDL	false	boolean
query	Deep visibility query	false	string
queryType	Either powerquery or events/ processes/None	false	string
timeRange	Deep visibility query time range	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see [DEPRECATED] Update Deep Visibility Filter - body - data table
filter	Filter	true	see [DEPRECATED] Update Deep Visibility Filter - body - filter table

[DEPRECATED] Update Deep Visibility Filter - body - data

Name	Description	Required	Value
filterFields	A set of parameters to filter by	true	see [DEPRECATED] Update Deep Visibility Filter - body - filterFields table
name	New filter name	true	string
frequency	Frequency	false	integer
notifications	Notifications	false	boolean
recipients	List of recipients	false	string []

[DEPRECATED] Update Deep Visibility Filter - body - filterFields

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
migratedToSdl	Whether the saved search was migrated to SDL	false	boolean
query	The query to be saved	false	string
queryType	Query Search Type	false	string
siteIds	List of Site IDs to filter by	false	string []
timeRange	The timeframe in which events occurred	false	string

[DEPRECATED] Update Deep Visibility Filter - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
scope_level	Filter scope	false	enum
siteIds	List of Site IDs to filter by	false	string []

Upload CSV file

POST /web/api/v2.1/filters/csv-filter

Upload CSV file

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Upload CSV file - response - data table
errors	Errors	false	array

Upload CSV file - response - data

Name	Description	Required	Value
activeEndpointFoundCount	Number of active endpoints found with these values	false	integer
endpointFoundCount	Number of endpoints found with these values (both active and decommissioned)	false	integer
filterId	ID of the filter	false	string
notFoundActiveEndpoints	Not found active endpoints	false	string []
notFoundEndpoints	Not found endpoints	false	string []
rowCount	Number of rows in the CSV file	false	integer
uniqueInputValuesCount	Number of unique values in the file	false	integer

Body Schema

Name	Description	Required	Value
formData		false	see Upload CSV file - body - formData table

Upload CSV file - body - formData

Name	Description	Required	Value
agentFilterField	The property of the endpoint to filter by	true	string
excludeHeader	Set to True to exclude the column header	true	boolean
file	File	true	file

Get Filters

GET /web/api/v2.1/xdr/filters

Get the list of saved filters. See Save Filter. The response includes the ID of the filter, which you can use in other commands.

Parameters

accountids	optional	List of Account IDs to filter by
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
ids	optional	A list of Filter IDs
includechildren	optional	Return filters from children scope levels (Default: false)
includeparents	optional	Return filters from parent scope levels (Default: false)
limit	optional	Limit number of returned items (1-1000)
query	optional	Text query for filter's name
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.

sortorder	optional	Sort direction
-----------	----------	----------------

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Get Filters - response - pagination table

Get Filters - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Save Filter

POST /web/api/v2.1/xdr/filters

Save a new filter to get a list of matching endpoints. When you save a filter, you can run actions on the Agents as a set of objects or create a dynamic group (automatically adds new Agents that match the filter and drops Agents if they change to not match).

For example, you can save a filter with {"data":{"filterFields":{"infected":true}}} to run kill and quarantine commands on all the Agents at once, or to create a group that holds currently infected endpoints. Best Practice: Set a scope for the new Saved Filter. Run "accounts", "sites", or "groups" to get the IDs for the scope.

BEST PRACTICE

Set a scope for the new Saved Filter. Run "accounts", "sites", or "groups" to get the IDs for the scope.

Response Messages

200 - Filter successfully saved. Returns created object.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed to perform this operation.

Response Schema

Name	Description	Required	Value
data		false	see Save Filter - response - data table

errors	Errors	false	array
--------	--------	-------	-------

Save Filter - response - data

Name	Description	Required	Value
createdAt	Created at	true	string
id	Id	true	string
name	Name	true	string
scopeLevel	Filter scope	true	enum
updatedAt	Updated at	true	string
filterFields	A set of arguments composing the filter	false	object
mgmtId	Management id	false	string
scopeId	Associated site/account	false	string

Body Schema

Name	Description	Required	Value
data		false	see Save Filter - body - data table
filter	Filter scope	false	object

Save Filter - body - data

Name	Description	Required	Value
name	New filter name	true	string
filter	Filter scope	false	object
filterFields	A set of parameters to filter by	false	object
scopeId	Scope id	false	integer
scopeLevel	Filter scope	false	string
visibility	Visibility of the filter. Controls whether the filter should be accessible only by the author, or by anyone with the same scope ID/level.	false	enum

Filters with Metadata

GET /web/api/v2.1/xdr/private/filters/enriched

Get a list of saved endpoint filters, with enriched data. One of the fields in the response is the ID of each filter, which you will need in other commands.

Parameters

accountids	optional	List of Account IDs to filter by
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
ids	optional	A list of Filter IDs
includechildren	optional	Return filters from children scope levels (Default: false)
includeparents	optional	Return filters from parent scope levels (Default: false)
limit	optional	Limit number of returned items (1-1000)
query	optional	Text query for filter's name
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".

skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Filters with Metadata - response - pagination table

Filters with Metadata - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Update Filter

PUT /web/api/v2.1/xdr/filters/{filter_id}

Update an existing filter

Response Messages

200 - Filter successfully updated. Returns updated object.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed to perform this operation.

404 - Filter not found

Response Schema

Name	Description	Required	Value
data		false	see Update Filter - response - data table
errors	Errors	false	array

Update Filter - response - data

Name	Description	Required	Value
createdAt	Created at	true	string
id	Id	true	string
name	Name	true	string
scopeLevel	Filter scope	true	enum
updatedAt	Updated at	true	string
filterFields	A set of arguments composing the filter	false	object
mgmtId	Management id	false	string
scopeId	Associated site/account	false	string

Body Schema

Name	Description	Required	Value
data		false	see Update Filter - body - data table
filter	Filter scope	false	object

Update Filter - body - data

Name	Description	Required	Value
filterFields	A set of parameters to filter by (If supplied, replaces existing parameter set	false	object
name	Updated filter name	false	string

Delete Filter

DELETE /web/api/v2.1/xdr/filters/{filter_id}

Delete a saved filter.

Response Messages

200 - Filter successfully deleted.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed to perform this operation.

404 - Filter not found

Response Schema

Name	Description	Required	Value
data		false	see Delete Filter - response - data table
errors	Errors	false	array

Delete Filter - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Firewall Control

Get Firewall Rules

GET /web/api/v2.1/firewall-control

Get the Firewall Control rules for a scope specified by ID (run "accounts", "sites", "groups", or set "tenant" to "true") that match the filter. The response will be quite long because it includes all the rule properties, thus at least one of these filters is required: action, status, osType, name, or scope ID.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
actions	optional	Return firewall rules with the filtered action. Example: "Allow".
application__contains	optional	Free-text filter by application (supports multiple values)
applications	optional	Return firewall rules with the filtered firewall class.
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__between	optional	Return firewall rules created within this range (inclusive). Example: "1514978764288-1514978999999".
createdat__gt	optional	Return firewall rules created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Return firewall rules created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Return firewall rules created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Return firewall rules created before or at this timestamp. Example:

		"2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
directions	optional	Return firewall rules with the filtered directions. Example: "any".
disablepagination	optional	If true, all rules for requested scope will be returned
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of ids to filter by. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".
locationids	optional	Filter by associated locations. Example: "225494730938493804,225494730938493915".
name	optional	Return firewall rules with the filtered name.
name__contains	optional	Free-text filter by the Rule name (supports multiple values)
ostypes	optional	Return firewall rules with the filtered os_type. Example: "linux".
protocol__contains	optional	Free-text filter by protocol (supports multiple values)
protocols	optional	Return firewall rules with the filtered protocols.
query	optional	Free text search on name, tag, application, protocol
scopes	optional	Return only firewall rules in this scope. Example: "account".
service__contains	optional	Free-text filter by service (supports multiple values)
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
statuses	optional	Return firewall rules with the filtered status. Example: "Enabled".
tagids	optional	Filter by associated tags. Example: "225494730938493804,225494730938493915".

tagname__contains	optional	Free-text filter by the Tag name (supports multiple values)
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Firewall Rules - response - pagination table
data	Response data	false	see Get Firewall Rules - response - data table
errors	Errors	false	array

Get Firewall Rules - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Firewall Rules - response - data

Name	Description	Required	Value
action	Defines if agent shall Block or Allow use of firewalls which matches the rule parameters.	false	enum
application	Application for the rule	false	
createdAt	Date of rule creation	false	string
creator	Full name of the creating user	false	string
creatorId	Id of the creating user	false	string
description	Description	false	string
direction	Defines the Direction of the Firewall rule.	false	enum
editable	True if the rule can be modified at this scope level	false	boolean
id	Rule ID	false	string
localHost	Local host	false	
localPort	Local ports	false	
location	Location associated with the rule	false	see Get Firewall Rules - response - location table
name	The name of the firewall rule.	false	string
order	Position in the list of rules	false	integer
osType	[DEPRECATED] Please use os_types since multiple os types are	false	enum

	supported.This field will return the first os_type, not necessarily the only one.		
osTypes	Os types	false	string []
productId	Product identifier. Unique for a specific product module, per vendor ID, Interface.	false	string
protocol	The protocol.	false	string
remoteHost	[DEPRECATED] First remote host in the rule. Full list in remote_hosts	false	
remoteHosts	List of remote hosts	false	see Get Firewall Rules - response - remoteHosts table
remotePort	Remote ports	false	
ruleCategory	Network quarantine rule or standard firewall rule	false	enum
scope	Scope of the rule	false	enum
scopeId	The group or site id depending on the scope. null if it is global.	false	string
status	Defines if rule is Enabled or Disabled	false	enum
tag	[DEPRECATED] Free text to describe the rule. Please use description instead.	false	string
tagIds	Tag ids	false	string []
tagNames	Tag names	false	string []
tags	Tags	false	see Get Firewall Rules - response - tags table
updatedAt	Date of last update	false	string

Get Firewall Rules - response - location

Name	Description	Required	Value
type	Location type	true	enum
values	Location IDs (applicable for the "specific" location type only)	false	see Get Firewall Rules - response - values table

Get Firewall Rules - response - values

Name	Description	Required	Value
id	Location ID	true	string
name	Location name	false	string
scope	Location scope	false	enum

Get Firewall Rules - response - remoteHosts

Name	Description	Required	Value
type	Type of the host	false	enum
values	Value of the host	false	string []

Get Firewall Rules - response - tags

Name	Description	Required	Value
id		false	string
name		false	string

Create Firewall Rule

POST /web/api/v2.1/firewall-control

Create a Firewall Control rule for a scope specified by ID (run "accounts", "sites", "groups", or set "tenant" to "true") and specific OS, to allow or block network traffic to matching endpoints.

You can create one clean-up rule, with the Action of Allow or Block and with no other parameters defined explicitly. Make this the default rule at the end of your rule list. Traffic that does not match other rules first will match this rule. If you do not have a clean-up rule to match all traffic, the default Firewall Control behavior is to allow traffic that is not explicitly blocked.

Firewall Control requires Control SKU.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Firewall Rule - response - data table
errors	Errors	false	array

Create Firewall Rule - response - data

Name	Description	Required	Value
action	Defines if agent shall Block or Allow use of firewalls which matches the rule parameters.	false	enum
application	Application for the rule	false	
createdAt	Date of rule creation	false	string
creator	Full name of the creating user	false	string
creatorId	Id of the creating user	false	string
description	Description	false	string
direction	Defines the Direction of the Firewall rule.	false	enum
editable	True if the rule can be modified at this scope level	false	boolean
id	Rule ID	false	string
localHost	Local host	false	
localPort	Local ports	false	
location	Location associated with the rule	false	see Create Firewall Rule - response - location table
name	The name of the firewall rule.	false	string
order	Position in the list of rules	false	integer
osType	[DEPRECATED] Please use os_types since multiple os types are supported.This field will return the first os_type, not necessarily the only one.	false	enum
osTypes	Os types	false	string []
productId	Product identifier. Unique for a specific product module, per vendor ID, Interface.	false	string
protocol	The protocol.	false	string
remoteHost	[DEPRECATED] First remote host in the rule. Full list in remote_hosts	false	
remoteHosts	List of remote hosts	false	see Create Firewall Rule - response - remoteHosts table

remotePort	Remote ports	false	
ruleCategory	Network quarantine rule or standard firewall rule	false	enum
scope	Scope of the rule	false	enum
scopeId	The group or site id depending on the scope. null if it is global.	false	string
status	Defines if rule is Enabled or Disabled	false	enum
tag	[DEPRECATED] Free text to describe the rule. Please use description instead.	false	string
tagIds	Tag ids	false	string []
tagNames	Tag names	false	string []
tags	Tags	false	see Create Firewall Rule - response - tags table
updatedAt	Date of last update	false	string

Create Firewall Rule - response - location

Name	Description	Required	Value
type	Location type	true	enum
values	Location IDs (applicable for the "specific" location type only)	false	see Create Firewall Rule - response - values table

Create Firewall Rule - response - values

Name	Description	Required	Value
id	Location ID	true	string
name	Location name	false	string
scope	Location scope	false	enum

Create Firewall Rule - response - remoteHosts

Name	Description	Required	Value
------	-------------	----------	-------

type	Type of the host	false	enum
values	Value of the host	false	string []

Create Firewall Rule - response - tags

Name	Description	Required	Value
id		false	string
name		false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Firewall Rule - body - data table
filter	Filter	true	see Create Firewall Rule - body - filter table

Create Firewall Rule - body - data

Name	Description	Required	Value
action	Defines if agent shall Block or Allow use of firewalls which matches the rule parameters.	true	enum
name	The name of the firewall rule.	true	string
status	Defines if rule is Enabled or Disabled	true	enum
application	Application for the rule	false	see Create Firewall Rule - body - application table
description	Description	false	string
direction	Defines the Direction of the Firewall rule.	false	enum
localHost	Local host structure with a type and a set of values	false	see Create Firewall Rule - body - localHost table
localPort	Local ports structure with a type and a set of values	false	see Create Firewall Rule - body - localPort table
location	Location structure with a type and a set of values	false	see Create Firewall Rule - body - location table
osType	[DEPRECATED] Please use os_types since multiple os types are supported.This field will return the first os_type, not necessarily the only one.	false	enum
osTypes	Os types	false	string []
protocol	The protocol	false	string
remoteHost	[DEPRECATED] Please use remote_hosts.Remote host structure with a type and a set of values.	false	see Create Firewall Rule - body - remoteHost table
remoteHosts	List of remote hosts, each structured with a type and a set of values	false	see Create Firewall Rule - body - remoteHosts table
remotePort	Remote ports structure with a type and a set of values	false	see Create Firewall Rule - body - remotePort table
tag	[DEPRECATED] Free text to describe the rule. Please use description instead.	false	string
tagIds	Tag ids	false	string []

Create Firewall Rule - body - application

Name	Description	Required	Value
type	Type of the application	false	enum
values	Value of the application	false	string []

Create Firewall Rule - body - localHost

Name	Description	Required	Value
type	Type of the host	false	enum
values	Value of the host	false	string []

Create Firewall Rule - body - localPort

Name	Description	Required	Value
type	Type of the ports	false	enum
values	A list of port numbers	false	integer []

Create Firewall Rule - body - location

Name	Description	Required	Value
type	Location type	true	enum
values	Location IDs (applicable for the "specific" location type only)	false	see Create Firewall Rule - body - values table

Create Firewall Rule - body - values

Name	Description	Required	Value
id	Location ID	true	string
name	Location name	false	string

scope	Location scope	false	enum
-------	----------------	-------	------

Create Firewall Rule - body - remoteHost

Name	Description	Required	Value
type	Type of the host	false	enum
values	Value of the host	false	string []

Create Firewall Rule - body - remoteHosts

Name	Description	Required	Value
type	Type of the host	false	enum
values	Value of the host	false	string []

Create Firewall Rule - body - remotePort

Name	Description	Required	Value
type	Type of the ports	false	enum
values	A list of port numbers	false	integer []

Create Firewall Rule - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Delete Rules

DELETE /web/api/v2.1/firewall-control

Delete Firewall Control rules that match the filter.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Rules - response - data table
errors	Errors	false	array

Delete Rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	false	see Delete Rules - body - filter table

Delete Rules - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
actions	Return firewall rules with the filtered action.	false	string []
application__contains	Free-text filter by application (supports multiple values)	false	string []
applications	Return firewall rules with the filtered firewall class.	false	string []
createdAt__between	Return firewall rules created within this range (inclusive)	false	string
createdAt__gt	Return firewall rules created after this timestamp.	false	string
createdAt__gte	Return firewall rules created after or at this timestamp.	false	string
createdAt__lt	Return firewall rules created before this timestamp.	false	string
createdAt__lte	Return firewall rules created before or at this timestamp.	false	string
directions	Return firewall rules with the filtered directions.	false	string []
groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
locationIds	Filter by associated locations	false	string []
name	Return firewall rules with the filtered name.	false	string
name__contains	Free-text filter by the Rule name (supports multiple values)	false	string []
osTypes	Return firewall rules with the filtered os_type.	false	string []
protocol__contains	Free-text filter by protocol (supports multiple values)	false	string []
protocols	Return firewall rules with the filtered protocols.	false	string []

query	Free text search on name, tag, application, protocol	false	string
scopes	Return only firewall rules in this scope	false	string []
service__contains	Free-text filter by service (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
statuses	Return firewall rules with the filtered status.	false	string []
tagIds	Filter by associated tags	false	string []
tagName__contains	Free-text filter by the Tag name (supports multiple values)	false	string []
tenant	Indicates a tenant scope request	false	boolean

Copy Rules

POST /web/api/v2.1/firewall-control/copy-rules

Copy a set of rules to other scopes.

In the filter of the body, enter the properties to define the source. In the data field of the body, define the targets by ID. To get a scope ID, run 'accounts', 'sites', or 'groups'.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Copy Rules - response - data table
errors	Errors	false	array

Copy Rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	false	see Copy Rules - body - data table
filter	Filter	false	see Copy Rules - body - filter table

Copy Rules - body - data

Name	Description	Required	Value
accountId	Target account	false	string
accountIds	List of Account IDs to filter by	false	string []
groupId	Target group	false	string
groupIds	[DEPRECATED] Target group(s)	false	string []
siteId	Target site	false	string
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Copy Rules - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
actions	Return firewall rules with the filtered action.	false	string []
application__contains	Free-text filter by application (supports multiple values)	false	string []
applications	Return firewall rules with the filtered firewall class.	false	string []
createdAt__between	Return firewall rules created within this range (inclusive)	false	string
createdAt__gt	Return firewall rules created after this timestamp.	false	string
createdAt__gte	Return firewall rules created after or at this timestamp.	false	string
createdAt__lt	Return firewall rules created before this timestamp.	false	string
createdAt__lte	Return firewall rules created before or at this timestamp.	false	string
directions	Return firewall rules with the filtered directions.	false	string []

groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
locationIds	Filter by associated locations	false	string []
name	Return firewall rules with the filtered name.	false	string
name__contains	Free-text filter by the Rule name (supports multiple values)	false	string []
osTypes	Return firewall rules with the filtered os_type.	false	string []
protocol__contains	Free-text filter by protocol (supports multiple values)	false	string []
protocols	Return firewall rules with the filtered protocols.	false	string []
query	Free text search on name, tag, application, protocol	false	string
scopes	Return only firewall rules in this scope	false	string []
service__contains	Free-text filter by service (supports multiple values)	false	string []
siteIds	List of Site IDs to filter by	false	string []
statuses	Return firewall rules with the filtered status.	false	string []
tagIds	Filter by associated tags	false	string []
tagName__contains	Free-text filter by the Tag name (supports multiple values)	false	string []
tenant	Indicates a tenant scope request	false	boolean

Move Rules

POST /web/api/v2.1/firewall-control/move-rules

Remove Firewall Rules, defined with the ID of the rules (run 'firewall-control'), from scopes specified by ID (run 'accounts', 'sites', or 'groups') and add the rules to the scope IDs in the data field.

Firewall Control requires Control SKU.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Move Rules - response - data table
errors	Errors	false	array

Move Rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	false	see Move Rules - body - data table
filter	Filter	false	see Move Rules - body - filter table

Move Rules - body - data

Name	Description	Required	Value
accountId	Target account	false	string
accountIds	List of Account IDs to filter by	false	string []
groupId	Target group	false	string
groupIds	[DEPRECATED] Target group(s)	false	string []
siteId	Target site	false	string
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Move Rules - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
actions	Return firewall rules with the filtered action.	false	string []
application__contains	Free-text filter by application (supports multiple values)	false	string []
applications	Return firewall rules with the filtered firewall class.	false	string []
createdAt__between	Return firewall rules created within this range (inclusive)	false	string
createdAt__gt	Return firewall rules created after this timestamp.	false	string
createdAt__gte	Return firewall rules created after or at this timestamp.	false	string
createdAt__lt	Return firewall rules created before this timestamp.	false	string
createdAt__lte	Return firewall rules created before or at this timestamp.	false	string
directions	Return firewall rules with the filtered directions.	false	string []

groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
locationIds	Filter by associated locations	false	string []
name	Return firewall rules with the filtered name.	false	string
name__contains	Free-text filter by the Rule name (supports multiple values)	false	string []
osTypes	Return firewall rules with the filtered os_type.	false	string []
protocol__contains	Free-text filter by protocol (supports multiple values)	false	string []
protocols	Return firewall rules with the filtered protocols.	false	string []
query	Free text search on name, tag, application, protocol	false	string
scopes	Return only firewall rules in this scope	false	string []
service__contains	Free-text filter by service (supports multiple values)	false	string []
siteIds	List of Site IDs to filter by	false	string []
statuses	Return firewall rules with the filtered status.	false	string []
tagIds	Filter by associated tags	false	string []
tagName__contains	Free-text filter by the Tag name (supports multiple values)	false	string []
tenant	Indicates a tenant scope request	false	boolean

Set Location

POST /web/api/v2.1/firewall-control/set-location

Set location attributes for a Location Aware Firewall Control rule. These rules are applied by Agents only if the network parameters of the endpoint match the properties of the location definition. To get a Location ID, run "locations".
Firewall Control requires Control SKU.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set Location - response - data table
errors	Errors	false	array

Set Location - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Set Location - body - data table
filter	Filter	false	see Set Location - body - filter table

Set Location - body - data

Name	Description	Required	Value
type	Location type	true	enum
values	Location IDs (applicable for the "specific" location type only)	false	see Set Location - body - values table

Set Location - body - values

Name	Description	Required	Value
id	Location ID	true	string
name	Location name	false	string
scope	Location scope	false	enum

Set Location - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
actions	Return firewall rules with the filtered action.	false	string []
application__contains	Free-text filter by application (supports multiple values)	false	string []
applications	Return firewall rules with the filtered firewall class.	false	string []
createdAt__between	Return firewall rules created within this range (inclusive)	false	string
createdAt__gt	Return firewall rules created after this timestamp.	false	string
createdAt__gte	Return firewall rules created after or at this timestamp.	false	string
createdAt__lt	Return firewall rules created before this timestamp.	false	string

createdAt__lte	Return firewall rules created before or at this timestamp.	false	string
directions	Return firewall rules with the filtered directions.	false	string []
groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
locationIds	Filter by associated locations	false	string []
name	Return firewall rules with the filtered name.	false	string
name__contains	Free-text filter by the Rule name (supports multiple values)	false	string []
osTypes	Return firewall rules with the filtered os_type.	false	string []
protocol__contains	Free-text filter by protocol (supports multiple values)	false	string []
protocols	Return firewall rules with the filtered protocols.	false	string []
query	Free text search on name, tag, application, protocol	false	string
scopes	Return only firewall rules in this scope	false	string []
service__contains	Free-text filter by service (supports multiple values)	false	string []
siteIds	List of Site IDs to filter by	false	string []
statuses	Return firewall rules with the filtered status.	false	string []
tagIds	Filter by associated tags	false	string []
tagName__contains	Free-text filter by the Tag name (supports multiple values)	false	string []
tenant	Indicates a tenant scope request	false	boolean

Reorder Rules

PUT /web/api/v2.1/firewall-control/reorder

Change the order of rules for a scope specified by ID (run "accounts", "sites", or "groups").

The Agent looks at the rules based on their order in the Firewall Control policy, from the top to the bottom. First it goes through the Group rules, then the Site rules, then the Account rules, then the Global rules. When the Agent finds a rule that matches the parameters of the traffic, that rule is applied. The Agent does not continue to the lower rules in the list. Thus, the scope and the order of the rules is important.

Firewall Control requires Control SKU.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Reorder Rules - response - data table
errors	Errors	false	array

Reorder Rules - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Reorder Rules - body - filter table
data	Data	false	see Reorder Rules - body - data table

Reorder Rules - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
osTypes	[DEPRECATED] Rules OS type (was relevant for when each OS type had its own rule order)	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Reorder Rules - body - data

Name	Description	Required	Value
id	Rule ID	true	string
order	Desired position in the list of rules	true	integer

Get Configuration

GET /web/api/v2.1/firewall-control/configuration

Get the Firewall Control configuration for a given scope.

To filter the results for a scope:

* Global - Make sure "tenant" is "true" and no other scope ID is given.

* Account - Make sure "tenant" is "false" and at least one Account ID is given.

* Site - Make sure "tenant" is "false" and at least one Site ID is given.

The response shows if Firewall Control is enabled for the scope, if Location Awareness is enabled, the higher scope from which this scope inherited the configuration, and whether a lower scope inherits this configuration.

Firewall Control requires Control SKU.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
------------	----------	---

groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Configuration - response - data table
errors	Errors	false	array

Get Configuration - response - data

Name	Description	Required	Value
enabled	Firewall control enabled for the scope	false	boolean
inheritAllFirewallRules	Inherit all the rules and tags from the parent scope. Expands on 'inherits' value.	false	boolean
inheritedFrom	If null it means it is own policy else it tells the ancestor for the policy. For groups options are null/Site/Global, for site options are null/Global.	false	string
inherits	True if rules are decoupled from parent rules	false	boolean
inheritSettings	Inherit firewall settings from parent scope	false	boolean
locationAware	Firewall control supports location awareness for the scope	false	boolean
reportBlocked	Agent should report blocked events	false	boolean
selectedTags	Selected tags	false	string []

Update Configuration

PUT /web/api/v2.1/firewall-control/configuration

Change the Firewall Control configuration for a given scope.

To get the ID of a scope, run "accounts", "sites", or "groups". To change the Global configuration, leave the filters empty and set "tenant" to "true". In the Body, you can set if Firewall Control is enabled for the scope, if Location Awareness is enabled, the higher scope from which this scope inherits the configuration ("Global" or a scope ID), whether the lower scopes inherit this configuration, and whether blocked actions are reported.

Firewall Control requires Control SKU.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Configuration - response - data table
errors	Errors	false	array

Update Configuration - response - data

Name	Description	Required	Value
enabled	Firewall control enabled for the scope	false	boolean
inheritAllFirewallRules	Inherit all the rules and tags from the parent scope. Expands on 'inherits' value.	false	boolean
inheritedFrom	If null it means it is own policy else it tells the ancestor for the policy.For groups options are null/Site/Global, for site options are null/Global.	false	string
inherits	True if rules are decoupled from parent rules	false	boolean
inheritSettings	Inherit firewall settings from parent scope	false	boolean
locationAware	Firewall control supports location awareness for the scope	false	boolean
reportBlocked	Agent should report blocked events	false	boolean
selectedTags	Selected tags	false	string []

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Configuration - body - data table
filter	Filter	true	see Update Configuration - body - filter table

Update Configuration - body - data

Name	Description	Required	Value
enabled	Firewall control enabled for the scope	false	boolean
inheritAllFirewallRules	Inherit all the rules and tags from the parent scope. Expands on 'inherits' value.	false	boolean
inheritedFrom	If null it means it is own policy else it tells the ancestor for the policy. For groups options are null/Site/Global, for site options are null/Global.	false	string
inherits	True if rules are decoupled from parent rules	false	boolean
inheritSettings	Inherit firewall settings from parent scope	false	boolean
locationAware	Firewall control supports location awareness for the scope	false	boolean
reportBlocked	Agent should report blocked events	false	boolean
selectedTags	Selected tags	false	string []

Update Configuration - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Export Rules

GET /web/api/v2.1/firewall-control/export

Export Firewall Control rules that match the filter to a JSON file from a scope specified by ID (run "accounts", "sites", "groups", or leave the scope empty and set "tenant" to "true") and import them to another scope (with the "import" command).
Firewall Control requires Control SKU.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
actions	optional	Return firewall rules with the filtered action. Example: "Allow".
application__contains	optional	Free-text filter by application (supports multiple values)
applications	optional	Return firewall rules with the filtered firewall class.
createdat__between	optional	Return firewall rules created within this range (inclusive). Example: "1514978764288-1514978999999".
createdat__gt	optional	Return firewall rules created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Return firewall rules created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Return firewall rules created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Return firewall rules created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
directions	optional	Return firewall rules with the filtered directions. Example: "any".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of ids to filter by. Example: "225494730938493804,225494730938493915".
locationids	optional	Filter by associated locations. Example: "225494730938493804,225494730938493915".
name	optional	Return firewall rules with the filtered name.
name__contains	optional	Free-text filter by the Rule name (supports multiple values)
ostypes	optional	Return firewall rules with the filtered os_type. Example: "linux".
protocol__contains	optional	Free-text filter by protocol (supports multiple values)
protocols	optional	Return firewall rules with the filtered protocols.
query	optional	Free text search on name, tag, application, protocol
scopes	optional	Return only firewall rules in this scope. Example: "account".
service__contains	optional	Free-text filter by service (supports multiple values)
siteids	optional	List of Site IDs to filter by. Example:

		"225494730938493804,225494730938493915".
statuses	optional	Return firewall rules with the filtered status. Example: "Enabled".
tagids	optional	Filter by associated tags. Example: "225494730938493804,225494730938493915".
tagname__contains	optional	Free-text filter by the Tag name (supports multiple values)
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Import Rules

POST /web/api/v2.1/firewall-control/import

Import Firewall Control rules from an exported JSON file to scopes specified by ID (run "accounts", "sites", "groups", or leave the scope empty and set "tenant" to "true"). Firewall Control requires Control SKU, in the target and in the source.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Import Rules - response - data table
errors	Errors	false	array

Import Rules - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
formData		false	see Import Rules - body - formData table

Import Rules - body - formData

Name	Description	Required	Value
file	File	true	file
accountIds	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".	false	string []
groupIds	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".	false	string []
siteIds	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".	false	string []
tenant	Indicates a tenant scope request	false	boolean

Enable/Disable Rules

PUT /web/api/v2.1/firewall-control/enable

Change the status of a set of Firewall Control rules that match the filter to "Enabled" or "Disabled". In one request, you can set one status or the other.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Enable/Disable Rules - response - data table
errors	Errors	false	array

Enable/Disable Rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Enable/Disable Rules - body - data table
filter	Filter	true	see Enable/Disable Rules - body - filter table

Enable/Disable Rules - body - data

Name	Description	Required	Value
status	should the rules be enabled/disabled	true	enum

Enable/Disable Rules - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
actions	Return firewall rules with the filtered action.	false	string []
application__contains	Free-text filter by application (supports multiple values)	false	string []
applications	Return firewall rules with the filtered firewall class.	false	string []
createdAt__between	Return firewall rules created within this range (inclusive)	false	string
createdAt__gt	Return firewall rules created after this timestamp.	false	string
createdAt__gte	Return firewall rules created after or at this timestamp.	false	string
createdAt__lt	Return firewall rules created before this timestamp.	false	string
createdAt__lte	Return firewall rules created before or at this timestamp.	false	string
directions	Return firewall rules with the filtered directions.	false	string []
groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
locationIds	Filter by associated locations	false	string []
name	Return firewall rules with the filtered name.	false	string
name__contains	Free-text filter by the Rule name	false	string []

	(supports multiple values)		
osTypes	Return firewall rules with the filtered os_type.	false	string []
protocol__contains	Free-text filter by protocol (supports multiple values)	false	string []
protocols	Return firewall rules with the filtered protocols.	false	string []
query	Free text search on name, tag, application, protocol	false	string
scopes	Return only firewall rules in this scope	false	string []
service__contains	Free-text filter by service (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
statuses	Return firewall rules with the filtered status.	false	string []
tagIds	Filter by associated tags	false	string []
tagName__contains	Free-text filter by the Tag name (supports multiple values)	false	string []
tenant	Indicates a tenant scope request	false	boolean

Get Protocols

GET /web/api/v2.1/firewall-control/protocols

Get a list of protocols that can be used in Firewall Control rules.

Parameters

countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
disablepagination	optional	If true, all rules for requested scope will be returned
limit	optional	Limit number of returned items (1-1000). Example: "10".
query	optional	Full text search on protocols
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000

		items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Protocols - response - pagination table
data	Response data	false	see Get Protocols - response - data table
errors	Errors	false	array

Get Protocols - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Protocols - response - data

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
name	Description of the protocol	false	string
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean
value	Short code identifying the protocol	false	string

Add Rule Tags

POST /web/api/v2.1/firewall-control/add-tags

Create a Firewall Rule tag.

Create tags to represent Firewall policies - a set of rules in a specific order. After you create the tag, add rules to it.

Notes:

* Tags apply to a scope and cannot be linked to rules from different scopes.

* Tags must be 2 to 256 characters.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Add Rule Tags - response - data table
errors	Errors	false	array

Add Rule Tags - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Add Rule Tags - body - data table
filter	Filter	true	see Add Rule Tags - body - filter table

Add Rule Tags - body - data

Name	Description	Required	Value
tagIds	Tag ids	false	string []

Add Rule Tags - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
actions	Return firewall rules with the filtered action.	false	string []
application__contains	Free-text filter by application (supports multiple values)	false	string []
applications	Return firewall rules with the filtered firewall class.	false	string []
createdAt__between	Return firewall rules created within this range (inclusive)	false	string
createdAt__gt	Return firewall rules created after this timestamp.	false	string
createdAt__gte	Return firewall rules created after or at this timestamp.	false	string
createdAt__lt	Return firewall rules created before this timestamp.	false	string
createdAt__lte	Return firewall rules created before or at this timestamp.	false	string
directions	Return firewall rules with the filtered directions.	false	string []
groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
locationIds	Filter by associated locations	false	string []
name	Return firewall rules with the filtered name.	false	string
name__contains	Free-text filter by the Rule name	false	string []

	(supports multiple values)		
osTypes	Return firewall rules with the filtered os_type.	false	string []
protocol__contains	Free-text filter by protocol (supports multiple values)	false	string []
protocols	Return firewall rules with the filtered protocols.	false	string []
query	Free text search on name, tag, application, protocol	false	string
scopes	Return only firewall rules in this scope	false	string []
service__contains	Free-text filter by service (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
statuses	Return firewall rules with the filtered status.	false	string []
tagIds	Filter by associated tags	false	string []
tagName__contains	Free-text filter by the Tag name (supports multiple values)	false	string []
tenant	Indicates a tenant scope request	false	boolean

Remove Rule Tags

POST /web/api/v2.1/firewall-control/remove-tags

Remove firewall tags from rules matching the filter.

Tags represent Firewall policies - a set of rules in a specific order. When you remove a rule with a tag, all scopes that subscribe to the tag get the change.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Remove Rule Tags - response - data table
errors	Errors	false	array

Remove Rule Tags - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Remove Rule Tags - body - data table
filter	Filter	true	see Remove Rule Tags - body - filter table

Remove Rule Tags - body - data

Name	Description	Required	Value
tagIds	Tag ids	false	string []

Remove Rule Tags - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
actions	Return firewall rules with the filtered action.	false	string []
application__contains	Free-text filter by application (supports multiple values)	false	string []
applications	Return firewall rules with the filtered firewall class.	false	string []
createdAt__between	Return firewall rules created within this range (inclusive)	false	string
createdAt__gt	Return firewall rules created after this timestamp.	false	string
createdAt__gte	Return firewall rules created after or at this timestamp.	false	string
createdAt__lt	Return firewall rules created before this timestamp.	false	string
createdAt__lte	Return firewall rules created before or at this timestamp.	false	string
directions	Return firewall rules with the filtered directions.	false	string []
groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
locationIds	Filter by associated locations	false	string []
name	Return firewall rules with the filtered name.	false	string
name__contains	Free-text filter by the Rule name	false	string []

	(supports multiple values)		
osTypes	Return firewall rules with the filtered os_type.	false	string []
protocol__contains	Free-text filter by protocol (supports multiple values)	false	string []
protocols	Return firewall rules with the filtered protocols.	false	string []
query	Free text search on name, tag, application, protocol	false	string
scopes	Return only firewall rules in this scope	false	string []
service__contains	Free-text filter by service (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
statuses	Return firewall rules with the filtered status.	false	string []
tagIds	Filter by associated tags	false	string []
tagName__contains	Free-text filter by the Tag name (supports multiple values)	false	string []
tenant	Indicates a tenant scope request	false	boolean

Get Tag Firewall Rules

GET /web/api/v2.1/firewall-control/tag-rules/{tag_id}

Get all Firewall rules linked to tag, regardless of inheritance mode.

To get the ID of a tag, run the firewall-control API (see Get Firewall Rules) and see tagIDs in the response.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
actions	optional	Return firewall rules with the filtered action. Example: "Allow".
application__contains	optional	Free-text filter by application (supports multiple values)
applications	optional	Return firewall rules with the filtered firewall class.
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__between	optional	Return firewall rules created within this range (inclusive). Example:

		"1514978764288-15149789999999".
createdat__gt	optional	Return firewall rules created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Return firewall rules created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Return firewall rules created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Return firewall rules created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
directions	optional	Return firewall rules with the filtered directions. Example: "any".
disablepagination	optional	If true, all rules for requested scope will be returned
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of ids to filter by. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".
locationids	optional	Filter by associated locations. Example: "225494730938493804,225494730938493915".
name	optional	Return firewall rules with the filtered name.
name__contains	optional	Free-text filter by the Rule name (supports multiple values)
ostypes	optional	Return firewall rules with the filtered os_type. Example: "linux".
protocol__contains	optional	Free-text filter by protocol (supports multiple values)
protocols	optional	Return firewall rules with the filtered protocols.
query	optional	Free text search on name, tag, application, protocol
scopes	optional	Return only firewall rules in this scope. Example: "account".
service__contains	optional	Free-text filter by service (supports multiple values)
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".

skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
statuses	optional	Return firewall rules with the filtered status. Example: "Enabled".
tagids	optional	Filter by associated tags. Example: "225494730938493804,225494730938493915".
tagname__contains	optional	Free-text filter by the Tag name (supports multiple values)
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Tag Firewall Rules - response - pagination table
data	Response data	false	see Get Tag Firewall Rules - response - data table
errors	Errors	false	array

Get Tag Firewall Rules - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Tag Firewall Rules - response - data

Name	Description	Required	Value
action	Defines if agent shall Block or Allow use of firewalls which matches the rule parameters.	false	enum
application	Application for the rule	false	
createdAt	Date of rule creation	false	string
creator	Full name of the creating user	false	string
creatorId	Id of the creating user	false	string
description	Description	false	string
direction	Defines the Direction of the Firewall rule.	false	enum
editable	True if the rule can be modified at this scope level	false	boolean
id	Rule ID	false	string
localHost	Local host	false	
localPort	Local ports	false	
location	Location associated with the rule	false	see Get Tag Firewall Rules - response - location table
name	The name of the firewall rule.	false	string
order	Position in the list of rules	false	integer
osType	[DEPRECATED] Please use os_types since multiple os types are	false	enum

	supported.This field will return the first os_type, not necessarily the only one.		
osTypes	Os types	false	string []
productId	Product identifier. Unique for a specific product module, per vendor ID, Interface.	false	string
protocol	The protocol.	false	string
remoteHost	[DEPRECATED] First remote host in the rule. Full list in remote_hosts	false	
remoteHosts	List of remote hosts	false	see Get Tag Firewall Rules - response - remoteHosts table
remotePort	Remote ports	false	
ruleCategory	Network quarantine rule or standard firewall rule	false	enum
scope	Scope of the rule	false	enum
scopeId	The group or site id depending on the scope. null if it is global.	false	string
status	Defines if rule is Enabled or Disabled	false	enum
tag	[DEPRECATED] Free text to describe the rule. Please use description instead.	false	string
tagIds	Tag ids	false	string []
tagNames	Tag names	false	string []
tags	Tags	false	see Get Tag Firewall Rules - response - tags table
updatedAt	Date of last update	false	string

Get Tag Firewall Rules - response - location

Name	Description	Required	Value
type	Location type	true	enum
values	Location IDs (applicable for the "specific" location type only)	false	see Get Tag Firewall Rules - response - values table

Get Tag Firewall Rules - response - values

Name	Description	Required	Value
id	Location ID	true	string
name	Location name	false	string
scope	Location scope	false	enum

Get Tag Firewall Rules - response - remoteHosts

Name	Description	Required	Value
type	Type of the host	false	enum
values	Value of the host	false	string []

Get Tag Firewall Rules - response - tags

Name	Description	Required	Value
id		false	string
name		false	string

Update Firewall Rule

PUT /web/api/v2.1/firewall-control/{firewall_rule_category}

Change a Firewall Control rule.

This command requires the rule ID, which you can get from "firewall-control" (see Get Firewall Rules) or "firewall-control/unscooped" (see Get Unscoped Rules).

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Firewall rule not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Firewall Rule - response - data table
errors	Errors	false	array

Update Firewall Rule - response - data

Name	Description	Required	Value
action	Defines if agent shall Block or Allow use of firewalls which matches the rule parameters.	false	enum
application	Application for the rule	false	
createdAt	Date of rule creation	false	string
creator	Full name of the creating user	false	string
creatorId	Id of the creating user	false	string
description	Description	false	string
direction	Defines the Direction of the Firewall rule.	false	enum
editable	True if the rule can be modified at this scope level	false	boolean
id	Rule ID	false	string
localHost	Local host	false	
localPort	Local ports	false	
location	Location associated with the rule	false	see Update Firewall Rule - response - location table
name	The name of the firewall rule.	false	string
order	Position in the list of rules	false	integer
osType	[DEPRECATED] Please use os_types since multiple os types are supported.This field will return the first os_type, not necessarily the only one.	false	enum
osTypes	Os types	false	string []
productId	Product identifier. Unique for a specific product module, per vendor ID, Interface.	false	string
protocol	The protocol.	false	string
remoteHost	[DEPRECATED] First remote host in the rule. Full list in remote_hosts	false	
remoteHosts	List of remote hosts	false	see Update Firewall Rule - response - remoteHosts table

remotePort	Remote ports	false	
ruleCategory	Network quarantine rule or standard firewall rule	false	enum
scope	Scope of the rule	false	enum
scopeld	The group or site id depending on the scope. null if it is global.	false	string
status	Defines if rule is Enabled or Disabled	false	enum
tag	[DEPRECATED] Free text to describe the rule. Please use description instead.	false	string
tagIds	Tag ids	false	string []
tagNames	Tag names	false	string []
tags	Tags	false	see Update Firewall Rule - response - tags table
updatedAt	Date of last update	false	string

Update Firewall Rule - response - location

Name	Description	Required	Value
type	Location type	true	enum
values	Location IDs (applicable for the "specific" location type only)	false	see Update Firewall Rule - response - values table

Update Firewall Rule - response - values

Name	Description	Required	Value
id	Location ID	true	string
name	Location name	false	string
scope	Location scope	false	enum

Update Firewall Rule - response - remoteHosts

Name	Description	Required	Value
------	-------------	----------	-------

type	Type of the host	false	enum
values	Value of the host	false	string []

Update Firewall Rule - response - tags

Name	Description	Required	Value
id		false	string
name		false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Firewall Rule - body - data table

Update Firewall Rule - body - data

Name	Description	Required	Value
action	Defines if agent shall Block or Allow use of firewalls which matches the rule parameters.	false	enum
application	Application for the rule	false	see Update Firewall Rule - body - application table
description	Description	false	string
direction	Defines the Direction of the Firewall rule.	false	enum
localHost	Local host structure with a type and a set of values	false	see Update Firewall Rule - body - localHost table
localPort	Local ports structure with a type and a set of values	false	see Update Firewall Rule - body - localPort table
location	Location structure with a type and a set of values	false	see Update Firewall Rule - body - location table
name	The name of the firewall rule.	false	string
osType	[DEPRECATED] Please use os_types since multiple os types are supported.This field will return the first os_type, not necessarily the only one.	false	enum
osTypes	Os types	false	string []
protocol	The protocol	false	string
remoteHost	[DEPRECATED] Please use remote_hosts.Remote host structure with a type and a set of values.	false	see Update Firewall Rule - body - remoteHost table
remoteHosts	List of remote hosts, each structured with a type and a set of values	false	see Update Firewall Rule - body - remoteHosts table
remotePort	Remote ports structure with a type and a set of values	false	see Update Firewall Rule - body - remotePort table
status	Defines if rule is Enabled or Disabled	false	enum
tag	[DEPRECATED] Free text to describe the rule. Please use description instead.	false	string
tagIds	Tag ids	false	string []

Update Firewall Rule - body - application

Name	Description	Required	Value
type	Type of the application	false	enum
values	Value of the application	false	string []

Update Firewall Rule - body - localHost

Name	Description	Required	Value
type	Type of the host	false	enum
values	Value of the host	false	string []

Update Firewall Rule - body - localPort

Name	Description	Required	Value
type	Type of the ports	false	enum
values	A list of port numbers	false	integer []

Update Firewall Rule - body - location

Name	Description	Required	Value
type	Location type	true	enum
values	Location IDs (applicable for the "specific" location type only)	false	see Update Firewall Rule - body - values table

Update Firewall Rule - body - values

Name	Description	Required	Value
id	Location ID	true	string
name	Location name	false	string

scope	Location scope	false	enum
-------	----------------	-------	------

Update Firewall Rule - body - remoteHost

Name	Description	Required	Value
type	Type of the host	false	enum
values	Value of the host	false	string []

Update Firewall Rule - body - remoteHosts

Name	Description	Required	Value
type	Type of the host	false	enum
values	Value of the host	false	string []

Update Firewall Rule - body - remotePort

Name	Description	Required	Value
type	Type of the ports	false	enum
values	A list of port numbers	false	integer []

Forensics

Application Forensics

GET /web/api/v2.1/applications/{application_id}/forensics

DEPRECATED

Parameters

accountids	optional	List of Account IDs to filter by. Example:
------------	----------	--

		"225494730938493804,225494730938493915".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Application Forensics - response - data table
errors	Errors	false	array

Application Forensics - response - data

Name	Description	Required	Value
result	Result	false	see Application Forensics - response - result table
success	Success	false	boolean

Application Forensics - response - result

Name	Description	Required	Value
agent	Agent	false	string
application_created	Application created	false	string
application_id	Application id	false	string
fetch_story_status	Fetch story status	false	string
file	File	false	see Application Forensics - response - file table
malicious_process_arguments	Malicious process arguments	false	string
process	Process	false	see Application Forensics - response - process table
process_created_at	Process created at	false	string
process_display_name	Process display name	false	string
seen_on_network	Seen on network	false	integer

Application Forensics - response - file

Name	Description	Required	Value
content_hash	Content hash	false	string
created_date	Created date	false	string
display_name	Display name	false	string
is_system	Is system	false	boolean
object_id	Object id	false	string
path	Path	false	string

permission	Permission	false	string
size	Size	false	integer

Application Forensics - response - process

Name	Description	Required	Value
bundle_id	Bundle id	false	string
created_date	Created date	false	string
display_name	Display name	false	string
executable_file_id	Executable file id	false	string
is_primary	Is primary	false	boolean
is_root	Is root	false	boolean
object_id	Object id	false	string
pid	Pid	false	integer
username	Username	false	string

Application Forensics - Detailed

GET /web/api/v2.1/applications/{application_id}/forensics/details

[DEPRECATED] Returns an empty array

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Application Forensics - Detailed - response - data table
errors	Errors	false	array

Application Forensics - Detailed - response - data

Name	Description	Required	Value
result	Result	false	see Application Forensics - Detailed - response - result table
success	Success	false	boolean

Application Forensics - Detailed - response - result

Name	Description	Required	Value
agent	Agent	false	string
application_created	Application created	false	string
application_duration	Application duration	false	string
application_id	Application id	false	string
category_scores	Category scores	false	
fetch_story_error_at	Fetch story error at	false	string
fetch_story_sent_at	Fetch story sent at	false	string
fetch_story_status	Fetch story status	false	string
file	File	false	see Application Forensics - Detailed - response - file table
graph	Graph	false	
last_event_seen_at	Last event seen at	false	string
process	Process	false	see Application Forensics - Detailed - response - process table
process_created_at	Process created at	false	string
process_display_name	Process display name	false	string
raw_data	Raw data	false	
seen_on_network	Seen on network	false	integer
summary	Summary	false	
summary_overview	Summary overview	false	see Application Forensics - Detailed - response - summary_overview table

Application Forensics - Detailed - response - file

Name	Description	Required	Value
content_hash	Content hash	false	string
created_date	Created date	false	string
display_name	Display name	false	string
is_system	Is system	false	boolean
object_id	Object id	false	string
path	Path	false	string
permission	Permission	false	string
size	Size	false	integer

Application Forensics - Detailed - response - process

Name	Description	Required	Value
bundle_id	Bundle id	false	string
created_date	Created date	false	string
display_name	Display name	false	string
executable_file_id	Executable file id	false	string
is_primary	Is primary	false	boolean
is_root	Is root	false	boolean
object_id	Object id	false	string
pid	Pid	false	integer
username	Username	false	string

Application Forensics - Detailed - response - summary_overview

Name	Description	Required	Value
file	File	false	see Application Forensics - Detailed - response - file table
network	Network	false	see Application Forensics - Detailed - response - network table
registry	Registry	false	see Application Forensics - Detailed - response - registry table

Application Forensics - Detailed - response - file

Name	Description	Required	Value
create	Create	false	integer
delete	Delete	false	integer
write	Write	false	integer

Application Forensics - Detailed - response - network

Name	Description	Required	Value
connections	Connections	false	integer
dns	Dns	false	integer

Application Forensics - Detailed - response - registry

Name	Description	Required	Value
persistence	Persistence	false	integer
security	Security	false	integer
stealth	Stealth	false	integer

Application Connections

GET /web/api/v2.1/applications/{application_id}/forensics/connections

[DEPRECATED] Returns an empty array

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
country_code	optional	Country code
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Application Connections - response - data table
errors	Errors	false	array

Application Connections - response - data

Name	Description	Required	Value
data	Data	false	see Application Connections - response - data table

Application Connections - response - data

Name	Description	Required	Value
		false	object

Export Application

GET /web/api/v2.1/applications/{application_id}/forensics/export/{export_format}

[DEPRECATED] Returns an empty array

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Not found

Gateways

Get Gateways

GET /web/api/v2.1/ranger/gateways

Get the gateways in your deployment that match the filter from a Network Discovery scan. Network Discovery requires a Network Discovery license.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
agentpercentage__between	optional	Percentage of agents of the account in this network calculated as $\text{numberOfAgents}/\text{totalAgents} * 100$. Example: "70-80".
agentpercentage__gt	optional	Agent percentage (more than)
agentpercentage__gte	optional	Agent percentage (more than or equal)
agentpercentage__lt	optional	Agent percentage (less than)
agentpercentage__lte	optional	Agent percentage (less than or equal)
allowscan	optional	Do we allow scanning in this network
archived	optional	Archived network
connectedrangers__between	optional	The total of non decommissioned agents in the account. Example: "2-8".
connectedrangers__gt	optional	Total agents (more than)
connectedrangers__gte	optional	Total agents (more than or equal)
connectedrangers__lt	optional	Total agents (less than)
connectedrangers__lte	optional	Total agents (less than or equal)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".

createdat__gt	optional	Gateway created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Gateway created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Gateway created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Gateway created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
externalip	optional	Search external ip using a CIDR expression or exact IP
externalip__contains	optional	Free-text filter by visible IP (supports multiple values). Example: "192.168.0.1/24,10.1".
icmpscan	optional	ICMP scan enabled
ids	optional	List of gateway ids. Example: "225494730938493804,225494730938493915".
ip	optional	Search ip using a CIDR expression exact IP
ip__contains	optional	Free-text filter by IP Address (supports multiple values). Example: "192.168.0.1/24,10.1".
limit	optional	Limit number of returned items (1-1000). Example: "10".
macaddress	optional	The gateway mac address
macaddress__contains	optional	Free-text filter by mac address (supports multiple values). Example: "aa:ee:b1".
manufacturer	optional	The gateway manufacturer obtained from the mac address
manufacturer__contains	optional	Free-text filter by manufacturer (supports multiple values). Example: "Company".
mdnsscan	optional	MDNS scan enabled
networkname__contains	optional	Free-text filter by network name (supports multiple values). Example: "Network1".
new	optional	True if this is network was first seen some days ago, 3 by default
numberofagents__between	optional	The number of non decommissioned agents in this network. Example: "2-8".
numberofagents__gt	optional	Agent count (more than)

numberofagents__gte	optional	Agent count (more than or equal)
numberofagents__lt	optional	Agent count (less than)
numberofagents__lte	optional	Agent count (less than or equal)
numberofrangers__between	optional	The number of non decommissioned agents in this network. Example: "2-8".
numberofrangers__gt	optional	Network Discovery count (more than)
numberofrangers__gte	optional	Network Discovery count (more than or equal)
numberofrangers__lt	optional	Network Discovery count (less than)
numberofrangers__lte	optional	Network Discovery count (less than or equal)
query	optional	Free text query
rdnsscan	optional	RDNS scan enabled
scanonlylocalsubnets	optional	Allow remote tasks form this network
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
smbscan	optional	SMB scan enabled
snmpscan	optional	SNMP scan enabled
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
tcpports__contains	optional	Free-text filter by tcp port (supports multiple values). Example: "80,24".
totalagents__between	optional	The total of non decommissioned agents in the account. Example: "2-8".
totalagents__gt	optional	Total agents (more than)
totalagents__gte	optional	Total agents (more than or equal)
totalagents__lt	optional	Total agents (less than)
totalagents__lte	optional	Total agents (less than or equal)
udpports__contains	optional	Free-text filter by udp port (supports multiple values). Example: "137,2002".

updatedat__between	optional	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedat__gt	optional	Gateway updated after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Gateway updated after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Gateway updated before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Gateway updated before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Gateways - response - pagination table
data	Response data	false	see Get Gateways - response - data table
errors	Errors	false	array

Get Gateways - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Gateways - response - data

Name	Description	Required	Value
accountId	The Account Id	false	integer
accountName	Account name	false	string
agentPercentage	Percentage of agents of the account in this network calculated as $\text{numberOfAgents} / \text{totalAgents} * 100$	false	number
allowScan	Do we allow scanning in this network	false	boolean
archived	Archived network	false	boolean
connectedRangers	The number of active scanners	false	integer
createdAt	Created at	false	string
discoveryMethod	Discovery method	false	enum
expiryDate	Date when this network will expire, null if it won't expire	false	string
externalIp	The gateway external Ip	false	string
icmpScan	ICMP scan enabled	false	boolean
id	The gateway id	false	string
inheritSettings	True if inherited values are taken from account settings	false	boolean
ip	The gateway local ip	false	string
macAddress	The gateway mac address	false	string

manufacturer	The gateway manufacturer obtained from the mac address	false	string
mdnsScan	MDNS scan enabled	false	boolean
multiScanSsdP	Multicast SSDP scan enabled	false	boolean
networkName	The network name	false	string
new	True if this is network was first seen some days ago, 3 by default	false	boolean
numberOfAgents	The number of non decommissioned agents in this network	false	integer
numberOfRangers	The number of scanners in this network	false	integer
rdnsScan	RDNS scan enabled	false	boolean
restrictions	A set of IP addresses that should not be scanned in the specific network	false	see Get Gateways - response - restrictions table
scanOnlyLocalSubnets	Allow remote tasks form this network	false	boolean
siteId	The Site Id	false	integer
smbScan	SMB scan enabled	false	boolean
snmpScan	SNMP scan enabled	false	boolean
tcpPorts	Allowed TCP ports	false	integer []
tcpPortScan	TCP Port scan enabled	false	boolean
totalAgents	The total of non decommissioned agents in the account	false	integer
udpPorts	Allowed UDP ports	false	integer []
udpPortScan	UDP Port scan enabled	false	boolean

Get Gateways - response - restrictions

Name	Description	Required	Value
annotation	An optional note with the reason for the restriction	false	string
type		false	enum
values	It will be one IP or one CIDR or two values for a Range	false	string []

Update Gateways

POST /web/api/v2.1/ranger/gateways/update

Change the status of filtered gateways discovered by Network Discovery. You can set the archived status, whether the network behind the gateway may be scanned by Network Discovery, and whether Network Discovery will scan only local networks.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Gateways - response - data table
errors	Errors	false	array

Update Gateways - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Gateways - body - data table
filter	Filter	true	see Update Gateways - body - filter table

Update Gateways - body - data

Name	Description	Required	Value
allowScan	Do we allow scanning in this network	false	boolean
archived	True if we should archive the network, valid for networks that are not allowed to scan only	false	boolean
inheritSettings	True if inherited values are taken from account settings	false	boolean
scanOnlyLocalSubnets	Allow remote tasks form this network	false	boolean

Update Gateways - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
agentPercentage__between	Percentage of agents of the account in this network calculated as $\text{numberOfAgents}/\text{totalAgents} * 100$	false	string
agentPercentage__gt	Agent percentage (more than)	false	number
agentPercentage__gte	Agent percentage (more than or equal)	false	number
agentPercentage__lt	Agent percentage (less than)	false	number
agentPercentage__lte	Agent percentage (less than or equal)	false	number
allowScan	Do we allow scanning in this network	false	string
archived	Archived network	false	boolean
connectedRangers__between	The total of non decommissioned agents in the account	false	string
connectedRangers__gt	Total agents (more than)	false	integer
connectedRangers__gte	Total agents (more than or equal)	false	integer
connectedRangers__lt	Total agents (less than)	false	integer
connectedRangers__lte	Total agents (less than or equal)	false	integer
createdAt__between	Date range for creation time (format:	false	string

	<from_timestamp>-<to_timestamp>, inclusive)		
createdAt__gt	Gateway created after this timestamp	false	string
createdAt__gte	Gateway created after or at this timestamp	false	string
createdAt__lt	Gateway created before this timestamp	false	string
createdAt__lte	Gateway created before or at this timestamp	false	string
externalIp	Search external ip using a CIDR expression or exact IP	false	string
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
icmpScan	ICMP scan enabled	false	boolean
ids	List of gateway ids	false	string []
ip	Search ip using a CIDR expression exact IP	false	string
ip__contains	Free-text filter by IP Address (supports multiple values)	false	string []
macAddress	The gateway mac address	false	string
macAddress__contains	Free-text filter by mac address (supports multiple values)	false	string []
manufacturer	The gateway manufacturer obtained from the mac address	false	string
manufacturer__contains	Free-text filter by manufacturer (supports multiple values)	false	string []
mdnsScan	MDNS scan enabled	false	boolean
networkName__contains	Free-text filter by network name (supports multiple values)	false	string []
new	True if this is network was first seen some days ago, 3 by default	false	boolean
numberOfAgents__between	The number of non decommissioned agents in this network	false	string
numberOfAgents__gt	Agent count (more than)	false	integer
numberOfAgents__gte	Agent count (more than or equal)	false	integer
numberOfAgents__lt	Agent count (less than)	false	integer

numberOfAgents__lte	Agent count (less than or equal)	false	integer
numberOfRangers__between	The number of non decommissioned agents in this network	false	string
numberOfRangers__gt	Network Discovery count (more than)	false	integer
numberOfRangers__gte	Network Discovery count (more than or equal)	false	integer
numberOfRangers__lt	Network Discovery count (less than)	false	integer
numberOfRangers__lte	Network Discovery count (less than or equal)	false	integer
query	Free text query	false	string
rdnsScan	RDNS scan enabled	false	boolean
scanOnlyLocalSubnets	Allow remote tasks form this network	false	boolean
sitelds	List of Site IDs to filter by	false	string []
smbScan	SMB scan enabled	false	boolean
snmpScan	SNMP scan enabled	false	boolean
tcpPorts__contains	Free-text filter by tcp port (supports multiple values)	false	integer []
totalAgents__between	The total of non decommissioned agents in the account	false	string
totalAgents__gt	Total agents (more than)	false	integer
totalAgents__gte	Total agents (more than or equal)	false	integer
totalAgents__lt	Total agents (less than)	false	integer
totalAgents__lte	Total agents (less than or equal)	false	integer
udpPorts__contains	Free-text filter by udp port (supports multiple values)	false	integer []
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Gateway updated after this timestamp	false	string
updatedAt__gte	Gateway updated after or at this timestamp	false	string
updatedAt__lt	Gateway updated before this timestamp	false	string
updatedAt__lte	Gateway updated before or at this timestamp	false	string

Update Gateway

PUT /web/api/v2.1/ranger/gateways/{gateway_id}

Change the Network Discovery scan configuration for a gateway that Network Discovery discovered

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Gateway - response - data table
errors	Errors	false	array

Update Gateway - response - data

Name	Description	Required	Value
accountId	The Account Id	false	integer
accountName	Account name	false	string
agentPercentage	Percentage of agents of the account in this network calculated as $\text{numberOfAgents}/\text{totalAgents} * 100$	false	number
allowScan	Do we allow scanning in this network	false	boolean
archived	Archived network	false	boolean
connectedRangers	The number of active scanners	false	integer
createdAt	Created at	false	string
discoveryMethod	Discovery method	false	enum
expiryDate	Date when this network will expire, null if it won't expire	false	string
externalIp	The gateway external Ip	false	string
icmpScan	ICMP scan enabled	false	boolean
id	The gateway id	false	string
inheritSettings	True if inherited values are taken from account settings	false	boolean
ip	The gateway local ip	false	string
macAddress	The gateway mac address	false	string
manufacturer	The gateway manufacturer obtained from the mac address	false	string
mdnsScan	MDNS scan enabled	false	boolean
multiScanSsdP	Multicast SSDP scan enabled	false	boolean
networkName	The network name	false	string
new	True if this is network was first seen some days ago, 3 by default	false	boolean
numberOfAgents	The number of non decommissioned agents in this network	false	integer
numberOfRangers	The number of scanners in this network	false	integer

rdnsScan	RDNS scan enabled	false	boolean
restrictions	A set of IP addresses that should not be scanned in the specific network	false	see Update Gateway - response - restrictions table
scanOnlyLocalSubnets	Allow remote tasks form this network	false	boolean
siteId	The Site Id	false	integer
smbScan	SMB scan enabled	false	boolean
snmpScan	SNMP scan enabled	false	boolean
tcpPorts	Allowed TCP ports	false	integer []
tcpPortScan	TCP Port scan enabled	false	boolean
totalAgents	The total of non decommissioned agents in the account	false	integer
udpPorts	Allowed UDP ports	false	integer []
udpPortScan	UDP Port scan enabled	false	boolean

Update Gateway - response - restrictions

Name	Description	Required	Value
annotation	An optional note with the reason for the restriction	false	string
type		false	enum
values	It will be one IP or one CIDR or two values for a Range	false	string []

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Gateway - body - data table

Update Gateway - body - data

Name	Description	Required	Value
accountId	The Account Id	false	integer
allowScan	Do we allow scanning in this network	false	boolean
archived	Archived network	false	boolean
icmpScan	ICMP scan enabled	false	boolean
inheritSettings	True if inherited values are taken from account settings	false	boolean
mdnsScan	MDNS scan enabled	false	boolean
multiCastSsdpscan	Multicast SSDP scan enabled	false	boolean
networkName	The network name	false	string
rdnsScan	RDNS scan enabled	false	boolean
restrictions	A set of IP addresses that should not be scanned in the specific network	false	see Update Gateway - body - restrictions table
scanOnlyLocalSubnets	Can we scan remote networks from this gateway	false	boolean
siteId	The Site Id	false	integer
smbScan	SMB scan enabled	false	boolean
snmpScan	SNMP scan enabled	false	boolean
tcpPorts	Allowed TCP ports	false	integer []
tcpPortScan	TCP Port scan enabled	false	boolean
udpPorts	Allowed UDP ports	false	integer []
udpPortScan	UDP Port scan enabled	false	boolean

Update Gateway - body - restrictions

Name	Description	Required	Value
annotation	An optional note with the reason for the restriction	false	string
type		false	enum

values	It will be one IP or one CIDR or two values for a Range	false	string []
--------	---	-------	-----------

Graph

Query the graph based on query builder filters

POST /web/api/v2.1/xdr/graph-explorer/query/explorer/v2

Query the graph

Parameters

accountids	optional	List of Account IDs to filter by
continuationtoken	optional	Continuation token
groupids	optional	List of Group IDs to filter by
limit	optional	Limit
mock	optional	Mock
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Query the graph based on query builder filters - response - data table
errors	Errors	false	array

Query the graph based on query builder filters - response - data

Name	Description	Required	Value
maxLimit	Max limit	true	boolean
timeOut	Time out	true	boolean
totalAvailableNodes	Total available nodes	true	integer
continuationToken	Continuation token	false	string
links	Links	false	object
nodes	Nodes	false	object

Body Schema

Name	Description	Required	Value
name	Name	true	string
search		false	see Query the graph based on query builder filters - body - search table

Query the graph based on query builder filters - body - search

Name	Description	Required	Value
entityType	Entity type	true	enum
id	Id	true	string
children	Children	false	undefined []
op	Op	false	enum
parentId	Parent id	false	string
value		false	see Query the graph based on query builder filters - body - value table

Query the graph based on query builder filters - body - value

Query the graph based on query builder filters

POST /web/api/v2.1/xdr/graph-explorer/query/explorer

Query the graph

Parameters

accountids	optional	List of Account IDs to filter by
continuationtoken	optional	Continuation token
groupids	optional	List of Group IDs to filter by
limit	optional	Limit
mock	optional	Mock
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Query the graph based on query builder filters - response - data table
errors	Errors	false	array

Query the graph based on query builder filters - response - data

Name	Description	Required	Value
maxLimit	Max limit	true	boolean
timeOut	Time out	true	boolean
totalAvailableNodes	Total available nodes	true	integer
continuationToken	Continuation token	false	string
links	Links	false	object
nodes	Nodes	false	object

Body Schema

Name	Description	Required	Value
search		false	see Query the graph based on query builder filters - body - search table

Query the graph based on query builder filters - body - search

Name	Description	Required	Value
entityType	Entity type	true	enum
id	Id	true	string
children	Children	false	undefined []
op	Op	false	enum
parentId	Parent id	false	string
value		false	see Query the graph based on query builder filters - body - value table

Query the graph based on query builder filters - body - value

Query the sub graph of an asset type and id

POST /web/api/v2.1/xdr/graph-explorer/query/subgraph

Query the sub graph of an asset type and id

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Query the sub graph of an asset type and id - response - data table
errors	Errors	false	array

Query the sub graph of an asset type and id - response - data

Name	Description	Required	Value
maxLimit	Max limit	true	boolean
timeOut	Time out	true	boolean
totalAvailableNodes	Total available nodes	true	integer
continuationToken	Continuation token	false	string
links	Links	false	object
nodes	Nodes	false	object

Body Schema

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
ids	Ids	false	string []
siteIds	List of Site IDs to filter by	false	string []

Graph Query Builder

Get Graph Query Builder Initial Metadata

GET /web/api/v2.1/xdr/graph-explorer/query/builder/metadata

Get graph query builder initial metadata

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Get Graph Query Builder Initial Metadata - response - data table
errors	Errors	false	array

Get Graph Query Builder Initial Metadata - response - data

Name	Description	Required	Value
categories	Categories	false	undefined []

Get Graph Query Builder Initial Metadata

GET /web/api/v2.1/xdr/assets/query/builder/metadata

Get graph query builder initial metadata

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Get Graph Query Builder Initial Metadata - response - data table
errors	Errors	false	array

Get Graph Query Builder Initial Metadata - response - data

Name	Description	Required	Value
categories	Categories	false	undefined []

Get Query Builder metadata For Requested Resource Types

GET /web/api/v2.1/xdr/graph-explorer/query/builder/metadata/available-options/v2

Get query builder metadata for requested cloud asset types

Parameters

accountids	optional	List of Account IDs to filter by
categoryids	optional	List of category ids
groupids	optional	List of Group IDs to filter by
ids	optional	List of asset type ids
siteids	optional	List of Site IDs to filter by
subcategoriesids	optional	List of subCategory ids
version	optional	Version

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Get Query Builder metadata For Requested Resource Types - response - data table
errors	Errors	false	array

Get Query Builder metadata For Requested Resource Types - response - data

Name	Description	Required	Value
properties	Properties	false	undefined []
relations	Relations	false	undefined []

Auto Complete

GET /web/api/v2.1/xdr/graph-explorer/query/builder/autocomplete

This api is now deprecated use /xdr/graph-explorer/query/builder/autocomplete/v2 instead.

Parameters

key	required	Search field key
accountids	optional	List of Account IDs to filter by
categoryids	optional	List of category ids
groupids	optional	List of Group IDs to filter by
ids	optional	List of asset type ids
limit	optional	Limit number of returned items
siteids	optional	List of Site IDs to filter by
subcategoriesids	optional	List of subCategory ids
text	optional	Search term text
version	optional	Version

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Auto Complete

GET /web/api/v2.1/xdr/graph-explorer/query/builder/autocomplete/v2

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
accountids	optional	List of Account IDs to filter by
categoryids	optional	List of category ids
groupids	optional	List of Group IDs to filter by
ids	optional	List of asset type ids
limit	optional	Limit number of returned items
siteids	optional	List of Site IDs to filter by
subcategoriesids	optional	List of subCategory ids
text	optional	Search term text
version	optional	Version

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Tag Auto Complete

POST /web/api/v2.1/xdr/graph-explorer/query/builder/tag/autocomplete

Use this command to get tag keys or values. When you send this command with input value and field name either `key` or `value`, it returns auto-complete suggestions for the field.

Parameters

field	required	Search in keys or values
accountids	optional	List of Account IDs to filter by
categoryids	optional	List of category ids
groupids	optional	List of Group IDs to filter by
ids	optional	List of asset type ids
limit	optional	Limit number of returned items
siteids	optional	List of Site IDs to filter by
subcategoriesids	optional	List of subCategory ids
value	optional	Search term value
version	optional	Version

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Tag Auto Complete - response - data table
errors	Errors	false	array

Tag Auto Complete - response - data

Name	Description	Required	Value
title	Tag filtered based on key or value	false	string
values	Values	false	string []

Get all of the feature toggles for graph services.

GET /web/api/v2.1/xdr/private/graph-services-features

Get all of the feature toggles for graph services

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Get all of the feature toggles for graph services. - response - data table
errors	Errors	false	array

Get all of the feature toggles for graph services. - response - data

Name	Description	Required	Value
graph_feature_toggles	Graph feature toggles	false	

Get the available relations

GET /web/api/v2.1/xdr/graph-explorer/query/builder/metadata/available-relations

Get the available relations

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Graph Query Management

Get graph recent query list

GET /web/api/v2.1/xdr/graph-explorer/query/management/recent-queries

Get graph recent query list

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
limit	optional	Limit number of returned items
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Get graph query list

GET /web/api/v2.1/xdr/graph-explorer/query/management/query

Get graph query list

Parameters

accountids	optional	List of Account IDs to filter by
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
groupids	optional	List of Group IDs to filter by
limit	optional	Limit number of returned items (1-1000)
name__contains	optional	Free-text search filter by query name
querytype	optional	Query type
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
version	optional	Version

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Get graph query list - response - pagination table

Get graph query list - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Save graph query

POST /web/api/v2.1/xdr/graph-explorer/query/management/query

Save graph query

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Save graph query - response - data table
errors	Errors	false	array

Save graph query - response - data

Name	Description	Required	Value
queryId	Query id	false	string

Body Schema

Name	Description	Required	Value
name	Name	true	string
query	Query	true	string
queryDescription	Query description	true	string
shared	Shared	true	boolean

Get graph query counts by type

GET /web/api/v2.1/xdr/graph-explorer/query/management/query/type-counts

Get graph query counts by type

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Get graph query counts by type - response - data table
errors	Errors	false	array
pagination		false	see Get graph query counts by type - response - pagination table

Get graph query counts by type - response - data

Name	Description	Required	Value
saved	Saved	false	integer
shared	Shared	false	integer
suggested	Suggested	false	integer

Get graph query counts by type - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Update graph query

PUT /web/api/v2.1/xdr/graph-explorer/query/management/query/{query_id}

Update graph query

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Update graph query - response - data table
errors	Errors	false	array

Update graph query - response - data

Name	Description	Required	Value
message	Simple response message denoting action success	false	string

Body Schema

Name	Description	Required	Value
name	Name	true	string
query	Query	true	string
queryDescription	Query description	true	string
shared	Shared	true	boolean

Delete graph query

DELETE /web/api/v2.1/xdr/graph-explorer/query/management/query/{query_id}

Delete graph query

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Delete graph query - response - data table
errors	Errors	false	array

Delete graph query - response - data

Name	Description	Required	Value
message	Simple response message denoting action success	false	string

Groups

Get Groups

GET /web/api/v2.1/groups

Get data of groups that match the filter. Best practice: use as narrow a filter as you can. The data can be quite long for many groups. The response returns the ID of each group, which you can use in other commands.

BEST PRACTICE

use as narrow a filter as you can. The data can be quite long for many groups. The response returns the ID of each group, which you can use in other commands.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
description	optional	The description for the Group
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
id	optional	Id. Example: "225494730938493804".
isdefault	optional	Is this the default group?

limit	optional	Limit number of returned items (1-1000). Example: "10".
name	optional	Name
query	optional	Free text search on fields name, description
rank	optional	The rank sets the priority of a dynamic group over others. Example: "1".
registrationtoken	optional	Registration token. Example: "eyJ1cmwiOiAiaHR0cHM6Ly9jb25zb2xlLnNlbnRpbmVsb25lM5ldClIsICJzaXRlX2tleSI6IClwNzhkYjliMWUyOTA1Y2NhIn0=".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
type	optional	Group type. Example: "static".
types	optional	A list of Group types. Example: "static".
updatedat__gt	optional	Updated at greater than. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Updated at greater or equal than. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Updated at lesser than. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Updated at lesser or equal than. Example: "2018-02-27T04:49:26.257525Z".

Response Messages

200 - Data retrieved successfully

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Groups - response - pagination table
data	Response data	false	see Get Groups - response - data table
errors	Errors	false	array

Get Groups - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Groups - response - data

Name	Description	Required	Value
createdAt	Timestamp of group creation	false	string
creator	The user that created the group	false	string
creatorId	The ID of the user that created the group	false	string
description	The user-defined description for the Group	false	string
filterId	If the group is dynamic id of the filter which is used to associate agents	false	string
filterName	If the group is dynamic the name of the filter which is used to associate agents	false	string
id	Id	false	string
inherits	True if the policy is inherited from Site, False if the group has its own edited policy	false	boolean
isDefault	True only for the default group of the Site	false	boolean
name	Name	false	string
rank	The rank sets the priority of a dynamic group over others	false	integer
registrationToken	[DEPRECATED] token generation in	false	

	dedicated endpoint - /groups/<group_id>/token		
siteld	The id of the site this group is part of	false	string
totalAgents	Count of agents in the group	false	integer
type	Group type	false	enum
updatedAt	Timestamp of last update	false	string

Create Group

POST /web/api/v2.1/groups

Create a new group. You must create the Group in a Site (run "sites" to get the Site ID) for which you have permissions. If you create a dynamic Group, you must have the ID of a filter saved in the Site (run "filters?sitelds=<id from sites>").

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Group - response - data table
errors	Errors	false	array

Create Group - response - data

Name	Description	Required	Value
createdAt	Timestamp of group creation	false	string
creator	The user who created the group	false	string
creatorId	The ID of the user that created the group	false	string
description	The user-defined description for the Group	false	string
filterId	If the group is dynamic id of the filter which is used to associate agents	false	string
id	Id	false	string
isDefault	True only for the default group of the Site	false	boolean
name	Name	false	string
rank	The rank sets the priority of a dynamic group over others	false	integer
registrationToken	[DEPRECATED] token generation in dedicated endpoint - /groups/<group_id>/token	false	
siteId	The id of the site this group is part of	false	string
type	Group type	false	enum
updatedAt	Timestamp of last update	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Group - body - data table

Create Group - body - data

Name	Description	Required	Value
inherits	True to inherit from site policy.	true	boolean
name	Name	true	string
siteld	The site this group should be part of	true	string
description	The user-defined description for the Group	false	string
filterId	If supplied this group will be dynamic using the filter to associate agents.	false	string
isDefault	Obsolete for POST, always false	false	boolean
policy	The group policy, it is required only if inherits is False, ignored else.	false	see Create Group - body - policy table
rank	Obsolete for post - The rank of the group	false	integer
source	Obsolete - Always MGMT	false	string
type	Type of Group: Static, Dynamic, or Pinned	false	enum

Create Group - body - policy

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Create Group - body - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved	false	boolean

	Process on/off		
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Create Group - body - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Create Group - body - dvAttributesPerEventType table
engines	The engines statuses	false	see Create Group - body - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Create Group - body - forensicsAutoTriggering table
identityConfigurationSettings	Identity configuration	false	see Create Group - body - identityConfigurationSettings table
identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Create Group - body - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean

isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Create Group - body - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Create Group - body - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean
researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first registration	false	boolean
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Create Group - body - agentUi

Name	Description	Required	Value
------	-------------	----------	-------

agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Create Group - body - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Create Group - body - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Create Group - body - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Create Group - body - behavioralIndicators table
commandScripts	Command scripts event	false	see Create Group - body - commandScripts table
crossProcess	Cross process event	false	see Create Group - body - crossProcess table
dataMasking	Data masking	false	see Create Group - body - dataMasking table
dllModuleLoad	DLL module load event	false	see Create Group - body - dllModuleLoad table
dns	Network event - DNS	false	see Create Group - body - dns table
driver	Driver	false	see Create Group - body - driver table
externalDeviceActivity	External Device Activity	false	see Create Group - body - externalDeviceActivity table
file	File event	false	see Create Group - body - file table
ip	Network event - IP	false	see Create Group - body - ip table
login	User login/logout event	false	see Create Group - body - login table
namedPipe	Named Pipe	false	see Create Group - body - namedPipe table
namedPipeExtended	Named Pipe Extended	false	see Create Group - body - namedPipeExtended table
openDirectoryActivity	Open Directory Activity	false	see Create Group - body - openDirectoryActivity table
process	Process event	false	see Create Group - body - process table
profileActivity	Profile Activity	false	see Create Group - body - profileActivity table
registry	Registry event	false	see Create Group - body - registry table
scheduledTask	Scheduled task event	false	see Create Group - body - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Create Group - body - smartFileMonitoring table
url	URL Actions event	false	see Create Group - body - url table
userSubstitution	User Substitution	false	see Create Group - body - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Create Group - body - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Create Group - body - windowsEventLogsExtended table

Create Group - body - autoInstallBrowserExtensions

Name	Description	Required	Value
------	-------------	----------	-------

autoInstallBrowserExtensions	Auto install browser extensions	false	boolean
------------------------------	---------------------------------	-------	---------

Create Group - body - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Create Group - body - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Create Group - body - crossProcess

Name	Description	Required	Value
dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Create Group - body - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Create Group - body - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Create Group - body - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Create Group - body - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Create Group - body - externalDeviceActivity

Name	Description	Required	Value
dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Create Group - body - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Create Group - body - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Create Group - body - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Create Group - body - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean
dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean

Create Group - body - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Create Group - body - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMember	Add Member to Group Event Type	false	boolean

erToGroup			
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean
dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean

Create Group - body - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Create Group - body - profileActivity

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Create Group - body - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Create Group - body - scheduledTask

Name	Description	Required	Value
dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Create Group - body - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Create Group - body - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Create Group - body - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Create Group - body - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Create Group - body - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Create Group - body - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum

executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Create Group - body - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean
macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Create Group - body - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Create Group - body - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean
externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean

scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Create Group - body - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Create Group - body - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer

maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Regenerate Group Token

PUT /web/api/v2.1/groups/{group_id}/regenerate-key

Get a new Group Token for a static Group. This command requires the Group ID ("groups") and you must have permissions for the Group. If you run this command on a dynamic Group, it ends in an error. If you use the API in scripts to add new endpoints with a Group Token rather than a Site Token, be aware that you must update the token value in your scripts.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

403 - No permission for regenerating a key.

404 - Group not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Regenerate Group Token - response - data table
errors	Errors	false	array

Regenerate Group Token - response - data

Name	Description	Required	Value
registrationToken	Registration token	false	string

Delete Group

DELETE /web/api/v2.1/groups/{group_id}

Delete a Group given by the required Group ID (run "groups"). If there are Agents in the Group, and the Group is dynamic, the next dynamic Groups will collect matching Agents, and unmatched Agents will go to the Default Group. If this is a static Group with Agents, all the Agents will go to the Default Group. (Agents always go to matching dynamic Groups. If a static Group holds Agents, there are no matching dynamic Groups.)

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

404 - Group not found.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Group - response - data table
errors	Errors	false	array

Delete Group - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Update Group

PUT /web/api/v2.1/groups/{group_id}

Change properties of a Group specified by its ID (run "groups"). The body of the request holds all the properties of a Group. You must have access permissions on the Site.
Note: iocAttributes refers to Deep Visibility. If you do not have a Complete SKU, you can remove this set.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions.

404 - Group not found.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Group - response - data table
errors	Errors	false	array

Update Group - response - data

Name	Description	Required	Value
createdAt	Timestamp of group creation	false	string
creator	The user who created the group	false	string
creatorId	The ID of the user that created the group	false	string
description	The user-defined description for the Group	false	string
filterId	If the group is dynamic id of the filter which is used to associate agents	false	string
id	Id	false	string
isDefault	True only for the default group of the Site	false	boolean
name	Name	false	string
rank	The rank sets the priority of a dynamic group over others	false	integer
registrationToken	[DEPRECATED] token generation in dedicated endpoint - /groups/<group_id>/token	false	
siteId	The id of the site this group is part of	false	string
type	Group type	false	enum
updatedAt	Timestamp of last update	false	string

Body Schema

Name	Description	Required	Value
data	Data	false	see Update Group - body - data table

Update Group - body - data

Name	Description	Required	Value
description	The user-defined description for the Group	false	string
filterId	If supplied this group will be dynamic using the filter to associate agents.	false	string
id	Id	false	string
inherits	True to inherit from Site Policy.	false	boolean
isDefault	Obsolete for POST, always false	false	boolean
name	Name	false	string
policy	The group policy, it is required only if inherits is False, ignored else.	false	see Update Group - body - policy table
rank	Obsolete for post - The rank of the group	false	integer
siteId	The site this group should be part of	false	string
source	Obsolete	false	string

Update Group - body - policy

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Update Group - body - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean

antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Update Group - body - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Update Group - body - dvAttributesPerEventType table
engines	The engines statuses	false	see Update Group - body - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Update Group - body - forensicsAutoTriggering table
identityConfigurationSettings	Identity configuration	false	see Update Group - body - identityConfigurationSettings table
identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Update Group - body - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean

isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Update Group - body - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Update Group - body - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean
researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first registration	false	boolean
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Update Group - body - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean

contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Update Group - body - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Update Group - body - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Update Group - body - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Update Group - body - behavioralIndicators table
commandScripts	Command scripts event	false	see Update Group - body - commandScripts table
crossProcess	Cross process event	false	see Update Group - body - crossProcess table
dataMasking	Data masking	false	see Update Group - body - dataMasking table
dllModuleLoad	DLL module load event	false	see Update Group - body - dllModuleLoad table
dns	Network event - DNS	false	see Update Group - body - dns table
driver	Driver	false	see Update Group - body - driver table
externalDeviceActivity	External Device Activity	false	see Update Group - body - externalDeviceActivity table
file	File event	false	see Update Group - body - file table
ip	Network event - IP	false	see Update Group - body - ip table
login	User login/logout event	false	see Update Group - body - login table
namedPipe	Named Pipe	false	see Update Group - body - namedPipe table
namedPipeExtended	Named Pipe Extended	false	see Update Group - body - namedPipeExtended table
openDirectoryActivity	Open Directory Activity	false	see Update Group - body - openDirectoryActivity table
process	Process event	false	see Update Group - body - process table
profileActivity	Profile Activity	false	see Update Group - body - profileActivity table
registry	Registry event	false	see Update Group - body - registry table
scheduledTask	Scheduled task event	false	see Update Group - body - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Update Group - body - smartFileMonitoring table
url	URL Actions event	false	see Update Group - body - url table
userSubstitution	User Substitution	false	see Update Group - body - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Update Group - body - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Update Group - body - windowsEventLogsExtended table

Update Group - body - autoInstallBrowserExtensions

Name	Description	Required	Value
------	-------------	----------	-------

autoInstallBrowserExtensions	Auto install browser extensions	false	boolean
------------------------------	---------------------------------	-------	---------

Update Group - body - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Update Group - body - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Update Group - body - crossProcess

Name	Description	Required	Value
dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Update Group - body - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Update Group - body - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Update Group - body - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Update Group - body - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Update Group - body - externalDeviceActivity

Name	Description	Required	Value
dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Update Group - body - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Update Group - body - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Update Group - body - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Update Group - body - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean
dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean

Update Group - body - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Update Group - body - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMember	Add Member to Group Event Type	false	boolean

erToGroup			
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean
dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean

Update Group - body - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Update Group - body - profileActivity

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Update Group - body - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Update Group - body - scheduledTask

Name	Description	Required	Value
dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Update Group - body - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Update Group - body - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Update Group - body - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Update Group - body - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Update Group - body - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Update Group - body - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum

executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Update Group - body - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean
macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Update Group - body - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Update Group - body - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean
externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean

scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Update Group - body - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Update Group - body - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer

maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Get Group by ID

GET /web/api/v2.1/groups/{group_id}

Get data of a given Group. To get a Group ID, run "groups". This command responds with the ID of the Site of the Group, Group name, type (dynamic or static), and similar data. Your username must permissions for the Site.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Group by ID - response - data table
errors	Errors	false	array

Get Group by ID - response - data

Name	Description	Required	Value
createdAt	Timestamp of group creation	false	string
creator	The user who created the group	false	string
creatorId	The ID of the user that created the group	false	string
description	The user-defined description for the Group	false	string
filterId	If the group is dynamic id of the filter which is used to associate agents	false	string
id	Id	false	string
isDefault	True only for the default group of the Site	false	boolean
name	Name	false	string
rank	The rank sets the priority of a dynamic group over others	false	integer
registrationToken	[DEPRECATED] token generation in dedicated endpoint - /groups/<group_id>/token	false	
siteId	The id of the site this group is part of	false	string
type	Group type	false	enum
updatedAt	Timestamp of last update	false	string

Revert Policy

PUT /web/api/v2.1/groups/{group_id}/revert-policy

A Group can have a policy that is different from its Site policy. Use this command to revert the changes on the Group policy to inherit the Site policy. Your user must have permissions on the Site.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Revert Policy - response - data table
errors	Errors	false	array

Revert Policy - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	false	see Revert Policy - body - data table

Revert Policy - body - data

Name	Description	Required	Value
id	Id	false	string

Move Agents

PUT /web/api/v2.1/groups/{group_id}/move-agents

Move Agents that match the filter to a Group. The Group ID (run "groups") is required and there can be only one. This will move the matched Agents that are in the same Site as the given Group.

Response Messages

204 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

409 - Conflict

Body Schema

Name	Description	Required	Value
filter	Specification of which agents should be moved	true	see Move Agents - body - filter table

Move Agents - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentIds	(DEPRECATED; use 'ids' instead) List of agent ids to move to a new group	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []

agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location	false	string []

	(supports multiple values)		
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Move Agents - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format:	false	string

	<from_timestamp>-<to_timestamp>, inclusive)		
createdAt__gt	Agents created after this timestamp	false	string
createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []

encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []

isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string

lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceLocalnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum

osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []

remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []
scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot	false	boolean []

	to succeed		
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer
totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Move Agents - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer

podsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Update Ranks

PUT /web/api/v2.1/groups/ranks

An Agent can belong to only one Group. If the Agent matches multiple Dynamic Groups, it goes to the Group with the highest rank. The "rank" parameter has a minimum of "1". The lower the integer, the higher priority it has to collect Agents. Make sure the IDs of the groups in this command are for Dynamic groups.

Response Messages

204 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Ranks - body - data table
filter	Filter	true	see Update Ranks - body - filter table
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Update Ranks - body - data

Name	Description	Required	Value
ranks	List of ranks to update	false	see Update Ranks - body - ranks table

Update Ranks - body - ranks

Name	Description	Required	Value
id	Id	false	string
rank	The new rank for the group	false	integer

Update Ranks - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Get Site registration token by ID

GET /web/api/v2.1/groups/{group_id}/token

Get the registration token of the Group of the ID.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Site registration token by ID - response - data table
errors	Errors	false	array

Get Site registration token by ID - response - data

Name	Description	Required	Value
token	Token	false	string

Hashes

Hash Reputation verdict

GET /web/api/v2.1/hashes/{hash}/verdict

[DEPRECATED] Get the verdict of the of a hash, given the required SHA1.

A hash, either malicious or non-malicious, means it has been marked as such by the Reputation's sources.

An unknown answer is given for hashes that are not yet known by Reputation.

Response Messages

200 - Verdict of the hash known to the management

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Hash Reputation verdict - response - data table
errors	Errors	false	array

Hash Reputation verdict - response - data

Name	Description	Required	Value
verdict	The hash verdict, could be malicious, non-malicious or unknown	false	string

Hyperautomation

List all workflow executions

GET /web/api/v2.1/hyper-automate/api/public/workflow-execution

Parameters

accountids	optional	
created_at__gte	optional	
created_at__lt	optional	
cursor	optional	Base64-url-encoded cursor for cursor-based pagination. Omit on the first request or pass the literal string <code>`"null"`</code>; on subsequent requests, pass the <code>`pagination.nextCursor`</code> value returned by the previous response. When <code>`nextCursor`</code> is the literal string <code>`"null"`</code>, the end of the result set has been reached. Requires <code>`sortBy`</code> to be set; <code>`sortBy`</code> and <code>`sortOrder`</code> (default <code>`ASC`</code>) must match the values used when the cursor was issued, otherwise the request fails with HTTP 400. A malformed cursor returns HTTP 400 <code>`invalid cursor`</code>. The query filters must be preserved across multiple requests fetching subsequent pages.
groupids	optional	
integrations	optional	
is_snippet	optional	
limit	optional	

scope_ids	optional	
siteids	optional	
skip	optional	
sortby	optional	
sortorder	optional	
states	optional	
tags	optional	
trigger_types	optional	
versions_count	optional	
workflow_id	optional	
workflow_name__contains	optional	

Response Messages

200 - Successful Response

422 - Validation Error

Response Schema

Name	Description	Required	Value
data		false	undefined []
pagination		false	see List all workflow executions - response - pagination table

List all workflow executions - response - pagination

Name	Description	Required	Value
nextCursor		true	string
totalItems		true	integer

Get a workflow execution by its ID

GET /web/api/v2.1/hyper-automate/api/public/workflow-execution/{workflow_execution_id}

Parameters

accountids	optional	
groupids	optional	
siteids	optional	

Response Messages

200 - Successful Response

422 - Validation Error

Response Schema

Name	Description	Required	Value
id		true	string
mgmt_id		true	string
scope_id		true	string
singularity_response_event_id		true	string
version_id		true	string
workflow_id		true	string
created_at		false	string
duration		false	string

error_actions		false	undefined []
executed_actions		false	integer
has_execution_output		false	boolean
scope_level		false	enum
singularity_response_event_type		false	enum
state		false	enum
time_saved		false	number
updated_at		false	string
workflow_state		false	enum

Trigger a workflow that uses a manual trigger or a scheduled trigger

POST /web/api/v2.1/hyper-automate/api/public/workflow-execution/manual/{workflow_id}/{version_id}

Parameters

accountids	optional	
groupids	optional	
siteids	optional	

Response Messages

201 - Successful Response

422 - Validation Error

Body Schema

Name	Description	Required	Value
data		false	see Trigger a workflow that uses a manual trigger or a scheduled trigger - body - data table
filter		false	see Trigger a workflow that uses a manual trigger or a scheduled trigger - body - filter table

Trigger a workflow that uses a manual trigger or a scheduled trigger - body - data

Name	Description	Required	Value
is_downstream_execution		false	boolean
is_snippet_execution		false	boolean
parent_execution_id		false	string
payload		false	string
singularity_response_event_dedup_id		false	string
singularity_response_event_id		false	string
singularity_response_event_type		false	enum
singularity_response_execution_source		false	enum

Trigger a workflow that uses a manual trigger or a scheduled trigger - body - filter

Name	Description	Required	Value
type		true	enum
value		true	string

Get workflow execution output

GET /web/api/v2.1/hyper-automate/api/public/workflow-execution/output/{execution_id}/raw

Parameters

accountids	optional	
groupids	optional	
siteids	optional	

Response Messages

200 - Successful Response

422 - Validation Error

Response Schema

Name	Description	Required	Value
ExecutionOutput		false	object

List workflow versions

GET /web/api/v2.1/hyper-automate/api/public/workflows/versions/list/{workflow_id}

Parameters

accountids	optional	
groupids	optional	
siteids	optional	

Response Messages

200 - Successful Response

422 - Validation Error

Response Schema

Name	Description	Required	Value
versions		false	undefined []

List all workflows

GET /web/api/v2.1/hyper-automate/api/public/workflows

Parameters

accountids	optional	
action_name__contains	optional	
core_actions	optional	
cursor	optional	Base64-url-encoded cursor for cursor-based pagination. Omit on the first request or pass the literal string <code>`"null"`</code>; on subsequent requests, pass the <code>`pagination.nextCursor`</code> value returned by the previous response. When <code>`nextCursor`</code> is the literal string <code>`"null"`</code>, the end of the result set has been reached. Requires <code>`sortBy`</code> to be set; <code>`sortBy`</code> and <code>`sortOrder`</code> (default <code>`ASC`</code>) must match the values used when the cursor was issued, otherwise the request fails with HTTP 400. A malformed cursor returns HTTP 400 <code>`invalid cursor`</code>. The query filters must be preserved across multiple requests fetching subsequent pages.
description__contains	optional	
groupids	optional	
integrations	optional	
is_snippet	optional	
limit	optional	
name__contains	optional	
name__eq	optional	
oversight	optional	
scope_ids	optional	
siteids	optional	
skip	optional	
sortby	optional	

sortorder	optional	
states	optional	
tags	optional	
trigger_types	optional	
workflow_ids	optional	

Response Messages

200 - Successful Response

422 - Validation Error

Response Schema

Name	Description	Required	Value
data		false	undefined []
pagination		false	see List all workflows - response - pagination table

List all workflows - response - pagination

Name	Description	Required	Value
nextCursor		true	string
totalItems		true	integer

Activate a workflow version

POST /web/api/v2.1/hyper-automate/api/public/workflows/{workflow_id}/{version_id}/activation

Parameters

accountids	optional	
groupids	optional	
siteids	optional	

Response Messages

204 - Successful Response

422 - Validation Error

Body Schema

Name	Description	Required	Value
data		false	see Activate a workflow version - body - data table
filter		false	see Activate a workflow version - body - filter table

Activate a workflow version - body - data

Name	Description	Required	Value
daily_max_executions		false	integer
dimensions		false	see Activate a workflow version - body - dimensions table
is_snippet		false	boolean
max_concurrency		false	integer
notify_to		false	string []
time_saved		false	integer
time_saved_unit		false	string
timeout		false	integer
version_description		false	string

Activate a workflow version - body - dimensions

Name	Description	Required	Value
height		false	number
width		false	number

Activate a workflow version - body - filter

Name	Description	Required	Value
type		true	enum
value		true	string

Deactivate The active workflow

POST /web/api/v2.1/hyper-automate/api/public/workflows/{workflow_id}/deactivate

Parameters

accountids	optional	
groupids	optional	
siteids	optional	
version_id	optional	

Response Messages

204 - Successful Response

422 - Validation Error

Body Schema

Name	Description	Required	Value
data		false	
filter		false	see Deactivate The active workflow - body - filter table

Deactivate The active workflow - body - filter

Name	Description	Required	Value
type		true	enum
value		true	string

Export workflow

GET /web/api/v2.1/hyper-automate/api/public/workflow-import-export/export/{workflow_id}/{version_id}

Export a specific workflow version.

Parameters

accountids	optional	
groupids	optional	
siteids	optional	

Response Messages

200 - Successful Response

422 - Validation Error

Response Schema

Name	Description	Required	Value
name		true	string
actions		false	undefined []
description		false	string
notes		false	undefined []

Batch export workflows

GET /web/api/v2.1/hyper-automate/api/public/workflow-import-export/export

Parameters

accountids	optional	
core_actions	optional	
description__contains	optional	
groupids	optional	
integrations	optional	
name__contains	optional	
name__eq	optional	
oversight	optional	
scope_ids	optional	
siteids	optional	
states	optional	
tags	optional	
trigger_types	optional	
workflow_ids	optional	

Response Messages

200 - Successful Response

422 - Validation Error

Import workflow

POST /web/api/v2.1/hyper-automate/api/public/workflow-import-export/import

Import workflows that have been previously exported from Hyperautomation.

Parameters

accountids	optional	
groupids	optional	
siteids	optional	

Response Messages

200 - Successful Response

422 - Validation Error

Response Schema

Name	Description	Required	Value
created_by		true	string
id		true	string
mgmt_id		true	string
name		true	string
scope_id		true	string
updated_by		true	string
version_id		true	string
account_name		false	string
account_state		false	enum
activated_at		false	string
created_at		false	string
created_by_user		false	see Import workflow - response - created_by_user table
daily_max_executions		false	integer
description		false	string
dimensions		false	see Import workflow - response - dimensions table
is_snippet		false	boolean
lifecycle_state		false	enum
max_concurrency		false	integer
notify_to		false	string []

parent_scope_id		false	string
scope_level		false	enum
site_name		false	string
site_state		false	enum
state		false	string
status		false	enum
tags		false	string []
time_saved		false	integer
time_saved_unit		false	string
timeout		false	integer
updated_at		false	string
updated_by_user		false	see Import workflow - response - updated_by_user table
version_count		false	integer
version_description		false	string

Import workflow - response - created_by_user

Name	Description	Required	Value
id		true	string
email		false	string
name		false	string

Import workflow - response - dimensions

Name	Description	Required	Value
height		false	number
width		false	number

Import workflow - response - updated_by_user

Name	Description	Required	Value
id		true	string
email		false	string
name		false	string

Body Schema

Name	Description	Required	Value
data		false	see Import workflow - body - data table
filter		false	see Import workflow - body - filter table

Import workflow - body - data

Name	Description	Required	Value
name		true	string
actions		false	undefined []
description		false	string
notes		false	undefined []

Import workflow - body - filter

Name	Description	Required	Value
type		true	enum
value		true	string

Batch import workflows

POST /web/api/v2.1/hyper-automate/api/public/workflow-import-export/import/batch

Import workflows that have been previously exported from Hyperautomation.

Response Messages

201 - Successful Response

422 - Validation Error

Body Schema

Name	Description	Required	Value
file		true	string
filter		true	string

Import custom integration from OpenAPI/Swagger spec file

POST /web/api/v2.1/hyper-automate/api/public/custom-integration-import-export/import/openapi/file

Response Messages

200 - Successful Response

422 - Validation Error

Response Schema

Name	Description	Required	Value
integration		false	see Import custom integration from OpenAPI/Swagger spec file - response - integration table
warnings		false	string []

Import custom integration from OpenAPI/Swagger spec file - response - integration

Name	Description	Required	Value
id		true	string
product_name		true	string
vendor_name		true	string
account_name		false	string
account_state		false	enum
auth_form_metadata		false	object
created_at		false	string
default_connection_data		false	object
description		false	string
logo		false	string
mgmt_id		false	string
origin_id		false	string
parent_scope_id		false	string
product_key		false	string
scope_id		false	string
scope_level		false	enum
site_name		false	string
site_state		false	enum
state		false	
updated_at		false	string
vendor_key		false	string
vendor_logo		false	string

Body Schema

Name	Description	Required	Value
file		true	string
filter		true	string
data		false	string

Export custom integration

GET /web/api/v2.1/hyper-automate/api/public/custom-integration-import-export/export/{custom_integration_id}

Export a specific custom integration with its actions.

Parameters

accountids	optional	
groupids	optional	
siteids	optional	

Response Messages

200 - Successful Response

422 - Validation Error

Response Schema

Name	Description	Required	Value
product_name		true	string
vendor_name		true	string
actions		false	undefined []
auth_form_metadata		false	object
default_connection_data		false	object
description		false	string
logo		false	string
product_key		false	string
state		false	
vendor_key		false	string
vendor_logo		false	string

Batch export custom custom integrations

GET /web/api/v2.1/hyper-automate/api/public/custom-integration-import-export/export

Parameters

custom_integration_ids	required	
accountids	optional	
groupids	optional	
siteids	optional	

Response Messages

200 - Successful Response

422 - Validation Error

Import custom integration

POST /web/api/v2.1/hyper-automate/api/public/custom-integration-import-export/import

Import a custom integration that has been previously exported.

Parameters

accountids	optional	
groupids	optional	
siteids	optional	

Response Messages

200 - Successful Response

422 - Validation Error

Response Schema

Name	Description	Required	Value
id		true	string
product_name		true	string
vendor_name		true	string
account_name		false	string
account_state		false	enum
auth_form_metadata		false	object
created_at		false	string
default_connection_data		false	object
description		false	string
logo		false	string
mgmt_id		false	string
origin_id		false	string
parent_scope_id		false	string
product_key		false	string
scope_id		false	string
scope_level		false	enum
site_name		false	string
site_state		false	enum
state		false	
updated_at		false	string
vendor_key		false	string
vendor_logo		false	string

Body Schema

Name	Description	Required	Value
data		false	see Import custom integration - body - data table
filter		false	see Import custom integration - body - filter table

Import custom integration - body - data

Name	Description	Required	Value
product_name		true	string
vendor_name		true	string
actions		false	undefined []
auth_form_metadata		false	object
default_connection_data		false	object
description		false	string
logo		false	string
product_key		false	string
state		false	
vendor_key		false	string
vendor_logo		false	string

Import custom integration - body - filter

Name	Description	Required	Value
type		true	enum
value		true	string

Batch import custom integrations

POST /web/api/v2.1/hyper-automate/api/public/custom-integration-import-export/import/batch

Import custom integrations that have been previously exported.

Response Messages

201 - Successful Response

422 - Validation Error

Body Schema

Name	Description	Required	Value
file		true	string
filter		true	string

Expression Breakdown

POST /web/api/v2.1/hyper-automate/api/public/workflow-action-expressions/{base_action_id}/expression-breakdown

Parameters

accountids	optional	
groupids	optional	
siteids	optional	

Response Messages

200 - Successful Response

422 - Validation Error

Response Schema

Name	Description	Required	Value
error		false	see Expression Breakdown - response - error table
results		false	undefined []

Expression Breakdown - response - error

Name	Description	Required	Value
text		true	string
values		false	undefined []

Body Schema

Name	Description	Required	Value
data		false	see Expression Breakdown - body - data table
filter		false	see Expression Breakdown - body - filter table

Expression Breakdown - body - data

Name	Description	Required	Value
expression		true	string
loop_context		false	object

Expression Breakdown - body - filter

Name	Description	Required	Value
type		true	enum
value		true	string

Evaluate Expression

POST /web/api/v2.1/hyper-automate/api/public/workflow-action-expressions/{base_action_id}/evaluate-expression

Parameters

accountids	optional	
groupids	optional	
siteids	optional	

Response Messages

200 - Successful Response

422 - Validation Error

Response Schema

Name	Description	Required	Value
error		false	see Evaluate Expression - response - error table

results		false	undefined []
---------	--	-------	--------------

Evaluate Expression - response - error

Name	Description	Required	Value
text		true	string
values		false	undefined []

Body Schema

Name	Description	Required	Value
data		false	see Evaluate Expression - body - data table
filter		false	see Evaluate Expression - body - filter table

Evaluate Expression - body - data

Name	Description	Required	Value
expression		true	string
loop_context		false	object

Evaluate Expression - body - filter

Name	Description	Required	Value
type		true	enum
value		true	string

ISPM

Get Assessment Status

GET /web/api/v2.1/ranger-ad/assessment-status

Use the below Cloud API to get the status of the AD Assessment status for that account

Parameters

accountids	optional	List of account IDs separated by comma
siteids	optional	List of site IDs separated by comma

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Assessment Status - response - data table
errors	Errors	false	array

Get Assessment Status - response - data

Name	Description	Required	Value
domainWiseCurrentStatusList	List of assessment status for AD domains	false	see Get Assessment Status - response - domainWiseCurrentStatusList table
status	Overall assessment status	false	enum
tenantWiseCurrentStatusList	List of assessment status for Azure tenants	false	see Get Assessment Status - response - tenantWiseCurrentStatusList table

Get Assessment Status - response - domainWiseCurrentStatusList

Name	Description	Required	Value
completedJobs	Number of assessment jobs completed for this domain	false	integer
domainCompletedStatus	Whether the assessment is completed for this domain	false	boolean
domainName	Name of the Active Directory domain	false	string
forestName	Name of the Active Directory forest containing the domain	false	string
totalJobs	Total number of assessment jobs for this domain	false	integer

Get Assessment Status - response - tenantWiseCurrentStatusList

Name	Description	Required	Value
completedJobs	Number of assessment jobs completed for this tenant	false	integer
tenantCompletedStatus	Whether the assessment is completed for this tenant	false	boolean
tenantId	Unique identifier of the Azure tenant	false	string
totalJobs	Total number of assessment jobs for this tenant	false	integer

Get Exposures

POST /web/api/v2.1/ranger-ad/get-exposures

Use the below Cloud API to get all the exposures based on the selected filters

Parameters

accountids	optional	List of account IDs separated by comma
limit	optional	Limit number of returned items (1-1000). Example: "10".
siteids	optional	List of site IDs separated by comma
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Exposures - response - pagination table
data	Response data	false	see Get Exposures - response - data table
errors	Errors	false	array

Get Exposures - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Exposures - response - data

Name	Description	Required	Value
acknowledged	Whether the exposure has been acknowledged by an user	true	boolean
detectionId	Numeric identifier of the detection rule	true	integer
detectionName	Name of the detection rule that identified this exposure	true	string
detectionStatus	Current status of the exposure detection	true	enum
domainName	Active Directory domain where the exposure was found	true	string
forestName	Active Directory forest containing the domain	true	string
id	Unique identifier for the exposure	true	string
remediable	Whether the exposure can be automatically remediated	true	boolean
runTimestamp	Unix timestamp when the detection was last run	true	integer
severity	Severity level of the exposure	true	enum
source	Source of the detection	true	enum
vulnerableCount	Number of vulnerable objects affected by this exposure	true	integer

hasExcludableObjects	Whether the exposure contains objects that can be excluded	false	boolean
prevVulnerableCount	Number of vulnerable objects from the previous assessment	false	integer
skipCode	Code indicating why the exposure was skipped, if applicable	false	string
skipReason	Human-readable reason why the exposure was skipped	false	string
specialRun	Whether the re-run was performed	false	boolean
specialRunTimestamp	Unix timestamp of the re-run, if applicable	false	integer

Body Schema

Name	Description	Required	Value
filter	Filtering criteria for exposures	false	see Get Exposures - body - filter table

Get Exposures - body - filter

Name	Description	Required	Value
detectionName	Filter by specific detection names	false	string []
detectionStatus	Filter by exposure detection status	false	string []
domainName	Filter by Active Directory domain names	false	string []
forestName	Filter by Active Directory forest names	false	string []
severity	Filter by exposure severity level	false	string []
source	Filter by detection source	false	string []

Get Affected Objects

POST /web/api/v2.1/ranger-ad/get-affected-objects

Use the below Cloud API to get all the affected objects based on the selected filters

Parameters

accountids	optional	List of account IDs separated by comma
limit	optional	Limit number of returned items (1-1000). Example: "10".
siteids	optional	List of site IDs separated by comma
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Affected Objects - response - pagination table
data	Response data	false	see Get Affected Objects - response - data table
errors	Errors	false	array

Get Affected Objects - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Affected Objects - response - data

Name	Description	Required	Value
id	Unique identifier for the affected object	true	integer
runId	Identifier of the detection run that found this object	true	integer
accountStatus	Current status of the user account (enabled/disabled)	false	string
attr1	Reserved attribute field for exposure specific data	false	string
attr2	Reserved attribute field for exposure specific data	false	string
attr3	Reserved attribute field for exposure specific data	false	string
attr4	Reserved attribute field for exposure specific data	false	string
attr5	Reserved attribute field for exposure specific data	false	string
attr6	Reserved attribute field for exposure specific data	false	string
attr7	Reserved attribute field for exposure specific data	false	string
badPasswordTime	Unix timestamp of the last bad password attempt	false	integer

badPwdCount	Number of bad password attempts	false	integer
caIssuerName	Certificate Authority issuer name	false	string
caServerName	Certificate Authority server name	false	string
certAuthorityName	Name of the Certificate Authority	false	string
certificateAuthority	Certificate Authority that issued the certificate	false	string
certSerialNumber	Serial number of the certificate	false	string
certSubjectName	Subject name of the certificate	false	string
commonName	Common name (CN) of the Active Directory object	false	string
containerName	Name of the container holding the object	false	string
delegation	Delegation settings for the account	false	string
description	Description of the Azure AD object	false	string
displayName	Display name of the Active Directory object	false	string
dn	Distinguished Name (DN) of the object in Active Directory	false	string
dnsHostName	DNS hostname of the computer object	false	string
endUserConsentSetting	End user consent settings for the application	false	string
firstSeen	Unix timestamp when the object was first detected	false	integer
gPCFilePath	Group Policy Container file system path	false	string
groupType	Type of Active Directory group (Security, Distribution, etc.)	false	string
guestUser	Whether the user is a guest user in Azure AD	false	boolean
guestUserAccess	Access level granted to guest users	false	string
joinDeviceMFAConfig	Multi-factor authentication configuration for joined devices	false	string
lastLogonTimestamp	Unix timestamp of the last logon	false	integer
lockoutStatus	Whether the account is currently locked out	false	boolean

mfaRegistered	Whether the user is registered for multi-factor authentication	false	boolean
msdsGroupMsaMembership	Managed Service Account (MSA) group membership	false	string
objectGUID	Globally Unique Identifier (GUID) of the object	false	string
objectSid	Security Identifier (SID) of the object	false	string
objectType	Type of Active Directory object (User, Computer, Group, etc.)	false	string
os	Operating system information for computer objects	false	string
passwordExpiryTime	Unix timestamp when the password expires	false	integer
permission	Permission level or access rights	false	string
permissionName	Name of the permission granted	false	string
permissionType	Type of permission (Application, Delegated, etc.)	false	string
pwdLastSet	Unix timestamp when password was last set	false	integer
resource	Resource to which the permission applies	false	string
runTime	Unix timestamp when the detection was run	false	integer
samAccountName	Security Account Manager (SAM) account name	false	string
spn	Service Principal Name (SPN) associated with the account	false	string
templateName	Certificate template name	false	string
upn	User Principal Name of the object	false	string
username	Username of the Azure AD user	false	string
whenChanged	Unix timestamp when the object was last modified	false	integer
whenCreated	Unix timestamp when the object was created	false	integer

Body Schema

Name	Description	Required	Value
filter	Filtering criteria for affected objects	true	see Get Affected Objects - body - filter table

Get Affected Objects - body - filter

Name	Description	Required	Value
detectionName	Filter by specific detection names (required)	false	string []
detectionSrc	Filter by detection module source	false	string []
dn	Filter by Distinguished Name (DN) of objects	false	string []
domainName	Filter by Active Directory domain names (required)	false	string []
forestName	Filter by Active Directory forest names	false	string []
objectType	Filter by Active Directory object type	false	string []
runJobType	Filter by assessment job type	false	string []

Trigger Assessment

POST /web/api/v2.1/ranger-ad/trigger-assessment

Use the below Cloud API to trigger ADAssessment

Parameters

accountids	optional	List of account IDs separated by comma
siteids	optional	List of site IDs separated by comma

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Trigger Assessment - response - data table
errors	Errors	false	array

Trigger Assessment - response - data

Name	Description	Required	Value
message	Success message describing the completed operation	false	string
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
filter	Assessment trigger configuration	true	see Trigger Assessment - body - filter table

Trigger Assessment - body - filter

Name	Description	Required	Value
isFullScan	Whether to perform a full scan (true) or reassess specific exposures (false)	true	boolean
domainName	List of domain names to scan (used when isFullScan=true)	false	string []
exposureList	List of specific exposures to reassess (used when isFullScan=false)	false	see Trigger Assessment - body - exposureList table
scanSource	Source type for full scan (OnPrem-AD or Azure-AD)	false	enum

Trigger Assessment - body - exposureList

Name	Description	Required	Value
detectionName	Name of the detection to reassess	true	string
domainName	Domain name where the exposure exists	true	string

Set Skipped Exposures

POST /web/api/v2.1/ranger-ad/set-skipped-exposures

Use the below Cloud API to set the list of exposures to be skipped

Parameters

accountids	optional	List of account IDs separated by comma
siteids	optional	List of site IDs separated by comma

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set Skipped Exposures - response - data table
errors	Errors	false	array

Set Skipped Exposures - response - data

Name	Description	Required	Value
message	Success message describing the completed operation	false	string
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
filter	Filtering criteria for exposures to mark as skipped	true	see Set Skipped Exposures - body - filter table

Set Skipped Exposures - body - filter

Name	Description	Required	Value
detectionName	List of detection names to mark as skipped (required)	false	string []
domainName	List of domain names where exposures should be skipped (required)	false	string []
forestName	List of forest names to filter by	false	string []

Set Acknowledged Status

POST /web/api/v2.1/ranger-ad/set-ack-status

Use the below Cloud API to set acknowledgement status

Parameters

accountids	optional	List of account IDs separated by comma
siteids	optional	List of site IDs separated by comma

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set Acknowledged Status - response - data table
errors	Errors	false	array

Set Acknowledged Status - response - data

Name	Description	Required	Value
message	Success message describing the completed operation	false	string
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
filter	Filtering criteria for exposures to acknowledge	true	see Set Acknowledged Status - body - filter table

Set Acknowledged Status - body - filter

Name	Description	Required	Value
detectionName	List of detection names to acknowledge (required)	false	string []
domainName	List of domain names where exposures should be acknowledged (required)	false	string []
forestName	List of forest names to filter by	false	string []

Identity AD Service - Configuration

Delete AD configuration

POST /web/api/v2.1/identity/adservice/api/deleteAdConfiguration

Delete one or more AD configurations

Response Messages

200 - Successfully deleted AD configurations

401 - Unauthorized

403 - Forbidden

500 - Internal server error

Response Schema

Name	Description	Required	Value
data		false	

Body Schema

Name	Description	Required	Value
filter	Enter exactly one scope based on the user's scope level: use accountIds for account-scoped users, siteIds for site-scoped users, or groupIds for group-scoped users.	false	see Delete AD configuration - body - filter table
input		false	integer []

Delete AD configuration - body - filter

Name	Description	Required	Value
accountIds	Use when the user is at account scope.	false	string []
groupIds	Use when the user is at group scope.	false	string []
siteIds	Use when the user is at site scope.	false	string []

Add complete AD configuration

POST /web/api/v2.1/identity/adservice/api/addCompleteAdConfiguration

Add a new AD configuration together with its refresh schedule configuration

Response Messages

200 - Successfully added complete AD configuration

401 - Unauthorized

403 - Forbidden

500 - Internal server error

Response Schema

Name	Description	Required	Value
data		false	

Body Schema

Name	Description	Required	Value
filter	Enter exactly one scope based on the user's scope level: use accountIds for account-scoped users, siteIds for site-scoped users, or groupIds for group-scoped users.	false	see Add complete AD configuration - body - filter table
input		false	see Add complete AD configuration - body - input table

Add complete AD configuration - body - filter

Name	Description	Required	Value
accountIds	Use when the user is at account scope.	false	string []
groupIds	Use when the user is at group scope.	false	string []
siteIds	Use when the user is at site scope.	false	string []

Add complete AD configuration - body - input

Name	Description	Required	Value
adConfigurationInput		false	see Add complete AD configuration - body - adConfigurationInput table
adRefreshScheduleConfigurationInput		false	see Add complete AD configuration - body - adRefreshScheduleConfigurationInput table

Add complete AD configuration - body - adConfigurationInput

Name	Description	Required	Value
accessOverTrustInfo		false	see Add complete AD configuration - body - accessOverTrustInfo table
adConfigId		false	integer
adSync		false	boolean
allowedScopes		false	undefined []
assessOtherDomainsInForest		false	boolean
cloudLinkId		false	integer
createdAt		false	see Add complete AD configuration - body - createdAt table
domainControllerFqdn		false	string
domainName		false	string
enableThreatDetection		false	boolean
encryptionMethod		false	enum
featuresOpted		false	string []

isAllScopesAllowed		false	boolean
ldapReferral		false	boolean
password		false	string
update		false	boolean
userName		false	string
useWinRmOverSsl		false	boolean

Add complete AD configuration - body - accessOverTrustInfo

Name	Description	Required	Value
accessOverTrustEnabled		false	boolean
trustingDomainControllerFqdn		false	string
trustingDomainName		false	string

Add complete AD configuration - body - createdAt

Name	Description	Required	Value
scopeId		false	string
scopeLevel		false	enum
scopeName		false	string
scopePath		false	string

Add complete AD configuration - body - adRefreshScheduleConfigurationInput

Name	Description	Required	Value
ad_domain_name		false	string
day_of_month		false	integer
frequency		false	enum
hour		false	integer
minute		false	integer

time_zone		false	string
weekday		false	enum

Get timezones

GET /web/api/v2.1/identity/adservice/api/timezones

Retrieve list of available timezone pairs

Parameters

accountids	optional	List of account IDs separated by comma
siteids	optional	List of site IDs separated by comma

Response Messages

200 - Successfully retrieved timezones

401 - Unauthorized

403 - Forbidden

500 - Internal server error

Response Schema

Name	Description	Required	Value
data		false	

Get AD domains

GET /web/api/v2.1/identity/adservice/api/getAdDomains

Retrieve AD domain information

Parameters

accountids	optional	List of account IDs separated by comma
siteids	optional	List of site IDs separated by comma

Response Messages

200 - Successfully retrieved AD domains

401 - Unauthorized

403 - Forbidden

500 - Internal server error

Response Schema

Name	Description	Required	Value
data		false	

Get available features

GET /web/api/v2.1/identity/adservice/api/availableFeatures

Retrieve list of available AD features

Parameters

accountids	optional	List of account IDs separated by comma
siteids	optional	List of site IDs separated by comma

Response Messages

200 - Successfully retrieved available features

401 - Unauthorized

403 - Forbidden

500 - Internal server error

Response Schema

Name	Description	Required	Value
data		false	

Get AD configurations

GET /web/api/v2.1/identity/adservice/api/adConfigurations

Retrieve all AD configurations

Parameters

accountids	optional	List of account IDs separated by comma
siteids	optional	List of site IDs separated by comma

Response Messages

200 - Successfully retrieved AD configurations

401 - Unauthorized

403 - Forbidden

500 - Internal server error

Response Schema

Name	Description	Required	Value
data		false	

Get AD configuration features

GET /web/api/v2.1/identity/adservice/api/adConfigurationFeatures

Retrieve list of AD configuration features

Parameters

accountids	optional	List of account IDs separated by comma
siteids	optional	List of site IDs separated by comma

Response Messages

200 - Successfully retrieved AD configuration features

401 - Unauthorized

403 - Forbidden

500 - Internal server error

Response Schema

Name	Description	Required	Value
data		false	

Identity AD Service - Connector

Replace AD Connector

POST /web/api/v2.1/identity/adservice/api/replaceAdConnector

Replace the AD connector with a new agent

Parameters

agentuuid	required	Agent UUID
-----------	----------	------------

Response Messages

200 - Successfully replaced AD Connector

401 - Unauthorized

403 - Forbidden

500 - Internal server error

Response Schema

Name	Description	Required	Value
data		false	

Body Schema

Name	Description	Required	Value
filter	Enter exactly one scope based on the user's scope level: use accountlds for account-scoped users, sitelds for site-scoped users, or grouplds for group-scoped users.	false	see Replace AD Connector - body - filter table

Replace AD Connector - body - filter

Name	Description	Required	Value
accountIds	Use when the user is at account scope.	false	string []
groupIds	Use when the user is at group scope.	false	string []
siteIds	Use when the user is at site scope.	false	string []

Check if IDR is enabled on endpoint

POST /web/api/v2.1/identity/adservice/api/isIDREnabledOnEndpoint

Check if Incident Detection and Response is enabled on the specified endpoint

Response Messages

200 - Successfully checked IDR status

401 - Unauthorized

403 - Forbidden

500 - Internal server error

Response Schema

Name	Description	Required	Value
data		false	

Body Schema

Name	Description	Required	Value
filter	Enter exactly one scope based on the user's scope level: use accountIds for account-scoped users, siteIds for site-scoped users, or groupIds for group-scoped users.	false	see Check if IDR is enabled on endpoint - body - filter table
input		false	see Check if IDR is enabled on endpoint - body - input table

Check if IDR is enabled on endpoint - body - filter

Name	Description	Required	Value
accountIds	Use when the user is at account scope.	false	string []
groupIds	Use when the user is at group scope.	false	string []
siteIds	Use when the user is at site scope.	false	string []

Check if IDR is enabled on endpoint - body - input

Name	Description	Required	Value
agentUuid		false	string
requestId		false	string

Get Windows Unified Agents

GET /web/api/v2.1/identity/adservice/api/getWindowsUnifiedAgents

Retrieve Windows unified agents based on filter criteria

Parameters

filterinput	required	Filter input for agents
accountids	optional	List of account IDs separated by comma
requestid	optional	Request ID
siteids	optional	List of site IDs separated by comma

Response Messages

200 - Successfully retrieved Windows Unified Agents

401 - Unauthorized

403 - Forbidden

500 - Internal server error

Response Schema

Name	Description	Required	Value
data		false	

Get Cloudlink Configurations

GET /web/api/v2.1/identity/adservice/api/getCloudlinkConfigurations

Retrieve all Cloudlink configurations

Parameters

accountids	optional	List of account IDs separated by comma
siteids	optional	List of site IDs separated by comma

Response Messages

200 - Successfully retrieved Cloudlink Configurations

401 - Unauthorized

403 - Forbidden

500 - Internal server error

Response Schema

Name	Description	Required	Value
data		false	

Identity AD Service - Onboarding

Get onboarding status

GET /web/api/v2.1/identity/adservice/api/getOnboardingStatus

Retrieve the current onboarding status for the AD service

Parameters

accountids	optional	List of account IDs separated by comma
siteids	optional	List of site IDs separated by comma

Response Messages

200 - Successfully retrieved onboarding status

401 - Unauthorized

403 - Forbidden

500 - Internal server error

Response Schema

Name	Description	Required	Value
data		false	

Identity Policy Service

Get Policy List

GET /web/api/v2.1/identity/identity-policy-service/api/getPolicy

Fetches paginated policy list for a given scope and descendant scopes.

Parameters

limit	required	Number of items per page. Must be 1 or greater.
accountids	optional	Account-level scope. Provide exactly one of: accountIds, sitelds, or groupIds.
apply_on_windows_server	optional	Filter by Windows server deployment.
cursor	optional	Pagination cursor from previous response.
groupids	optional	Group-level scope. Provide exactly one of: accountIds, sitelds, or groupIds.
policytype	optional	Filter by policy type.
query	optional	Free-text search query.
scope	optional	Filter by scope type(s).
siteids	optional	Site-level scope. Provide exactly one of: accountIds, sitelds, or groupIds.
sortby	optional	Field to sort by.
sortorder	optional	Sort direction.
status	optional	Filter by policy status.

Response Messages

200 - Paginated policy list with cursor

401 - Unauthorized

500 - Internal server error

Get Inheritance Status

GET /web/api/v2.1/identity/identity-policy-service/api/getInheritanceStatus

Returns the current policy inheritance status for the authenticated scope

Parameters

accountIds	optional	Account-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.
groupIds	optional	Group-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.
siteIds	optional	Site-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.

Response Messages

200 - Inheritance status

401 - Unauthorized

500 - Internal server error

Response Schema

Name	Description	Required	Value
inheritanceStatus	Current inheritance state of the scope	false	enum
status	Response status of the retrieval	false	enum

Activate Policy

POST /web/api/v2.1/identity/identity-policy-service/api/activatingPolicy

Activates one or more policies for the current scope.

Response Messages

200 - Activation status

400 - Bad request - invalid policy IDs

401 - Unauthorized

500 - Internal server error

Response Schema

Name	Description	Required	Value
status	Result of the operation	false	enum

Body Schema

Name	Description	Required	Value
filter	Enter exactly one scope based on the user's scope level: use accountIds for account-scoped users, siteIds for site-scoped users, or groupIds for group-scoped users.	false	see Activate Policy - body - filter table
input	DTO for activating policies.	false	see Activate Policy - body - input table

Activate Policy - body - filter

Name	Description	Required	Value
accountIds	Use when the user is at account scope.	false	string []
groupIds	Use when the user is at group scope.	false	string []
siteIds	Use when the user is at site scope.	false	string []

Activate Policy - body - input

Name	Description	Required	Value
loggedInUser	Username or ID of the user performing the activation (used for audit trail)	false	string
override	If true, forces activation even when validation warnings exist (e.g. overrides conflict checks)	false	boolean
policyIds	List of policy UUIDs to activate	false	string []

Get Identity Policy Details

GET /web/api/v2.1/identity/identity-policy-service/api/getIdentityPolicyDetails

Returns full details for a specific policy by ID.

Parameters

policyid	required	UUID of the policy
accountids	optional	Account-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.
groupids	optional	Group-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.
siteids	optional	Site-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.

Response Messages

200 - Policy details

400 - Bad request - policyId missing or invalid

401 - Unauthorized

500 - Internal server error

Response Schema

Name	Description	Required	Value
createdBy		false	string
createdTimestamp		false	integer
deployedOnServer		false	boolean
description		false	string
engineConfigurations		false	undefined []
lastModifiedBy		false	string
lastModifiedTimestamp		false	integer
name		false	string
policyId		false	string
policyStatus		false	enum
policyType		false	enum
rootDomainList	Root AD domain list for the policy	false	see Get Identity Policy Details - response - rootDomainList table

Get Identity Policy Details - response - rootDomainList

Name	Description	Required	Value
domains	List of root AD domain names	false	string []

Delete Policies

POST /web/api/v2.1/identity/identity-policy-service/api/deletePolicy

Deletes one or more non-active policies belonging to the current scope.

Response Messages

200 - Deletion result

400 - Bad request - invalid policy IDs

401 - Unauthorized

500 - Internal server error

Body Schema

Name	Description	Required	Value
input		true	see Delete Policies - body - input table
filter	Enter exactly one scope based on the user's scope level: use accountIds for account-scoped users, sitelds for site-scoped users, or groupIds for group-scoped users.	false	see Delete Policies - body - filter table

Delete Policies - body - input

Name	Description	Required	Value
policyIds	List of policy UUIDs to delete	false	string []

Delete Policies - body - filter

Name	Description	Required	Value
accountIds	Use when the user is at account scope.	false	string []
groupIds	Use when the user is at group scope.	false	string []
siteIds	Use when the user is at site scope.	false	string []

Detach Policy Inheritance

POST /web/api/v2.1/identity/identity-policy-service/api/detachInheritance

Breaks the policy inheritance link for the current scope.

Response Messages

200 - Detach inheritance status

401 - Unauthorized

500 - Internal server error

Response Schema

Name	Description	Required	Value
status	Result of the operation	false	enum

Body Schema

Name	Description	Required	Value
input		true	see Detach Policy Inheritance - body - input table
filter	Enter exactly one scope based on the user's scope level: use accountIds for account-scoped users, siteIds for site-scoped users, or groupIds for group-scoped users.	false	see Detach Policy Inheritance - body - filter table

Detach Policy Inheritance - body - input

Name	Description	Required	Value
loggedInUser	Username or ID of the user performing the detach (audit trail)	false	string

Detach Policy Inheritance - body - filter

Name	Description	Required	Value
accountIds	Use when the user is at account scope.	false	string []
groupIds	Use when the user is at group scope.	false	string []
siteIds	Use when the user is at site scope.	false	string []

Revert Policy Inheritance

POST /web/api/v2.1/identity/identity-policy-service/api/revertInheritance

Reverts a previously detached policy inheritance for the current scope.

Response Messages

200 - Revert inheritance status

401 - Unauthorized

500 - Internal server error

Response Schema

Name	Description	Required	Value
status	Result of the operation	false	enum

Body Schema

Name	Description	Required	Value
filter	Enter exactly one scope based on the user's scope level: use accountIds for account-scoped users, siteIds for site-scoped users, or groupIds for group-scoped users.	false	see Revert Policy Inheritance - body - filter table

Revert Policy Inheritance - body - filter

Name	Description	Required	Value
accountIds	Use when the user is at account scope.	false	string []
groupIds	Use when the user is at group scope.	false	string []
siteIds	Use when the user is at site scope.	false	string []

Deactivate Policies

POST /web/api/v2.1/identity/identity-policy-service/api/deactivatingPolicy

Deactivates one or more active policies for the current scope.

Response Messages

200 - Deactivation status

400 - Bad request - invalid policy IDs

401 - Unauthorized

500 - Internal server error

Response Schema

Name	Description	Required	Value
status	Result of the operation	false	enum

Body Schema

Name	Description	Required	Value
input		true	see Deactivate Policies - body - input table
filter	Enter exactly one scope based on the user's scope level: use accountIds for account-scoped users, siteIds for site-scoped users, or groupIds for group-scoped users.	false	see Deactivate Policies - body - filter table

Deactivate Policies - body - input

Name	Description	Required	Value
policyIds	List of policy UUIDs to deactivate	false	string []

Deactivate Policies - body - filter

Name	Description	Required	Value
accountIds	Use when the user is at account scope.	false	string []
groupIds	Use when the user is at group scope.	false	string []
siteIds	Use when the user is at site scope.	false	string []

Get Policy Info for Agent

GET /web/api/v2.1/identity/identity-policy-service/api/policy-info

Returns the active DC and Conditional Access policy configuration for the scope of a given agent UUID.

Parameters

uuid	required	Agent UUID
accountIds	optional	Account-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.
groupIds	optional	Group-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.
siteIds	optional	Site-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.

Response Messages

200 - Policy config info

400 - Bad request - uuid missing

401 - Unauthorized

500 - Internal server error

Response Schema

Name	Description	Required	Value
conditionalAccess	Conditional access configuration string	false	string
connectorName	Name of the connector associated with the policy	false	string
conditionalAccessPolicyId	UUID of the active Conditional Access policy	false	string
conditionalAccessPolicyName	Name of the active Conditional Access policy	false	string
dcPolicyId	UUID of the active DC policy	false	string
dcPolicyName	Name of the active DC policy for the agent's scope	false	string
policyStatus	Status of the DC policy (e.g. ACTIVE, INACTIVE)	false	string

Create Policy

POST /web/api/v2.1/identity/identity-policy-service/api/createPolicy

Creates a new identity policy for the current scope.

Response Messages

200 - Created policy response

400 - Bad request - validation failed (name: 3-30 chars, description: 0-1000 chars)

401 - Unauthorized

500 - Internal server error

Response Schema

Name	Description	Required	Value
message	Human-readable result or error message	false	string
policyId	UUID of the affected policy	false	string
policyName	Name of the affected policy	false	string
policyType	Type of the policy	false	string
status	True if the operation succeeded, false otherwise	false	boolean

Body Schema

Name	Description	Required	Value
filter	Enter exactly one scope based on the user's scope level: use accountIds for account-scoped users, siteIds for site-scoped users, or groupIds for group-scoped users.	false	see Create Policy - body - filter table
input	Policy create/update input.	false	see Create Policy - body - input table

Create Policy - body - filter

Name	Description	Required	Value
accountIds	Use when the user is at account scope.	false	string []
groupIds	Use when the user is at group scope.	false	string []
siteIds	Use when the user is at site scope.	false	string []

Create Policy - body - input

Name	Description	Required	Value
createdBy	Creator username	false	string
createdTimestamp	Creation epoch timestamp in milliseconds	false	integer
deployedOnServer	Whether the policy is deployed on a server endpoint.	false	boolean
description	Policy description. Max 1000 characters.	false	string
ednInstanceId	EDN instance ID	false	string
engineConfigurationInput	List of engine configurations for the policy.	false	undefined []
lastModifiedBy	Last modifier username	false	string
lastModifiedTimestamp	Last modification epoch timestamp in milliseconds	false	integer
loggedInUser	Username or ID of the logged-in user.	false	string
mgmtId	Management console ID	false	string
name	Policy name. Min 3, max 30 characters.	false	string
policyId	Policy UUID. Required for update.	false	string
policyStatus	Policy status	false	enum
policyType	Type of policy.	false	enum
rootDomainList	Root AD domain list for the policy	false	see Create Policy - body - rootDomainList table

scopeId	Scope ID	false	string
scopeLevel	Scope level	false	enum
tenantId	Tenant ID	false	string

Create Policy - body - rootDomainList

Name	Description	Required	Value
domains	List of root AD domain names	false	string []

Update Policy

POST /web/api/v2.1/identity/identity-policy-service/api/updatePolicy

Updates an existing identity policy.

Response Messages

200 - Updated policy response

401 - Unauthorized

500 - Internal server error

Response Schema

Name	Description	Required	Value
message	Human-readable result or error message	false	string
policyId	UUID of the affected policy	false	string
policyName	Name of the affected policy	false	string
policyType	Type of the policy	false	string
status	True if the operation succeeded, false otherwise	false	boolean

Body Schema

Name	Description	Required	Value
filter	Enter exactly one scope based on the user's scope level: use accountIds for account-scoped users, siteIds for site-scoped users, or groupIds for group-scoped users.	false	see Update Policy - body - filter table
input	Policy create/update input.	false	see Update Policy - body - input table

Update Policy - body - filter

Name	Description	Required	Value
accountIds	Use when the user is at account scope.	false	string []
groupIds	Use when the user is at group scope.	false	string []
siteIds	Use when the user is at site scope.	false	string []

Update Policy - body - input

Name	Description	Required	Value
createdBy	Creator username	false	string
createdTimestamp	Creation epoch timestamp in milliseconds	false	integer
deployedOnServer	Whether the policy is deployed on a server endpoint.	false	boolean
description	Policy description. Max 1000 characters.	false	string
ednInstanceId	EDN instance ID	false	string
engineConfigurationInput	List of engine configurations for the policy.	false	undefined []
lastModifiedBy	Last modifier username	false	string
lastModifiedTimestamp	Last modification epoch timestamp in milliseconds	false	integer
loggedInUser	Username or ID of the logged-in user.	false	string
mgmtId	Management console ID	false	string
name	Policy name. Min 3, max 30 characters.	false	string
policyId	Policy UUID. Required for update.	false	string
policyStatus	Policy status	false	enum
policyType	Type of policy.	false	enum
rootDomainList	Root AD domain list for the policy	false	see Update Policy - body - rootDomainList table

scopeId	Scope ID	false	string
scopeLevel	Scope level	false	enum
tenantId	Tenant ID	false	string

Update Policy - body - rootDomainList

Name	Description	Required	Value
domains	List of root AD domain names	false	string []

Duplicate Policy

POST /web/api/v2.1/identity/identity-policy-service/api/duplicatePolicy

Creates a copy of an existing identity policy with a new name.

Response Messages

200 - Duplicated policy response

401 - Unauthorized

500 - Internal server error

Response Schema

Name	Description	Required	Value
message	Human-readable result or error message	false	string
policyId	UUID of the affected policy	false	string
policyName	Name of the affected policy	false	string
policyType	Type of the policy	false	string
status	True if the operation succeeded, false otherwise	false	boolean

Body Schema

Name	Description	Required	Value
filter	Enter exactly one scope based on the user's scope level: use accountIds for account-scoped users, siteIds for site-scoped users, or groupIds for group-scoped users.	false	see Duplicate Policy - body - filter table
input	Parameters for duplicating a policy	false	see Duplicate Policy - body - input table

Duplicate Policy - body - filter

Name	Description	Required	Value
accountIds	Use when the user is at account scope.	false	string []
groupIds	Use when the user is at group scope.	false	string []
siteIds	Use when the user is at site scope.	false	string []

Duplicate Policy - body - input

Name	Description	Required	Value
name	Name for the new duplicated policy	true	string
policyId	UUID of the policy to duplicate	true	string

Identity Policy Service - AD EP Data

Get Privileged Admins

GET /web/api/v2.1/identity/identity-policy-service/api/adPrivilegeAdmins

Returns the list of privileged admin AD objects for the given domains.

Parameters

domains	required	List of AD domain names
accountIds	optional	Account-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.
groupIds	optional	Group-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.
siteIds	optional	Site-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.

Response Messages

200 - List of privileged admin AD objects

401 - Unauthorized

500 - Internal server error

Response Schema

Name	Description	Required	Value
data		false	undefined []

Get Service Accounts

GET /web/api/v2.1/identity/identity-policy-service/api/adServiceAccounts

Returns the list of service account AD objects for the given domains.

Parameters

domains	required	List of AD domain names
accountids	optional	Account-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.
groupids	optional	Group-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.
siteids	optional	Site-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.

Response Messages

200 - List of service account AD objects

401 - Unauthorized

500 - Internal server error

Response Schema

Name	Description	Required	Value
data		false	undefined []

Get Domain Controllers

GET /web/api/v2.1/identity/identity-policy-service/api/adDomainControllers

Returns the list of domain controller objects for the given domains.

Parameters

domains	required	List of AD domain names
accountids	optional	Account-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.
groupids	optional	Group-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.
siteids	optional	Site-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.

Response Messages

200 - List of domain controller objects

401 - Unauthorized

500 - Internal server error

Response Schema

Name	Description	Required	Value
data		false	undefined []

Get Delegated Admins

GET /web/api/v2.1/identity/identity-policy-service/api/adDelegatedAdmins

Returns the list of delegated admin objects for the given domains.

Parameters

domains	required	List of AD domain names
accountids	optional	Account-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.
groupids	optional	Group-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.
siteids	optional	Site-level scope. Provide exactly one of: accountIds, siteIds, or groupIds.

Response Messages

200 - List of delegated admin objects

401 - Unauthorized

500 - Internal server error

Response Schema

Name	Description	Required	Value
data		false	undefined []

Inventory

Categories and counts

GET /web/api/v2.1/xdr/assets/categories

Get inventory categories and their asset counts

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Categories and counts - response - data table
errors	Errors	false	array

Categories and counts - response - data

Name	Description	Required	Value
account	Account	false	integer
container	Container	false	integer
device	Device	false	integer
identity	Identity	false	integer
inventory	Inventory	false	integer
server	Server	false	integer
storage	Storage	false	integer
workstation	Workstation	false	integer

Counts per subcategory for categories

GET /web/api/v2.1/xdr/assets/sub-categories

Get asset counts per subcategory for each category

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data		false	see Counts per subcategory for categories - response - data table
errors	Errors	false	array

Counts per subcategory for categories - response - data

Name	Description	Required	Value
account		false	see Counts per subcategory for categories - response - account table
aiMI		false	see Counts per subcategory for categories - response - aiMI table
applicationIntegration		false	see Counts per subcategory for categories - response - applicationIntegration table
cloudApplication		false	see Counts per subcategory for categories - response - cloudApplication table
code		false	see Counts per subcategory for categories - response - code table
container		false	see Counts per subcategory for categories - response - container table
dataAnalysis		false	see Counts per subcategory for categories - response - dataAnalysis table
dataStore		false	see Counts per subcategory for categories - response - dataStore table
developerTool		false	see Counts per subcategory for categories - response - developerTool table
device		false	see Counts per subcategory for categories - response - device table
function		false	see Counts per subcategory for categories - response - function table
governance		false	see Counts per subcategory for categories - response - governance table
identity		false	see Counts per subcategory for categories - response - identity table
inventory		false	see Counts per subcategory for categories - response - inventory table
network		false	see Counts per subcategory for categories - response - network table
secrets		false	see Counts per subcategory for categories - response - secrets table
server		false	see Counts per subcategory for categories - response - server table
storage		false	see Counts per subcategory for categories - response - storage table
workstation		false	see Counts per subcategory for categories - response - workstation table

Counts per subcategory for categories - response - account

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - aiMI

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - applicationIntegration

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - cloudApplication

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - code

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - container

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - dataAnalysis

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - dataStore

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - developerTool

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - device

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - function

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - governance

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - identity

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - inventory

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - network

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - secrets

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - server

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - storage

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Counts per subcategory for categories - response - workstation

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items

GET /web/api/v2.1/xdr/assets/asset-counts

Get inventory counts categories, subcategories and surfaces

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Get inventory counts for menu items - response - data table
errors	Errors	false	array

Get inventory counts for menu items - response - data

Name	Description	Required	Value
categories		false	see Get inventory counts for menu items - response - categories table
surfaces		false	see Get inventory counts for menu items - response - surfaces table

Get inventory counts for menu items - response - categories

Name	Description	Required	Value
account		false	see Get inventory counts for menu items - response - account table
aiMI		false	see Get inventory counts for menu items - response - aiMI table
applicationIntegration		false	see Get inventory counts for menu items - response - applicationIntegration table
cloudApplication		false	see Get inventory counts for menu items - response - cloudApplication table
code		false	see Get inventory counts for menu items - response - code table
container		false	see Get inventory counts for menu items - response - container table
dataAnalysis		false	see Get inventory counts for menu items - response - dataAnalysis table
dataStore		false	see Get inventory counts for menu items - response - dataStore table
developerTool		false	see Get inventory counts for menu items - response - developerTool table
device		false	see Get inventory counts for menu items - response - device table
function		false	see Get inventory counts for menu items - response - function table
governance		false	see Get inventory counts for menu items - response - governance table
identity		false	see Get inventory counts for menu items - response - identity table
inventory		false	see Get inventory counts for menu items - response - inventory table
network		false	see Get inventory counts for menu items - response - network table
secrets		false	see Get inventory counts for menu items - response - secrets table
server		false	see Get inventory counts for menu items - response - server table
storage		false	see Get inventory counts for menu items - response - storage table
workstation		false	see Get inventory counts for menu items - response - workstation table

Get inventory counts for menu items - response - account

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - aiMI

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - applicationIntegration

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - cloudApplication

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - code

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - container

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - dataAnalysis

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - dataStore

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - developerTool

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - device

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - function

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - governance

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - identity

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - inventory

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - network

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - secrets

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - server

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - storage

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - workstation

Name	Description	Required	Value
count	Count	false	integer
subcategories	Subcategories	false	undefined []

Get inventory counts for menu items - response - surfaces

Name	Description	Required	Value
cloud		false	see Get inventory counts for menu items - response - cloud table
endpoint		false	see Get inventory counts for menu items - response - endpoint table
identity		false	see Get inventory counts for menu items - response - identity table
network		false	see Get inventory counts for menu items - response - network table
networkDiscovery		false	see Get inventory counts for menu items - response - networkDiscovery table

Get inventory counts for menu items - response - cloud

Name	Description	Required	Value
count	Count	false	integer

Get inventory counts for menu items - response - endpoint

Name	Description	Required	Value
count	Count	false	integer

Get inventory counts for menu items - response - identity

Name	Description	Required	Value
count	Count	false	integer

Get inventory counts for menu items - response - network

Name	Description	Required	Value
count	Count	false	integer

Get inventory counts for menu items - response - networkDiscovery

Name	Description	Required	Value
count	Count	false	integer

Export Cloud Tags to CSV or JSON

GET /web/api/v2.1/xdr/assets/cloud-tags/export

Returns the tags for given id in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
id	optional	List of resource ids to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Assets

GET /web/api/v2.1/xdr/assets

Get assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
agentagentversion	optional	The agent version
agentantitamperingstatus	optional	The agent anti tampering status
agentconsoleconnectivity	optional	The agent console connectivity
agentidrconnectivity	optional	The agent idr connectivity
agentoperationalstate	optional	The agent operational state
agentpendingactions	optional	The agent pending actions
agentvssrollbackstatus	optional	The agent VSS rollback status

alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
category	optional	The category that each resource belongs to
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization

cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)

missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
osfamily	optional	The operating system family of the device
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists

tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets

POST API to get assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
agentAgentVersion	The agent version	false	string []
agentAntiTamperingStatus	The agent anti tampering status	false	string []
agentConsoleConnectivity	The agent console connectivity	false	boolean []
agentIdrConnectivity	The agent idr connectivity	false	boolean []
agentOperationalState	The agent operational state	false	string []
agentPendingActions	The agent pending actions	false	string []
agentVssRollbackStatus	The agent VSS rollback status	false	string []
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []
assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists	false	string []

	in - AWS Azure GCP Active Directory		
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
category	The category that each resource belongs to	false	string []
cloudProviderAccountId	The cloud provider account id	false	string []
cloudProviderAccountId__contains	The cloud provider account ID	false	string []
cloudProviderAccountId__nin	The cloud provider account id (not in)	false	string []
cloudProviderAccountName	The cloud provider account name	false	string []
cloudProviderAccountName__contains	The cloud provider account name	false	string []
cloudProviderAccountName__nin	The cloud provider account name (not in)	false	string []
cloudProviderOrganization__contains	The cloud provider organization	false	string []
cloudProviderOrganizationUnit__contains	The cloud provider organization unit	false	string []
cloudProviderProjectId__contains	The cloud provider project ID	false	string []
cloudProviderSubscriptionId__contains	The cloud provider subscription ID	false	string []
cloudResourceId__contains	The cloud resource ID	false	string []
cloudTagsKey	The cloud tags key	false	string []
cloudTagsKey__contains	Free-text filter by cloud tag key (supports multiple values)	false	string []
cloudTagsKey__nin	The cloud tags key (not in)	false	string []
cloudTagsKeyValue	The cloud tags key value	false	string []
cloudTagsKeyValue__contains	Free-text filter by cloud tag key value (supports multiple values)	false	string []
cloudTagsKeyValue__nin	The cloud tags key value (not in)	false	string []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count	false	string []

	would be returned for		
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
eppUnsupportedUnknown	The agent supported or unknown state	false	string []
groupIds	List of Group IDs to filter by	false	string []
id__contains	The ID	false	string []
id__in	The ID	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
limit	Limit number of returned items (1-1000)	false	integer
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []
name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
osFamily	The operating system family of the device	false	string []
region	The region	false	string []
region__contains	The geographical area where cloud resources are hosted	false	string []
region__nin	The region (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []

riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
sitelds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".	false	integer
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum
subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
agentagentversion	optional	The agent version
agentantitamperingstatus	optional	The agent anti tampering status
agentconsoleconnectivity	optional	The agent console connectivity
agentidrconnectivity	optional	The agent idr connectivity
agentoperationalstate	optional	The agent operational state
agentpendingactions	optional	The agent pending actions
agentvssrollbackstatus	optional	The agent VSS rollback status
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset

assetstatus__nin	optional	The status of the asset (not in)
category	optional	The category that each resource belongs to
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of

		the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
eppunsupportedunkn own	optional	The agent supported or unknown state
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
osfamily	optional	The operating system family of the device
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contain s	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset

n		
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Perform action

POST /web/api/v2.1/xdr/assets/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
agentagentversion	optional	The agent version
agentantitamperingstatus	optional	The agent anti tampering status
agentconsoleconnectivity	optional	The agent console connectivity
agentidrconnectivity	optional	The agent idr connectivity
agentoperationalstate	optional	The agent operational state
agentpendingactions	optional	The agent pending actions
agentvssrollbackstatus	optional	The agent VSS rollback status
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)

assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
category	optional	The category that each resource belongs to
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)

countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
eppunsupportedunkn own	optional	The agent supported or unknown state
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
osfamily	optional	The operating system family of the device
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contain s	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__betwee n	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)

surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Available actions

POST /web/api/v2.1/xdr/assets/available-actions/with-status

Get available actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
agentagentversion	optional	The agent version
agentantitamperingstatus	optional	The agent anti tampering status
agentconsoleconnectivity	optional	The agent console connectivity
agentidrconnectivity	optional	The agent idr connectivity
agentoperationalstate	optional	The agent operational state
agentpendingactions	optional	The agent pending actions
agentvssrollbackstatus	optional	The agent VSS rollback status
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)

assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
category	optional	The category that each resource belongs to
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value

cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
osfamily	optional	The operating system family of the device
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset

n		
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory AI ML

Assets

GET /web/api/v2.1/xdr/assets/ai-ml

Get assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)

cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for

csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".

skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/ai-ml

POST API to get Assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []
assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
cloudProviderAccountId	The cloud provider account id	false	string []

cloudProviderAccountId__contains	The cloud provider account ID	false	string []
cloudProviderAccountId__nin	The cloud provider account id (not in)	false	string []
cloudProviderAccountName	The cloud provider account name	false	string []
cloudProviderAccountName__contains	The cloud provider account name	false	string []
cloudProviderAccountName__nin	The cloud provider account name (not in)	false	string []
cloudProviderOrganization__contains	The cloud provider organization	false	string []
cloudProviderOrganizationUnit__contains	The cloud provider organization unit	false	string []
cloudProviderProjectId__contains	The cloud provider project ID	false	string []
cloudProviderSubscriptionId__contains	The cloud provider subscription ID	false	string []
cloudResourceId__contains	The cloud resource ID	false	string []
cloudTagsKey	The cloud tags key	false	string []
cloudTagsKey__contains	Free-text filter by cloud tag key (supports multiple values)	false	string []
cloudTagsKey__nin	The cloud tags key (not in)	false	string []
cloudTagsKeyValue	The cloud tags key value	false	string []
cloudTagsKeyValue__contains	Free-text filter by cloud tag key value (supports multiple values)	false	string []
cloudTagsKeyValue__nin	The cloud tags key value (not in)	false	string []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
groupIds	List of Group IDs to filter by	false	string []
id__contains	The ID	false	string []

id__in	The ID	false	string []
imageName__contains	Free-text filter by the image name	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
limit	Limit number of returned items (1-1000)	false	integer
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []
name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
region	The region	false	string []
region__contains	The geographical area where cloud resources are hosted	false	string []
region__nin	The region (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
sitelds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".	false	integer
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum

subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []

Perform action

POST /web/api/v2.1/xdr/assets/ai-ml/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)

alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID

ains		
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from	false	string []

	select_all		
--	------------	--	--

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/ai-ml/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid	optional	The cloud provider account ID

d__contains		
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.

devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.

sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Available actions

POST /web/api/v2.1/xdr/assets/ai-ml/available-actions/with-status

Get available actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)

alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganiza	optional	The cloud provider organization unit

tionunit__contains		
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)

region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory AI ML Filters

Filter counts

GET /web/api/v2.1/xdr/assets/ai-ml/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)

cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review

devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)

tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/ai-ml/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/ai-ml/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by

id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists

tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Account

Assets

GET /web/api/v2.1/xdr/assets/account

Get assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)

assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)

cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/account

POST API to get Assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []
assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
cloudProviderAccountId	The cloud provider account id	false	string []

cloudProviderAccountId__contains	The cloud provider account ID	false	string []
cloudProviderAccountId__nin	The cloud provider account id (not in)	false	string []
cloudProviderAccountName	The cloud provider account name	false	string []
cloudProviderAccountName__contains	The cloud provider account name	false	string []
cloudProviderAccountName__nin	The cloud provider account name (not in)	false	string []
cloudProviderOrganization__contains	The cloud provider organization	false	string []
cloudProviderOrganizationUnit__contains	The cloud provider organization unit	false	string []
cloudProviderProjectId__contains	The cloud provider project ID	false	string []
cloudProviderSubscriptionId__contains	The cloud provider subscription ID	false	string []
cloudResourceId__contains	The cloud resource ID	false	string []
cloudTagsKey	The cloud tags key	false	string []
cloudTagsKey__contains	Free-text filter by cloud tag key (supports multiple values)	false	string []
cloudTagsKey__nin	The cloud tags key (not in)	false	string []
cloudTagsKeyValue	The cloud tags key value	false	string []
cloudTagsKeyValue__contains	Free-text filter by cloud tag key value (supports multiple values)	false	string []
cloudTagsKeyValue__nin	The cloud tags key value (not in)	false	string []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
groupIds	List of Group IDs to filter by	false	string []
id__contains	The ID	false	string []

id__in	The ID	false	string []
imageName__contains	Free-text filter by the image name	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
limit	Limit number of returned items (1-1000)	false	integer
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []
name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
region	The region	false	string []
region__contains	The geographical area where cloud resources are hosted	false	string []
region__nin	The region (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
sitelds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".	false	integer
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum

subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []

Perform action

POST /web/api/v2.1/xdr/assets/account/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)

alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID

ains		
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from	false	string []

	select_all		
--	------------	--	--

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/account/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid	optional	The cloud provider account ID

d__contains		
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.

devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.

sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Available actions

POST /web/api/v2.1/xdr/assets/account/available-actions/with-status

Get available actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)

alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganiza	optional	The cloud provider organization unit

tionunit__contains		
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)

region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Account Filters

Filter counts

GET /web/api/v2.1/xdr/assets/account/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)

cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review

devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)

tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/account/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/account/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by

id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists

tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Application Integration

Assets

GET /web/api/v2.1/xdr/assets/application-integration

Get assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)

assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)

cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/application-integration

POST API to get Assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []
assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
cloudProviderAccountId	The cloud provider account id	false	string []

cloudProviderAccountId__contains	The cloud provider account ID	false	string []
cloudProviderAccountId__nin	The cloud provider account id (not in)	false	string []
cloudProviderAccountName	The cloud provider account name	false	string []
cloudProviderAccountName__contains	The cloud provider account name	false	string []
cloudProviderAccountName__nin	The cloud provider account name (not in)	false	string []
cloudProviderOrganization__contains	The cloud provider organization	false	string []
cloudProviderOrganizationUnit__contains	The cloud provider organization unit	false	string []
cloudProviderProjectId__contains	The cloud provider project ID	false	string []
cloudProviderSubscriptionId__contains	The cloud provider subscription ID	false	string []
cloudResourceId__contains	The cloud resource ID	false	string []
cloudTagsKey	The cloud tags key	false	string []
cloudTagsKey__contains	Free-text filter by cloud tag key (supports multiple values)	false	string []
cloudTagsKey__nin	The cloud tags key (not in)	false	string []
cloudTagsKeyValue	The cloud tags key value	false	string []
cloudTagsKeyValue__contains	Free-text filter by cloud tag key value (supports multiple values)	false	string []
cloudTagsKeyValue__nin	The cloud tags key value (not in)	false	string []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
groupIds	List of Group IDs to filter by	false	string []
id__contains	The ID	false	string []

id__in	The ID	false	string []
imageName__contains	Free-text filter by the image name	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
limit	Limit number of returned items (1-1000)	false	integer
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []
name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
region	The region	false	string []
region__contains	The geographical area where cloud resources are hosted	false	string []
region__nin	The region (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
sitelds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".	false	integer
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum

subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []

Perform action

POST /web/api/v2.1/xdr/assets/application-integration/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)

alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID

ains		
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from	false	string []

	select_all		
--	------------	--	--

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/application-integration/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid	optional	The cloud provider account ID

d__contains		
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.

devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.

sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Available actions

POST /web/api/v2.1/xdr/assets/application-integration/available-actions/with-status

Get available actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)

alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganiza	optional	The cloud provider organization unit

tionunit__contains		
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)

region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Application Integration Filters

Filter counts

GET /web/api/v2.1/xdr/assets/application-integration/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)

cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review

devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)

tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/application-integration/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/application-integration/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by

id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists

tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Cloud Application

Assets

GET /web/api/v2.1/xdr/assets/cloud-application

Get assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)

assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)

cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/cloud-application

POST API to get Assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []
assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
cloudProviderAccountId	The cloud provider account id	false	string []

cloudProviderAccountId__contains	The cloud provider account ID	false	string []
cloudProviderAccountId__nin	The cloud provider account id (not in)	false	string []
cloudProviderAccountName	The cloud provider account name	false	string []
cloudProviderAccountName__contains	The cloud provider account name	false	string []
cloudProviderAccountName__nin	The cloud provider account name (not in)	false	string []
cloudProviderOrganization__contains	The cloud provider organization	false	string []
cloudProviderOrganizationUnit__contains	The cloud provider organization unit	false	string []
cloudProviderProjectId__contains	The cloud provider project ID	false	string []
cloudProviderSubscriptionId__contains	The cloud provider subscription ID	false	string []
cloudResourceId__contains	The cloud resource ID	false	string []
cloudTagsKey	The cloud tags key	false	string []
cloudTagsKey__contains	Free-text filter by cloud tag key (supports multiple values)	false	string []
cloudTagsKey__nin	The cloud tags key (not in)	false	string []
cloudTagsKeyValue	The cloud tags key value	false	string []
cloudTagsKeyValue__contains	Free-text filter by cloud tag key value (supports multiple values)	false	string []
cloudTagsKeyValue__nin	The cloud tags key value (not in)	false	string []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
groupIds	List of Group IDs to filter by	false	string []
id__contains	The ID	false	string []

id__in	The ID	false	string []
imageName__contains	Free-text filter by the image name	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
limit	Limit number of returned items (1-1000)	false	integer
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []
name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
region	The region	false	string []
region__contains	The geographical area where cloud resources are hosted	false	string []
region__nin	The region (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
sitelds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".	false	integer
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum

subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []

Perform action

POST /web/api/v2.1/xdr/assets/cloud-application/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)

alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID

ains		
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from	false	string []

	select_all		
--	------------	--	--

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/cloud-application/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid	optional	The cloud provider account ID

d__contains		
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.

devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.

sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Available actions

POST /web/api/v2.1/xdr/assets/cloud-application/available-actions/with-status

Get available actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)

alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganiza	optional	The cloud provider organization unit

tionunit__contains		
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)

region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Cloud Application Filters

Filter counts

GET /web/api/v2.1/xdr/assets/cloud-application/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)

cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review

devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)

tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/cloud-application/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/cloud-application/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by

id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists

tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Cloud Surface

Assets

GET /web/api/v2.1/xdr/assets/surface/cloud

Get Cloud assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email

assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contain	optional	Free-text filter by cloud tag key (supports multiple values)

s		
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name

infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isrogues	optional	Whether the instance is a rogue or not
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8sdeploymentstrategy__contains	optional	Deployment Strategy
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8spolicytype__contains	optional	Policy Type

k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8sservicename__contains	optional	Service Name
k8sservicetype__contains	optional	Service Type
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8supdatestrategy__contains	optional	Update Strategy
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
limit	optional	Limit number of returned items (1-1000)
macaddresses__contains	optional	The MAC addresses
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networksecuritygroups__contains	optional	The network security group
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)

osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
state	optional	The state of the instance

state__contains	optional	The state
state__nin	optional	The state of the instance (not in)
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus__contains	optional	The threat detection status
threatdetectionstatus__nin	optional	Threat Detection Status (not in)
virtualnetworkid__contains	optional	The virtual network ID

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/surface/cloud/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__ni	optional	Asset Contact Email (not in)

n		
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)

cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset

infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isrogues	optional	Whether the instance is a rogue or not
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8sdeploymentstrategy__contains	optional	Deployment Strategy
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8spolicytype__contains	optional	Policy Type
k8sresourceid	optional	The Kubernetes Resource ID

k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8sservicename__contains	optional	Service Name
k8sservicetype__contains	optional	Service Type
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8supdatestrategy__contains	optional	Update Strategy
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
limit	optional	Limit number of returned items (1-1000)
macaddresses__contains	optional	The MAC addresses
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networksecuritygroups__contains	optional	The network security group
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device

osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
state	optional	The state of the instance
state__contains	optional	The state

state__nin	optional	The state of the instance (not in)
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus__contains	optional	The threat detection status
threatdetectionstatus__nin	optional	Threat Detection Status (not in)
virtualnetworkid__contains	optional	The virtual network ID

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Perform action

POST /web/api/v2.1/xdr/assets/surface/cloud/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review

devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isrogues	optional	Whether the instance is a rogue or not
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)

k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8sdeploymentstrategy__contains	optional	Deployment Strategy
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8spolicytype__contains	optional	Policy Type
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8sservicename__contains	optional	Service Name
k8sservicetype__contains	optional	Service Type
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8supdatestrategy__contains	optional	Update Strategy
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
macaddresses__contains	optional	The MAC addresses

ns		
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networksecuritygroups__contains	optional	The network security group
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset

riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by
state	optional	The state of the instance
state__contains	optional	The state
state__nin	optional	The state of the instance (not in)
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus__contains	optional	The threat detection status
threatdetectionstatus__nin	optional	Threat Detection Status (not in)

_nin		
virtualnetworkid__contains	optional	The virtual network ID

Response Messages

- 200 - Success
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Available actions

POST /web/api/v2.1/xdr/assets/surface/cloud/available-actions/with-status

Get available actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review

devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isrogues	optional	Whether the instance is a rogue or not
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)

k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8sdeploymentstrategy__contains	optional	Deployment Strategy
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8spolicytype__contains	optional	Policy Type
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8sservicename__contains	optional	Service Name
k8sservicetype__contains	optional	Service Type
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8supdatestrategy__contains	optional	Update Strategy
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
macaddresses__contains	optional	The MAC addresses

ns		
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networksecuritygroups__contains	optional	The network security group
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset

riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by
state	optional	The state of the instance
state__contains	optional	The state
state__nin	optional	The state of the instance (not in)
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus__contains	optional	The threat detection status
threatdetectionstatus__	optional	Threat Detection Status (not in)

_nin		
virtualnetworkid__contains	optional	The virtual network ID

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Cloud Surface Filters

Filter counts

GET /web/api/v2.1/xdr/assets/surface/cloud/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)

assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
corecount	optional	The number of cores

corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isrogues	optional	Whether the instance is a rogue or not
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunified	optional	Free-text filter by Kubernetes Annotations key value (supports

keyvalue__contains		multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8sdeploymentstrategy__contains	optional	Deployment Strategy
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8spolicytype__contains	optional	Policy Type
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8sservicename__contains	optional	Service Name
k8sservicetype__contains	optional	Service Type
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)

k8supdatestrategy__contains	optional	Update Strategy
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
macaddresses__contains	optional	The MAC addresses
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networksecuritygroups__contains	optional	The network security group
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)

resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by
state	optional	The state of the instance
state__contains	optional	The state
state__nin	optional	The state of the instance (not in)
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
threatdetectionpolicys	optional	Threat Detection Policy

tatus		
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus_ _contains	optional	The threat detection status
threatdetectionstatus_ _nin	optional	Threat Detection Status (not in)
virtualnetworkid__con tains	optional	The virtual network ID

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/surface/cloud/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/surface/cloud/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset

assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)

countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isrogues	optional	Whether the instance is a rogue or not
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)

k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8sdeploymentstrategy__contains	optional	Deployment Strategy
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8spolicytype__contains	optional	Policy Type
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8sservicename__contains	optional	Service Name
k8sservicetype__contains	optional	Service Type
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8supdatestrategy__contains	optional	Update Strategy

k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
limit	optional	Limit number of returned items
macaddresses__contains	optional	The MAC addresses
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networksecuritygroups__contains	optional	The network security group
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type

resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by
state	optional	The state of the instance
state__contains	optional	The state
state__nin	optional	The state of the instance (not in)
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
threatdetectionpolicystatus	optional	Threat Detection Policy

threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus_ _contains	optional	The threat detection status
threatdetectionstatus_ _nin	optional	Threat Detection Status (not in)
virtualnetworkid__con tains	optional	The virtual network ID

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Container

Assets

GET /web/api/v2.1/xdr/assets/container

Get assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine

agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)
agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type
agentdiskmetricsvolumetype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)

agentidrconnectivity	optional	The agent ldr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID

agentsubscribeondt__between	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionstatus	optional	The agent VSS protection status
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffareafreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__ni	optional	Asset Contact Email (not in)

n		
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)

cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups

identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups
imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID

k8sdeploymentstrategy	optional	Deployment Strategy
k8sdeploymentstrategy__contains	optional	Deployment Strategy
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8spolicytype	optional	Policy Type
k8spolicytype__contains	optional	Policy Type
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8sservicename	optional	Service Name
k8sservicename__contains	optional	Service Name
k8sservicetype	optional	Service Type
k8sservicetype__contains	optional	Service Type
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8supdatestrategy	optional	Update Strategy
k8supdatestrategy__contains	optional	Update Strategy

contains		
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
lastactivedt__between	optional	The last active date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
limit	optional	Limit number of returned items (1-1000)
macaddresses__contains	optional	The MAC addresses
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networksecuritygroups__contains	optional	The network security group
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)

region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists

tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
virtualnetworkid__contains	optional	The virtual network ID

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/container

POST API to get Assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
adsEnabled	ADS Enabled	false	boolean []
agentAgentVersion	The agent version	false	string []
agentAgentVersion__contains	The agent version	false	string []
agentAgentVersion__nin	The agent version (not in)	false	string []
agentAntiTamperingStatus	The agent anti tampering status	false	string []
agentAntiTamperingStatus__nin	The agent anti tampering status (not in)	false	string []
agentConfigurableNetworkQuarantine	Whether the agent can configure network quarantine	false	boolean []
agentConfigurableNetworkQuarantine__nin	Whether the agent can configure network quarantine (not in)	false	boolean []
agentConsoleConnectivity	The agent console connectivity	false	boolean []
agentConsoleMigrationStatus	The agent console migration status	false	string []
agentConsoleMigrationStatus__nin	The agent console migration status (not in)	false	string []
agentCustomerIdIdentifier__contains	The customer identifier	false	string []
agentDecommissioned	Whether the agent is decommissioned	false	boolean []
agentDiskEncryption	The agent disk encryption	false	boolean []
agentDiskMetricsFreePercentage__between	The agent free disk percentage on any of the disks	false	string
agentDiskMetricsFreePercentage__gte	The agent free disk percentage on any of the disks	false	number

agentDiskMetricsFreePercentage__lte	The agent free disk percentage on any of the disks	false	number
agentDiskMetricsVolumeType	The agent disk metrics volume type	false	string []
agentDiskMetricsVolumeType__nin	The agent disk metrics volume type (not in)	false	string []
agentDvConnectivity	The connection status between the agent and the SDL service	false	string []
agentDvConnectivity__nin	The connection status between the agent and the SDL service (not in)	false	string []
agentDvConnectivityLastUpdatedDt__between	The SDL connectivity last active	false	string
agentFullDiskScanDt__between	The agent full disk scan date	false	string
agentHasLocalConfig	Whether the agent has local configuration	false	boolean []
agentHealthStatus	The agent health status	false	string []
agentHealthStatus__nin	The agent health status (not in)	false	string []
agentIldrConnectivity	The agent Ildr connectivity	false	boolean []
agentInstallerType	The agent installer type	false	string []
agentInstallerType__nin	The agent installer type (not in)	false	string []
agentLastLoggedInUser__contains	The last logged in user	false	string []
agentLocation	The agent location	false	string []
agentLocation__nin	The agent location (not in)	false	string []
agentLocationAwareness__contains	The location awareness	false	string []
agentMissingPermissions	The agent missing permissions	false	string []
agentMissingPermissions__nin	The agent missing permissions (not in)	false	string []
agentNetworkStatus	The agent network status	false	string []
agentNetworkStatus__nin	The agent network status (not in)	false	string []
agentOperationalState	The agent operational state	false	string []
agentOperationalState__nin	The agent operational state (not in)	false	string []
agentPendingActions	The agent pending actions	false	string []
agentPendingActions__nin	The agent pending actions (not in)	false	string []
agentPendingUninstall	Whether the agent is pending uninstall	false	boolean []
agentPendingUpgrade	Whether the agent is pending upgrade	false	boolean []

agentRangerStatus	The agent network scanner status	false	string []
agentRangerStatus__nin	The agent network scanner status (not in)	false	string []
agentRangerVersion	The agent network scanner version	false	string []
agentRangerVersion__nin	The agent network scanner version (not in)	false	string []
agentS1AgentLiveUpdatesVersion__contains	Live update ID	false	string []
agentSubscribeOnDt__between	The agent subscribe time	false	string
agentUninstalled	Whether the agent is uninstalled	false	boolean []
agentUuid	Match by the agent UUID	false	string []
agentUuid__contains	The UUID	false	string []
agentVssLastSnapshotDt__between	The agent VSS last snapshot date	false	string
agentVssProtectionStatus	The agent VSS protection status	false	string []
agentVssProtectionStatus__nin	The agent VSS protection status (not in)	false	string []
agentVssRollbackStatus	The agent VSS rollback status	false	string []
agentVssRollbackStatus__nin	The agent VSS rollback status (not in)	false	string []
agentVssServiceStatus	The agent VSS service status	false	string []
agentVssServiceStatus__nin	The agent VSS service status (not in)	false	string []
agentVssVolumesDiffAreaFreePercentage__between	The agent free VSS volume percentage on any of the volumes	false	string
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
applicationName	The name of the application installed on a workstation or a server	false	string []
architecture	The architecture of the device	false	string []
architecture__nin	The architecture of the device (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []

assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
cloudProviderAccountId	The cloud provider account id	false	string []
cloudProviderAccountId__contains	The cloud provider account ID	false	string []
cloudProviderAccountId__nin	The cloud provider account id (not in)	false	string []
cloudProviderAccountName	The cloud provider account name	false	string []
cloudProviderAccountName__contains	The cloud provider account name	false	string []
cloudProviderAccountName__nin	The cloud provider account name (not in)	false	string []
cloudProviderOrganization__contains	The cloud provider organization	false	string []
cloudProviderOrganizationUnit__contains	The cloud provider organization unit	false	string []
cloudProviderProjectId__contains	The cloud provider project ID	false	string []
cloudProviderSubscriptionId__contains	The cloud provider subscription ID	false	string []
cloudResourceId__contains	The cloud resource ID	false	string []
cloudTagsKey	The cloud tags key	false	string []
cloudTagsKey__contains	Free-text filter by cloud tag key (supports multiple values)	false	string []
cloudTagsKey__nin	The cloud tags key (not in)	false	string []
cloudTagsKeyValue	The cloud tags key value	false	string []
cloudTagsKeyValue__contains	Free-text filter by cloud tag key value (supports multiple values)	false	string []
cloudTagsKeyValue__nin	The cloud tags key value (not in)	false	string []

coreCount	The number of cores	false	integer []
coreCount__nin	The number of cores (not in)	false	integer []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
cpu__contains	The CPU	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
domain	The domain of the device	false	string []
domain__contains	The domain	false	string []
domain__nin	The domain of the device (not in)	false	string []
firstSeenDt__between	The first seen date	false	string
gatewayIps__contains	The gateway IPs	false	string []
gatewayMacs__contains	The gateway MACs	false	string []
groupIds	List of Group IDs to filter by	false	string []
hostnames__contains	The hostnames	false	string []
id__contains	The ID	false	string []
id__in	The ID	false	string []
identityAd__contains	Any AD string	false	string []
identityAdMachine__contains	AD machine or its groups	false	string []
identityAdMachineDistinguishedName__contains	AD machine DN	false	string []
identityAdMachineMembership__contains	AD machine groups	false	string []
identityAdUser__contains	AD user or their groups	false	string []
identityAdUserDistinguishedName__contains	AD user DN	false	string []
identityAdUserMembership__contains	AD user groups	false	string []

imageId__contains	The image ID	false	string []
imageName__contains	Free-text filter by the image name	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
instanceId__contains	The instance ID	false	string []
instanceRole__contains	The instance role	false	string []
instanceType__contains	The instance type	false	string []
internalIps__contains	The internal IPs	false	string []
ipAddress__contains	The IP addresses	false	string []
isAdConnector	Is AD Connector	false	boolean []
isDcServer	Is DC Server	false	boolean []
k8sAnnotationsUnifiedKey__contains	Free-text filter by Kubernetes Annotations key (supports multiple values)	false	string []
k8sAnnotationsUnifiedKeyValue__contains	Free-text filter by Kubernetes Annotations key value (supports multiple values)	false	string []
k8sCluster	The Kubernetes Cluster	false	string []
k8sCluster__contains	The Kubernetes cluster	false	string []
k8sCluster__nin	The Kubernetes Cluster (not in)	false	string []
k8sClusterId	The Kubernetes Cluster ID	false	string []
k8sClusterId__contains	Kubernetes Cluster ID	false	string []
k8sDeploymentStrategy	Deployment Strategy	false	string []
k8sDeploymentStrategy__contains	Deployment Strategy	false	string []
k8sLabelsUnifiedKey__contains	Free-text filter by Kubernetes Labels key (supports multiple values)	false	string []
k8sLabelsUnifiedKeyValue__contains	Free-text filter by Kubernetes Labels key value (supports multiple values)	false	string []
k8sNamespace	The Kubernetes Namespace Name	false	string []
k8sNamespace__contains	Namespace Name	false	string []
k8sNode	The Kubernetes Node	false	string []
k8sNode__contains	The Kubernetes node	false	string []
k8sNode__nin	The Kubernetes Node (not in)	false	string []
k8sPolicyType	Policy Type	false	see Assets using POST - body - k8sPolicyType table

k8sPolicyType__contains	Policy Type	false	string []
k8sResourceId	The Kubernetes Resource ID	false	string []
k8sResourceId__contains	Kubernetes Resource ID	false	string []
k8sRunningOnNodes	Running on Nodes	false	string []
k8sRunningOnNodes__contains	Running on nodes	false	see Assets using POST - body - k8sRunningOnNodes__contains table
k8sServiceName	Service Name	false	string []
k8sServiceName__contains	Service Name	false	string []
k8sServiceType	Service Type	false	string []
k8sServiceType__contains	Service Type	false	string []
k8sType	The Kubernetes Type	false	string []
k8sType__nin	The Kubernetes Type (not in)	false	string []
k8sUpdateStrategy	Update Strategy	false	string []
k8sUpdateStrategy__contains	Update Strategy	false	string []
k8sVersion	The Kubernetes Version	false	string []
k8sVersion__nin	The Kubernetes Version (not in)	false	string []
lastActiveDt__between	The last active date	false	string
legacy_identity_policy_name__contains	The legacy identity policy name	false	string []
legacyIdentityPolicyName	Legacy Identity Policy Name	false	string []
limit	Limit number of returned items (1-1000)	false	integer
macAddresses__contains	The MAC addresses	false	string []
memoryReadable	The memory of the device in human readable format	false	string []
memoryReadable__nin	The memory of the device in human readable format (not in)	false	string []
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []
name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
networkSecurityGroups__contains	The network security group	false	string []
os	The operating system of the device	false	string []

os__nin	The operating system of the device (not in)	false	string []
osFamily	The operating system family of the device	false	string []
osFamily__nin	The operating system family of the device (not in)	false	string []
osNameVersion	The operating system name and version of the device	false	string []
osNameVersion__contains	The OS names and versions	false	string []
osNameVersion__nin	The operating system name and version of the device (not in)	false	string []
osVersion	The operating system version of the device	false	string []
osVersion__contains	The OS versions	false	string []
osVersion__nin	The operating system version of the device (not in)	false	string []
region	The region	false	string []
region__contains	The geographical area where cloud resources are hosted	false	string []
region__nin	The region (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
serialNumber	The serial number	false	string []
serialNumber__contains	The serial number	false	string []
serialNumber__nin	The serial number (not in)	false	string []
sitelds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000).	false	integer

	To iterate over more than 1000 items, use "cursor".		
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum
subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
subnetId__contains	The subnet ID	false	string []
subnets__contains	The subnets	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []
virtualNetworkId__contains	The virtual network ID	false	string []

Assets using POST - body - k8sPolicyType

Name	Description	Required	Value
		false	string []

Assets using POST - body - k8sRunningOnNodes__contains

Name	Description	Required	Value
		false	string []

Perform action

POST /web/api/v2.1/xdr/assets/container/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigration	optional	The agent console migration status (not in)

status__nin		
agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type
agentdiskmetricsvolumetype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent Idr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user

agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentsubscribeondbetween	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshot	optional	The agent VSS last snapshot date

dt__between		
agentvssprotectionstatus	optional	The agent VSS protection status
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffareafreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP

n		Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)

corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups

imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8sdeploymentstrategy	optional	Deployment Strategy
k8sdeploymentstrategy__contains	optional	Deployment Strategy
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name

k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8spolicytype	optional	Policy Type
k8spolicytype__contains	optional	Policy Type
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8sservicename	optional	Service Name
k8sservicename__contains	optional	Service Name
k8sservicetype	optional	Service Type
k8sservicetype__contains	optional	Service Type
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8supdatestrategy	optional	Update Strategy
k8supdatestrategy__contains	optional	Update Strategy
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
lastactivedt__between	optional	The last active date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
macaddresses__contains	optional	The MAC addresses

memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networksecuritygroups__contains	optional	The network security group
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset

serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
virtualnetworkid__contains	optional	The virtual network ID

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
------	-------------	----------	-------

actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/container/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)
agentcustomeridentifier__contains	optional	The customer identifier

agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfree percentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfree percentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfree percentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolume type	optional	The agent disk metrics volume type
agentdiskmetricsvolume type__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylast updateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent Idr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness

agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentsubscribeondbetween	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionstatus	optional	The agent VSS protection status
agentvssprotectionstatus	optional	The agent VSS protection status (not in)

tus__nin		
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffareafreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id

d		
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.

countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups

imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8sdeploymentstrategy	optional	Deployment Strategy
k8sdeploymentstrategy__contains	optional	Deployment Strategy
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name

k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8spolicytype	optional	Policy Type
k8spolicytype__contains	optional	Policy Type
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8sservicename	optional	Service Name
k8sservicename__contains	optional	Service Name
k8sservicetype	optional	Service Type
k8sservicetype__contains	optional	Service Type
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8supdatestrategy	optional	Update Strategy
k8supdatestrategy__contains	optional	Update Strategy
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
lastactivedt__between	optional	The last active date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
limit	optional	Limit number of returned items (1-1000)
macaddresses__contains	optional	The MAC addresses

ns		
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networksecuritygroups__contains	optional	The network security group
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset

n		
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
virtualnetworkid__contains	optional	The virtual network ID

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Available actions

POST /web/api/v2.1/xdr/assets/container/available-actions/with-status

Get available actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigration	optional	The agent console migration status (not in)

status__nin		
agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type
agentdiskmetricsvolumetype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent Idr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user

agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentsubscribeondbetween	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshot	optional	The agent VSS last snapshot date

dt__between		
agentvssprotectionstatus	optional	The agent VSS protection status
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffareafreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP

n		Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)

corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups

imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcservers	optional	Is DC Server
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8sdeploymentstrategy	optional	Deployment Strategy
k8sdeploymentstrategy__contains	optional	Deployment Strategy
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name

k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8spolicytype	optional	Policy Type
k8spolicytype__contains	optional	Policy Type
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8sservicename	optional	Service Name
k8sservicename__contains	optional	Service Name
k8sservicetype	optional	Service Type
k8sservicetype__contains	optional	Service Type
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8supdatestrategy	optional	Update Strategy
k8supdatestrategy__contains	optional	Update Strategy
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
lastactivedt__between	optional	The last active date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
macaddresses__contains	optional	The MAC addresses

memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networksecuritygroups__contains	optional	The network security group
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset

serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
virtualnetworkid__contains	optional	The virtual network ID

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Container Filters

Filter counts

GET /web/api/v2.1/xdr/assets/container/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)

agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type
agentdiskmetricsvolumetype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent Idr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)

agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentssubscribeondt__between	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionsta	optional	The agent VSS protection status

tus		
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdifferfreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset

assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)

countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups
imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name

infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8sdeploymentstrategy	optional	Deployment Strategy
k8sdeploymentstrategy__contains	optional	Deployment Strategy
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node

k8snode__nin	optional	The Kubernetes Node (not in)
k8spolicytype	optional	Policy Type
k8spolicytype__contains	optional	Policy Type
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8sservicename	optional	Service Name
k8sservicename__contains	optional	Service Name
k8sservicetype	optional	Service Type
k8sservicetype__contains	optional	Service Type
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8supdatestrategy	optional	Update Strategy
k8supdatestrategy__contains	optional	Update Strategy
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
lastactivedt__between	optional	The last active date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
macaddresses__contains	optional	The MAC addresses
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)

missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networksecuritygroups__contains	optional	The network security group
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number

s		
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
virtualnetworkid__contains	optional	The virtual network ID

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []

errors	Errors	false	array
--------	--------	-------	-------

Free text filters

GET /web/api/v2.1/xdr/assets/container/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/container/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)
agentcustomeridentifi	optional	The customer identifier

er__contains		
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfree percentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfree percentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfree percentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolume type	optional	The agent disk metrics volume type
agentdiskmetricsvolume type__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylast updateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent ldr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)

agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentssubscribeondbetween	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionstatus	optional	The agent VSS protection status

tus		
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdifferfreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset

assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)

countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups
imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name

infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8sdeploymentstrategy	optional	Deployment Strategy
k8sdeploymentstrategy__contains	optional	Deployment Strategy
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node

k8snode__nin	optional	The Kubernetes Node (not in)
k8spolicytype	optional	Policy Type
k8spolicytype__contains	optional	Policy Type
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8sservicename	optional	Service Name
k8sservicename__contains	optional	Service Name
k8sservicetype	optional	Service Type
k8sservicetype__contains	optional	Service Type
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8supdatestrategy	optional	Update Strategy
k8supdatestrategy__contains	optional	Update Strategy
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
lastactivedt__between	optional	The last active date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
limit	optional	Limit number of returned items
macaddresses__contains	optional	The MAC addresses
memoryreadable	optional	The memory of the device in human readable format

memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networksecuritygroups__contains	optional	The network security group
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number

serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
virtualnetworkid__contains	optional	The virtual network ID

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table

errors	Errors	false	array
--------	--------	-------	-------

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Data Analysis

Assets

GET /web/api/v2.1/xdr/assets/data-analysis

Get assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)

assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)

cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/data-analysis

POST API to get Assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []
assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
cloudProviderAccountId	The cloud provider account id	false	string []

cloudProviderAccountId__contains	The cloud provider account ID	false	string []
cloudProviderAccountId__nin	The cloud provider account id (not in)	false	string []
cloudProviderAccountName	The cloud provider account name	false	string []
cloudProviderAccountName__contains	The cloud provider account name	false	string []
cloudProviderAccountName__nin	The cloud provider account name (not in)	false	string []
cloudProviderOrganization__contains	The cloud provider organization	false	string []
cloudProviderOrganizationUnit__contains	The cloud provider organization unit	false	string []
cloudProviderProjectId__contains	The cloud provider project ID	false	string []
cloudProviderSubscriptionId__contains	The cloud provider subscription ID	false	string []
cloudResourceId__contains	The cloud resource ID	false	string []
cloudTagsKey	The cloud tags key	false	string []
cloudTagsKey__contains	Free-text filter by cloud tag key (supports multiple values)	false	string []
cloudTagsKey__nin	The cloud tags key (not in)	false	string []
cloudTagsKeyValue	The cloud tags key value	false	string []
cloudTagsKeyValue__contains	Free-text filter by cloud tag key value (supports multiple values)	false	string []
cloudTagsKeyValue__nin	The cloud tags key value (not in)	false	string []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
groupIds	List of Group IDs to filter by	false	string []
id__contains	The ID	false	string []

id__in	The ID	false	string []
imageName__contains	Free-text filter by the image name	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
limit	Limit number of returned items (1-1000)	false	integer
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []
name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
region	The region	false	string []
region__contains	The geographical area where cloud resources are hosted	false	string []
region__nin	The region (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
sitelds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".	false	integer
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum

subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []

Perform action

POST /web/api/v2.1/xdr/assets/data-analysis/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)

alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID

ains		
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from	false	string []

	select_all		
--	------------	--	--

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/data-analysis/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid	optional	The cloud provider account ID

d__contains		
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.

devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.

sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Available actions

POST /web/api/v2.1/xdr/assets/data-analysis/available-actions/with-status

Get available actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)

alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganiza	optional	The cloud provider organization unit

tionunit__contains		
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)

region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Data Analysis Filters

Filter counts

GET /web/api/v2.1/xdr/assets/data-analysis/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)

cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review

devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)

tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/data-analysis/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/data-analysis/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by

id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists

tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Data Store

Assets

GET /web/api/v2.1/xdr/assets/data-store

Get assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)

assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)

cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__notin	optional	The cloud tags key value (not in)
connectivitystatus	optional	Connectivity
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
data_classification_scan_status__contains	optional	Data classification scan status
data_classification_status__contains	optional	Data classification status
data_types__contains	optional	Data types contains
dataclassificationpolicystatus	optional	Data Classification Policy
dataclassificationscanstatus	optional	Data classification scan status to exclude
dataclassificationstatuses	optional	Data Classification Status
dataclassificationstatuses__notin	optional	Data Classification Status (not in)
datatypes	optional	Data Types
datatypes__notin	optional	Data Types (not in)
devicereview	optional	The asset review
devicereview__notin	optional	The asset review (not in)
encryptiontype	optional	The encryption type
encryptiontype__notin	optional	The encryption type (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID

id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
ispublic	optional	Whether there is public access or not
ispublic__nin	optional	Whether there is public access or not (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scannerstatus	optional	Scanner
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by

skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus__contains	optional	The threat detection status
threatdetectionstatus__nin	optional	Threat Detection Status (not in)
versioningenabled	optional	Whether there is versioning enabled or not

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/data-store

POST API to get Assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []
assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
cloudProviderAccountId	The cloud provider account id	false	string []

cloudProviderAccountId__contains	The cloud provider account ID	false	string []
cloudProviderAccountId__nin	The cloud provider account id (not in)	false	string []
cloudProviderAccountName	The cloud provider account name	false	string []
cloudProviderAccountName__contains	The cloud provider account name	false	string []
cloudProviderAccountName__nin	The cloud provider account name (not in)	false	string []
cloudProviderOrganization__contains	The cloud provider organization	false	string []
cloudProviderOrganizationUnit__contains	The cloud provider organization unit	false	string []
cloudProviderProjectId__contains	The cloud provider project ID	false	string []
cloudProviderSubscriptionId__contains	The cloud provider subscription ID	false	string []
cloudResourceId__contains	The cloud resource ID	false	string []
cloudTagsKey	The cloud tags key	false	string []
cloudTagsKey__contains	Free-text filter by cloud tag key (supports multiple values)	false	string []
cloudTagsKey__nin	The cloud tags key (not in)	false	string []
cloudTagsKeyValue	The cloud tags key value	false	string []
cloudTagsKeyValue__contains	Free-text filter by cloud tag key value (supports multiple values)	false	string []
cloudTagsKeyValue__nin	The cloud tags key value (not in)	false	string []
connectivityStatus	Connectivity	false	string []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
data_classification_scan_status__contains	Data classification scan status	false	string []
data_classification_status__contains	Data classification status	false	string []
data_types__contains	Data types contains	false	string []

dataClassificationPolicyStatus	Data Classification Policy	false	string []
dataClassificationScanStatus	Data classification scan status to exclude	false	string []
dataClassificationStatus	Data Classification Status	false	string []
dataClassificationStatus__nin	Data Classification Status (not in)	false	string []
dataTypes	Data Types	false	string []
dataTypes__nin	Data Types (not in)	false	string []
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
encryptionType	The encryption type	false	string []
encryptionType__nin	The encryption type (not in)	false	string []
groupIds	List of Group IDs to filter by	false	string []
id__contains	The ID	false	string []
id__in	The ID	false	string []
imageName__contains	Free-text filter by the image name	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
isPublic	Whether there is public access or not	false	boolean []
isPublic__nin	Whether there is public access or not (not in)	false	boolean []
limit	Limit number of returned items (1-1000)	false	integer
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []
name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
objectCount	The number of objects in the bucket	false	integer []
objectCount__nin	The number of objects in the bucket (not in)	false	integer []
region	The region	false	string []
region__contains	The geographical area where cloud resources are hosted	false	string []

region__nin	The region (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
scannerStatus	Scanner	false	string []
scanStatus	The CDS malware scan status	false	string []
scanStatus__contains	The CDS malware scan status	false	string []
scanStatus__nin	The CDS malware scan status (not in)	false	string []
sitelds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".	false	integer
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum
subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []

tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []
threatDetectionPolicyStatus	Threat Detection Policy	false	string []
threatDetectionStatus	Threat Detection Status	false	string []
threatDetectionStatus__contains	The threat detection status	false	string []
threatDetectionStatus__nin	Threat Detection Status (not in)	false	string []
versioningEnabled	Whether there is versioning enabled or not	false	boolean []

Perform action

POST /web/api/v2.1/xdr/assets/data-store/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__ni	optional	Asset Contact Email (not in)

n		
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)

cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
connectivitystatus	optional	Connectivity
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
data_classification_scan_status__contains	optional	Data classification scan status
data_classification_status__contains	optional	Data classification status
data_types__contains	optional	Data types contains
dataclassificationpolicystatus	optional	Data Classification Policy
dataclassificationscanstatus	optional	Data classification scan status to exclude
dataclassificationstatuses	optional	Data Classification Status
dataclassificationstatus__nin	optional	Data Classification Status (not in)
datatypes	optional	Data Types
datatypes__nin	optional	Data Types (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name

infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
ispublic	optional	Whether there is public access or not
ispublic__nin	optional	Whether there is public access or not (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scannerstatus	optional	Scanner
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to

surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus__contains	optional	The threat detection status
threatdetectionstatus__nin	optional	Threat Detection Status (not in)
versioningenabled	optional	Whether there is versioning enabled or not

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/data-store/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid	optional	The cloud provider account ID

d__contains		
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
connectivitystatus	optional	Connectivity
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by

cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
data_classification_scan_status__contains	optional	Data classification scan status
data_classification_status__contains	optional	Data classification status
data_types__contains	optional	Data types contains
dataclassificationpolicystatus	optional	Data Classification Policy
dataclassificationscanstatus	optional	Data classification scan status to exclude
dataclassificationstatus	optional	Data Classification Status
dataclassificationstatus__nin	optional	Data Classification Status (not in)
datatypes	optional	Data Types
datatypes__nin	optional	Data Types (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
ispublic	optional	Whether there is public access or not
ispublic__nin	optional	Whether there is public access or not (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)

name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scannerstatus	optional	Scanner
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)

tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus__contains	optional	The threat detection status
threatdetectionstatus__nin	optional	Threat Detection Status (not in)
versioningenabled	optional	Whether there is versioning enabled or not

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Available actions

POST /web/api/v2.1/xdr/assets/data-store/available-actions/with-status

Get available actions

Parameters

accountids	optional	List of Account IDs to filter by
------------	----------	----------------------------------

activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)

cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
connectivitystatus	optional	Connectivity
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
data_classification_scan_status__contains	optional	Data classification scan status
data_classification_status__contains	optional	Data classification status
data_types__contains	optional	Data types contains
dataclassificationpolicystatus	optional	Data Classification Policy
dataclassificationstatus	optional	Data classification scan status to exclude
dataclassificationstatus	optional	Data Classification Status
dataclassificationstatus	optional	Data Classification Status (not in)

s__nin		
datatypes	optional	Data Types
datatypes__nin	optional	Data Types (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
ispublic	optional	Whether there is public access or not
ispublic__nin	optional	Whether there is public access or not (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset

riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scannerstatus	optional	Scanner
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus__contains	optional	The threat detection status
threatdetectionstatus__nin	optional	Threat Detection Status (not in)
versioningenabled	optional	Whether there is versioning enabled or not

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Data Store Filters

Filter counts

GET /web/api/v2.1/xdr/assets/data-store/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)

cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
connectivitystatus	optional	Connectivity
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by

data_classification_scan_status__contains	optional	Data classification scan status
data_classification_status__contains	optional	Data classification status
data_types__contains	optional	Data types contains
dataclassificationpolicystatus	optional	Data Classification Policy
dataclassificationscanstatus	optional	Data classification scan status to exclude
dataclassificationstatuses	optional	Data Classification Status
dataclassificationstatus__nin	optional	Data Classification Status (not in)
datatypes	optional	Data Types
datatypes__nin	optional	Data Types (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
ispublic	optional	Whether there is public access or not
ispublic__nin	optional	Whether there is public access or not (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name

names__nin	optional	Name (not in)
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scannerstatus	optional	Scanner
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)

tagskeyvalue__nin	optional	Tags (not in)
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus_ _contains	optional	The threat detection status
threatdetectionstatus_ _nin	optional	Threat Detection Status (not in)
versioningenabled	optional	Whether there is versioning enabled or not

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/data-store/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/data-store/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
connectivitystatus	optional	Connectivity
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
data_classification_scan_status__contains	optional	Data classification scan status

data_classification_status__contains	optional	Data classification status
data_types__contains	optional	Data types contains
dataclassificationpolicystatus	optional	Data Classification Policy
dataclassificationscanstatus	optional	Data classification scan status to exclude
dataclassificationstatuses	optional	Data Classification Status
dataclassificationstatuses__nin	optional	Data Classification Status (not in)
datatypes	optional	Data Types
datatypes__nin	optional	Data Types (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
ispublic	optional	Whether there is public access or not
ispublic__nin	optional	Whether there is public access or not (not in)
limit	optional	Limit number of returned items
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)

objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scannerstatus	optional	Scanner
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus_contains	optional	The threat detection status
threatdetectionstatus_nin	optional	Threat Detection Status (not in)
versioningenabled	optional	Whether there is versioning enabled or not

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Developer Tool

Assets

GET /web/api/v2.1/xdr/assets/developer-tool

Get assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)

assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)

cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/developer-tool

POST API to get Assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []
assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
cloudProviderAccountId	The cloud provider account id	false	string []

cloudProviderAccountId__contains	The cloud provider account ID	false	string []
cloudProviderAccountId__nin	The cloud provider account id (not in)	false	string []
cloudProviderAccountName	The cloud provider account name	false	string []
cloudProviderAccountName__contains	The cloud provider account name	false	string []
cloudProviderAccountName__nin	The cloud provider account name (not in)	false	string []
cloudProviderOrganization__contains	The cloud provider organization	false	string []
cloudProviderOrganizationUnit__contains	The cloud provider organization unit	false	string []
cloudProviderProjectId__contains	The cloud provider project ID	false	string []
cloudProviderSubscriptionId__contains	The cloud provider subscription ID	false	string []
cloudResourceId__contains	The cloud resource ID	false	string []
cloudTagsKey	The cloud tags key	false	string []
cloudTagsKey__contains	Free-text filter by cloud tag key (supports multiple values)	false	string []
cloudTagsKey__nin	The cloud tags key (not in)	false	string []
cloudTagsKeyValue	The cloud tags key value	false	string []
cloudTagsKeyValue__contains	Free-text filter by cloud tag key value (supports multiple values)	false	string []
cloudTagsKeyValue__nin	The cloud tags key value (not in)	false	string []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
groupIds	List of Group IDs to filter by	false	string []
id__contains	The ID	false	string []

id__in	The ID	false	string []
imageName__contains	Free-text filter by the image name	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
limit	Limit number of returned items (1-1000)	false	integer
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []
name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
region	The region	false	string []
region__contains	The geographical area where cloud resources are hosted	false	string []
region__nin	The region (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
sitelds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".	false	integer
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum

subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []

Perform action

POST /web/api/v2.1/xdr/assets/developer-tool/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)

alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID

ains		
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from	false	string []

	select_all		
--	------------	--	--

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/developer-tool/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid	optional	The cloud provider account ID

d__contains		
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.

devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.

sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Available actions

POST /web/api/v2.1/xdr/assets/developer-tool/available-actions/with-status

Get available actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)

alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganization	optional	The cloud provider organization unit

tionunit__contains		
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)

region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Developer Tool Filters

Filter counts

GET /web/api/v2.1/xdr/assets/developer-tool/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)

cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review

devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)

tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/developer-tool/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/developer-tool/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by

id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists

tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Device

Assets

GET /web/api/v2.1/xdr/assets/device

Get assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email

assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)

firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
lastupdatedt__between	optional	The last update date
limit	optional	Limit number of returned items (1-1000)
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)

os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up

		execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

pagination		false	see Assets - response - pagination table
------------	--	-------	--

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/device

POST API to get Assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
architecture	The architecture of the device	false	string []
architecture__nin	The architecture of the device (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []
assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []

assetStatus__nin	The status of the asset (not in)	false	string []
coreCount	The number of cores	false	integer []
coreCount__nin	The number of cores (not in)	false	integer []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
detectedFromSite	The site from which the device was detected	false	string []
detectedFromSite__nin	The site from which the device was detected (not in)	false	string []
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
discoveryMethods	The discovery methods	false	string []
discoveryMethods__nin	The discovery methods (not in)	false	string []
domain	The domain of the device	false	string []
domain__contains	The domain	false	string []
domain__nin	The domain of the device (not in)	false	string []
eppUnsupportedUnknown	The agent supported or unknown state	false	string []
eppUnsupportedUnknown__nin	The agent supported or unknown state (not in)	false	string []
firstSeenDt__between	The first seen date	false	string
gatewayIps__contains	The gateway IPs	false	string []
gatewayMacs__contains	The gateway MACs	false	string []
groupIds	List of Group IDs to filter by	false	string []
hostnames__contains	The hostnames	false	string []
id__contains	The ID	false	string []
id__in	The ID	false	string []
imageName__contains	Free-text filter by the image name	false	string []

infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
internalIps__contains	The internal IPs	false	string []
ipAddress__contains	The IP addresses	false	string []
lastUpdateDt__between	The last update date	false	string
limit	Limit number of returned items (1-1000)	false	integer
macAddresses__contains	The MAC addresses	false	string []
manufacturer	The manufacturer of the device	false	string []
manufacturer__contains	The manufacturer	false	string []
manufacturer__nin	The manufacturer of the device (not in)	false	string []
memoryReadable	The memory of the device in human readable format	false	string []
memoryReadable__nin	The memory of the device in human readable format (not in)	false	string []
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []
name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
networkName	The network name	false	string []
networkName__nin	The network name (not in)	false	string []
os	The operating system of the device	false	string []
os__nin	The operating system of the device (not in)	false	string []
osFamily	The operating system family of the device	false	string []
osFamily__nin	The operating system family of the device (not in)	false	string []
osNameVersion	The operating system name and version of the device	false	string []
osNameVersion__contains	The OS names and versions	false	string []
osNameVersion__nin	The operating system name and	false	string []

	version of the device (not in)		
osVersion	The operating system version of the device	false	string []
osVersion__contains	The OS versions	false	string []
osVersion__nin	The operating system version of the device (not in)	false	string []
rangerTagKey__contains	Free-text filter by Ranger tag key (supports multiple values)	false	string []
rangerTagKeyValue__contains	Free-text filter by Ranger tag key value (supports multiple values)	false	string []
rangerTagsKey	The ranger tags key	false	string []
rangerTagsKey__nin	The ranger tags key (not in)	false	string []
rangerTagsKeyValue	The ranger tags key value	false	string []
rangerTagsKeyValue__nin	The ranger tags key value (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
siteIds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".	false	integer
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum
subCategory	The sub-category that each resource belongs to	false	string []

subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
subnets__contains	The subnets	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []
tcpPorts	The TCP ports	false	string []
udpPorts	The UDP ports	false	string []

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/device/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists

alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)

n		
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunkn own	optional	The agent supported or unknown state
eppunsupportedunkno wn__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contai ns	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
lastupdatedt__betwee n	optional	The last update date
limit	optional	Limit number of returned items (1-1000)
macaddresses__contai ns	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contai ns	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format

memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Perform action

POST /web/api/v2.1/xdr/assets/device/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset

assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs

ipaddress__contains	optional	The IP addresses
lastupdatedt__between	optional	The last update date
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)

rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports

udpports	optional	The UDP ports
----------	----------	---------------

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Available actions

POST /web/api/v2.1/xdr/assets/device/available-actions/with-status

Get cloud inventory device available-actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores

corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
lastupdatedt__between	optional	The last update date

n		
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)

rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Device Filters

Filter counts

GET /web/api/v2.1/xdr/assets/device/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)

assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)

internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
lastupdatedt__between	optional	The last update date
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contain	optional	Free-text filter by Ranger tag key (supports multiple values)

s		
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/device/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/device/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset

assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs

ipaddress__contains	optional	The IP addresses
lastupdatedt__between	optional	The last update date
limit	optional	Limit number of returned items
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contain	optional	Free-text filter by Ranger tag key (supports multiple values)

s		
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Endpoint Surface

Assets

GET /web/api/v2.1/xdr/assets/surface/endpoint

Get inventory endpoint assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine

agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)
agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type
agentdiskmetricsvolumetype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)

agentidrconnectivity	optional	The agent ldr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID

agentsubscribeondt__between	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionstatus	optional	The agent VSS protection status
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffareafreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__ni	optional	Asset Contact Email (not in)

n		
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID

identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcservice	optional	Is DC Server
lastactivedt__between	optional	The last active date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
limit	optional	Limit number of returned items (1-1000)
macaddresses__contains	optional	The MAC addresses
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)

name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.

sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/surface/endpoint

POST API to get endpoint assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
adsEnabled	ADS Enabled	false	boolean []
agentAgentVersion	The agent version	false	string []
agentAgentVersion__contains	The agent version	false	string []
agentAgentVersion__nin	The agent version (not in)	false	string []
agentAntiTamperingStatus	The agent anti tampering status	false	string []
agentAntiTamperingStatus__nin	The agent anti tampering status (not in)	false	string []
agentConfigurableNetworkQuarantine	Whether the agent can configure network quarantine	false	boolean []
agentConfigurableNetworkQuarantine__nin	Whether the agent can configure network quarantine (not in)	false	boolean []
agentConsoleConnectivity	The agent console connectivity	false	boolean []
agentConsoleMigrationStatus	The agent console migration status	false	string []
agentConsoleMigrationStatus__nin	The agent console migration status (not in)	false	string []
agentCustomerIdIdentifier__contains	The customer identifier	false	string []
agentDecommissioned	Whether the agent is decommissioned	false	boolean []
agentDiskEncryption	The agent disk encryption	false	boolean []
agentDiskMetricsFreePercentage__between	The agent free disk percentage on any of the disks	false	string
agentDiskMetricsFreePercentage__gte	The agent free disk percentage on any of the disks	false	number

agentDiskMetricsFreePercentage__lte	The agent free disk percentage on any of the disks	false	number
agentDiskMetricsVolumeType	The agent disk metrics volume type	false	string []
agentDiskMetricsVolumeType__nin	The agent disk metrics volume type (not in)	false	string []
agentDvConnectivity	The connection status between the agent and the SDL service	false	string []
agentDvConnectivity__nin	The connection status between the agent and the SDL service (not in)	false	string []
agentDvConnectivityLastUpdatedDt__between	The SDL connectivity last active	false	string
agentFullDiskScanDt__between	The agent full disk scan date	false	string
agentHasLocalConfig	Whether the agent has local configuration	false	boolean []
agentHealthStatus	The agent health status	false	string []
agentHealthStatus__nin	The agent health status (not in)	false	string []
agentIldrConnectivity	The agent Ildr connectivity	false	boolean []
agentInstallerType	The agent installer type	false	string []
agentInstallerType__nin	The agent installer type (not in)	false	string []
agentLastLoggedInUser__contains	The last logged in user	false	string []
agentLocation	The agent location	false	string []
agentLocation__nin	The agent location (not in)	false	string []
agentLocationAwareness__contains	The location awareness	false	string []
agentMissingPermissions	The agent missing permissions	false	string []
agentMissingPermissions__nin	The agent missing permissions (not in)	false	string []
agentNetworkStatus	The agent network status	false	string []
agentNetworkStatus__nin	The agent network status (not in)	false	string []
agentOperationalState	The agent operational state	false	string []
agentOperationalState__nin	The agent operational state (not in)	false	string []
agentPendingActions	The agent pending actions	false	string []
agentPendingActions__nin	The agent pending actions (not in)	false	string []
agentPendingUninstall	Whether the agent is pending uninstall	false	boolean []
agentPendingUpgrade	Whether the agent is pending upgrade	false	boolean []

agentRangerStatus	The agent network scanner status	false	string []
agentRangerStatus__nin	The agent network scanner status (not in)	false	string []
agentRangerVersion	The agent network scanner version	false	string []
agentRangerVersion__nin	The agent network scanner version (not in)	false	string []
agentS1AgentLiveUpdatesVersion__contains	Live update ID	false	string []
agentSubscribeOnDt__between	The agent subscribe time	false	string
agentUninstalled	Whether the agent is uninstalled	false	boolean []
agentUuid	Match by the agent UUID	false	string []
agentUuid__contains	The UUID	false	string []
agentVssLastSnapshotDt__between	The agent VSS last snapshot date	false	string
agentVssProtectionStatus	The agent VSS protection status	false	string []
agentVssProtectionStatus__nin	The agent VSS protection status (not in)	false	string []
agentVssRollbackStatus	The agent VSS rollback status	false	string []
agentVssRollbackStatus__nin	The agent VSS rollback status (not in)	false	string []
agentVssServiceStatus	The agent VSS service status	false	string []
agentVssServiceStatus__nin	The agent VSS service status (not in)	false	string []
agentVssVolumesDiffAreaFreePercentage__between	The agent free VSS volume percentage on any of the volumes	false	string
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
applicationName	The name of the application installed on a workstation or a server	false	string []
architecture	The architecture of the device	false	string []
architecture__nin	The architecture of the device (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []

assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
coreCount	The number of cores	false	integer []
coreCount__nin	The number of cores (not in)	false	integer []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
cpu__contains	The CPU	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
domain	The domain of the device	false	string []
domain__contains	The domain	false	string []
domain__nin	The domain of the device (not in)	false	string []
firstSeenDt__between	The first seen date	false	string
gatewayIps__contains	The gateway IPs	false	string []
gatewayMacs__contains	The gateway MACs	false	string []
groupIds	List of Group IDs to filter by	false	string []
hostnames__contains	The hostnames	false	string []

id__contains	The ID	false	string []
id__in	The ID	false	string []
identityAd__contains	Any AD string	false	string []
identityAdMachine__contains	AD machine or its groups	false	string []
identityAdMachineDistinguishedName__contains	AD machine DN	false	string []
identityAdMachineMembership__contains	AD machine groups	false	string []
identityAdUser__contains	AD user or their groups	false	string []
identityAdUserDistinguishedName__contains	AD user DN	false	string []
identityAdUserMembership__contains	AD user groups	false	string []
imageName__contains	Free-text filter by the image name	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
internalIps__contains	The internal IPs	false	string []
ipAddress__contains	The IP addresses	false	string []
isAdConnector	Is AD Connector	false	boolean []
isDcServer	Is DC Server	false	boolean []
lastActiveDt__between	The last active date	false	string
legacy_identity_policy_name__contains	The legacy identity policy name	false	string []
legacyIdentityPolicyName	Legacy Identity Policy Name	false	string []
limit	Limit number of returned items (1-1000)	false	integer
macAddresses__contains	The MAC addresses	false	string []
memoryReadable	The memory of the device in human readable format	false	string []
memoryReadable__nin	The memory of the device in human readable format (not in)	false	string []
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []
name__contains	The name	false	string []

names	Name	false	string []
names__nin	Name (not in)	false	string []
os	The operating system of the device	false	string []
os__nin	The operating system of the device (not in)	false	string []
osFamily	The operating system family of the device	false	string []
osFamily__nin	The operating system family of the device (not in)	false	string []
osNameVersion	The operating system name and version of the device	false	string []
osNameVersion__contains	The OS names and versions	false	string []
osNameVersion__nin	The operating system name and version of the device (not in)	false	string []
osVersion	The operating system version of the device	false	string []
osVersion__contains	The OS versions	false	string []
osVersion__nin	The operating system version of the device (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
serialNumber	The serial number	false	string []
serialNumber__contains	The serial number	false	string []
serialNumber__nin	The serial number (not in)	false	string []
sitelds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items,	false	integer

	use "cursor".		
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum
subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
subnets__contains	The subnets	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/surface/endpoint/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by

activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)
agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type

agentdiskmetricsvolume__type__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent Idr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)

agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentssubscribeondt__between	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionstatus	optional	The agent VSS protection status
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffareafreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes

alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review

devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector

isdcserver	optional	Is DC Server
lastactivedt__between	optional	The last active date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
limit	optional	Limit number of returned items (1-1000)
macaddresses__contains	optional	The MAC addresses
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)

riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Perform action

POST /web/api/v2.1/xdr/assets/surface/endpoint/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigration	optional	The agent console migration status (not in)

status__nin		
agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type
agentdiskmetricsvolumetype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent Idr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user

agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentsubscribeondbetween	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshot	optional	The agent VSS last snapshot date

dt__between		
agentvssprotectionstatus	optional	The agent VSS protection status
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffareafreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP

n		Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups

identityaduserdisting uishedname__contains	optional	AD user DN
identityadusermember ship__contains	optional	AD user groups
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcservice	optional	Is DC Server
lastactivedt__between	optional	The last active date
legacy_identity_polic y_name__contains	optional	The legacy identity policy name
legacyidentitypolicyn ame	optional	Legacy Identity Policy Name
macaddresses__contai ns	optional	The MAC addresses
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__conta	optional	The OS names and versions

ins		
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)

tagskeyvalue__nin	optional	Tags (not in)
-------------------	----------	---------------

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Available actions

POST /web/api/v2.1/xdr/assets/surface/endpoint/available-actions/with-status

Get endpoint available actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)
agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned

agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type
agentdiskmetricsvolumetype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent ldr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions

ns		
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentsubscribeondbetween	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionstatus	optional	The agent VSS protection status
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)

agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffareafreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)

countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset

infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
lastactivedt__between	optional	The last active date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
macaddresses__contains	optional	The MAC addresses
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
resourcetype	optional	The canonical name for the resource type

resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Endpoint Surface Filters

Filter counts

GET /web/api/v2.1/xdr/assets/surface/endpoint/filters/count

Get Endpoint filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)

agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type
agentdiskmetricsvolumetype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent Idr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)

agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentssubscribeondt__between	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionsta	optional	The agent VSS protection status

tus		
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdifferfreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset

assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermember	optional	AD user groups

ship__contains		
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
lastactivedt__between	optional	The last active date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
macaddresses__contains	optional	The MAC addresses
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device

osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/surface/endpoint/filters/free-text

Get Endpoint free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/surface/endpoint/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)
agentcustomeridentifi	optional	The customer identifier

er__contains		
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfree percentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfree percentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfree percentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolu metype	optional	The agent disk metrics volume type
agentdiskmetricsvolu metype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__ nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivityl astupdateddt__betwe en	optional	The SDL connectivity last active
agentfulldiskscandt__ between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__ni n	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent ldr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__ni n	optional	The agent installer type (not in)
agentlastloggedinuser __contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)

agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentssubscribeondt__between	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionsta	optional	The agent VSS protection status

tus		
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdifferfreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset

assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermember	optional	AD user groups

ship__contains		
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
lastactivedt__between	optional	The last active date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
limit	optional	Limit number of returned items
macaddresses__contains	optional	The MAC addresses
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)

osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Filters

Filter counts

GET /web/api/v2.1/xdr/assets/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
agentagentversion	optional	The agent version
agentantitamperingstatus	optional	The agent anti tampering status
agentconsoleconnectivity	optional	The agent console connectivity
agentidrconnectivity	optional	The agent idr connectivity
agentoperationalstate	optional	The agent operational state
agentpendingactions	optional	The agent pending actions
agentvssrollbackstatus	optional	The agent VSS rollback status
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys

alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
category	optional	The category that each resource belongs to
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit

cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
osfamily	optional	The operating system family of the device

region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
agentagentversion	optional	The agent version
agentantitamperingstatus	optional	The agent anti tampering status
agentconsoleconnectivity	optional	The agent console connectivity
agentidrconnectivity	optional	The agent idr connectivity
agentoperationalstate	optional	The agent operational state
agentpendingactions	optional	The agent pending actions
agentvssrollbackstatus	optional	The agent VSS rollback status
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)

assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
category	optional	The category that each resource belongs to
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)

cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
osfamily	optional	The operating system family of the device
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)

riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Upload CSV file

POST /web/api/v2.1/xdr/assets/filters/csv-filter

Upload CSV file

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Upload CSV file - response - data table
errors	Errors	false	array

Upload CSV file - response - data

Name	Description	Required	Value
assetFoundCount	Number of assets found with these values	false	integer
filterId	ID of the filter	false	string
notFoundAssets	Not found assets	false	string []
rowCount	Number of rows in the CSV file	false	integer
uniqueInputValuesCount	Number of unique values in the file	false	integer

Body Schema

Name	Description	Required	Value
formData		false	see Upload CSV file - body - formData table

Upload CSV file - body - formData

Name	Description	Required	Value
excludeHeader	Set to True to exclude the column header	true	boolean
file	File	true	file
assetFilterField	The property of the asset to filter by	false	string
category	The category that each resource belongs to	false	enum
surface	The surface that each resource belongs to	false	enum

Inventory Function

Assets

GET /web/api/v2.1/xdr/assets/function

Get assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags

alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID

cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted

region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/function

POST API to get Assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []
assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
cloudProviderAccountId	The cloud provider account id	false	string []

cloudProviderAccountId__contains	The cloud provider account ID	false	string []
cloudProviderAccountId__nin	The cloud provider account id (not in)	false	string []
cloudProviderAccountName	The cloud provider account name	false	string []
cloudProviderAccountName__contains	The cloud provider account name	false	string []
cloudProviderAccountName__nin	The cloud provider account name (not in)	false	string []
cloudProviderOrganization__contains	The cloud provider organization	false	string []
cloudProviderOrganizationUnit__contains	The cloud provider organization unit	false	string []
cloudProviderProjectId__contains	The cloud provider project ID	false	string []
cloudProviderSubscriptionId__contains	The cloud provider subscription ID	false	string []
cloudResourceId__contains	The cloud resource ID	false	string []
cloudTagsKey	The cloud tags key	false	string []
cloudTagsKey__contains	Free-text filter by cloud tag key (supports multiple values)	false	string []
cloudTagsKey__nin	The cloud tags key (not in)	false	string []
cloudTagsKeyValue	The cloud tags key value	false	string []
cloudTagsKeyValue__contains	Free-text filter by cloud tag key value (supports multiple values)	false	string []
cloudTagsKeyValue__nin	The cloud tags key value (not in)	false	string []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
groupIds	List of Group IDs to filter by	false	string []
id__contains	The ID	false	string []

id__in	The ID	false	string []
imageName__contains	Free-text filter by the image name	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
limit	Limit number of returned items (1-1000)	false	integer
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []
name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
region	The region	false	string []
region__contains	The geographical area where cloud resources are hosted	false	string []
region__nin	The region (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
sitelds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".	false	integer
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum

subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []

Perform action

POST /web/api/v2.1/xdr/assets/function/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)

alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID

ains		
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from	false	string []

	select_all		
--	------------	--	--

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/function/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid	optional	The cloud provider account ID

d__contains		
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.

devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.

sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Available actions

POST /web/api/v2.1/xdr/assets/function/available-actions/with-status

Get available actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)

alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganiza	optional	The cloud provider organization unit

tionunit__contains		
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)

region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Function Filters

Filter counts

GET /web/api/v2.1/xdr/assets/function/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)

cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review

devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)

tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/function/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/function/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by

id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists

tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Governance

Assets

GET /web/api/v2.1/xdr/assets/governance

Get assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)

assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)

cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__notin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__notin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__notin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__notin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__notin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__notin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/governance

POST API to get Assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []
assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
cloudProviderAccountId	The cloud provider account id	false	string []

cloudProviderAccountId__contains	The cloud provider account ID	false	string []
cloudProviderAccountId__nin	The cloud provider account id (not in)	false	string []
cloudProviderAccountName	The cloud provider account name	false	string []
cloudProviderAccountName__contains	The cloud provider account name	false	string []
cloudProviderAccountName__nin	The cloud provider account name (not in)	false	string []
cloudProviderOrganization__contains	The cloud provider organization	false	string []
cloudProviderOrganizationUnit__contains	The cloud provider organization unit	false	string []
cloudProviderProjectId__contains	The cloud provider project ID	false	string []
cloudProviderSubscriptionId__contains	The cloud provider subscription ID	false	string []
cloudResourceId__contains	The cloud resource ID	false	string []
cloudTagsKey	The cloud tags key	false	string []
cloudTagsKey__contains	Free-text filter by cloud tag key (supports multiple values)	false	string []
cloudTagsKey__nin	The cloud tags key (not in)	false	string []
cloudTagsKeyValue	The cloud tags key value	false	string []
cloudTagsKeyValue__contains	Free-text filter by cloud tag key value (supports multiple values)	false	string []
cloudTagsKeyValue__nin	The cloud tags key value (not in)	false	string []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
groupIds	List of Group IDs to filter by	false	string []
id__contains	The ID	false	string []

id__in	The ID	false	string []
imageName__contains	Free-text filter by the image name	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
limit	Limit number of returned items (1-1000)	false	integer
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []
name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
region	The region	false	string []
region__contains	The geographical area where cloud resources are hosted	false	string []
region__nin	The region (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
sitelds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".	false	integer
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum

subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/governance/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists

alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID

cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)

region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Perform action

POST /web/api/v2.1/xdr/assets/governance/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)

assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for

csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)

tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Available actions

POST /web/api/v2.1/xdr/assets/governance/available-actions/with-status

Get cloud inventory governance available-actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID

cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID

id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)

tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Governance Filters

Filter counts

GET /web/api/v2.1/xdr/assets/governance/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)

cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review

devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)

tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/governance/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/governance/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by

id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists

tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Identity

Assets

GET /web/api/v2.1/xdr/assets/identity

Get assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)

assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
badpasswordtime__between	optional	Bad Password Time
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contain	optional	Free-text filter by cloud tag key (supports multiple values)

s		
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
cn	optional	The LDAP Common Name
cn__contains	optional	The LDAP Common Name
cn__nin	optional	The LDAP Common Name (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
deleted	optional	Whether the AD Entity is deleted or not
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
displayname__contains	optional	The Display Name
distinguishedname__contains	optional	The Distinguished Name
domain	optional	The AD Domain Name
domain__contains	optional	The AD Domain Name
domain__nin	optional	The AD Domain Name (not in)
enabled	optional	Whether the Identity Group is enabled or not
forest	optional	The Forest Name
forest__contains	optional	The Forest Name
forest__nin	optional	The Forest Name (not in)
givenname__contains	optional	Given Name

groupids	optional	List of Group IDs to filter by
grouptype	optional	The Group Type
grouptype__nin	optional	The Group Type (not in)
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
last_modified_time__between	optional	Lock-out Time
lastlogontime__between	optional	The Last time of User Login
limit	optional	Limit number of returned items (1-1000)
lockouttime__between	optional	Lock-out Time
mail	optional	The Email Address
mail__contains	optional	The Email Address
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcategory	optional	The Object Category
objectcategory__nin	optional	The Object Category (not in)
objectclass	optional	The Object Class
objectclass__nin	optional	The Object Class (not in)
objectguid__contains	optional	The Object GUID
objectsid__contains	optional	The Object SID
onpremisesdistinguishedname__contains	optional	
onpremisesdomainname__contains	optional	On Premises Distinguished Name

onpremisesaccountname__contains	optional	On Premises SAM Account Name
onpremisessecurityidentifier__contains	optional	
onpremisesuserprincipalname__contains	optional	On Premises User Principal Name
othermails__contains	optional	Other Mails
passwordneverexpires	optional	Whether the password never expires
privileged	optional	Whether the AD Entity is privileged or not
proxyaddresses__contains	optional	Proxy Addresses
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
lastupdatedat__between	optional	The Last Seen date and time for the asset
samaccountname	optional	The SAM Account Name
samaccountname__nin	optional	The SAM Account Name (not in)
serviceaccount	optional	The Service Account
serviceprincipalname__contains	optional	The Service Principal Name
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.

sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
useraccountcontrol	optional	The User Account Control
useraccountcontrol__nin	optional	The User Account Control (not in)
userpasswordexpirytimecomputed__between	optional	The User Password Expiry Time
userprincipalname	optional	The User Principal Name
userprincipalname__contains	optional	The User Principal Name
userprincipalname__nin	optional	The User Principal Name (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/identity

POST API to get Assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []
assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
badPasswordTime__between	Bad Password Time	false	string

cloudProviderAccountId	The cloud provider account id	false	string []
cloudProviderAccountId__contains	The cloud provider account ID	false	string []
cloudProviderAccountId__nin	The cloud provider account id (not in)	false	string []
cloudProviderAccountName	The cloud provider account name	false	string []
cloudProviderAccountName__contains	The cloud provider account name	false	string []
cloudProviderAccountName__nin	The cloud provider account name (not in)	false	string []
cloudProviderOrganization__contains	The cloud provider organization	false	string []
cloudProviderOrganizationUnit__contains	The cloud provider organization unit	false	string []
cloudProviderProjectId__contains	The cloud provider project ID	false	string []
cloudProviderSubscriptionId__contains	The cloud provider subscription ID	false	string []
cloudResourceId__contains	The cloud resource ID	false	string []
cloudTagsKey	The cloud tags key	false	string []
cloudTagsKey__contains	Free-text filter by cloud tag key (supports multiple values)	false	string []
cloudTagsKey__nin	The cloud tags key (not in)	false	string []
cloudTagsKeyValue	The cloud tags key value	false	string []
cloudTagsKeyValue__contains	Free-text filter by cloud tag key value (supports multiple values)	false	string []
cloudTagsKeyValue__nin	The cloud tags key value (not in)	false	string []
cn	The LDAP Common Name	false	string []
cn__contains	The LDAP Common Name	false	string []
cn__nin	The LDAP Common Name (not in)	false	string []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string

deleted	Whether the AD Entity is deleted or not	false	boolean []
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
displayName__contains	The Display Name	false	string []
distinguishedName__contains	The Distinguished Name	false	string []
domain	The AD Domain Name	false	string []
domain__contains	The AD Domain Name	false	string []
domain__nin	The AD Domain Name (not in)	false	string []
enabled	Whether the Identity Group is enabled or not	false	boolean []
forest	The Forest Name	false	string []
forest__contains	The Forest Name	false	string []
forest__nin	The Forest Name (not in)	false	string []
givenName__contains	Given Name	false	string []
groupIds	List of Group IDs to filter by	false	string []
groupType	The Group Type	false	integer []
groupType__nin	The Group Type (not in)	false	integer []
id__contains	The ID	false	string []
id__in	The ID	false	string []
imageName__contains	Free-text filter by the image name	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
last_modified_time__between	Lock-out Time	false	string
lastLogonTime__between	The Last time of User Login	false	string
limit	Limit number of returned items (1-1000)	false	integer
lockOutTime__between	Lock-out Time	false	string
mail	The Email Address	false	string []
mail__contains	The Email Address	false	string []
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []

name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
objectCategory	The Object Category	false	string []
objectCategory__nin	The Object Category (not in)	false	string []
objectClass	The Object Class	false	string []
objectClass__nin	The Object Class (not in)	false	string []
objectGuid__contains	The Object GUID	false	string []
objectSid__contains	The Object SID	false	string []
onPremisesDistinguishedName__contains		false	string []
onPremisesDomainName__contains	On Premises Distinguished Name	false	string []
onPremisesSamAccountName__contains	On Premises SAM Account Name	false	string []
onPremisesSecurityIdentifier__contains		false	string []
onPremisesUserPrincipalName__contains	On Premises User Principal Name	false	string []
otherMails__contains	Other Mails	false	string []
passwordNeverExpire	Whether the password never expires	false	boolean []
privileged	Whether the AD Entity is privileged or not	false	boolean []
proxyAddresses__contains	Proxy Addresses	false	string []
region	The region	false	string []
region__contains	The geographical area where cloud resources are hosted	false	string []
region__nin	The region (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the	false	string []

	asset (not in)		
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
samAccountName	The SAM Account Name	false	string []
samAccountName__nin	The SAM Account Name (not in)	false	string []
serviceAccount	The Service Account	false	boolean []
servicePrincipalName__contains	The Service Principal Name	false	string []
siteIds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".	false	integer
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum
subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []
userAccountControl	The User Account Control	false	integer []

userAccountControl__nin	The User Account Control (not in)	false	integer []
userPasswordExpiryTimeComputed__between	The User Password Expiry Time	false	string
userPrincipalName	The User Principal Name	false	string []
userPrincipalName__contains	The User Principal Name	false	string []
userPrincipalName__nin	The User Principal Name (not in)	false	string []

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/identity/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP

n		Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
badpasswordtime__between	optional	Bad Password Time
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)

cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
cn	optional	The LDAP Common Name
cn__contains	optional	The LDAP Common Name
cn__nin	optional	The LDAP Common Name (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
deleted	optional	Whether the AD Entity is deleted or not
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
displayname__contains	optional	The Display Name
distinguishedname__contains	optional	The Distinguished Name
domain	optional	The AD Domain Name
domain__contains	optional	The AD Domain Name
domain__nin	optional	The AD Domain Name (not in)
enabled	optional	Whether the Identity Group is enabled or not
forest	optional	The Forest Name
forest__contains	optional	The Forest Name
forest__nin	optional	The Forest Name (not in)
givenname__contains	optional	Given Name
groupids	optional	List of Group IDs to filter by
grouptype	optional	The Group Type
grouptype__nin	optional	The Group Type (not in)
id__contains	optional	The ID
id__in	optional	The ID

imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
last_modified_time__between	optional	Lock-out Time
lastlogontime__between	optional	The Last time of User Login
limit	optional	Limit number of returned items (1-1000)
lockouttime__between	optional	Lock-out Time
mail	optional	The Email Address
mail__contains	optional	The Email Address
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcategory	optional	The Object Category
objectcategory__nin	optional	The Object Category (not in)
objectclass	optional	The Object Class
objectclass__nin	optional	The Object Class (not in)
objectguid__contains	optional	The Object GUID
objectsid__contains	optional	The Object SID
onpremisesdistinguishedname__contains	optional	
onpremisesdomainname__contains	optional	On Premises Distinguished Name
onpremisesaccountname__contains	optional	On Premises SAM Account Name
onpremisessecurityidentifier__contains	optional	
onpremisesuserprincipalname__contains	optional	On Premises User Principal Name

othermails__contains	optional	Other Mails
passwordneverexpire	optional	Whether the password never expires
privileged	optional	Whether the AD Entity is privileged or not
proxyaddresses__contains	optional	Proxy Addresses
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
samaccountname	optional	The SAM Account Name
samaccountname__nin	optional	The SAM Account Name (not in)
serviceaccount	optional	The Service Account
serviceprincipalname__contains	optional	The Service Principal Name
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to

surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
useraccountcontrol	optional	The User Account Control
useraccountcontrol__nin	optional	The User Account Control (not in)
userpasswordexpirytimecomputed__between	optional	The User Password Expiry Time
userprincipalname	optional	The User Principal Name
userprincipalname__contains	optional	The User Principal Name
userprincipalname__nin	optional	The User Principal Name (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Perform action

POST /web/api/v2.1/xdr/assets/identity/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
badpasswordtime__between	optional	Bad Password Time
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name

cloudprovideraccount name__contains	optional	The cloud provider account name
cloudprovideraccount name__nin	optional	The cloud provider account name (not in)
cloudproviderorganiza tion__contains	optional	The cloud provider organization
cloudproviderorganiza tionunit__contains	optional	The cloud provider organization unit
cloudproviderprojecti d__contains	optional	The cloud provider project ID
cloudprovidersubscript ionid__contains	optional	The cloud provider subscription ID
cloudresourceid__cont ains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contain s	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__co ntains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__ni n	optional	The cloud tags key value (not in)
cn	optional	The LDAP Common Name
cn__contains	optional	The LDAP Common Name
cn__nin	optional	The LDAP Common Name (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
deleted	optional	Whether the AD Entity is deleted or not
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
displayname__contain s	optional	The Display Name

distinguishedname__contains	optional	The Distinguished Name
domain	optional	The AD Domain Name
domain__contains	optional	The AD Domain Name
domain__nin	optional	The AD Domain Name (not in)
enabled	optional	Whether the Identity Group is enabled or not
forest	optional	The Forest Name
forest__contains	optional	The Forest Name
forest__nin	optional	The Forest Name (not in)
givenname__contains	optional	Given Name
groupids	optional	List of Group IDs to filter by
grouptype	optional	The Group Type
grouptype__nin	optional	The Group Type (not in)
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
last_modified_time__between	optional	Lock-out Time
lastlogontime__between	optional	The Last time of User Login
lockouttime__between	optional	Lock-out Time
mail	optional	The Email Address
mail__contains	optional	The Email Address
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcategory	optional	The Object Category

objectcategory__nin	optional	The Object Category (not in)
objectclass	optional	The Object Class
objectclass__nin	optional	The Object Class (not in)
objectguid__contains	optional	The Object GUID
objectsid__contains	optional	The Object SID
onpremisesdistinguis hedname__contains	optional	
onpremisesdomainnam e__contains	optional	On Premises Distinguished Name
onpremisesamaccoun tname__contains	optional	On Premises SAM Account Name
onpremisessecurityiden tifier__contains	optional	
onpremisesuserprinci palname__contains	optional	On Premises User Principal Name
othermails__contains	optional	Other Mails
passwordneverexpire	optional	Whether the password never expires
privileged	optional	Whether the AD Entity is privileged or not
proxyaddresses__conta ins	optional	Proxy Addresses
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contain s	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__betwee n	optional	The Last Seen date and time for the asset
samaccountname	optional	The SAM Account Name

samaccountname__nin	optional	The SAM Account Name (not in)
serviceaccount	optional	The Service Account
serviceprincipalname__contains	optional	The Service Principal Name
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
useraccountcontrol	optional	The User Account Control
useraccountcontrol__nin	optional	The User Account Control (not in)
userpasswordexpirytimecomputed__between	optional	The User Password Expiry Time
userprincipalname	optional	The User Principal Name
userprincipalname__contains	optional	The User Principal Name
userprincipalname__nin	optional	The User Principal Name (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Available actions

POST /web/api/v2.1/xdr/assets/identity/available-actions/with-status

Get cloud inventory identity available-actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
badpasswordtime__between	optional	Bad Password Time
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
cn	optional	The LDAP Common Name
cn__contains	optional	The LDAP Common Name
cn__nin	optional	The LDAP Common Name (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by

deleted	optional	Whether the AD Entity is deleted or not
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
displayname__contains	optional	The Display Name
distinguishedname__contains	optional	The Distinguished Name
domain	optional	The AD Domain Name
domain__contains	optional	The AD Domain Name
domain__nin	optional	The AD Domain Name (not in)
enabled	optional	Whether the Identity Group is enabled or not
forest	optional	The Forest Name
forest__contains	optional	The Forest Name
forest__nin	optional	The Forest Name (not in)
givenname__contains	optional	Given Name
groupids	optional	List of Group IDs to filter by
grouptype	optional	The Group Type
grouptype__nin	optional	The Group Type (not in)
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
last_modified_time__between	optional	Lock-out Time
lastlogontime__between	optional	The Last time of User Login
lockouttime__between	optional	Lock-out Time
mail	optional	The Email Address
mail__contains	optional	The Email Address
missingcoverage	optional	The missing coverage for the asset

missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcategory	optional	The Object Category
objectcategory__nin	optional	The Object Category (not in)
objectclass	optional	The Object Class
objectclass__nin	optional	The Object Class (not in)
objectguid__contains	optional	The Object GUID
objectsid__contains	optional	The Object SID
onpremisesdistinguis hedname__contains	optional	
onpremisesdomainnam e__contains	optional	On Premises Distinguished Name
onpremisesamaccoun tname__contains	optional	On Premises SAM Account Name
onpremisessecurityiden tifier__contains	optional	
onpremisesuserprinci palname__contains	optional	On Premises User Principal Name
othermails__contains	optional	Other Mails
passwordneverexpire	optional	Whether the password never expires
privileged	optional	Whether the AD Entity is privileged or not
proxyaddresses__conta ins	optional	Proxy Addresses
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contain s	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)

riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
samaccountname	optional	The SAM Account Name
samaccountname__nin	optional	The SAM Account Name (not in)
serviceaccount	optional	The Service Account
serviceprincipalname__contains	optional	The Service Principal Name
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
useraccountcontrol	optional	The User Account Control
useraccountcontrol__nin	optional	The User Account Control (not in)
userpasswordexpirytimecomputed__between	optional	The User Password Expiry Time
userprincipalname	optional	The User Principal Name
userprincipalname__contains	optional	The User Principal Name

userprincipalname__n	optional	The User Principal Name (not in)
----------------------	----------	----------------------------------

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Identity Filters

Filter counts

GET /web/api/v2.1/xdr/assets/identity/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)

badpasswordtime__between	optional	Bad Password Time
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
cn	optional	The LDAP Common Name

cn__contains	optional	The LDAP Common Name
cn__nin	optional	The LDAP Common Name (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
deleted	optional	Whether the AD Entity is deleted or not
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
displayname__contains	optional	The Display Name
distinguishedname__contains	optional	The Distinguished Name
domain	optional	The AD Domain Name
domain__contains	optional	The AD Domain Name
domain__nin	optional	The AD Domain Name (not in)
enabled	optional	Whether the Identity Group is enabled or not
forest	optional	The Forest Name
forest__contains	optional	The Forest Name
forest__nin	optional	The Forest Name (not in)
givenname__contains	optional	Given Name
groupids	optional	List of Group IDs to filter by
grouptype	optional	The Group Type
grouptype__nin	optional	The Group Type (not in)
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
last_modified_time__between	optional	Lock-out Time
lastlogontime__between	optional	The Last time of User Login

lockouttime__between	optional	Lock-out Time
mail	optional	The Email Address
mail__contains	optional	The Email Address
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcategory	optional	The Object Category
objectcategory__nin	optional	The Object Category (not in)
objectclass	optional	The Object Class
objectclass__nin	optional	The Object Class (not in)
objectguid__contains	optional	The Object GUID
objectsid__contains	optional	The Object SID
onpremisesdistinguis hedname__contains	optional	
onpremisesdomainnam e__contains	optional	On Premises Distinguished Name
onpremisesamaccoun tname__contains	optional	On Premises SAM Account Name
onpremisessecurityiden tifier__contains	optional	
onpremisesuserprinci palname__contains	optional	On Premises User Principal Name
othermails__contains	optional	Other Mails
passwordneverexpire	optional	Whether the password never expires
privileged	optional	Whether the AD Entity is privileged or not
proxyaddresses__conta ins	optional	Proxy Addresses
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted

region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
samaccountname	optional	The SAM Account Name
samaccountname__nin	optional	The SAM Account Name (not in)
serviceaccount	optional	The Service Account
serviceprincipalname__contains	optional	The Service Principal Name
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
useraccountcontrol	optional	The User Account Control
useraccountcontrol__nin	optional	The User Account Control (not in)

userpasswordexpirytimecomputed__between	optional	The User Password Expiry Time
userprincipalname	optional	The User Principal Name
userprincipalname__contains	optional	The User Principal Name
userprincipalname__notin	optional	The User Principal Name (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/identity/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/identity/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
badpasswordtime__between	optional	Bad Password Time

cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
cn	optional	The LDAP Common Name
cn__contains	optional	The LDAP Common Name
cn__nin	optional	The LDAP Common Name (not in)

countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
deleted	optional	Whether the AD Entity is deleted or not
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
displayname__contains	optional	The Display Name
distinguishedname__contains	optional	The Distinguished Name
domain	optional	The AD Domain Name
domain__contains	optional	The AD Domain Name
domain__nin	optional	The AD Domain Name (not in)
enabled	optional	Whether the Identity Group is enabled or not
forest	optional	The Forest Name
forest__contains	optional	The Forest Name
forest__nin	optional	The Forest Name (not in)
givenname__contains	optional	Given Name
groupids	optional	List of Group IDs to filter by
grouptype	optional	The Group Type
grouptype__nin	optional	The Group Type (not in)
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
last_modified_time__between	optional	Lock-out Time
lastlogontime__between	optional	The Last time of User Login
limit	optional	Limit number of returned items
lockouttime__between	optional	Lock-out Time

mail	optional	The Email Address
mail__contains	optional	The Email Address
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcategory	optional	The Object Category
objectcategory__nin	optional	The Object Category (not in)
objectclass	optional	The Object Class
objectclass__nin	optional	The Object Class (not in)
objectguid__contains	optional	The Object GUID
objectsid__contains	optional	The Object SID
onpremisesdistinguis hedname__contains	optional	
onpremisesdomainnam e__contains	optional	On Premises Distinguished Name
onpremisesamaccoun tname__contains	optional	On Premises SAM Account Name
onpremisessecurityiden tifier__contains	optional	
onpremisesuserprinci palname__contains	optional	On Premises User Principal Name
othermails__contains	optional	Other Mails
passwordneverexpire	optional	Whether the password never expires
privileged	optional	Whether the AD Entity is privileged or not
proxyaddresses__conta ins	optional	Proxy Addresses
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)

resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
samaccountname	optional	The SAM Account Name
samaccountname__nin	optional	The SAM Account Name (not in)
serviceaccount	optional	The Service Account
serviceprincipalname__contains	optional	The Service Principal Name
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
useraccountcontrol	optional	The User Account Control
useraccountcontrol__nin	optional	The User Account Control (not in)
userpasswordexpiryt	optional	The User Password Expiry Time

imecomputed__between		
userprincipalname	optional	The User Principal Name
userprincipalname__contains	optional	The User Principal Name
userprincipalname__notin	optional	The User Principal Name (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Identity Surface

Assets

GET /web/api/v2.1/xdr/assets/surface/identity

Get identity surface assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)

assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
badpasswordtime__between	optional	Bad Password Time
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contain	optional	Free-text filter by cloud tag key (supports multiple values)

s		
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
cn	optional	The LDAP Common Name
cn__contains	optional	The LDAP Common Name
cn__nin	optional	The LDAP Common Name (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
deleted	optional	Whether the AD Entity is deleted or not
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
displayname__contains	optional	The Display Name
distinguishedname__contains	optional	The Distinguished Name
domain	optional	The AD Domain Name
domain__contains	optional	The AD Domain Name
domain__nin	optional	The AD Domain Name (not in)
enabled	optional	Whether the Identity Group is enabled or not
forest	optional	The Forest Name
forest__contains	optional	The Forest Name
forest__nin	optional	The Forest Name (not in)
givenname__contains	optional	Given Name

groupids	optional	List of Group IDs to filter by
grouptype	optional	The Group Type
grouptype__nin	optional	The Group Type (not in)
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
last_modified_time__between	optional	Lock-out Time
lastlogontime__between	optional	The Last time of User Login
limit	optional	Limit number of returned items (1-1000)
lockouttime__between	optional	Lock-out Time
mail	optional	The Email Address
mail__contains	optional	The Email Address
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcategory	optional	The Object Category
objectcategory__nin	optional	The Object Category (not in)
objectclass	optional	The Object Class
objectclass__nin	optional	The Object Class (not in)
objectguid__contains	optional	The Object GUID
objectsid__contains	optional	The Object SID
onpremisesdistinguishedname__contains	optional	
onpremisesdomainname__contains	optional	On Premises Distinguished Name

onpremisesamaccountname__contains	optional	On Premises SAM Account Name
onpremisessecurityidentifier__contains	optional	
onpremisesuserprincipalname__contains	optional	On Premises User Principal Name
othermails__contains	optional	Other Mails
passwordneverexpire	optional	Whether the password never expires
privileged	optional	Whether the AD Entity is privileged or not
proxyaddresses__contains	optional	Proxy Addresses
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
slupdatedat__between	optional	The Last Seen date and time for the asset
samaccountname	optional	The SAM Account Name
samaccountname__nin	optional	The SAM Account Name (not in)
serviceaccount	optional	The Service Account
serviceprincipalname__contains	optional	The Service Principal Name
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.

sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
useraccountcontrol	optional	The User Account Control
useraccountcontrol__nin	optional	The User Account Control (not in)
userpasswordexpirytimecomputed__between	optional	The User Password Expiry Time
userprincipalname	optional	The User Principal Name
userprincipalname__contains	optional	The User Principal Name
userprincipalname__nin	optional	The User Principal Name (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/surface/identity/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to

assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
badpasswordtime__between	optional	Bad Password Time
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)

cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
cn	optional	The LDAP Common Name
cn__contains	optional	The LDAP Common Name
cn__nin	optional	The LDAP Common Name (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
deleted	optional	Whether the AD Entity is deleted or not
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
displayname__contains	optional	The Display Name
distinguishedname__contains	optional	The Distinguished Name
domain	optional	The AD Domain Name
domain__contains	optional	The AD Domain Name
domain__nin	optional	The AD Domain Name (not in)
enabled	optional	Whether the Identity Group is enabled or not
forest	optional	The Forest Name
forest__contains	optional	The Forest Name
forest__nin	optional	The Forest Name (not in)
givenname__contains	optional	Given Name
groupids	optional	List of Group IDs to filter by

grouptype	optional	The Group Type
grouptype__nin	optional	The Group Type (not in)
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
last_modified_time__between	optional	Lock-out Time
lastlogontime__between	optional	The Last time of User Login
limit	optional	Limit number of returned items (1-1000)
lockouttime__between	optional	Lock-out Time
mail	optional	The Email Address
mail__contains	optional	The Email Address
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcategory	optional	The Object Category
objectcategory__nin	optional	The Object Category (not in)
objectclass	optional	The Object Class
objectclass__nin	optional	The Object Class (not in)
objectguid__contains	optional	The Object GUID
objectsid__contains	optional	The Object SID
onpremisesdistinguishedname__contains	optional	
onpremisesdomainname__contains	optional	On Premises Distinguished Name
onpremisesaccountname	optional	On Premises SAM Account Name

tname__contains		
onpremisessecurityidentifier__contains	optional	
onpremisesuserprincipalname__contains	optional	On Premises User Principal Name
othermails__contains	optional	Other Mails
passwordneverexpire	optional	Whether the password never expires
privileged	optional	Whether the AD Entity is privileged or not
proxyaddresses__contains	optional	Proxy Addresses
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
samaccountname	optional	The SAM Account Name
samaccountname__nin	optional	The SAM Account Name (not in)
serviceaccount	optional	The Service Account
serviceprincipalname__contains	optional	The Service Principal Name
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.

sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
useraccountcontrol	optional	The User Account Control
useraccountcontrol__nin	optional	The User Account Control (not in)
userpasswordexpirytimecomputed__between	optional	The User Password Expiry Time
userprincipalname	optional	The User Principal Name
userprincipalname__contains	optional	The User Principal Name
userprincipalname__nin	optional	The User Principal Name (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Perform action

POST /web/api/v2.1/xdr/assets/surface/identity/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
badpasswordtime__between	optional	Bad Password Time
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
cn	optional	The LDAP Common Name
cn__contains	optional	The LDAP Common Name
cn__nin	optional	The LDAP Common Name (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by

deleted	optional	Whether the AD Entity is deleted or not
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
displayname__contains	optional	The Display Name
distinguishedname__contains	optional	The Distinguished Name
domain	optional	The AD Domain Name
domain__contains	optional	The AD Domain Name
domain__nin	optional	The AD Domain Name (not in)
enabled	optional	Whether the Identity Group is enabled or not
forest	optional	The Forest Name
forest__contains	optional	The Forest Name
forest__nin	optional	The Forest Name (not in)
givenname__contains	optional	Given Name
groupids	optional	List of Group IDs to filter by
grouptype	optional	The Group Type
grouptype__nin	optional	The Group Type (not in)
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
last_modified_time__between	optional	Lock-out Time
lastlogontime__between	optional	The Last time of User Login
lockouttime__between	optional	Lock-out Time
mail	optional	The Email Address
mail__contains	optional	The Email Address
missingcoverage	optional	The missing coverage for the asset

missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcategory	optional	The Object Category
objectcategory__nin	optional	The Object Category (not in)
objectclass	optional	The Object Class
objectclass__nin	optional	The Object Class (not in)
objectguid__contains	optional	The Object GUID
objectsid__contains	optional	The Object SID
onpremisesdistinguis hedname__contains	optional	
onpremisesdomainnam e__contains	optional	On Premises Distinguished Name
onpremisesamaccoun tname__contains	optional	On Premises SAM Account Name
onpremisessecurityiden tifier__contains	optional	
onpremisesuserprinci palname__contains	optional	On Premises User Principal Name
othermails__contains	optional	Other Mails
passwordneverexpire	optional	Whether the password never expires
privileged	optional	Whether the AD Entity is privileged or not
proxyaddresses__conta ins	optional	Proxy Addresses
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contain s	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)

riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
samaccountname	optional	The SAM Account Name
samaccountname__nin	optional	The SAM Account Name (not in)
serviceaccount	optional	The Service Account
serviceprincipalname__contains	optional	The Service Principal Name
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
useraccountcontrol	optional	The User Account Control
useraccountcontrol__nin	optional	The User Account Control (not in)
userpasswordexpirytimecomputed__between	optional	The User Password Expiry Time
userprincipalname	optional	The User Principal Name
userprincipalname__contains	optional	The User Principal Name

userprincipalname__n	optional	The User Principal Name (not in)
----------------------	----------	----------------------------------

Response Messages

- 200 - Success
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Available actions

POST /web/api/v2.1/xdr/assets/surface/identity/available-actions/with-status

Get available actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
badpasswordtime__between	optional	Bad Password Time
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
cn	optional	The LDAP Common Name
cn__contains	optional	The LDAP Common Name
cn__nin	optional	The LDAP Common Name (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by

deleted	optional	Whether the AD Entity is deleted or not
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
displayname__contains	optional	The Display Name
distinguishedname__contains	optional	The Distinguished Name
domain	optional	The AD Domain Name
domain__contains	optional	The AD Domain Name
domain__nin	optional	The AD Domain Name (not in)
enabled	optional	Whether the Identity Group is enabled or not
forest	optional	The Forest Name
forest__contains	optional	The Forest Name
forest__nin	optional	The Forest Name (not in)
givenname__contains	optional	Given Name
groupids	optional	List of Group IDs to filter by
grouptype	optional	The Group Type
grouptype__nin	optional	The Group Type (not in)
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
last_modified_time__between	optional	Lock-out Time
lastlogontime__between	optional	The Last time of User Login
lockouttime__between	optional	Lock-out Time
mail	optional	The Email Address
mail__contains	optional	The Email Address
missingcoverage	optional	The missing coverage for the asset

missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcategory	optional	The Object Category
objectcategory__nin	optional	The Object Category (not in)
objectclass	optional	The Object Class
objectclass__nin	optional	The Object Class (not in)
objectguid__contains	optional	The Object GUID
objectsid__contains	optional	The Object SID
onpremisesdistinguis hedname__contains	optional	
onpremisesdomainnam e__contains	optional	On Premises Distinguished Name
onpremisesamaccoun tname__contains	optional	On Premises SAM Account Name
onpremisessecurityiden tifier__contains	optional	
onpremisesuserprinci palname__contains	optional	On Premises User Principal Name
othermails__contains	optional	Other Mails
passwordneverexpire	optional	Whether the password never expires
privileged	optional	Whether the AD Entity is privileged or not
proxyaddresses__conta ins	optional	Proxy Addresses
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contain s	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)

riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
samaccountname	optional	The SAM Account Name
samaccountname__nin	optional	The SAM Account Name (not in)
serviceaccount	optional	The Service Account
serviceprincipalname__contains	optional	The Service Principal Name
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
useraccountcontrol	optional	The User Account Control
useraccountcontrol__nin	optional	The User Account Control (not in)
userpasswordexpirytimecomputed__between	optional	The User Password Expiry Time
userprincipalname	optional	The User Principal Name
userprincipalname__contains	optional	The User Principal Name

userprincipalname__n	optional	The User Principal Name (not in)
----------------------	----------	----------------------------------

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Identity Surface Filters

Filter counts

GET /web/api/v2.1/xdr/assets/surface/identity/filters/count

Get identity filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)

badpasswordtime__between	optional	Bad Password Time
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
cn	optional	The LDAP Common Name

cn__contains	optional	The LDAP Common Name
cn__nin	optional	The LDAP Common Name (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
deleted	optional	Whether the AD Entity is deleted or not
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
displayname__contains	optional	The Display Name
distinguishedname__contains	optional	The Distinguished Name
domain	optional	The AD Domain Name
domain__contains	optional	The AD Domain Name
domain__nin	optional	The AD Domain Name (not in)
enabled	optional	Whether the Identity Group is enabled or not
forest	optional	The Forest Name
forest__contains	optional	The Forest Name
forest__nin	optional	The Forest Name (not in)
givenname__contains	optional	Given Name
groupids	optional	List of Group IDs to filter by
grouptype	optional	The Group Type
grouptype__nin	optional	The Group Type (not in)
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
last_modified_time__between	optional	Lock-out Time
lastlogontime__between	optional	The Last time of User Login

lockouttime__between	optional	Lock-out Time
mail	optional	The Email Address
mail__contains	optional	The Email Address
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcategory	optional	The Object Category
objectcategory__nin	optional	The Object Category (not in)
objectclass	optional	The Object Class
objectclass__nin	optional	The Object Class (not in)
objectguid__contains	optional	The Object GUID
objectsid__contains	optional	The Object SID
onpremisesdistinguis hedname__contains	optional	
onpremisesdomainnam e__contains	optional	On Premises Distinguished Name
onpremisesamaccoun tname__contains	optional	On Premises SAM Account Name
onpremisessecurityiden tifier__contains	optional	
onpremisesuserprinci palname__contains	optional	On Premises User Principal Name
othermails__contains	optional	Other Mails
passwordneverexpire	optional	Whether the password never expires
privileged	optional	Whether the AD Entity is privileged or not
proxyaddresses__conta ins	optional	Proxy Addresses
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted

region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
samaccountname	optional	The SAM Account Name
samaccountname__nin	optional	The SAM Account Name (not in)
serviceaccount	optional	The Service Account
serviceprincipalname__contains	optional	The Service Principal Name
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
useraccountcontrol	optional	The User Account Control
useraccountcontrol__nin	optional	The User Account Control (not in)

userpasswordexpirytimecomputed__between	optional	The User Password Expiry Time
userprincipalname	optional	The User Principal Name
userprincipalname__contains	optional	The User Principal Name
userprincipalname__notin	optional	The User Principal Name (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/surface/identity/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/surface/identity/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
badpasswordtime__between	optional	Bad Password Time

cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
cn	optional	The LDAP Common Name
cn__contains	optional	The LDAP Common Name
cn__nin	optional	The LDAP Common Name (not in)

countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
deleted	optional	Whether the AD Entity is deleted or not
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
displayname__contains	optional	The Display Name
distinguishedname__contains	optional	The Distinguished Name
domain	optional	The AD Domain Name
domain__contains	optional	The AD Domain Name
domain__nin	optional	The AD Domain Name (not in)
enabled	optional	Whether the Identity Group is enabled or not
forest	optional	The Forest Name
forest__contains	optional	The Forest Name
forest__nin	optional	The Forest Name (not in)
givenname__contains	optional	Given Name
groupids	optional	List of Group IDs to filter by
grouptype	optional	The Group Type
grouptype__nin	optional	The Group Type (not in)
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
last_modified_time__between	optional	Lock-out Time
lastlogontime__between	optional	The Last time of User Login
limit	optional	Limit number of returned items
lockouttime__between	optional	Lock-out Time

mail	optional	The Email Address
mail__contains	optional	The Email Address
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcategory	optional	The Object Category
objectcategory__nin	optional	The Object Category (not in)
objectclass	optional	The Object Class
objectclass__nin	optional	The Object Class (not in)
objectguid__contains	optional	The Object GUID
objectsid__contains	optional	The Object SID
onpremisesdistinguis hedname__contains	optional	
onpremisesdomainnam e__contains	optional	On Premises Distinguished Name
onpremisesamaccoun tname__contains	optional	On Premises SAM Account Name
onpremisessecurityiden tifier__contains	optional	
onpremisesuserprinci palname__contains	optional	On Premises User Principal Name
othermails__contains	optional	Other Mails
passwordneverexpire	optional	Whether the password never expires
privileged	optional	Whether the AD Entity is privileged or not
proxyaddresses__conta ins	optional	Proxy Addresses
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)

resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
samaccountname	optional	The SAM Account Name
samaccountname__nin	optional	The SAM Account Name (not in)
serviceaccount	optional	The Service Account
serviceprincipalname__contains	optional	The Service Principal Name
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
useraccountcontrol	optional	The User Account Control
useraccountcontrol__nin	optional	The User Account Control (not in)
userpasswordexpiryt	optional	The User Password Expiry Time

imecomputed__between		
userprincipalname	optional	The User Principal Name
userprincipalname__contains	optional	The User Principal Name
userprincipalname__notin	optional	The User Principal Name (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Network

Assets

GET /web/api/v2.1/xdr/assets/network

Get assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)

assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)

cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__notin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__notin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__notin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__notin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__notin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__notin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/network

POST API to get Assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []
assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
cloudProviderAccountId	The cloud provider account id	false	string []

cloudProviderAccountId__contains	The cloud provider account ID	false	string []
cloudProviderAccountId__nin	The cloud provider account id (not in)	false	string []
cloudProviderAccountName	The cloud provider account name	false	string []
cloudProviderAccountName__contains	The cloud provider account name	false	string []
cloudProviderAccountName__nin	The cloud provider account name (not in)	false	string []
cloudProviderOrganization__contains	The cloud provider organization	false	string []
cloudProviderOrganizationUnit__contains	The cloud provider organization unit	false	string []
cloudProviderProjectId__contains	The cloud provider project ID	false	string []
cloudProviderSubscriptionId__contains	The cloud provider subscription ID	false	string []
cloudResourceId__contains	The cloud resource ID	false	string []
cloudTagsKey	The cloud tags key	false	string []
cloudTagsKey__contains	Free-text filter by cloud tag key (supports multiple values)	false	string []
cloudTagsKey__nin	The cloud tags key (not in)	false	string []
cloudTagsKeyValue	The cloud tags key value	false	string []
cloudTagsKeyValue__contains	Free-text filter by cloud tag key value (supports multiple values)	false	string []
cloudTagsKeyValue__nin	The cloud tags key value (not in)	false	string []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
groupIds	List of Group IDs to filter by	false	string []
id__contains	The ID	false	string []

id__in	The ID	false	string []
imageName__contains	Free-text filter by the image name	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
limit	Limit number of returned items (1-1000)	false	integer
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []
name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
region	The region	false	string []
region__contains	The geographical area where cloud resources are hosted	false	string []
region__nin	The region (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
sitelds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".	false	integer
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum

subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/network/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists

alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID

cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)

region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Perform action

POST /web/api/v2.1/xdr/assets/network/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)

assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for

csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)

tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Available actions

POST /web/api/v2.1/xdr/assets/network/available-actions/with-status

Get cloud inventory network available-actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID

cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID

id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)

tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Network Discovery Surface

Assets

GET /web/api/v2.1/xdr/assets/surface/networkDiscovery

Get inventory of Network Discovery surface assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)

assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
category	optional	The category that each resource belongs to
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames

id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
lastupdatedt__between	optional	The last update date
limit	optional	Limit number of returned items (1-1000)
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions

ins		
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets

surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/surface/networkDiscovery/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__ni	optional	Asset Contact Email (not in)

n		
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date

gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
lastupdatedt__between	optional	The last update date
limit	optional	Limit number of returned items (1-1000)
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device

os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.

sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Perform action

POST /web/api/v2.1/xdr/assets/surface/networkDiscovery/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
category	optional	The category that each resource belongs to
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review

devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
lastupdatedt__between	optional	The last update date
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)

memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkeys__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

s		
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Available actions

POST /web/api/v2.1/xdr/assets/surface/networkDiscovery/available-actions/with-status

Get inventory network discovery available actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
category	optional	The category that each resource belongs to

corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses

lastupdatedt__between	optional	The last update date
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)

ntains		
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Network Discovery Surface Filters

Filter counts

GET /web/api/v2.1/xdr/assets/surface/networkDiscovery/filters/count

Get Network Discovery filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)

assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
category	optional	The category that each resource belongs to
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset

infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
lastupdatedt__between	optional	The last update date
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)

rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)

tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/surface/networkDiscovery/filters/free-text

Get Network Discovery free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/surface/networkDiscovery/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset

assetstatus__nin	optional	The status of the asset (not in)
category	optional	The category that each resource belongs to
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)

internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
lastupdatedt__between	optional	The last update date
limit	optional	Limit number of returned items
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)

rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)

tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Network Filters

Filter counts

GET /web/api/v2.1/xdr/assets/network/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)

assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)

cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset

siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/network/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/network/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
groupids	optional	List of Group IDs to filter by

id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists

tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Notes

Create or update note against asset

POST /web/api/v2.1/xdr/assets/notes

create or update note

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
id	Id	false	string
note	Note	false	string
resourceId	Resource id	false	string

Delete note

DELETE /web/api/v2.1/xdr/assets/notes

Delete note

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
id	Id	false	string
note	Note	false	string
resourceId	Resource id	false	string

Inventory Server

Assets

GET /web/api/v2.1/xdr/assets/server

Get assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)

agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type
agentdiskmetricsvolumetype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent Idr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)

agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentssubscribeondt__between	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionsta	optional	The agent VSS protection status

tus		
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdifferentialfreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset

assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)

countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups

identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups
imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
isrogues	optional	Whether the instance is a rogue or not
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID

k8sclusterid__contains	optional	Kubernetes Cluster ID
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
lastactivedt__between	optional	The last active date
lastupdatedt__between	optional	The last update date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
limit	optional	Limit number of returned items (1-1000)
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device

manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
networksecuritygroups__contains	optional	The network security group
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)

rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
state	optional	The state of the instance
state__contains	optional	The state
state__nin	optional	The state of the instance (not in)
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID

subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports
virtualnetworkid__contains	optional	The virtual network ID

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/server

POST API to get Assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
adsEnabled	ADS Enabled	false	boolean []
agentAgentVersion	The agent version	false	string []
agentAgentVersion__contains	The agent version	false	string []
agentAgentVersion__nin	The agent version (not in)	false	string []
agentAntiTamperingStatus	The agent anti tampering status	false	string []
agentAntiTamperingStatus__nin	The agent anti tampering status (not in)	false	string []
agentConfigurableNetworkQuarantine	Whether the agent can configure network quarantine	false	boolean []
agentConfigurableNetworkQuarantine__nin	Whether the agent can configure network quarantine (not in)	false	boolean []
agentConsoleConnectivity	The agent console connectivity	false	boolean []
agentConsoleMigrationStatus	The agent console migration status	false	string []
agentConsoleMigrationStatus__nin	The agent console migration status (not in)	false	string []
agentCustomerIdIdentifier__contains	The customer identifier	false	string []
agentDecommissioned	Whether the agent is decommissioned	false	boolean []
agentDiskEncryption	The agent disk encryption	false	boolean []
agentDiskMetricsFreePercentage__between	The agent free disk percentage on any of the disks	false	string
agentDiskMetricsFreePercentage__gte	The agent free disk percentage on any of the disks	false	number

agentDiskMetricsFreePercentage__lte	The agent free disk percentage on any of the disks	false	number
agentDiskMetricsVolumeType	The agent disk metrics volume type	false	string []
agentDiskMetricsVolumeType__nin	The agent disk metrics volume type (not in)	false	string []
agentDvConnectivity	The connection status between the agent and the SDL service	false	string []
agentDvConnectivity__nin	The connection status between the agent and the SDL service (not in)	false	string []
agentDvConnectivityLastUpdatedDt__between	The SDL connectivity last active	false	string
agentFullDiskScanDt__between	The agent full disk scan date	false	string
agentHasLocalConfig	Whether the agent has local configuration	false	boolean []
agentHealthStatus	The agent health status	false	string []
agentHealthStatus__nin	The agent health status (not in)	false	string []
agentIldrConnectivity	The agent Ildr connectivity	false	boolean []
agentInstallerType	The agent installer type	false	string []
agentInstallerType__nin	The agent installer type (not in)	false	string []
agentLastLoggedInUser__contains	The last logged in user	false	string []
agentLocation	The agent location	false	string []
agentLocation__nin	The agent location (not in)	false	string []
agentLocationAwareness__contains	The location awareness	false	string []
agentMissingPermissions	The agent missing permissions	false	string []
agentMissingPermissions__nin	The agent missing permissions (not in)	false	string []
agentNetworkStatus	The agent network status	false	string []
agentNetworkStatus__nin	The agent network status (not in)	false	string []
agentOperationalState	The agent operational state	false	string []
agentOperationalState__nin	The agent operational state (not in)	false	string []
agentPendingActions	The agent pending actions	false	string []
agentPendingActions__nin	The agent pending actions (not in)	false	string []
agentPendingUninstall	Whether the agent is pending uninstall	false	boolean []
agentPendingUpgrade	Whether the agent is pending upgrade	false	boolean []

agentRangerStatus	The agent network scanner status	false	string []
agentRangerStatus__nin	The agent network scanner status (not in)	false	string []
agentRangerVersion	The agent network scanner version	false	string []
agentRangerVersion__nin	The agent network scanner version (not in)	false	string []
agentS1AgentLiveUpdatesVersion__contains	Live update ID	false	string []
agentSubscribeOnDt__between	The agent subscribe time	false	string
agentUninstalled	Whether the agent is uninstalled	false	boolean []
agentUuid	Match by the agent UUID	false	string []
agentUuid__contains	The UUID	false	string []
agentVssLastSnapshotDt__between	The agent VSS last snapshot date	false	string
agentVssProtectionStatus	The agent VSS protection status	false	string []
agentVssProtectionStatus__nin	The agent VSS protection status (not in)	false	string []
agentVssRollbackStatus	The agent VSS rollback status	false	string []
agentVssRollbackStatus__nin	The agent VSS rollback status (not in)	false	string []
agentVssServiceStatus	The agent VSS service status	false	string []
agentVssServiceStatus__nin	The agent VSS service status (not in)	false	string []
agentVssVolumesDiffAreaFreePercentage__between	The agent free VSS volume percentage on any of the volumes	false	string
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
applicationName	The name of the application installed on a workstation or a server	false	string []
architecture	The architecture of the device	false	string []
architecture__nin	The architecture of the device (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []

assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
cloudProviderAccountId	The cloud provider account id	false	string []
cloudProviderAccountId__contains	The cloud provider account ID	false	string []
cloudProviderAccountId__nin	The cloud provider account id (not in)	false	string []
cloudProviderAccountName	The cloud provider account name	false	string []
cloudProviderAccountName__contains	The cloud provider account name	false	string []
cloudProviderAccountName__nin	The cloud provider account name (not in)	false	string []
cloudProviderOrganization__contains	The cloud provider organization	false	string []
cloudProviderOrganizationUnit__contains	The cloud provider organization unit	false	string []
cloudProviderProjectId__contains	The cloud provider project ID	false	string []
cloudProviderSubscriptionId__contains	The cloud provider subscription ID	false	string []
cloudResourceId__contains	The cloud resource ID	false	string []
cloudTagsKey	The cloud tags key	false	string []
cloudTagsKey__contains	Free-text filter by cloud tag key (supports multiple values)	false	string []
cloudTagsKey__nin	The cloud tags key (not in)	false	string []
cloudTagsKeyValue	The cloud tags key value	false	string []
cloudTagsKeyValue__contains	Free-text filter by cloud tag key value (supports multiple values)	false	string []
cloudTagsKeyValue__nin	The cloud tags key value (not in)	false	string []

coreCount	The number of cores	false	integer []
coreCount__nin	The number of cores (not in)	false	integer []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
cpu__contains	The CPU	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
detectedFromSite	The site from which the device was detected	false	string []
detectedFromSite__nin	The site from which the device was detected (not in)	false	string []
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
discoveryMethods	The discovery methods	false	string []
discoveryMethods__nin	The discovery methods (not in)	false	string []
domain	The domain of the device	false	string []
domain__contains	The domain	false	string []
domain__nin	The domain of the device (not in)	false	string []
eppUnsupportedUnknown	The agent supported or unknown state	false	string []
eppUnsupportedUnknown__nin	The agent supported or unknown state (not in)	false	string []
firstSeenDt__between	The first seen date	false	string
gatewayIps__contains	The gateway IPs	false	string []
gatewayMacs__contains	The gateway MACs	false	string []
groupIds	List of Group IDs to filter by	false	string []
hostnames__contains	The hostnames	false	string []
id__contains	The ID	false	string []
id__in	The ID	false	string []
identityAd__contains	Any AD string	false	string []

identityAdMachine__contains	AD machine or its groups	false	string []
identityAdMachineDistinguishedName__contains	AD machine DN	false	string []
identityAdMachineMembership__contains	AD machine groups	false	string []
identityAdUser__contains	AD user or their groups	false	string []
identityAdUserDistinguishedName__contains	AD user DN	false	string []
identityAdUserMembership__contains	AD user groups	false	string []
imageId__contains	The image ID	false	string []
imageName__contains	Free-text filter by the image name	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
instanceId__contains	The instance ID	false	string []
instanceRole__contains	The instance role	false	string []
instanceType__contains	The instance type	false	string []
internalIps__contains	The internal IPs	false	string []
ipAddress__contains	The IP addresses	false	string []
isAdConnector	Is AD Connector	false	boolean []
isDcServer	Is DC Server	false	boolean []
isRogues	Whether the instance is a rogue or not	false	boolean []
k8sAnnotationsUnifiedKey__contains	Free-text filter by Kubernetes Annotations key (supports multiple values)	false	string []
k8sAnnotationsUnifiedKeyValue__contains	Free-text filter by Kubernetes Annotations key value (supports multiple values)	false	string []
k8sCluster	The Kubernetes Cluster	false	string []
k8sCluster__contains	The Kubernetes cluster	false	string []
k8sCluster__nin	The Kubernetes Cluster (not in)	false	string []
k8sClusterId	The Kubernetes Cluster ID	false	string []
k8sClusterId__contains	Kubernetes Cluster ID	false	string []
k8sLabelsUnifiedKey__contains	Free-text filter by Kubernetes Labels	false	string []

	key (supports multiple values)		
k8sLabelsUnifiedKeyValue__contains	Free-text filter by Kubernetes Labels key value (supports multiple values)	false	string []
k8sNamespace	The Kubernetes Namespace Name	false	string []
k8sNamespace__contains	Namespace Name	false	string []
k8sNode	The Kubernetes Node	false	string []
k8sNode__contains	The Kubernetes node	false	string []
k8sNode__nin	The Kubernetes Node (not in)	false	string []
k8sResourceId	The Kubernetes Resource ID	false	string []
k8sResourceId__contains	Kubernetes Resource ID	false	string []
k8sRunningOnNodes	Running on Nodes	false	string []
k8sRunningOnNodes__contains	Running on nodes	false	see Assets using POST - body - k8sRunningOnNodes__contains table
k8sType	The Kubernetes Type	false	string []
k8sType__nin	The Kubernetes Type (not in)	false	string []
k8sVersion	The Kubernetes Version	false	string []
k8sVersion__nin	The Kubernetes Version (not in)	false	string []
lastActiveDt__between	The last active date	false	string
lastUpdateDt__between	The last update date	false	string
legacy_identity_policy_name__contains	The legacy identity policy name	false	string []
legacyIdentityPolicyName	Legacy Identity Policy Name	false	string []
limit	Limit number of returned items (1-1000)	false	integer
macAddresses__contains	The MAC addresses	false	string []
manufacturer	The manufacturer of the device	false	string []
manufacturer__contains	The manufacturer	false	string []
manufacturer__nin	The manufacturer of the device (not in)	false	string []
memoryReadable	The memory of the device in human readable format	false	string []
memoryReadable__nin	The memory of the device in human readable format (not in)	false	string []
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset	false	string []

	(not in)		
name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
networkName	The network name	false	string []
networkName__nin	The network name (not in)	false	string []
networkSecurityGroups__contains	The network security group	false	string []
os	The operating system of the device	false	string []
os__nin	The operating system of the device (not in)	false	string []
osFamily	The operating system family of the device	false	string []
osFamily__nin	The operating system family of the device (not in)	false	string []
osNameVersion	The operating system name and version of the device	false	string []
osNameVersion__contains	The OS names and versions	false	string []
osNameVersion__nin	The operating system name and version of the device (not in)	false	string []
osVersion	The operating system version of the device	false	string []
osVersion__contains	The OS versions	false	string []
osVersion__nin	The operating system version of the device (not in)	false	string []
rangerTagKey__contains	Free-text filter by Ranger tag key (supports multiple values)	false	string []
rangerTagKeyValue__contains	Free-text filter by Ranger tag key value (supports multiple values)	false	string []
rangerTagsKey	The ranger tags key	false	string []
rangerTagsKey__nin	The ranger tags key (not in)	false	string []
rangerTagsKeyValue	The ranger tags key value	false	string []
rangerTagsKeyValue__nin	The ranger tags key value (not in)	false	string []
region	The region	false	string []
region__contains	The geographical area where cloud resources are hosted	false	string []

region__nin	The region (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
serialNumber	The serial number	false	string []
serialNumber__contains	The serial number	false	string []
serialNumber__nin	The serial number (not in)	false	string []
sitelds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".	false	integer
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum
state	The state of the instance	false	string []
state__contains	The state	false	string []
state__nin	The state of the instance (not in)	false	string []
subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
subnetId__contains	The subnet ID	false	string []
subnets__contains	The subnets	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs	false	string []

	to (not in)		
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []
tcpPorts	The TCP ports	false	string []
udpPorts	The UDP ports	false	string []
virtualNetworkId__contains	The virtual network ID	false	string []

Assets using POST - body - k8sRunningOnNodes__contains

Name	Description	Required	Value
		false	string []

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/server/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version

agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)
agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type
agentdiskmetricsvolumetype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__	optional	The connection status between the agent and the SDL service (not

nin		in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent ldr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)

agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentsubscribeondt__between	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionstatus	optional	The agent VSS protection status
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffareafreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists

alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganiza	optional	The cloud provider organization unit

tionunit__contains		
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)

domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunkn own	optional	The agent supported or unknown state
eppunsupportedunkno wn__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contai ns	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__co ntains	optional	AD machine or its groups
identityadmachinedist inguishedname__conta ins	optional	AD machine DN
identityadmachinemem bership__contains	optional	AD machine groups
identityaduser__contai ns	optional	AD user or their groups
identityaduserdisting uishedname__contains	optional	AD user DN
identityadusermember ship__contains	optional	AD user groups
imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)

instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
isrogues	optional	Whether the instance is a rogue or not
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes

k8srunningonnodes__contains	optional	Running on nodes
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
lastactivedt__between	optional	The last active date
lastupdatedt__between	optional	The last update date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
limit	optional	Limit number of returned items (1-1000)
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
networksecuritygroups__contains	optional	The network security group
os	optional	The operating system of the device

os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number

serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
state	optional	The state of the instance
state__contains	optional	The state
state__nin	optional	The state of the instance (not in)
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports
virtualnetworkid__contains	optional	The virtual network ID

tains		
-------	--	--

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Perform action

POST /web/api/v2.1/xdr/assets/server/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity

ity		
agentconsolemigration status	optional	The agent console migration status
agentconsolemigration status__nin	optional	The agent console migration status (not in)
agentcustomeridentifi er__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfree percentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreep ercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreep ercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolu metype	optional	The agent disk metrics volume type
agentdiskmetricsvolu metype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__ nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivityl astupdateddt__betwe en	optional	The SDL connectivity last active
agentfulldiskscandt__ between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__ni n	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent ldr connectivity
agentinstallertype	optional	The agent installer type

agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentsubscribeondt__between	optional	The agent subscribe time

agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshot dt__between	optional	The agent VSS last snapshot date
agentvssprotectionsta tus	optional	The agent VSS protection status
agentvssprotectionsta tus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus __nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus_ _nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffa reafreepercentage__b etween	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__ni n	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to

assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value

cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID

identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups
imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcservers	optional	Is DC Server
isrogues	optional	Whether the instance is a rogue or not
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster

k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
lastactivedt__between	optional	The last active date
lastupdatedt__between	optional	The last update date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
macaddresses__contains	optional	The MAC addresses

manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
networksecuritygroups__contains	optional	The network security group
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key

rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
state	optional	The state of the instance
state__contains	optional	The state
state__nin	optional	The state of the instance (not in)
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)

tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports
virtualnetworkid__contains	optional	The virtual network ID

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Available actions

POST /web/api/v2.1/xdr/assets/server/available-actions/with-status

Get available actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)
agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned

agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type
agentdiskmetricsvolumetype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent ldr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions

ns		
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentsubscribeondbetween	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionstatus	optional	The agent VSS protection status
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)

agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffareafreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by

detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups

identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups
imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
isrogues	optional	Whether the instance is a rogue or not
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name

ins		
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
lastactivedt__between	optional	The last active date
lastupdatedt__between	optional	The last update date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name

names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
networksecuritygroups__contains	optional	The network security group
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

s		
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
state	optional	The state of the instance
state__contains	optional	The state
state__nin	optional	The state of the instance (not in)
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports

virtualnetworkid__contains	optional	The virtual network ID
----------------------------	----------	------------------------

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Server Filters

Filter counts

GET /web/api/v2.1/xdr/assets/server/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)

agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type
agentdiskmetricsvolumetype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent Idr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)

agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentssubscribeondt__between	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionsta	optional	The agent VSS protection status

tus		
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdifferfreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset

assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)

countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemem	optional	AD machine groups

bership__contains		
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups
imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
isrogues	optional	Whether the instance is a rogue or not
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyval	optional	Free-text filter by Kubernetes Labels key value (supports multiple

ue__contains		values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
lastactivedt__between	optional	The last active date
lastupdatedt__between	optional	The last update date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)

missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
networksecuritygroups__contains	optional	The network security group
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted

region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
state	optional	The state of the instance
state__contains	optional	The state
state__nin	optional	The state of the instance (not in)
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)

tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports
virtualnetworkid__contains	optional	The virtual network ID

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/server/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/server/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)
agentcustomeridentifi	optional	The customer identifier

er__contains		
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfree percentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfree percentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfree percentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolu metype	optional	The agent disk metrics volume type
agentdiskmetricsvolu metype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__ nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivityl astupdateddt__betwe en	optional	The SDL connectivity last active
agentfulldiskscandt__ between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__ni n	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent ldr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__ni n	optional	The agent installer type (not in)
agentlastloggedinuser __contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)

agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentssubscribeondt__between	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionsta	optional	The agent VSS protection status

tus		
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdifferfreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset

assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)

countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemem	optional	AD machine groups

bership__contains		
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups
imageid__contains	optional	The image ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
instanceid__contains	optional	The instance ID
instanceroles__contains	optional	The instance role
instancetype__contains	optional	The instance type
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
isrogues	optional	Whether the instance is a rogue or not
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyval	optional	Free-text filter by Kubernetes Labels key value (supports multiple

ue__contains		values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
lastactivedt__between	optional	The last active date
lastupdatedt__between	optional	The last update date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
limit	optional	Limit number of returned items
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format

memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
networksecuritygroups__contains	optional	The network security group
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkeys__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
region	optional	The region

region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
state	optional	The state of the instance
state__contains	optional	The state
state__nin	optional	The state of the instance (not in)
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnetid__contains	optional	The subnet ID
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)

s		
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports
virtualnetworkid__contains	optional	The virtual network ID

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Storage

Assets

GET /web/api/v2.1/xdr/assets/storage

Get assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)

assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)

cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
connectivitystatus	optional	Connectivity
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
data_classification_scan_status__contains	optional	Data classification scan status
data_classification_status__contains	optional	Data classification status
data_types__contains	optional	Data types contains
dataclassificationpolicystatus	optional	Data Classification Policy
dataclassificationscanstatus	optional	Data classification scan status to exclude
dataclassificationstatuses	optional	Data Classification Status
dataclassificationstatuses__nin	optional	Data Classification Status (not in)
datatypes	optional	Data Types
datatypes__nin	optional	Data Types (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID

id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
ispublic	optional	Whether there is public access or not
ispublic__nin	optional	Whether there is public access or not (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scannerstatus	optional	Scanner
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by

skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus__contains	optional	The threat detection status
threatdetectionstatus__nin	optional	Threat Detection Status (not in)
versioningenabled	optional	Whether there is versioning enabled or not

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/storage

POST API to get Assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []
assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
cloudProviderAccountId	The cloud provider account id	false	string []

cloudProviderAccountId__contains	The cloud provider account ID	false	string []
cloudProviderAccountId__nin	The cloud provider account id (not in)	false	string []
cloudProviderAccountName	The cloud provider account name	false	string []
cloudProviderAccountName__contains	The cloud provider account name	false	string []
cloudProviderAccountName__nin	The cloud provider account name (not in)	false	string []
cloudProviderOrganization__contains	The cloud provider organization	false	string []
cloudProviderOrganizationUnit__contains	The cloud provider organization unit	false	string []
cloudProviderProjectId__contains	The cloud provider project ID	false	string []
cloudProviderSubscriptionId__contains	The cloud provider subscription ID	false	string []
cloudResourceId__contains	The cloud resource ID	false	string []
cloudTagsKey	The cloud tags key	false	string []
cloudTagsKey__contains	Free-text filter by cloud tag key (supports multiple values)	false	string []
cloudTagsKey__nin	The cloud tags key (not in)	false	string []
cloudTagsKeyValue	The cloud tags key value	false	string []
cloudTagsKeyValue__contains	Free-text filter by cloud tag key value (supports multiple values)	false	string []
cloudTagsKeyValue__nin	The cloud tags key value (not in)	false	string []
connectivityStatus	Connectivity	false	string []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
data_classification_scan_status__contains	Data classification scan status	false	string []
data_classification_status__contains	Data classification status	false	string []
data_types__contains	Data types contains	false	string []

dataClassificationPolicyStatus	Data Classification Policy	false	string []
dataClassificationScanStatus	Data classification scan status to exclude	false	string []
dataClassificationStatus	Data Classification Status	false	string []
dataClassificationStatus__nin	Data Classification Status (not in)	false	string []
dataTypes	Data Types	false	string []
dataTypes__nin	Data Types (not in)	false	string []
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
encryptionType	The encryption type	false	string []
encryptionType__nin	The encryption type (not in)	false	string []
groupIds	List of Group IDs to filter by	false	string []
id__contains	The ID	false	string []
id__in	The ID	false	string []
imageName__contains	Free-text filter by the image name	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
isPublic	Whether there is public access or not	false	boolean []
isPublic__nin	Whether there is public access or not (not in)	false	boolean []
limit	Limit number of returned items (1-1000)	false	integer
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []
name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
objectCount	The number of objects in the bucket	false	integer []
objectCount__nin	The number of objects in the bucket (not in)	false	integer []
region	The region	false	string []
region__contains	The geographical area where cloud resources are hosted	false	string []

region__nin	The region (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
scannerStatus	Scanner	false	string []
scanStatus	The CDS malware scan status	false	string []
scanStatus__contains	The CDS malware scan status	false	string []
scanStatus__nin	The CDS malware scan status (not in)	false	string []
sitelds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".	false	integer
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []

tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []
threatDetectionPolicyStatus	Threat Detection Policy	false	string []
threatDetectionStatus	Threat Detection Status	false	string []
threatDetectionStatus__contains	The threat detection status	false	string []
threatDetectionStatus__nin	Threat Detection Status (not in)	false	string []
versioningEnabled	Whether there is versioning enabled or not	false	boolean []

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/storage/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)

assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)

cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
connectivitystatus	optional	Connectivity
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
data_classification_scan_status__contains	optional	Data classification scan status
data_classification_status__contains	optional	Data classification status
data_types__contains	optional	Data types contains
dataclassificationpolicystatus	optional	Data Classification Policy
dataclassificationscanstatus	optional	Data classification scan status to exclude
dataclassificationstatuses	optional	Data Classification Status
dataclassificationstatuses__nin	optional	Data Classification Status (not in)
datatypes	optional	Data Types
datatypes__nin	optional	Data Types (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID

id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
ispublic	optional	Whether there is public access or not
ispublic__nin	optional	Whether there is public access or not (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scannerstatus	optional	Scanner
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by

skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus__contains	optional	The threat detection status
threatdetectionstatus__nin	optional	Threat Detection Status (not in)
versioningenabled	optional	Whether there is versioning enabled or not

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Available actions

POST /web/api/v2.1/xdr/assets/storage/available-actions/with-status

Get available actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID

cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
connectivitystatus	optional	Connectivity
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
data_classification_scan_status__contains	optional	Data classification scan status
data_classification_status__contains	optional	Data classification status

data_types__contains	optional	Data types contains
dataclassificationpolicystatus	optional	Data Classification Policy
dataclassificationscanstatus	optional	Data classification scan status to exclude
dataclassificationstatuses	optional	Data Classification Status
dataclassificationstatus__nin	optional	Data Classification Status (not in)
datatypes	optional	Data Types
datatypes__nin	optional	Data Types (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
ispublic	optional	Whether there is public access or not
ispublic__nin	optional	Whether there is public access or not (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
region	optional	The region

region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scannerstatus	optional	Scanner
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status

threatdetectionstatus_ _contains	optional	The threat detection status
threatdetectionstatus_ _nin	optional	Threat Detection Status (not in)
versioningenabled	optional	Whether there is versioning enabled or not

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Perform action

POST /web/api/v2.1/xdr/assets/storage/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID

cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
connectivitystatus	optional	Connectivity
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
data_classification_scan_status__contains	optional	Data classification scan status
data_classification_status__contains	optional	Data classification status

data_types__contains	optional	Data types contains
dataclassificationpolicystatus	optional	Data Classification Policy
dataclassificationscanstatus	optional	Data classification scan status to exclude
dataclassificationstatuses	optional	Data Classification Status
dataclassificationstatus__nin	optional	Data Classification Status (not in)
datatypes	optional	Data Types
datatypes__nin	optional	Data Types (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
ispublic	optional	Whether there is public access or not
ispublic__nin	optional	Whether there is public access or not (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
region	optional	The region

region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scannerstatus	optional	Scanner
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status

threatdetectionstatus_ _contains	optional	The threat detection status
threatdetectionstatus_ _nin	optional	Threat Detection Status (not in)
versioningenabled	optional	Whether there is versioning enabled or not

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Inventory Storage Filters

Filter counts

GET /web/api/v2.1/xdr/assets/storage/filters/count

Get filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)

cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
connectivitystatus	optional	Connectivity
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by

data_classification_scan_status__contains	optional	Data classification scan status
data_classification_status__contains	optional	Data classification status
data_types__contains	optional	Data types contains
dataclassificationpolicystatus	optional	Data Classification Policy
dataclassificationscanstatus	optional	Data classification scan status to exclude
dataclassificationstatuses	optional	Data Classification Status
dataclassificationstatus__nin	optional	Data Classification Status (not in)
datatypes	optional	Data Types
datatypes__nin	optional	Data Types (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
ispublic	optional	Whether there is public access or not
ispublic__nin	optional	Whether there is public access or not (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name

names__nin	optional	Name (not in)
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scannerstatus	optional	Scanner
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)

tagskeyvalue__nin	optional	Tags (not in)
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus_ _contains	optional	The threat detection status
threatdetectionstatus_ _nin	optional	Threat Detection Status (not in)
versioningenabled	optional	Whether there is versioning enabled or not

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/storage/filters/free-text

Get free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/storage/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
cloudprovideraccountid	optional	The cloud provider account id

cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
connectivitystatus	optional	Connectivity
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
data_classification_scan_status__contains	optional	Data classification scan status

data_classification_status__contains	optional	Data classification status
data_types__contains	optional	Data types contains
dataclassificationpolicystatus	optional	Data Classification Policy
dataclassificationscanstatus	optional	Data classification scan status to exclude
dataclassificationstatus	optional	Data Classification Status
dataclassificationstatus__nin	optional	Data Classification Status (not in)
datatypes	optional	Data Types
datatypes__nin	optional	Data Types (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
ispublic	optional	Whether there is public access or not
ispublic__nin	optional	Whether there is public access or not (not in)
limit	optional	Limit number of returned items
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)

objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
scannerstatus	optional	Scanner
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus_contains	optional	The threat detection status
threatdetectionstatus_nin	optional	Threat Detection Status (not in)
versioningenabled	optional	Whether there is versioning enabled or not

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Inventory Tags

Get asset tags filters count

GET /web/api/v2.1/xdr/assets/tags/filters-count

Get asset tags filters count

Parameters

accountids	optional	List of Account IDs to filter by
category	optional	The category that each resource belongs to
groupids	optional	List of Group IDs to filter by
includeparent	optional	Include parent
key__contains	optional	Free-text filter by tag key
query	optional	Query
readonly	optional	Read only
siteids	optional	List of Site IDs to filter by
source	optional	The source that tag belongs to
value__contains	optional	Free-text filter by tag value

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Fetch all Unique Tags

GET /web/api/v2.1/xdr/assets/tags

Fetch all tags removing duplicates

Parameters

accountids	optional	List of Account IDs to filter by
category	optional	The category that each resource belongs to
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
groupids	optional	List of Group IDs to filter by
includeparent	optional	Include parent
key__contains	optional	Free-text filter by tag key
limit	optional	Limit number of returned items (1-1000)
query	optional	Query
readonly	optional	Read only
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
source	optional	The source that tag belongs to
value__contains	optional	Free-text filter by tag value

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Fetch all Unique Tags - response - pagination table

Fetch all Unique Tags - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get count of assets by tag id

POST /web/api/v2.1/xdr/assets/tags/count

Get asset count for given tag ids

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Body Schema

Name	Description	Required	Value
tagIds	Tag ids	false	string []

Get tags info of assets by asset id

POST /web/api/v2.1/xdr/assets/fetch-tags

Get tags info for all assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
agentagentversion	optional	The agent version
agentantitamperingstatus	optional	The agent anti tampering status
agentconsoleconnectivity	optional	The agent console connectivity
agentidrconnectivity	optional	The agent idr connectivity
agentoperationalstate	optional	The agent operational state
agentpendingactions	optional	The agent pending actions
agentvssrollbackstatus	optional	The agent VSS rollback status
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)

assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
category	optional	The category that each resource belongs to
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value

cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__notin	optional	The cloud tags key value (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
devicereview	optional	The asset review
devicereview__notin	optional	The asset review (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
groupids	optional	List of Group IDs to filter by
id__contains	optional	The ID
id__in	optional	The ID
infectionstatus	optional	The status alerts of the asset
infectionstatus__notin	optional	The status alerts of the asset (not in)
limit	optional	Limit number of returned items (1-1000)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__notin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__notin	optional	Name (not in)
osfamily	optional	The operating system family of the device
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__notin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contain	optional	The Asset Type

s		
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Get tags info of assets by asset id - response - pagination table

Get tags info of assets by asset id - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
id__in	List of selected entity ids	false	object
id__nin	List of entity ids to exclude from select_all	false	object

Inventory Unified Actions

Get Available Actions by Asset/Entity Type

POST /web/api/v2.1/xdr/assets/actions/fetch-unified-actions

Get Available Actions by Asset/Entity Type

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agegroup	optional	Age Group
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigration	optional	The agent console migration status (not in)

status__nin		
agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type
agentdiskmetricsvolumetype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent Idr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user

agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentsubscribeondbetween	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshot	optional	The agent VSS last snapshot date

dt__between		
agentvssprotectionstatus	optional	The agent VSS protection status
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffareafreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP

n		Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
badpasswordtime__between	optional	Bad Password Time
classification	optional	Classification
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value

cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
cn	optional	The LDAP Common Name
cn__contains	optional	The LDAP Common Name
cn__nin	optional	The LDAP Common Name (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
deleted	optional	Whether the AD Entity is deleted or not
deletedtime__between	optional	Deleted Time
department	optional	Department
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
displayname__contains	optional	The Display Name
distinguishedname__contains	optional	The Distinguished Name
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
employeeetype	optional	Employee Type
enabled	optional	Whether the Identity Group is enabled or not

encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
entraidgrouptype	optional	Entra ID Group Type
entraidgrouptype__nin	optional	Entra ID Group Type (not in)
eppunsupportedunkn own	optional	The agent supported or unknown state
eppunsupportedunkno wn__nin	optional	The agent supported or unknown state (not in)
expirationtime__betw een	optional	Expiration Time
firstseendt__between	optional	The first seen date
forest	optional	The Forest Name
forest__contains	optional	The Forest Name
forest__nin	optional	The Forest Name (not in)
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contai ns	optional	The gateway MACs
givenname	optional	Given Name
givenname__contains	optional	Given Name
groupids	optional	List of Group IDs to filter by
grouptype	optional	The Group Type
grouptype__nin	optional	The Group Type (not in)
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__co ntains	optional	AD machine or its groups
identityadmachinedist inguishedname__conta ins	optional	AD machine DN
identityadmachinemem	optional	AD machine groups

bership__contains		
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
isrogues	optional	Whether the instance is a rogue or not
jobtitle	optional	Job Title
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name

k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8sresourceid	optional	The Kubernetes Resource ID
k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
last_modified_time__between	optional	Lock-out Time
lastactivedt__between	optional	The last active date
lastlogontime__between	optional	The Last time of User Login
lastupdatedt__between	optional	The last update date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
lockouttime__between	optional	Lock-out Time
macaddresses__contains	optional	The MAC addresses
mail	optional	The Email Address
mail__contains	optional	The Email Address
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer

manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
objectcategory	optional	The Object Category
objectcategory__nin	optional	The Object Category (not in)
objectclass	optional	The Object Class
objectclass__nin	optional	The Object Class (not in)
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
objectguid__contains	optional	The Object GUID
objectsid__contains	optional	The Object SID
onpremisesdistinguis hedname	optional	On Premises Distinguished Name
onpremisesdistinguis hedname__contains	optional	
onpremisesdomainna me	optional	On Premises Domain Name
onpremisesdomainnam e__contains	optional	On Premises Distinguished Name
onpremisesimmutablei d	optional	On Premises Immutable Id
onpremiseslastsyncti me__between	optional	On Premises Last Sync Time
onpremisesamaccou ntname	optional	On Premises SAM Account Name

onpremisesamaccountname__contains	optional	On Premises SAM Account Name
onpremisessecurityidentifier	optional	On Premises Security Identifier
onpremisessecurityidentifier__contains	optional	
onpremisesyncenabled	optional	On Premises Sync Enabled
onpremisesuserprincipalname	optional	On Premises User Principal Name
onpremisesuserprincipalname__contains	optional	On Premises User Principal Name
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
othermails	optional	Other Mails
othermails__contains	optional	Other Mails
passwordneverexpire	optional	Whether the password never expires
privileged	optional	Whether the AD Entity is privileged or not
proxyaddresses	optional	Proxy Addresses
proxyaddresses__contains	optional	Proxy Addresses
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)

rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
samaccountname	optional	The SAM Account Name
samaccountname__nin	optional	The SAM Account Name (not in)
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
securityenabled	optional	Security Enabled
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
serviceaccount	optional	The Service Account
serviceprincipalname__contains	optional	The Service Principal Name

siteids	optional	List of Site IDs to filter by
state	optional	The state of the instance
state__contains	optional	The state
state__nin	optional	The state of the instance (not in)
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
surname	optional	Surname
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus__contains	optional	The threat detection status
threatdetectionstatus__nin	optional	Threat Detection Status (not in)
udpports	optional	The UDP ports
uniquename	optional	Unique Name
useraccountcontrol	optional	The User Account Control
useraccountcontrol__n	optional	The User Account Control (not in)

in		
userpasswordexpirytimecomputed__between	optional	The User Password Expiry Time
userprincipalname	optional	The User Principal Name
userprincipalname__contains	optional	The User Principal Name
userprincipalname__notin	optional	The User Principal Name (not in)
visibility	optional	Visibility

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Get Available Actions by Asset/Entity Type - response - data table
errors	Errors	false	array

Get Available Actions by Asset/Entity Type - response - data

Name	Description	Required	Value
unifiedActions	Unified actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected entity ids	false	object
id__nin	List of entity ids to exclude from select_all	false	object

Perform an Action on selected assets/entities

POST /web/api/v2.1/xdr/assets/actions/perform-unified-action

Perform an Action on selected assets/entities

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agegroup	optional	Age Group
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)
agentcustomeridentifier__contains	optional	The customer identifier

agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfree percentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfree percentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfree percentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolume type	optional	The agent disk metrics volume type
agentdiskmetricsvolume type__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylast updateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent Idr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness

agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentsubscribeondbetween	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionstatus	optional	The agent VSS protection status
agentvssprotectionstatus	optional	The agent VSS protection status (not in)

tus__nin		
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffareafreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
badpasswordtime__be	optional	Bad Password Time

tween		
classification	optional	Classification
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
cn	optional	The LDAP Common Name

cn__contains	optional	The LDAP Common Name
cn__nin	optional	The LDAP Common Name (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
deleted	optional	Whether the AD Entity is deleted or not
deletedtime__between	optional	Deleted Time
department	optional	Department
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
displayname__contains	optional	The Display Name
distinguishedname__contains	optional	The Distinguished Name
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
employeetype	optional	Employee Type
enabled	optional	Whether the Identity Group is enabled or not
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
entraidgrouptype	optional	Entra ID Group Type
entraidgrouptype__nin	optional	Entra ID Group Type (not in)
eppunsupportedunkn	optional	The agent supported or unknown state

own		
eppunsupportedunknow wn__nin	optional	The agent supported or unknown state (not in)
expirationtime__betw een	optional	Expiration Time
firstseendt__between	optional	The first seen date
forest	optional	The Forest Name
forest__contains	optional	The Forest Name
forest__nin	optional	The Forest Name (not in)
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contai ns	optional	The gateway MACs
givenname	optional	Given Name
givenname__contains	optional	Given Name
groupids	optional	List of Group IDs to filter by
grouptype	optional	The Group Type
grouptype__nin	optional	The Group Type (not in)
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__co ntains	optional	AD machine or its groups
identityadmachinedist inguishedname__conta ins	optional	AD machine DN
identityadmachinemem bership__contains	optional	AD machine groups
identityaduser__contai ns	optional	AD user or their groups
identityaduserdisting uishedname__contains	optional	AD user DN

identityadusermembership__contains	optional	AD user groups
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
isrogues	optional	Whether the instance is a rogue or not
jobtitle	optional	Job Title
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8sresourceid	optional	The Kubernetes Resource ID

k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
last_modified_time__between	optional	Lock-out Time
lastactivedt__between	optional	The last active date
lastlogontime__between	optional	The Last time of User Login
lastupdatedt__between	optional	The last update date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
lockouttime__between	optional	Lock-out Time
macaddresses__contains	optional	The MAC addresses
mail	optional	The Email Address
mail__contains	optional	The Email Address
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset

missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
objectcategory	optional	The Object Category
objectcategory__nin	optional	The Object Category (not in)
objectclass	optional	The Object Class
objectclass__nin	optional	The Object Class (not in)
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
objectguid__contains	optional	The Object GUID
objectsid__contains	optional	The Object SID
onpremisesdistinguis hedname	optional	On Premises Distinguished Name
onpremisesdistinguis hedname__contains	optional	
onpremisesdomainna me	optional	On Premises Domain Name
onpremisesdomainnam e__contains	optional	On Premises Distinguished Name
onpremisesimmutablei d	optional	On Premises Immutable Id
onpremiseslastsyncti me__between	optional	On Premises Last Sync Time
onpremisesamaccou ntname	optional	On Premises SAM Account Name
onpremisesamaccoun tname__contains	optional	On Premises SAM Account Name
onpremisessecurityiden tifier	optional	On Premises Security Identifier

onpremisessecurityidentifier__contains	optional	
onpremisesyncenabled	optional	On Premises Sync Enabled
onpremisesuserprincipalname	optional	On Premises User Principal Name
onpremisesuserprincipalname__contains	optional	On Premises User Principal Name
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
othermails	optional	Other Mails
othermails__contains	optional	Other Mails
passwordneverexpire	optional	Whether the password never expires
privileged	optional	Whether the AD Entity is privileged or not
proxyaddresses	optional	Proxy Addresses
proxyaddresses__contains	optional	Proxy Addresses
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)

rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
samaccountname	optional	The SAM Account Name
samaccountname__nin	optional	The SAM Account Name (not in)
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
securityenabled	optional	Security Enabled
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
serviceaccount	optional	The Service Account
serviceprincipalname__contains	optional	The Service Principal Name
siteids	optional	List of Site IDs to filter by
state	optional	The state of the instance
state__contains	optional	The state
state__nin	optional	The state of the instance (not in)

subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
surname	optional	Surname
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus__contains	optional	The threat detection status
threatdetectionstatus__nin	optional	Threat Detection Status (not in)
udpports	optional	The UDP ports
uniquename	optional	Unique Name
useraccountcontrol	optional	The User Account Control
useraccountcontrol__nin	optional	The User Account Control (not in)
userpasswordexpirytimecomputed__between	optional	The User Password Expiry Time
userprincipalname	optional	The User Principal Name

userprincipalname__contains	optional	The User Principal Name
userprincipalname__nin	optional	The User Principal Name (not in)
visibility	optional	Visibility

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionPath	Action path	true	string
id__in	List of selected entity ids	false	object
id__nin	List of entity ids to exclude from select_all	false	object
payload	Payload	false	

Loads all agent ids for the unified actions

POST /web/api/v2.1/xdr/assets/actions/fetch-agent-ids

Loads all agent ids for the unified actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agegroup	optional	Age Group
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)
agentcustomeridentifier__contains	optional	The customer identifier

agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfree percentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfree percentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfree percentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolume type	optional	The agent disk metrics volume type
agentdiskmetricsvolume type__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylast updateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent Idr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness

agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentsubscribeondbetween	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionstatus	optional	The agent VSS protection status
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)

tus__nin		
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffareafreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
badpasswordtime__be	optional	Bad Password Time

tween		
classification	optional	Classification
cloudprovideraccountid	optional	The cloud provider account id
cloudprovideraccountid__contains	optional	The cloud provider account ID
cloudprovideraccountid__nin	optional	The cloud provider account id (not in)
cloudprovideraccountname	optional	The cloud provider account name
cloudprovideraccountname__contains	optional	The cloud provider account name
cloudprovideraccountname__nin	optional	The cloud provider account name (not in)
cloudproviderorganization__contains	optional	The cloud provider organization
cloudproviderorganizationunit__contains	optional	The cloud provider organization unit
cloudproviderprojectid__contains	optional	The cloud provider project ID
cloudprovidersubscriptionid__contains	optional	The cloud provider subscription ID
cloudresourceid__contains	optional	The cloud resource ID
cloudtagskey	optional	The cloud tags key
cloudtagskey__contains	optional	Free-text filter by cloud tag key (supports multiple values)
cloudtagskey__nin	optional	The cloud tags key (not in)
cloudtagskeyvalue	optional	The cloud tags key value
cloudtagskeyvalue__contains	optional	Free-text filter by cloud tag key value (supports multiple values)
cloudtagskeyvalue__nin	optional	The cloud tags key value (not in)
cn	optional	The LDAP Common Name

cn__contains	optional	The LDAP Common Name
cn__nin	optional	The LDAP Common Name (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
deleted	optional	Whether the AD Entity is deleted or not
deletedtime__between	optional	Deleted Time
department	optional	Department
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
displayname__contains	optional	The Display Name
distinguishedname__contains	optional	The Distinguished Name
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
employeetype	optional	Employee Type
enabled	optional	Whether the Identity Group is enabled or not
encryptiontype	optional	The encryption type
encryptiontype__nin	optional	The encryption type (not in)
entraidgrouptype	optional	Entra ID Group Type
entraidgrouptype__nin	optional	Entra ID Group Type (not in)
eppunsupportedunkn	optional	The agent supported or unknown state

own		
eppunsupportedunknow wn__nin	optional	The agent supported or unknown state (not in)
expirationtime__betw een	optional	Expiration Time
firstseendt__between	optional	The first seen date
forest	optional	The Forest Name
forest__contains	optional	The Forest Name
forest__nin	optional	The Forest Name (not in)
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contai ns	optional	The gateway MACs
givenname	optional	Given Name
givenname__contains	optional	Given Name
groupids	optional	List of Group IDs to filter by
grouptype	optional	The Group Type
grouptype__nin	optional	The Group Type (not in)
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__co ntains	optional	AD machine or its groups
identityadmachinedist inguishedname__conta ins	optional	AD machine DN
identityadmachinemem bership__contains	optional	AD machine groups
identityaduser__contai ns	optional	AD user or their groups
identityaduserdisting uishedname__contains	optional	AD user DN

identityadusermembership__contains	optional	AD user groups
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
isrogues	optional	Whether the instance is a rogue or not
jobtitle	optional	Job Title
k8sannotationsunifiedkey__contains	optional	Free-text filter by Kubernetes Annotations key (supports multiple values)
k8sannotationsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Annotations key value (supports multiple values)
k8scluster	optional	The Kubernetes Cluster
k8scluster__contains	optional	The Kubernetes cluster
k8scluster__nin	optional	The Kubernetes Cluster (not in)
k8sclusterid	optional	The Kubernetes Cluster ID
k8sclusterid__contains	optional	Kubernetes Cluster ID
k8slabelsunifiedkey__contains	optional	Free-text filter by Kubernetes Labels key (supports multiple values)
k8slabelsunifiedkeyvalue__contains	optional	Free-text filter by Kubernetes Labels key value (supports multiple values)
k8snamespace	optional	The Kubernetes Namespace Name
k8snamespace__contains	optional	Namespace Name
k8snode	optional	The Kubernetes Node
k8snode__contains	optional	The Kubernetes node
k8snode__nin	optional	The Kubernetes Node (not in)
k8sresourceid	optional	The Kubernetes Resource ID

k8sresourceid__contains	optional	Kubernetes Resource ID
k8srunningonnodes	optional	Running on Nodes
k8srunningonnodes__contains	optional	Running on nodes
k8stype	optional	The Kubernetes Type
k8stype__nin	optional	The Kubernetes Type (not in)
k8sversion	optional	The Kubernetes Version
k8sversion__nin	optional	The Kubernetes Version (not in)
last_modified_time__between	optional	Lock-out Time
lastactivedt__between	optional	The last active date
lastlogontime__between	optional	The Last time of User Login
lastupdatedt__between	optional	The last update date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
lockouttime__between	optional	Lock-out Time
macaddresses__contains	optional	The MAC addresses
mail	optional	The Email Address
mail__contains	optional	The Email Address
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset

missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
objectcategory	optional	The Object Category
objectcategory__nin	optional	The Object Category (not in)
objectclass	optional	The Object Class
objectclass__nin	optional	The Object Class (not in)
objectcount	optional	The number of objects in the bucket
objectcount__nin	optional	The number of objects in the bucket (not in)
objectguid__contains	optional	The Object GUID
objectsid__contains	optional	The Object SID
onpremisesdistinguis hedname	optional	On Premises Distinguished Name
onpremisesdistinguis hedname__contains	optional	
onpremisesdomainna me	optional	On Premises Domain Name
onpremisesdomainnam e__contains	optional	On Premises Distinguished Name
onpremisesimmutablei d	optional	On Premises Immutable Id
onpremiseslastsyncti me__between	optional	On Premises Last Sync Time
onpremisesamaccou ntname	optional	On Premises SAM Account Name
onpremisesamaccoun tname__contains	optional	On Premises SAM Account Name
onpremisessecurityiden tifier	optional	On Premises Security Identifier

onpremisessecurityidentifier__contains	optional	
onpremisesyncenabled	optional	On Premises Sync Enabled
onpremisesuserprincipalname	optional	On Premises User Principal Name
onpremisesuserprincipalname__contains	optional	On Premises User Principal Name
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
othermails	optional	Other Mails
othermails__contains	optional	Other Mails
passwordneverexpire	optional	Whether the password never expires
privileged	optional	Whether the AD Entity is privileged or not
proxyaddresses	optional	Proxy Addresses
proxyaddresses__contains	optional	Proxy Addresses
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)

rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
region	optional	The region
region__contains	optional	The geographical area where cloud resources are hosted
region__nin	optional	The region (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
samaccountname	optional	The SAM Account Name
samaccountname__nin	optional	The SAM Account Name (not in)
scanstatus	optional	The CDS malware scan status
scanstatus__contains	optional	The CDS malware scan status
scanstatus__nin	optional	The CDS malware scan status (not in)
securityenabled	optional	Security Enabled
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
serviceaccount	optional	The Service Account
serviceprincipalname__contains	optional	The Service Principal Name
siteids	optional	List of Site IDs to filter by
state	optional	The state of the instance
state__contains	optional	The state
state__nin	optional	The state of the instance (not in)

subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
surname	optional	Surname
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
threatdetectionpolicystatus	optional	Threat Detection Policy
threatdetectionstatus	optional	Threat Detection Status
threatdetectionstatus__contains	optional	The threat detection status
threatdetectionstatus__nin	optional	Threat Detection Status (not in)
udpports	optional	The UDP ports
uniquename	optional	Unique Name
useraccountcontrol	optional	The User Account Control
useraccountcontrol__nin	optional	The User Account Control (not in)
userpasswordexpirytimecomputed__between	optional	The User Password Expiry Time
userprincipalname	optional	The User Principal Name

userprincipalname__contains	optional	The User Principal Name
userprincipalname__notin	optional	The User Principal Name (not in)
visibility	optional	Visibility

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Loads all agent ids for the unified actions - response - data table
errors	Errors	false	array

Loads all agent ids for the unified actions - response - data

Name	Description	Required	Value
agentIds	Agent ids	false	string []

Body Schema

Name	Description	Required	Value
id__in	List of selected entity ids	false	object
id__nin	List of entity ids to exclude from select_all	false	object

Inventory Workstation

Filter counts

GET /web/api/v2.1/xdr/assets/workstation/filters/count

Get workstation filter counts

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)

agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type
agentdiskmetricsvolumetype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent Idr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)

agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentssubscribeondt__between	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionsta	optional	The agent VSS protection status

tus		
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdifferfreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset

assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups

identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
lastactivedt__between	optional	The last active date
lastupdatedt__between	optional	The last update date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)

missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)

riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Free text filters

GET /web/api/v2.1/xdr/assets/workstation/filters/free-text

Get Workstation free text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array

Auto Complete

GET /web/api/v2.1/xdr/assets/workstation/filters/autocomplete

Use this command to get values for other fields. When you send this command with input text and a field name, it returns auto-complete suggestions for the field.

Parameters

key	required	Search field key
text	required	Search term text
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)
agentcustomeridentifi	optional	The customer identifier

er__contains		
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfree percentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfree percentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfree percentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolume type	optional	The agent disk metrics volume type
agentdiskmetricsvolume type__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylast updateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent ldr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)

agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentssubscribeondt__between	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionsta	optional	The agent VSS protection status

tus		
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffareafreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset

assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups

identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
lastactivedt__between	optional	The last active date
lastupdatedt__between	optional	The last update date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
limit	optional	Limit number of returned items
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format

memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type

resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Auto Complete - response - data table
errors	Errors	false	array

Auto Complete - response - data

Name	Description	Required	Value
key	Filter argument key	false	string
title	Filter description	false	string
values	Auto complete values	false	undefined []

Assets

GET /web/api/v2.1/xdr/assets/workstation

Get inventory workstation assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity

ity		
agentconsolemigration status	optional	The agent console migration status
agentconsolemigration status__nin	optional	The agent console migration status (not in)
agentcustomeridentifi er__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfree percentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreep ercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreep ercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolu metype	optional	The agent disk metrics volume type
agentdiskmetricsvolu metype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__ nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivityl astupdateddt__betwe en	optional	The SDL connectivity last active
agentfulldiskscandt__ between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__ni n	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent ldr connectivity
agentinstallertype	optional	The agent installer type

agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentsubscribeondt__between	optional	The agent subscribe time

agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshot dt__between	optional	The agent VSS last snapshot date
agentvssprotectionsta tus	optional	The agent VSS protection status
agentvssprotectionsta tus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus __nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus_ _nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffa reafreepercentage__b etween	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__ni n	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to

assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs

gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
lastactivedt__between	optional	The last active date
lastupdatedt__between	optional	The last update date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyn	optional	Legacy Identity Policy Name

ame		
limit	optional	Limit number of returned items (1-1000)
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)

ntains		
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.
sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys

tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets - response - pagination table

Assets - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Assets using POST

POST /web/api/v2.1/xdr/assets/workstation

POST API to get workstation assets

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
errors	Errors	false	array
pagination		false	see Assets using POST - response - pagination table

Assets using POST - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Body Schema

Name	Description	Required	Value
data		false	see Assets using POST - body - data table
filter		false	see Assets using POST - body - filter table

Assets using POST - body - data

Assets using POST - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeCoverage	The active coverage for the asset	false	string []
activeCoverage__nin	The active coverage for the asset (not in)	false	string []
adsEnabled	ADS Enabled	false	boolean []
agentAgentVersion	The agent version	false	string []
agentAgentVersion__contains	The agent version	false	string []
agentAgentVersion__nin	The agent version (not in)	false	string []
agentAntiTamperingStatus	The agent anti tampering status	false	string []
agentAntiTamperingStatus__nin	The agent anti tampering status (not in)	false	string []
agentConfigurableNetworkQuarantine	Whether the agent can configure network quarantine	false	boolean []
agentConfigurableNetworkQuarantine__nin	Whether the agent can configure network quarantine (not in)	false	boolean []
agentConsoleConnectivity	The agent console connectivity	false	boolean []
agentConsoleMigrationStatus	The agent console migration status	false	string []
agentConsoleMigrationStatus__nin	The agent console migration status (not in)	false	string []
agentCustomerIdIdentifier__contains	The customer identifier	false	string []
agentDecommissioned	Whether the agent is decommissioned	false	boolean []
agentDiskEncryption	The agent disk encryption	false	boolean []
agentDiskMetricsFreePercentage__between	The agent free disk percentage on any of the disks	false	string
agentDiskMetricsFreePercentage__gte	The agent free disk percentage on any of the disks	false	number

agentDiskMetricsFreePercentage__lte	The agent free disk percentage on any of the disks	false	number
agentDiskMetricsVolumeType	The agent disk metrics volume type	false	string []
agentDiskMetricsVolumeType__nin	The agent disk metrics volume type (not in)	false	string []
agentDvConnectivity	The connection status between the agent and the SDL service	false	string []
agentDvConnectivity__nin	The connection status between the agent and the SDL service (not in)	false	string []
agentDvConnectivityLastUpdatedDt__between	The SDL connectivity last active	false	string
agentFullDiskScanDt__between	The agent full disk scan date	false	string
agentHasLocalConfig	Whether the agent has local configuration	false	boolean []
agentHealthStatus	The agent health status	false	string []
agentHealthStatus__nin	The agent health status (not in)	false	string []
agentIldrConnectivity	The agent Ildr connectivity	false	boolean []
agentInstallerType	The agent installer type	false	string []
agentInstallerType__nin	The agent installer type (not in)	false	string []
agentLastLoggedInUser__contains	The last logged in user	false	string []
agentLocation	The agent location	false	string []
agentLocation__nin	The agent location (not in)	false	string []
agentLocationAwareness__contains	The location awareness	false	string []
agentMissingPermissions	The agent missing permissions	false	string []
agentMissingPermissions__nin	The agent missing permissions (not in)	false	string []
agentNetworkStatus	The agent network status	false	string []
agentNetworkStatus__nin	The agent network status (not in)	false	string []
agentOperationalState	The agent operational state	false	string []
agentOperationalState__nin	The agent operational state (not in)	false	string []
agentPendingActions	The agent pending actions	false	string []
agentPendingActions__nin	The agent pending actions (not in)	false	string []
agentPendingUninstall	Whether the agent is pending uninstall	false	boolean []
agentPendingUpgrade	Whether the agent is pending upgrade	false	boolean []

agentRangerStatus	The agent network scanner status	false	string []
agentRangerStatus__nin	The agent network scanner status (not in)	false	string []
agentRangerVersion	The agent network scanner version	false	string []
agentRangerVersion__nin	The agent network scanner version (not in)	false	string []
agentS1AgentLiveUpdatesVersion__contains	Live update ID	false	string []
agentSubscribeOnDt__between	The agent subscribe time	false	string
agentUninstalled	Whether the agent is uninstalled	false	boolean []
agentUuid	Match by the agent UUID	false	string []
agentUuid__contains	The UUID	false	string []
agentVssLastSnapshotDt__between	The agent VSS last snapshot date	false	string
agentVssProtectionStatus	The agent VSS protection status	false	string []
agentVssProtectionStatus__nin	The agent VSS protection status (not in)	false	string []
agentVssRollbackStatus	The agent VSS rollback status	false	string []
agentVssRollbackStatus__nin	The agent VSS rollback status (not in)	false	string []
agentVssServiceStatus	The agent VSS service status	false	string []
agentVssServiceStatus__nin	The agent VSS service status (not in)	false	string []
agentVssVolumesDiffAreaFreePercentage__between	The agent free VSS volume percentage on any of the volumes	false	string
alertSeverity	The severity of the alert	false	string []
allTagsKey	User and cloud tag keys	false	string []
allTagsKey__exists	User and cloud tag keys exists	false	string []
allTagsKey__nexists	User and cloud tag keys not exists	false	string []
allTagsKey__nin	User and cloud tag keys (not in)	false	string []
allTagsKeyValue	User and cloud tags	false	string []
allTagsKeyValue__nin	User and cloud tags (not in)	false	string []
applicationName	The name of the application installed on a workstation or a server	false	string []
architecture	The architecture of the device	false	string []
architecture__nin	The architecture of the device (not in)	false	string []
assetContactEmail	Asset Contact Email	false	string []

assetContactEmail__nin	Asset Contact Email (not in)	false	string []
assetCriticality	The criticality that each asset belongs to	false	string []
assetCriticality__nin	The criticality that each asset belongs to (not in)	false	string []
assetEnvironment	The environment that the asset exists in - AWS Azure GCP Active Directory	false	string []
assetEnvironment__nin	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)	false	string []
assetStatus	The status of the asset	false	string []
assetStatus__nin	The status of the asset (not in)	false	string []
coreCount	The number of cores	false	integer []
coreCount__nin	The number of cores (not in)	false	integer []
countOnly	If true, only total number of items will be returned, without any of the actual objects.	false	boolean
countsFor	The columns for which filter count would be returned for	false	string []
cpu__contains	The CPU	false	string []
csvFilterId	The ID of the CSV file to filter by	false	integer
cursor	Cursor position returned by the last request. Use to iterate over more than 1000 items.	false	string
detectedFromSite	The site from which the device was detected	false	string []
detectedFromSite__nin	The site from which the device was detected (not in)	false	string []
deviceReview	The asset review	false	string []
deviceReview__nin	The asset review (not in)	false	string []
discoveryMethods	The discovery methods	false	string []
discoveryMethods__nin	The discovery methods (not in)	false	string []
domain	The domain of the device	false	string []
domain__contains	The domain	false	string []
domain__nin	The domain of the device (not in)	false	string []

eppUnsupportedUnknown	The agent supported or unknown state	false	string []
eppUnsupportedUnknown__nin	The agent supported or unknown state (not in)	false	string []
firstSeenDt__between	The first seen date	false	string
gatewayIps__contains	The gateway IPs	false	string []
gatewayMacs__contains	The gateway MACs	false	string []
groupIds	List of Group IDs to filter by	false	string []
hostnames__contains	The hostnames	false	string []
id__contains	The ID	false	string []
id__in	The ID	false	string []
identityAd__contains	Any AD string	false	string []
identityAdMachine__contains	AD machine or its groups	false	string []
identityAdMachineDistinguishedName__contains	AD machine DN	false	string []
identityAdMachineMembership__contains	AD machine groups	false	string []
identityAdUser__contains	AD user or their groups	false	string []
identityAdUserDistinguishedName__contains	AD user DN	false	string []
identityAdUserMembership__contains	AD user groups	false	string []
imageName__contains	Free-text filter by the image name	false	string []
infectionStatus	The status alerts of the asset	false	string []
infectionStatus__nin	The status alerts of the asset (not in)	false	string []
internalIps__contains	The internal IPs	false	string []
ipAddress__contains	The IP addresses	false	string []
isAdConnector	Is AD Connector	false	boolean []
isDcServer	Is DC Server	false	boolean []
lastActiveDt__between	The last active date	false	string
lastUpdateDt__between	The last update date	false	string
legacy_identity_policy_name__contains	The legacy identity policy name	false	string []
legacyIdentityPolicyName	Legacy Identity Policy Name	false	string []

limit	Limit number of returned items (1-1000)	false	integer
macAddresses__contains	The MAC addresses	false	string []
manufacturer	The manufacturer of the device	false	string []
manufacturer__contains	The manufacturer	false	string []
manufacturer__nin	The manufacturer of the device (not in)	false	string []
memoryReadable	The memory of the device in human readable format	false	string []
memoryReadable__nin	The memory of the device in human readable format (not in)	false	string []
missingCoverage	The missing coverage for the asset	false	string []
missingCoverage__nin	The missing coverage for the asset (not in)	false	string []
name__contains	The name	false	string []
names	Name	false	string []
names__nin	Name (not in)	false	string []
networkName	The network name	false	string []
networkName__nin	The network name (not in)	false	string []
os	The operating system of the device	false	string []
os__nin	The operating system of the device (not in)	false	string []
osFamily	The operating system family of the device	false	string []
osFamily__nin	The operating system family of the device (not in)	false	string []
osNameVersion	The operating system name and version of the device	false	string []
osNameVersion__contains	The OS names and versions	false	string []
osNameVersion__nin	The operating system name and version of the device (not in)	false	string []
osVersion	The operating system version of the device	false	string []
osVersion__contains	The OS versions	false	string []
osVersion__nin	The operating system version of the device (not in)	false	string []

rangerTagKey__contains	Free-text filter by Ranger tag key (supports multiple values)	false	string []
rangerTagKeyValue__contains	Free-text filter by Ranger tag key value (supports multiple values)	false	string []
rangerTagsKey	The ranger tags key	false	string []
rangerTagsKey__nin	The ranger tags key (not in)	false	string []
rangerTagsKeyValue	The ranger tags key value	false	string []
rangerTagsKeyValue__nin	The ranger tags key value (not in)	false	string []
resourceType	The canonical name for the resource type	false	string []
resourceType__contains	The Asset Type	false	string []
resourceType__nin	The canonical name for the resource type (not in)	false	string []
riskFactors	The risk factors associated with the asset	false	string []
riskFactors__nin	The risk factors associated with the asset (not in)	false	string []
s1UpdatedAt__between	The Last Seen date and time for the asset	false	string
serialNumber	The serial number	false	string []
serialNumber__contains	The serial number	false	string []
serialNumber__nin	The serial number (not in)	false	string []
sitelds	List of Site IDs to filter by	false	string []
skip	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".	false	integer
skipCount	If true, total number of items will not be calculated, which speeds up execution time.	false	boolean
sortBy	The column to sort the results by.	false	enum
sortOrder	Sort direction	false	enum
subCategory	The sub-category that each resource belongs to	false	string []
subCategory__nin	The sub-category that each resource belongs to (not in)	false	string []
subnets__contains	The subnets	false	string []

surfaces	The Surface that each asset belongs to	false	string []
surfaces__nin	The Surface that each asset belongs to (not in)	false	string []
tagsKey	Tag Keys	false	string []
tagsKey__contains	Free-text filter by tag key (supports multiple values)	false	string []
tagsKey__exists	Tag Keys exists	false	string []
tagsKey__nexists	Tag Keys not exists	false	string []
tagsKey__nin	Tag Keys (not in)	false	string []
tagsKeyValue	Tags	false	string []
tagsKeyValue__contains	Free-text filter by tag key value (supports multiple values)	false	string []
tagsKeyValue__nin	Tags (not in)	false	string []
tcpPorts	The TCP ports	false	string []
udpPorts	The UDP ports	false	string []

Export assets to CSV or JSON

GET /web/api/v2.1/xdr/assets/workstation/export

Returns the results for given inventory filter in a CSV or JSON format

Parameters

exportformat	required	Export format
accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)

agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)
agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type
agentdiskmetricsvolumetype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active

agentfuldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent ldr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)

n		
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentsubscribeondt__between	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionstatus	optional	The agent VSS protection status
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffareafreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)

applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items.
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device

domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunkn own	optional	The agent supported or unknown state
eppunsupportedunkno wn__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contai ns	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__co ntains	optional	AD machine or its groups
identityadmachinedist inguishedname__conta ins	optional	AD machine DN
identityadmachinemem bership__contains	optional	AD machine groups
identityaduser__contai ns	optional	AD user or their groups
identityaduserdisting uishedname__contains	optional	AD user DN
identityadusermember ship__contains	optional	AD user groups
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses

isadconnector	optional	Is AD Connector
isdcservice	optional	Is DC Server
lastactivedt__between	optional	The last active date
lastupdatedt__between	optional	The last update date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
limit	optional	Limit number of returned items (1-1000)
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions

ins		
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by.

sortorder	optional	Sort direction
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Perform action

POST /web/api/v2.1/xdr/assets/workstation/action

Perform action on selected assets

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)
agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned
agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolume	optional	The agent disk metrics volume type

metype		
agentdiskmetricsvolume__metype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscan__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent Idr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state

agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentsubscribeondt__between	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionstatus	optional	The agent VSS protection status
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)
agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffa	optional	The agent free VSS volume percentage on any of the volumes

reafreepercentage__between		
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)
countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review

devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemembership__contains	optional	AD machine groups
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups

imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcservice	optional	Is DC Server
lastactivedt__between	optional	The last active date
lastupdatedt__between	optional	The last update date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name
names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)

osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to

subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
actionName	Action name	true	enum
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Available actions

POST /web/api/v2.1/xdr/assets/workstation/available-actions/with-status

Get inventory workstation available actions

Parameters

accountids	optional	List of Account IDs to filter by
activecoverage	optional	The active coverage for the asset
activecoverage__nin	optional	The active coverage for the asset (not in)
adsenabled	optional	ADS Enabled
agentagentversion	optional	The agent version
agentagentversion__contains	optional	The agent version
agentagentversion__nin	optional	The agent version (not in)
agentantitamperingstatus	optional	The agent anti tampering status
agentantitamperingstatus__nin	optional	The agent anti tampering status (not in)
agentconfigurablenetworkquarantine	optional	Whether the agent can configure network quarantine
agentconfigurablenetworkquarantine__nin	optional	Whether the agent can configure network quarantine (not in)
agentconsoleconnectivity	optional	The agent console connectivity
agentconsolemigrationstatus	optional	The agent console migration status
agentconsolemigrationstatus__nin	optional	The agent console migration status (not in)
agentcustomeridentifier__contains	optional	The customer identifier
agentdecommissioned	optional	Whether the agent is decommissioned

agentdiskencryption	optional	The agent disk encryption
agentdiskmetricsfreepercentage__between	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__gte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsfreepercentage__lte	optional	The agent free disk percentage on any of the disks
agentdiskmetricsvolumetype	optional	The agent disk metrics volume type
agentdiskmetricsvolumetype__nin	optional	The agent disk metrics volume type (not in)
agentdvconnectivity	optional	The connection status between the agent and the SDL service
agentdvconnectivity__nin	optional	The connection status between the agent and the SDL service (not in)
agentdvconnectivitylastupdateddt__between	optional	The SDL connectivity last active
agentfulldiskscandt__between	optional	The agent full disk scan date
agenthaslocalconfig	optional	Whether the agent has local configuration
agenthealthstatus	optional	The agent health status
agenthealthstatus__nin	optional	The agent health status (not in)
agentidrconnectivity	optional	The agent ldr connectivity
agentinstallertype	optional	The agent installer type
agentinstallertype__nin	optional	The agent installer type (not in)
agentlastloggedinuser__contains	optional	The last logged in user
agentlocation	optional	The agent location
agentlocation__nin	optional	The agent location (not in)
agentlocationawareness__contains	optional	The location awareness
agentmissingpermissions	optional	The agent missing permissions

ns		
agentmissingpermissions__nin	optional	The agent missing permissions (not in)
agentnetworkstatus	optional	The agent network status
agentnetworkstatus__nin	optional	The agent network status (not in)
agentoperationalstate	optional	The agent operational state
agentoperationalstate__nin	optional	The agent operational state (not in)
agentpendingactions	optional	The agent pending actions
agentpendingactions__nin	optional	The agent pending actions (not in)
agentpendinguninstall	optional	Whether the agent is pending uninstall
agentpendingupgrade	optional	Whether the agent is pending upgrade
agentrangerstatus	optional	The agent network scanner status
agentrangerstatus__nin	optional	The agent network scanner status (not in)
agentrangerversion	optional	The agent network scanner version
agentrangerversion__nin	optional	The agent network scanner version (not in)
agents1agentliveupdatesversion__contains	optional	Live update ID
agentsubscribeondbetween	optional	The agent subscribe time
agentuninstalled	optional	Whether the agent is uninstalled
agentuuid	optional	Match by the agent UUID
agentuuid__contains	optional	The UUID
agentvsslastsnapshotdt__between	optional	The agent VSS last snapshot date
agentvssprotectionstatus	optional	The agent VSS protection status
agentvssprotectionstatus__nin	optional	The agent VSS protection status (not in)

agentvssrollbackstatus	optional	The agent VSS rollback status
agentvssrollbackstatus__nin	optional	The agent VSS rollback status (not in)
agentvssservicestatus	optional	The agent VSS service status
agentvssservicestatus__nin	optional	The agent VSS service status (not in)
agentvssvolumesdiffareafreepercentage__between	optional	The agent free VSS volume percentage on any of the volumes
alertseverity	optional	The severity of the alert
alltagskey	optional	User and cloud tag keys
alltagskey__exists	optional	User and cloud tag keys exists
alltagskey__nexists	optional	User and cloud tag keys not exists
alltagskey__nin	optional	User and cloud tag keys (not in)
alltagskeyvalue	optional	User and cloud tags
alltagskeyvalue__nin	optional	User and cloud tags (not in)
applicationname	optional	The name of the application installed on a workstation or a server
architecture	optional	The architecture of the device
architecture__nin	optional	The architecture of the device (not in)
assetcontactemail	optional	Asset Contact Email
assetcontactemail__nin	optional	Asset Contact Email (not in)
assetcriticality	optional	The criticality that each asset belongs to
assetcriticality__nin	optional	The criticality that each asset belongs to (not in)
assetenvironment	optional	The environment that the asset exists in - AWS Azure GCP Active Directory
assetenvironment__nin	optional	The environment that the asset exists in - AWS Azure GCP Active Directory (not in)
assetstatus	optional	The status of the asset
assetstatus__nin	optional	The status of the asset (not in)
corecount	optional	The number of cores
corecount__nin	optional	The number of cores (not in)

countsfor	optional	The columns for which filter count would be returned for
cpu__contains	optional	The CPU
csvfilterid	optional	The ID of the CSV file to filter by
detectedfromsite	optional	The site from which the device was detected
detectedfromsite__nin	optional	The site from which the device was detected (not in)
devicereview	optional	The asset review
devicereview__nin	optional	The asset review (not in)
discoverymethods	optional	The discovery methods
discoverymethods__nin	optional	The discovery methods (not in)
domain	optional	The domain of the device
domain__contains	optional	The domain
domain__nin	optional	The domain of the device (not in)
eppunsupportedunknown	optional	The agent supported or unknown state
eppunsupportedunknown__nin	optional	The agent supported or unknown state (not in)
firstseendt__between	optional	The first seen date
gatewayips__contains	optional	The gateway IPs
gatewaymacs__contains	optional	The gateway MACs
groupids	optional	List of Group IDs to filter by
hostnames__contains	optional	The hostnames
id__contains	optional	The ID
id__in	optional	The ID
identityad__contains	optional	Any AD string
identityadmachine__contains	optional	AD machine or its groups
identityadmachinedistinguishedname__contains	optional	AD machine DN
identityadmachinemem	optional	AD machine groups

bership__contains		
identityaduser__contains	optional	AD user or their groups
identityaduserdistinguishedname__contains	optional	AD user DN
identityadusermembership__contains	optional	AD user groups
imagename__contains	optional	Free-text filter by the image name
infectionstatus	optional	The status alerts of the asset
infectionstatus__nin	optional	The status alerts of the asset (not in)
internalips__contains	optional	The internal IPs
ipaddress__contains	optional	The IP addresses
isadconnector	optional	Is AD Connector
isdcserver	optional	Is DC Server
lastactivedt__between	optional	The last active date
lastupdatedt__between	optional	The last update date
legacy_identity_policy_name__contains	optional	The legacy identity policy name
legacyidentitypolicyname	optional	Legacy Identity Policy Name
macaddresses__contains	optional	The MAC addresses
manufacturer	optional	The manufacturer of the device
manufacturer__contains	optional	The manufacturer
manufacturer__nin	optional	The manufacturer of the device (not in)
memoryreadable	optional	The memory of the device in human readable format
memoryreadable__nin	optional	The memory of the device in human readable format (not in)
missingcoverage	optional	The missing coverage for the asset
missingcoverage__nin	optional	The missing coverage for the asset (not in)
name__contains	optional	The name

names	optional	Name
names__nin	optional	Name (not in)
networkname	optional	The network name
networkname__nin	optional	The network name (not in)
os	optional	The operating system of the device
os__nin	optional	The operating system of the device (not in)
osfamily	optional	The operating system family of the device
osfamily__nin	optional	The operating system family of the device (not in)
osnameversion	optional	The operating system name and version of the device
osnameversion__contains	optional	The OS names and versions
osnameversion__nin	optional	The operating system name and version of the device (not in)
osversion	optional	The operating system version of the device
osversion__contains	optional	The OS versions
osversion__nin	optional	The operating system version of the device (not in)
rangertagkey__contains	optional	Free-text filter by Ranger tag key (supports multiple values)
rangertagkeyvalue__contains	optional	Free-text filter by Ranger tag key value (supports multiple values)
rangertagskey	optional	The ranger tags key
rangertagskey__nin	optional	The ranger tags key (not in)
rangertagskeyvalue	optional	The ranger tags key value
rangertagskeyvalue__nin	optional	The ranger tags key value (not in)
resourcetype	optional	The canonical name for the resource type
resourcetype__contains	optional	The Asset Type
resourcetype__nin	optional	The canonical name for the resource type (not in)
riskfactors	optional	The risk factors associated with the asset
riskfactors__nin	optional	The risk factors associated with the asset (not in)
s1updatedat__between	optional	The Last Seen date and time for the asset

n		
serialnumber	optional	The serial number
serialnumber__contains	optional	The serial number
serialnumber__nin	optional	The serial number (not in)
siteids	optional	List of Site IDs to filter by
subcategory	optional	The sub-category that each resource belongs to
subcategory__nin	optional	The sub-category that each resource belongs to (not in)
subnets__contains	optional	The subnets
surfaces	optional	The Surface that each asset belongs to
surfaces__nin	optional	The Surface that each asset belongs to (not in)
tagskey	optional	Tag Keys
tagskey__contains	optional	Free-text filter by tag key (supports multiple values)
tagskey__exists	optional	Tag Keys exists
tagskey__nexists	optional	Tag Keys not exists
tagskey__nin	optional	Tag Keys (not in)
tagskeyvalue	optional	Tags
tagskeyvalue__contains	optional	Free-text filter by tag key value (supports multiple values)
tagskeyvalue__nin	optional	Tags (not in)
tcpports	optional	The TCP ports
udpports	optional	The UDP ports

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Available actions - response - data table
errors	Errors	false	array

Available actions - response - data

Name	Description	Required	Value
availableActions	Available actions	false	undefined []

Body Schema

Name	Description	Required	Value
id__in	List of selected inventory ids	false	string []
id__nin	List of inventory ids to exclude from select_all	false	string []

Licenses

Update sites add-ons

PUT /web/api/v2.1/licenses/update-sites-modules

Change the add-ons of the sites by a given filter

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update sites add-ons - response - data table
errors	Errors	false	array

Update sites add-ons - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Update sites add-ons - body - data table
filter	Filter	true	see Update sites add-ons - body - filter table

Update sites add-ons - body - data

Name	Description	Required	Value
operation	Operation	true	enum
modules	Modules	false	see Update sites add-ons - body - modules table

Update sites add-ons - body - modules

Name	Description	Required	Value
name	Name	true	string

Update sites add-ons - body - filter

Name	Description	Required	Value
accountId	Account id	false	string
accountIds	List of Account IDs to filter by	false	string []
accountName__contains	Free-text filter by account name (supports multiple values)	false	string []
activeLicenses	Active licenses	false	integer
adminOnly	[DEPRECATED] Show sites the user has Admin privileges to	false	boolean
availableMoveSites	Only return sites the user can move agents to	false	boolean
createdAt	Timestamp of site creation	false	string
description	The description for the Site	false	string
description__contains	Free-text filter by site description (supports multiple values)	false	string []
expiration	Expiration	false	string
externalId	Id in a CRM external system	false	string
features	If sent return only sites that support this features	false	string []

healthStatus	Health status	false	boolean
isDefault	Is default	false	boolean
module	Module	false	string
name	Name	false	string
name__contains	Free-text filter by site name (supports multiple values)	false	string []
query	Full text search for fields: name, account_name, description. (Note: on single-account consoles account name will not be matched)	false	string
registrationToken	Registration token	false	string
sitelds	List of Site IDs to filter by	false	string []
siteType	Site type	false	enum
sku	Sku	false	string
state	Site state	false	enum
states	List of states to filter	false	string []
statesNin	List of states to not filter	false	string []
suite	[DEPRECATED] Use sku instead	false	enum
totalLicenses	Total licenses	false	integer
updatedAt	Timestamp of last update	false	string

Live Updates

Get Agent Merged Updates

GET /web/api/v2.1/content-updates-inventory

Get Agent's merged updates.

Parameters

agentid	required	The ID of the Agent. Example: "225494730938493804".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.

cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
limit	optional	Limit number of returned items (1-1000). Example: "10".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Agent Merged Updates - response - pagination table
data	Response data	false	see Get Agent Merged Updates - response - data table
errors	Errors	false	array

Get Agent Merged Updates - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Agent Merged Updates - response - data

Name	Description	Required	Value
agentContentUpdateId	Agent content update ID	false	string
appliedAt	Timestamp of when the update was applied	false	string
assetFamilyType	Live update category	false	string
displayName	Live update type name	false	string
liveUpdateId	Live update ID	false	string

Locations

Create Location

POST /web/api/v2.1/locations

Create a location that defines parameters of Agents in a scope filter. Parameters include:

- * ipAddresses - The Agent compares the endpoint active IPv4 or IPv6 addresses to the IP addresses, ranges, and CIDRs defined for the location.
- * dnsServers - The Agent compares the configured DNS servers of the endpoint to the DNS servers defined for the location.
- * dnsLookup - The Agent resolves the FQDN of the endpoint to IPv4 or IPv6 addresses and compares them to the addresses configured in the location setting.
- * networkInterfaces - The Agent determines if the endpoint is connected to the network over a wireless connection. If one connected interface is wireless, the endpoint is considered wireless.
- * serverConnectivity - The Agent reports if it is connected to its Management.

* registryKeys - The Agent compares the endpoint registry keys in HKEY_LOCAL_MACHINE\SOFTWARE with the registry key of the location definition. When you set a location parameter, also set the operator to ALL, NONE, or at least 1.
The serverConnectivity parameter takes "enabled" (true or false) and "value" (connected or disconnected).
The networkInterfaces parameter takes "enabled" (true or false) and "value" (wired or wireless).

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Location - response - data table
errors	Errors	false	array

Create Location - response - data

Name	Description	Required	Value
name	Location name (should be unique per scope)	true	string
operator	Logical operator to apply between the set of identifiers	true	enum
activeFirewallRules	Number of active firewall rules defined in the location	false	integer
createdAt	Created at	false	string
creator	Location creator name	false	string
creatorId	Location creator ID	false	string
description	Location description	false	string
dnsLookup	Identify a location by DNS lookup results	false	see Create Location - response - dnsLookup table
dnsServers	Identify a location by DNS servers defined on the endpoint	false	see Create Location - response - dnsServers table
editable	Is location editable in current scope	false	boolean
id	Id	false	string
ipAddresses	Identify a location the assigned IP addresses	false	see Create Location - response - ipAddresses table
isFallback	Is fallback	false	boolean
networkInterfaces	Identify a location by available network interface types	false	see Create Location - response - networkInterfaces table
registryKeys	Identify a location by a registry key or value	false	see Create Location - response - registryKeys table
reportingAgents	Number of agents in the location	false	integer
scope	Scope	false	enum
scopeId	Scope id	false	string
scopeName	Scope name	false	string
serverConnectivity	Identify a location by connectivity to the management server	false	see Create Location - response - serverConnectivity table
updatedAt	Updated at	false	string

updater	Location updater name	false	string
updaterId	Location updater	false	string

Create Location - response - dnsLookup

Name	Description	Required	Value
operator	Logical operator to apply between the set of identifiers	true	enum
identifiers	A list of DNS lookup identifiers	false	see Create Location - response - identifiers table

Create Location - response - identifiers

Name	Description	Required	Value
host	Hostname to resolve	true	string
ip	Resolved IP address	true	string

Create Location - response - dnsServers

Name	Description	Required	Value
operator	Logical operator to apply between the set of identifiers	true	enum
identifiers	A list of identifiers	false	see Create Location - response - identifiers table

Create Location - response - identifiers

Name	Description	Required	Value
type	Address type	true	enum
values	IP address, CIDR or range of two addresses. May be either IPv4 or IPv6	false	string []

Create Location - response - ipAddresses

Name	Description	Required	Value
operator	Logical operator to apply between the set of identifiers	true	enum
identifiers	A list of identifiers	false	see Create Location - response - identifiers table

Create Location - response - identifiers

Name	Description	Required	Value
type	Address type	true	enum
values	IP address, CIDR or range of two addresses. May be either IPv4 or IPv6	false	string []

Create Location - response - networkInterfaces

Name	Description	Required	Value
enabled	Use or discard this location identifier	true	boolean
value	Network interface type	false	enum

Create Location - response - registryKeys

Name	Description	Required	Value
key	Registry key path to match. Must start with "HKEY_LOCAL_MACHINE\SOFTWARE\".	true	string
data	Content of the value to match (may be a string or a 64-bit integer, optional)	false	string
value	Value name in the registry key path to match (optional)	false	string

Create Location - response - serverConnectivity

Name	Description	Required	Value
enabled	Use or discard this location identifier	true	boolean
value	Server connectivity status	false	enum

Body Schema

Name	Description	Required	Value
data	Location data	true	see Create Location - body - data table
filter	Location scope	true	see Create Location - body - filter table

Create Location - body - data

Name	Description	Required	Value
name	Location name (should be unique per scope)	true	string
operator	Logical operator to apply between the set of identifiers	true	enum
description	Location description	false	string
dnsLookup	Identify a location by DNS lookup results	false	see Create Location - body - dnsLookup table
dnsServers	Identify a location by DNS servers defined on the endpoint	false	see Create Location - body - dnsServers table
ipAddresses	Identify a location the assigned IP addresses	false	see Create Location - body - ipAddresses table
networkInterfaces	Identify a location by available network interface types	false	see Create Location - body - networkInterfaces table
registryKeys	Identify a location by a registry key or value	false	see Create Location - body - registryKeys table
serverConnectivity	Identify a location by connectivity to the management server	false	see Create Location - body - serverConnectivity table

Create Location - body - dnsLookup

Name	Description	Required	Value
operator	Logical operator to apply between the set of identifiers	true	enum
identifiers	A list of DNS lookup identifiers	false	see Create Location - body - identifiers table

Create Location - body - identifiers

Name	Description	Required	Value
host	Hostname to resolve	true	string

ip	Resolved IP address	true	string
----	---------------------	------	--------

Create Location - body - dnsServers

Name	Description	Required	Value
operator	Logical operator to apply between the set of identifiers	true	enum
identifiers	A list of identifiers	false	see Create Location - body - identifiers table

Create Location - body - identifiers

Name	Description	Required	Value
type	Address type	true	enum
values	IP address, CIDR or range of two addresses. May be either IPv4 or IPv6	false	string []

Create Location - body - ipAddresses

Name	Description	Required	Value
operator	Logical operator to apply between the set of identifiers	true	enum
identifiers	A list of identifiers	false	see Create Location - body - identifiers table

Create Location - body - identifiers

Name	Description	Required	Value
type	Address type	true	enum
values	IP address, CIDR or range of two addresses. May be either IPv4 or IPv6	false	string []

Create Location - body - networkInterfaces

Name	Description	Required	Value
enabled	Use or discard this location identifier	true	boolean
value	Network interface type	false	enum

Create Location - body - registryKeys

Name	Description	Required	Value
key	Registry key path to match. Must start with "HKEY_LOCAL_MACHINE\SOFTWARE\".	true	string
data	Content of the value to match (may be a string or a 64-bit integer, optional)	false	string
value	Value name in the registry key path to match (optional)	false	string

Create Location - body - serverConnectivity

Name	Description	Required	Value
enabled	Use or discard this location identifier	true	boolean
value	Server connectivity status	false	enum

Create Location - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Get Locations

GET /web/api/v2.1/locations

Get the locations of Agents in a given scope that match the filter. Agent locations are based on endpoint network parameters (IP, DNS, NIC, Registry Key, or SentinelOne

connection set for all true, at least one true, or none true and applied to a Site, Account, or Global). Agents detect their location settings and apply Firewall Control rules that have Location Aware parameters that match the Agent location. Agents can be in multiple locations at the same time. If an Agent that supports Locations does not detect that it is in a defined location, it uses the Firewall rules assigned to the Fallback location.

Use this command with a filter for "hasFirewallRules" to find Locations that do not have matching Firewall Control rules. The response to this request includes the ID of the location, which you can use in other commands.

Firewall Control and Location Awareness require Control SKU.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
creator__contains	optional	Free-text filter by creator of the location (supports multiple values). Example: "max,mike".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
description__contains	optional	Free-text filter by description (supports multiple values). Example: "out of office".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
hasfirewallrules	optional	Filter by locations with/without firewall rules associated to them
hostname__contains	optional	Free-text filter by hostname (supports multiple values). Example: "sentinelone.com,localhost".
ids	optional	Filter results by location IDs. Example: "225494730938493804,225494730938493915".
ipaddress__contains	optional	Free-text filter by IP address (supports multiple values). Example: "29.213.22.17".
limit	optional	Limit number of returned items (1-1000). Example: "10".
name__contains	optional	Free-text filter by location name (supports multiple values). Example: "office".
registrykey__contains	optional	Free-text filter by registry key (supports multiple values). Example: "system\software,sentinel".
scopename__contains	optional	Free-text filter by scope name (supports multiple values). Example: "my_group,my_site".

scopes	optional	Filter results by scope. Example: "account".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Locations - response - pagination table
data	Response data	false	see Get Locations - response - data table
errors	Errors	false	array

Get Locations - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Locations - response - data

Name	Description	Required	Value
name	Location name (should be unique per scope)	true	string
operator	Logical operator to apply between the set of identifiers	true	enum
activeFirewallRules	Number of active firewall rules defined in the location	false	integer
createdAt	Created at	false	string
creator	Location creator name	false	string
creatorId	Location creator ID	false	string
description	Location description	false	string
dnsLookup	Identify a location by DNS lookup results	false	see Get Locations - response - dnsLookup table
dnsServers	Identify a location by DNS servers defined on the endpoint	false	see Get Locations - response - dnsServers table
editable	Is location editable in current scope	false	boolean
id	Id	false	string
ipAddresses	Identify a location the assigned IP addresses	false	see Get Locations - response - ipAddresses table
isFallback	Is fallback	false	boolean
networkInterfaces	Identify a location by available	false	see Get Locations - response - networkInterfaces table

	network interface types		
registryKeys	Identify a location by a registry key or value	false	see Get Locations - response - registryKeys table
reportingAgents	Number of agents in the location	false	integer
scope	Scope	false	enum
scopeId	Scope id	false	string
scopeName	Scope name	false	string
serverConnectivity	Identify a location by connectivity to the management server	false	see Get Locations - response - serverConnectivity table
updatedAt	Updated at	false	string
updater	Location updater name	false	string
updaterId	Location updater	false	string

Get Locations - response - dnsLookup

Name	Description	Required	Value
operator	Logical operator to apply between the set of identifiers	true	enum
identifiers	A list of DNS lookup identifiers	false	see Get Locations - response - identifiers table

Get Locations - response - identifiers

Name	Description	Required	Value
host	Hostname to resolve	true	string
ip	Resolved IP address	true	string

Get Locations - response - dnsServers

Name	Description	Required	Value
operator	Logical operator to apply between the set of identifiers	true	enum

[see Get Locations - response - identifiers table](#)

identifiers	A list of identifiers	false	
-------------	-----------------------	-------	--

Get Locations - response - identifiers

Name	Description	Required	Value
type	Address type	true	enum
values	IP address, CIDR or range of two addresses. May be either IPv4 or IPv6	false	string []

Get Locations - response - ipAddresses

Name	Description	Required	Value
operator	Logical operator to apply between the set of identifiers	true	enum
identifiers	A list of identifiers	false	see Get Locations - response - identifiers table

Get Locations - response - identifiers

Name	Description	Required	Value
type	Address type	true	enum
values	IP address, CIDR or range of two addresses. May be either IPv4 or IPv6	false	string []

Get Locations - response - networkInterfaces

Name	Description	Required	Value
enabled	Use or discard this location identifier	true	boolean
value	Network interface type	false	enum

Get Locations - response - registryKeys

Name	Description	Required	Value
key	Registry key path to match. Must start with "HKEY_LOCAL_MACHINE\SOFTWARE\".	true	string
data	Content of the value to match (may be a string or a 64-bit integer, optional)	false	string
value	Value name in the registry key path to match (optional)	false	string

Get Locations - response - serverConnectivity

Name	Description	Required	Value
enabled	Use or discard this location identifier	true	boolean
value	Server connectivity status	false	enum

Delete Locations

DELETE /web/api/v2.1/locations

Delete location definitions of a given location. To get location IDs, run "locations".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Locations - response - data table

errors	Errors	false	array
--------	--------	-------	-------

Delete Locations - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Delete Locations - body - data table

Delete Locations - body - data

Name	Description	Required	Value
ids	List of location IDs to delete	false	string []

Update Location

PUT /web/api/v2.1/locations/{location_id}

Change the parameter values of a location definition. See Create Location.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

404 - Location not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Location - response - data table
errors	Errors	false	array

Update Location - response - data

Name	Description	Required	Value
name	Location name (should be unique per scope)	true	string
operator	Logical operator to apply between the set of identifiers	true	enum
activeFirewallRules	Number of active firewall rules defined in the location	false	integer
createdAt	Created at	false	string
creator	Location creator name	false	string
creatorId	Location creator ID	false	string
description	Location description	false	string
dnsLookup	Identify a location by DNS lookup results	false	see Update Location - response - dnsLookup table
dnsServers	Identify a location by DNS servers defined on the endpoint	false	see Update Location - response - dnsServers table
editable	Is location editable in current scope	false	boolean
id	Id	false	string
ipAddresses	Identify a location the assigned IP addresses	false	see Update Location - response - ipAddresses table
isFallback	Is fallback	false	boolean
networkInterfaces	Identify a location by available network interface types	false	see Update Location - response - networkInterfaces table
registryKeys	Identify a location by a registry key or value	false	see Update Location - response - registryKeys table
reportingAgents	Number of agents in the location	false	integer
scope	Scope	false	enum
scopeId	Scope id	false	string
scopeName	Scope name	false	string
serverConnectivity	Identify a location by connectivity to the management server	false	see Update Location - response - serverConnectivity table
updatedAt	Updated at	false	string

updater	Location updater name	false	string
updaterId	Location updater	false	string

Update Location - response - dnsLookup

Name	Description	Required	Value
operator	Logical operator to apply between the set of identifiers	true	enum
identifiers	A list of DNS lookup identifiers	false	see Update Location - response - identifiers table

Update Location - response - identifiers

Name	Description	Required	Value
host	Hostname to resolve	true	string
ip	Resolved IP address	true	string

Update Location - response - dnsServers

Name	Description	Required	Value
operator	Logical operator to apply between the set of identifiers	true	enum
identifiers	A list of identifiers	false	see Update Location - response - identifiers table

Update Location - response - identifiers

Name	Description	Required	Value
type	Address type	true	enum
values	IP address, CIDR or range of two addresses. May be either IPv4 or IPv6	false	string []

Update Location - response - ipAddresses

Name	Description	Required	Value
operator	Logical operator to apply between the set of identifiers	true	enum
identifiers	A list of identifiers	false	see Update Location - response - identifiers table

Update Location - response - identifiers

Name	Description	Required	Value
type	Address type	true	enum
values	IP address, CIDR or range of two addresses. May be either IPv4 or IPv6	false	string []

Update Location - response - networkInterfaces

Name	Description	Required	Value
enabled	Use or discard this location identifier	true	boolean
value	Network interface type	false	enum

Update Location - response - registryKeys

Name	Description	Required	Value
key	Registry key path to match. Must start with "HKEY_LOCAL_MACHINE\SOFTWARE\".	true	string
data	Content of the value to match (may be a string or a 64-bit integer, optional)	false	string
value	Value name in the registry key path to match (optional)	false	string

Update Location - response - serverConnectivity

Name	Description	Required	Value
enabled	Use or discard this location identifier	true	boolean
value	Server connectivity status	false	enum

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Location - body - data table

Update Location - body - data

Name	Description	Required	Value
name	Location name (should be unique per scope)	true	string
description	Location description	false	string
dnsLookup	Identify a location by DNS lookup results	false	see Update Location - body - dnsLookup table
dnsServers	Identify a location by DNS servers defined on the endpoint	false	see Update Location - body - dnsServers table
ipAddresses	Identify a location the assigned IP addresses	false	see Update Location - body - ipAddresses table
networkInterfaces	Identify a location by available network interface types	false	see Update Location - body - networkInterfaces table
operator	Logical operator to apply between the set of identifiers	false	enum
registryKeys	Identify a location by a registry key or value	false	see Update Location - body - registryKeys table
serverConnectivity	Identify a location by connectivity to the management server	false	see Update Location - body - serverConnectivity table

Update Location - body - dnsLookup

Name	Description	Required	Value
operator	Logical operator to apply between the set of identifiers	true	enum
identifiers	A list of DNS lookup identifiers	false	see Update Location - body - identifiers table

Update Location - body - identifiers

Name	Description	Required	Value
host	Hostname to resolve	true	string

ip	Resolved IP address	true	string
----	---------------------	------	--------

Update Location - body - dnsServers

Name	Description	Required	Value
operator	Logical operator to apply between the set of identifiers	true	enum
identifiers	A list of identifiers	false	see Update Location - body - identifiers table

Update Location - body - identifiers

Name	Description	Required	Value
type	Address type	true	enum
values	IP address, CIDR or range of two addresses. May be either IPv4 or IPv6	false	string []

Update Location - body - ipAddresses

Name	Description	Required	Value
operator	Logical operator to apply between the set of identifiers	true	enum
identifiers	A list of identifiers	false	see Update Location - body - identifiers table

Update Location - body - identifiers

Name	Description	Required	Value
type	Address type	true	enum
values	IP address, CIDR or range of two addresses. May be either IPv4 or IPv6	false	string []

Update Location - body - networkInterfaces

Name	Description	Required	Value
enabled	Use or discard this location identifier	true	boolean
value	Network interface type	false	enum

Update Location - body - registryKeys

Name	Description	Required	Value
key	Registry key path to match. Must start with "HKEY_LOCAL_MACHINE\SOFTWARE\".	true	string
data	Content of the value to match (may be a string or a 64-bit integer, optional)	false	string
value	Value name in the registry key path to match (optional)	false	string

Update Location - body - serverConnectivity

Name	Description	Required	Value
enabled	Use or discard this location identifier	true	boolean
value	Server connectivity status	false	enum

Log Collection

Get Log Collection rules

GET /web/api/v2.1/log-collection/rules

Parameters

accountids	optional	List of account IDs to filter by. Example:
------------	----------	--

		"225494730938493804,225494730938493915".
agenttype	optional	Agent type. Example: "windows".
agenttypes	optional	List of agent types to filter by. Example: "windows".
collectionpath	optional	Collection path
collectionpath__contains	optional	Free-text filter by rule collection path (supports multiple)
collectionpathorchannel	optional	Collection path or channel
collectionpathorchannel__contains	optional	Free-text filter by rule collection path or channel (supports multiple)
collectionpaths	optional	List of collection paths to filter by.
collectionpathsorchannel	optional	List of collection paths to filter by.
collectiontags	optional	Exact match filter by collection tags (supports multiple)
collectiontags__contains	optional	Free-text filter by rule collection tags (supports multiple)
collectiontype	optional	Collection type. Example: "applicationLog".
collectiontypes	optional	List of collection types to filter by. Example: "applicationLog".
configurationtype	optional	Configuration type. Example: "collectionPath".
configurationtypes	optional	List of configuration types to filter by. Example: "collectionPath".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdby__contains	optional	Free-text filter by rule author (supports multiple)
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
description__contains	optional	Free-text filter by rule description (supports multiple)
enabled	optional	Include enabled, disabled or both. Example: "True,False".
eventids	optional	Exact match filter by event ids (supports multiple)
eventids__contains	optional	Free-text filter by rule eventIds (supports multiple)

excludedids	optional	List of IDs to exclude. Example: "225494730938493804,225494730938493915".
excludedlogs__contains	optional	Free-text filter by rule excluded logs (supports multiple)
excludedtags	optional	Exact match filter by excluded tags (supports multiple)
excludedtags__contains	optional	Free-text filter by rule excluded tags (supports multiple)
groupids	optional	List of group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of IDs to filter by. Example: "225494730938493804,225494730938493915".
includechildren	optional	Return filters from children scope levels
includeparents	optional	Return rules from parent scope levels
limit	optional	Limit number of returned items (1-1000). Example: "10".
logprefix__contains	optional	Free-text filter by rule parser (supports multiple)
name	optional	Name
name__contains	optional	Free-text filter by rule name (supports multiple)
names	optional	List of names to filter by.
parser__contains	optional	Free-text filter by rule parser (supports multiple)
scope	optional	Scope. Example: "group".
scopepath	optional	Scope path
scopepath__contains	optional	Free-text filter by scope path (supports multiple)
scopepaths	optional	List of scope paths to filter by.
scopes	optional	List of scopes to filter by. Example: "group".
siteids	optional	List of site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

state	optional	State
tenant	optional	Indicates a tenant scope request
updatedat__between	optional	Date range for last update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedby__contains	optional	Free-text filter by rule last updater (supports multiple)
welexcludedids__contains	optional	Free-text filter by rule excluded ids (supports multiple)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Log Collection rules - response - pagination table
data	Response data	false	see Get Log Collection rules - response - data table
errors	Errors	false	array

Get Log Collection rules - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Log Collection rules - response - data

Name	Description	Required	Value
agentType	Agent type (windows linux macos k8s)	false	enum
createdAt	Created at	false	string
createdBy	Created by	false	string
description	Description	false	string
enabled	Enabled	false	boolean
id	Log Collection Rule ID	false	string
k8sParams	K8s params	false	see Get Log Collection rules - response - k8sParams table
linuxParams	Linux params	false	see Get Log Collection rules - response - linuxParams table
macosParams	Macos params	false	see Get Log Collection rules - response - macosParams table
name	Name	false	string
scopeId	Scope id	false	string
scopeLevel	Scope level	false	string
scopePath	Scope path	false	string
updatedAt	Updated at	false	string
updatedBy	Updated by	false	string
uuid	Uuid	false	string
windowsParams	Windows params	false	see Get Log Collection rules - response - windowsParams table

Get Log Collection rules - response - k8sParams

Name	Description	Required	Value
collectionTags	Collection tags	false	string []
excludedTags	Excluded tags	false	string []
logPrefix	Log prefix	false	string
parser	Parser	false	string

Get Log Collection rules - response - linuxParams

Name	Description	Required	Value
collectionPath	Collection path	false	string
excludedLogs	Excluded logs	false	string []
logPrefix	Log prefix	false	string
parser	Parser	false	string

Get Log Collection rules - response - macosParams

Name	Description	Required	Value
collectionPath	Collection path	false	string
collectionType	Collection type	false	enum
configurationType	Configuration type	false	enum
debugLogs	Debug logs	false	boolean
excludedLogs	Excluded logs	false	string []
infoLogs	Info logs	false	boolean
logPrefix	Log prefix	false	string
parser	Parser	false	string

Get Log Collection rules - response - windowsParams

Name	Description	Required	Value
collectionPathOrChannel	Collection path or channel	true	string
allEvents	All events	false	see Get Log Collection rules - response - allEvents table
collectionType	Collection type	false	enum
collectXml	Collect xml	false	boolean
eventIds	Event ids	false	see Get Log Collection rules - response - eventIds table
excludedLogs	Excluded logs	false	string []
levelsAndProviders	Levels and providers	false	see Get Log Collection rules - response - levelsAndProviders table
logPrefix	Log prefix	false	string
parser	Parser	false	string
rawXml	Raw xml	false	boolean

Get Log Collection rules - response - allEvents

Name	Description	Required	Value
weExcludedIds	Wel excluded ids	false	string []

Get Log Collection rules - response - eventIds

Name	Description	Required	Value
eventIds	Event ids	false	string []

Get Log Collection rules - response - levelsAndProviders

Name	Description	Required	Value
levels	Levels	false	undefined []
providers	Providers	false	string []
weExcludedIds	Wel excluded ids	false	string []

Create a log collection rule

POST /web/api/v2.1/log-collection/rules

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

409 - Conflict

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create a log collection rule - response - data table
errors	Errors	false	array

Create a log collection rule - response - data

Name	Description	Required	Value
id	Id	true	string
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
agentType	Agent type	true	enum
name	Name	true	string
scopeLevel	Scope level	true	enum
description	Description	false	string
k8sParams	K8s params	false	see Create a log collection rule - body - k8sParams table
linuxParams	Linux params	false	see Create a log collection rule - body - linuxParams table
macosParams	Macos params	false	see Create a log collection rule - body - macosParams table
scopeId	Scope id	false	integer
windowsParams	Windows params	false	see Create a log collection rule - body - windowsParams table

Create a log collection rule - body - k8sParams

Name	Description	Required	Value
collectionTags	Collection tags	false	string []
excludedTags	Excluded tags	false	string []
logPrefix	Log prefix	false	string
parser	Parser	false	string

Create a log collection rule - body - linuxParams

Name	Description	Required	Value
collectionPath	Collection path	true	string
excludedLogs	Excluded logs	false	string []
logPrefix	Log prefix	false	string
parser	Parser	false	string

Create a log collection rule - body - macosParams

Name	Description	Required	Value
collectionPath	Collection path	true	string
collectionType	Collection type	true	enum
configurationType	Configuration type	true	enum
debugLogs	Debug logs	false	boolean
excludedLogs	Excluded logs	false	string []
infoLogs	Info logs	false	boolean
logPrefix	Log prefix	false	string
parser	Parser	false	string

Create a log collection rule - body - windowsParams

Name	Description	Required	Value
collectionPathOrChannel	Collection path or channel	true	string
collectionType	Collection type	true	enum
allEvents	All events	false	see Create a log collection rule - body - allEvents table
collectXml	Collect xml	false	boolean
eventIds	Event ids	false	see Create a log collection rule - body - eventIds table
excludedLogs	Excluded logs	false	string []
levelsAndProviders	Levels and providers	false	see Create a log collection rule - body - levelsAndProviders table
logPrefix	Log prefix	false	string
parser	Parser	false	string
rawXml	Raw xml	false	boolean

Create a log collection rule - body - allEvents

Name	Description	Required	Value
weExcludedIds	Wel excluded ids	false	string []

Create a log collection rule - body - eventIds

Name	Description	Required	Value
eventIds	Event ids	false	string []

Create a log collection rule - body - levelsAndProviders

Name	Description	Required	Value
levels	Levels	false	undefined []
providers	Providers	false	string []
weExcludedIds	Wel excluded ids	false	string []

Delete log collection rules

DELETE /web/api/v2.1/log-collection/rules

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete log collection rules - response - data table
errors	Errors	false	array

Delete log collection rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer
ids	Ids	false	string []

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Delete log collection rules - body - filter table

Delete log collection rules - body - filter

Name	Description	Required	Value
accountIds	List of account IDs to filter by.	false	string []
agentType	Agent type	false	enum
agentTypes	List of agent types to filter by.	false	string []
collectionPath	Collection path	false	string
collectionPath__contains	Free-text filter by rule collection path (supports multiple)	false	string []
collectionPathOrChannel	Collection path or channel	false	string
collectionPathOrChannel__contains	Free-text filter by rule collection path or channel (supports multiple)	false	string []
collectionPaths	List of collection paths to filter by.	false	string []
collectionPathsOrChannel	List of collection paths to filter by.	false	string []
collectionTags	Exact match filter by collection tags (supports multiple)	false	string []
collectionTags__contains	Free-text filter by rule collection tags (supports multiple)	false	string []
collectionType	Collection type	false	enum
collectionTypes	List of collection types to filter by.	false	string []
configurationType	Configuration type	false	enum
configurationTypes	List of configuration types to filter by.	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdBy__contains	Free-text filter by rule author (supports multiple)	false	string []
description__contains	Free-text filter by rule description (supports multiple)	false	string []
enabled	Include enabled, disabled or both	false	boolean []
eventIds	Exact match filter by event ids (supports multiple)	false	string []
eventIds__contains	Free-text filter by rule eventIds (supports multiple)	false	string []

excludedIds	List of IDs to exclude.	false	string []
excludedLogs__contains	Free-text filter by rule excluded logs (supports multiple)	false	string []
excludedTags	Exact match filter by excluded tags (supports multiple)	false	string []
excludedTags__contains	Free-text filter by rule excluded tags (supports multiple)	false	string []
groupIds	List of group IDs to filter by.	false	string []
ids	List of IDs to filter by.	false	string []
logPrefix__contains	Free-text filter by rule parser (supports multiple)	false	string []
name	Name	false	string
name__contains	Free-text filter by rule name (supports multiple)	false	string []
names	List of names to filter by.	false	string []
parser__contains	Free-text filter by rule parser (supports multiple)	false	string []
scope	Scope	false	enum
scopePath	Scope path	false	string
scopePath__contains	Free-text filter by scope path (supports multiple)	false	string []
scopePaths	List of scope paths to filter by.	false	string []
scopes	List of scopes to filter by.	false	string []
sitelds	List of site IDs to filter by.	false	string []
state	State	false	boolean
tenant	Indicates a tenant scope request	false	boolean
updatedAt__between	Date range for last update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedBy__contains	Free-text filter by rule last updater (supports multiple)	false	string []
weExcludedIds__contains	Free-text filter by rule excluded ids (supports multiple)	false	string []

Get Log Collection rules by agent type

GET /web/api/v2.1/log-collection/rules/{agent_type}

Parameters

accountids	optional	List of account IDs to filter by. Example: "225494730938493804,225494730938493915".
agenttype	optional	Agent type. Example: "windows".
agenttypes	optional	List of agent types to filter by. Example: "windows".
collectionpath	optional	Collection path
collectionpath__contains	optional	Free-text filter by rule collection path (supports multiple)
collectionpathorchannel	optional	Collection path or channel
collectionpathorchannel__contains	optional	Free-text filter by rule collection path or channel (supports multiple)
collectionpaths	optional	List of collection paths to filter by.
collectionpathsorchannel	optional	List of collection paths to filter by.
collectiontags	optional	Exact match filter by collection tags (supports multiple)
collectiontags__contains	optional	Free-text filter by rule collection tags (supports multiple)
collectiontype	optional	Collection type. Example: "applicationLog".
collectiontypes	optional	List of collection types to filter by. Example: "applicationLog".
configurationtype	optional	Configuration type. Example: "collectionPath".
configurationtypes	optional	List of configuration types to filter by. Example: "collectionPath".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdby__contains	optional	Free-text filter by rule author (supports multiple)
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example:

		"YWdlbnRfaWQ6NTgwMjkzODE=".
description__contains	optional	Free-text filter by rule description (supports multiple)
enabled	optional	Include enabled, disabled or both. Example: "True,False".
eventids	optional	Exact match filter by event Ids (supports multiple)
eventids__contains	optional	Free-text filter by rule eventIds (supports multiple)
excludedids	optional	List of IDs to exclude. Example: "225494730938493804,225494730938493915".
excludedlogs__contains	optional	Free-text filter by rule excluded logs (supports multiple)
excludedtags	optional	Exact match filter by excluded tags (supports multiple)
excludedtags__contains	optional	Free-text filter by rule excluded tags (supports multiple)
groupids	optional	List of group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of IDs to filter by. Example: "225494730938493804,225494730938493915".
includechildren	optional	Return filters from children scope levels
includeparents	optional	Return rules from parent scope levels
limit	optional	Limit number of returned items (1-1000). Example: "10".
logprefix__contains	optional	Free-text filter by rule parser (supports multiple)
name	optional	Name
name__contains	optional	Free-text filter by rule name (supports multiple)
names	optional	List of names to filter by.
parser__contains	optional	Free-text filter by rule parser (supports multiple)
scope	optional	Scope. Example: "group".
scopepath	optional	Scope path
scopepath__contains	optional	Free-text filter by scope path (supports multiple)
scopepaths	optional	List of scope paths to filter by.
scopes	optional	List of scopes to filter by. Example: "group".
siteids	optional	List of site IDs to filter by. Example: "225494730938493804,225494730938493915".

skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
state	optional	State
tenant	optional	Indicates a tenant scope request
updatedat__between	optional	Date range for last update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedby__contains	optional	Free-text filter by rule last updater (supports multiple)
welxcludedids__contains	optional	Free-text filter by rule excluded ids (supports multiple)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Log Collection rules by agent type - response - pagination table
data	Response data	false	see Get Log Collection rules by agent type - response - data table
errors	Errors	false	array

Get Log Collection rules by agent type - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Log Collection rules by agent type - response - data

Name	Description	Required	Value
agentType	Agent type (windows linux macos k8s)	false	enum
createdAt	Created at	false	string
createdBy	Created by	false	string
description	Description	false	string
enabled	Enabled	false	boolean
id	Log Collection Rule ID	false	string
k8sParams	K8s params	false	see Get Log Collection rules by agent type - response - k8sParams table
linuxParams	Linux params	false	see Get Log Collection rules by agent type - response - linuxParams table
macosParams	Macos params	false	see Get Log Collection rules by agent type - response - macosParams table
name	Name	false	string
scopeId	Scope id	false	string
scopeLevel	Scope level	false	string
scopePath	Scope path	false	string
updatedAt	Updated at	false	string
updatedBy	Updated by	false	string
uuid	Uuid	false	string
windowsParams	Windows params	false	see Get Log Collection rules by agent type - response - windowsParams table

Get Log Collection rules by agent type - response - k8sParams

Name	Description	Required	Value
collectionTags	Collection tags	false	string []
excludedTags	Excluded tags	false	string []
logPrefix	Log prefix	false	string
parser	Parser	false	string

Get Log Collection rules by agent type - response - linuxParams

Name	Description	Required	Value
collectionPath	Collection path	false	string
excludedLogs	Excluded logs	false	string []
logPrefix	Log prefix	false	string
parser	Parser	false	string

Get Log Collection rules by agent type - response - macosParams

Name	Description	Required	Value
collectionPath	Collection path	false	string
collectionType	Collection type	false	enum
configurationType	Configuration type	false	enum
debugLogs	Debug logs	false	boolean
excludedLogs	Excluded logs	false	string []
infoLogs	Info logs	false	boolean
logPrefix	Log prefix	false	string
parser	Parser	false	string

Get Log Collection rules by agent type - response - windowsParams

Name	Description	Required	Value
collectionPathOrChannel	Collection path or channel	true	string
allEvents	All events	false	see Get Log Collection rules by agent type - response - allEvents table
collectionType	Collection type	false	enum
collectXml	Collect xml	false	boolean
eventIds	Event ids	false	see Get Log Collection rules by agent type - response - eventIds table
excludedLogs	Excluded logs	false	string []
levelsAndProviders	Levels and providers	false	see Get Log Collection rules by agent type - response - levelsAndProviders table
logPrefix	Log prefix	false	string
parser	Parser	false	string
rawXml	Raw xml	false	boolean

Get Log Collection rules by agent type - response - allEvents

Name	Description	Required	Value
weExcludedIds	We excluded ids	false	string []

Get Log Collection rules by agent type - response - eventIds

Name	Description	Required	Value
eventIds	Event ids	false	string []

Get Log Collection rules by agent type - response - levelsAndProviders

Name	Description	Required	Value
levels	Levels	false	undefined []
providers	Providers	false	string []
weExcludedIds	We excluded ids	false	string []

Get Agent type count

GET /web/api/v2.1/log-collection/agent-type-count

Get the total number of log collection rules per agent type

Parameters

accountids	optional	List of account IDs to filter by. Example: "225494730938493804,225494730938493915".
groupids	optional	List of group IDs to filter by. Example: "225494730938493804,225494730938493915".
includechildren	optional	Return filters from children scope levels
includeparents	optional	Return rules from parent scope levels
siteids	optional	List of site IDs to filter by. Example: "225494730938493804,225494730938493915".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Agent type count - response - data table
errors	Errors	false	array

Get Agent type count - response - data

Name	Description	Required	Value
totalRules	Total rules	true	integer
agentTypes	Agent types	false	see Get Agent type count - response - agentTypes table

Get Agent type count - response - agentTypes

Name	Description	Required	Value
agentType	Agent type	true	string
count	Count	true	integer

Update a log collection rule

PUT /web/api/v2.1/log-collection/rules/{rule_id}

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

409 - Conflict

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update a log collection rule - response - data table
errors	Errors	false	array

Update a log collection rule - response - data

Name	Description	Required	Value
id	Id	true	string
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
agentType	Agent type	true	enum
name	Name	true	string
scopeLevel	Scope level	true	enum
description	Description	false	string
k8sParams	K8s params	false	see Update a log collection rule - body - k8sParams table
linuxParams	Linux params	false	see Update a log collection rule - body - linuxParams table
macosParams	Macos params	false	see Update a log collection rule - body - macosParams table
scopeId	Scope id	false	integer
windowsParams	Windows params	false	see Update a log collection rule - body - windowsParams table

Update a log collection rule - body - k8sParams

Name	Description	Required	Value
collectionTags	Collection tags	false	string []
excludedTags	Excluded tags	false	string []
logPrefix	Log prefix	false	string
parser	Parser	false	string

Update a log collection rule - body - linuxParams

Name	Description	Required	Value
collectionPath	Collection path	true	string
excludedLogs	Excluded logs	false	string []
logPrefix	Log prefix	false	string
parser	Parser	false	string

Update a log collection rule - body - macosParams

Name	Description	Required	Value
collectionPath	Collection path	true	string
collectionType	Collection type	true	enum
configurationType	Configuration type	true	enum
debugLogs	Debug logs	false	boolean
excludedLogs	Excluded logs	false	string []
infoLogs	Info logs	false	boolean
logPrefix	Log prefix	false	string
parser	Parser	false	string

Update a log collection rule - body - windowsParams

Name	Description	Required	Value
collectionPathOrChannel	Collection path or channel	true	string
collectionType	Collection type	true	enum
allEvents	All events	false	see Update a log collection rule - body - allEvents table
collectXml	Collect xml	false	boolean
eventIds	Event ids	false	see Update a log collection rule - body - eventIds table
excludedLogs	Excluded logs	false	string []
levelsAndProviders	Levels and providers	false	see Update a log collection rule - body - levelsAndProviders table
logPrefix	Log prefix	false	string
parser	Parser	false	string
rawXml	Raw xml	false	boolean

Update a log collection rule - body - allEvents

Name	Description	Required	Value
weExcludedIds	Wel excluded ids	false	string []

Update a log collection rule - body - eventIds

Name	Description	Required	Value
eventIds	Event ids	false	string []

Update a log collection rule - body - levelsAndProviders

Name	Description	Required	Value
levels	Levels	false	undefined []
providers	Providers	false	string []
weExcludedIds	Wel excluded ids	false	string []

Change activation status of log collection rules

POST /web/api/v2.1/log-collection/rules/activation

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Change activation status of log collection rules - response - data table
errors	Errors	false	array

Change activation status of log collection rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer
ids	Ids	false	string []

Body Schema

Name	Description	Required	Value
data	Data	true	see Change activation status of log collection rules - body - data table
filter	Filter	false	see Change activation status of log collection rules - body - filter table

Change activation status of log collection rules - body - data

Name	Description	Required	Value
activate	Activate	true	boolean

Change activation status of log collection rules - body - filter

Name	Description	Required	Value
accountIds	List of account IDs to filter by.	false	string []
agentType	Agent type	false	enum
agentTypes	List of agent types to filter by.	false	string []
collectionPath	Collection path	false	string
collectionPath__contains	Free-text filter by rule collection path (supports multiple)	false	string []
collectionPathOrChannel	Collection path or channel	false	string
collectionPathOrChannel__contains	Free-text filter by rule collection path or channel (supports multiple)	false	string []
collectionPaths	List of collection paths to filter by.	false	string []
collectionPathsOrChannel	List of collection paths to filter by.	false	string []
collectionTags	Exact match filter by collection tags (supports multiple)	false	string []
collectionTags__contains	Free-text filter by rule collection tags (supports multiple)	false	string []
collectionType	Collection type	false	enum
collectionTypes	List of collection types to filter by.	false	string []
configurationType	Configuration type	false	enum
configurationTypes	List of configuration types to filter by.	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdBy__contains	Free-text filter by rule author (supports multiple)	false	string []

description__contains	Free-text filter by rule description (supports multiple)	false	string []
enabled	Include enabled, disabled or both	false	boolean []
eventIds	Exact match filter by event Ids (supports multiple)	false	string []
eventIds__contains	Free-text filter by rule eventIds (supports multiple)	false	string []
excludedIds	List of IDs to exclude.	false	string []
excludedLogs__contains	Free-text filter by rule excluded logs (supports multiple)	false	string []
excludedTags	Exact match filter by excluded tags (supports multiple)	false	string []
excludedTags__contains	Free-text filter by rule excluded tags (supports multiple)	false	string []
groupIds	List of group IDs to filter by.	false	string []
ids	List of IDs to filter by.	false	string []
logPrefix__contains	Free-text filter by rule parser (supports multiple)	false	string []
name	Name	false	string
name__contains	Free-text filter by rule name (supports multiple)	false	string []
names	List of names to filter by.	false	string []
parser__contains	Free-text filter by rule parser (supports multiple)	false	string []
scope	Scope	false	enum
scopePath	Scope path	false	string
scopePath__contains	Free-text filter by scope path (supports multiple)	false	string []
scopePaths	List of scope paths to filter by.	false	string []
scopes	List of scopes to filter by.	false	string []
sitIds	List of site IDs to filter by.	false	string []
state	State	false	boolean
tenant	Indicates a tenant scope request	false	boolean
updatedAt__between	Date range for last update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string

updatedBy__contains	Free-text filter by rule last updater (supports multiple)	false	string []
weExcludedIds__contains	Free-text filter by rule excluded ids (supports multiple)	false	string []

Export log collection rules

GET /web/api/v2.1/log-collection/rules/export

Get a CSV file with all log collection rules according to the passed filters

Parameters

accountids	optional	List of account IDs to filter by. Example: "225494730938493804,225494730938493915".
agenttype	optional	Agent type. Example: "windows".
agenttypes	optional	List of agent types to filter by. Example: "windows".
collectionpath	optional	Collection path
collectionpath__contains	optional	Free-text filter by rule collection path (supports multiple)
collectionpathorchannel	optional	Collection path or channel
collectionpathorchannel__contains	optional	Free-text filter by rule collection path or channel (supports multiple)
collectionpaths	optional	List of collection paths to filter by.
collectionpathsorchannel	optional	List of collection paths to filter by.
collectiontags	optional	Exact match filter by collection tags (supports multiple)
collectiontags__contains	optional	Free-text filter by rule collection tags (supports multiple)
collectiontype	optional	Collection type. Example: "applicationLog".
collectiontypes	optional	List of collection types to filter by. Example: "applicationLog".
configurationtype	optional	Configuration type. Example: "collectionPath".
configurationtypes	optional	List of configuration types to filter by. Example: "collectionPath".
createdat__between	optional	Date range for creation time (format: <from_timestamp>-

		<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdby__contains	optional	Free-text filter by rule author (supports multiple)
description__contains	optional	Free-text filter by rule description (supports multiple)
enabled	optional	Include enabled, disabled or both. Example: "True,False".
eventids	optional	Exact match filter by event Ids (supports multiple)
eventids__contains	optional	Free-text filter by rule eventIds (supports multiple)
excludedids	optional	List of IDs to exclude. Example: "225494730938493804,225494730938493915".
excludedlogs__contains	optional	Free-text filter by rule excluded logs (supports multiple)
excludedtags	optional	Exact match filter by excluded tags (supports multiple)
excludedtags__contains	optional	Free-text filter by rule excluded tags (supports multiple)
groupids	optional	List of group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of IDs to filter by. Example: "225494730938493804,225494730938493915".
includechildren	optional	Return filters from children scope levels
includeparents	optional	Return rules from parent scope levels
logprefix__contains	optional	Free-text filter by rule parser (supports multiple)
name	optional	Name
name__contains	optional	Free-text filter by rule name (supports multiple)
names	optional	List of names to filter by.
parser__contains	optional	Free-text filter by rule parser (supports multiple)
scope	optional	Scope. Example: "group".
scopepath	optional	Scope path
scopepath__contains	optional	Free-text filter by scope path (supports multiple)
scopepaths	optional	List of scope paths to filter by.
scopes	optional	List of scopes to filter by. Example: "group".
siteids	optional	List of site IDs to filter by. Example: "225494730938493804,225494730938493915".

state	optional	State
tenant	optional	Indicates a tenant scope request
updatedat__between	optional	Date range for last update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedby__contains	optional	Free-text filter by rule last updater (supports multiple)
welexcludedids__contains	optional	Free-text filter by rule excluded ids (supports multiple)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Export log collection rules

GET /web/api/v2.1/log-collection/rules/export/{agent_type}

Get a CSV file with all log collection rules according to the passed filters

Parameters

accountids	optional	List of account IDs to filter by. Example: "225494730938493804,225494730938493915".
agenttype	optional	Agent type. Example: "windows".
agenttypes	optional	List of agent types to filter by. Example: "windows".
collectionpath	optional	Collection path
collectionpath__contains	optional	Free-text filter by rule collection path (supports multiple)
collectionpathorchannel	optional	Collection path or channel
collectionpathorchannel__contains	optional	Free-text filter by rule collection path or channel (supports multiple)

collectionpaths	optional	List of collection paths to filter by.
collectionpathsorchannel	optional	List of collection paths to filter by.
collectiontags	optional	Exact match filter by collection tags (supports multiple)
collectiontags__contains	optional	Free-text filter by rule collection tags (supports multiple)
collectiontype	optional	Collection type. Example: "applicationLog".
collectiontypes	optional	List of collection types to filter by. Example: "applicationLog".
configurationtype	optional	Configuration type. Example: "collectionPath".
configurationtypes	optional	List of configuration types to filter by. Example: "collectionPath".
createdat__between	optional	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdby__contains	optional	Free-text filter by rule author (supports multiple)
description__contains	optional	Free-text filter by rule description (supports multiple)
enabled	optional	Include enabled, disabled or both. Example: "True,False".
eventids	optional	Exact match filter by event Ids (supports multiple)
eventids__contains	optional	Free-text filter by rule eventIds (supports multiple)
excludedids	optional	List of IDs to exclude. Example: "225494730938493804,225494730938493915".
excludedlogs__contains	optional	Free-text filter by rule excluded logs (supports multiple)
excludedtags	optional	Exact match filter by excluded tags (supports multiple)
excludedtags__contains	optional	Free-text filter by rule excluded tags (supports multiple)
groupids	optional	List of group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of IDs to filter by. Example: "225494730938493804,225494730938493915".
includechildren	optional	Return filters from children scope levels
includeparents	optional	Return rules from parent scope levels
logprefix__contains	optional	Free-text filter by rule parser (supports multiple)

name	optional	Name
name__contains	optional	Free-text filter by rule name (supports multiple)
names	optional	List of names to filter by.
parser__contains	optional	Free-text filter by rule parser (supports multiple)
scope	optional	Scope. Example: "group".
scopepath	optional	Scope path
scopepath__contains	optional	Free-text filter by scope path (supports multiple)
scopepaths	optional	List of scope paths to filter by.
scopes	optional	List of scopes to filter by. Example: "group".
siteids	optional	List of site IDs to filter by. Example: "225494730938493804,225494730938493915".
state	optional	State
tenant	optional	Indicates a tenant scope request
updatedat__between	optional	Date range for last update time (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
updatedby__contains	optional	Free-text filter by rule last updater (supports multiple)
welexcludedids__contains	optional	Free-text filter by rule excluded ids (supports multiple)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Long Running Query

Launch a query

POST /sdl/v2/api/queries

Returns a ``QueryResult`` containing the query identifier, status, and, if the query completes immediately, the full result set in the ``data`` field. If the query is still processing, the ``data`` field will be null. Use the returned query id to poll the query via GET ``/v2/api/queries/{id}`` until results are available.

Log queries have a default limit of 1000 events but by paginating can be used to return essentially unlimited results. Power query results are subject to the standard power query limits on row count and memory consumption. A successful response will also include a ``X-Dataset-Query-Forward-Tag`` header that must be applied to the subsequent Poll and Delete requests for routing.

Authorization is accomplished via a Bearer service token in the request header. Service user tokens are not tied to a specific physical user. Learn more about service users here: <https://community.sentinelone.com/s/article/000005290>.

Due to limitations, clicking "Run on console" may not work as expected, and the "Body Sample" may not be accurate because of polymorphism in the body. Refer to the "Body Schema" instead. Only one set of attributes like ``log`` or ``pq`` should be supplied, depending on the specified ``queryType``.

Response Messages

- 200 - Query launched successfully.
- 400 - Bad Request. The request body is malformed or contains invalid parameters.
- 401 - Unauthorized. Authentication is required or the provided credentials are invalid.
- 403 - Forbidden. The authenticated user does not have permission to execute this query.
- 429 - Too Many Requests. Rate limit exceeded for this user, account, or IP address.
- 500 - Internal Server Error. An unexpected error occurred while processing the request.

Response Schema

Name	Description	Required	Value
cpuUsage	cost of the query execution measured in CPU usage in nanoseconds	false	integer
data	Data object containing results of the query. Note that <code>`PQ`</code> queries may return either <code>`PlotResultData`</code> or <code>`TableResultData`</code> depending on the <code>`resultType`</code> specified in the request.	false	object
error	Error if the query was not executed. If not null, will always have <code>`message`</code> key which will provide the basic error message and an optional <code>`details`</code> field providing further information. If	false	see Launch a query - response - error table

	the query execution was successful, the error field will be null.		
id	The unique query identifier. Used in Poll requests to fetch query status and results.	false	string
resolvedTimeRange	Start time and end time for the query in nanoseconds.	false	see Launch a query - response - resolvedTimeRange table
stepsCompleted	Number of steps completed in this long running query.	false	integer
stepsTotal	Total number of steps to execute.	false	integer

Launch a query - response - error

Name	Description	Required	Value
details	Additional error details	false	object
message	Basic error message	false	string

Launch a query - response - resolvedTimeRange

Name	Description	Required	Value
end		false	integer
start		false	integer

Body Schema

Name	Description	Required	Value
queryType	Specifies the type of query to launch.* `LOG`: Fetch a time-ordered list of matching events, with support for pagination.* `TOP_FACETS`: Find the top facets & facet values for all matching events.* `FACET_VALUES`: Find the top values for a particular facet across all matching events.* `PLOT`: Generate a plot of a numeric function applied to all matching events. The plot can be broken down by values of a certain facet, if needed.* `PQ`: Fetch data using Power Query language. Results can be returned as a table or a plot.* `DISTRIBUTION`: Map, as a histogram, the distribution of values for a facet.	true	enum
accountIds	List of account ids to query. We do not currently support a corresponding sitelds parameter. You can instead supply sitelds as part of the query filter, like `site.id` in	false	string []

	('1383518925981773650', '479559923400588751')'. You can also restrict query space by supplying an appropriately scoped service token in the auth header.		
distribution	Attributes specific to the `DISTRIBUTION` query type.	false	see Launch a query - body - distribution table
endTime	Specifies end of the time range to query, using the same syntax as the Start and End fields in the query UI. You can also supply a simple timestamp, measured in seconds, milliseconds, or nanoseconds since 1/1/1970. The default is to query the last 24 hours. If you specify startTime but not endTime, the query covers 24 hours beginning at the startTime. If you specify endTime but not startTime, the query covers 24 hours ending at the endTime.	false	string
facetValues	Attributes specific to the `FACET_VALUES` query type.	false	see Launch a query - body - facetValues table
log	Attributes specific to the `LOG` query type.	false	see Launch a query - body - log table
plot	Attributes specific to the `PLOT` query type.	false	see Launch a query - body - plot table
pq	Attributes specific to the `PQ` query type.	false	see Launch a query - body - pq table
queryPriority	Specifies the execution priority for this query; defaults to "LOW". Use "LOW" for background operations where a delay of a second or so is acceptable. LOW-priority queries have more generous rate limits.* `HIGH`: Standard query priority for API requests, with tighter rate limits.* `LOW`: Use low priority for scripted queries where a slight delay is acceptable; low priority queries are subject to less rate limiting.	false	enum
startTime	Specifies start of the time range to query, using the same syntax as the Start and End fields in the query	false	string

	UI.You can also supply a simple timestamp, measured in seconds, milliseconds, or nanoseconds since 1/1/1970.The default is to query the last 24 hours. If you specify startTime but not endTime, the query covers 24 hours beginning at the startTime. If you specify endTime but not startTime, the query covers 24 hours ending at the endTime.		
tenant	Controls the scope of the query across accessible data. When set to `true`: - Global admin users: Queries across global scope and all accounts - Account-level users: Queries only within the authorized account - Multi-account users: Queries across all authorized accounts - Site-level users: Queries only within the authorized site - Multi-site users: Queries across all authorized sites Tenant must be set to `false` when specifying scope via `accountIds`.	false	boolean
topFacets	Attributes specific to the `TOP_FACETS` query type.	false	see Launch a query - body - topFacets table

Launch a query - body - distribution

Name	Description	Required	Value
facet	The facet to query and aggregate on. Currently all facet queries will be aggregated using the 'count' function.	false	string
filter	Specifies which events to match, using the same syntax as the Expression field in the query UI. To match all events, omit this field or pass an empty string.	false	string

Launch a query - body - facetValues

Name	Description	Required	Value
determineNumeric	Whether to determine if a value is numeric.	false	boolean
filter	Specifies which events to match, using the same syntax as the Expression field in the query UI. To match all events, omit this field or pass an empty string.	false	string
maxValues	The maximum number of unique values to return per facet for the request.	false	integer
name	Specifies the facet name to get values for.	false	string

Launch a query - body - log

Name	Description	Required	Value
ascending	If true, results are returned in order	false	boolean

	from oldest to newest; if false, results are returned in order from newest to oldest.		
cursor	Cursor returned by a previous `LOG` query, used for pagination. When provided, the query returns events starting with this cursor (inclusive) up to the specified `limit`. This allows retrieval of additional results beyond the default maximum per request (typically 5000). To page further, take the `cursor` value from the last event in the previous response and launch a new query with the same time range and this `cursor`; the API will resume where it left off. Note: The boundary event (the event whose cursor you're using) will be included in the next query's results, so it will appear as a duplicate across consecutive API calls. To avoid duplicates, you can skip the first event in each paginated response after the initial query. If not provided, a request with `ascending=true` starts at the beginning of the specified time range, and with `ascending=false` starts at the end.	false	string
exclusive	When set to `true` and a `cursor` is provided, pagination continues from the event represented by the cursor exclusively (the cursor event will NOT be included). This provides standard pagination behavior without duplicates. This parameter overrides the default inclusive behavior.	false	boolean
filter	Specifies which events to match, using the same syntax as the Expression field in the query UI. To match all events, omit this field or pass an empty string.	false	string
limit	Limits the number of returned log events.	false	integer

Launch a query - body - plot

Name	Description	Required	Value
autoAggregate	When set to true, no matter what function is specified in the expression, the result of this query will include a list of plots with the following aggregations applied: - count - mean - min - max - sum - sumPerSecond - countPerSecond - p10 - p50 - p90 - p95 - p99 - p999	false	boolean
autoAlign	Based on a the time range and a target number of slices, auto aligns the slices to a meaningful boundary.	false	boolean
breakdownFacet	Additional facet to breakdown by.	false	string
expression	Expression to query and filter numeric data.	false	string
filter	Specifies which events to match, using the same syntax as the Expression field in the query UI. To match all events, omit this field or pass an empty string.	false	string
frequency	Clients should set frequency to `HIGH` if the query with the same expression will be repeated. Defaults to `LOW`.	false	enum
slices	Number of parts the time range will be divided into. Cannot be used together with `sliceWidth`.	false	integer
sliceWidth	Width in duration the time range will	false	string

	be divided into. Cannot be used together with `slices`. Supported units: `seconds` or `s`, `minutes` or `m`, `hours` or `h`, `days` or `d`, `weeks` or `w`.		
--	---	--	--

Launch a query - body - pq

Name	Description	Required	Value
query	The power query to execute.	true	string
frequency	Clients should set frequency to `HIGH` if the query with the same expression will be repeated. Defaults to `LOW`.	false	enum
resultType	Specifies the result type of a power query.	false	enum

Launch a query - body - topFacets

Name	Description	Required	Value
determineNumeric	Whether to determine if a value is numeric.	false	boolean
filter	Specifies which events to match, using the same syntax as the Expression field in the query UI. To match all events, omit this field or pass an empty string.	false	string
numFacetsToReturn	Number of facets to return. Before facets are returned, they are sorted by the number of events that have them, and in the event of a tie alphabetically.	false	integer
numValuesToReturnPerFacet	The maximum number of values to return per facet for the request	false	integer

Poll query

GET /sdl/v2/api/queries/{id}

Poll a previously launched query by its unique identifier. Responses will return a `QueryResult`. If the query has not yet completed, the `data` field will be null. Once the query completes, `data` will contain the full result set (up to configured limits). It is recommended to poll every second; queries expire after the configured TTL (default 30 seconds). The `X-Dataset-Query-Forward-Tag` header value from the launch query response must be applied for routing.

Authorization is accomplished via a Bearer service token in the request header. Service tokens are not tied to a specific user. Learn more about service users here: <https://community.sentinelone.com/s/article/000005290>.

Due to limitations, clicking "Run on console" may not work as expected

Parameters

laststepseen	required	The step to start return result from
--------------	----------	--------------------------------------

Response Messages

200 - Results retrieved successfully.

400 - Bad Request. Invalid query parameters.

401 - Unauthorized. Authentication is required or the provided credentials are invalid.

403 - Forbidden. The authenticated user does not have permission to access this query.

404 - Not Found. No launched query found for the combination of query id + current account.

429 - Too Many Requests. Rate limit exceeded for this user, account, or IP address.

500 - Internal Server Error. An unexpected error occurred while processing the request.

Response Schema

Name	Description	Required	Value
cpuUsage	cost of the query execution measured in CPU usage in nanoseconds	false	integer
data	Data object containing results of the query. Note that `PQ` queries may return either `PlotResultData` or `TableResultData` depending on the	false	object

	`resultType` specified in the request.		
error	Error if the query was not executed. If not null, will always have `message` key which will provide the basic error message and an optional `details` field providing further information. If the query execution was successful, the error field will be null.	false	see Poll query - response - error table
id	The unique query identifier. Used in Poll requests to fetch query status and results.	false	string
resolvedTimeRange	Start time and end time for the query in nanoseconds.	false	see Poll query - response - resolvedTimeRange table
stepsCompleted	Number of steps completed in this long running query.	false	integer
stepsTotal	Total number of steps to execute.	false	integer

Poll query - response - error

Name	Description	Required	Value
details	Additional error details	false	object
message	Basic error message	false	string

Poll query - response - resolvedTimeRange

Name	Description	Required	Value
end		false	integer
start		false	integer

Delete query

DELETE /sdl/v2/api/queries/{id}

Remove query from the list of launched queries. Clients are required to call this after their query is complete. Subsequent polls using specified token will return not found response. The `X-Dataset-Query-Forward-Tag` header value from the launch query response must be applied for routing.

Authorization is accomplished via a Bearer service token in the request header. Service tokens are not tied to a specific user. Learn more about service users here: <https://community.sentinelone.com/s/article/000005290>.

Due to limitations, clicking "Run on console" may not work as expected

Response Messages

204 - Query has been removed successfully

400 - Bad Request. Invalid query parameters.

401 - Unauthorized. Authentication is required or the provided credentials are invalid.

403 - Forbidden. The authenticated user does not have permission to delete this query.

404 - Not Found. No launched query found for the specified query id.

429 - Too Many Requests. Rate limit exceeded for this user, account, or IP address.

500 - Internal Server Error. An unexpected error occurred while processing the request.

Marketplace

Delete Application

DELETE /web/api/v2.1/singularity-marketplace/applications

Delete application integration from your Marketplace.

Response Messages

200 - OK

Response Schema

Name	Description	Required	Value
data		false	see Delete Application - response - data table

Delete Application - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	true	integer

Body Schema

Name	Description	Required	Value
filter		false	see Delete Application - body - filter table

Delete Application - body - filter

Name	Description	Required	Value
accountIds		false	string []
application_catalog_id		false	string []
creator__contains		false	string
groupIds		false	string []
id		false	string []
name__contains		false	string
query		false	string
siteIds		false	string []
tenant		false	boolean

Get Installed Applications

GET /web/api/v2.1/singularity-marketplace/applications

Get the installed Marketplace applications for a scope specified.

Parameters

accountids	optional	Filter results by account id. Example: "225494730938493804,225494730938493915".
applicationcatalogid	optional	Filter results by application catalog id. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only the number of items will be returned.
creator__contains	optional	Free-text filter by application creator (supports multiple values). Example: "Service Pack 1".
cursor	optional	Cursor position returned by the last request.
disablepagination	optional	If true, pagination will be disabled.
id	optional	A list of applications IDs. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".

name__contains	optional	Free-text filter by application name (supports multiple values). Example: "Service Pack 1".
query	optional	Free-text filter to match name or creator.
siteids	optional	Filter results by site id. Example: "225494730938493804,225494730938493915".
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction (asc/desc). Example: "asc".

Response Messages

200 - OK

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
pagination	Pagination information	false	see Get Installed Applications - response - pagination table

Get Installed Applications - response - pagination

Name	Description	Required	Value
totalItems		true	integer
nextCursor		false	string

Install Applications

POST /web/api/v2.1/singularity-marketplace/applications

Install application from the Application Catalog.

Response Messages

200 - OK

Response Schema

Name	Description	Required	Value
data		false	see Install Applications - response - data table

Install Applications - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	true	integer

Body Schema

Name	Description	Required	Value
data		false	see Install Applications - body - data table
filter		false	see Install Applications - body - filter table

Install Applications - body - data

Name	Description	Required	Value
applicationInstanceName		false	string
configurations		false	undefined []

Install Applications - body - filter

Name	Description	Required	Value
applicationCatalogId		true	string
accountIds		false	string []
groupIds		false	string []
siteIds		false	string []
tenant		false	boolean

Update Application Configuration

PUT /web/api/v2.1/singularity-marketplace/applications

Update installed application configuration.

Response Messages

200 - OK

Response Schema

Name	Description	Required	Value
data		false	see Update Application Configuration - response - data table

Update Application Configuration - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	true	integer

Body Schema

Name	Description	Required	Value
data		false	see Update Application Configuration - body - data table
filter		false	see Update Application Configuration - body - filter table

Update Application Configuration - body - data

Name	Description	Required	Value
applicationIdToNameMap		false	object
configurations		false	undefined []

Update Application Configuration - body - filter

Name	Description	Required	Value
accountIds		false	string []
groupIds		false	string []
ids		false	string []
siteIds		false	string []
tenant		false	boolean

Get Applications Catalog

GET /web/api/v2.1/singularity-marketplace/applications-catalog

Get the Marketplace Application Catalog.

Parameters

category__contains	optional	Free-text filter by catalog application category (supports multiple values). Example: "Service Pack 1".
categoryids	optional	Filter results by application catalog category id. Example: "225494730938493804,225494730938493915".
cursor	optional	Cursor position returned by the last request.
description__contains	optional	Free-text filter by catalog application description (supports multiple values). Example: "Service Pack 1".
id	optional	Filter results by application catalog id. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".

name__contains	optional	Free-text filter by catalog application name (supports multiple values). Example: "Service Pack 1".
query	optional	Free-text filter to match name, description or category.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction (asc/desc). Example: "asc".

Response Messages

200 - OK

Response Schema

Name	Description	Required	Value
data	Response data	false	undefined []
pagination	Pagination information	false	see Get Applications Catalog - response - pagination table

Get Applications Catalog - response - pagination

Name	Description	Required	Value
totalItems		true	integer
nextCursor		false	string

Get Configuration Fields

GET /web/api/v2.1/singularity-marketplace/applications-catalog/{applicationCatalogId}/config

Get the Configuration Fields of the Catalog Application.

Response Messages

200 - OK

Response Schema

Name	Description	Required	Value
data		false	see Get Configuration Fields - response - data table

Get Configuration Fields - response - data

Name	Description	Required	Value
fields		false	undefined []

Get Configuration Fields For Installed Application

GET /web/api/v2.1/singularity-marketplace/applications/{applicationId}/config

Get the Catalog Application Configuration Fields.

Response Messages

200 - OK

Response Schema

Name	Description	Required	Value
data		false	see Get Configuration Fields For Installed Application - response - data table

Get Configuration Fields For Installed Application - response - data

Name	Description	Required	Value
alertMessage		true	string
applicationInstanceName		true	string
createdAt		true	string
creator		true	string
creatorId		true	string
desiredStatus		true	enum
hasAlert		true	boolean
id		true	string
scopeId		true	string
scopeLevel		true	enum
status		true	enum
account		false	string
accountId		false	string
capabilityAnnotations	Optional annotations for specific capabilities with status information	false	see Get Configuration Fields For Installed Application - response - capabilityAnnotations table
errorLog		false	see Get Configuration Fields For Installed Application - response - errorLog table
fields		false	undefined []
group		false	string
groupId		false	string
lastEntityCreatedAt		false	string
modifier		false	string
modifierId		false	string
retryUntil		false	string
site		false	string
siteId		false	string
updatedAt		false	string

Get Configuration Fields For Installed Application - response - capabilityAnnotations

Name	Description	Required	Value
name	The capability name to annotate	true	enum
status	Status annotation for this capability	true	enum

Get Configuration Fields For Installed Application - response - errorLog

Name	Description	Required	Value
applicationId	Application ID	true	string
createdAt	Date of application invocation start (log record was created)	true	string
status	'Created' (started) 'Success' (finished successfully) 'Failure' (final attempt failed) 'Retry' (failed, will be retried)	true	enum
httpStatus	HTTP status response code of application invocation	false	integer
message	Result of application invocation	false	string
title	Title of the log record	false	string
traceld	Tracing ID, useful for searching system logs related to this application invocation	false	string

Enable Or Disable Application

POST /web/api/v2.1/singularity-marketplace/applications/{applicationMode}

Use this command to enable or disable application integrations that match the filter.

Response Messages

200 - OK

Response Schema

Name	Description	Required	Value
data		false	see Enable Or Disable Application - response - data table

Enable Or Disable Application - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	true	integer

Body Schema

Name	Description	Required	Value
filter		false	see Enable Or Disable Application - body - filter table

Enable Or Disable Application - body - filter

Name	Description	Required	Value
applicationId		true	string
accountIds		false	string []
groupIds		false	string []
siteIds		false	string []
tenant		false	boolean

Get application log

GET /web/api/v2.1/singularity-marketplace/applications/{id}/log

Returns application invocation log.

Parameters

only_errors	optional	If true, only logs with error status ('Failure' or 'Retry') will be returned
-------------	----------	--

Response Messages

200 - OK

Response Schema

Name	Description	Required	Value
data		false	undefined []

Mobile Integration

Provision - Persist MSSP partner key

POST /web/api/v2.1/mobile-integration/provisioning/partner-key

Persists MSSP partner key - client ID and secret - for future customer provisioning.

Response Messages

201 - Partner key persisted successfully.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - 403 - You do not have authorization to complete request.

Body Schema

Name	Description	Required	Value
data	Data	true	see Provision - Persist MSSP partner key - body - data table
filter	Filter	false	see Provision - Persist MSSP partner key - body - filter table

Provision - Persist MSSP partner key - body - data

Name	Description	Required	Value
clientId	Partner client ID	true	string
secret	Partner secret	true	string

Provision - Persist MSSP partner key - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Provision - Update MSSP partner key

PUT /web/api/v2.1/mobile-integration/provisioning/partner-key

Updates MSSP partner key - client ID and secret - for future customer provisioning.

Response Messages

201 - Partner key updated successfully.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - 403 - You do not have authorization to complete request.

404 - 404 - Partner key not found.

Body Schema

Name	Description	Required	Value
data	Data	true	see Provision - Update MSSP partner key - body - data table
filter	Filter	false	see Provision - Update MSSP partner key - body - filter table

Provision - Update MSSP partner key - body - data

Name	Description	Required	Value
clientId	Partner client ID	true	string
secret	Partner secret	true	string

Provision - Update MSSP partner key - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Provision - Get MSSP partner key

GET /web/api/v2.1/mobile-integration/provisioning/partner-key

Gets MSSP partner key by scope

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Partner key retrieved successfully.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Provision - Get MSSP partner key - response - data table
errors	Errors	false	array

Provision - Get MSSP partner key - response - data

Name	Description	Required	Value
clientId	Partner client ID	true	string

Deletes MSSP partner key by client ID

DELETE /web/api/v2.1/mobile-integration/provisioning/partner-key/{client_id}

Provision - Delete MSSP partner key

Response Messages

204 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Partner key not found

Body Schema

Name	Description	Required	Value
filter	Filter	false	see Deletes MSSP partner key by client ID - body - filter table

Deletes MSSP partner key by client ID - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Provision - Provision tenant with admin user

POST /web/api/v2.1/mobile-integration/provisioning/tenant

Provision a new tenant and create an admin user for the tenant account

Response Messages

201 - Tenant provisioned and admin user created

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - 403 - You do not have authorization to complete request.

Body Schema

Name	Description	Required	Value
data	Data	true	see Provision - Provision tenant with admin user - body - data table
filter	Filter	false	see Provision - Provision tenant with admin user - body - filter table

Provision - Provision tenant with admin user - body - data

Name	Description	Required	Value
adminEmail	User's email address	true	string
adminFirstName	User's first name	true	string
adminLastName	User's last name	true	string
adminNotificationEmail	Notification email for sending details	false	string

Provision - Provision tenant with admin user - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Provision - Get tenant with users

GET /web/api/v2.1/mobile-integration/provisioning/tenant

Gets tenant with users by scope

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Tenant retrieved

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Provision - Get tenant with users - response - data table
errors	Errors	false	array

Provision - Get tenant with users - response - data

Name	Description	Required	Value
id	Tenant ID	true	string
name	Tenant name	true	string
adminUser	Tenant admin user	false	see Provision - Get tenant with users - response - adminUser table
users	Tenant users	false	see Provision - Get tenant with users - response - users table

Provision - Get tenant with users - response - adminUser

Name	Description	Required	Value
created	User's creation date	true	string
email	User's email address	true	string
firstName	User's first name	true	string
id	User ID	true	string
lastName	User's last name	true	string
role	User's role	true	see Provision - Get tenant with users - response - role table
notificationEmail	Notification email for sending details	false	string

Provision - Get tenant with users - response - role

Name	Description	Required	Value
id	Role ID	true	string
name	Role name	true	string

Provision - Get tenant with users - response - users

Name	Description	Required	Value
created	User's creation date	true	string

email	User's email address	true	string
firstName	User's first name	true	string
id	User ID	true	string
lastName	User's last name	true	string
role	User's role	true	see Provision - Get tenant with users - response - role table
notificationEmail	Notification email for sending details	false	string

Provision - Get tenant with users - response - role

Name	Description	Required	Value
id	Role ID	true	string
name	Role name	true	string

Provision - Check if tenant can be provisioned

GET /web/api/v2.1/mobile-integration/provisioning/can-provision-tenant

Checks if tenant can be provisioned by scope

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Tenant retrieved

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Provision - Check if tenant can be provisioned - response - data table
errors	Errors	false	array

Provision - Check if tenant can be provisioned - response - data

Name	Description	Required	Value
canProvision	Can provision tenant	true	boolean
affectingScopes	Affectingscopes	false	see Provision - Check if tenant can be provisioned - response - affectingScopes table
msspScope	Is MSSP scope	false	boolean
reason	Reason for not being able to provision tenant	false	string
reasonCode	Reason code for not being able to provision tenant	false	string
underMSSPScope	Is under MSSP scope	false	boolean

Provision - Check if tenant can be provisioned - response - affectingScopes

Name	Description	Required	Value
id	Scope ID	true	string
level	Scope level	true	string

Provision - Provision MSSP partner with admin user

POST /web/api/v2.1/mobile-integration/mssp-provisioning/partner

Provision a new MSSP partner and create an admin user for the partner account

Response Messages

201 - MSSP partner provisioned and admin user created

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - 403 - You do not have authorization to complete request.

Body Schema

Name	Description	Required	Value
data	Data	true	see Provision - Provision MSSP partner with admin user - body - data table
filter	Filter	false	see Provision - Provision MSSP partner with admin user - body - filter table

Provision - Provision MSSP partner with admin user - body - data

Name	Description	Required	Value
adminEmail	User's email address	true	string
adminFirstName	User's first name	true	string
adminLastName	User's last name	true	string
adminNotificationEmail	Notification email for sending details	false	string

Provision - Provision MSSP partner with admin user - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Provision - Get MSSP partner with admin user

GET /web/api/v2.1/mobile-integration/mssp-provisioning/partner

Gets MSSP partner with the first admin user by scope

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - MSSP partner retrieved

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Provision - Get MSSP partner with admin user - response - data table
errors	Errors	false	array

Provision - Get MSSP partner with admin user - response - data

Name	Description	Required	Value
id	MSSP partner ID	true	string
name	MSSP partner name	true	string
adminUser	MSSP partner admin user	false	see Provision - Get MSSP partner with admin user - response - adminUser table

Provision - Get MSSP partner with admin user - response - adminUser

Name	Description	Required	Value
created	User's creation date	true	string
email	User's email address	true	string
firstName	User's first name	true	string
id	User ID	true	string
lastName	User's last name	true	string
role	User's role	true	see Provision - Get MSSP partner with admin user - response - role table
notificationEmail	Notification email for sending details	false	string

Provision - Get MSSP partner with admin user - response - role

Name	Description	Required	Value
id	Role ID	true	string
name	Role name	true	string

Devices - Get list of devices for specific scope

GET /web/api/v2.1/mobile-integration/devices

Devices - Get list devices for specific scope

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
appversion__in	optional	Include devices with given app versions. Example: "2.5.1.1320".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
deviceid__contains	optional	Include devices by device IDs that contain text
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
healthstate__in	optional	Include devices only with given health state. Example: "normal".
limit	optional	Limit number of returned items (1-1000). Example: "10".
model__contains	optional	Include devices by models that contain text
osversion__contains	optional	Include devices by os version that contain text
platform__in	optional	Include devices only of given platforms. Example: "android".
privileges__in	optional	Include devices only with given privileges. Example: "none".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
tenant	optional	Indicates a tenant scope request
trackingid1__contains	optional	Include devices by external tracking IDs that contain text
trackingid2__contains	optional	Include devices by another external tracking IDs that contain text
user__contains	optional	Include devices by users that contain text

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Devices - Get list of devices for specific scope - response - pagination table
data	Response data	false	see Devices - Get list of devices for specific scope - response - data table
errors	Errors	false	array

Devices - Get list of devices for specific scope - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Devices - Get list of devices for specific scope - response - data

Name	Description	Required	Value
accountId	A reference to the containing account	true	string
accountName	Name of the containing account	true	string
alertCounts	Alertcounts	true	see Devices - Get list of devices for specific scope - response - alertCounts table
deviceId	MDM device ID	true	string
groupId	A reference to the containing network group	true	string
groupName	Name of the containing network group	true	string
id	Id	true	integer
registrationSource	MDM name or initiator in case of activations	true	string
registrationType	Registration type	true	enum
siteId	A reference to the containing site	true	string
siteName	Name of the containing site	true	string
threatCounts	Threatcounts	true	see Devices - Get list of devices for specific scope - response - threatCounts table
appState	ZipApp state	false	enum
appVersion	Version of the ZippApp	false	string
debugMode	Debugmode	false	boolean
developerMode	Developermode	false	boolean

encrypted	Encrypted	false	boolean
healthState	Highest health state of the device	false	enum
lastActiveOn	When we received last heartbeat	false	string
managedState	UEM state of the device	false	enum
model	Device manufacturer and model	false	string
osVersion	Device os version	false	string
owner	User email	false	string
platform	Device platform	false	enum
policyUpdatedAt	When the corresponding policy was updated	false	string
privileges	Either rooted or jailbroken for devices with privileges. Otherwise none	false	enum
protected	Protected	false	boolean
registeredOn	When the ZippApp registered	false	string
registrationDate	When the activation for this device was created	false	string
screenLocked	Screenlocked	false	boolean
stagefreightVulnerable	Stagefreightvulnerable	false	boolean
trackingId1	External tracking ID of device	false	string
trackingId2	Another external tracking ID of device	false	string
unofficialAppstore	Unofficialappstore	false	boolean

Devices - Get list of devices for specific scope - response - alertCounts

Name	Description	Required	Value
adminResolvedCount	How many threats are resolved by admin	true	integer
conditionalAccessCount	How many threats is in conditional access	true	integer
mitigatedCount	How many threats are mitigated	true	integer
notMitigatedCount	How many threats are not mitigated	true	integer

Devices - Get list of devices for specific scope - response - threatCounts

Name	Description	Required	Value
adminResolvedCount	How many threats are resolved by admin	true	integer
conditionalAccessCount	How many threats is in conditional access	true	integer
mitigatedCount	How many threats are mitigated	true	integer
notMitigatedCount	How many threats are not mitigated	true	integer

Incidents - Get list of incidents

GET /web/api/v2.1/mobile-integration/incidents

Incidents - Get list of incidents

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
analystverdict__in	optional	Include incident only of given analyst verdicts. Example: "true_positive".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
deviceid__contains	optional	Include incidents by device IDs that contain text
deviceid__in	optional	Include incidents only of given device ids. Example: "a,b,c,-,1,2,3,-,4,5,6".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
incidentstatus__in	optional	Include incident only of given incident statuses. Example: "unresolved".
kind__in	optional	Include incidents only of given kinds. Example: "t,h,r,e,a,t".
limit	optional	Limit number of returned items (1-1000). Example: "10".

severity__in	optional	Include incident only of given severities. Example: "low".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
status__in	optional	Include incident only of given statuses. Example: "not_mitigated".
statusaction__in	optional	Include incident only of given status actions. Example: "conditional_access".
tenant	optional	Indicates a tenant scope request
user__contains	optional	Include incidents by user email that contain text

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Incidents - Get list of incidents - response - pagination table
data	Response data	false	see Incidents - Get list of incidents - response - data table
errors	Errors	false	array

Incidents - Get list of incidents - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Incidents - Get list of incidents - response - data

Name	Description	Required	Value
accountId	A reference to the containing account	true	string
accountName	Name of the containing account	true	string
analystVerdict	Analystverdict	true	string
description	Description	true	string
details	Details	true	see Incidents - Get list of incidents - response - details table
detectionEngine	Detectionengine	true	string
detectionType	Detectiontype	true	string
deviceId	Deviceid	true	string
groupId	A reference to the containing network group	true	string
groupName	Name of the containing network group	true	string
id	Id	true	integer
incidentStatus	Incidentstatus	true	string
investigation	Investigation	true	string
kind	Kind	true	string
osType	Ostype	true	string
osVersion	Osversion	true	string
remediationStep	Remediationstep	true	string

reportedTime	Reportedtime	true	string
severity	Severity	true	string
siteld	A reference to the containing site	true	string
siteName	Name of the containing site	true	string
status	Status	true	string
statusAction	Statusaction	true	string
trackingId1	Trackingid1	true	string
trackingId2	Trackingid2	true	string
type	Type	true	string
userEmail	Useremail	true	string
userNotified	Usernotified	true	boolean
detail	Detail	false	string
network	Network	false	string
notes	Notes	false	see Incidents - Get list of incidents - response - notes table

Incidents - Get list of incidents - response - details

Name	Description	Required	Value
applicationDeveloper	Applicationdeveloper	true	string
applicationName	Applicationname	true	string
applicationPackage	Applicationpackage	true	string
deviceTime	Devicetime	true	string
fileHash	Filehash	true	string
fileName	Filename	true	string
installerSource	Installersource	true	string
malwareThreatName	Malwarethreatname	true	string
networkInterface	Networkinterface	true	string
processName	Processname	true	string
routerBSSID	Routerbssid	true	string
routerSSID	Routerssid	true	string
suspectedUrl	Suspectedurl	true	string

Incidents - Get list of incidents - response - notes

Name	Description	Required	Value
author		true	string
authorId		true	string
createdAt		true	string
edited		true	boolean
id		true	integer
text		true	string
updatedAt		true	string

Network Discovery

Get Network Discovery Table

GET /web/api/v2.1/ranger/table-view

Get the data for each row in the Network Discovery Device Inventory Table. Best practice: Set filters. Each row is a set of parameters that quickly fills the pagination limits.

BEST PRACTICE

Set filters. Each row is a set of parameters that quickly fills the pagination limits.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
agentids	optional	List of agent ids. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
devicefunction__conta	optional	Free-text filter by device function (supports multiple values).

ins		Example: "security,mobile".
devicereviews	optional	The device review state
devicetype	optional	Device type. Example: "Server/Workstation/...".
devicetypes	optional	Device types
discoverymethods	optional	Discovery methods
domains	optional	Included network domains. Example: "mybusiness,workgroup".
externalip	optional	Search using external IP
externalip__contains	optional	Free-text filter by visible IP (supports multiple values). Example: "192.168.0.1/24,10.1".
firstseen__between	optional	Date range refor first seen(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
firstseen__gt	optional	Devices first seen after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
firstseen__gte	optional	Devices first seen after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
firstseen__lt	optional	Devices first seen before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
firstseen__lte	optional	Devices first seen before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
gatewaymacaddress	optional	A gateway mac address to search for
gatewaymacaddress__contains	optional	Free-text filter by gateway mac address (supports multiple values). Example: "aa:ee:b1".
hostnames	optional	Hostnames
hostnames__contains	optional	Free-text filter by hostname (supports multiple values). Example: "s1_host,SomeHost".
ids	optional	List of device ids. Example: "225494730938493804,225494730938493915".
knownfingerprintingdata	optional	Known fingerprinting data. Example: "Manufacturer".
lastseen__between	optional	Date range for last seen(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".

lastseen__gt	optional	Devices last seen after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastseen__gte	optional	Devices last seen after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastseen__lt	optional	Devices last seen before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastseen__lte	optional	Devices last seen before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
limit	optional	Limit number of returned items (1-1000). Example: "10".
localip	optional	Search using local IP
localip__contains	optional	Free-text filter by IP Address (supports multiple values). Example: "192.168.0.1/24,10.1".
macaddress	optional	A mac address to search for
macaddress__contains	optional	Free-text filter by mac address (supports multiple values). Example: "aa:ee:b1".
managedstate	optional	Is the device managed
managedstates	optional	Is the device managed
manufacturer	optional	Manufacturer of the device or network interface
manufacturer__contains	optional	Free-text filter by manufacturer (supports multiple values). Example: "Company".
networkname	optional	Search using network name
networkname__contains	optional	Free-text filter by network name (supports multiple values). Example: "Office".
osname	optional	Os name
ostype	optional	OS type
ostypes	optional	Included OS types
osversion	optional	Os version
osversion__contains	optional	Free-text filter by OS full name and version (supports multiple values). Example: "Service Pack 1".
period	optional	Period. Example: "latest".
query	optional	Query
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".

sitenames	optional	Included site names. Example: "Office,Test".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
subnetaddress__contains	optional	Free-text filter by Subnet Address (supports multiple values). Example: "192.168.0.1/24,10.1".
tagname__contains	optional	Free-text filter by tag name (supports multiple values). Example: "iot".
tcpports__contains	optional	Free-text filter by tcp port (supports multiple values). Example: "80,24".
udpports__contains	optional	Free-text filter by udp port (supports multiple values). Example: "137,2002".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Network Discovery Table - response - pagination table
data	Response data	false	see Get Network Discovery Table - response - data table
errors	Errors	false	array

Get Network Discovery Table - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Network Discovery Table - response - data

Name	Description	Required	Value
agentId	The agent id if this is a known managed device	false	string
deviceFunction	Function of the device	false	string
deviceReview	The device review state	false	string
deviceReviewLog	Log of actions for this device	false	see Get Network Discovery Table - response - deviceReviewLog table
deviceType	Role of the device	false	string
discoveryMethods	Methods used to discover the device	false	string []
domain	The domain of the device	false	string
externallp	Main Gateway Visible IP	false	string
fingerprintScore	The confidence for this fingerprinting result	false	integer
firstSeen	Time the device was first seen	false	string
gatewayIpAddress	Main gateway IP address	false	string
gatewayMacAddress	Main gateway MAC address	false	string
hasIdentity	Would we be able to identify this device over time	false	boolean
hasUserLabel	True if it has a user label	false	boolean
hostnames	Array of host names	false	string []
id	Id of the device	false	string

ipAddresses	A list of ip addresses. When it is not combined it is always one element	false	string []
labelUpdatedAt	The date of the last label update	false	string
labelUserName	The user that changed the label	false	string
lastSeen	Time the device was last seen	false	string
localIp	Local ip of the device	false	string
macAddress	Mac address of the device	false	string
managedState	Protection state of the device	false	string
manufacturer	Manufacturer of the device or network interface	false	string
networkName	The network name	false	string
networks	A list of all the networks associated to the device. When it is not combined it is always one element	false	see Get Network Discovery Table - response - networks table
osName	OS Name/Version of the device	false	string
osType	Os Type of the device	false	string
osVersion	OS Version of the device	false	string
previousDeviceFunction	Previous Function of the device if manually changed	false	string
previousOsType	Previous Os Type of the device if manually changed	false	string
previousOsVersion	Previous OS Version of the device if manually changed	false	string
siteName	Site name	false	string
subnetAddress	Main subnet address	false	string
tags	The tags	false	see Get Network Discovery Table - response - tags table
tcpPorts	TCP Ports	false	integer []
udpPorts	UDP Ports	false	integer []

Get Network Discovery Table - response - deviceReviewLog

Name	Description	Required	Value
current		false	string
previous		false	string

reason		false	string
reasonDetails		false	string
updatedAt		false	string
username		false	string

Get Network Discovery Table - response - networks

Name	Description	Required	Value
externallp	Main Gateway Visible IP	false	string
gatewayIpAddress	Main gateway IP address	false	string
gatewayMacAddress	Main gateway MAC address	false	string
ip	The IP of the device in the network	false	string
networkName	The network name	false	string
subnetAddress	Main subnet address	false	string

Get Network Discovery Table - response - tags

Name	Description	Required	Value
id	The tag id	true	string
description	The tag description	false	string
kind	Kind of tag if relevant	false	string
name	The tag name	false	string

Export Network Discovery Data

GET /web/api/v2.1/ranger/report/csv

Export Network Discovery data to csv. You can set filters to get only relevant data. The response sends the csv data as text.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
agentids	optional	List of agent ids. Example:

		"225494730938493804,225494730938493915".
devicefunction__contains	optional	Free-text filter by device function (supports multiple values). Example: "security,mobile".
devicereviews	optional	The device review state
devicetype	optional	Device type. Example: "Server/Workstation/...".
devicetypes	optional	Device types
discoverymethods	optional	Discovery methods
domains	optional	Included network domains. Example: "mybusiness,workgroup".
externalip	optional	Search using external IP
externalip__contains	optional	Free-text filter by visible IP (supports multiple values). Example: "192.168.0.1/24,10.1".
firstseen__between	optional	Date range for first seen(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
firstseen__gt	optional	Devices first seen after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
firstseen__gte	optional	Devices first seen after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
firstseen__lt	optional	Devices first seen before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
firstseen__lte	optional	Devices first seen before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
gatewaymacaddress	optional	A gateway mac address to search for
gatewaymacaddress__contains	optional	Free-text filter by gateway mac address (supports multiple values). Example: "aa:ee:b1".
hostnames	optional	Hostnames
hostnames__contains	optional	Free-text filter by hostname (supports multiple values). Example: "s1_host,SomeHost".
ids	optional	List of device ids. Example: "225494730938493804,225494730938493915".
knownfingerprintingdata	optional	Known fingerprinting data. Example: "Manufacturer".
lastseen__between	optional	Date range for last seen(format: <from_timestamp>-

		<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
lastseen__gt	optional	Devices last seen after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastseen__gte	optional	Devices last seen after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastseen__lt	optional	Devices last seen before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastseen__lte	optional	Devices last seen before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
localip	optional	Search using local IP
localip__contains	optional	Free-text filter by IP Address (supports multiple values). Example: "192.168.0.1/24,10.1".
macaddress	optional	A mac address to search for
macaddress__contains	optional	Free-text filter by mac address (supports multiple values). Example: "aa:ee:b1".
managedstate	optional	Is the device managed
managedstates	optional	Is the device managed
manufacturer	optional	Manufacturer of the device or network interface
manufacturer__contains	optional	Free-text filter by manufacturer (supports multiple values). Example: "Company".
networkname	optional	Search using network name
networkname__contains	optional	Free-text filter by network name (supports multiple values). Example: "Office".
osname	optional	Os name
ostype	optional	OS type
ostypes	optional	Included OS types
osversion	optional	Os version
osversion__contains	optional	Free-text filter by OS full name and version (supports multiple values). Example: "Service Pack 1".
period	optional	Period. Example: "latest".
query	optional	Query
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".

sitenames	optional	Included site names. Example: "Office,Test".
subnetaddress__contains	optional	Free-text filter by Subnet Address (supports multiple values). Example: "192.168.0.1/24,10.1".
tagname__contains	optional	Free-text filter by tag name (supports multiple values). Example: "iot".
tcpports__contains	optional	Free-text filter by tcp port (supports multiple values). Example: "80,24".
udpports__contains	optional	Free-text filter by udp port (supports multiple values). Example: "137,2002".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

JSON Raw Data

GET /web/api/v2.1/ranger/{inventory_id}/json

Get a json string with the Network Discovery data for one device, by ID in the Device Inventory Data.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	
errors	Errors	false	array

Export JSON Raw Data

GET /web/api/v2.1/ranger/{inventory_id}/json/export

Export the raw data for one device, by its ID in the Device Inventory Data. To get the ID, run ranger/table-view (see Get Network Discovery Table). Use this command to get data for Support.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

404 - Not found

Get Network Discovery Settings

GET /web/api/v2.1/ranger/settings

Network Discovery gives full visibility of all devices connected to your network. Network Discovery scans your corporate environment to identify and manage connected devices, even those not protected by or supported by SentinelOne. Network Discovery identifies devices as:

- * Secured - End-user computer or laptop, or server, with a SentinelOne Agent.
- * Unsecured - Endpoint of supported hardware and OS, without an Agent.
- * Unsupported - Hardware or software that are not compatible with the SentinelOne Agent.
- * Unknown - Network Discovery cannot determine if the device is Unsecured or Unsupported.

When you install Windows Agents with Network Discovery, the Agents can become scanners. Selected scanners from networks that you enable for scanning find connected devices with passive and active scan techniques. The scanners send the collected data to Network Discovery on the Management. Network Discovery then runs fingerprinting to identify and classify unique devices and to update the Device Inventory Table in the Management Console. With port scanning, it is important that you understand the legal and ethical considerations and that you document a Network Discovery plan and implementation. See <https://support.sentinelone.com/hc/en-us/articles/360041484913> > Legal Considerations and Proper Implementation.

Requirements: Network Discovery license, Cloud-based Management (not supported for On-Prem), Global user or Account user with scope access to the Account with a Network Discovery license.

Use this command to get the Network Discovery Settings for the Account of the given ID (run "accounts" to get an Account ID). The Response shows if Network Discovery is enabled on the Account, the protocols and ports of the scans, and more:

- * minAgentsInNetworkToScan - To help you determine which networks are corporate, Network Discovery looks at the number of secured endpoints (Agents) in a network. If there are not enough Agents in a network - set by this parameter value - Network Discovery considers the network to be non-corporate and will not scan it.
- * scanOnlyLocalSubnets - If false, Network Discovery scans remote subnets that do not have online Network Discovery scanners. This will create network traffic through the corporate firewall (and between different corporate locations), which can impact network performance.
- * usePeriodicSnapshots - A complete scan includes scanner port scanning and Network Discovery AI analysis of the scanner data to update the Device Inventory Snapshot. If this setting is true, Network Discovery runs a new scan on an interval. If snapshotPeriod is shorter, the data is more accurate. If longer, there is better performance.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Network Discovery Settings - response - data table
errors	Errors	false	array

Get Network Discovery Settings - response - data

Name	Description	Required	Value
accountId	Account id	false	string
autoEnableNetworks	All networks that match the min agents configuration will be enabled automatically	false	boolean
combineDevices	Combine devices as one among multiple networks	false	boolean
enabled	Is the Network Discovery collection enabled for the account	false	boolean
icmpScan	ICMP scan enabled	false	boolean
mdnsScan	MDNS scan enabled	false	boolean
minAgentsInNetworkToScan	Minimum agents required in a network to be listed as selectable for scan	false	integer
multiScanSsdP	SSDP Multicast scan enabled	false	boolean
networkDecommissionValue	The number of days to archive a network which was not enabled for scan	false	integer
newNetworkInHours	Networks are going to be marked as new for this period	false	integer
rdnsScan	RDNS scan enabled	false	boolean
restrictions	A set of IP addresses that should not be scanned in the specific network	false	see Get Network Discovery Settings - response - restrictions table
scanOnlyLocalSubnets	Scan only local subnets	false	boolean
scopeId	Scope id	false	string
smbScan	SMB scan enabled	false	boolean
snapshotPeriod	Period in minutes for each snapshot	false	integer
snmpScan	SNMP scan enabled	false	boolean
specificPorts	[FUTURE] A set of specific ports allowed to be used as source ports for an active scan	false	see Get Network Discovery Settings - response - specificPorts table
tcpPorts	TCP Ports	false	integer []

tcpPortScan	TCP Port scan enabled	false	boolean
udpPorts	UDP Ports	false	integer []
udpPortScan	UDP Port scan enabled	false	boolean
useFullDnsScan	DNS Full scan enabled	false	boolean
usePeriodicSnapshots	Network Discovery views are generated periodically by the snapshot period	false	boolean
useSpecificPorts	[FUTURE] Use only specific ports defined in specific ports as source ports of active scans	false	boolean

Get Network Discovery Settings - response - restrictions

Name	Description	Required	Value
annotation	An optional note with the reason for the restriction	false	string
type		false	enum
values	It will be one IP or one CIDR or two values for a Range	false	string []

Get Network Discovery Settings - response - specificPorts

Name	Description	Required	Value
type		false	enum
values	It can be a single port or two ports [start, end] for a Range	false	integer []

Update Network Discovery Settings

PUT /web/api/v2.1/ranger/settings

Change the Network Discovery Settings. Best Practice: Get the current settings before you change them. See: Get Network Discovery Settings.

BEST PRACTICE

Get the current settings before you change them. See: [Get Network Discovery Settings](#).

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Network Discovery Settings - response - data table
errors	Errors	false	array

Update Network Discovery Settings - response - data

Name	Description	Required	Value
accountId	Account id	false	string
autoEnableNetworks	All networks that match the min agents configuration will be enabled automatically	false	boolean
combineDevices	Combine devices as one among multiple networks	false	boolean
enabled	Is the Network Discovery collection enabled for the account	false	boolean
icmpScan	ICMP scan enabled	false	boolean
mdnsScan	MDNS scan enabled	false	boolean
minAgentsInNetworkToScan	Minimum agents required in a network to be listed as selectable for scan	false	integer
multiScanSsdP	SSDP Multicast scan enabled	false	boolean
networkDecommissionValue	The number of days to archive a network which was not enabled for scan	false	integer
newNetworkInHours	Networks are going to be marked as new for this period	false	integer
rdnsScan	RDNS scan enabled	false	boolean
restrictions	A set of IP addresses that should not be scanned in the specific network	false	see Update Network Discovery Settings - response - restrictions table
scanOnlyLocalSubnets	Scan only local subnets	false	boolean
scopeId	Scope id	false	string
smbScan	SMB scan enabled	false	boolean
snapshotPeriod	Period in minutes for each snapshot	false	integer
snmpScan	SNMP scan enabled	false	boolean
specificPorts	[FUTURE] A set of specific ports allowed to be used as source ports for an active scan	false	see Update Network Discovery Settings - response - specificPorts table
tcpPorts	TCP Ports	false	integer []

tcpPortScan	TCP Port scan enabled	false	boolean
udpPorts	UDP Ports	false	integer []
udpPortScan	UDP Port scan enabled	false	boolean
useFullDnsScan	DNS Full scan enabled	false	boolean
usePeriodicSnapshots	Network Discovery views are generated periodically by the snapshot period	false	boolean
useSpecificPorts	[FUTURE] Use only specific ports defined in specific ports as source ports of active scans	false	boolean

Update Network Discovery Settings - response - restrictions

Name	Description	Required	Value
annotation	An optional note with the reason for the restriction	false	string
type		false	enum
values	It will be one IP or one CIDR or two values for a Range	false	string []

Update Network Discovery Settings - response - specificPorts

Name	Description	Required	Value
type		false	enum
values	It can be a single port or two ports [start, end] for a Range	false	integer []

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Network Discovery Settings - body - data table
filter	Filter	true	see Update Network Discovery Settings - body - filter table

Update Network Discovery Settings - body - data

Name	Description	Required	Value
accountId	Account id	false	string
autoEnableNetworks	All networks that match the min agents configuration will be enabled automatically	false	boolean
combineDevices	Combine devices as one among multiple networks	false	boolean
enabled	Is the Network Discovery collection enabled for the account	false	boolean
icmpScan	ICMP scan enabled	false	boolean
mdnsScan	MDNS scan enabled	false	boolean
minAgentsInNetworkToScan	Minimum agents required in a network to be listed as selectable for scan	false	integer
multiScanSsdP	SSDP Multicast scan enabled	false	boolean
networkDecommissionValue	The number of days to archive a network which was not enabled for scan	false	integer
newNetworkInHours	Networks are going to be marked as new for this period	false	integer
rdnsScan	RDNS scan enabled	false	boolean
restrictions	A set of IP addresses that should not be scanned in the specific network	false	see Update Network Discovery Settings - body - restrictions table
scanOnlyLocalSubnets	Scan only local subnets	false	boolean
scopeId	Scope id	false	string
smbScan	SMB scan enabled	false	boolean
snapshotPeriod	Period in minutes for each snapshot	false	integer
snmpScan	SNMP scan enabled	false	boolean
specificPorts	[FUTURE] A set of specific ports allowed to be used as source ports for an active scan	false	see Update Network Discovery Settings - body - specificPorts table
tcpPorts	TCP Ports	false	integer []

tcpPortScan	TCP Port scan enabled	false	boolean
udpPorts	UDP Ports	false	integer []
udpPortScan	UDP Port scan enabled	false	boolean
useFullDnsScan	DNS Full scan enabled	false	boolean
usePeriodicSnapshots	Network Discovery views are generated periodically by the snapshot period	false	boolean
useSpecificPorts	[FUTURE] Use only specific ports defined in specific ports as source ports of active scans	false	boolean

Update Network Discovery Settings - body - restrictions

Name	Description	Required	Value
annotation	An optional note with the reason for the restriction	false	string
type		false	enum
values	It will be one IP or one CIDR or two values for a Range	false	string []

Update Network Discovery Settings - body - specificPorts

Name	Description	Required	Value
type		false	enum
values	It can be a single port or two ports [start, end] for a Range	false	integer []

Update Network Discovery Settings - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Change Device Review in Bulk

POST /web/api/v2.1/ranger/device-review

Change the review state of more than one device.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Change Device Review in Bulk - response - data table
errors	Errors	false	array

Change Device Review in Bulk - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Change Device Review in Bulk - body - data table
filter	Filter	true	see Change Device Review in Bulk - body - filter table

Change Device Review in Bulk - body - data

Name	Description	Required	Value
deviceReview	The device review state	true	enum
reason	Reason for the change	false	string
reasonDetails	Reason details for the change	false	string

Change Device Review in Bulk - body - filter

Name	Description	Required	Value
accountIds	Single Account ID to filter by	false	string []
agentIds	List of agent ids	false	string []
deviceFunction__contains	Free-text filter by device function (supports multiple values)	false	string []
deviceReviews	The device review state	false	string []
deviceType	Device type	false	string
deviceTypes	Device types	false	string []
discoveryMethods	Discovery methods	false	string []
domains	Included network domains	false	string []
externalIp	Search using external IP	false	string
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
firstSeen__between	Date range refor first seen(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
firstSeen__gt	Devices first seen after this timestamp	false	string
firstSeen__gte	Devices first seen after or at this timestamp	false	string
firstSeen__lt	Devices first seen before this timestamp	false	string
firstSeen__lte	Devices first seen before or at this	false	string

	timestamp		
gatewayMacAddress	A gateway mac address to search for	false	string
gatewayMacAddress__contains	Free-text filter by gateway mac address (supports multiple values)	false	string []
hasUserLabel		false	boolean
hostnames	Hostnames	false	string []
hostnames__contains	Free-text filter by hostname (supports multiple values)	false	string []
ids	List of device ids	false	string []
knownFingerprintingData	Known fingerprinting data	false	string []
lastSeen__between	Date range for last seen(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSeen__gt	Devices last seen after this timestamp	false	string
lastSeen__gte	Devices last seen after or at this timestamp	false	string
lastSeen__lt	Devices last seen before this timestamp	false	string
lastSeen__lte	Devices last seen before or at this timestamp	false	string
localIp	Search using local IP	false	string
localIp__contains	Free-text filter by IP Address (supports multiple values)	false	string []
macAddress	A mac address to search for	false	string
macAddress__contains	Free-text filter by mac address (supports multiple values)	false	string []
managedState	Is the device managed	false	string
managedStates	Is the device managed	false	string []
manufacturer	Manufacturer of the device or network interface	false	string
manufacturer__contains	Free-text filter by manufacturer (supports multiple values)	false	string []
networkName	Search using network name	false	string
networkName__contains	Free-text filter by network name (supports multiple values)	false	string []
osName	Os name	false	string

osType	OS type	false	string
osTypes	Included OS types	false	string []
osVersion	Os version	false	string
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
period	Period	false	enum
query	Query	false	string
siteIds	Single Site ID to filter by	false	string []
siteNames	Included site names	false	string []
subnetAddress__contains	Free-text filter by Subnet Address (supports multiple values)	false	string []
tagName__contains	Free-text filter by tag name (supports multiple values)	false	string []
tcpPorts__contains	Free-text filter by tcp port (supports multiple values)	false	integer []
udpPorts__contains	Free-text filter by udp port (supports multiple values)	false	integer []

Change Device Review

PUT /web/api/v2.1/ranger/device-review/{inventory_id}

Change the review state of one device.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Change Device Review - response - data table
errors	Errors	false	array

Change Device Review - response - data

Name	Description	Required	Value
agentId	The agent id if this is a known managed device	false	string
deviceFunction	Function of the device	false	string
deviceReview	The device review state	false	string
deviceReviewLog	Log of actions for this device	false	see Change Device Review - response - deviceReviewLog table
deviceType	Role of the device	false	string
discoveryMethods	Methods used to discover the device	false	string []
domain	The domain of the device	false	string
externallp	Main Gateway Visible IP	false	string
fingerPrintScore	The confidence for this fingerprinting result	false	integer
firstSeen	Time the device was first seen	false	string
gatewayIpAddress	Main gateway IP address	false	string
gatewayMacAddress	Main gateway MAC address	false	string
hasIdentity	Would we be able to identify this device over time	false	boolean
hasUserLabel	True if it has a user label	false	boolean
hostnames	Array of host names	false	string []
id	Id of the device	false	string
ipAddresses	A list of ip addresses. When it is not combined it is always one element	false	string []
labelUpdatedAt	The date of the last label update	false	string
labelUserName	The user that changed the label	false	string
lastSeen	Time the device was last seen	false	string
localIp	Local ip of the device	false	string
macAddress	Mac address of the device	false	string
managedState	Protection state of the device	false	string
manufacturer	Manufacturer of the device or network interface	false	string

networkName	The network name	false	string
networks	A list of all the networks associated to the device. When it is not combined it is always one element	false	see Change Device Review - response - networks table
osName	OS Name/Version of the device	false	string
osType	Os Type of the device	false	string
osVersion	OS Version of the device	false	string
previousDeviceFunction	Previous Function of the device if manually changed	false	string
previousOsType	Previous Os Type of the device if manually changed	false	string
previousOsVersion	Previous OS Version of the device if manually changed	false	string
siteName	Site name	false	string
subnetAddress	Main subnet address	false	string
tags	The tags	false	see Change Device Review - response - tags table
tcpPorts	TCP Ports	false	integer []
udpPorts	UDP Ports	false	integer []

Change Device Review - response - deviceReviewLog

Name	Description	Required	Value
current		false	string
previous		false	string
reason		false	string
reasonDetails		false	string
updatedAt		false	string
username		false	string

Change Device Review - response - networks

Name	Description	Required	Value
------	-------------	----------	-------

externallp	Main Gateway Visible IP	false	string
gatewayIpAddress	Main gateway IP address	false	string
gatewayMacAddress	Main gateway MAC address	false	string
ip	The IP of the device in the network	false	string
networkName	The network name	false	string
subnetAddress	Main subnet address	false	string

Change Device Review - response - tags

Name	Description	Required	Value
id	The tag id	true	string
description	The tag description	false	string
kind	Kind of tag if relevant	false	string
name	The tag name	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Change Device Review - body - data table

Change Device Review - body - data

Name	Description	Required	Value
deviceReview	The device review state	true	enum
reason	Reason for the change	false	string
reasonDetails	Reason details for the change	false	string

Change Device Tags

POST /web/api/v2.1/ranger/tags

Change the device tags.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Change Device Tags - response - data table
errors	Errors	false	array

Change Device Tags - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Change Device Tags - body - filter table
data	Data	false	see Change Device Tags - body - data table

Change Device Tags - body - filter

Name	Description	Required	Value
accountIds	Single Account ID to filter by	false	string []
agentIds	List of agent ids	false	string []
deviceFunction__contains	Free-text filter by device function (supports multiple values)	false	string []
deviceReviews	The device review state	false	string []
deviceType	Device type	false	string
deviceTypes	Device types	false	string []
discoveryMethods	Discovery methods	false	string []
domains	Included network domains	false	string []
externalIp	Search using external IP	false	string
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
firstSeen__between	Date range refor first seen(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
firstSeen__gt	Devices first seen after this timestamp	false	string
firstSeen__gte	Devices first seen after or at this timestamp	false	string
firstSeen__lt	Devices first seen before this timestamp	false	string
firstSeen__lte	Devices first seen before or at this timestamp	false	string
gatewayMacAddress	A gateway mac address to search for	false	string
gatewayMacAddress__contains	Free-text filter by gateway mac address (supports multiple values)	false	string []
hasUserLabel		false	boolean
hostnames	Hostnames	false	string []
hostnames__contains	Free-text filter by hostname (supports multiple values)	false	string []
ids	List of device ids	false	string []

knownFingerprintingData	Known fingerprinting data	false	string []
lastSeen__between	Date range for last seen(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSeen__gt	Devices last seen after this timestamp	false	string
lastSeen__gte	Devices last seen after or at this timestamp	false	string
lastSeen__lt	Devices last seen before this timestamp	false	string
lastSeen__lte	Devices last seen before or at this timestamp	false	string
localIp	Search using local IP	false	string
localIp__contains	Free-text filter by IP Address (supports multiple values)	false	string []
macAddress	A mac address to search for	false	string
macAddress__contains	Free-text filter by mac address (supports multiple values)	false	string []
managedState	Is the device managed	false	string
managedStates	Is the device managed	false	string []
manufacturer	Manufacturer of the device or network interface	false	string
manufacturer__contains	Free-text filter by manufacturer (supports multiple values)	false	string []
networkName	Search using network name	false	string
networkName__contains	Free-text filter by network name (supports multiple values)	false	string []
osName	Os name	false	string
osType	OS type	false	string
osTypes	Included OS types	false	string []
osVersion	Os version	false	string
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
period	Period	false	enum
query	Query	false	string
sitelds	Single Site ID to filter by	false	string []

siteNames	Included site names	false	string []
subnetAddress__contains	Free-text filter by Subnet Address (supports multiple values)	false	string []
tagName__contains	Free-text filter by tag name (supports multiple values)	false	string []
tcpPorts__contains	Free-text filter by tcp port (supports multiple values)	false	integer []
udpPorts__contains	Free-text filter by udp port (supports multiple values)	false	integer []

Change Device Tags - body - data

Name	Description	Required	Value
id	The tag id	true	string
description	The tag description	false	string
kind	Kind of tag if relevant	false	string
name	The tag name	false	string

Network Discovery Self Enablement

Get Self Enablement

GET /web/api/v2.1/ranger/enablement

[DEPRECATED] Use the Update Account, Get Account, Get Sites, or the Update Site Add-ons APIs instead.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
activeagents	optional	The number of non-decommissioned agents in the site
activeagents__between	optional	Agent count (between). Example: "2-8".
activeagents__gt	optional	Agent count (more than)

activeagents__gte	optional	Agent count (more than or equal)
activeagents__lt	optional	Agent count (less than)
activeagents__lte	optional	Agent count (less than or equal)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
id	optional	The enablement id. Example: "225494730938493804".
ids	optional	A list of ids to get. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".
rangerenabled	optional	Network Discovery Enabled true/false
rangerproenabled	optional	[DEPRECATED]. Use rangerEnabled instead. Network Discovery Pro Enabled true/false
roguesenabled	optional	Unprotected Endpoints Discovery Enabled true/false
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
sitename	optional	The site name
sitename__contains	optional	Free-text filter by site name (supports multiple values)
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
tenant	optional	Indicates a tenant scope request

Response Messages

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 -

Change Network Discovery or Unprotected Endpoints Discovery Features

POST /web/api/v2.1/ranger/enablement

[DEPRECATED] Use the Update Account, Get Account, Get Sites, or the Update Site Add-ons APIs instead.

Response Messages

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 -

Body Schema

Name	Description	Required	Value
data	Data	true	see Change Network Discovery or Unprotected Endpoints Discovery Features - body - data table
filter	Filter	true	see Change Network Discovery or Unprotected Endpoints Discovery Features - body - filter table

Change Network Discovery or Unprotected Endpoints Discovery Features - body - data

Name	Description	Required	Value
rangerEnabled	Network Discovery Enabled true/false	false	boolean
rangerProEnabled	[DEPRECATED] Use rangerEnabled parameter instead. Network Discovery Pro Enabled true/false	false	boolean
roguesEnabled	Unprotected Endpoints Discovery Enabled true/false	false	boolean

Change Network Discovery or Unprotected Endpoints Discovery Features - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeAgents	The number of non-decommissioned agents in the site	false	integer
activeAgents__between	Agent count (between)	false	string
activeAgents__gt	Agent count (more than)	false	integer
activeAgents__gte	Agent count (more than or equal)	false	integer
activeAgents__lt	Agent count (less than)	false	integer
activeAgents__lte	Agent count (less than or equal)	false	integer
groupIds	List of Group IDs to filter by	false	string []
id	The enablement id	false	string
ids	A list of ids to get	false	string []
rangerEnabled	Network Discovery Enabled true/false	false	boolean
rangerProEnabled	[DEPRECATED]. Use rangerEnabled instead. Network Discovery Pro Enabled true/false	false	boolean
roguesEnabled	Unprotected Endpoints Discovery Enabled true/false	false	boolean
siteIds	List of Site IDs to filter by	false	string []

siteName	The site name	false	string
siteName__contains	Free-text filter by site name (supports multiple values)	false	string []
tenant	Indicates a tenant scope request	false	boolean

Change the Self-Enablement for Accounts

POST /web/api/v2.1/ranger/enable-self-management

[DEPRECATED] Use the Update Account, Get Account, Get Sites, or the Update Site Add-ons APIs instead.

Response Messages

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 -

Body Schema

Name	Description	Required	Value
data	Data	true	see Change the Self-Enablement for Accounts - body - data table
filter	Filter	true	see Change the Self-Enablement for Accounts - body - filter table

Change the Self-Enablement for Accounts - body - data

Name	Description	Required	Value
enable	enable: true/false	false	boolean

Change the Self-Enablement for Accounts - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []

Features Configuration for New Sites

GET /web/api/v2.1/ranger/enablement/defaults

[DEPRECATED] Use the Update Account, Get Account, Get Sites, or the Update Site Add-ons APIs instead..

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
------------	----------	---

Response Messages

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 -

Change Feature Defaults for New Sites

POST /web/api/v2.1/ranger/enablement/defaults

[DEPRECATED] Use the Update Account, Get Account, Get Sites, or the Update Site Add-ons APIs instead.

Response Messages

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 -

Body Schema

Name	Description	Required	Value
data	Data	true	see Change Feature Defaults for New Sites - body - data table
filter	Filter	true	see Change Feature Defaults for New Sites - body - filter table

Change Feature Defaults for New Sites - body - data

Name	Description	Required	Value
rangerEnabled	Network Discovery Enabled true/false	false	boolean
rangerProEnabled	[DEPRECATED] Use rangerEnabled parameter instead. Network Discovery Pro Enabled true/false	false	boolean
roguesEnabled	Unprotected Endpoints Discovery Enabled true/false	false	boolean

Change Feature Defaults for New Sites - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeAgents	The number of non-decommissioned agents in the site	false	integer
activeAgents__between	Agent count (between)	false	string
activeAgents__gt	Agent count (more than)	false	integer
activeAgents__gte	Agent count (more than or equal)	false	integer
activeAgents__lt	Agent count (less than)	false	integer
activeAgents__lte	Agent count (less than or equal)	false	integer
groupIds	List of Group IDs to filter by	false	string []
id	The enablement id	false	string
ids	A list of ids to get	false	string []
rangerEnabled	Network Discovery Enabled true/false	false	boolean
rangerProEnabled	[DEPRECATED]. Use rangerEnabled instead. Network Discovery Pro Enabled true/false	false	boolean
roguesEnabled	Unprotected Endpoints Discovery Enabled true/false	false	boolean
sitels	List of Site IDs to filter by	false	string []

siteName	The site name	false	string
siteName__contains	Free-text filter by site name (supports multiple values)	false	string []
tenant	Indicates a tenant scope request	false	boolean

Network Quarantine Control

Get Firewall Rules

GET /web/api/v2.1/firewall-control/{firewall_rule_category}

Get the Firewall Control rules for a scope specified by ID (run "accounts", "sites", "groups", or set "tenant" to "true") that match the filter. The response will be quite long because it includes all the rule properties, thus at least one of these filters is required: action, status, osType, name, or scope ID.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
actions	optional	Return firewall rules with the filtered action. Example: "Allow".
application__contains	optional	Free-text filter by application (supports multiple values)
applications	optional	Return firewall rules with the filtered firewall class.
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__between	optional	Return firewall rules created within this range (inclusive). Example: "1514978764288-1514978999999".
createdat__gt	optional	Return firewall rules created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Return firewall rules created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Return firewall rules created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Return firewall rules created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over

		more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
directions	optional	Return firewall rules with the filtered directions. Example: "any".
disablepagination	optional	If true, all rules for requested scope will be returned
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of ids to filter by. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".
locationids	optional	Filter by associated locations. Example: "225494730938493804,225494730938493915".
name	optional	Return firewall rules with the filtered name.
name__contains	optional	Free-text filter by the Rule name (supports multiple values)
ostypes	optional	Return firewall rules with the filtered os_type. Example: "linux".
protocol__contains	optional	Free-text filter by protocol (supports multiple values)
protocols	optional	Return firewall rules with the filtered protocols.
query	optional	Free text search on name, tag, application, protocol
scopes	optional	Return only firewall rules in this scope. Example: "account".
service__contains	optional	Free-text filter by service (supports multiple values)
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
statuses	optional	Return firewall rules with the filtered status. Example: "Enabled".
tagids	optional	Filter by associated tags. Example: "225494730938493804,225494730938493915".
tagname__contains	optional	Free-text filter by the Tag name (supports multiple values)
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Firewall Rules - response - pagination table
data	Response data	false	see Get Firewall Rules - response - data table
errors	Errors	false	array

Get Firewall Rules - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Firewall Rules - response - data

Name	Description	Required	Value
action	Defines if agent shall Block or Allow use of firewalls which matches the rule parameters.	false	enum
application	Application for the rule	false	
createdAt	Date of rule creation	false	string
creator	Full name of the creating user	false	string
creatorId	Id of the creating user	false	string
description	Description	false	string
direction	Defines the Direction of the Firewall rule.	false	enum
editable	True if the rule can be modified at this scope level	false	boolean
id	Rule ID	false	string
localHost	Local host	false	
localPort	Local ports	false	
location	Location associated with the rule	false	see Get Firewall Rules - response - location table
name	The name of the firewall rule.	false	string
order	Position in the list of rules	false	integer
osType	[DEPRECATED] Please use os_types since multiple os types are	false	enum

	supported.This field will return the first os_type, not necessarily the only one.		
osTypes	Os types	false	string []
productId	Product identifier. Unique for a specific product module, per vendor ID, Interface.	false	string
protocol	The protocol.	false	string
remoteHost	[DEPRECATED] First remote host in the rule. Full list in remote_hosts	false	
remoteHosts	List of remote hosts	false	see Get Firewall Rules - response - remoteHosts table
remotePort	Remote ports	false	
ruleCategory	Network quarantine rule or standard firewall rule	false	enum
scope	Scope of the rule	false	enum
scopeId	The group or site id depending on the scope. null if it is global.	false	string
status	Defines if rule is Enabled or Disabled	false	enum
tag	[DEPRECATED] Free text to describe the rule. Please use description instead.	false	string
tagIds	Tag ids	false	string []
tagNames	Tag names	false	string []
tags	Tags	false	see Get Firewall Rules - response - tags table
updatedAt	Date of last update	false	string

Get Firewall Rules - response - location

Name	Description	Required	Value
type	Location type	true	enum
values	Location IDs (applicable for the "specific" location type only)	false	see Get Firewall Rules - response - values table

Get Firewall Rules - response - values

Name	Description	Required	Value
id	Location ID	true	string
name	Location name	false	string
scope	Location scope	false	enum

Get Firewall Rules - response - remoteHosts

Name	Description	Required	Value
type	Type of the host	false	enum
values	Value of the host	false	string []

Get Firewall Rules - response - tags

Name	Description	Required	Value
id		false	string
name		false	string

Create Firewall Rule

POST /web/api/v2.1/firewall-control/{firewall_rule_category}

Create a Firewall Control rule for a scope specified by ID (run "accounts", "sites", "groups", or set "tenant" to "true") and specific OS, to allow or block network traffic to matching endpoints.

You can create one clean-up rule, with the Action of Allow or Block and with no other parameters defined explicitly. Make this the default rule at the end of your rule list. Traffic that does not match other rules first will match this rule. If you do not have a clean-up rule to match all traffic, the default Firewall Control behavior is to allow traffic that is not explicitly blocked.

Firewall Control requires Control SKU.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Firewall Rule - response - data table
errors	Errors	false	array

Create Firewall Rule - response - data

Name	Description	Required	Value
action	Defines if agent shall Block or Allow use of firewalls which matches the rule parameters.	false	enum
application	Application for the rule	false	
createdAt	Date of rule creation	false	string
creator	Full name of the creating user	false	string
creatorId	Id of the creating user	false	string
description	Description	false	string
direction	Defines the Direction of the Firewall rule.	false	enum
editable	True if the rule can be modified at this scope level	false	boolean
id	Rule ID	false	string
localHost	Local host	false	
localPort	Local ports	false	
location	Location associated with the rule	false	see Create Firewall Rule - response - location table
name	The name of the firewall rule.	false	string
order	Position in the list of rules	false	integer
osType	[DEPRECATED] Please use os_types since multiple os types are supported.This field will return the first os_type, not necessarily the only one.	false	enum
osTypes	Os types	false	string []
productId	Product identifier. Unique for a specific product module, per vendor ID, Interface.	false	string
protocol	The protocol.	false	string
remoteHost	[DEPRECATED] First remote host in the rule. Full list in remote_hosts	false	
remoteHosts	List of remote hosts	false	see Create Firewall Rule - response - remoteHosts table

remotePort	Remote ports	false	
ruleCategory	Network quarantine rule or standard firewall rule	false	enum
scope	Scope of the rule	false	enum
scopeId	The group or site id depending on the scope. null if it is global.	false	string
status	Defines if rule is Enabled or Disabled	false	enum
tag	[DEPRECATED] Free text to describe the rule. Please use description instead.	false	string
tagIds	Tag ids	false	string []
tagNames	Tag names	false	string []
tags	Tags	false	see Create Firewall Rule - response - tags table
updatedAt	Date of last update	false	string

Create Firewall Rule - response - location

Name	Description	Required	Value
type	Location type	true	enum
values	Location IDs (applicable for the "specific" location type only)	false	see Create Firewall Rule - response - values table

Create Firewall Rule - response - values

Name	Description	Required	Value
id	Location ID	true	string
name	Location name	false	string
scope	Location scope	false	enum

Create Firewall Rule - response - remoteHosts

Name	Description	Required	Value
------	-------------	----------	-------

type	Type of the host	false	enum
values	Value of the host	false	string []

Create Firewall Rule - response - tags

Name	Description	Required	Value
id		false	string
name		false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Firewall Rule - body - data table
filter	Filter	true	see Create Firewall Rule - body - filter table

Create Firewall Rule - body - data

Name	Description	Required	Value
action	Defines if agent shall Block or Allow use of firewalls which matches the rule parameters.	true	enum
name	The name of the firewall rule.	true	string
status	Defines if rule is Enabled or Disabled	true	enum
application	Application for the rule	false	see Create Firewall Rule - body - application table
description	Description	false	string
direction	Defines the Direction of the Firewall rule.	false	enum
localHost	Local host structure with a type and a set of values	false	see Create Firewall Rule - body - localHost table
localPort	Local ports structure with a type and a set of values	false	see Create Firewall Rule - body - localPort table
location	Location structure with a type and a set of values	false	see Create Firewall Rule - body - location table
osType	[DEPRECATED] Please use os_types since multiple os types are supported.This field will return the first os_type, not necessarily the only one.	false	enum
osTypes	Os types	false	string []
protocol	The protocol	false	string
remoteHost	[DEPRECATED] Please use remote_hosts.Remote host structure with a type and a set of values.	false	see Create Firewall Rule - body - remoteHost table
remoteHosts	List of remote hosts, each structured with a type and a set of values	false	see Create Firewall Rule - body - remoteHosts table
remotePort	Remote ports structure with a type and a set of values	false	see Create Firewall Rule - body - remotePort table
tag	[DEPRECATED] Free text to describe the rule. Please use description instead.	false	string
tagIds	Tag ids	false	string []

Create Firewall Rule - body - application

Name	Description	Required	Value
type	Type of the application	false	enum
values	Value of the application	false	string []

Create Firewall Rule - body - localHost

Name	Description	Required	Value
type	Type of the host	false	enum
values	Value of the host	false	string []

Create Firewall Rule - body - localPort

Name	Description	Required	Value
type	Type of the ports	false	enum
values	A list of port numbers	false	integer []

Create Firewall Rule - body - location

Name	Description	Required	Value
type	Location type	true	enum
values	Location IDs (applicable for the "specific" location type only)	false	see Create Firewall Rule - body - values table

Create Firewall Rule - body - values

Name	Description	Required	Value
id	Location ID	true	string
name	Location name	false	string

scope	Location scope	false	enum
-------	----------------	-------	------

Create Firewall Rule - body - remoteHost

Name	Description	Required	Value
type	Type of the host	false	enum
values	Value of the host	false	string []

Create Firewall Rule - body - remoteHosts

Name	Description	Required	Value
type	Type of the host	false	enum
values	Value of the host	false	string []

Create Firewall Rule - body - remotePort

Name	Description	Required	Value
type	Type of the ports	false	enum
values	A list of port numbers	false	integer []

Create Firewall Rule - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Delete Rules

DELETE /web/api/v2.1/firewall-control/{firewall_rule_category}

Delete Firewall Control rules that match the filter.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Rules - response - data table
errors	Errors	false	array

Delete Rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	false	see Delete Rules - body - filter table

Delete Rules - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
actions	Return firewall rules with the filtered action.	false	string []
application__contains	Free-text filter by application (supports multiple values)	false	string []
applications	Return firewall rules with the filtered firewall class.	false	string []
createdAt__between	Return firewall rules created within this range (inclusive)	false	string
createdAt__gt	Return firewall rules created after this timestamp.	false	string
createdAt__gte	Return firewall rules created after or at this timestamp.	false	string
createdAt__lt	Return firewall rules created before this timestamp.	false	string
createdAt__lte	Return firewall rules created before or at this timestamp.	false	string
directions	Return firewall rules with the filtered directions.	false	string []
groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
locationIds	Filter by associated locations	false	string []
name	Return firewall rules with the filtered name.	false	string
name__contains	Free-text filter by the Rule name (supports multiple values)	false	string []
osTypes	Return firewall rules with the filtered os_type.	false	string []
protocol__contains	Free-text filter by protocol (supports multiple values)	false	string []
protocols	Return firewall rules with the filtered protocols.	false	string []

query	Free text search on name, tag, application, protocol	false	string
scopes	Return only firewall rules in this scope	false	string []
service__contains	Free-text filter by service (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
statuses	Return firewall rules with the filtered status.	false	string []
tagIds	Filter by associated tags	false	string []
tagName__contains	Free-text filter by the Tag name (supports multiple values)	false	string []
tenant	Indicates a tenant scope request	false	boolean

Copy Rules

POST /web/api/v2.1/firewall-control/{firewall_rule_category}/copy-rules

Copy a set of rules to other scopes.

In the filter of the body, enter the properties to define the source. In the data field of the body, define the targets by ID. To get a scope ID, run 'accounts', 'sites', or 'groups'.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Copy Rules - response - data table
errors	Errors	false	array

Copy Rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	false	see Copy Rules - body - data table
filter	Filter	false	see Copy Rules - body - filter table

Copy Rules - body - data

Name	Description	Required	Value
accountId	Target account	false	string
accountIds	List of Account IDs to filter by	false	string []
groupId	Target group	false	string
groupIds	[DEPRECATED] Target group(s)	false	string []
siteId	Target site	false	string
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Copy Rules - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
actions	Return firewall rules with the filtered action.	false	string []
application__contains	Free-text filter by application (supports multiple values)	false	string []
applications	Return firewall rules with the filtered firewall class.	false	string []
createdAt__between	Return firewall rules created within this range (inclusive)	false	string
createdAt__gt	Return firewall rules created after this timestamp.	false	string
createdAt__gte	Return firewall rules created after or at this timestamp.	false	string
createdAt__lt	Return firewall rules created before this timestamp.	false	string
createdAt__lte	Return firewall rules created before or at this timestamp.	false	string
directions	Return firewall rules with the filtered directions.	false	string []

groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
locationIds	Filter by associated locations	false	string []
name	Return firewall rules with the filtered name.	false	string
name__contains	Free-text filter by the Rule name (supports multiple values)	false	string []
osTypes	Return firewall rules with the filtered os_type.	false	string []
protocol__contains	Free-text filter by protocol (supports multiple values)	false	string []
protocols	Return firewall rules with the filtered protocols.	false	string []
query	Free text search on name, tag, application, protocol	false	string
scopes	Return only firewall rules in this scope	false	string []
service__contains	Free-text filter by service (supports multiple values)	false	string []
siteIds	List of Site IDs to filter by	false	string []
statuses	Return firewall rules with the filtered status.	false	string []
tagIds	Filter by associated tags	false	string []
tagName__contains	Free-text filter by the Tag name (supports multiple values)	false	string []
tenant	Indicates a tenant scope request	false	boolean

Move Rules

POST /web/api/v2.1/firewall-control/{firewall_rule_category}/move-rules

Remove Firewall Rules, defined with the ID of the rules (run 'firewall-control'), from scopes specified by ID (run 'accounts', 'sites', or 'groups') and add the rules to the scope IDs in the data field.

Firewall Control requires Control SKU.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Move Rules - response - data table
errors	Errors	false	array

Move Rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	false	see Move Rules - body - data table
filter	Filter	false	see Move Rules - body - filter table

Move Rules - body - data

Name	Description	Required	Value
accountId	Target account	false	string
accountIds	List of Account IDs to filter by	false	string []
groupId	Target group	false	string
groupIds	[DEPRECATED] Target group(s)	false	string []
siteId	Target site	false	string
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Move Rules - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
actions	Return firewall rules with the filtered action.	false	string []
application__contains	Free-text filter by application (supports multiple values)	false	string []
applications	Return firewall rules with the filtered firewall class.	false	string []
createdAt__between	Return firewall rules created within this range (inclusive)	false	string
createdAt__gt	Return firewall rules created after this timestamp.	false	string
createdAt__gte	Return firewall rules created after or at this timestamp.	false	string
createdAt__lt	Return firewall rules created before this timestamp.	false	string
createdAt__lte	Return firewall rules created before or at this timestamp.	false	string
directions	Return firewall rules with the filtered directions.	false	string []

groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
locationIds	Filter by associated locations	false	string []
name	Return firewall rules with the filtered name.	false	string
name__contains	Free-text filter by the Rule name (supports multiple values)	false	string []
osTypes	Return firewall rules with the filtered os_type.	false	string []
protocol__contains	Free-text filter by protocol (supports multiple values)	false	string []
protocols	Return firewall rules with the filtered protocols.	false	string []
query	Free text search on name, tag, application, protocol	false	string
scopes	Return only firewall rules in this scope	false	string []
service__contains	Free-text filter by service (supports multiple values)	false	string []
siteIds	List of Site IDs to filter by	false	string []
statuses	Return firewall rules with the filtered status.	false	string []
tagIds	Filter by associated tags	false	string []
tagName__contains	Free-text filter by the Tag name (supports multiple values)	false	string []
tenant	Indicates a tenant scope request	false	boolean

Set Location

POST /web/api/v2.1/firewall-control/{firewall_rule_category}/set-location

Set location attributes for a Location Aware Firewall Control rule. These rules are applied by Agents only if the network parameters of the endpoint match the properties of the location definition. To get a Location ID, run "locations".
Firewall Control requires Control SKU.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set Location - response - data table
errors	Errors	false	array

Set Location - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Set Location - body - data table
filter	Filter	false	see Set Location - body - filter table

Set Location - body - data

Name	Description	Required	Value
type	Location type	true	enum
values	Location IDs (applicable for the "specific" location type only)	false	see Set Location - body - values table

Set Location - body - values

Name	Description	Required	Value
id	Location ID	true	string
name	Location name	false	string
scope	Location scope	false	enum

Set Location - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
actions	Return firewall rules with the filtered action.	false	string []
application__contains	Free-text filter by application (supports multiple values)	false	string []
applications	Return firewall rules with the filtered firewall class.	false	string []
createdAt__between	Return firewall rules created within this range (inclusive)	false	string
createdAt__gt	Return firewall rules created after this timestamp.	false	string
createdAt__gte	Return firewall rules created after or at this timestamp.	false	string
createdAt__lt	Return firewall rules created before this timestamp.	false	string

createdAt__lte	Return firewall rules created before or at this timestamp.	false	string
directions	Return firewall rules with the filtered directions.	false	string []
groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
locationIds	Filter by associated locations	false	string []
name	Return firewall rules with the filtered name.	false	string
name__contains	Free-text filter by the Rule name (supports multiple values)	false	string []
osTypes	Return firewall rules with the filtered os_type.	false	string []
protocol__contains	Free-text filter by protocol (supports multiple values)	false	string []
protocols	Return firewall rules with the filtered protocols.	false	string []
query	Free text search on name, tag, application, protocol	false	string
scopes	Return only firewall rules in this scope	false	string []
service__contains	Free-text filter by service (supports multiple values)	false	string []
siteIds	List of Site IDs to filter by	false	string []
statuses	Return firewall rules with the filtered status.	false	string []
tagIds	Filter by associated tags	false	string []
tagName__contains	Free-text filter by the Tag name (supports multiple values)	false	string []
tenant	Indicates a tenant scope request	false	boolean

Reorder Rules

PUT /web/api/v2.1/firewall-control/{firewall_rule_category}/reorder

Change the order of rules for a scope specified by ID (run "accounts", "sites", or "groups").

The Agent looks at the rules based on their order in the Firewall Control policy, from the top to the bottom. First it goes through the Group rules, then the Site rules, then the Account rules, then the Global rules. When the Agent finds a rule that matches the parameters of the traffic, that rule is applied. The Agent does not continue to the lower rules in the list. Thus, the scope and the order of the rules is important.

Firewall Control requires Control SKU.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Reorder Rules - response - data table
errors	Errors	false	array

Reorder Rules - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Reorder Rules - body - filter table
data	Data	false	see Reorder Rules - body - data table

Reorder Rules - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
osTypes	[DEPRECATED] Rules OS type (was relevant for when each OS type had its own rule order)	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Reorder Rules - body - data

Name	Description	Required	Value
id	Rule ID	true	string
order	Desired position in the list of rules	true	integer

Get Configuration

GET /web/api/v2.1/firewall-control/{firewall_rule_category}/configuration

Get the Firewall Control configuration for a given scope.

To filter the results for a scope:

* Global - Make sure "tenant" is "true" and no other scope ID is given.

* Account - Make sure "tenant" is "false" and at least one Account ID is given.

* Site - Make sure "tenant" is "false" and at least one Site ID is given.

The response shows if Firewall Control is enabled for the scope, if Location Awareness is enabled, the higher scope from which this scope inherited the configuration, and whether a lower scope inherits this configuration.

Firewall Control requires Control SKU.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
------------	----------	---

groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Configuration - response - data table
errors	Errors	false	array

Get Configuration - response - data

Name	Description	Required	Value
enabled	Firewall control enabled for the scope	false	boolean
inheritAllFirewallRules	Inherit all the rules and tags from the parent scope. Expands on 'inherits' value.	false	boolean
inheritedFrom	If null it means it is own policy else it tells the ancestor for the policy. For groups options are null/Site/Global, for site options are null/Global.	false	string
inherits	True if rules are decoupled from parent rules	false	boolean
inheritSettings	Inherit firewall settings from parent scope	false	boolean
locationAware	Firewall control supports location awareness for the scope	false	boolean
reportBlocked	Agent should report blocked events	false	boolean
selectedTags	Selected tags	false	string []

Update Configuration

PUT /web/api/v2.1/firewall-control/{firewall_rule_category}/configuration

Change the Firewall Control configuration for a given scope.

To get the ID of a scope, run "accounts", "sites", or "groups". To change the Global configuration, leave the filters empty and set "tenant" to "true". In the Body, you can set if Firewall Control is enabled for the scope, if Location Awareness is enabled, the higher scope from which this scope inherits the configuration ("Global" or a scope ID), whether the lower scopes inherit this configuration, and whether blocked actions are reported.

Firewall Control requires Control SKU.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Configuration - response - data table
errors	Errors	false	array

Update Configuration - response - data

Name	Description	Required	Value
enabled	Firewall control enabled for the scope	false	boolean
inheritAllFirewallRules	Inherit all the rules and tags from the parent scope. Expands on 'inherits' value.	false	boolean
inheritedFrom	If null it means it is own policy else it tells the ancestor for the policy. For groups options are null/Site/Global, for site options are null/Global.	false	string
inherits	True if rules are decoupled from parent rules	false	boolean
inheritSettings	Inherit firewall settings from parent scope	false	boolean
locationAware	Firewall control supports location awareness for the scope	false	boolean
reportBlocked	Agent should report blocked events	false	boolean
selectedTags	Selected tags	false	string []

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Configuration - body - data table
filter	Filter	true	see Update Configuration - body - filter table

Update Configuration - body - data

Name	Description	Required	Value
enabled	Firewall control enabled for the scope	false	boolean
inheritAllFirewallRules	Inherit all the rules and tags from the parent scope. Expands on 'inherits' value.	false	boolean
inheritedFrom	If null it means it is own policy else it tells the ancestor for the policy. For groups options are null/Site/Global, for site options are null/Global.	false	string
inherits	True if rules are decoupled from parent rules	false	boolean
inheritSettings	Inherit firewall settings from parent scope	false	boolean
locationAware	Firewall control supports location awareness for the scope	false	boolean
reportBlocked	Agent should report blocked events	false	boolean
selectedTags	Selected tags	false	string []

Update Configuration - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Export Rules

GET /web/api/v2.1/firewall-control/{firewall_rule_category}/export

Export Firewall Control rules that match the filter to a JSON file from a scope specified by ID (run "accounts", "sites", "groups", or leave the scope empty and set "tenant" to "true") and import them to another scope (with the "import" command).

Firewall Control requires Control SKU.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
actions	optional	Return firewall rules with the filtered action. Example: "Allow".
application__contains	optional	Free-text filter by application (supports multiple values)
applications	optional	Return firewall rules with the filtered firewall class.
createdat__between	optional	Return firewall rules created within this range (inclusive). Example: "1514978764288-1514978999999".
createdat__gt	optional	Return firewall rules created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Return firewall rules created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Return firewall rules created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Return firewall rules created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
directions	optional	Return firewall rules with the filtered directions. Example: "any".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of ids to filter by. Example: "225494730938493804,225494730938493915".
locationids	optional	Filter by associated locations. Example: "225494730938493804,225494730938493915".
name	optional	Return firewall rules with the filtered name.
name__contains	optional	Free-text filter by the Rule name (supports multiple values)
ostypes	optional	Return firewall rules with the filtered os_type. Example: "linux".
protocol__contains	optional	Free-text filter by protocol (supports multiple values)
protocols	optional	Return firewall rules with the filtered protocols.
query	optional	Free text search on name, tag, application, protocol
scopes	optional	Return only firewall rules in this scope. Example: "account".
service__contains	optional	Free-text filter by service (supports multiple values)
siteids	optional	List of Site IDs to filter by. Example:

		"225494730938493804,225494730938493915".
statuses	optional	Return firewall rules with the filtered status. Example: "Enabled".
tagids	optional	Filter by associated tags. Example: "225494730938493804,225494730938493915".
tagname__contains	optional	Free-text filter by the Tag name (supports multiple values)
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Import Rules

POST /web/api/v2.1/firewall-control/{firewall_rule_category}/import

Import Firewall Control rules from an exported JSON file to scopes specified by ID (run "accounts", "sites", "groups", or leave the scope empty and set "tenant" to "true"). Firewall Control requires Control SKU, in the target and in the source.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Import Rules - response - data table
errors	Errors	false	array

Import Rules - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
formData		false	see Import Rules - body - formData table

Import Rules - body - formData

Name	Description	Required	Value
file	File	true	file
accountIds	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".	false	string []
groupIds	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".	false	string []
siteIds	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".	false	string []
tenant	Indicates a tenant scope request	false	boolean

Enable/Disable Rules

PUT /web/api/v2.1/firewall-control/{firewall_rule_category}/enable

Change the status of a set of Firewall Control rules that match the filter to "Enabled" or "Disabled". In one request, you can set one status or the other.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Enable/Disable Rules - response - data table
errors	Errors	false	array

Enable/Disable Rules - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Enable/Disable Rules - body - data table
filter	Filter	true	see Enable/Disable Rules - body - filter table

Enable/Disable Rules - body - data

Name	Description	Required	Value
status	should the rules be enabled/disabled	true	enum

Enable/Disable Rules - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
actions	Return firewall rules with the filtered action.	false	string []
application__contains	Free-text filter by application (supports multiple values)	false	string []
applications	Return firewall rules with the filtered firewall class.	false	string []
createdAt__between	Return firewall rules created within this range (inclusive)	false	string
createdAt__gt	Return firewall rules created after this timestamp.	false	string
createdAt__gte	Return firewall rules created after or at this timestamp.	false	string
createdAt__lt	Return firewall rules created before this timestamp.	false	string
createdAt__lte	Return firewall rules created before or at this timestamp.	false	string
directions	Return firewall rules with the filtered directions.	false	string []
groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
locationIds	Filter by associated locations	false	string []
name	Return firewall rules with the filtered name.	false	string
name__contains	Free-text filter by the Rule name	false	string []

	(supports multiple values)		
osTypes	Return firewall rules with the filtered os_type.	false	string []
protocol__contains	Free-text filter by protocol (supports multiple values)	false	string []
protocols	Return firewall rules with the filtered protocols.	false	string []
query	Free text search on name, tag, application, protocol	false	string
scopes	Return only firewall rules in this scope	false	string []
service__contains	Free-text filter by service (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
statuses	Return firewall rules with the filtered status.	false	string []
tagIds	Filter by associated tags	false	string []
tagName__contains	Free-text filter by the Tag name (supports multiple values)	false	string []
tenant	Indicates a tenant scope request	false	boolean

Get Protocols

GET /web/api/v2.1/firewall-control/{firewall_rule_category}/protocols

Get a list of protocols that can be used in Firewall Control rules.

Parameters

countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
disablepagination	optional	If true, all rules for requested scope will be returned
limit	optional	Limit number of returned items (1-1000). Example: "10".
query	optional	Full text search on protocols
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000

		items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Protocols - response - pagination table
data	Response data	false	see Get Protocols - response - data table
errors	Errors	false	array

Get Protocols - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Protocols - response - data

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
name	Description of the protocol	false	string
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean
value	Short code identifying the protocol	false	string

Add Rule Tags

POST /web/api/v2.1/firewall-control/{firewall_rule_category}/add-tags

Create a Firewall Rule tag.

Create tags to represent Firewall policies - a set of rules in a specific order. After you create the tag, add rules to it.

Notes:

- * Tags apply to a scope and cannot be linked to rules from different scopes.
- * Tags must be 2 to 256 characters.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Add Rule Tags - response - data table
errors	Errors	false	array

Add Rule Tags - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Add Rule Tags - body - data table
filter	Filter	true	see Add Rule Tags - body - filter table

Add Rule Tags - body - data

Name	Description	Required	Value
tagIds	Tag ids	false	string []

Add Rule Tags - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
actions	Return firewall rules with the filtered action.	false	string []
application__contains	Free-text filter by application (supports multiple values)	false	string []
applications	Return firewall rules with the filtered firewall class.	false	string []
createdAt__between	Return firewall rules created within this range (inclusive)	false	string
createdAt__gt	Return firewall rules created after this timestamp.	false	string
createdAt__gte	Return firewall rules created after or at this timestamp.	false	string
createdAt__lt	Return firewall rules created before this timestamp.	false	string
createdAt__lte	Return firewall rules created before or at this timestamp.	false	string
directions	Return firewall rules with the filtered directions.	false	string []
groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
locationIds	Filter by associated locations	false	string []
name	Return firewall rules with the filtered name.	false	string
name__contains	Free-text filter by the Rule name	false	string []

	(supports multiple values)		
osTypes	Return firewall rules with the filtered os_type.	false	string []
protocol__contains	Free-text filter by protocol (supports multiple values)	false	string []
protocols	Return firewall rules with the filtered protocols.	false	string []
query	Free text search on name, tag, application, protocol	false	string
scopes	Return only firewall rules in this scope	false	string []
service__contains	Free-text filter by service (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
statuses	Return firewall rules with the filtered status.	false	string []
tagIds	Filter by associated tags	false	string []
tagName__contains	Free-text filter by the Tag name (supports multiple values)	false	string []
tenant	Indicates a tenant scope request	false	boolean

Remove Rule Tags

POST /web/api/v2.1/firewall-control/{firewall_rule_category}/remove-tags

Remove firewall tags from rules matching the filter.

Tags represent Firewall policies - a set of rules in a specific order. When you remove a rule with a tag, all scopes that subscribe to the tag get the change.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Remove Rule Tags - response - data table
errors	Errors	false	array

Remove Rule Tags - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Remove Rule Tags - body - data table
filter	Filter	true	see Remove Rule Tags - body - filter table

Remove Rule Tags - body - data

Name	Description	Required	Value
tagIds	Tag ids	false	string []

Remove Rule Tags - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
actions	Return firewall rules with the filtered action.	false	string []
application__contains	Free-text filter by application (supports multiple values)	false	string []
applications	Return firewall rules with the filtered firewall class.	false	string []
createdAt__between	Return firewall rules created within this range (inclusive)	false	string
createdAt__gt	Return firewall rules created after this timestamp.	false	string
createdAt__gte	Return firewall rules created after or at this timestamp.	false	string
createdAt__lt	Return firewall rules created before this timestamp.	false	string
createdAt__lte	Return firewall rules created before or at this timestamp.	false	string
directions	Return firewall rules with the filtered directions.	false	string []
groupIds	List of Group IDs to filter by	false	string []
ids	List of ids to filter by	false	string []
locationIds	Filter by associated locations	false	string []
name	Return firewall rules with the filtered name.	false	string
name__contains	Free-text filter by the Rule name	false	string []

	(supports multiple values)		
osTypes	Return firewall rules with the filtered os_type.	false	string []
protocol__contains	Free-text filter by protocol (supports multiple values)	false	string []
protocols	Return firewall rules with the filtered protocols.	false	string []
query	Free text search on name, tag, application, protocol	false	string
scopes	Return only firewall rules in this scope	false	string []
service__contains	Free-text filter by service (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
statuses	Return firewall rules with the filtered status.	false	string []
tagIds	Filter by associated tags	false	string []
tagName__contains	Free-text filter by the Tag name (supports multiple values)	false	string []
tenant	Indicates a tenant scope request	false	boolean

Overview

Cloud Inventory resource overview

POST /web/api/v2.1/xdr/assets/overview

Get overview of a resource belonging to a category

Parameters

accountids	optional	List of Account IDs to filter by
groupids	optional	List of Group IDs to filter by
siteids	optional	List of Site IDs to filter by

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data		false	see Cloud Inventory resource overview - response - data table
errors	Errors	false	array

Cloud Inventory resource overview - response - data

Name	Description	Required	Value
properties		false	see Cloud Inventory resource overview - response - properties table

Cloud Inventory resource overview - response - properties

Body Schema

Name	Description	Required	Value
agentUuid	Agent uuid	false	string
resourceId	Resource id	false	string

Platform Detection Rules

Get Managed Detection Rules

GET /web/api/v2.1/detection-library/rules

Return Catalog Rules for the given scope

Parameters

accountids	optional	account scope level id. Example: "225494730938493804".
activeresponse	optional	The active response status for the rule.
attacksurfaces	optional	To filter by attack surfaces associated with the rule.
categories	optional	Categories. Example: "Events".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__gte	optional	To filter by created-at greater than or equal to a datetime. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	To filter by created-at less than or equal to a datetime. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
customruleids	optional	custom rule ids. Example: "225494730938493804,225494730938493915".
description__contains	optional	To filter by a substring of the rule description
hidequery	optional	To filter by hideQuery of the rule params. Example: "Shown".
labels	optional	To filter by labels.
limit	optional	Limit number of returned items (1-1000). Example: "10".
mitretactics	optional	To filter by sources associated with the rule.
name__contains	optional	To filter by a substring of the rule name
platformruleids	optional	platform rule ids. Example:

		"225494730938493804,225494730938493915".
query	optional	Free-text filter by All fields(name, description, query content). You can enter multiple values, separated by commas. Example: "Service Pack 1".
s1ql__contains	optional	To filter by a substring of the query content
severities	optional	Severities. Example: "Info".
siteids	optional	site scope level id. Example: "225494730938493804".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
sources	optional	To filter by sources associated with the rule.
statuses	optional	Statuses. Example: "Activating".
tags	optional	To filter by tags.
updatedat__gte	optional	To filter by updated-at greater than or equal to a datetime. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	To filter by updated-at less than or equal to a datetime. Example: "2018-02-27T04:49:26.257525Z".
uselabels	optional	If True, use Labels naming instead of Tags (e.g., "Labels" instead of "Tags", "core" instead of "autoDefault").

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Managed Detection Rules not found

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

pagination	Pagination information	true	see Get Managed Detection Rules - response - pagination table
data	Response data	false	see Get Managed Detection Rules - response - data table
errors	Errors	false	array

Get Managed Detection Rules - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Managed Detection Rules - response - data

Name	Description	Required	Value
status	Enabled (Activated and sends alerts if triggered) or Disabled.	true	enum
activeResponse	The Active Response status of the Rule.	false	boolean
attackSurfaces	The attack surfaces associated with the rule.	false	string []
coolOffSettings	Receive only one alert and suppress additional alerts when a rule is triggered multiple times during the cool-off period. Mitigation actions set in the rule will not be applied to suppressed alerts.	false	see Get Managed Detection Rules - response - coolOffSettings table
correlationParams	Correlation params	false	see Get Managed Detection Rules - response - correlationParams table
createdAt	The time when the rule was created	false	string
createdBy	The vendor who created the rule.	false	string
deletedRuleIds	The associated rule IDs that have been already deleted.	false	string []
description	The rule description	false	string
generatedAlerts	The number of alerts generated by the rule.	false	integer
highestInheritedScopeLevel	The highest scope level the rule inherits from.	false	enum

id	The platform rule ID.	false	string
labels	Labels	false	
lastAlertTime	The time when the last alert was caught	false	string
mitre	The mitre tactics associated with the rule.	false	see Get Managed Detection Rules - response - mitre table
name	The rule name	false	string
networkQuarantine	True if the network quarantine is on.	false	boolean
notDeletedRuleIds	The associated rule IDs that have not been deleted.	false	string []
queryType	Define the query type: Correlation (made of multiple subqueries), Event (single query), or Processes (Deprecated).	false	enum
s1ql	The query	false	string
scheduledParams	Scheduled params	false	see Get Managed Detection Rules - response - scheduledParams table
scopeLevel	The scope level the rule is enabled for.	false	enum
severity	The severity of the rule.	false	enum
sources	The sources associated with the rule.	false	string []
tags	The tags associated with the rule. Tags are used to group rules together.	false	string []
treatAsThreat	The Treat as threat auto response - UNDEFINED/suspicious/malicious	false	enum
updatedAt	The time when the rule was updated	false	string

Get Managed Detection Rules - response - coolOffSettings

Name	Description	Required	Value
renotifyMinutes	The period of time in minutes in which alerts will be suppressed after the rule has been triggered.	true	integer

Get Managed Detection Rules - response - correlationParams

Name	Description	Required	Value
entity	A common entity used to group matching events.	true	enum
matchInOrder	Set to True to require subqueries to match in sequence to trigger an alert.	true	boolean
subQueries	The list of subqueries for the custom detection rule.	false	see Get Managed Detection Rules - response - subQueries table
timeWindow	The period of time in minutes in which subqueries must match to trigger an alert.	false	see Get Managed Detection Rules - response - timeWindow table

Get Managed Detection Rules - response - subQueries

Name	Description	Required	Value
matchesRequired	The number of times a subquery must match.	true	integer
subQuery	A subquery	true	string

Get Managed Detection Rules - response - timeWindow

Name	Description	Required	Value
windowMinutes	The period of time in minutes in which subqueries must match to trigger an alert.	false	enum

Get Managed Detection Rules - response - mitre

Name	Description	Required	Value
tactic	The mitre tactic	false	string
techniques	The mitre techniques	false	see Get Managed Detection Rules - response - techniques table

Get Managed Detection Rules - response - techniques

Name	Description	Required	Value
id	The mitre technique id	false	string
link	The mitre technique link	false	string
title	The mitre technique title	false	string

Get Managed Detection Rules - response - scheduledParams

Name	Description	Required	Value
lookbackWindowMinutes	Sets the evaluation lookback window in minutes. For example, set to 5 evaluates the alert over the past five minutes.	true	integer
query	The PowerQuery to run	true	string
runIntervalMinutes	How often the alert is evaluated, in minutes. If used with coolOffSettings then it must be a denominator of renotifyMinutes. If the lookbackWindowMinutes is less than 60 (1 hour), the minimum is 1 minute. For a window between 1 and 360 (6 hours), 5 minutes. For a window between 360 (6 hours) and 10080 (7 days), 15 minutes. For a window between 10080 (7 days) and 43200 (30 days), 60 minutes.	true	integer
alertPerRow	If True, an alert will be generated for each row detected in the defined lookback window. If False (default), get one alert for all detected events matched in the defined lookback window.	false	boolean
disableStreaksLogic	If True (default), disables streak counting logic for scheduled rules. If False, streak counting logic is enabled.	false	boolean
threshold	Receive an alert only if the number of rows in the result of the query matches the condition in the threshold	false	see Get Managed Detection Rules - response - threshold table

Get Managed Detection Rules - response - threshold

Name	Description	Required	Value
operator	Defines the operator to use in combination with the query and thresholdValue to set the threshold condition for an alert to trigger The default value is Greater	false	enum
value	Defines the threshold value that in combination with operator and the query sets the threshold condition for an alert to be triggered. The default value is 0	false	integer

Get Managed Detection Rules

GET /web/api/v2.1/detection-library/platform-rules

Return Managed Detection Rules for the given scope

Parameters

activeresponse	optional	The active response status for the rule.
attacksurfaces	optional	To filter by attack surfaces associated with the rule.
categories	optional	Categories. Example: "Events".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
description__contains	optional	To filter by a substring of the rule description
excludeids	optional	List of entity ids to exclude from select_all. Example: "225494730938493804,225494730938493915".
hidequery	optional	To filter by hideQuery of the rule params. Example: "Shown".
labels	optional	To filter by labels.
limit	optional	Limit number of returned items (1-1000). Example: "10".
mitretactics	optional	To filter by sources associated with the rule.

platformruleids	optional	platform rule ids. Example: "225494730938493804,225494730938493915".
rulenamesubstring	optional	To filter by a substring of the rule name
s1ql__contains	optional	To filter by a substring of the query content
scopeid	optional	The Account, Site, or Group ID, depending on the scope. Null if the scope is Global. Example: "225494730938493804".
scopelevel	optional	To filter by scope, enter one or more scopes, separated by commas. Example: "group".
severities	optional	Severities. Example: "Info".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sources	optional	To filter by sources associated with the rule.
statuses	optional	Statuses. Example: "Activating".
tags	optional	To filter by tags associated with the rule.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Managed Detection Rules not found

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Managed Detection Rules - response - pagination table
data	Response data	false	see Get Managed Detection Rules - response - data table
errors	Errors	false	array

Get Managed Detection Rules - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Managed Detection Rules - response - data

Name	Description	Required	Value
status	Enabled (Activated and sends alerts if triggered) or Disabled.	true	enum
activeResponse	The Active Response status of the Rule.	false	boolean
attackSurfaces	The attack surfaces associated with the rule.	false	string []
coolOffSettings	Receive only one alert and suppress additional alerts when a rule is triggered multiple times during the cool-off period. Mitigation actions set in the rule will not be applied to suppressed alerts.	false	see Get Managed Detection Rules - response - coolOffSettings table
correlationParams	Correlation params	false	see Get Managed Detection Rules - response - correlationParams table
createdAt	The time when the rule was created	false	string
createdBy	The vendor who created the rule.	false	string
deletedRuleIds	The associated rule IDs that have been already deleted.	false	string []
description	The rule description	false	string
generatedAlerts	The number of alerts generated by the rule.	false	integer
highestInheritedScopeLevel	The highest scope level the rule inherits from.	false	enum

id	The platform rule ID.	false	string
labels	Labels	false	
lastAlertTime	The time when the last alert was caught	false	string
mitre	The mitre tactics associated with the rule.	false	see Get Managed Detection Rules - response - mitre table
name	The rule name	false	string
networkQuarantine	True if the network quarantine is on.	false	boolean
notDeletedRuleIds	The associated rule IDs that have not been deleted.	false	string []
queryType	Define the query type: Correlation (made of multiple subqueries), Event (single query), or Processes (Deprecated).	false	enum
s1ql	The query	false	string
scheduledParams	Scheduled params	false	see Get Managed Detection Rules - response - scheduledParams table
scopeLevel	The scope level the rule is enabled for.	false	enum
severity	The severity of the rule.	false	enum
sources	The sources associated with the rule.	false	string []
tags	The tags associated with the rule. Tags are used to group rules together.	false	string []
treatAsThreat	The Treat as threat auto response - UNDEFINED/suspicious/malicious	false	enum
updatedAt	The time when the rule was updated	false	string

Get Managed Detection Rules - response - coolOffSettings

Name	Description	Required	Value
renotifyMinutes	The period of time in minutes in which alerts will be suppressed after the rule has been triggered.	true	integer

Get Managed Detection Rules - response - correlationParams

Name	Description	Required	Value
entity	A common entity used to group matching events.	true	enum
matchInOrder	Set to True to require subqueries to match in sequence to trigger an alert.	true	boolean
subQueries	The list of subqueries for the custom detection rule.	false	see Get Managed Detection Rules - response - subQueries table
timeWindow	The period of time in minutes in which subqueries must match to trigger an alert.	false	see Get Managed Detection Rules - response - timeWindow table

Get Managed Detection Rules - response - subQueries

Name	Description	Required	Value
matchesRequired	The number of times a subquery must match.	true	integer
subQuery	A subquery	true	string

Get Managed Detection Rules - response - timeWindow

Name	Description	Required	Value
windowMinutes	The period of time in minutes in which subqueries must match to trigger an alert.	false	enum

Get Managed Detection Rules - response - mitre

Name	Description	Required	Value
tactic	The mitre tactic	false	string
techniques	The mitre techniques	false	see Get Managed Detection Rules - response - techniques table

Get Managed Detection Rules - response - techniques

Name	Description	Required	Value
id	The mitre technique id	false	string
link	The mitre technique link	false	string
title	The mitre technique title	false	string

Get Managed Detection Rules - response - scheduledParams

Name	Description	Required	Value
lookbackWindowMinutes	Sets the evaluation lookback window in minutes. For example, set to 5 evaluates the alert over the past five minutes.	true	integer
query	The PowerQuery to run	true	string
runIntervalMinutes	How often the alert is evaluated, in minutes. If used with coolOffSettings then it must be a denominator of renotifyMinutes. If the lookbackWindowMinutes is less than 60 (1 hour), the minimum is 1 minute. For a window between 1 and 360 (6 hours), 5 minutes. For a window between 360 (6 hours) and 10080 (7 days), 15 minutes. For a window between 10080 (7 days) and 43200 (30 days), 60 minutes.	true	integer
alertPerRow	If True, an alert will be generated for each row detected in the defined lookback window. If False (default), get one alert for all detected events matched in the defined lookback window.	false	boolean
disableStreaksLogic	If True (default), disables streak counting logic for scheduled rules. If False, streak counting logic is enabled.	false	boolean
threshold	Receive an alert only if the number of rows in the result of the query matches the condition in the threshold	false	see Get Managed Detection Rules - response - threshold table

Get Managed Detection Rules - response - threshold

Name	Description	Required	Value
operator	Defines the operator to use in combination with the query and thresholdValue to set the threshold condition for an alert to trigger The default value is Greater	false	enum
value	Defines the threshold value that in combination with operator and the query sets the threshold condition for an alert to be triggered. The default value is 0	false	integer

Get Template Detection Rules

GET /web/api/v2.1/detection-library/template-rules

Return Template Detection Rules for the given scope

Parameters

activeresponse	optional	The active response status for the rule.
attacksurfaces	optional	To filter by attack surfaces associated with the rule.
categories	optional	Categories. Example: "Events".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
description__contains	optional	To filter by a substring of the rule description
excludeids	optional	List of entity ids to exclude from select_all. Example: "225494730938493804,225494730938493915".
hidequery	optional	To filter by hideQuery of the rule params. Example: "Shown".
labels	optional	To filter by labels.
limit	optional	Limit number of returned items (1-1000). Example: "10".
mitretactics	optional	To filter by sources associated with the rule.

platformruleids	optional	platform rule ids. Example: "225494730938493804,225494730938493915".
rulenamesubstring	optional	To filter by a substring of the rule name
s1ql__contains	optional	To filter by a substring of the query content
scopeid	optional	The Account, Site, or Group ID, depending on the scope. Null if the scope is Global. Example: "225494730938493804".
scopelevel	optional	To filter by scope, enter one or more scopes, separated by commas. Example: "group".
severities	optional	Severities. Example: "Info".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sources	optional	To filter by sources associated with the rule.
statuses	optional	Statuses. Example: "Activating".
tags	optional	To filter by tags associated with the rule.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Template Detection Rules - response - pagination table
data	Response data	false	see Get Template Detection Rules - response - data table
errors	Errors	false	array

Get Template Detection Rules - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Template Detection Rules - response - data

Name	Description	Required	Value
queryType	Define the query type: Correlation (made of multiple subqueries), Event (single query)	true	enum
attackSurfaces	The attack surfaces associated with the rule.	false	string []
coolOffSettings	Receive only one alert and suppress additional alerts when a rule is triggered multiple times during the cool-off period. Mitigation actions set in the rule will not be applied to suppressed alerts.	false	see Get Template Detection Rules - response - coolOffSettings table
correlationParams	Correlation params	false	see Get Template Detection Rules - response - correlationParams table
createdAt	The time when the rule was created	false	string
createdBy	The vendor who created the rule.	false	string
description	The rule description	false	string
id	The platform rule ID.	false	string
inUse	Indicates if user has created at least one rule from this template	false	boolean
mitre	The mitre tactics associated with the rule.	false	see Get Template Detection Rules - response - mitre table
name	The rule name	false	string

s1ql	The query	false	string
scheduledParams	Scheduled params	false	see Get Template Detection Rules - response - scheduledParams table
severity	The severity of the rule.	false	enum
sources	The sources associated with the rule.	false	string []
updatedAt	The time when the rule was updated	false	string

Get Template Detection Rules - response - coolOffSettings

Name	Description	Required	Value
renotifyMinutes	The period of time in minutes in which alerts will be suppressed after the rule has been triggered.	true	integer

Get Template Detection Rules - response - correlationParams

Name	Description	Required	Value
entity	A common entity used to group matching events.	true	enum
matchInOrder	Set to True to require subqueries to match in sequence to trigger an alert.	true	boolean
subQueries	The list of subqueries for the custom detection rule.	false	see Get Template Detection Rules - response - subQueries table
timeWindow	The period of time in minutes in which subqueries must match to trigger an alert.	false	see Get Template Detection Rules - response - timeWindow table

Get Template Detection Rules - response - subQueries

Name	Description	Required	Value
matchesRequired	The number of times a subquery must match.	true	integer
subQuery	A subquery	true	string

Get Template Detection Rules - response - timeWindow

Name	Description	Required	Value
windowMinutes	The period of time in minutes in which subqueries must match to trigger an alert.	false	enum

Get Template Detection Rules - response - mitre

Name	Description	Required	Value
tactic	The mitre tactic	false	string
techniques	The mitre techniques	false	see Get Template Detection Rules - response - techniques table

Get Template Detection Rules - response - techniques

Name	Description	Required	Value
id	The mitre technique id	false	string
link	The mitre technique link	false	string
title	The mitre technique title	false	string

Get Template Detection Rules - response - scheduledParams

Name	Description	Required	Value
lookbackWindowMinutes	Sets the evaluation lookback window in minutes. For example, set to 5 evaluates the alert over the past five minutes.	true	integer
query	The PowerQuery to run	true	string
runIntervalMinutes	How often the alert is evaluated, in minutes. If used with coolOffSettings then it must be a denominator of renotifyMinutes. If the lookbackWindowMinutes is less than	true	integer

	60 (1 hour), the minimum is 1 minute. For a window between 1 and 360 (6 hours), 5 minutes. For a window between 360 (6 hours) and 10080 (7 days), 15 minutes. For a window between 10080 (7 days) and 43200 (30 days), 60 minutes.		
alertPerRow	If True, an alert will be generated for each row detected in the defined lookback window. If False (default), get one alert for all detected events matched in the defined lookback window.	false	boolean
disableStreaksLogic	If True (default), disables streak counting logic for scheduled rules. If False, streak counting logic is enabled.	false	boolean
threshold	Receive an alert only if the number of rows in the result of the query matches the condition in the threshold	false	see Get Template Detection Rules - response - threshold table

Get Template Detection Rules - response - threshold

Name	Description	Required	Value
operator	Defines the operator to use in combination with the query and thresholdValue to set the threshold condition for an alert to trigger The default value is Greater	false	enum
value	Defines the threshold value that in combination with operator and the query sets the threshold condition for an alert to be triggered. The default value is 0	false	integer

Enable a Managed Detection Rule

PUT /web/api/v2.1/detection-library/platform-rules/enable

Enable a Managed Detection Rule creates a new rule and activates it.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Managed Detection Rule not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Enable a Managed Detection Rule - response - data table
errors	Errors	false	array

Enable a Managed Detection Rule - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
activeResponse	The active response status for the rule.	false	boolean
attackSurfaces	To filter by attack surfaces associated with the rule.	false	string []
categories	Categories	false	string []
description__contains	To filter by a substring of the rule description	false	string
excludelds	List of entity ids to exclude from select_all	false	string []
hideQuery	To filter by hideQuery of the rule params.	false	enum
labels	To filter by labels.	false	string []
mitreTactics	To filter by sources associated with the rule.	false	string []
name__contains	To filter by a substring of the rule name	false	string
networkQuarantine	True if the network quarantine is on.	false	boolean
platformRuleIds	platform rule ids	false	string []
query	Free-text filter by All fields(name, description, query content). You can enter multiple values, separated by commas.	false	string []
ruleNameSubstring	To filter by a substring of the rule name	false	string
s1ql__contains	To filter by a substring of the query content	false	string
scopeld	The Account, Site, or Group ID,	false	string

	depending on the scope. Null if the scope is Global.		
scopeLevel	To filter by scope, enter one or more scopes, separated by commas.	false	enum
severities	Severities	false	string []
sources	To filter by sources associated with the rule.	false	string []
statuses	Statuses	false	string []
tags	To filter by tags associated with the rule.	false	string []
treatAsThreat	Defines the Treat as a threat auto response. Undefined, Suspicious, or Malicious.	false	enum

Disable a Managed Detection Rule

PUT /web/api/v2.1/detection-library/platform-rules/disable

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Managed Detection Rule not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Disable a Managed Detection Rule - response - data table
errors	Errors	false	array

Disable a Managed Detection Rule - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
activeResponse	The active response status for the rule.	false	boolean
attackSurfaces	To filter by attack surfaces associated with the rule.	false	string []
categories	Categories	false	string []
description__contains	To filter by a substring of the rule description	false	string
excludelds	List of entity ids to exclude from select_all	false	string []
hideQuery	To filter by hideQuery of the rule params.	false	enum
labels	To filter by labels.	false	string []
mitreTactics	To filter by sources associated with the rule.	false	string []
name__contains	To filter by a substring of the rule name	false	string
networkQuarantine	True if the network quarantine is on.	false	boolean
platformRuleIds	platform rule ids	false	string []
query	Free-text filter by All fields(name, description, query content). You can enter multiple values, separated by commas.	false	string []
ruleNameSubstring	To filter by a substring of the rule name	false	string
s1ql__contains	To filter by a substring of the query content	false	string
scopeld	The Account, Site, or Group ID,	false	string

	depending on the scope. Null if the scope is Global.		
scopeLevel	To filter by scope, enter one or more scopes, separated by commas.	false	enum
severities	Severities	false	string []
sources	To filter by sources associated with the rule.	false	string []
statuses	Statuses	false	string []
tags	To filter by tags associated with the rule.	false	string []
treatAsThreat	Defines the Treat as a threat auto response. Undefined, Suspicious, or Malicious.	false	enum

Free-Text Filters

GET /web/api/v2.1/detection-library/rules/free-text-filters

Get a metadata list of the available free-text filters

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Free-Text Filters - response - data table
errors	Errors	false	array

Free-Text Filters - response - data

Name	Description	Required	Value
autoComplete	API path for auto-complete query (if applicable)	false	string
icon	Filter icon	false	string
key	Filter argument key	false	string
title	Filter description	false	string
validation	A regular expression for values validation	false	string

Update settings for Managed Detection Rules

PUT /web/api/v2.1/detection-library/platform-rules/settings

Update settings for Managed Detection Rules

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update settings for Managed Detection Rules - response - data table
errors	Errors	false	array

Update settings for Managed Detection Rules - response - data

Body Schema

Name	Description	Required	Value
scopeLevel	Scope level.	true	enum
autoDefault	Set to On to enable all auto default Platform Detection Rules. Set to Off to stop auto enabling all future Auto Default Platform Detection Rules.	false	enum
core	Set to On to enable all Core Platform Detection Rules. Set to Off to stop auto enabling all future Core Platform Detection Rules.	false	enum
disableInheritance	Set to true to disable Platform Detection settings inheritance from the parent scope.	false	boolean
emergingThreat	Set to On to auto enable all future Emerging Threat Platform Detection Rules. Set to Off to stop auto enabling all future Emerging Threat Platform Detection Rules.	false	enum
scopeId	The Account or Site ID, depending on the scope. Null if the scope is Global.	false	string
smartDefault	Set to On to enable all smart default Platform Detection Rules. Set to Off to stop auto enabling all future Smart Default Platform Detection Rules.	false	enum

Get settings for Managed Detection Rules

GET /web/api/v2.1/detection-library/platform-rules/settings

Get settings for Managed Detection Rules for the given scope

Parameters

scopelevel	required	Scope level. Example: "group".
scopeid	optional	The Account or Site ID, depending on the scope. Null if the scope is Global. Example: "225494730938493804".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get settings for Managed Detection Rules - response - data table
errors	Errors	false	array

Get settings for Managed Detection Rules - response - data

Name	Description	Required	Value
inheritanceAvailable	Is inheritance configuration available for the provided scope?	true	boolean
scopeLevel	Scope level.	true	enum
autoDefault	Set to On to enable all auto default Platform Detection Rules. Set to Off to stop auto enabling all future Auto Default Platform Detection Rules.	false	enum
autoDefaultCount	Number of rules tagged as auto-default	false	integer
combinedLabelCount	Total number of unique rules with labels (same as combinedTagCount, for frontend compatibility)	false	integer
combinedTagCount	Total number of unique rules with either emergingThreat or autoDefault tags	false	integer
core	Set to On to enable all Core Platform Detection Rules. Set to Off to stop auto enabling all future Core Platform Detection Rules.	false	enum
coreCount	Number of rules tagged as core	false	integer
disableInheritance	Set to true to disable Platform Detection settings inheritance from the parent scope.	false	boolean
emergingThreat	Set to On to auto enable all future Emerging Threat Platform Detection Rules. Set to Off to stop auto enabling all future Emerging Threat Platform Detection Rules.	false	enum
emergingThreatCount	Number of rules tagged as emerging threats	false	integer
scopeId	The Account or Site ID, depending on the scope. Null if the scope is Global.	false	string
smartDefault	Set to On to enable all smart default Platform Detection Rules. Set to Off	false	enum

	to stop auto enabling all future Smart Default Platform Detection Rules.		
--	--	--	--

Get Surfaces

GET /web/api/v2.1/detection-library/surfaces

Get all Surfaces valid for Managed Detection Rules

Response Messages

401 - Unauthorized access - please sign in and retry.

Get Severities

GET /web/api/v2.1/detection-library/severities

Get Severities valid for Managed Detection Rules

Response Messages

401 - Unauthorized access - please sign in and retry.

Get Data Sources

GET /web/api/v2.1/detection-library/data-sources

Get Data Sources valid for Managed Detection Rules

Response Messages

401 - Unauthorized access - please sign in and retry.

Get Statuses

GET /web/api/v2.1/detection-library/statuses

Get all rule statuses valid for Managed Detection Rules

Response Messages

401 - Unauthorized access - please sign in and retry.

Policies

Group Policy

GET /web/api/v2.1/groups/{group_id}/policy

Get the policy of the Group given by ID. To get the ID of a Group, run "groups". See also: Get Policy.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

404 - Policy not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Group Policy - response - data table
errors	Errors	false	array

Group Policy - response - data

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Group Policy - response - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Group Policy - response - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Group Policy - response - dvAttributesPerEventType table
engines	The engines statuses	false	see Group Policy - response - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Group Policy - response - forensicsAutoTriggering table
fwForNetworkQuarantineEnabled	True if Firewall Control for Network	false	boolean

	Quarantine is enabled		
identityConfigurationSettings	Identity configuration	false	see Group Policy - response - identityConfigurationSettings table
identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Group Policy - response - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Group Policy - response - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Group Policy - response - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean

researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first registration	false	boolean
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Group Policy - response - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Group Policy - response - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Group Policy - response - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Group Policy - response - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Group Policy - response - behavioralIndicators table
commandScripts	Command scripts event	false	see Group Policy - response - commandScripts table
crossProcess	Cross process event	false	see Group Policy - response - crossProcess table
dataMasking	Data masking	false	see Group Policy - response - dataMasking table
dllModuleLoad	DLL module load event	false	see Group Policy - response - dllModuleLoad table
dns	Network event - DNS	false	see Group Policy - response - dns table
driver	Driver	false	see Group Policy - response - driver table
externalDeviceActivity	External Device Activity	false	see Group Policy - response - externalDeviceActivity table
file	File event	false	see Group Policy - response - file table
ip	Network event - IP	false	see Group Policy - response - ip table
login	User login/logout event	false	see Group Policy - response - login table
namedPipe	Named Pipe	false	see Group Policy - response - namedPipe table

[see Group Policy - response - namedPipeExtended table](#)

namedPipeExtended	Named Pipe Extended	false	
openDirectoryActivity	Open Directory Activity	false	see Group Policy - response - openDirectoryActivity table
process	Process event	false	see Group Policy - response - process table
profileActivity	Profile Activity	false	see Group Policy - response - profileActivity table
registry	Registry event	false	see Group Policy - response - registry table
scheduledTask	Scheduled task event	false	see Group Policy - response - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Group Policy - response - smartFileMonitoring table
url	URL Actions event	false	see Group Policy - response - url table
userSubstitution	User Substitution	false	see Group Policy - response - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Group Policy - response - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Group Policy - response - windowsEventLogsExtended table

Group Policy - response - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Group Policy - response - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Group Policy - response - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Group Policy - response - crossProcess

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Group Policy - response - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Group Policy - response - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Group Policy - response - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Group Policy - response - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Group Policy - response - externalDeviceActivity

Name	Description	Required	Value
dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Group Policy - response - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Group Policy - response - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Group Policy - response - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Group Policy - response - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean

dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean
------------------------------	--------------------------------	-------	---------

Group Policy - response - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Group Policy - response - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean

dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean
---	---------------------------------	-------	---------

Group Policy - response - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Group Policy - response - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Group Policy - response - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Group Policy - response - scheduledTask

Name	Description	Required	Value
dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Group Policy - response - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Group Policy - response - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Group Policy - response - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Group Policy - response - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Group Policy - response - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Group Policy - response - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Group Policy - response - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean

macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Group Policy - response - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Group Policy - response - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean

externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Group Policy - response - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Group Policy - response - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Update Group Policy

PUT /web/api/v2.1/groups/{group_id}/policy

Change the policy for the Group given by ID. Best practice: Get the policy of the Group before you attempt to change it. See also: [Get Policy](#).

BEST PRACTICE

Get the policy of the Group before you attempt to change it. See also: [Get Policy](#).

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Group not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Group Policy - response - data table
errors	Errors	false	array

Update Group Policy - response - data

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Update Group Policy - response - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Update Group Policy - response - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Update Group Policy - response - dvAttributesPerEventType table
engines	The engines statuses	false	see Update Group Policy - response - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Update Group Policy - response - forensicsAutoTriggering table
fwForNetworkQuarantineEnabled	True if Firewall Control for Network	false	boolean

	Quarantine is enabled		
identityConfigurationSettings	Identity configuration	false	see Update Group Policy - response - identityConfigurationSettings table
identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Update Group Policy - response - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Update Group Policy - response - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Update Group Policy - response - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean

researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first registration	false	boolean
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Update Group Policy - response - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Update Group Policy - response - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Update Group Policy - response - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Update Group Policy - response - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Update Group Policy - response - behavioralIndicators table
commandScripts	Command scripts event	false	see Update Group Policy - response - commandScripts table
crossProcess	Cross process event	false	see Update Group Policy - response - crossProcess table
dataMasking	Data masking	false	see Update Group Policy - response - dataMasking table
dllModuleLoad	DLL module load event	false	see Update Group Policy - response - dllModuleLoad table
dns	Network event - DNS	false	see Update Group Policy - response - dns table
driver	Driver	false	see Update Group Policy - response - driver table
externalDeviceActivity	External Device Activity	false	see Update Group Policy - response - externalDeviceActivity table
file	File event	false	see Update Group Policy - response - file table
ip	Network event - IP	false	see Update Group Policy - response - ip table
login	User login/logout event	false	see Update Group Policy - response - login table
namedPipe	Named Pipe	false	see Update Group Policy - response - namedPipe table

[see Update Group Policy - response - namedPipeExtended table](#)

namedPipeExtended	Named Pipe Extended	false	
openDirectoryActivity	Open Directory Activity	false	see Update Group Policy - response - openDirectoryActivity table
process	Process event	false	see Update Group Policy - response - process table
profileActivity	Profile Activity	false	see Update Group Policy - response - profileActivity table
registry	Registry event	false	see Update Group Policy - response - registry table
scheduledTask	Scheduled task event	false	see Update Group Policy - response - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Update Group Policy - response - smartFileMonitoring table
url	URL Actions event	false	see Update Group Policy - response - url table
userSubstitution	User Substitution	false	see Update Group Policy - response - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Update Group Policy - response - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Update Group Policy - response - windowsEventLogsExtended table

Update Group Policy - response - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Update Group Policy - response - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Update Group Policy - response - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Update Group Policy - response - crossProcess

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Update Group Policy - response - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Update Group Policy - response - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Update Group Policy - response - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Update Group Policy - response - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Update Group Policy - response - externalDeviceActivity

Name	Description	Required	Value
dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Update Group Policy - response - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Update Group Policy - response - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Update Group Policy - response - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Update Group Policy - response - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean

dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean
------------------------------	--------------------------------	-------	---------

Update Group Policy - response - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Update Group Policy - response - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean

dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean
---	---------------------------------	-------	---------

Update Group Policy - response - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Update Group Policy - response - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Update Group Policy - response - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Update Group Policy - response - scheduledTask

Name	Description	Required	Value
dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Update Group Policy - response - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Update Group Policy - response - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Update Group Policy - response - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Update Group Policy - response - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Update Group Policy - response - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Update Group Policy - response - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Update Group Policy - response - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean

macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Update Group Policy - response - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Update Group Policy - response - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean

externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Update Group Policy - response - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Update Group Policy - response - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Group Policy - body - data table

Update Group Policy - body - data

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Update Group Policy - body - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Update Group Policy - body - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Update Group Policy - body - dvAttributesPerEventType table
engines	The engines statuses	false	see Update Group Policy - body - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Update Group Policy - body - forensicsAutoTriggering table
identityConfigurationSettings	Identity configuration	false	see Update Group Policy - body - identityConfigurationSettings table

identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Update Group Policy - body - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Update Group Policy - body - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Update Group Policy - body - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean
researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first	false	boolean

	registration		
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Update Group Policy - body - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Update Group Policy - body - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Update Group Policy - body - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Update Group Policy - body - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Update Group Policy - body - behavioralIndicators table
commandScripts	Command scripts event	false	see Update Group Policy - body - commandScripts table
crossProcess	Cross process event	false	see Update Group Policy - body - crossProcess table
dataMasking	Data masking	false	see Update Group Policy - body - dataMasking table
dllModuleLoad	DLL module load event	false	see Update Group Policy - body - dllModuleLoad table
dns	Network event - DNS	false	see Update Group Policy - body - dns table
driver	Driver	false	see Update Group Policy - body - driver table
externalDeviceActivity	External Device Activity	false	see Update Group Policy - body - externalDeviceActivity table
file	File event	false	see Update Group Policy - body - file table
ip	Network event - IP	false	see Update Group Policy - body - ip table
login	User login/logout event	false	see Update Group Policy - body - login table
namedPipe	Named Pipe	false	see Update Group Policy - body - namedPipe table
namedPipeExtended	Named Pipe Extended	false	see Update Group Policy - body - namedPipeExtended table
openDirectoryActivity	Open Directory Activity	false	see Update Group Policy - body - openDirectoryActivity table
process	Process event	false	see Update Group Policy - body - process table

profileActivity	Profile Activity	false	see Update Group Policy - body - profileActivity table
registry	Registry event	false	see Update Group Policy - body - registry table
scheduledTask	Scheduled task event	false	see Update Group Policy - body - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Update Group Policy - body - smartFileMonitoring table
url	URL Actions event	false	see Update Group Policy - body - url table
userSubstitution	User Substitution	false	see Update Group Policy - body - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Update Group Policy - body - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Update Group Policy - body - windowsEventLogsExtended table

Update Group Policy - body - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Update Group Policy - body - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Update Group Policy - body - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Update Group Policy - body - crossProcess

Name	Description	Required	Value
dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean

read			
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Update Group Policy - body - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Update Group Policy - body - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Update Group Policy - body - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Update Group Policy - body - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Update Group Policy - body - externalDeviceActivity

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Update Group Policy - body - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Update Group Policy - body - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Update Group Policy - body - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Update Group Policy - body - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean
dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean

Update Group Policy - body - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Update Group Policy - body - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean
dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean

Update Group Policy - body - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Update Group Policy - body - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Update Group Policy - body - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Update Group Policy - body - scheduledTask

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Update Group Policy - body - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Update Group Policy - body - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Update Group Policy - body - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Update Group Policy - body - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Update Group Policy - body - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Update Group Policy - body - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Update Group Policy - body - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean

macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Update Group Policy - body - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Update Group Policy - body - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean

externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Update Group Policy - body - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Update Group Policy - body - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Site Policy

GET /web/api/v2.1/sites/{site_id}/policy

Get the policy of the Site given by ID. To get the ID of a Site, run "sites". See also: Get Policy.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

404 - Policy not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Site Policy - response - data table

errors	Errors	false	array
--------	--------	-------	-------

Site Policy - response - data

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Site Policy - response - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Site Policy - response - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Site Policy - response - dvAttributesPerEventType table
engines	The engines statuses	false	see Site Policy - response - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Site Policy - response - forensicsAutoTriggering table
fwForNetworkQuarantineEnabled	True if Firewall Control for Network	false	boolean

	Quarantine is enabled		
identityConfigurationSettings	Identity configuration	false	see Site Policy - response - identityConfigurationSettings table
identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Site Policy - response - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Site Policy - response - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Site Policy - response - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean

researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first registration	false	boolean
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Site Policy - response - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Site Policy - response - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Site Policy - response - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Site Policy - response - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Site Policy - response - behavioralIndicators table
commandScripts	Command scripts event	false	see Site Policy - response - commandScripts table
crossProcess	Cross process event	false	see Site Policy - response - crossProcess table
dataMasking	Data masking	false	see Site Policy - response - dataMasking table
dllModuleLoad	DLL module load event	false	see Site Policy - response - dllModuleLoad table
dns	Network event - DNS	false	see Site Policy - response - dns table
driver	Driver	false	see Site Policy - response - driver table
externalDeviceActivity	External Device Activity	false	see Site Policy - response - externalDeviceActivity table
file	File event	false	see Site Policy - response - file table
ip	Network event - IP	false	see Site Policy - response - ip table
login	User login/logout event	false	see Site Policy - response - login table
namedPipe	Named Pipe	false	see Site Policy - response - namedPipe table

[see Site Policy - response - namedPipeExtended table](#)

namedPipeExtended	Named Pipe Extended	false	
openDirectoryActivity	Open Directory Activity	false	see Site Policy - response - openDirectoryActivity table
process	Process event	false	see Site Policy - response - process table
profileActivity	Profile Activity	false	see Site Policy - response - profileActivity table
registry	Registry event	false	see Site Policy - response - registry table
scheduledTask	Scheduled task event	false	see Site Policy - response - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Site Policy - response - smartFileMonitoring table
url	URL Actions event	false	see Site Policy - response - url table
userSubstitution	User Substitution	false	see Site Policy - response - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Site Policy - response - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Site Policy - response - windowsEventLogsExtended table

Site Policy - response - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Site Policy - response - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Site Policy - response - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Site Policy - response - crossProcess

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Site Policy - response - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Site Policy - response - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Site Policy - response - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Site Policy - response - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Site Policy - response - externalDeviceActivity

Name	Description	Required	Value
dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Site Policy - response - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Site Policy - response - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Site Policy - response - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Site Policy - response - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean

dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean
------------------------------	--------------------------------	-------	---------

Site Policy - response - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Site Policy - response - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean

dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean
---	---------------------------------	-------	---------

Site Policy - response - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Site Policy - response - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Site Policy - response - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Site Policy - response - scheduledTask

Name	Description	Required	Value
dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Site Policy - response - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Site Policy - response - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Site Policy - response - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Site Policy - response - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Site Policy - response - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Site Policy - response - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Site Policy - response - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean

macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Site Policy - response - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Site Policy - response - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean

externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Site Policy - response - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Site Policy - response - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Update Site Policy

PUT /web/api/v2.1/sites/{site_id}/policy

Change the policy for the Site given by ID. Best practice: Get the policy of the Site before you attempt to change it. See also: Get Policy.

BEST PRACTICE

Get the policy of the Site before you attempt to change it. See also: Get Policy.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Site not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Site Policy - response - data table
errors	Errors	false	array

Update Site Policy - response - data

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Update Site Policy - response - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Update Site Policy - response - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Update Site Policy - response - dvAttributesPerEventType table
engines	The engines statuses	false	see Update Site Policy - response - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Update Site Policy - response - forensicsAutoTriggering table
fwForNetworkQuarantineEnabled	True if Firewall Control for Network	false	boolean

	Quarantine is enabled		
identityConfigurationSettings	Identity configuration	false	see Update Site Policy - response - identityConfigurationSettings table
identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Update Site Policy - response - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Update Site Policy - response - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Update Site Policy - response - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean

researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first registration	false	boolean
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Update Site Policy - response - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Update Site Policy - response - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Update Site Policy - response - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Update Site Policy - response - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Update Site Policy - response - behavioralIndicators table
commandScripts	Command scripts event	false	see Update Site Policy - response - commandScripts table
crossProcess	Cross process event	false	see Update Site Policy - response - crossProcess table
dataMasking	Data masking	false	see Update Site Policy - response - dataMasking table
dllModuleLoad	DLL module load event	false	see Update Site Policy - response - dllModuleLoad table
dns	Network event - DNS	false	see Update Site Policy - response - dns table
driver	Driver	false	see Update Site Policy - response - driver table
externalDeviceActivity	External Device Activity	false	see Update Site Policy - response - externalDeviceActivity table
file	File event	false	see Update Site Policy - response - file table
ip	Network event - IP	false	see Update Site Policy - response - ip table
login	User login/logout event	false	see Update Site Policy - response - login table
namedPipe	Named Pipe	false	see Update Site Policy - response - namedPipe table

[see Update Site Policy - response - namedPipeExtended table](#)

namedPipeExtended	Named Pipe Extended	false	
openDirectoryActivity	Open Directory Activity	false	see Update Site Policy - response - openDirectoryActivity table
process	Process event	false	see Update Site Policy - response - process table
profileActivity	Profile Activity	false	see Update Site Policy - response - profileActivity table
registry	Registry event	false	see Update Site Policy - response - registry table
scheduledTask	Scheduled task event	false	see Update Site Policy - response - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Update Site Policy - response - smartFileMonitoring table
url	URL Actions event	false	see Update Site Policy - response - url table
userSubstitution	User Substitution	false	see Update Site Policy - response - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Update Site Policy - response - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Update Site Policy - response - windowsEventLogsExtended table

Update Site Policy - response - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Update Site Policy - response - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Update Site Policy - response - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Update Site Policy - response - crossProcess

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Update Site Policy - response - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Update Site Policy - response - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Update Site Policy - response - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Update Site Policy - response - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Update Site Policy - response - externalDeviceActivity

Name	Description	Required	Value
dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Update Site Policy - response - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Update Site Policy - response - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Update Site Policy - response - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Update Site Policy - response - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean

dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean
------------------------------	--------------------------------	-------	---------

Update Site Policy - response - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Update Site Policy - response - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean

dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean
---	---------------------------------	-------	---------

Update Site Policy - response - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Update Site Policy - response - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Update Site Policy - response - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Update Site Policy - response - scheduledTask

Name	Description	Required	Value
dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Update Site Policy - response - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Update Site Policy - response - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Update Site Policy - response - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Update Site Policy - response - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Update Site Policy - response - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Update Site Policy - response - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Update Site Policy - response - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean

macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Update Site Policy - response - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Update Site Policy - response - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean

externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Update Site Policy - response - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Update Site Policy - response - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Site Policy - body - data table

Update Site Policy - body - data

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Update Site Policy - body - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Update Site Policy - body - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Update Site Policy - body - dvAttributesPerEventType table
engines	The engines statuses	false	see Update Site Policy - body - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Update Site Policy - body - forensicsAutoTriggering table
identityConfigurationSettings	Identity configuration	false	see Update Site Policy - body - identityConfigurationSettings table

identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Update Site Policy - body - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Update Site Policy - body - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Update Site Policy - body - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean
researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first	false	boolean

	registration		
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Update Site Policy - body - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Update Site Policy - body - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Update Site Policy - body - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Update Site Policy - body - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Update Site Policy - body - behavioralIndicators table
commandScripts	Command scripts event	false	see Update Site Policy - body - commandScripts table
crossProcess	Cross process event	false	see Update Site Policy - body - crossProcess table
dataMasking	Data masking	false	see Update Site Policy - body - dataMasking table
dllModuleLoad	DLL module load event	false	see Update Site Policy - body - dllModuleLoad table
dns	Network event - DNS	false	see Update Site Policy - body - dns table
driver	Driver	false	see Update Site Policy - body - driver table
externalDeviceActivity	External Device Activity	false	see Update Site Policy - body - externalDeviceActivity table
file	File event	false	see Update Site Policy - body - file table
ip	Network event - IP	false	see Update Site Policy - body - ip table
login	User login/logout event	false	see Update Site Policy - body - login table
namedPipe	Named Pipe	false	see Update Site Policy - body - namedPipe table
namedPipeExtended	Named Pipe Extended	false	see Update Site Policy - body - namedPipeExtended table
openDirectoryActivity	Open Directory Activity	false	see Update Site Policy - body - openDirectoryActivity table
process	Process event	false	see Update Site Policy - body - process table

profileActivity	Profile Activity	false	see Update Site Policy - body - profileActivity table
registry	Registry event	false	see Update Site Policy - body - registry table
scheduledTask	Scheduled task event	false	see Update Site Policy - body - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Update Site Policy - body - smartFileMonitoring table
url	URL Actions event	false	see Update Site Policy - body - url table
userSubstitution	User Substitution	false	see Update Site Policy - body - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Update Site Policy - body - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Update Site Policy - body - windowsEventLogsExtended table

Update Site Policy - body - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Update Site Policy - body - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Update Site Policy - body - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Update Site Policy - body - crossProcess

Name	Description	Required	Value
dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean

read			
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Update Site Policy - body - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Update Site Policy - body - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Update Site Policy - body - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Update Site Policy - body - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Update Site Policy - body - externalDeviceActivity

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Update Site Policy - body - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Update Site Policy - body - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Update Site Policy - body - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Update Site Policy - body - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean
dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean

Update Site Policy - body - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Update Site Policy - body - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean
dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean

Update Site Policy - body - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Update Site Policy - body - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Update Site Policy - body - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Update Site Policy - body - scheduledTask

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Update Site Policy - body - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Update Site Policy - body - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Update Site Policy - body - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Update Site Policy - body - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Update Site Policy - body - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Update Site Policy - body - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Update Site Policy - body - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean

macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Update Site Policy - body - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Update Site Policy - body - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean

externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Update Site Policy - body - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Update Site Policy - body - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Account Policy

GET /web/api/v2.1/accounts/{account_id}/policy

Get the policy for the Account given by ID. To get the ID of an Account, run "accounts". See also: Get Policy.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

404 - Policy not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Account Policy - response - data table

errors	Errors	false	array
--------	--------	-------	-------

Account Policy - response - data

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Account Policy - response - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Account Policy - response - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Account Policy - response - dvAttributesPerEventType table
engines	The engines statuses	false	see Account Policy - response - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Account Policy - response - forensicsAutoTriggering table
fwForNetworkQuarantineEnabled	True if Firewall Control for Network	false	boolean

	Quarantine is enabled		
identityConfigurationSettings	Identity configuration	false	see Account Policy - response - identityConfigurationSettings table
identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Account Policy - response - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Account Policy - response - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Account Policy - response - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean

researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first registration	false	boolean
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Account Policy - response - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Account Policy - response - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Account Policy - response - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Account Policy - response - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Account Policy - response - behavioralIndicators table
commandScripts	Command scripts event	false	see Account Policy - response - commandScripts table
crossProcess	Cross process event	false	see Account Policy - response - crossProcess table
dataMasking	Data masking	false	see Account Policy - response - dataMasking table
dllModuleLoad	DLL module load event	false	see Account Policy - response - dllModuleLoad table
dns	Network event - DNS	false	see Account Policy - response - dns table
driver	Driver	false	see Account Policy - response - driver table
externalDeviceActivity	External Device Activity	false	see Account Policy - response - externalDeviceActivity table
file	File event	false	see Account Policy - response - file table
ip	Network event - IP	false	see Account Policy - response - ip table
login	User login/logout event	false	see Account Policy - response - login table
namedPipe	Named Pipe	false	see Account Policy - response - namedPipe table

[see Account Policy - response - namedPipeExtended table](#)

namedPipeExtended	Named Pipe Extended	false	
openDirectoryActivity	Open Directory Activity	false	see Account Policy - response - openDirectoryActivity table
process	Process event	false	see Account Policy - response - process table
profileActivity	Profile Activity	false	see Account Policy - response - profileActivity table
registry	Registry event	false	see Account Policy - response - registry table
scheduledTask	Scheduled task event	false	see Account Policy - response - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Account Policy - response - smartFileMonitoring table
url	URL Actions event	false	see Account Policy - response - url table
userSubstitution	User Substitution	false	see Account Policy - response - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Account Policy - response - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Account Policy - response - windowsEventLogsExtended table

Account Policy - response - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Account Policy - response - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Account Policy - response - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Account Policy - response - crossProcess

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Account Policy - response - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Account Policy - response - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Account Policy - response - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Account Policy - response - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Account Policy - response - externalDeviceActivity

Name	Description	Required	Value
dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Account Policy - response - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Account Policy - response - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Account Policy - response - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Account Policy - response - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean

dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean
------------------------------	--------------------------------	-------	---------

Account Policy - response - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Account Policy - response - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean

dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean
---	---------------------------------	-------	---------

Account Policy - response - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Account Policy - response - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Account Policy - response - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Account Policy - response - scheduledTask

Name	Description	Required	Value
dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Account Policy - response - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Account Policy - response - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Account Policy - response - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Account Policy - response - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Account Policy - response - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Account Policy - response - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Account Policy - response - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean

macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Account Policy - response - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Account Policy - response - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean

externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Account Policy - response - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Account Policy - response - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Update Account Policy

PUT /web/api/v2.1/accounts/{account_id}/policy

Change the policy for the Account given by ID. Best practice: Get the policy of the Account before you attempt to change it. See also: [Get Policy](#).

BEST PRACTICE

Get the policy of the Account before you attempt to change it. See also: [Get Policy](#).

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Account not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Account Policy - response - data table
errors	Errors	false	array

Update Account Policy - response - data

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Update Account Policy - response - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Update Account Policy - response - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Update Account Policy - response - dvAttributesPerEventType table
engines	The engines statuses	false	see Update Account Policy - response - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Update Account Policy - response - forensicsAutoTriggering table
fwForNetworkQuarantineEnabled	True if Firewall Control for Network	false	boolean

	Quarantine is enabled		
identityConfigurationSettings	Identity configuration	false	see Update Account Policy - response - identityConfigurationSettings table
identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Update Account Policy - response - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Update Account Policy - response - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Update Account Policy - response - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean

researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first registration	false	boolean
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Update Account Policy - response - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Update Account Policy - response - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Update Account Policy - response - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Update Account Policy - response - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Update Account Policy - response - behavioralIndicators table
commandScripts	Command scripts event	false	see Update Account Policy - response - commandScripts table
crossProcess	Cross process event	false	see Update Account Policy - response - crossProcess table
dataMasking	Data masking	false	see Update Account Policy - response - dataMasking table
dllModuleLoad	DLL module load event	false	see Update Account Policy - response - dllModuleLoad table
dns	Network event - DNS	false	see Update Account Policy - response - dns table
driver	Driver	false	see Update Account Policy - response - driver table
externalDeviceActivity	External Device Activity	false	see Update Account Policy - response - externalDeviceActivity table
file	File event	false	see Update Account Policy - response - file table
ip	Network event - IP	false	see Update Account Policy - response - ip table
login	User login/logout event	false	see Update Account Policy - response - login table
namedPipe	Named Pipe	false	see Update Account Policy - response - namedPipe table

[see Update Account Policy - response - namedPipeExtended table](#)

namedPipeExtended	Named Pipe Extended	false	
openDirectoryActivity	Open Directory Activity	false	see Update Account Policy - response - openDirectoryActivity table
process	Process event	false	see Update Account Policy - response - process table
profileActivity	Profile Activity	false	see Update Account Policy - response - profileActivity table
registry	Registry event	false	see Update Account Policy - response - registry table
scheduledTask	Scheduled task event	false	see Update Account Policy - response - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Update Account Policy - response - smartFileMonitoring table
url	URL Actions event	false	see Update Account Policy - response - url table
userSubstitution	User Substitution	false	see Update Account Policy - response - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Update Account Policy - response - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Update Account Policy - response - windowsEventLogsExtended table

Update Account Policy - response - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Update Account Policy - response - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Update Account Policy - response - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Update Account Policy - response - crossProcess

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Update Account Policy - response - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Update Account Policy - response - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Update Account Policy - response - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Update Account Policy - response - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Update Account Policy - response - externalDeviceActivity

Name	Description	Required	Value
dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Update Account Policy - response - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Update Account Policy - response - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Update Account Policy - response - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Update Account Policy - response - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean

dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean
------------------------------	--------------------------------	-------	---------

Update Account Policy - response - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Update Account Policy - response - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean

dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean
---	---------------------------------	-------	---------

Update Account Policy - response - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Update Account Policy - response - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Update Account Policy - response - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Update Account Policy - response - scheduledTask

Name	Description	Required	Value
dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Update Account Policy - response - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Update Account Policy - response - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Update Account Policy - response - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Update Account Policy - response - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Update Account Policy - response - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Update Account Policy - response - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Update Account Policy - response - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean

macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Update Account Policy - response - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Update Account Policy - response - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean

externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Update Account Policy - response - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Update Account Policy - response - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Account Policy - body - data table

Update Account Policy - body - data

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Update Account Policy - body - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Update Account Policy - body - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Update Account Policy - body - dvAttributesPerEventType table
engines	The engines statuses	false	see Update Account Policy - body - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Update Account Policy - body - forensicsAutoTriggering table
identityConfigurationSettings	Identity configuration	false	see Update Account Policy - body - identityConfigurationSettings table

identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Update Account Policy - body - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Update Account Policy - body - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Update Account Policy - body - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean
researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first	false	boolean

	registration		
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Update Account Policy - body - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Update Account Policy - body - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Update Account Policy - body - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Update Account Policy - body - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Update Account Policy - body - behavioralIndicators table
commandScripts	Command scripts event	false	see Update Account Policy - body - commandScripts table
crossProcess	Cross process event	false	see Update Account Policy - body - crossProcess table
dataMasking	Data masking	false	see Update Account Policy - body - dataMasking table
dllModuleLoad	DLL module load event	false	see Update Account Policy - body - dllModuleLoad table
dns	Network event - DNS	false	see Update Account Policy - body - dns table
driver	Driver	false	see Update Account Policy - body - driver table
externalDeviceActivity	External Device Activity	false	see Update Account Policy - body - externalDeviceActivity table
file	File event	false	see Update Account Policy - body - file table
ip	Network event - IP	false	see Update Account Policy - body - ip table
login	User login/logout event	false	see Update Account Policy - body - login table
namedPipe	Named Pipe	false	see Update Account Policy - body - namedPipe table
namedPipeExtended	Named Pipe Extended	false	see Update Account Policy - body - namedPipeExtended table
openDirectoryActivity	Open Directory Activity	false	see Update Account Policy - body - openDirectoryActivity table
process	Process event	false	see Update Account Policy - body - process table

profileActivity	Profile Activity	false	see Update Account Policy - body - profileActivity table
registry	Registry event	false	see Update Account Policy - body - registry table
scheduledTask	Scheduled task event	false	see Update Account Policy - body - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Update Account Policy - body - smartFileMonitoring table
url	URL Actions event	false	see Update Account Policy - body - url table
userSubstitution	User Substitution	false	see Update Account Policy - body - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Update Account Policy - body - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Update Account Policy - body - windowsEventLogsExtended table

Update Account Policy - body - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Update Account Policy - body - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Update Account Policy - body - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Update Account Policy - body - crossProcess

Name	Description	Required	Value
dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean

read			
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Update Account Policy - body - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Update Account Policy - body - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Update Account Policy - body - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Update Account Policy - body - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Update Account Policy - body - externalDeviceActivity

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Update Account Policy - body - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Update Account Policy - body - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Update Account Policy - body - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Update Account Policy - body - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean
dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean

Update Account Policy - body - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Update Account Policy - body - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean
dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean

Update Account Policy - body - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Update Account Policy - body - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Update Account Policy - body - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Update Account Policy - body - scheduledTask

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Update Account Policy - body - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Update Account Policy - body - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Update Account Policy - body - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Update Account Policy - body - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Update Account Policy - body - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Update Account Policy - body - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Update Account Policy - body - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean

macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Update Account Policy - body - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Update Account Policy - body - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean

externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Update Account Policy - body - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Update Account Policy - body - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Global Policy

GET /web/api/v2.1/tenant/policy

Get the Global policy. This is the default policy for your deployment. See also: Get Policy.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

404 - Policy not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Global Policy - response - data table

errors	Errors	false	array
--------	--------	-------	-------

Global Policy - response - data

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Global Policy - response - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Global Policy - response - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Global Policy - response - dvAttributesPerEventType table
engines	The engines statuses	false	see Global Policy - response - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Global Policy - response - forensicsAutoTriggering table
fwForNetworkQuarantineEnabled	True if Firewall Control for Network	false	boolean

	Quarantine is enabled		
identityConfigurationSettings	Identity configuration	false	see Global Policy - response - identityConfigurationSettings table
identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Global Policy - response - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Global Policy - response - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Global Policy - response - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean

researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first registration	false	boolean
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Global Policy - response - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Global Policy - response - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Global Policy - response - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Global Policy - response - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Global Policy - response - behavioralIndicators table
commandScripts	Command scripts event	false	see Global Policy - response - commandScripts table
crossProcess	Cross process event	false	see Global Policy - response - crossProcess table
dataMasking	Data masking	false	see Global Policy - response - dataMasking table
dllModuleLoad	DLL module load event	false	see Global Policy - response - dllModuleLoad table
dns	Network event - DNS	false	see Global Policy - response - dns table
driver	Driver	false	see Global Policy - response - driver table
externalDeviceActivity	External Device Activity	false	see Global Policy - response - externalDeviceActivity table
file	File event	false	see Global Policy - response - file table
ip	Network event - IP	false	see Global Policy - response - ip table
login	User login/logout event	false	see Global Policy - response - login table
namedPipe	Named Pipe	false	see Global Policy - response - namedPipe table

[see Global Policy - response - namedPipeExtended table](#)

namedPipeExtended	Named Pipe Extended	false	
openDirectoryActivity	Open Directory Activity	false	see Global Policy - response - openDirectoryActivity table
process	Process event	false	see Global Policy - response - process table
profileActivity	Profile Activity	false	see Global Policy - response - profileActivity table
registry	Registry event	false	see Global Policy - response - registry table
scheduledTask	Scheduled task event	false	see Global Policy - response - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Global Policy - response - smartFileMonitoring table
url	URL Actions event	false	see Global Policy - response - url table
userSubstitution	User Substitution	false	see Global Policy - response - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Global Policy - response - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Global Policy - response - windowsEventLogsExtended table

Global Policy - response - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Global Policy - response - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Global Policy - response - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Global Policy - response - crossProcess

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Global Policy - response - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Global Policy - response - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Global Policy - response - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Global Policy - response - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Global Policy - response - externalDeviceActivity

Name	Description	Required	Value
dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Global Policy - response - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Global Policy - response - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Global Policy - response - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Global Policy - response - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean

dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean
------------------------------	--------------------------------	-------	---------

Global Policy - response - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Global Policy - response - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean

dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean
---	---------------------------------	-------	---------

Global Policy - response - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Global Policy - response - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Global Policy - response - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Global Policy - response - scheduledTask

Name	Description	Required	Value
dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Global Policy - response - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Global Policy - response - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Global Policy - response - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Global Policy - response - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Global Policy - response - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Global Policy - response - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Global Policy - response - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean

macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Global Policy - response - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Global Policy - response - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean

externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Global Policy - response - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Global Policy - response - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Update Global Policy

PUT /web/api/v2.1/tenant/policy

Change the policy of your deployment. Best practice: Get the Global policy before you attempt to change it. See also: Get Policy. You must be a Global Admin user to change the Global Policy.

BEST PRACTICE

Get the Global policy before you attempt to change it. See also: Get Policy. You must be a Global Admin user to change the Global Policy.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Policy not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Global Policy - response - data table
errors	Errors	false	array

Update Global Policy - response - data

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Update Global Policy - response - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Update Global Policy - response - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Update Global Policy - response - dvAttributesPerEventType table
engines	The engines statuses	false	see Update Global Policy - response - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Update Global Policy - response - forensicsAutoTriggering table
fwForNetworkQuarantineEnabled	True if Firewall Control for Network	false	boolean

	Quarantine is enabled		
identityConfigurationSettings	Identity configuration	false	see Update Global Policy - response - identityConfigurationSettings table
identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Update Global Policy - response - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Update Global Policy - response - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Update Global Policy - response - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean

researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first registration	false	boolean
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Update Global Policy - response - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Update Global Policy - response - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Update Global Policy - response - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Update Global Policy - response - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Update Global Policy - response - behavioralIndicators table
commandScripts	Command scripts event	false	see Update Global Policy - response - commandScripts table
crossProcess	Cross process event	false	see Update Global Policy - response - crossProcess table
dataMasking	Data masking	false	see Update Global Policy - response - dataMasking table
dllModuleLoad	DLL module load event	false	see Update Global Policy - response - dllModuleLoad table
dns	Network event - DNS	false	see Update Global Policy - response - dns table
driver	Driver	false	see Update Global Policy - response - driver table
externalDeviceActivity	External Device Activity	false	see Update Global Policy - response - externalDeviceActivity table
file	File event	false	see Update Global Policy - response - file table
ip	Network event - IP	false	see Update Global Policy - response - ip table
login	User login/logout event	false	see Update Global Policy - response - login table
namedPipe	Named Pipe	false	see Update Global Policy - response - namedPipe table

[see Update Global Policy - response - namedPipeExtended table](#)

namedPipeExtended	Named Pipe Extended	false	
openDirectoryActivity	Open Directory Activity	false	see Update Global Policy - response - openDirectoryActivity table
process	Process event	false	see Update Global Policy - response - process table
profileActivity	Profile Activity	false	see Update Global Policy - response - profileActivity table
registry	Registry event	false	see Update Global Policy - response - registry table
scheduledTask	Scheduled task event	false	see Update Global Policy - response - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Update Global Policy - response - smartFileMonitoring table
url	URL Actions event	false	see Update Global Policy - response - url table
userSubstitution	User Substitution	false	see Update Global Policy - response - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Update Global Policy - response - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Update Global Policy - response - windowsEventLogsExtended table

Update Global Policy - response - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Update Global Policy - response - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Update Global Policy - response - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Update Global Policy - response - crossProcess

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Update Global Policy - response - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Update Global Policy - response - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Update Global Policy - response - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Update Global Policy - response - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Update Global Policy - response - externalDeviceActivity

Name	Description	Required	Value
dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Update Global Policy - response - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Update Global Policy - response - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Update Global Policy - response - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Update Global Policy - response - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean

dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean
------------------------------	--------------------------------	-------	---------

Update Global Policy - response - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Update Global Policy - response - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean

dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean
---	---------------------------------	-------	---------

Update Global Policy - response - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Update Global Policy - response - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Update Global Policy - response - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Update Global Policy - response - scheduledTask

Name	Description	Required	Value
dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Update Global Policy - response - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Update Global Policy - response - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Update Global Policy - response - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Update Global Policy - response - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Update Global Policy - response - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Update Global Policy - response - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Update Global Policy - response - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean

macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Update Global Policy - response - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Update Global Policy - response - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean

externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Update Global Policy - response - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Update Global Policy - response - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Global Policy - body - data table

Update Global Policy - body - data

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Update Global Policy - body - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Update Global Policy - body - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Update Global Policy - body - dvAttributesPerEventType table
engines	The engines statuses	false	see Update Global Policy - body - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Update Global Policy - body - forensicsAutoTriggering table
identityConfigurationSettings	Identity configuration	false	see Update Global Policy - body - identityConfigurationSettings table

identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Update Global Policy - body - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Update Global Policy - body - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Update Global Policy - body - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean
researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first	false	boolean

	registration		
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Update Global Policy - body - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Update Global Policy - body - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Update Global Policy - body - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Update Global Policy - body - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Update Global Policy - body - behavioralIndicators table
commandScripts	Command scripts event	false	see Update Global Policy - body - commandScripts table
crossProcess	Cross process event	false	see Update Global Policy - body - crossProcess table
dataMasking	Data masking	false	see Update Global Policy - body - dataMasking table
dllModuleLoad	DLL module load event	false	see Update Global Policy - body - dllModuleLoad table
dns	Network event - DNS	false	see Update Global Policy - body - dns table
driver	Driver	false	see Update Global Policy - body - driver table
externalDeviceActivity	External Device Activity	false	see Update Global Policy - body - externalDeviceActivity table
file	File event	false	see Update Global Policy - body - file table
ip	Network event - IP	false	see Update Global Policy - body - ip table
login	User login/logout event	false	see Update Global Policy - body - login table
namedPipe	Named Pipe	false	see Update Global Policy - body - namedPipe table
namedPipeExtended	Named Pipe Extended	false	see Update Global Policy - body - namedPipeExtended table
openDirectoryActivity	Open Directory Activity	false	see Update Global Policy - body - openDirectoryActivity table
process	Process event	false	see Update Global Policy - body - process table

profileActivity	Profile Activity	false	see Update Global Policy - body - profileActivity table
registry	Registry event	false	see Update Global Policy - body - registry table
scheduledTask	Scheduled task event	false	see Update Global Policy - body - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Update Global Policy - body - smartFileMonitoring table
url	URL Actions event	false	see Update Global Policy - body - url table
userSubstitution	User Substitution	false	see Update Global Policy - body - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Update Global Policy - body - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Update Global Policy - body - windowsEventLogsExtended table

Update Global Policy - body - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Update Global Policy - body - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Update Global Policy - body - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Update Global Policy - body - crossProcess

Name	Description	Required	Value
dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean

read			
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Update Global Policy - body - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Update Global Policy - body - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Update Global Policy - body - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Update Global Policy - body - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Update Global Policy - body - externalDeviceActivity

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Update Global Policy - body - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Update Global Policy - body - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Update Global Policy - body - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Update Global Policy - body - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean
dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean

Update Global Policy - body - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Update Global Policy - body - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean
dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean

Update Global Policy - body - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Update Global Policy - body - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Update Global Policy - body - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Update Global Policy - body - scheduledTask

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Update Global Policy - body - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Update Global Policy - body - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Update Global Policy - body - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Update Global Policy - body - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Update Global Policy - body - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Update Global Policy - body - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Update Global Policy - body - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean

macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Update Global Policy - body - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Update Global Policy - body - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean

externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Update Global Policy - body - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Update Global Policy - body - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

RBAC

Get All Roles

GET /web/api/v2.1/rbac/roles

See roles assigned to users that match the filter, a basic description of the roles, and the number of users for each role.

Role-Based Access Control (RBAC) has predefined roles. (Currently, customized roles are not supported.), This command gives the ID of the role, which you can use in other commands.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
accountname	optional	Name of the account that contains the role
countonly	optional	If true, only total number of items will be returned, without any of

		the actual objects.
createdat	optional	Created at. Example: "2018-02-27T04:49:26.257525Z".
createdat__between	optional	Return RBAC roles created within this range (inclusive). Example: "1514978764288-1514978999999".
createdat__gt	optional	Return RBAC roles created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Return RBAC roles created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Return RBAC roles created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Return RBAC roles created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
creator	optional	Email of the creating user
creatorid	optional	Id of the creating user. Example: "225494730938493804".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
description	optional	Description
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of ids to filter by. Example: "225494730938493804,225494730938493915".
includechildren	optional	Include child scopes roles
includeparents	optional	Include parent scopes roles
limit	optional	Limit number of returned items (1-1000). Example: "10".
name	optional	Return RBAC role matching the name
predefinedrole	optional	Filter only system/custom roles
query	optional	Free text search on role name, and description
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
sitename	optional	Name of the site that contains the role
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".

skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
tenancyids	optional	List of Tenancies IDs to filter by. Example: "225494730938493804,225494730938493915".
tenant	optional	Indicates a tenant scope request
updatedat	optional	Updated at. Example: "2018-02-27T04:49:26.257525Z".
updatedat__between	optional	Return RBAC roles updated within this range (inclusive). Example: "1514978764288-1514978999999".
updatedat__gt	optional	Return RBAC roles updated after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Return RBAC roles updated after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Return RBAC roles updated before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Return RBAC roles updated before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedby	optional	Email of the updating user
updatedbyid	optional	Id of the updating user. Example: "225494730938493804".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get All Roles - response - pagination table
data	Response data	false	see Get All Roles - response - data table
errors	Errors	false	array

Get All Roles - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get All Roles - response - data

Name	Description	Required	Value
accountName	Account name	false	string
createdAt	Created at	false	string
creator	Email of the creating user	false	string
creatorId	Id of the creating user	false	string
description	Description	false	string
id	Id	false	string
name	Name	false	string
predefinedRole	Whether this role is a system role	false	boolean
scope	Scope of the role (Group/Site/Account/Tenant)	false	string
scopeId	Id of the containing scope	false	string
siteName	Site name	false	string
updatedAt	Updated at	false	string
updatedBy	Email of the updating user	false	string
updatedById	Id of the creating user	false	string
usersInRoles	How many users use this role	false	integer

Get Specific Role Definition

GET /web/api/v2.1/rbac/role/{role_id}

With the ID of a role (see Get All Roles) you can see the permissions of that role.

The definition of a role can change in different scopes and SKUs. For example, an Admin role with the scope access of a Site does not have Network Discovery permissions, but an IT role with the scope access of an Account with a Network Discovery license does have permissions on Network Discovery.

The Response shows role permissions to see views in the WebUI and to use Console features.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
createdat__between	optional	Return RBAC roles created within this range (inclusive). Example: "1514978764288-15149789999999".
createdat__gt	optional	Return RBAC roles created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Return RBAC roles created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Return RBAC roles created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Return RBAC roles created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
name	optional	Return RBAC role matching the name
query	optional	Free text search on role name, and description
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
tenant	optional	Indicates a tenant scope request
updatedat__between	optional	Return RBAC roles updated within this range (inclusive). Example: "1514978764288-15149789999999".
updatedat__gt	optional	Return RBAC roles updated after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Return RBAC roles updated after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Return RBAC roles updated before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Return RBAC roles updated before or at this timestamp. Example:

		"2018-02-27T04:49:26.257525Z".
--	--	--------------------------------

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Specific Role Definition - response - data table
errors	Errors	false	array

Get Specific Role Definition - response - data

Name	Description	Required	Value
accountName	Account name	false	string
createdAt	Created at	false	string
creator	Email of the creating user	false	string
creatorId	Id of the creating user	false	string
description	Description	false	string
id	Id	false	string
name	Name	false	string
pages	Pages	false	see Get Specific Role Definition - response - pages table
predefinedRole	Whether this role is a system role	false	boolean
scope	Scope of the role (Group/Site/Account/Tenant)	false	string
scopeId	Id of the containing scope	false	string
siteName	Site name	false	string
updatedAt	Updated at	false	string
updatedBy	Email of the updating user	false	string
updatedById	Id of the creating user	false	string
usersInRoles	How many users use this role	false	integer

Get Specific Role Definition - response - pages

Name	Description	Required	Value
identifier	Identifier	false	string
name	Name	false	string
permissions	Permissions	false	see Get Specific Role Definition - response - permissions table

Get Specific Role Definition - response - permissions

Name	Description	Required	Value
additionalDescription	Additional description	false	string
dependsOn	Depends on	false	string []
description	Description	false	string
disabledReason	Disabled reason	false	string
disabledReasonCode	Disabled reason code	false	string
groupName	Group name	false	string
identifier	Identifier	false	string
title	Title	false	string
type	Type	false	string
value	Value	false	boolean

Update role

PUT /web/api/v2.1/rbac/role/{role_id}

With the ID of a role (see Get All Roles), you can update the permissions of users with this role.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update role - response - data table
errors	Errors	false	array

Update role - response - data

Name	Description	Required	Value
accountName	Account name	false	string
createdAt	Created at	false	string
creator	Email of the creating user	false	string
creatorId	Id of the creating user	false	string
description	Description	false	string
id	Id	false	string
name	Name	false	string
pages	Pages	false	see Update role - response - pages table
predefinedRole	Whether this role is a system role	false	boolean
scope	Scope of the role (Group/Site/Account/Tenant)	false	string
scopeId	Id of the containing scope	false	string
siteName	Site name	false	string
updatedAt	Updated at	false	string
updatedBy	Email of the updating user	false	string
updatedById	Id of the creating user	false	string
usersInRoles	How many users use this role	false	integer

Update role - response - pages

Name	Description	Required	Value
identifier	Identifier	false	string
name	Name	false	string
permissions	Permissions	false	see Update role - response - permissions table

Update role - response - permissions

Name	Description	Required	Value
additionalDescription	Additional description	false	string
dependsOn	Depends on	false	string []
description	Description	false	string
disabledReason	Disabled reason	false	string
disabledReasonCode	Disabled reason code	false	string
groupName	Group name	false	string
identifier	Identifier	false	string
title	Title	false	string
type	Type	false	string
value	Value	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Update role - body - data table
filter	Filter	false	see Update role - body - filter table

Update role - body - data

Name	Description	Required	Value
description	Description	true	string
name	Recommendation: Use a prefix or suffix for each role that identifies it as related to a specific Account or Site.	true	string
permissionIds	Permission ids	false	string []

Update role - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Delete role

DELETE /web/api/v2.1/rbac/role/{role_id}

With the ID of a role (see Get All Roles), you can delete a role. If there are users assigned to the role, specify the ID of their new role.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Delete role - response - data table
errors	Errors	false	array

Delete role - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Delete role - body - data table

Delete role - body - data

Name	Description	Required	Value
targetId	Role ID of new role to assign to users with the role	false	string

Create new role

POST /web/api/v2.1/rbac/role

Create a new role for Role-Based Access Control (RBAC).

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create new role - response - data table
errors	Errors	false	array

Create new role - response - data

Name	Description	Required	Value
accountName	Account name	false	string
createdAt	Created at	false	string
creator	Email of the creating user	false	string
creatorId	Id of the creating user	false	string
description	Description	false	string
id	Id	false	string
name	Name	false	string
pages	Pages	false	see Create new role - response - pages table
predefinedRole	Whether this role is a system role	false	boolean
scope	Scope of the role (Group/Site/Account/Tenant)	false	string
scopeId	Id of the containing scope	false	string
siteName	Site name	false	string
updatedAt	Updated at	false	string
updatedBy	Email of the updating user	false	string
updatedById	Id of the creating user	false	string
usersInRoles	How many users use this role	false	integer

Create new role - response - pages

Name	Description	Required	Value
identifier	Identifier	false	string
name	Name	false	string
permissions	Permissions	false	see Create new role - response - permissions table

Create new role - response - permissions

Name	Description	Required	Value
additionalDescription	Additional description	false	string
dependsOn	Depends on	false	string []
description	Description	false	string
disabledReason	Disabled reason	false	string
disabledReasonCode	Disabled reason code	false	string
groupName	Group name	false	string
identifier	Identifier	false	string
title	Title	false	string
type	Type	false	string
value	Value	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Create new role - body - data table
filter	Filter	true	see Create new role - body - filter table

Create new role - body - data

Name	Description	Required	Value
description	Description	true	string
name	Recommendation: Use a prefix or suffix for each role that identifies it as related to a specific Account or Site.	true	string
permissionIds	Permission ids	false	string []

Create new role - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Get template for new role

GET /web/api/v2.1/rbac/role

Get the template for a new role.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get template for new role - response - data table
errors	Errors	false	array

Get template for new role - response - data

Name	Description	Required	Value
description	Description	true	string
pages	Pages	false	see Get template for new role - response - pages table

Get template for new role - response - pages

Name	Description	Required	Value
identifier	Identifier	false	string
name	Name	false	string
permissions	Permissions	false	see Get template for new role - response - permissions table

Get template for new role - response - permissions

Name	Description	Required	Value
additionalDescription	Additional description	false	string
dependsOn	Depends on	false	string []
description	Description	false	string
disabledReason	Disabled reason	false	string
disabledReasonCode	Disabled reason code	false	string
groupName	Group name	false	string
identifier	Identifier	false	string
title	Title	false	string
type	Type	false	string
value	Value	false	boolean

Remote Ops MMS

Create new Destination profile.

POST /web/api/v2.1/remote-ops/data-exporter/destination-profiles

Create Destination profile inside specified scope. If the created profile is requested to be default, the default profile of the specified scope is overridden.

Response Messages

200 - Successes

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create new Destination profile. - response - data table
errors	Errors	false	array

Create new Destination profile. - response - data

Name	Description	Required	Value
profileId	Profile ID	true	string

Body Schema

Name	Description	Required	Value
apiKey	Write key of api account to upload data	true	string
apiUrl	URL of api instance to upload the events	true	string
destination	Destination profile type	true	enum
name	Destination profile name	true	string
scopeId	Scope ID to store the Destination profile	true	string
scopeLevel	Scope level to store the Destination profile	true	enum
isDefault	Flag if the profile should be marked as default in it's scope	false	boolean

Get available Destination profiles

GET /web/api/v2.1/remote-ops/data-exporter/destination-profiles

Get Destination profiles available for the specified scope. The profiles are inherited downwards, e.g. the profiles from parent Account and Tenant scopes are available for a Site. At most one of returned destination profiles will be marked as default for the scope. If the scope does not have default profile defined, it's inherited from the higher scope, unless inheritance was broken

Parameters

scopeid	optional	Scope ID to get Destination profiles configuration. Example: "225494730938493804".
scopelevel	optional	Scope level to get Destination profile configuration. Example: "tenant".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permission to perform such action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get available Destination profiles - response - data table
errors	Errors	false	array

Get available Destination profiles - response - data

Name	Description	Required	Value
apiKey	Write key of destination account to upload data	true	string
apiUrl	URL of destination instance to upload data	true	string
creator	Email of user who created the Destination profile	true	string
creatorId	ID of user who created the Destination profile	true	string
destination	Destination type where the results will be uploaded	true	string
id	Destination profile ID	true	string
isDefault	Flag if the Destination profile is default for the scope	true	boolean
name	Destination profile name	true	string
scopePath	Path of scope where the Destination profile is stored	true	string
updater	Email of user who updated the Destination profile	true	string
updaterId	ID of user who updated the Destination profile	true	string

Delete multiple Destination profiles by ID

DELETE /web/api/v2.1/remote-ops/data-exporter/destination-profiles

Delete multiple Destination profiles. The profiles that are not possible to delete (e.g.non-existing or user does not have proper permissions) are skipped. IDs of successfully deleted profiles are returned in response.

Response Messages

200 - Delete was completed or partially completed.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete multiple Destination profiles by ID - response - data table
errors	Errors	false	array

Delete multiple Destination profiles by ID - response - data

Name	Description	Required	Value
affected	Deleted Destination profile IDs	false	string []

Body Schema

Name	Description	Required	Value
data	Data	false	see Delete multiple Destination profiles by ID - body - data table
filter	Filter	false	see Delete multiple Destination profiles by ID - body - filter table

Delete multiple Destination profiles by ID - body - data

Delete multiple Destination profiles by ID - body - filter

Name	Description	Required	Value
ids	List of Destination profile IDs to delete	false	string []

Delete Destination profile by ID

DELETE /web/api/v2.1/remote-ops/data-exporter/destination-profiles/{profile_id}

Delete Destination profile with specified ID. If the profile was used as default for a scope, the last created profile will be marked as default for that scope.

Response Messages

200 - Destination profile is deleted

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permission to perform such action

404 - Destination profile is not found

Update existing Destination profile

PUT /web/api/v2.1/remote-ops/data-exporter/destination-profiles/{profile_id}

Update contents of existing Destination profile with specified ID. All the profile data should be specified, even if the values are not changed. If the updated profile is requested to be default, the default profile of its scope is modified.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permission to perform such action

404 - Destination profile is not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update existing Destination profile - response - data table
errors	Errors	false	array

Update existing Destination profile - response - data

Name	Description	Required	Value
profileId	Profile ID	true	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Update existing Destination profile - body - data table

Update existing Destination profile - body - data

Name	Description	Required	Value
apiKey	Write key of api account to upload data	true	string
apiUrl	URL of api instance to upload the events	true	string
name	Destination profile name	true	string
isDefault	Flag if the profile should be marked as default in it's scope	false	boolean

Get Destination profile by ID

GET /web/api/v2.1/remote-ops/data-exporter/destination-profiles/{profile_id}

Get Destination profile with specified ID

Parameters

scopeid	optional	Scope ID to get Destination profiles configuration. Example: "225494730938493804".
scopelevel	optional	Scope level to get Destination profile configuration. Example: "tenant".

Response Messages

200 - Get Destination profile

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permission to perform such action

404 - Destination profile is not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Destination profile by ID - response - data table
errors	Errors	false	array

Get Destination profile by ID - response - data

Name	Description	Required	Value
apiKey	Write key of destination account to upload data	true	string
apiUrl	URL of destination instance to upload data	true	string
creator	Email of user who created the Destination profile	true	string
creatorId	ID of user who created the Destination profile	true	string
destination	Destination type where the results will be uploaded	true	string
id	Destination profile ID	true	string
isDefault	Flag if the Destination profile is default for the scope	true	boolean
name	Destination profile name	true	string
scopePath	Path of scope where the Destination profile is stored	true	string
updater	Email of user who updated the Destination profile	true	string
updaterId	ID of user who updated the Destination profile	true	string

Set profile as default profile of the scope

POST /web/api/v2.1/remote-ops/data-exporter/destination-profiles/set-default

Set profile as default profile of the scope

Response Messages

200 - Get Destination profile

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permission to perform such action

Body Schema

Name	Description	Required	Value
data	Data	true	see Set profile as default profile of the scope - body - data table

Set profile as default profile of the scope - body - data

Name	Description	Required	Value
profileId	Profile Id to set as default profile	true	string
scopeLevel	Scope level to get Destination profile configuration	true	enum
scopeId	Scope ID to get Destination profiles configuration	false	string

Get results sent to data exporter

GET /web/api/v2.1/remote-ops/data-exporter/results

Get results sent to data exporter

Parameters

agentId	required	Id of the agent the data came from
maliciousgroupId	optional	Threat malicious group id
taskId	optional	Task id

Response Messages

200 - Get Destination profile results

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permission to perform such action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get results sent to data exporter - response - data table
errors	Errors	false	array

Get results sent to data exporter - response - data

Name	Description	Required	Value
agentResults	Agent results	false	see Get results sent to data exporter - response - agentResults table
taskResults	Task results	false	see Get results sent to data exporter - response - taskResults table
threatResults	Threat results	false	see Get results sent to data exporter - response - threatResults table

Get results sent to data exporter - response - agentResults

Name	Description	Required	Value
hasFailures	Indicates if not failures has occurred during upload returned	true	boolean
isEmpty	Indicates if not results returned	true	boolean
url	Url to relevant data source	true	string
endTime	Ending point of the results timeframe	false	string
errorMessage	Last error message	false	string
query	Query filter to find the result	false	string
startTime	Starting point of the results timeframe	false	string

Get results sent to data exporter - response - taskResults

Name	Description	Required	Value
hasFailures	Indicates if not failures has occurred during upload returned	true	boolean
isEmpty	Indicates if not results returned	true	boolean
url	Url to relevant data source	true	string
endTime	Ending point of the results timeframe	false	string
errorMessage	Last error message	false	string
query	Query filter to find the result	false	string

startTime	Starting point of the results timeframe	false	string
-----------	---	-------	--------

Get results sent to data exporter - response - threatResults

Name	Description	Required	Value
hasFailures	Indicates if not failures has occurred during upload returned	true	boolean
isEmpty	Indicates if not results returned	true	boolean
url	Url to relevant data source	true	string
endTime	Ending point of the results timeframe	false	string
errorMessage	Last error message	false	string
query	Query filter to find the result	false	string
startTime	Starting point of the results timeframe	false	string

Schedule remote script for future run.

POST /web/api/v2.1/remote-ops/schedule/remote-script

Schedule remote script for future run. The script will be scheduled for execution on all endpoints matching the filter.If appropriate, pending approval will be created for the execution.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Schedule remote script for future run. - response - data table
errors	Errors	false	array

Schedule remote script for future run. - response - data

Name	Description	Required	Value
affected	Number of affected endpoints that matched the filter	true	integer
scheduledTaskId	Scheduled Task ID	true	string
pendingExecutionId	Pending execution id	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Schedule remote script for future run. - body - data table
filter	Filter	true	see Schedule remote script for future run. - body - filter table

Schedule remote script for future run. - body - data

Name	Description	Required	Value
action	Action	true	see Schedule remote script for future run. - body - action table
scheduling	Scheduling	true	see Schedule remote script for future run. - body - scheduling table

Schedule remote script for future run. - body - action

Name	Description	Required	Value
outputDestination	Output destination	true	enum
scriptId	Script id	true	string
taskDescription	Task description	true	string
apiKey	Api key	false	string
destinationProfileId	Id of destination profile to use	false	string
destinationProfileKeyword	Destination profile keyword	false	string
inputParams	Input params	false	string
outputDirectory	Output directory	false	string
outputFilePaths	Output file paths	false	string []
password	Password	false	string
passwordFromScope	Used to specify execution where a generic password is used	false	see Schedule remote script for future run. - body - passwordFromScope table
requiresApproval	If set to true, execution will require approval	false	boolean
scriptRuntimeTimeoutSeconds	Script runtime timeout in seconds for current execution	false	integer
singularityxdrKeyword	Singularityxdr keyword	false	string
singularityxdrUrl	Singularityxdr url	false	string

Schedule remote script for future run. - body - passwordFromScope

Name	Description	Required	Value
scopeLevel	User scope	true	enum
scopeId	string repr. of scope id	false	string

Schedule remote script for future run. - body - scheduling

Name	Description	Required	Value
scheduledTime	Scheduled time	true	see Schedule remote script for future run. - body - scheduledTime table
expireTime	Expire time	false	see Schedule remote script for future run. - body - expireTime table
recurrence	Recurrence	false	see Schedule remote script for future run. - body - recurrence table

Schedule remote script for future run. - body - scheduledTime

Name	Description	Required	Value
tz	Tz	true	string
utc	Utc	true	string

Schedule remote script for future run. - body - expireTime

Name	Description	Required	Value
tz	Tz	true	string
utc	Utc	true	string

Schedule remote script for future run. - body - recurrence

Name	Description	Required	Value
dayOfMonth	The day of the month. Accepts only 1 or None.	false	integer
interval	The interval of the units	false	integer
unit	The unit of the recurrence	false	enum

Schedule remote script for future run. - body - filter

Name	Description	Required	Value
accountIds	Account ids	false	string []
groupIds	Group ids	false	string []
ids	Ids	false	string []
siteIds	Site ids	false	string []
tenant	Tenant	false	boolean

Schedule forensics for future run.

POST /web/api/v2.1/remote-ops/schedule/forensics

Schedule forensics for future run. The profile will be scheduled for execution on all endpoints matching the filter.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Schedule forensics for future run. - response - data table
errors	Errors	false	array

Schedule forensics for future run. - response - data

Name	Description	Required	Value
affected	Number of affected endpoints that matched the filter	true	integer
scheduledTaskId	Scheduled Task ID	true	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Schedule forensics for future run. - body - data table
filter	Filter	true	see Schedule forensics for future run. - body - filter table

Schedule forensics for future run. - body - data

Name	Description	Required	Value
action	Action	true	see Schedule forensics for future run. - body - action table
scheduling	Scheduling	true	see Schedule forensics for future run. - body - scheduling table

Schedule forensics for future run. - body - action

Name	Description	Required	Value
destination	Destination	true	see Schedule forensics for future run. - body - destination table
collectionProfileId	ID of the Collection Profile that will be used	false	string
description	Description of the collection	false	string
tag	Tag identifier of the collection	false	string

Schedule forensics for future run. - body - destination

Name	Description	Required	Value
password	Password for encrypting uploaded binary artifacts	false	string
passwordFromScope	Used to specify execution where a generic password is used	false	see Schedule forensics for future run. - body - passwordFromScope table
profileId	ID of profile for destination of exported collection data	false	string

Schedule forensics for future run. - body - passwordFromScope

Name	Description	Required	Value
scopeLevel	User scope	true	enum
scopeId	string repr. of scope id	false	string

Schedule forensics for future run. - body - scheduling

Name	Description	Required	Value
scheduledTime	Scheduled time	true	see Schedule forensics for future run. - body - scheduledTime table
expireTime	Expire time	false	see Schedule forensics for future run. - body - expireTime table
recurrence	Recurrence	false	see Schedule forensics for future run. - body - recurrence table

Schedule forensics for future run. - body - scheduledTime

Name	Description	Required	Value
tz	Tz	true	string
utc	Utc	true	string

Schedule forensics for future run. - body - expireTime

Name	Description	Required	Value
tz	Tz	true	string
utc	Utc	true	string

Schedule forensics for future run. - body - recurrence

Name	Description	Required	Value
dayOfMonth	The day of the month. Accepts only 1 or None.	false	integer
interval	The interval of the units	false	integer
unit	The unit of the recurrence	false	enum

Schedule forensics for future run. - body - filter

Name	Description	Required	Value
------	-------------	----------	-------

accountIds	Account ids	false	string []
groupIds	Group ids	false	string []
ids	Ids	false	string []
siteIds	Site ids	false	string []
tenant	Tenant	false	boolean

Delete multiple scheduled tasks by ID

DELETE /web/api/v2.1/remote-ops/scheduled-tasks

Delete multiple Scheduled tasks. The tasks that are not possible to delete (e.g.non-existing or user does not have proper permissions) are skipped. IDs of successfully deleted tasks are returned in response.

Response Messages

200 - Delete was completed or partially completed.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete multiple scheduled tasks by ID - response - data table
errors	Errors	false	array

Delete multiple scheduled tasks by ID - response - data

Name	Description	Required	Value
affected	Deleted Destination profile IDs	false	string []

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Delete multiple scheduled tasks by ID - body - filter table
data	Data	false	see Delete multiple scheduled tasks by ID - body - data table

Delete multiple scheduled tasks by ID - body - filter

Name	Description	Required	Value
ids	List of Scheduled Tasks IDs to delete	false	string []

Delete multiple scheduled tasks by ID - body - data

Get available Scheduled Tasks

GET /web/api/v2.1/remote-ops/scheduled-tasks

Get available Scheduled Tasks

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__between	optional	Date range for creation time
creatorid	optional	IDs of creating user of scheduled task. Example: "225494730938493804,225494730938493915".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
description__contains	optional	Keyword to search in description
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
id__contains	optional	Keyword to search in task ID
ids	optional	A list of scheduled tasks ids. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".

name__contains	optional	Keyword to search in task name
ostypes	optional	List of the OS types. Example: "linux".
outputdestination	optional	List of the tasks types. Example: "SentinelCloud".
query	optional	Keyword to search in scheduled tasks profile name
scheduledtime__between	optional	Date range for scheduled execution time
scopename__contains	optional	Keyword to search in scope name
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
status	optional	List of the tasks status. Example: "scheduled".
targetscope	optional	IDs of target scopes of scheduled task. Example: "225494730938493804,225494730938493915".
type	optional	List of the tasks types. Example: "action".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permission to perform such action

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get available Scheduled Tasks - response - pagination table
data	Response data	false	see Get available Scheduled Tasks - response - data table

errors	Errors	false	array
--------	--------	-------	-------

Get available Scheduled Tasks - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get available Scheduled Tasks - response - data

Name	Description	Required	Value
createdAt	Initiation (creation) time	true	string
creator	name/email of creating user	true	string
description	Description	true	string
id	Scheduled task ID	true	string
name	Name	true	string
outputDestination	Output destination	true	enum
scheduledTime	Scheduled time	true	see Get available Scheduled Tasks - response - scheduledTime table
status	Status of the task	true	enum
updatedAt	Latest update time	true	string
dynamicEndpointsFilter	endpoints filter, JSON-encoded	false	string
endpointsCount	count of targeted endpoints	false	integer
endpointsFilter	target agents filter (scopes or IDs)	false	see Get available Scheduled Tasks - response - endpointsFilter table
expireTime	Expire time	false	see Get available Scheduled Tasks - response - expireTime table
nameKey	Name key	false	string
osTypes	Os types	false	string []
recurrence	Recurrence	false	see Get available Scheduled Tasks - response - recurrence table
targetEndpointNames	list of endpoint names will be targeted in current scope	false	string []
targetEndpointsCount	number of endpoints that will be	false	integer

	targeted in current scope		
targetScopePath	if scope is targeted, the user readable scope path is provided, otherwise null	false	string
type	Type	false	enum

Get available Scheduled Tasks - response - scheduledTime

Name	Description	Required	Value
tz	Tz	true	string
utc	Utc	true	string

Get available Scheduled Tasks - response - endpointsFilter

Name	Description	Required	Value
accountIds	Account ids	false	string []
groupIds	Group ids	false	string []
ids	Ids	false	string []
siteIds	Site ids	false	string []
tenant	Tenant	false	boolean

Get available Scheduled Tasks - response - expireTime

Name	Description	Required	Value
tz	Tz	true	string
utc	Utc	true	string

Get available Scheduled Tasks - response - recurrence

Name	Description	Required	Value
dayOfMonth	The day of the month. Accepts only 1	false	integer

	or None.		
interval	The interval of the units	false	integer
unit	The unit of the recurrence	false	enum

Update existing Scheduled task

PUT /web/api/v2.1/remote-ops/scheduled-tasks/{scheduled_task_id}

Update existing Scheduled task

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permission to perform such action

404 - Scheduled task is not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update existing Scheduled task - response - data table
errors	Errors	false	array

Update existing Scheduled task - response - data

Name	Description	Required	Value
scheduledTaskId	Scheduled Task ID	true	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Update existing Scheduled task - body - data table

Update existing Scheduled task - body - data

Name	Description	Required	Value
scheduling	Scheduling	true	see Update existing Scheduled task - body - scheduling table

Update existing Scheduled task - body - scheduling

Name	Description	Required	Value
expireTime	Expire time	true	see Update existing Scheduled task - body - expireTime table
recurrence	Recurrence	true	see Update existing Scheduled task - body - recurrence table
scheduledTime	Scheduled time	true	see Update existing Scheduled task - body - scheduledTime table

Update existing Scheduled task - body - expireTime

Name	Description	Required	Value
tz	Tz	true	string
utc	Utc	true	string

Update existing Scheduled task - body - recurrence

Name	Description	Required	Value
dayOfMonth	The day of the month. Accepts only 1 or None.	false	integer
interval	The interval of the units	false	integer
unit	The unit of the recurrence	false	enum

Update existing Scheduled task - body - scheduledTime

Name	Description	Required	Value
------	-------------	----------	-------

tz	Tz	true	string
utc	Utc	true	string

RemoteOps Forensics

Start collection of Forensics artifacts according to specified profile

POST /web/api/v2.1/remote-ops/forensics/start-collection

Start collection of Forensics artifacts according to specified profile

Response Messages

202 - Forensics collection has been started

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
data	Data	true	see Start collection of Forensics artifacts according to specified profile - body - data table
filter	Filter specification of targeted agents	true	see Start collection of Forensics artifacts according to specified profile - body - filter table

Start collection of Forensics artifacts according to specified profile - body - data

Name	Description	Required	Value
collectionProfileId	ID of the Collection Profile that will be used	true	string
destination	Destination	true	see Start collection of Forensics artifacts according to specified profile - body - destination table
description	Description of the collection	false	string
tag	Tag identifier of the collection	false	string

Start collection of Forensics artifacts according to specified profile - body - destination

Name	Description	Required	Value
password	Password for encrypting uploaded binary artifacts	false	string
passwordFromScope	Used to specify execution where a generic password is used	false	see Start collection of Forensics artifacts according to specified profile - body - passwordFromScope table
profileId	ID of profile for destination of exported collection date	false	string

Start collection of Forensics artifacts according to specified profile - body - passwordFromScope

Name	Description	Required	Value
scopeLevel	User scope	true	enum
scopeId	string repr. of scope id	false	string

Start collection of Forensics artifacts according to specified profile - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []

activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []
agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal	false	string

	to given version		
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []

computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Start collection of Forensics artifacts according to specified profile - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string
createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time	false	string

	(format: <from_timestamp>-<to_timestamp>, inclusive)		
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []
externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved	false	string

	filter		
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA enabled if True, or not if False	false	boolean []
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []

isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string
liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []

locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceLocalnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []
osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []

proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []
scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []

storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string
totalMemory__gt	Memory size (MB, more than)	false	integer
totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string

	inclusive)		
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Start collection of Forensics artifacts according to specified profile - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Return result of collection task

GET /web/api/v2.1/remote-ops/forensics/task-result

Return result of collection task

Parameters

taskid	required	Task id. Example: "225494730938493804".
--------	----------	---

Response Messages

200 - Task is found and result is returned

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Return result of collection task - response - data table
errors	Errors	false	array

Return result of collection task - response - data

Name	Description	Required	Value
collection	Details of the collection	false	see Return result of collection task - response - collection table
collectionFile	Details of the collection file, if exists	false	see Return result of collection task - response - collectionFile table
collectionFileError	Collection file error	false	string
collectionProfile	Details of the collection profile used for collection	false	see Return result of collection task - response - collectionProfile table
destination	Details of the destination	false	see Return result of collection task - response - destination table
skylightParentTaskResultsUrl	Link to Skylight view with results for parent task	false	string
skylightResultsStatus	Status of Skylight results	false	see Return result of collection task - response - skylightResultsStatus table
skylightResultsUrl	Link to Skylight view with results for the single task	false	string

Return result of collection task - response - collection

Name	Description	Required	Value
tag	Tag of the collection	true	string
artifacts	Artifacts included in the collection	false	see Return result of collection task - response - artifacts table
description	Description of the collection	false	string

Return result of collection task - response - artifacts

Name	Description	Required	Value
artifactType	Type of the artifact	true	string
detailedStatus	Detailed status of the artifact collection	true	string
osType	Target Os	true	string
status	Status of the artifact collection	true	string
parameters	Parameters passed to the artifact	false	object

	collector		
--	-----------	--	--

Return result of collection task - response - collectionFile

Name	Description	Required	Value
agentId	Agent id	true	string
signature	File Signature	true	string
siteId	Site id	true	string
uploadedTimestamp	Uploaded timestamp	true	string
signatureType	Signature type	false	string

Return result of collection task - response - collectionProfile

Name	Description	Required	Value
id	ID of used collection profile	true	string
name	Name of used collection profile	true	string

Return result of collection task - response - destination

Name	Description	Required	Value
profileId	ID of destination profile used for collection	false	string

Return result of collection task - response - skylightResultsStatus

Name	Description	Required	Value
hasFailures	Indicates if there were failures during uploading data to Skylight	true	boolean
isEmpty	Indicates if the collection contains no data store in Skylight	true	boolean
errorMessage	Last error message if there were	false	string

	failures during upload		
--	------------------------	--	--

Returns collection file download pre-signed url

GET /web/api/v2.1/remote-ops/forensics/collection-file-url

Returns collection file download pre-signed url

Parameters

agentid	required	Agent id. Example: "225494730938493804".
signature	required	Signature
signaturetype	required	Signature type
siteid	required	Site id. Example: "225494730938493804".
uploadedtimestamp	required	Uploaded timestamp

Response Messages

- 200 - Remote Ops Forensics Collection File Found
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Returns collection file download pre-signed url - response - data table
errors	Errors	false	array

Returns collection file download pre-signed url - response - data

Name	Description	Required	Value
downloadUrl	download link for the file	false	string
fileName	the name of the file	false	string

Check if collection file exists for given storyline

GET /web/api/v2.1/remote-ops/forensics/is-collection-file

Check if collection file exists for given storyline

Parameters

agentid	required	Agent's ID. Example: "225494730938493804".
storyline	required	Storyline ID

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Collection file not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Check if collection file exists for given storyline - response - data table
errors	Errors	false	array

Check if collection file exists for given storyline - response - data

Name	Description	Required	Value
agentId	Agent's ID	true	string
signature	File's Signature	true	string
siteId	Site's ID	true	string
signatureType	Signature type	false	string
uploadedTimestamp	Collection file uploaded DateTime iso-formatted	false	string

Get list of supported artifact types

GET /web/api/v2.1/remote-ops/forensics/artifact-types

Return a complete list of supported artifact types

Response Messages

200 - Successes

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get list of supported artifact types - response - data table
errors	Errors	false	array

Get list of supported artifact types - response - data

Name	Description	Required	Value
artifactType	Artifact type code name, used as identifier of the artifact	true	string
category	Category of the artifact type	true	string
name	User-readable name of the artifact	true	string
categoryKey	Category key for translation	false	string
osTypes	Os types	false	string []
parameters	Parameters	false	see Get list of supported artifact types - response - parameters table
version	Internal version of the artifact type	false	integer

Get list of supported artifact types - response - parameters

Name	Description	Required	Value
default	Default value of artifact parameter, null if the parameter does not allow default	true	string
key	Unique key of artifact parameter	true	string
type	Type of artifact parameter	true	enum
description	Artifact parameter description	false	string
example	Example of the parameter value	false	string

Get Collection profile by ID

GET /web/api/v2.1/remote-ops/forensics/collection-profiles/{profile_id}

Get contents of an existing Forensics Collection profile, including specification of artifacts to be collected and profile metadata.

Response Messages

200 - Collection profile content is returned

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permission to perform such action

404 - Collection profile was not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Collection profile by ID - response - data table
errors	Errors	false	array

Get Collection profile by ID - response - data

Name	Description	Required	Value
createdAt	Timestamp when the profile was created	true	string
creator	Email of user who created the profile	true	string
description	Collection profile description	true	string
id	Collection profile ID	true	string
isBundled	Flag indicating if the Collection profile is bundled (provided by S1)	true	boolean
name	name of collection profile in db	true	string
scopeId	Scope ID where the Collection profile is stored	true	string
scopeLevel	Scope level where the Collection profile is stored	true	enum
scopeName	Scope name where the Collection profile is stored	true	string
scopePath	Full path of Scope where the Collection profile is stored	true	string
type	Type of RemoteOps Action (forensicsProfile)	true	enum
updater	Email of user who update the profile	true	string
version	Collection profile version	true	string
artifacts	Artifacts	false	see Get Collection profile by ID - response - artifacts table
nameKey	Profile name in camel case representation used for localization, only relevant for default profiles	false	string
osTypes	Os types	false	string []
updatedAt	Timestamp when the profile was updated	false	string

Get Collection profile by ID - response - artifacts

Name	Description	Required	Value
artifactType	Type of artifact to collect	true	string
osType	OS type where the artifact will be collected	true	enum
parameters	Input parameters for the artifact	false	object

Update Collection profile by ID

PUT /web/api/v2.1/remote-ops/forensics/collection-profiles/{profile_id}

Update contents of an existing Forensics Collection profile. All the profile data should be specified, even if the values are not changed. It's not allowed to change scope of profile. The name must be unique inside the scope, if different profile with specified name already exists, Bad request error is returned and no profile data is changed.

Response Messages

200 - Collection profile is updated

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User has insufficient permission to perform such action

404 - Collection profile was not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Collection profile by ID - response - data table
errors	Errors	false	array

Update Collection profile by ID - response - data

Name	Description	Required	Value
createdAt	Timestamp when the profile was created	true	string
creator	Email of user who created the profile	true	string
description	Collection profile description	true	string
id	Collection profile ID	true	string
isBundled	Flag indicating if the Collection profile is bundled (provided by S1)	true	boolean
name	name of collection profile in db	true	string
scopeId	Scope ID where the Collection profile is stored	true	string
scopeLevel	Scope level where the Collection profile is stored	true	enum
scopeName	Scope name where the Collection profile is stored	true	string
scopePath	Full path of Scope where the Collection profile is stored	true	string
type	Type of RemoteOps Action (forensicsProfile)	true	enum
updater	Email of user who update the profile	true	string
version	Collection profile version	true	string
artifacts	Artifacts	false	see Update Collection profile by ID - response - artifacts table
nameKey	Profile name in camel case representation used for localization, only relevant for default profiles	false	string
osTypes	Os types	false	string []
updatedAt	Timestamp when the profile was updated	false	string

Update Collection profile by ID - response - artifacts

Name	Description	Required	Value
artifactType	Type of artifact to collect	true	string
osType	OS type where the artifact will be collected	true	enum
parameters	Input parameters for the artifact	false	object

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Collection profile by ID - body - data table

Update Collection profile by ID - body - data

Name	Description	Required	Value
name	Collection profile name	true	string
artifacts	Artifacts	false	see Update Collection profile by ID - body - artifacts table
description	Collection profile description	false	string

Update Collection profile by ID - body - artifacts

Name	Description	Required	Value
artifactType	Type of artifact to collect	true	string
osType	OS type where the artifact will be collected	true	enum
parameters	Input parameters for the artifact	false	object

Delete Collection profiles

DELETE /web/api/v2.1/remote-ops/forensics/collection-profiles

Delete multiple Forensics Collection profiles. The profiles that are not possible to delete (e.g. bundled profiles by S1, non-existing or user does not have proper permissions) are skipped. Contents of successfully deleted profiles are returned in response.

Response Messages

200 - Delete was completed or partially completed.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Collection profiles - response - data table

errors	Errors	false	array
--------	--------	-------	-------

Delete Collection profiles - response - data

Name	Description	Required	Value
createdAt	Timestamp when the profile was created	true	string
creator	Email of user who created the profile	true	string
description	Collection profile description	true	string
id	Collection profile ID	true	string
isBundled	Flag indicating if the Collection profile is bundled (provided by S1)	true	boolean
name	name of collection profile in db	true	string
scopeId	Scope ID where the Collection profile is stored	true	string
scopeLevel	Scope level where the Collection profile is stored	true	enum
scopeName	Scope name where the Collection profile is stored	true	string
scopePath	Full path of Scope where the Collection profile is stored	true	string
type	Type of RemoteOps Action (forensicsProfile)	true	enum
updater	Email of user who update the profile	true	string
version	Collection profile version	true	string
artifacts	Artifacts	false	see Delete Collection profiles - response - artifacts table
nameKey	Profile name in camel case representation used for localization, only relevant for default profiles	false	string
osTypes	Os types	false	string []
updatedAt	Timestamp when the profile was updated	false	string

Delete Collection profiles - response - artifacts

Name	Description	Required	Value
artifactType	Type of artifact to collect	true	string
osType	OS type where the artifact will be collected	true	enum
parameters	Input parameters for the artifact	false	object

Body Schema

Name	Description	Required	Value
data	Data	false	see Delete Collection profiles - body - data table
filter	Filter	false	see Delete Collection profiles - body - filter table

Delete Collection profiles - body - data

Delete Collection profiles - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
ids	List of Collection profile IDs to delete	false	string []
sitelds	List of Site IDs to filter by	false	string []

Create new Collection profile

POST /web/api/v2.1/remote-ops/forensics/collection-profiles

Create a Forensics Collection profile with provided artifacts on the specified scope. The profile name must be unique inside the scope, if the name already exists, Bad request error is returned.

Response Messages

200 - Collection profile is created

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create new Collection profile - response - data table
errors	Errors	false	array

Create new Collection profile - response - data

Name	Description	Required	Value
createdAt	Timestamp when the profile was created	true	string
creator	Email of user who created the profile	true	string
description	Collection profile description	true	string
id	Collection profile ID	true	string
isBundled	Flag indicating if the Collection profile is bundled (provided by S1)	true	boolean
name	name of collection profile in db	true	string
scopeId	Scope ID where the Collection profile is stored	true	string
scopeLevel	Scope level where the Collection profile is stored	true	enum
scopeName	Scope name where the Collection profile is stored	true	string
scopePath	Full path of Scope where the Collection profile is stored	true	string
type	Type of RemoteOps Action (forensicsProfile)	true	enum
updater	Email of user who update the profile	true	string
version	Collection profile version	true	string
artifacts	Artifacts	false	see Create new Collection profile - response - artifacts table
nameKey	Profile name in camel case representation used for localization, only relevant for default profiles	false	string
osTypes	Os types	false	string []
updatedAt	Timestamp when the profile was updated	false	string

Create new Collection profile - response - artifacts

Name	Description	Required	Value
artifactType	Type of artifact to collect	true	string
osType	OS type where the artifact will be collected	true	enum
parameters	Input parameters for the artifact	false	object

Body Schema

Name	Description	Required	Value
data	Data	true	see Create new Collection profile - body - data table

Create new Collection profile - body - data

Name	Description	Required	Value
name	Collection profile name	true	string
scopeLevel	Scope level of the collection profile	true	enum
artifacts	Artifacts	false	see Create new Collection profile - body - artifacts table
description	Collection profile description	false	string
scopeId	Scope ID of the collection profile	false	string

Create new Collection profile - body - artifacts

Name	Description	Required	Value
artifactType	Type of artifact to collect	true	string
osType	OS type where the artifact will be collected	true	enum
parameters	Input parameters for the artifact	false	object

Get list of available Collection profiles

GET /web/api/v2.1/remote-ops/forensics/collection-profiles

Get list of available Forensics collection profiles. The list may be narrowed by specifying filter parameter. Profiles are inherited between scopes in both upward and downward directions, e.g. profiles on parent Account and Tenant scopes are returned when querying for a Site scope, and profiles on a Site scopes are returned when querying its parent Account. Bundled profiles are available regardless of requested scope. If scope is not specified in filter, the scopes of the requesting user are considered.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
autotriggeringcompatible	optional	Fetch auto triggering compatible profiles
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.

cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
ids	optional	A list of collection profiles IDs. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".
ostypes	optional	Os types. Example: "linux".
query	optional	Keyword to search in Collection profile name / description
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get list of available Collection profiles - response - pagination table
data	Response data	false	see Get list of available Collection profiles - response - data table
errors	Errors	false	array

Get list of available Collection profiles - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get list of available Collection profiles - response - data

Name	Description	Required	Value
createdAt	Timestamp when the profile was created	true	string
creator	Email of user who created the profile	true	string
creatorId	ID of user who created the profile	true	string
description	Collection profile description	true	string
id	Collection profile ID	true	string
isBundled	Flag indicating if the Collection profile is bundled (provided by S1)	true	boolean
name	name of collection profile in db	true	string
scopeId	Scope ID where the Collection profile is stored	true	string
scopeLevel	Scope level where the Collection profile is stored	true	enum
scopeName	Scope name where the Collection profile is stored	true	string
scopePath	Full path of Scope where the Collection profile is stored	true	string
type	Type of RemoteOps Action (forensicsProfile)	true	enum
updater	Email of user who update the profile	true	string

updaterId	ID of user who updated the profile	true	string
version	Collection profile version	true	string
nameKey	Profile name in camel case representation used for localization, only relevant for default profiles	false	string
osTypes	Os types	false	string []
updatedAt	Timestamp when the profile was updated	false	string

RemoteOps Scripts

Run Remote Script

POST /web/api/v2.1/remote-scripts/execute

Run a remote script that was uploaded to the SentinelOne Script Library.

Response Messages

200 - Run remote script request was successful

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Run Remote Script - response - data table
errors	Errors	false	array

Run Remote Script - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer
parentTaskId	The parent task id of the script execution task, null in case of pending execution	false	string
pending	Flag indicating if requested script execution requires approval and is created as pending execution	false	boolean
pendingExecutionId	ID of created pending execution, present only if pending flag is true	false	string

Body Schema

Name	Description	Required	Value
filter	Applied filter	true	see Run Remote Script - body - filter table
data	Data	false	see Run Remote Script - body - data table

Run Remote Script - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
activeProtection	Included agent active protections	false	string []
activeThreats	Include Agents with this amount of active threats	false	integer
activeThreats__gt	Include Agents with at least this amount of active threats	false	integer
adComputerMember__contains	Free-text filter by Active Directory computer groups string (supports multiple values)	false	string []
adComputerName__contains	Free-text filter by Active Directory computer name string (supports multiple values)	false	string []
adComputerQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
adQuery	An Active Directory query string	false	string
adQuery__contains	Free-text filter by Active Directory string (supports multiple values)	false	string []
adUserMember__contains	Free-text filter by Active Directory user groups string (supports multiple values)	false	string []
adUserName__contains	Free-text filter by Active Directory username string (supports multiple values)	false	string []
adUserQuery__contains	Free-text filter by Active Directory computer name or its groups (supports multiple values)	false	string []
agentNamespace__contains	Free-text filter by agent namespace (supports multiple values)	false	string []
agentOperatingMode__contains	Free-text filter by Agent Operating Mode (supports multiple values)	false	string []
agentOperatingModes	Agent operating mode in	false	string []
agentOperatingModesNin	Agent operating mode nin	false	string []

agentPodName__contains	Free-text filter by agent pod name (supports multiple values)	false	string []
agentVersion__between	Version range for agent version (format: <from_version>-<to_version>, inclusive)	false	string
agentVersion__gt	Agents versions greater than given version	false	string
agentVersion__gte	Agents versions greater than or equal to given version	false	string
agentVersion__lt	Agents versions less than given version	false	string
agentVersion__lte	Agents versions less than or equal to given version	false	string
agentVersions	Agent versions to include	false	string []
agentVersionsNin	Agent versions not to include	false	string []
appsVulnerabilityStatuses	Apps vulnerability status in	false	string []
appsVulnerabilityStatusesNin	Apps vulnerability status nin	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []

cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
cloudTags__contains	Free-text filter by cloud tags (supports multiple values)	false	string []
clusterName__contains	Free-text filter by cluster name (supports multiple values)	false	string []
computerName	Computer name	false	string
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
computerName__like	Match computer name partially (substring)	false	string
computerNameOrUuid__contains	Free-text filter by computer name or uuid (supports multiple values)	false	string []
consoleMigrationStatuses	Migration status in	false	string []
consoleMigrationStatusesNin	Migration status nin	false	string []
containerizedWorkloadCounts	Containerized workload counts	false	see Run Remote Script - body - containerizedWorkloadCounts table
coreCount__between	Possible number of CPU cores (inclusive)	false	string
coreCount__gt	CPU cores (more than)	false	integer
coreCount__gte	CPU cores (more than or equal)	false	integer
coreCount__lt	CPU cores (less than)	false	integer
coreCount__lte	CPU cores (less than or equal)	false	integer
cpuCount__between	Possible number of CPU cores (inclusive)	false	string
cpuCount__gt	Number of CPUs (more than)	false	integer
cpuCount__gte	Number of CPUs (more than or equal)	false	integer
cpuCount__lt	Number of CPUs (less than)	false	integer
cpuCount__lte	Number of CPUs (less than or equal)	false	integer
cpuld__contains	Free-text filter by CPU name (supports multiple values)	false	string []
createdAt__between	Date range for creation time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	Agents created after this timestamp	false	string

createdAt__gte	Agents created after or at this timestamp	false	string
createdAt__lt	Agents created before this timestamp	false	string
createdAt__lte	Agents created before or at this timestamp	false	string
csvFilterId	The ID of the CSV file to filter by	false	string
decommissionedAt__between	Date range for decommission time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
decommissionedAt__gt	Agents decommissioned after this timestamp	false	string
decommissionedAt__gte	Agents decommissioned after or at this timestamp	false	string
decommissionedAt__lt	Agents decommissioned before this timestamp	false	string
decommissionedAt__lte	Agents decommissioned before this timestamp	false	string
domains	Included network domains	false	string []
domainsNin	Not included network domains	false	string []
ecsClusterName__contains	Free-text filter by ECS cluster name	false	string []
ecsServiceArn__contains	Free-text filter by ECS service arn	false	string []
ecsServiceName__contains	Free-text filter by ECS service name	false	string []
ecsTaskArn__contains	Free-text filter by ECS task arn	false	string []
ecsTaskAvailabilityZone__contains	Free-text filter by ECS task availability zone	false	string []
ecsTaskDefinitionArn__contains	Free-text filter by ECS task definition arn	false	string []
ecsTaskDefinitionFamily__contains	Free-text filter by ECS task definition family	false	string []
ecsTaskDefinitionRevision__contains	Free-text filter by ECS task definition revision	false	string []
ecsType__contains	Free-text filter by ECS type	false	string []
ecsVersion__contains	Free-text filter by ECS version	false	string []
encryptedApplications	Disk encryption status	false	boolean []
entraId__contains	Free-text filter by Entra ID (supports multiple values)	false	string []

externalId__contains	Free-text filter by external ID (Customer ID)	false	string []
externalIp__contains	Free-text filter by visible IP (supports multiple values)	false	string []
filteredGroupIds	List of Group IDs to filter by	false	string []
filteredSiteIds	List of Site IDs to filter by	false	string []
filterId	Include all Agents matching this saved filter	false	string
firewallEnabled	The agents supports Firewall Control and it is enabled for the agent's group	false	boolean []
gatewayIp	Gateway ip	false	string
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasContainerizedWorkload	Indicates whether the agent protects containerized workload at the moment	false	boolean []
hasLocalConfiguration	Agent has a local configuration set	false	boolean
hasTags	Include only Agents that have any tags assigned if True, or none if False	false	boolean
ids	Included Agent IDs	false	string []
idsNin	Excluded Agent IDs	false	string []
infected	Include only Agents with at least one active threat	false	boolean
installerTypes	Include only Agents installed with these package types	false	string []
installerTypesNin	Exclude Agents installed with these package types	false	string []
isActive	Include only active Agents	false	boolean []
isAdConnector	The agents that are ADConnectors if True, or not if False	false	boolean []
isDecommissioned	Include active, decommissioned or both	false	boolean []
isEventSearchProxyEnabled	Include only Agents using event search proxy. Accepts true, false, or none (for not reported).	false	string []
isHyperAutomate	The agents has Hyper Automate PNA	false	boolean []

	enabled if True, or not if False		
isMgmtProxyEnabled	Include only Agents using mgmt proxy. Accepts true, false, or none (for not reported).	false	string []
isPendingUninstall	Include only Agents with pending uninstall requests	false	boolean []
isUninstalled	Include installed, uninstalled or both	false	boolean []
isUpToDate	Include only Agents with updated software	false	boolean []
k8sNodeLabels__contains	Free-text filter by K8s node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by K8s node name (supports multiple values)	false	string []
k8sType__contains	Free-text filter by K8s type(supports multiple values)	false	string []
k8sVersion__contains	Free-text filter by K8s version (supports multiple values)	false	string []
lastActiveDate__between	Date range for last active date(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActiveDate__gt	Agents last active after this time	false	string
lastActiveDate__gte	Agents last active after or at this time	false	string
lastActiveDate__lt	Agents last active before this time	false	string
lastActiveDate__lte	Agents last active before or at this time	false	string
lastLoggedInUserName__contains	Free-text filter by username (supports multiple values)	false	string []
lastSuccessfulScanDate__between	Date range for last successful full disk scan(format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastSuccessfulScanDate__gt	Agents last successful full disk scan after this time	false	string
lastSuccessfulScanDate__gte	Agents last successful full disk scan after or at this time	false	string
lastSuccessfulScanDate__lt	Agents last successful full disk scan before this time	false	string
lastSuccessfulScanDate__lte	Agents last successful full disk scan before or at this time	false	string

liveUpdateId__contains	Free-text filter by live update ID (supports multiple values)	false	string []
locationEnabled	The agents supports Location Awareness and it is enabled for the agent's group	false	boolean []
locationIds	Include only Agents reporting these locations	false	string []
locationIdsNin	Do not include only Agents reporting these locations	false	string []
machineTypes	Included machine types	false	string []
machineTypesNin	Not included machine types	false	string []
migrationStatus	Migration status	false	enum
missingPermissions	Included missing permissions	false	string []
missingPermissionsNin	Excluded missing permissions	false	string []
mitigationMode	Agent mitigation mode policy	false	enum
mitigationModeSuspicious	Mitigation mode policy for suspicious activity	false	enum
networkInterfaceGatewayMacAddress__contains	Free-text filter by Gateway MAC address (supports multiple values)	false	string []
networkInterfaceIpnet__contains	Free-text filter by local IP (supports multiple values)	false	string []
networkInterfacePhysical__contains	Free-text filter by MAC address (supports multiple values)	false	string []
networkQuarantineEnabled	The agents supports Network Quarantine Control and its enabled for the agent's group	false	boolean []
networkStatuses	Included network statuses	false	string []
networkStatusesNin	Included network statuses	false	string []
operationalStates	Agent operational state	false	string []
operationalStatesNin	Do not include these Agent operational states	false	string []
osArch	OS architecture	false	enum
osArches	OS architectures to include	false	string []
osArchesNin	OS architectures not to include	false	string []
osTypes	Included OS types	false	string []
osTypesNin	Not included OS types	false	string []

osVersion__contains	Free-text filter by OS full name and version (supports multiple values)	false	string []
pacFileUsage	Include only Agents using PAC file for proxy configuration. Accepts true, false, or none (for not reported).	false	string []
proxyMethod	Include only Agents using these proxy methods	false	string []
proxyMethodNin	Exclude Agents using these proxy methods	false	string []
query	A free-text search term, will match applicable attributes (sub-string match). Note: Device's physical addresses will be matched if they start with the search term only (no match if they contain the term).	false	string
rangerStatus	[DEPRECATED] Use rangerStatuses.	false	enum
rangerStatuses	Status of Network Discovery	false	string []
rangerStatusesNin	Do not include these Network Scanner Statuses	false	string []
rangerVersions	Network Scanner versions to include	false	string []
rangerVersionsNin	Network Scanner versions not to include	false	string []
registeredAt__between	Date range for first registration time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
registeredAt__gt	Agents registered after this time	false	string
registeredAt__gte	Agents registered after or at this time	false	string
registeredAt__lt	Agents registered before this time	false	string
registeredAt__lte	Agents registered before or at this time	false	string
remoteOpsForensicsSupported	Include only agents that has Remote Ops Forensicsfeature supported	false	boolean
remoteProfilingStates	Agent remote profiling state	false	string []
remoteProfilingStatesNin	Do not include these Agent remote profiling states	false	string []
rsoLevel	Supported Remote Script Orchestration level	false	enum
rsoLevels	A list of included rso_levels	false	string []

scanStatus	Scan status	false	enum
scanStatuses	Included scan statuses	false	string []
scanStatusesNin	Not included scan statuses	false	string []
serialNumber__contains	Free-text filter by Serial Number (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storageTypes	Included storage types	false	string []
storageTypesNin	Excluded storage types	false	string []
tagsData	Filter agents by their assigned tags. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
tenant	Indicates a tenant scope request	false	boolean
threatContentHash	Include only Agents that have at least one threat with this content hash	false	string
threatCreatedAt__between	Agents with threats reported in a date range (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
threatCreatedAt__gt	Agents with threats reported after this time	false	string
threatCreatedAt__gte	Agents with threats reported after or at this time	false	string
threatCreatedAt__lt	Agents with threats reported before this time	false	string
threatCreatedAt__lte	Agents with threats reported before or at this time	false	string
threatHidden	Include only Agents with at least one hidden threat	false	boolean
threatMitigationStatus	Include only Agents that have threats with this mitigation status	false	enum
threatRebootRequired	Has at least one threat with at least one mitigation action pending reboot to succeed	false	boolean []
threatResolved	Include only Agents with at least one resolved threat	false	boolean
totalMemory__between	Total memory range (GB, inclusive)	false	string

totalMemory__gt	Memory size (MB, more than)	false	integer
totalMemory__gte	Memory size (MB, more than or equal)	false	integer
totalMemory__lt	Memory size (MB, less than)	false	integer
totalMemory__lte	Memory size (MB, less than or equal)	false	integer
updatedAt__between	Date range for update time (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
updatedAt__gt	Agents updated after this timestamp	false	string
updatedAt__gte	Agents updated after or at this timestamp	false	string
updatedAt__lt	Agents updated before this timestamp	false	string
updatedAt__lte	Agents updated before or at this timestamp	false	string
userActionsNeeded	Included pending user actions	false	string []
userActionsNeededNin	Excluded pending user actions	false	string []
uuid	Agent's universally unique identifier	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
uuids	A list of included UUIDs	false	string []
windowsOsRevision__gte	Agents os revision than or equal to given version	false	integer
windowsOsRevision__lte	Agents os revision lower than or equal to given version	false	integer

Run Remote Script - body - containerizedWorkloadCounts

Name	Description	Required	Value
containersCount	Number of containers the agent is currently protecting	false	integer
PodsCount	Number of K8s pods the agent is currently protecting	false	integer
tasksCount	Number of tasks the agent is currently protecting	false	integer

Run Remote Script - body - data

Name	Description	Required	Value
outputDestination	Output destination	true	enum
scriptId	Script id	true	string
taskDescription	Task description	true	string
apiKey	Api key	false	string
destinationProfileId	Id of destination profile to use	false	string
destinationProfileKeyword	Destination profile keyword	false	string
inputParams	Input params	false	string
outputDirectory	Output directory	false	string
outputFilePaths	Output file paths	false	string []
password	Password	false	string
passwordFromScope	Used to specify execution where a generic password is used	false	see Run Remote Script - body - passwordFromScope table
requiresApproval	If set to true, execution will require approval	false	boolean
scriptRuntimeTimeoutSeconds	Script runtime timeout in seconds for current execution	false	integer
singularityxdrKeyword	Singularityxdr keyword	false	string
singularityxdrUrl	Singularityxdr url	false	string

Run Remote Script - body - passwordFromScope

Name	Description	Required	Value
scopeLevel	User scope	true	enum
scopeId	string repr. of scope id	false	string

Get Remote Scripts Tasks Status

GET /web/api/v2.1/remote-scripts/status

Get remote scripts tasks using a variety of filters. Accessible via API only
parent_task_id or parent_task_id__in query parameter is mandatory

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
computername__contains	optional	Free-text filter by agent computer name (supports multiple values)
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__gt	optional	Created at greater than. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Created at greater or equal than. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Created at lesser than. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Created at lesser or equal than. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
description__contains	optional	Only include tasks with specific description
detailedstatus__contains	optional	Only include tasks with specific detailed status
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of IDs to filter by. Example: "225494730938493804,225494730938493915".
initiatedby__contains	optional	Only include tasks from specific initiating user
limit	optional	Limit number of returned items (1-1000). Example: "10".
parenttaskid	optional	parent task id to fetch the status by. Example: "225494730938493804".
parenttaskid__in	optional	List of IDs to filter by
query	optional	Query
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".

skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
status	optional	Status in. Example: "created".
tenant	optional	Indicates a tenant scope request
type	optional	Type
types	optional	Type in
updatedat__gt	optional	Updated at greater than. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Updated at greater or equal than. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Updated at lesser than. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Updated at lesser or equal than. Example: "2018-02-27T04:49:26.257525Z".
uuid__contains	optional	Free-text filter by agent UUID (supports multiple values)

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Remote Scripts Tasks Status - response - pagination table
data	Response data	false	see Get Remote Scripts Tasks Status - response - data table
errors	Errors	false	array

Get Remote Scripts Tasks Status - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Remote Scripts Tasks Status - response - data

Name	Description	Required	Value
accountId	Account id	false	string
accountName	Account name	false	string
agentComputerName	Agent computer name	false	string
agentId	Agent id	false	string
agentIsActive	Agent is active	false	boolean
agentIsDecommissioned	Agent is decommissioned	false	boolean
agentMachineType	Agent machine type	false	string
agentOsType	OS type	false	enum
agentUuid	Agent uuid	false	string
createdAt	Timestamp of date creation	false	string
description	Description	false	string
detailedStatus	Detailed status	false	string
groupId	Group id	false	string
groupName	Group name	false	string
id	Task id	false	string
initiatedBy	Initiated by	false	string
initiatedById	Initiated by id	false	string
parentTaskId	Parent task id	false	string

scriptResultsBucket	Script results bucket	false	string
scriptResultsPath	Script results path	false	string
scriptResultsSignature	Script results signature	false	string
siteId	Site id	false	string
siteName	Site name	false	string
status	Status	false	enum
statusCode	Status code	false	integer
statusDescription	Status description	false	
type	Type	false	string
updatedAt	Timestamp of last update	false	string

Get Script Results

POST /web/api/v2.1/remote-scripts/fetch-files

Get scripts results URLs. Accessible via API only

Response Messages

200 - Get remote script results was successful

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Script Results - response - data table
errors	Errors	false	array

Get Script Results - response - data

Name	Description	Required	Value
data	Data	false	see Get Script Results - response - data table

Get Script Results - response - data

Name	Description	Required	Value
downloadLinks	List of download links	false	see Get Script Results - response - downloadLinks table
errors	Task id's and detailed errors for tasks which a download link couldn't be fetched	false	array

Get Script Results - response - downloadLinks

Name	Description	Required	Value
downloadUrl	download link for the file	false	string
fileName	the name of the file	false	string
taskId	the task id related to the download link	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Get Script Results - body - data table

Get Script Results - body - data

Name	Description	Required	Value
computerNames	A list of partial or whole computer names, which ran scripts, to get a download link for	false	string []
taskIds	A list of task ids to get a download link for	false	string []

Get upload limit for Package

GET /web/api/v2.1/remote-scripts/fetch-upload-limits

Get upload limit for Package

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Get script content

GET /web/api/v2.1/remote-scripts/script-content

Get Script content by script id

Parameters

scriptid	optional	Script ID. Example: "225494730938493804".
----------	----------	---

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Script not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get script content - response - data table
errors	Errors	false	array

Get script content - response - data

Name	Description	Required	Value
scriptContent	Script content	true	string

Get Scripts

GET /web/api/v2.1/remote-scripts

Get data of the scripts in the SentinelOne Script Library.

The SentinelOne Script Library, used for the Remote Script Orchestration feature, gives you a wide range of scripts to collect various forensic artifacts, parse them, and show them in formats that are easy to analyze. Use the scripts to collect information such as hardware and software inventory and configuration, running applications and processes, files and directories, network connections, and more.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
groupids	optional	List of group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	A list of script IDs. Example: "225494730938493804,225494730938493915".
isavailableforars	optional	Is the script runnable in Advanced Response Scripts
limit	optional	Limit number of returned items (1-1000). Example: "10".
ostypes	optional	List of the script OS types. Example: "linux".
query	optional	Query
scripttype	optional	List of the script types. Example: "artifactCollection".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Scripts - response - pagination table
data	Response data	false	see Get Scripts - response - data table
errors	Errors	false	array

Get Scripts - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Scripts - response - data

Name	Description	Required	Value
createdByUserId	Created by user id	true	string
inputExample	Input example	true	string
inputInstructions	Input instructions	true	string
inputRequired	Is input required	true	boolean
scriptName	Script name	true	string
scriptType	Script type	true	string
version	Version	true	string
bucketName	Bucket name	false	string
createdAt	Created at	false	string
createdByUser	Created by user	false	string
creator	Name of the creating user	false	string
creatorId	Id of the creating user	false	string
fileName	File name with full path	false	string
fileSize	File size	false	integer
id	Script ID	false	string
isAvailableForArs	Is the script runnable in Advanced Response Scripts	false	boolean
isAvailableForLite	Is the script runnable in Lite version	false	boolean
mgmtId	Mgmt id	false	integer

nameKey	Script name in camel case representation used for localization, only relevant for builtin-scripts	false	string
osTypes	OS types	false	string []
outputFilePaths	Output file paths	false	string []
package	Package	false	see Get Scripts - response - package table
scopeId	Scope ID	false	string
scopeLevel	Scope level	false	enum
scopeName	The scripts scope name	false	string
scopePath	The path of the scripts scope	false	string
scriptDescription	Script description	false	string
scriptRuntimeTimeoutSeconds	Script runtime timeout in seconds	false	integer
shortFileName	File name	false	string
signature	Signature	false	string
signatureType	Signature type	false	string
supportedDestinations	Supported destinations	false	string []
updatedAt	Updated at	false	string
updater	Name of the updating user	false	string
updaterId	Id of the updating user	false	string

Get Scripts - response - package

Name	Description	Required	Value
bucketName	Bucket name	false	string
endpointExpiration	Package expiration option on endpoint	false	string
endpointExpirationSeconds	Package expiration time on endpoint	false	integer
fileName	File name with full path	false	string
fileSize	File size	false	integer
id	Package ID	false	string
signature	Signature	false	string
signatureType	Signature type	false	string

Upload New Script

POST /web/api/v2.1/remote-scripts

Upload a new script file. The file and various properties are required. To see the mandatory and optional parameters and their valid values, see the Body Schema or click Run On Console.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Upload New Script - response - data table
errors	Errors	false	array

Upload New Script - response - data

Name	Description	Required	Value
createdById	Created by user id	true	string
inputExample	Input example	true	string
inputInstructions	Input instructions	true	string
inputRequired	Is input required	true	boolean
scriptName	Script name	true	string
scriptType	Script type	true	string
version	Version	true	string
bucketName	Bucket name	false	string
createdAt	Created at	false	string
createdByUser	Created by user	false	string
creator	Name of the creating user	false	string
creatorId	Id of the creating user	false	string
fileName	File name with full path	false	string
fileSize	File size	false	integer
id	Script ID	false	string
isAvailableForArs	Is the script runnable in Advanced Response Scripts	false	boolean
isAvailableForLite	Is the script runnable in Lite version	false	boolean
mgmtId	Mgmt id	false	integer
nameKey	Script name in camel case representation used for localization, only relevant for builtin-scripts	false	string
osTypes	OS types	false	string []
outputFilePaths	Output file paths	false	string []
package	Package	false	see Upload New Script - response - package table
scopeId	Scope ID	false	string
scopeLevel	Scope level	false	enum
scopeName	The scripts scope name	false	string

scopePath	The path of the scripts scope	false	string
scriptDescription	Script description	false	string
scriptRuntimeTimeoutSeconds	Script runtime timeout in seconds	false	integer
shortFileName	File name	false	string
signature	Signature	false	string
signatureType	Signature type	false	string
supportedDestinations	Supported destinations	false	string []
updatedAt	Updated at	false	string
updater	Name of the updating user	false	string
updaterId	Id of the updating user	false	string

Upload New Script - response - package

Name	Description	Required	Value
bucketName	Bucket name	false	string
endpointExpiration	Package expiration option on endpoint	false	string
endpointExpirationSeconds	Package expiration time on endpoint	false	integer
fileName	File name with full path	false	string
fileSize	File size	false	integer
id	Package ID	false	string
signature	Signature	false	string
signatureType	Signature type	false	string

Body Schema

Name	Description	Required	Value
formData		false	see Upload New Script - body - formData table

Upload New Script - body - formData

Name	Description	Required	Value
inputRequired	Is input required	true	boolean
scopeLevel	Scope level. Example: "site".	true	enum
scriptName	Script name	true	string
scriptType	Script type. Example: "artifactCollection".	true	enum
consoleData	Console data	false	string
file	File	false	file
inputExample	Input example	false	string
inputInstructions	Input instructions	false	string
isDuplication	True if script/package files should be taken from an existing script specified in original_script_id	false	boolean
isScriptContentEncoded	True if script content is encoded	false	boolean
originalScriptId	ID of script, from which the script/package files will be copied, applicable only if is_duplication is true. Example: "225494730938493804".	false	string
osTypes	Os types. Example: "m,a,c,o,s,,,l,i,n,u,x".	false	string []
packageEndpointExpiration	Package expiration option on endpoint. Example: "None".	false	enum
packageEndpointExpirationSeconds	Package expiration time on endpoint	false	integer
packageFile	Package file	false	file
packageMaxSize	Package max size	false	string
packageRemoved	True if package should file should not be copied, applicable only if is_duplication is true	false	boolean
scopeId	Scope ID. Example: "225494730938493804".	false	string
scriptContent	Content of the script file, applicable only if is_duplication is true	false	string

scriptDescription	Script description	false	string
scriptRuntimeTimeoutSeconds	Script runtime timeout in seconds	false	integer
sendActivity	Send activity	false	boolean

Delete Scripts

DELETE /web/api/v2.1/remote-scripts

Deletes scripts that match a filter.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Delete Scripts - response - pagination table
data	Response data	false	see Delete Scripts - response - data table
errors	Errors	false	array

Delete Scripts - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Delete Scripts - response - data

Name	Description	Required	Value
createdByUserId	Created by user id	true	string
inputExample	Input example	true	string
inputInstructions	Input instructions	true	string
inputRequired	Is input required	true	boolean
scriptName	Script name	true	string
scriptType	Script type	true	string
version	Version	true	string
bucketName	Bucket name	false	string
createdAt	Created at	false	string
createdByUser	Created by user	false	string
creator	Name of the creating user	false	string
creatorId	Id of the creating user	false	string
fileName	File name with full path	false	string
fileSize	File size	false	integer
id	Script ID	false	string
isAvailableForArs	Is the script runnable in Advanced Response Scripts	false	boolean
isAvailableForLite	Is the script runnable in Lite version	false	boolean
mgmtId	Mgmt id	false	integer

nameKey	Script name in camel case representation used for localization, only relevant for builtin-scripts	false	string
osTypes	OS types	false	string []
outputFilePaths	Output file paths	false	string []
package	Package	false	see Delete Scripts - response - package table
scopeId	Scope ID	false	string
scopeLevel	Scope level	false	enum
scopeName	The scripts scope name	false	string
scopePath	The path of the scripts scope	false	string
scriptDescription	Script description	false	string
scriptRuntimeTimeoutSeconds	Script runtime timeout in seconds	false	integer
shortFileName	File name	false	string
signature	Signature	false	string
signatureType	Signature type	false	string
supportedDestinations	Supported destinations	false	string []
updatedAt	Updated at	false	string
updater	Name of the updating user	false	string
updaterId	Id of the updating user	false	string

Delete Scripts - response - package

Name	Description	Required	Value
bucketName	Bucket name	false	string
endpointExpiration	Package expiration option on endpoint	false	string
endpointExpirationSeconds	Package expiration time on endpoint	false	integer
fileName	File name with full path	false	string
fileSize	File size	false	integer
id	Package ID	false	string
signature	Signature	false	string
signatureType	Signature type	false	string

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Delete Scripts - body - filter table
consoleData	Console data	false	string
sendActivity	Send activity	false	boolean

Delete Scripts - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of group IDs to filter by	false	string []
ids	A list of Scripts IDs	false	string []
osTypes	List of the script OS types.	false	string []
query	Query	false	string
scriptType	List of the script types	false	string []
sitelds	List of Site IDs to filter by	false	string []

Update a Script

PUT /web/api/v2.1/remote-scripts/{script_id}

Change the properties of a given script: runtime timeout, name, and whether input is required (if true, input example and instructions are required). This command requires the script ID, which you can get from the Get Scripts API.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Script not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update a Script - response - data table
errors	Errors	false	array

Update a Script - response - data

Name	Description	Required	Value
createdById	Created by user id	true	string
inputExample	Input example	true	string
inputInstructions	Input instructions	true	string
inputRequired	Is input required	true	boolean
scriptName	Script name	true	string
scriptType	Script type	true	string
version	Version	true	string
bucketName	Bucket name	false	string
createdAt	Created at	false	string
createdByUser	Created by user	false	string
creator	Name of the creating user	false	string
creatorId	Id of the creating user	false	string
fileName	File name with full path	false	string
fileSize	File size	false	integer
id	Script ID	false	string
isAvailableForArs	Is the script runnable in Advanced Response Scripts	false	boolean
isAvailableForLite	Is the script runnable in Lite version	false	boolean
mgmtId	Mgmt id	false	integer
nameKey	Script name in camel case representation used for localization, only relevant for builtin-scripts	false	string
osTypes	OS types	false	string []
outputFilePaths	Output file paths	false	string []
package	Package	false	see Update a Script - response - package table
scopeId	Scope ID	false	string
scopeLevel	Scope level	false	enum
scopeName	The scripts scope name	false	string

scopePath	The path of the scripts scope	false	string
scriptDescription	Script description	false	string
scriptRuntimeTimeoutSeconds	Script runtime timeout in seconds	false	integer
shortFileName	File name	false	string
signature	Signature	false	string
signatureType	Signature type	false	string
supportedDestinations	Supported destinations	false	string []
updatedAt	Updated at	false	string
updater	Name of the updating user	false	string
updaterId	Id of the updating user	false	string

Update a Script - response - package

Name	Description	Required	Value
bucketName	Bucket name	false	string
endpointExpiration	Package expiration option on endpoint	false	string
endpointExpirationSeconds	Package expiration time on endpoint	false	integer
fileName	File name with full path	false	string
fileSize	File size	false	integer
id	Package ID	false	string
signature	Signature	false	string
signatureType	Signature type	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Update a Script - body - data table
consoleData	Console data	false	string
sendActivity	Send activity	false	boolean

Update a Script - body - data

Name	Description	Required	Value
inputExample	Input example	true	string
inputInstructions	Input instructions	true	string
inputRequired	Is input required	true	boolean
scriptName	Script name	true	string
scriptRuntimeTimeoutSeconds	Script runtime timeout in seconds	true	integer
scriptType	Script type	true	enum
osTypes	Os types	false	string []
packageEndpointExpiration	Package expiration option on endpoint	false	enum
packageEndpointExpirationSeconds	Package expiration time on endpoint	false	integer
scriptDescription	Script description	false	string

Update a Script

PUT /web/api/v2.1/remote-scripts/edit/{script_id}

Change the properties of a given script: runtime timeout, name, and whether input is required (if true, input example and instructions are required), or script content itself. This command requires the script ID, which you can get from the Get Scripts API.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Script not found

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Update a Script - response - data table
errors	Errors	false	array

Update a Script - response - data

Name	Description	Required	Value
createdById	Created by user id	true	string
inputExample	Input example	true	string
inputInstructions	Input instructions	true	string
inputRequired	Is input required	true	boolean
scriptName	Script name	true	string
scriptType	Script type	true	string
version	Version	true	string
bucketName	Bucket name	false	string
createdAt	Created at	false	string
createdByUser	Created by user	false	string
creator	Name of the creating user	false	string
creatorId	Id of the creating user	false	string
fileName	File name with full path	false	string
fileSize	File size	false	integer
id	Script ID	false	string
isAvailableForArs	Is the script runnable in Advanced Response Scripts	false	boolean
isAvailableForLite	Is the script runnable in Lite version	false	boolean
mgmtId	Mgmt id	false	integer
nameKey	Script name in camel case representation used for localization, only relevant for builtin-scripts	false	string
osTypes	OS types	false	string []
outputFilePaths	Output file paths	false	string []
package	Package	false	see Update a Script - response - package table
scopeId	Scope ID	false	string
scopeLevel	Scope level	false	enum
scopeName	The scripts scope name	false	string

scopePath	The path of the scripts scope	false	string
scriptDescription	Script description	false	string
scriptRuntimeTimeoutSeconds	Script runtime timeout in seconds	false	integer
shortFileName	File name	false	string
signature	Signature	false	string
signatureType	Signature type	false	string
supportedDestinations	Supported destinations	false	string []
updatedAt	Updated at	false	string
updater	Name of the updating user	false	string
updaterId	Id of the updating user	false	string

Update a Script - response - package

Name	Description	Required	Value
bucketName	Bucket name	false	string
endpointExpiration	Package expiration option on endpoint	false	string
endpointExpirationSeconds	Package expiration time on endpoint	false	integer
fileName	File name with full path	false	string
fileSize	File size	false	integer
id	Package ID	false	string
signature	Signature	false	string
signatureType	Signature type	false	string

Body Schema

Name	Description	Required	Value
formData		false	see Update a Script - body - formData table

Update a Script - body - formData

Name	Description	Required	Value
inputExample	Input example	true	string
inputInstructions	Input instructions	true	string
inputRequired	Is input required	true	boolean
scriptName	Script name	true	string
scriptRuntimeTimeoutSeconds	Script runtime timeout in seconds	true	integer
scriptType	Script type. Example: "artifactCollection".	true	enum
consoleData	Console data	false	string
isScriptContentEncoded	Is the script content base64 encoded?	false	boolean
osTypes	Os types. Example: "m,a,c,o,s,,,l,i,n,u,x".	false	string []
packageEndpointExpiration	Package expiration option on endpoint. Example: "None".	false	enum
packageEndpointExpirationSeconds	Package expiration time on endpoint	false	integer
packageFile	Package file	false	file
packageMaxSize	Package max size	false	string
packageRemoved	Was package removed during edit of the script?	false	boolean
scriptContent	Filled out with a new content of a script if the script content was changed on an already previously uploaded script	false	string
scriptDescription	Script description	false	string
scriptFile	Script file	false	file
sendActivity	Send activity	false	boolean

Get paginated pending executions

GET /web/api/v2.1/remote-scripts/pending-executions

Get paginated pending executions

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
groupids	optional	List of group IDs to filter by. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get paginated pending executions - response - pagination table
data	Response data	false	see Get paginated pending executions - response - data table
errors	Errors	false	array

Get paginated pending executions - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get paginated pending executions - response - data

Name	Description	Required	Value
canApproveOrDecline	Can approve or decline	true	boolean
creator	Creator	true	string
creatorId	Creator id	true	string
executionData	Execution data	true	see Get paginated pending executions - response - executionData table
pendingExecutionId	Pending execution id	true	string
reviewer	Reviewer	true	string
reviewerId	Reviewer id	true	string
scriptData	Script data	true	see Get paginated pending executions - response - scriptData table
state	State	true	enum
totalEndpoints	Total endpoints	true	integer
createdAt	Created at	false	string
endpointsByScope	Endpoints by scope	false	see Get paginated pending executions - response - endpointsByScope table
scheduledTaskId	Scheduled task id	false	string

Get paginated pending executions - response - executionData

Name	Description	Required	Value
outputDestination	Output destination	true	enum

scriptId	Script id	true	string
taskDescription	Task description	true	string
apiKey	Api key	false	string
destinationProfileId	Id of destination profile to use	false	string
destinationProfileKeyword	Destination profile keyword	false	string
inputParams	Input params	false	string
outputDirectory	Output directory	false	string
outputFilePaths	Output file paths	false	string []
password	Password	false	string
passwordFromScope	Used to specify execution where a generic password is used	false	see Get paginated pending executions - response - passwordFromScope table
requiresApproval	If set to true, execution will require approval	false	boolean
scriptRuntimeTimeoutSeconds	Script runtime timeout in seconds for current execution	false	integer
singularityxdrKeyword	Singularityxdr keyword	false	string
singularityxdrUrl	Singularityxdr url	false	string

Get paginated pending executions - response - passwordFromScope

Name	Description	Required	Value
scopeLevel	User scope	true	enum
scopeId	string repr. of scope id	false	string

Get paginated pending executions - response - scriptData

Name	Description	Required	Value
createdByUserId	Created by user id	true	string
inputExample	Input example	true	string
inputInstructions	Input instructions	true	string
inputRequired	Is input required	true	boolean
scriptName	Script name	true	string

scriptType	Script type	true	string
version	Version	true	string
bucketName	Bucket name	false	string
createdAt	Created at	false	string
createdByUser	Created by user	false	string
creator	Name of the creating user	false	string
creatorId	Id of the creating user	false	string
fileName	File name with full path	false	string
fileSize	File size	false	integer
id	Script ID	false	string
isAvailableForArs	Is the script runnable in Advanced Response Scripts	false	boolean
isAvailableForLite	Is the script runnable in Lite version	false	boolean
mgmtId	Mgmt id	false	integer
nameKey	Script name in camel case representation used for localization, only relevant for builtin-scripts	false	string
osTypes	OS types	false	string []
outputFilePaths	Output file paths	false	string []
package	Package	false	see Get paginated pending executions - response - package table
scopeId	Scope ID	false	string
scopeLevel	Scope level	false	enum
scopeName	The scripts scope name	false	string
scopePath	The path of the scripts scope	false	string
scriptDescription	Script description	false	string
scriptRuntimeTimeoutSeconds	Script runtime timeout in seconds	false	integer
shortFileName	File name	false	string
signature	Signature	false	string
signatureType	Signature type	false	string
supportedDestinations	Supported destinations	false	string []
updatedAt	Updated at	false	string
updater	Name of the updating user	false	string
updaterId	Id of the updating user	false	string

Get paginated pending executions - response - package

Name	Description	Required	Value
bucketName	Bucket name	false	string
endpointExpiration	Package expiration option on endpoint	false	string
endpointExpirationSeconds	Package expiration time on endpoint	false	integer
fileName	File name with full path	false	string
fileSize	File size	false	integer
id	Package ID	false	string
signature	Signature	false	string
signatureType	Signature type	false	string

Get paginated pending executions - response - endpointsByScope

Name	Description	Required	Value
scopeName		true	string
totalEndpoints		true	integer

Approve/decline pending execution

PUT /web/api/v2.1/remote-scripts/pending-executions/{pending_execution_id}

Approve/decline pending execution

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Pending execution not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Approve/decline pending execution - response - data table
errors	Errors	false	array

Approve/decline pending execution - response - data

Name	Description	Required	Value
success	Operation result	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Approve/decline pending execution - body - data table

Approve/decline pending execution - body - data

Name	Description	Required	Value
action	Action	true	enum

Gets a guardrails configuration for a given scope

GET /web/api/v2.1/remote-scripts/guardrails/configuration

Gets a guardrails configuration for a given scope

Parameters

scopeid	required	Scope ID. Example: "225494730938493804".
scopelevel	required	Scope level. Example: "account".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Gets a guardrails configuration for a given scope - response - data table
errors	Errors	false	array

Gets a guardrails configuration for a given scope - response - data

Name	Description	Required	Value
enabled	Whether guardrail is active	true	boolean
endpointsQuantity	Threshold for number of endpoints	true	integer
inherited	Whether guardrail is inherited	true	boolean
scriptTypes	List of script types that the guardrail relates to	false	string []

Updates or inserts (if record does not exist) a guardrails configuration

POST /web/api/v2.1/remote-scripts/guardrails/configuration

Updates or inserts (if record does not exist) a guardrails configuration

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Updates or inserts (if record does not exist) a guardrails configuration - response - data table
errors	Errors	false	array

Updates or inserts (if record does not exist) a guardrails configuration - response - data

Name	Description	Required	Value
success	Operation result	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Updates or inserts (if record does not exist) a guardrails configuration - body - data table

Updates or inserts (if record does not exist) a guardrails configuration - body - data

Name	Description	Required	Value
enabled	Whether guardrail is active	true	boolean
endpointsQuantity	Threshold for number of endpoints	true	integer
scopeId	Scope ID	true	string
scopeLevel	Scope level	true	enum
scriptTypes	List of script types that the guardrail relates to	false	string []

Deletes a specific guardrails configuration

DELETE /web/api/v2.1/remote-scripts/guardrails/configuration

Deletes a specific guardrails configuration

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Deletes a specific guardrails configuration - response - data table
errors	Errors	false	array

Deletes a specific guardrails configuration - response - data

Name	Description	Required	Value
success	Operation result	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Deletes a specific guardrails configuration - body - data table

Deletes a specific guardrails configuration - body - data

Name	Description	Required	Value
scopeId	Scope ID	true	string
scopeLevel	Scope level	true	enum

Check whether guardrail applies to an execution

POST /web/api/v2.1/remote-scripts/guardrails/check

Check whether guardrail applies to an execution

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Check whether guardrail applies to an execution - response - data table
errors	Errors	false	array

Check whether guardrail applies to an execution - response - data

Name	Description	Required	Value
requiresApproval	Whether the guardrail check requires approval	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Check whether guardrail applies to an execution - body - data table

Check whether guardrail applies to an execution - body - data

Name	Description	Required	Value
scriptId	Script id	true	string
agentIds	Agent ids	false	string []

Saved Searches

List saved searches

GET /sdl/v2/api/saved-searches

Retrieves all saved searches visible to the current user. Saved searches allow you to persist and quickly access frequently used search queries in Event Search. Use the `type` parameter to filter by PRIVATE (user-specific) or SHARED (visible to all users in the scope) searches.

Parameters

type	optional	Filter by search type. PRIVATE searches are visible only to you, while SHARED searches are visible to all users in your current scope. Defaults to PRIVATE if not specified.
------	----------	--

Response Messages

200 - List of saved searches retrieved successfully.

401 - Unauthorized. Authentication is required.

403 - Forbidden. User does not have permission to manage searches.

Response Schema

Name	Description	Required	Value
index	Zero-based position of the saved search in the list. This determines the display order.	true	integer

name	Display name of the saved search. Must be unique within the same type and scope.	true	string
type	Visibility type. PRIVATE searches are visible only to you, while SHARED searches are visible to all users in the same scope. Use the S1-Scope header to manage searches in different scopes.	true	enum
url	Event Search URL path with query parameters, typically starting with / events. This URL is used to navigate to the saved search.	true	string

Create or update saved searches

PUT /sdl/v2/api/saved-searches

Create or update multiple saved searches in a single request. This endpoint allows you to save up to 100 searches at once. When a search with the same name already exists in the target scope, the `duplicateStrategy` parameter controls the behavior: `NEW_ONLY` (default) skips duplicates, `REPLACE` overwrites existing searches, or `APPEND_SUFFIX` creates new searches with numeric suffixes (e.g., 'My Search (2)'). You can change the active scope using the `S1-Scope` header to manage `SHARED` searches in different scopes.

Note: A `teamToken` query parameter will be automatically added to each search URL if it is not already present. This token ensures the searches are scoped correctly.

Response Messages

- 200 - All searches were processed successfully. This includes searches that were saved, as well as searches that were skipped due to the duplicate strategy.
- 207 - Partial success. Some searches were saved successfully, but others failed validation or encountered errors. Check the results array for details on each search.
- 400 - Invalid request. The request body is malformed or contains invalid parameters.
- 401 - Authentication required. Please provide valid credentials.
- 403 - Permission denied. You do not have the required permissions to manage saved searches.
- 500 - Internal server error. All searches failed to save due to a system error.

Response Schema

Name	Description	Required	Value
results	Individual result for each search in the request, in the same order as submitted.	false	undefined []

Body Schema

Name	Description	Required	Value
duplicateStrategy	How to handle searches with names that already exist in the target scope. NEW_ONLY (default) skips duplicates and marks them as SKIPPED in the response. REPLACE overwrites existing searches with the same name. APPEND_SUFFIX creates new searches by adding numeric suffixes like ' (2)', ' (3)' to duplicate names.	false	enum
searches	List of saved searches to create or update. Maximum 100 searches per request.	false	undefined []

Delete saved searches

POST /sdl/v2/api/saved-searches/batch-delete

Delete multiple saved searches in a single request. You can delete up to 100 searches at once by providing their names and types. Each search name must be unique within its type (PRIVATE or SHARED) and scope. Use the `S1-Scope` header to target SHARED searches in specific scopes.

Response Messages

- 200 - All searches were deleted successfully.
- 207 - Partial success. Some searches were deleted successfully, but others were not found or encountered errors. Check the results array for details on each search.
- 400 - Invalid request. The request body is malformed or contains invalid parameters.
- 401 - Authentication required. Please provide valid credentials.
- 403 - Permission denied. You do not have the required permissions to delete saved searches.
- 500 - Internal server error. All searches failed to delete due to a system error.

Response Schema

Name	Description	Required	Value
results	Individual result for each search in the request, in the same order as submitted.	false	undefined []

Body Schema

Name	Description	Required	Value
searches	List of saved searches to delete, identified by name and type. Maximum 100 searches per request.	false	undefined []

Sentinel Deploy

Create Cred Group

POST /web/api/v2.1/ranger/cred-groups

Create a new Cred Group.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Cred Group - response - data table
errors	Errors	false	array

Create Cred Group - response - data

Name	Description	Required	Value
groupName	The cred group name	true	string
groupPassphrase	Encrypted passphrase with key unknown by the management	true	string
scopeId	Scope id	true	string
domain	The domain associated to this cred group	false	string
id	The cred group id	false	string
targetOs	The os type for this cred group	false	enum
totalDetails	The number of cred details in the group	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Cred Group - body - data table

Create Cred Group - body - data

Name	Description	Required	Value
groupName	The cred group name	true	string
groupPassphrase	Encrypted passphrase with key unknown by the management	true	string
scopeld	Scope id	true	string
domain	The domain associated to this cred group	false	string
targetOs	The os type for this cred group	false	enum

Get Cred groups

GET /web/api/v2.1/ranger/cred-groups

Get the data for each row in the Cred Groups table.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
groupname	optional	Group name being searched
groupnamelike	optional	Group name being searched
ids	optional	A list of ids to get
limit	optional	Limit number of returned items (1-1000). Example: "10".
siteids	optional	Single Site ID to filter by. Example: "225494730938493804".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.

sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
targetos	optional	The os type for this cred group. Example: "windows".
totaldetails__gt	optional	Get creds with total details greater than the supplied number

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Cred groups - response - pagination table
data	Response data	false	see Get Cred groups - response - data table
errors	Errors	false	array

Get Cred groups - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Cred groups - response - data

Name	Description	Required	Value
groupName	The cred group name	true	string
groupPassphrase	Encrypted passphrase with key unknown by the management	true	string
scopeId	Scope id	true	string
domain	The domain associated to this cred group	false	string
id	The cred group id	false	string
targetOs	The os type for this cred group	false	enum
totalDetails	The number of cred details in the group	false	integer

Delete Cred Group

DELETE /web/api/v2.1/ranger/cred-groups/{cred_group_id}

Delete cred group value.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

404 - Cred group not found.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Cred Group - response - data table
errors	Errors	false	array

Delete Cred Group - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Add cred details

POST /web/api/v2.1/ranger/cred-groups/details

Add cred details to a cred group.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Cred group not found.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Add cred details - response - data table
errors	Errors	false	array

Add cred details - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	false	see Add cred details - body - data table

Add cred details - body - data

Name	Description	Required	Value
credGroupid	Cred group id	true	string
details	The cred group details	false	see Add cred details - body - details table

Add cred details - body - details

Name	Description	Required	Value
credType	The type of the cred	true	string
encryptedCred	The encrypted creds	true	string
encryptedKey	A encrypted key for the creds	true	string
title	The title for the cred	true	string

Get Cred group details

GET /web/api/v2.1/ranger/cred-groups/details

Get the data for each row in the Cred Groups details table.

Parameters

accountids	optional	Single Account ID to filter by. Example: "225494730938493804".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
credgroupids	optional	A list of ids to get
credtypelike	optional	The type of the cred group
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
ids	optional	A list of ids to get
limit	optional	Limit number of returned items (1-1000). Example: "10".

siteids	optional	Single Site ID to filter by. Example: "225494730938493804".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
title	optional	Exact filter by title
titlelike	optional	Like filter by title

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Cred group details - response - pagination table
data	Response data	false	see Get Cred group details - response - data table
errors	Errors	false	array

Get Cred group details - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Cred group details - response - data

Name	Description	Required	Value
credType	The type of the cred group	true	string
title	The title for the cred	true	string
createdAt	The creation time	false	string
createdBy	The user that created the details	false	string
credGroupId	The cred group id	false	string
id	The detail id	false	string
updatedAt	The last update time	false	string
updatedBy	The user that updated the details	false	string

Delete Cred Group Detail

DELETE /web/api/v2.1/ranger/cred-groups/details/{detail_id}

Delete cred group detail value.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

404 - Cred group not found.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Cred Group Detail - response - data table
errors	Errors	false	array

Delete Cred Group Detail - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Update Cred Group Details

PUT /web/api/v2.1/ranger/cred-groups/details/{detail_id}

Update cred group values.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Cred group not found.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Cred Group Details - response - data table
errors	Errors	false	array

Update Cred Group Details - response - data

Name	Description	Required	Value
credType	The type of the cred group	true	string
title	The title for the cred	true	string
createdAt	The creation time	false	string
createdBy	The user that created the details	false	string
credGroupId	The cred group id	false	string
id	The detail id	false	string
updatedAt	The last update time	false	string
updatedBy	The user that updated the details	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Cred Group Details - body - data table

Update Cred Group Details - body - data

Name	Description	Required	Value
credType	The type of the cred	true	string
encryptedCred	The encrypted creds	true	string
encryptedKey	A encrypted key for the creds	true	string
title	The title for the cred	true	string

Service Users

Get Service Users

GET /web/api/v2.1/service-users

Get a list of service users.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
ids	optional	List of service user IDs to filter by. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".
query	optional	Full text search for fields: full_name, email, description
roleids	optional	List of rbac roles to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example:

		"225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

Response Messages

200 - List of service users retrieved successfully.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Service Users - response - pagination table
data	Response data	false	see Get Service Users - response - data table
errors	Errors	false	array

Get Service Users - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Service Users - response - data

Name	Description	Required	Value
scope	User Scope	true	enum
apiToken	Api token	false	see Get Service Users - response - apiToken table
createdAt	Created at	false	string
createdBy	Created by	false	see Get Service Users - response - createdBy table
description	Description	false	string
id	Id	false	string
lastActivation	Last activation	false	string
name	Name	false	string
scopeRoles	Roles of the scope user	false	see Get Service Users - response - scopeRoles table
updatedAt	Updated at	false	string
updatedBy	Updated by	false	see Get Service Users - response - updatedBy table

Get Service Users - response - apiToken

Name	Description	Required	Value
createdAt	Created at	false	string
expiresAt	Expires at	false	string

Get Service Users - response - createdBy

Name	Description	Required	Value
id	Id	false	string
name	Name	false	string

Get Service Users - response - scopeRoles

Name	Description	Required	Value
accountName	Scope name	true	string
name	Scope name	true	string
id	Scope ID	false	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the desired role name in this scope. Use role_id or role_name instead.	false	string []

Get Service Users - response - updatedBy

Name	Description	Required	Value
id	Id	false	string
name	Name	false	string

Create Service User

POST /web/api/v2.1/service-users

Create a new service user.

Response Messages

200 - Service User created successfully.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Not enough permissions to create service user.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Service User - response - data table
errors	Errors	false	array

Create Service User - response - data

Name	Description	Required	Value
scope	User Scope	true	enum
apiToken	Api token	false	see Create Service User - response - apiToken table
createdAt	Created at	false	string
createdBy	Created by	false	see Create Service User - response - createdBy table
description	Description	false	string
id	Id	false	string
lastActivation	Last activation	false	string
name	Name	false	string
scopeRoles	Roles of the scope user	false	see Create Service User - response - scopeRoles table
updatedAt	Updated at	false	string
updatedBy	Updated by	false	see Create Service User - response - updatedBy table

Create Service User - response - apiToken

Name	Description	Required	Value
createdAt	Created at	false	string
expiresAt	Expires at	false	string
value	Value	false	string

Create Service User - response - createdBy

Name	Description	Required	Value
id	Id	false	string
name	Name	false	string

Create Service User - response - scopeRoles

Name	Description	Required	Value
accountName	Scope name	true	string
name	Scope name	true	string
id	Scope ID	false	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the desired role name in this scope. Use role_id or role_name instead.	false	string []

Create Service User - response - updatedBy

Name	Description	Required	Value
id	Id	false	string
name	Name	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Service User - body - data table

Create Service User - body - data

Name	Description	Required	Value
expirationDate	Date when the generated token expires	true	string
name	Name of the service user	true	string
scope	User scope	true	enum
description	Description	false	string
forceLegacy	Temporary attribute for WA: If the flag is set to True the legacy token will be generated even if the auth_tokens global switch is turned on	false	boolean
scopeRoles	List of id and role id, id is mandatory for user in scope account/site. User in tenant (global) role does not need to provide an id.	false	see Create Service User - body - scopeRoles table

Create Service User - body - scopeRoles

Name	Description	Required	Value
id	Scope ID	false	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the desired role name in this scope. Use role_id or role_name instead.	false	string []

Get Service User

GET /web/api/v2.1/service-users/{service_user_id}

Get a specific service user by ID.

Response Messages

200 - Service user retrieved successfully.

401 - Unauthorized access - please sign in and retry.

404 - Service User not found.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Service User - response - data table
errors	Errors	false	array

Get Service User - response - data

Name	Description	Required	Value
scope	User Scope	true	enum
account	Relevant if the user is a site level user or single account	false	see Get Service User - response - account table
apiToken	Api token	false	see Get Service User - response - apiToken table
createdAt	Created at	false	string
createdBy	Created by	false	see Get Service User - response - createdBy table
description	Description	false	string
id	Id	false	string
lastActivation	Last activation	false	string
name	Name	false	string
scopeRoles	Roles of the scope user	false	see Get Service User - response - scopeRoles table
updatedAt	Updated at	false	string
updatedBy	Updated by	false	see Get Service User - response - updatedBy table

Get Service User - response - account

Name	Description	Required	Value
id	The id of the account	false	string
name	The name of the account	false	string

Get Service User - response - apiToken

Name	Description	Required	Value
createdAt	Created at	false	string
expiresAt	Expires at	false	string

Get Service User - response - createdBy

Name	Description	Required	Value
id	Id	false	string
name	Name	false	string

Get Service User - response - scopeRoles

Name	Description	Required	Value
accountName	Scope name	true	string
name	Scope name	true	string
id	Scope ID	false	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the desired role name in this scope. Use role_id or role_name instead.	false	string []

Get Service User - response - updatedBy

Name	Description	Required	Value
id	Id	false	string
name	Name	false	string

Update Service User

PUT /web/api/v2.1/service-users/{service_user_id}

Change properties of the service user with the given ID.

Response Messages

200 - Service User updated successfully.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Forbidden.

404 - Service User not found.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Service User - response - data table
errors	Errors	false	array

Update Service User - response - data

Name	Description	Required	Value
scope	User Scope	true	enum
apiToken	Api token	false	see Update Service User - response - apiToken table
createdAt	Created at	false	string
createdBy	Created by	false	see Update Service User - response - createdBy table
description	Description	false	string
id	Id	false	string
lastActivation	Last activation	false	string
name	Name	false	string
scopeRoles	Roles of the scope user	false	see Update Service User - response - scopeRoles table
updatedAt	Updated at	false	string
updatedBy	Updated by	false	see Update Service User - response - updatedBy table

Update Service User - response - apiToken

Name	Description	Required	Value
createdAt	Created at	false	string
expiresAt	Expires at	false	string

Update Service User - response - createdBy

Name	Description	Required	Value
id	Id	false	string
name	Name	false	string

Update Service User - response - scopeRoles

Name	Description	Required	Value
accountName	Scope name	true	string
name	Scope name	true	string
id	Scope ID	false	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the desired role name in this scope. Use role_id or role_name instead.	false	string []

Update Service User - response - updatedBy

Name	Description	Required	Value
id	Id	false	string
name	Name	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Service User - body - data table

Update Service User - body - data

Name	Description	Required	Value
description	Description	false	string
scope	User scope	false	enum
scopeRoles	List of id and role id, id is mandatory for user in scope account/site. User in tenant (global) role does not need to provide an id.	false	see Update Service User - body - scopeRoles table

Update Service User - body - scopeRoles

Name	Description	Required	Value
id	Scope ID	false	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the desired role name in this scope. Use role_id or role_name instead.	false	string []

Delete Service User

DELETE /web/api/v2.1/service-users/{service_user_id}

Delete a service user by ID.

Response Messages

200 - Service User deleted successfully.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Service User - response - data table
errors	Errors	false	array

Delete Service User - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Export Service Users

GET /web/api/v2.1/export/service-users

Export Service User data to a CSV, for Service Users that match the filter.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of service user IDs to filter by. Example: "225494730938493804,225494730938493915".
query	optional	Full text search for fields: full_name, email, description
roleids	optional	List of rbac roles to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Generate API Token for Service User

POST /web/api/v2.1/service-users/{service_user_id}/generate-api-token

Generate a new API token for a service user and revoke the existing API token.

Response Messages

200 - API token delivered to user.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Forbidden.

404 - Service User not found.

409 - API token creation conflict.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Generate API Token for Service User - response - data table
errors	Errors	false	array

Generate API Token for Service User - response - data

Name	Description	Required	Value
token	Service User's API token	true	string
createdAt	Created at	false	string
expiresAt	Expires at	false	string

Body Schema

Name	Description	Required	Value
data	Data	false	see Generate API Token for Service User - body - data table

Generate API Token for Service User - body - data

Name	Description	Required	Value
expirationDate	Date when the generated token expires	true	string

Bulk Delete Service Users

POST /web/api/v2.1/service-users/delete-service-users

Delete all service users that match the filter.

Response Messages

200 - Service Users deleted successfully.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Bulk Delete Service Users - response - data table
errors	Errors	false	array

Bulk Delete Service Users - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Bulk Delete Service Users - body - filter table
data	Data	false	see Bulk Delete Service Users - body - data table

Bulk Delete Service Users - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
ids	List of service user IDs to filter by	false	string []
query	Full text search for fields: full_name, email, description	false	string
roleIds	List of rbac roles to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Bulk Delete Service Users - body - data

Settings

Get SSO Settings

GET /web/api/v2.1/settings/sso

Get the Single Sign-On configuration for the given Sites (to get the IDs, run "sites") or Accounts ("accounts").

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get SSO Settings - response - data table
errors	Errors	false	array

Get SSO Settings - response - data

Name	Description	Required	Value
autoProvisioning	True if the user should be auto provisioned	false	boolean
defaultUserRole	The role name of the default role for a new user logging in via SSO for the first time	false	string
defaultUserRoleId	The role name of the default role for a new user logging in via SSO for the first time	false	string
domains	A list of domain names associated with the scope	false	string []
enabled	Indicates if SSO is enabled	false	boolean
idpCertName	Identity provider's certificate file name (If not provided, cert name and content will stay untouched in the DB)	false	string
idpEntityId	Identity provider's Entity ID (a.k.a. Issuer)	false	string
idpSsoUrl	The SSO URL of the Identity Provider (Login URL)	false	string
signRequest	Indicates if SAML Request Signing is enabled	false	boolean
spAcsUrl	Management console Assertion Consumer Service (ACS) URL. This is where IDP should send the authentication request	false	string
spEntityId	Identifier the Management console creates to dialogue with the SSO provider.	false	string
ssoElevatedSessionReauthType	Type of re-authentication used for session elevation.	false	enum
ssoElevatedSessionReauthTypeEnabled	Marks whether re-auth type choice should be available in SSO settings	false	boolean
ssoInheritableDomains	A dictionary of inheritable domains	false	object
ssoInheritDomainsFrom	Scope(s) to inherit domains from	false	string []

ssoPropagateDomainsToChildren	True if the domains should be propagated to children scopes	false	boolean
-------------------------------	---	-------	---------

Set SSO Settings

PUT /web/api/v2.1/settings/sso

Change the Single Sign-On configuration for the given Sites (to get the IDs, run "sites") or Accounts ("accounts").

The Management supports SAML 2.0 and will integrate with SAML 2.0 compliant SSO providers.

SentinelOne Technical Support can help you with issues related to the provider we tested: Okta. To use a different ID provider, see the provider documentation and support.

For requirements and best practices of Okta integration, see <https://support.sentinelone.com/hc/en-us/articles/360004195714>.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set SSO Settings - response - data table
errors	Errors	false	array

Set SSO Settings - response - data

Name	Description	Required	Value
autoProvisioning	True if the user should be auto provisioned	false	boolean
defaultUserRole	The role name of the default role for a new user logging in via SSO for the first time	false	string
defaultUserRoleId	The role name of the default role for a new user logging in via SSO for the first time	false	string
domains	A list of domain names associated with the scope	false	string []
enabled	Indicates if SSO is enabled	false	boolean
idpCertName	Identity provider's certificate file name (If not provided, cert name and content will stay untouched in the DB)	false	string
idpEntityId	Identity provider's Entity ID (a.k.a. Issuer)	false	string
idpSsoUrl	The SSO URL of the Identity Provider (Login URL)	false	string
signRequest	Indicates if SAML Request Signing is enabled	false	boolean
spAcsUrl	Management console Assertion Consumer Service (ACS) URL. This is where IDP should send the authentication request	false	string
spEntityId	Identifier the Management console creates to dialogue with the SSO provider.	false	string
ssoElevatedSessionReauthType	Type of re-authentication used for session elevation.	false	enum
ssoElevatedSessionReauthTypeEnabled	Marks whether re-auth type choice should be available in SSO settings	false	boolean
ssoInheritableDomains	A dictionary of inheritable domains	false	object
ssoInheritDomainsFrom	Scope(s) to inherit domains from	false	string []

ssoPropagateDomainsToChildren	True if the domains should be propagated to children scopes	false	boolean
-------------------------------	---	-------	---------

Body Schema

Name	Description	Required	Value
data	Data	true	see Set SSO Settings - body - data table
filter	Filter	true	see Set SSO Settings - body - filter table

Set SSO Settings - body - data

Name	Description	Required	Value
enabled	If True, other arguments must also be supplied, if False, other arguments stay untouched in the DB	true	boolean
autoProvisioning	True if the user should be auto provisioned	false	boolean
defaultUserRole	The name of the default role for a new user who logs in with SSO. Sending it without default_user_role_id will search only in global scope	false	string
defaultUserRoleid	The role name of the default role for a new user logging in via SSO for the first time	false	string
domains	A list of domain names associated with the scope	false	string []
idpCertContent	Identity provider's certificate file content (Base64 encoded string)	false	string
idpCertName	Identity provider's certificate file name (If not provided, cert name and content will stay untouched in the DB)	false	string
idpEntityId	Identity provider's Entity ID (a.k.a. Issuer)	false	string
idpSsoUrl	The SSO URL of the Identity Provider (Login URL)	false	string
signRequest	Indicates if SAML Request Signing is enabled	false	boolean
ssoElevatedSessionReauthType	Type of re-authentication used for session elevation.	false	enum
ssoInheritDomainsFrom	Scope(s) to inherit domains from	false	string []
ssoPropagateDomainsToChildren	True if the domains should be propagated to children scopes	false	boolean

Set SSO Settings - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Get SSO Service Provider Certificate

GET /web/api/v2.1/settings/sso/sp-cert

Get the Service Provider Certificate for the Single Sign-On configuration for the given scope.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get SSO Service Provider Certificate - response - data table
errors	Errors	false	array

Get SSO Service Provider Certificate - response - data

Name	Description	Required	Value
expiresAt	Certificate expires at	false	string
fileName	File name of the signing certificate used by the service provider to sign SAML requests	false	string
issuedAt	Certificate issued at	false	string
pem	Certificate in PEM format	false	string

Download SSO Service Provider Certificate

GET /web/api/v2.1/settings/sso/sp-cert/download

Download the Service Provider Certificate for the Single Sign-On configuration for the given scope.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Test SSO Settings

POST /web/api/v2.1/settings/sso/test

Test Single Sign-On settings.

Response Messages

200 - The url to redirect too.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Test SSO Settings - response - data table
errors	Errors	false	array

Test SSO Settings - response - data

Name	Description	Required	Value
redirectUrl	The url to redirect for test.	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Test SSO Settings - body - data table
filter	Filter	true	see Test SSO Settings - body - filter table

Test SSO Settings - body - data

Name	Description	Required	Value
enabled	If True, other arguments must also be supplied, if False, other arguments stay untouched in the DB	true	boolean
autoProvisioning	True if the user should be auto provisioned	false	boolean
defaultUserRole	The name of the default role for a new user who logs in with SSO. Sending it without default_user_role_id will search only in global scope	false	string
defaultUserRoleid	The role name of the default role for a new user logging in via SSO for the first time	false	string
domains	A list of domain names associated with the scope	false	string []
idpCertContent	Identity provider's certificate file content (Base64 encoded string)	false	string
idpCertName	Identity provider's certificate file name (If not provided, cert name and content will stay untouched in the DB)	false	string
idpEntityId	Identity provider's Entity ID (a.k.a. Issuer)	false	string
idpSsoUrl	The SSO URL of the Identity Provider (Login URL)	false	string
signRequest	Indicates if SAML Request Signing is enabled	false	boolean
ssoElevatedSessionReauthType	Type of re-authentication used for session elevation.	false	enum
ssoInheritDomainsFrom	Scope(s) to inherit domains from	false	string []
ssoPropagateDomainsToChildren	True if the domains should be propagated to children scopes	false	boolean

Test SSO Settings - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Get Notification Settings

GET /web/api/v2.1/settings/notifications

Get the notification settings for the given Sites (to get the IDs, run "settings") or Accounts ("accounts").

The response shows every possible notification and whether it is active and if so, for email or syslog or both. It also shows the ID string for each notification, which can be used in other commands.

Note: Each notification also shows "sms" which is deprecated.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Data retrieved successfully

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Notification Settings - response - data table
errors	Errors	false	array

Get Notification Settings - response - data

Name	Description	Required	Value
configurations	Configurations	false	see Get Notification Settings - response - configurations table
lastModified	Notifications last modified	false	see Get Notification Settings - response - lastModified table
notifications	Notifications categories	false	see Get Notification Settings - response - notifications table

Get Notification Settings - response - configurations

Name	Description	Required	Value
email	If not empty, email configuration is missing	false	string
sms	If not empty, sms configuration is missing	false	string
syslog	If not empty, syslog configuration is missing	false	string

Get Notification Settings - response - lastModified

Name	Description	Required	Value
updatedAt	Last Modified details level data	false	string
updatedBy	Last Modified details level data	false	string

Get Notification Settings - response - notifications

Name	Description	Required	Value
activedirectory	Category Items	false	object
administrative	Category Items	false	object
compromisedcredentialsprotection	Category Items	false	object
customrules	Category Items	false	object

devicecontrol	Category Items	false	object
endpointtagging	Category Items	false	object
firewallcontrol	Category Items	false	object
hyperautomation	Category Items	false	object
identityfaultauditlog	Category Items	false	object
identitypolicyconfiguration	Category Items	false	object
locations	Category Items	false	object
malware	Category Items	false	object
mitigation	Category Items	false	object
operations	Category Items	false	object
ranger	Category Items	false	object
remoteshell	Category Items	false	object
threatmanagement	Category Items	false	object
whitelistblacklist	Category Items	false	object

Set Notification Settings

PUT /web/api/v2.1/settings/notifications

Change the notifications for the given Sites (to get the IDs, run "settings") or Accounts ("accounts"). Best practice: Get the current settings (see Get Notification Settings) before you run this command.

BEST PRACTICE

Get the current settings (see Get Notification Settings) before you run this command.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set Notification Settings - response - data table
errors	Errors	false	array

Set Notification Settings - response - data

Name	Description	Required	Value
configurations	Configurations	false	see Set Notification Settings - response - configurations table
lastModified	Notifications last modified	false	see Set Notification Settings - response - lastModified table
notifications	Notifications categories	false	see Set Notification Settings - response - notifications table

Set Notification Settings - response - configurations

Name	Description	Required	Value
email	If not empty, email configuration is missing	false	string
sms	If not empty, sms configuration is missing	false	string
syslog	If not empty, syslog configuration is missing	false	string

Set Notification Settings - response - lastModified

Name	Description	Required	Value
updatedAt	Last Modified details level data	false	string
updatedBy	Last Modified details level data	false	string

Set Notification Settings - response - notifications

Name	Description	Required	Value
activedirectory	Category Items	false	object
administrative	Category Items	false	object
compromisedcredentialsprotection	Category Items	false	object
customrules	Category Items	false	object

devicecontrol	Category Items	false	object
endpointtagging	Category Items	false	object
firewallcontrol	Category Items	false	object
hyperautomation	Category Items	false	object
identityfaultauditlog	Category Items	false	object
identitypolicyconfiguration	Category Items	false	object
locations	Category Items	false	object
malware	Category Items	false	object
mitigation	Category Items	false	object
operations	Category Items	false	object
ranger	Category Items	false	object
remoteshell	Category Items	false	object
threatmanagement	Category Items	false	object
whitelistblacklist	Category Items	false	object

Body Schema

Name	Description	Required	Value
data	Data	true	see Set Notification Settings - body - data table
filter	Filter	true	see Set Notification Settings - body - filter table

Set Notification Settings - body - data

Name	Description	Required	Value
configurations	Configurations	false	see Set Notification Settings - body - configurations table
lastModified	Notifications last modified	false	see Set Notification Settings - body - lastModified table
notifications	Notifications categories	false	see Set Notification Settings - body - notifications table

Set Notification Settings - body - configurations

Name	Description	Required	Value
email	If not empty, email configuration is missing	false	string
sms	If not empty, sms configuration is missing	false	string
syslog	If not empty, syslog configuration is missing	false	string

Set Notification Settings - body - lastModified

Name	Description	Required	Value
updatedAt	Last Modified details level data	false	string
updatedBy	Last Modified details level data	false	string

Set Notification Settings - body - notifications

Name	Description	Required	Value
activedirectory	Category Items	false	object
administrative	Category Items	false	object
compromisedcredentialsprotection	Category Items	false	object
customrules	Category Items	false	object

devicecontrol	Category Items	false	object
endpointtagging	Category Items	false	object
firewallcontrol	Category Items	false	object
hyperautomation	Category Items	false	object
identityfaultauditlog	Category Items	false	object
identitypolicyconfiguration	Category Items	false	object
locations	Category Items	false	object
malware	Category Items	false	object
mitigation	Category Items	false	object
operations	Category Items	false	object
ranger	Category Items	false	object
remoteshell	Category Items	false	object
threatmanagement	Category Items	false	object
whitelistblacklist	Category Items	false	object

Set Notification Settings - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
sitelds	List of Site IDs to filter by	false	string []

Clear Pending Emails

POST /web/api/v2.1/settings/notifications/cancel-pending-emails

Clear (discard without sending) pending email notifications for the given Sites (to get the IDs, run "sites") or Accounts ("accounts").
When you set email recipients to get notifications for activities in the system, you can set too many, or in other ways cause issues that demand that the queue be cleared.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Clear Pending Emails - response - data table
errors	Errors	false	array

Clear Pending Emails - response - data

Name	Description	Required	Value
canceled	Canceled	true	integer

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Clear Pending Emails - body - filter table

Clear Pending Emails - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Get SMTP Settings

GET /web/api/v2.1/settings/smtp

Get the SMTP server configuration of the given Sites (to get the IDs, run "sites") or Accounts ("accounts"). The SMTP integration is required to send notifications by email.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Data retrieved successfully

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get SMTP Settings - response - data table
errors	Errors	false	array

Get SMTP Settings - response - data

Name	Description	Required	Value
enabled	SMTP service is enabled	false	boolean
encryption	SMTP service encryption type	false	enum
host	SMTP service host	false	string
inherits	True if site inherits SMTP settings from global scope, False if using custom settings.	false	boolean
noReplyEmail	SMTP service no-reply-email	false	string
password	SMTP service password. Required when creating new SMTP settings or updating host and/or port of the existing one.	false	string
port	SMTP service port	false	integer
username	SMTP service username	false	string

Set SMTP Settings

PUT /web/api/v2.1/settings/smtp

Change the SMTP server configuration for the given Sites or Accounts. Use this command to integrate a different SMTP server, which is required to send notifications by email.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set SMTP Settings - response - data table
errors	Errors	false	array

Set SMTP Settings - response - data

Name	Description	Required	Value
enabled	SMTP service is enabled	false	boolean
encryption	SMTP service encryption type	false	enum
host	SMTP service host	false	string
inherits	True if site inherits SMTP settings from global scope, False if using custom settings.	false	boolean
noReplyEmail	SMTP service no-reply-email	false	string
password	SMTP service password. Required when creating new SMTP settings or updating host and/or port of the existing one.	false	string
port	SMTP service port	false	integer
username	SMTP service username	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Set SMTP Settings - body - data table
filter	Filter	true	see Set SMTP Settings - body - filter table

Set SMTP Settings - body - data

Name	Description	Required	Value
enabled	SMTP service is enabled	false	boolean
encryption	SMTP service encryption type	false	enum
host	SMTP service host	false	string
inherits	True if site inherits SMTP settings from global scope, False if using custom settings.	false	boolean
noReplyEmail	SMTP service no-reply-email	false	string
password	SMTP service password. Required when creating new SMTP settings or updating host and/or port of the existing one.	false	string
port	SMTP service port	false	integer
username	SMTP service username	false	string

Set SMTP Settings - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Test SMTP Settings

POST /web/api/v2.1/settings/smtp/test

Test SMTP settings between the Management and the SMTP server. This integration is required if you use email notifications.

Response Messages

200 - Data retrieved successfully

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Test SMTP Settings - response - data table
errors	Errors	false	array

Test SMTP Settings - response - data

Name	Description	Required	Value
status	Status	true	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Test SMTP Settings - body - data table
filter	Filter	false	see Test SMTP Settings - body - filter table

Test SMTP Settings - body - data

Name	Description	Required	Value
enabled	SMTP service is enabled	false	boolean
encryption	SMTP service encryption type	false	enum
host	SMTP service host	false	string
inherits	True if site inherits SMTP settings from global scope, False if using custom settings.	false	boolean
noReplyEmail	SMTP service no-reply-email	false	string
password	SMTP service password. Required when testing new SMTP settings or testing update of host and/or port of the existing one.	false	string
port	SMTP service port	false	integer
username	SMTP service username	false	string

Test SMTP Settings - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Get Syslog Settings

GET /web/api/v2.1/settings/syslog

Get the configuration of the syslog server integrated with the given Sites (to get the IDs, run "sites") or Accounts ("accounts").

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example:

		"225494730938493804,225494730938493915".
--	--	--

Response Messages

- 200 - Data retrieved successfully
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.
- 403 - User is not allowed in this scope
- 404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Syslog Settings - response - data table
errors	Errors	false	array

Get Syslog Settings - response - data

Name	Description	Required	Value
clientCertContent	SysLog service client certificate content in Base64	false	string
clientCertName	SysLog service client certificate name	false	string
clientKeyContent	SysLog service client key content in Base64	false	string
clientKeyName	SysLog service client key name	false	string
enabled	SysLog service is enabled	false	boolean
format	SysLog service format	false	enum
host	SysLog service host	false	string
port	SysLog service port	false	integer
serverCertContent	SysLog service server certificate content in Base64	false	string
serverCertName	SysLog service server certificate name	false	string
ssl	SysLog service uses ssl	false	boolean
token	SysLog server token	false	string

Set Syslog Settings

PUT /web/api/v2.1/settings/syslog

Change the configuration of the syslog server of the given Sites (to get the IDs, run "sites") or Accounts ("accounts"). Use this command to send notifications to a different syslog server. Best Practice: Get Syslog Settings before you run this command.

BEST PRACTICE

Get Syslog Settings before you run this command.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set Syslog Settings - response - data table
errors	Errors	false	array

Set Syslog Settings - response - data

Name	Description	Required	Value
clientCertContent	SysLog service client certificate content in Base64	false	string
clientCertName	SysLog service client certificate name	false	string
clientKeyContent	SysLog service client key content in Base64	false	string
clientKeyName	SysLog service client key name	false	string
enabled	SysLog service is enabled	false	boolean
format	SysLog service format	false	enum
host	SysLog service host	false	string
port	SysLog service port	false	integer
serverCertContent	SysLog service server certificate content in Base64	false	string
serverCertName	SysLog service server certificate name	false	string
ssl	SysLog service uses ssl	false	boolean
token	SysLog server token	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Set Syslog Settings - body - data table
filter	Filter	true	see Set Syslog Settings - body - filter table

Set Syslog Settings - body - data

Name	Description	Required	Value
clientCertContent	SysLog service client certificate content in Base64	false	string
clientCertName	SysLog service client certificate name	false	string
clientKeyContent	SysLog service client key content in Base64	false	string
clientKeyName	SysLog service client key name	false	string
enabled	SysLog service is enabled	false	boolean
format	SysLog service format	false	enum
host	SysLog service host	false	string
port	SysLog service port	false	integer
serverCertContent	SysLog service server certificate content in Base64	false	string
serverCertName	SysLog service server certificate name	false	string
ssl	SysLog service uses ssl	false	boolean
token	SysLog server token	false	string

Set Syslog Settings - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
sitelds	List of Site IDs to filter by	false	string []

Test Syslog Settings

POST /web/api/v2.1/settings/syslog/test

Test Syslog settings. The Management tests the connection to the Syslog server.

Response Messages

200 - Data retrieved successfully

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Test Syslog Settings - response - data table
errors	Errors	false	array

Test Syslog Settings - response - data

Name	Description	Required	Value
status	Status	true	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Test Syslog Settings - body - data table
filter	Filter	true	see Test Syslog Settings - body - filter table

Test Syslog Settings - body - data

Name	Description	Required	Value
clientCertContent	SysLog service client certificate content in Base64	false	string
clientCertName	SysLog service client certificate name	false	string
clientKeyContent	SysLog service client key content in Base64	false	string
clientKeyName	SysLog service client key name	false	string
enabled	SysLog service is enabled	false	boolean
format	SysLog service format	false	enum
host	SysLog service host	false	string
port	SysLog service port	false	integer
serverCertContent	SysLog service server certificate content in Base64	false	string
serverCertName	SysLog service server certificate name	false	string
ssl	SysLog service uses ssl	false	boolean
token	SysLog server token	false	string

Test Syslog Settings - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Get SMS Settings

GET /web/api/v2.1/settings/sms

[DEPRECATED] Gets the site's SMS settings.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Data retrieved successfully

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get SMS Settings - response - data table
errors	Errors	false	array

Get SMS Settings - response - data

Name	Description	Required	Value
enabled	SMS service is enabled	false	boolean

Set SMS Settings

PUT /web/api/v2.1/settings/sms

[DEPRECATED] Set SMS settings.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set SMS Settings - response - data table
errors	Errors	false	array

Set SMS Settings - response - data

Name	Description	Required	Value
enabled	SMS service is enabled	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Set SMS Settings - body - data table
filter	Filter	true	see Set SMS Settings - body - filter table

Set SMS Settings - body - data

Name	Description	Required	Value
enabled	SMS service is enabled	false	boolean

Set SMS Settings - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Get Notification Recipients

GET /web/api/v2.1/settings/recipients

Get the emails that are configured to receive notifications.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
email	optional	Email
name	optional	Name
query	optional	Full text search for fields: name, email, sms
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
sms	optional	Sms

Response Messages

200 - Data retrieved successfully

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Notification Recipients - response - data table
errors	Errors	false	array

Get Notification Recipients - response - data

Name	Description	Required	Value
recipients	Notification Recipients	false	see Get Notification Recipients - response - recipients table

Get Notification Recipients - response - recipients

Name	Description	Required	Value
createdAt	Creation Timestamp	false	string
email	Notification Recipients Email	false	string
id	Notification Recipients Id	false	string
name	Notification Recipients Email	false	string
sms	Notification Recipients SMS	false	string
updatedAt	Update Timestamp	false	string

Set Notification Recipients

PUT /web/api/v2.1/settings/recipients

Set the emails of recipients to get notifications.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set Notification Recipients - response - data table
errors	Errors	false	array

Set Notification Recipients - response - data

Name	Description	Required	Value
createdAt	Creation Timestamp	false	string
email	Notification Recipients Email	false	string
id	Notification Recipients Id	false	string
name	Notification Recipients Email	false	string
sms	Notification Recipients SMS	false	string
updatedAt	Update Timestamp	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Set Notification Recipients - body - data table
filter	Filter	true	see Set Notification Recipients - body - filter table

Set Notification Recipients - body - data

Name	Description	Required	Value
createdAt	Creation Timestamp	false	string
email	Notification Recipients Email	false	string
id	Notification Recipients Id	false	string
name	Notification Recipients Email	false	string
sms	Notification Recipients SMS	false	string
updatedAt	Update Timestamp	false	string

Set Notification Recipients - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Delete Notification Recipient

DELETE /web/api/v2.1/settings/recipients/{recipient_id}

Delete a notification recipient by ID. To get the IDs of recipients, run "recipients" (see Get Notification Recipients).

Response Messages

200 - Recipient deleted successfully.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Delete Notification Recipient - response - data table
errors	Errors	false	array

Delete Notification Recipient - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Get AD Settings

GET /web/api/v2.1/settings/active-directory

Get the Global Active Directory settings.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Data retrieved successfully

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get AD Settings - response - data table
errors	Errors	false	array

Get AD Settings - response - data

Name	Description	Required	Value
enabled	Is AD service enabled?	false	boolean
host	Active Directory server address	false	string
port	Active Directory server port	false	integer
rootDn	Root Domain Name of Active Directory	false	string
ssl	Should we speak to the Active Directory server using SSL?	false	boolean
username	Username used to log in to active directory	false	string

Set AD Settings

PUT /web/api/v2.1/settings/active-directory

Update the Global Active Directory settings.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set AD Settings - response - data table
errors	Errors	false	array

Set AD Settings - response - data

Name	Description	Required	Value
enabled	Is AD service enabled?	false	boolean
host	Active Directory server address	false	string
port	Active Directory server port	false	integer
rootDn	Root Domain Name of Active Directory	false	string
ssl	Should we speak to the Active Directory server using SSL?	false	boolean
username	Username used to log in to active directory	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Set AD Settings - body - data table

Set AD Settings - body - data

Name	Description	Required	Value
enabled	Is AD service enabled?	false	boolean
host	Active Directory server address	false	string
password	Password used to log in to active directory	false	string
port	Active Directory server port	false	integer
rootDn	Root Domain Name of Active Directory	false	string
ssl	Should we speak to the Active Directory server using SSL?	false	boolean
username	Username used to log in to active directory	false	string

Test AD Settings

POST /web/api/v2.1/settings/active-directory/test

Test Active Directory settings.

Response Messages

200 - Data retrieved successfully

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Test AD Settings - response - data table
errors	Errors	false	array

Test AD Settings - response - data

Name	Description	Required	Value
status	Status	true	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Test AD Settings - body - data table

Test AD Settings - body - data

Name	Description	Required	Value
enabled	Is AD service enabled?	false	boolean
host	Active Directory server address	false	string
password	Password used to log in to active directory	false	string
port	Active Directory server port	false	integer
rootDn	Root Domain Name of Active Directory	false	string
ssl	Should we speak to the Active Directory server using SSL?	false	boolean
username	Username used to log in to active directory	false	string

Get AD FQDNs

GET /web/api/v2.1/settings/active-directory/scope-mapping

Get the map of Active Directory FQDNs to user roles of the given Sites (use "sites" to get IDs) or Accounts ("accounts").

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Data retrieved successfully

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get AD FQDNs - response - data table
errors	Errors	false	array

Get AD FQDNs - response - data

Name	Description	Required	Value
admin	Admin	false	string []
viewer	Viewer	false	string []

Set AD FQDNs

PUT /web/api/v2.1/settings/active-directory/scope-mapping

Update the Active Directory FQDNs of a Site or Account.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set AD FQDNs - response - data table
errors	Errors	false	array

Set AD FQDNs - response - data

Name	Description	Required	Value
admin	Admin	false	string []
viewer	Viewer	false	string []

Body Schema

Name	Description	Required	Value
data	Data	true	see Set AD FQDNs - body - data table
filter	Filter	true	see Set AD FQDNs - body - filter table

Set AD FQDNs - body - data

Name	Description	Required	Value
admin	Admin	false	string []
viewer	Viewer	false	string []

Set AD FQDNs - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Get Microsoft Settings

GET /web/api/v2.1/settings/microsoft

[DEPRECATED] Gets the Microsoft settings of the Sites or Accounts.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Data retrieved successfully

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Microsoft Settings - response - data table
errors	Errors	false	array

Get Microsoft Settings - response - data

Name	Description	Required	Value
enabled	Microsoft service is enabled	false	boolean
expiryDate	The expiry time of the given url	false	string
inherits	True if site inherits SMTP settings from global scope, False if using custom settings.	false	boolean
url	URL used to authenticate with microsoft	false	string

Set Microsoft Settings

PUT /web/api/v2.1/settings/microsoft

[DEPRECATED] Update Microsoft settings for the given Sites or Accounts.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set Microsoft Settings - response - data table
errors	Errors	false	array

Set Microsoft Settings - response - data

Name	Description	Required	Value
enabled	Microsoft service is enabled	false	boolean
expiryDate	The expiry time of the given url	false	string
inherits	True if site inherits SMTP settings from global scope, False if using custom settings.	false	boolean
url	URL used to authenticate with microsoft	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Set Microsoft Settings - body - data table
filter	Filter	true	see Set Microsoft Settings - body - filter table

Set Microsoft Settings - body - data

Name	Description	Required	Value
enabled	Microsoft service is enabled	false	boolean
expiryDate	The expiry time of the given url	false	string
inherits	True if site inherits SMTP settings from global scope, False if using custom settings.	false	boolean
url	URL used to authenticate with microsoft	false	string

Set Microsoft Settings - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Test Microsoft Settings

POST /web/api/v2.1/settings/microsoft/test

[DEPRECATED] Test Microsoft settings.

Response Messages

200 - Data retrieved successfully

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Scope does not exist

Response Schema

Name	Description	Required	Value
data	Response data	false	see Test Microsoft Settings - response - data table
errors	Errors	false	array

Test Microsoft Settings - response - data

Name	Description	Required	Value
reason	Reason for unsuccessful call	false	string
success	True if succeeded	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Test Microsoft Settings - body - data table
filter	Filter	true	see Test Microsoft Settings - body - filter table

Test Microsoft Settings - body - data

Name	Description	Required	Value
enabled	Microsoft service is enabled	false	boolean
expiryDate	The expiry time of the given url	false	string
inherits	True if site inherits SMTP settings from global scope, False if using custom settings.	false	boolean
url	URL used to authenticate with microsoft	false	string

Test Microsoft Settings - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Sites

Get Sites

GET /web/api/v2.1/sites

Get the Sites that match the filters.

The response includes the IDs of Sites, which you can use in other commands.

Parameters

accountid	optional	Account id. Example: "225494730938493804".
accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
accountname__contain	optional	Free-text filter by account name (supports multiple values)

s		
activelicenses	optional	Active licenses
adminonly	optional	[DEPRECATED] Show sites the user has Admin privileges to
availablemovesites	optional	Only return sites the user can move agents to
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat	optional	Timestamp of site creation. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
description	optional	The description for the Site
description__contains	optional	Free-text filter by site description (supports multiple values)
expiration	optional	Expiration. Example: "2018-02-27T04:49:26.257525Z".
externalid	optional	Id in a CRM external system
features	optional	If sent return only sites that support this features. Example: "firewall-control".
healthstatus	optional	Health status
isdefault	optional	Is default
limit	optional	Limit number of returned items (1-1000). Example: "10".
module	optional	Module. Example: "star,rso".
name	optional	Name. Example: "My Site".
name__contains	optional	Free-text filter by site name (supports multiple values)
query	optional	Full text search for fields: name, account_name, description. (Note: on single-account consoles account name will not be matched)
registrationtoken	optional	Registration token. Example: "eyJ1cmwiOiAiaHR0cHM6Ly9jb25zb2xlLnNlbnRpbmVsb25lLm5ldCIsICJzaXRlX2tleSI6IClwNzhkYjliMWUyOTA1Y2NhIn0=".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
sitetype	optional	Site type. Example: "Trial".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".

skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sku	optional	Sku. Example: "core".
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
state	optional	Site state. Example: "active".
states	optional	List of states to filter
statesnin	optional	List of states to not filter
suite	optional	[DEPRECATED] Use sku instead. Example: "Core".
totallicenses	optional	Total licenses
updatedat	optional	Timestamp of last update. Example: "2018-02-27T04:49:26.257525Z".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Sites - response - pagination table
data	Response data	false	see Get Sites - response - data table
errors	Errors	false	array

Get Sites - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Sites - response - data

Name	Description	Required	Value
allSites	All sites	false	see Get Sites - response - allSites table
sites	Sites	false	see Get Sites - response - sites table

Get Sites - response - allSites

Name	Description	Required	Value
activeLicenses	Active licenses	false	integer
totalLicenses	Total licenses	false	integer

Get Sites - response - sites

Name	Description	Required	Value
accountId	Account id	false	string
accountName	Account name	false	string
activeLicenses	Number of active licenses for the site	false	integer
createdAt	Timestamp of site creation	false	string
creator	Full name of the creating user	false	string

creatorId	Id of the creating user	false	string
description	The user-defined description for the Site	false	string
expiration	Expiration	false	string
externalId	Id of CRM external system	false	string
healthStatus	Obsolete. Always true	false	boolean
id	Site ID	false	string
inheritAccountExpiration	Inherit account expiration	false	boolean
irFields	Ir fields	false	see Get Sites - response - irFields table
isDefault	Is default	false	boolean
licenses	The site licenses	false	see Get Sites - response - licenses table
name	Name	false	string
promptFields	Prompt fields	false	see Get Sites - response - promptFields table
registrationToken	[DEPRECATED] token generation in dedicated endpoint - /sites/<site_id>/token	false	
siteType	Site type	false	string
sku	[DEPRECATED] The sku of product features active for this site	false	enum
state	Site state	false	enum
suite	[DEPRECATED] Use sku instead	false	enum
totalLicenses	Total licenses	false	integer
unlimitedExpiration	The site does not expire	false	boolean
unlimitedLicenses	Site licenses unlimited	false	boolean
updatedAt	Timestamp of last update	false	string
usageType	Usage type	false	string

Get Sites - response - irFields

Name	Description	Required	Value
companyName	The customer's company name	true	string
contactEmail	Business email of the customer contact. Must not match the IR	true	string

	partner domain, the submitter's own domain, or a free/personal email provider (e.g. Gmail, Yahoo, Hotmail)		
contactFirstName	First name of the customer contact	true	string
contactLastName	Last name of the customer contact	true	string
country	Country of the customer	true	string
industry	Industry vertical of the customer	true	enum
numberOfEmployeesEndpoints	Estimated number of employees or endpoints at the customer	true	integer
city	City of the customer	false	string
postal	Postal / ZIP code of the customer	false	string
region	State or region within the country	false	string

Get Sites - response - licenses

Name	Description	Required	Value
bundles	The licenses Bundles	false	see Get Sites - response - bundles table
modules	The licenses Add-ons	false	see Get Sites - response - modules table
settings	The licenses Settings	false	see Get Sites - response - settings table

Get Sites - response - bundles

Name	Description	Required	Value
displayName	The Bundle display name	false	string
majorVersion	The Bundle major version	false	integer
minorVersion	The Bundle minor version	false	integer
name	The Bundle internal api name	false	string
surfaces	The Surfaces in the Bundle	false	see Get Sites - response - surfaces table
totalSurfaces	The total number of Surfaces in this Bundle. -1 indicates unlimited count.	false	integer

Get Sites - response - surfaces

Name	Description	Required	Value
count	The Surface count. -1 indicates unlimited count	false	integer
name	The Surface name.	false	string

Get Sites - response - modules

Name	Description	Required	Value
displayName	The Add-on display name	false	string
majorVersion	The Add-on major version	false	integer
name	The Add-on internal api name	false	string

Get Sites - response - settings

Name	Description	Required	Value
displayName	[DEPRECATED] The Setting display name	false	string
groupName	The Setting group name	false	
setting	The Setting display name	false	
settingGroup	[DEPRECATED] The Setting group name	false	string
settingGroupDisplayName	The Setting group display name	false	string

Get Sites - response - promptFields

Name	Description	Required	Value
promptRegion	Region associated with the prompt	false	enum
promptTenantName	Tenant name associated with the prompt	false	string
promptUserEmail	Email of the user associated with the prompt	false	string
promptUserName	Name of the user associated with the	false	string

	prompt		
--	--------	--	--

Create Site

POST /web/api/v2.1/sites

Create a Site. This requires an Admin role with a Global scope or Account scope that has permissions over the Account to which the Site will belong. You must have a license for a new Site.
In the body of this request, include the policy.

Response Messages

- 200 - Success
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Site - response - data table
errors	Errors	false	array

Create Site - response - data

Name	Description	Required	Value
accountId	Account id	false	string
accountName	Account name	false	string
activeLicenses	Number of active licenses for the site	false	integer
createdAt	Timestamp of site creation	false	string
creator	Full name of the creating user	false	string
creatorId	Id of the creating user	false	string
description	The user-defined description for the Site	false	string
expiration	Expiration	false	string
externalId	Id of CRM external system	false	string
healthStatus	Obsolete. Always true	false	boolean
id	Site ID	false	string
inheritAccountExpiration	Inherit account expiration	false	boolean
irFields	Ir fields	false	see Create Site - response - irFields table
isDefault	Is default	false	boolean
licenses	The site licenses	false	see Create Site - response - licenses table
name	Name	false	string
promptFields	Prompt fields	false	see Create Site - response - promptFields table
registrationToken	[DEPRECATED] token generation in dedicated endpoint - /sites/<site_id>/token	false	
siteType	Site type	false	string
sku	[DEPRECATED] The sku of product features active for this site	false	enum
state	Site state	false	enum
suite	[DEPRECATED] Use sku instead	false	enum
totalLicenses	Total licenses	false	integer
unlimitedExpiration	True if the Site has no expiration date	false	
unlimitedLicenses	True if the Site has unlimited licenses	false	boolean

updatedAt	Timestamp of last update	false	string
usageType	Usage type	false	string

Create Site - response - irFields

Name	Description	Required	Value
companyName	The customer's company name	true	string
contactEmail	Business email of the customer contact. Must not match the IR partner domain, the submitter's own domain, or a free/personal email provider (e.g. Gmail, Yahoo, Hotmail)	true	string
contactFirstName	First name of the customer contact	true	string
contactLastName	Last name of the customer contact	true	string
country	Country of the customer	true	string
industry	Industry vertical of the customer	true	enum
numberOfEmployeesEndpoints	Estimated number of employees or endpoints at the customer	true	integer
city	City of the customer	false	string
postal	Postal / ZIP code of the customer	false	string
region	State or region within the country	false	string

Create Site - response - licenses

Name	Description	Required	Value
bundles	The licenses Bundles	false	see Create Site - response - bundles table
modules	The licenses Add-ons	false	see Create Site - response - modules table
settings	The licenses Settings	false	see Create Site - response - settings table

Create Site - response - bundles

Name	Description	Required	Value
------	-------------	----------	-------

displayName	The Bundle display name	false	string
majorVersion	The Bundle major version	false	integer
minorVersion	The Bundle minor version	false	integer
name	The Bundle internal api name	false	string
surfaces	The Surfaces in the Bundle	false	see Create Site - response - surfaces table
totalSurfaces	The total number of Surfaces in this Bundle. -1 indicates unlimited count.	false	integer

Create Site - response - surfaces

Name	Description	Required	Value
count	The Surface count. -1 indicates unlimited count	false	integer
name	The Surface name.	false	string

Create Site - response - modules

Name	Description	Required	Value
displayName	The Add-on display name	false	string
majorVersion	The Add-on major version	false	integer
name	The Add-on internal api name	false	string

Create Site - response - settings

Name	Description	Required	Value
displayName	[DEPRECATED] The Setting display name	false	string
groupName	The Setting group name	false	
setting	The Setting display name	false	
settingGroup	[DEPRECATED] The Setting group name	false	string
settingGroupDisplayName	The Setting group display name	false	string

Create Site - response - promptFields

Name	Description	Required	Value
promptRegion	Region associated with the prompt	false	enum
promptTenantName	Tenant name associated with the prompt	false	string
promptUserEmail	Email of the user associated with the prompt	false	string
promptUserName	Name of the user associated with the prompt	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Site - body - data table

Create Site - body - data

Name	Description	Required	Value
name	Name	true	string
accountId	Associated account. Leave empty in single-account management consoles.	false	string
accountSfId		false	string
description	The user-defined description for the Site	false	string
expiration	Expiration	false	string
externalId	Id of CRM external system	false	string
inheritAccountExpiration	True, if expiration should be inherited from account	false	boolean
inherits	True if the policy is inherited from Tenant, False if the site has its own edited policy	false	boolean
irFields	IR related fields	false	see Create Site - body - irFields table
licenses	The license configuration for the Site	false	see Create Site - body - licenses table
policy	Policy is mandatory if inherits is false, else it will be ignored.	false	see Create Site - body - policy table
promptFields	Prompt related fields	false	see Create Site - body - promptFields table
siteType	Site types	false	enum
sku	[DEPRECATED] Use licenses instead	false	enum
suite	[DEPRECATED] Use licenses instead	false	enum
totalLicenses	Total licenses	false	integer
unlimitedExpiration	Is expiration unlimited, if not expiration should be supplied	false	boolean
unlimitedLicenses	Is the site unlimited, if not then total_licenses must be supplied	false	boolean
usageType	Usage type	false	enum

Create Site - body - irFields

Name	Description	Required	Value
companyName	The customer's company name	true	string
contactEmail	Business email of the customer contact. Must not match the IR partner domain, the submitter's own domain, or a free/personal email provider (e.g. Gmail, Yahoo, Hotmail)	true	string
contactFirstName	First name of the customer contact	true	string
contactLastName	Last name of the customer contact	true	string
country	Country of the customer	true	string
industry	Industry vertical of the customer	true	enum
numberOfEmployeesEndpoints	Estimated number of employees or endpoints at the customer	true	integer
city	City of the customer	false	string
postal	Postal / ZIP code of the customer	false	string
region	State or region within the country	false	string

Create Site - body - licenses

Name	Description	Required	Value
bundles	The list of Bundles selected	false	see Create Site - body - bundles table
modules	The list of Add-ons selected	false	see Create Site - body - modules table

Create Site - body - bundles

Name	Description	Required	Value
name		true	string
majorVersion		false	integer
surfaces		false	see Create Site - body - surfaces table

Create Site - body - surfaces

Name	Description	Required	Value
name		true	string
count	The number of licenses per Surface. -1 indicates unlimited count.	false	integer

Create Site - body - modules

Name	Description	Required	Value
name		true	string

Create Site - body - policy

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Create Site - body - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Create Site - body - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string

cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Create Site - body - dvAttributesPerEventType table
engines	The engines statuses	false	see Create Site - body - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Create Site - body - forensicsAutoTriggering table
identityConfigurationSettings	Identity configuration	false	see Create Site - body - identityConfigurationSettings table
identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Create Site - body - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean

networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Create Site - body - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Create Site - body - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean
researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first registration	false	boolean
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Create Site - body - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean

maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Create Site - body - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Create Site - body - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Create Site - body - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Create Site - body - behavioralIndicators table
commandScripts	Command scripts event	false	see Create Site - body - commandScripts table
crossProcess	Cross process event	false	see Create Site - body - crossProcess table
dataMasking	Data masking	false	see Create Site - body - dataMasking table

dllModuleLoad	DLL module load event	false	see Create Site - body - dllModuleLoad table
dns	Network event - DNS	false	see Create Site - body - dns table
driver	Driver	false	see Create Site - body - driver table
externalDeviceActivity	External Device Activity	false	see Create Site - body - externalDeviceActivity table
file	File event	false	see Create Site - body - file table
ip	Network event - IP	false	see Create Site - body - ip table
login	User login/logout event	false	see Create Site - body - login table
namedPipe	Named Pipe	false	see Create Site - body - namedPipe table
namedPipeExtended	Named Pipe Extended	false	see Create Site - body - namedPipeExtended table
openDirectoryActivity	Open Directory Activity	false	see Create Site - body - openDirectoryActivity table
process	Process event	false	see Create Site - body - process table
profileActivity	Profile Activity	false	see Create Site - body - profileActivity table
registry	Registry event	false	see Create Site - body - registry table
scheduledTask	Scheduled task event	false	see Create Site - body - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Create Site - body - smartFileMonitoring table
url	URL Actions event	false	see Create Site - body - url table
userSubstitution	User Substitution	false	see Create Site - body - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Create Site - body - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Create Site - body - windowsEventLogsExtended table

Create Site - body - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Create Site - body - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Create Site - body - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Create Site - body - crossProcess

Name	Description	Required	Value
dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Create Site - body - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Create Site - body - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Create Site - body - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Create Site - body - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Create Site - body - externalDeviceActivity

Name	Description	Required	Value
dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Create Site - body - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Create Site - body - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Create Site - body - login

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Create Site - body - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean
dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean

Create Site - body - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Create Site - body - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean

r			
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean
dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean

Create Site - body - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Create Site - body - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Create Site - body - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean

dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Create Site - body - scheduledTask

Name	Description	Required	Value
dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Create Site - body - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Create Site - body - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Create Site - body - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean

dvEventTypeSudo	sudo Event Type	false	boolean
-----------------	-----------------	-------	---------

Create Site - body - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Create Site - body - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Create Site - body - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum

remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Create Site - body - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean
macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Create Site - body - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Create Site - body - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean
externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Create Site - body - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection	false	integer

	process		
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Create Site - body - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Create Site - body - promptFields

Name	Description	Required	Value
promptRegion	Region associated with the prompt	false	enum

promptTenantName	Tenant name associated with the prompt	false	string
promptUserEmail	Email of the user associated with the prompt	false	string
promptUserName	Name of the user associated with the prompt	false	string

Export Sites

GET /web/api/v2.1/export/sites

Export Sites data to a CSV, for Sites that match the filter.

Parameters

accountid	optional	Account id. Example: "225494730938493804".
accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
accountname__contains	optional	Free-text filter by account name (supports multiple values)
activelicenses	optional	Active licenses
adminonly	optional	[DEPRECATED] Show sites the user has Admin privileges to
availablemovesites	optional	Only return sites the user can move agents to
createdat	optional	Timestamp of site creation. Example: "2018-02-27T04:49:26.257525Z".
description	optional	The description for the Site
description__contains	optional	Free-text filter by site description (supports multiple values)
expiration	optional	Expiration. Example: "2018-02-27T04:49:26.257525Z".
externalid	optional	Id in a CRM external system
features	optional	If sent return only sites that support this features. Example: "firewall-control".
healthstatus	optional	Health status
isdefault	optional	Is default
module	optional	Module. Example: "star,rso".
name	optional	Name. Example: "My Site".

name__contains	optional	Free-text filter by site name (supports multiple values)
query	optional	Full text search for fields: name, account_name, description. (Note: on single-account consoles account name will not be matched)
registrationtoken	optional	Registration token. Example: "eyJ1cmwiOiAiaHR0cHM6Ly9jb25zb2xlnNlbnRpbmVsb25lLm5ldCIsICJzaXRlX2tleSI6IClwNzhkYjliMWUyOTA1Y2NhIn0=".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
sitetype	optional	Site type. Example: "Trial".
sku	optional	Sku. Example: "core".
state	optional	Site state. Example: "active".
states	optional	List of states to filter
statesnin	optional	List of states to not filter
suite	optional	[DEPRECATED] Use sku instead. Example: "Core".
totallicenses	optional	Total licenses
updatedat	optional	Timestamp of last update. Example: "2018-02-27T04:49:26.257525Z".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Get Site by ID

GET /web/api/v2.1/sites/{site_id}

Get the data of the Site of the ID. To get the ID, run "sites".

The response shows the Site expiration date, SKU, licenses (total and active), token, Account name and ID, who and when it was created and changed, and its status.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

404 - Site not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Site by ID - response - data table
errors	Errors	false	array

Get Site by ID - response - data

Name	Description	Required	Value
accountId	Account id	false	string
accountName	Account name	false	string
activeLicenses	Number of active licenses for the site	false	integer
createdAt	Timestamp of site creation	false	string
creator	Full name of the creating user	false	string
creatorId	Id of the creating user	false	string
description	The user-defined description for the Site	false	string
expiration	Expiration	false	string
externalId	Id of CRM external system	false	string
healthStatus	Obsolete. Always true	false	boolean
id	Site ID	false	string
inheritAccountExpiration	Inherit account expiration	false	boolean
irFields	Ir fields	false	see Get Site by ID - response - irFields table
isDefault	Is default	false	boolean
licenses	The site licenses	false	see Get Site by ID - response - licenses table
name	Name	false	string
promptFields	Prompt fields	false	see Get Site by ID - response - promptFields table
registrationToken	[DEPRECATED] token generation in dedicated endpoint - /sites/<site_id>/token	false	
siteType	Site type	false	string
sku	[DEPRECATED] The sku of product features active for this site	false	enum
state	Site state	false	enum
suite	[DEPRECATED] Use sku instead	false	enum
totalLicenses	Total licenses	false	integer
unlimitedExpiration	The site does not expire	false	boolean
unlimitedLicenses	Site licenses unlimited	false	boolean

updatedAt	Timestamp of last update	false	string
usageType	Usage type	false	string

Get Site by ID - response - irFields

Name	Description	Required	Value
companyName	The customer's company name	true	string
contactEmail	Business email of the customer contact. Must not match the IR partner domain, the submitter's own domain, or a free/personal email provider (e.g. Gmail, Yahoo, Hotmail)	true	string
contactFirstName	First name of the customer contact	true	string
contactLastName	Last name of the customer contact	true	string
country	Country of the customer	true	string
industry	Industry vertical of the customer	true	enum
numberOfEmployeesEndpoints	Estimated number of employees or endpoints at the customer	true	integer
city	City of the customer	false	string
postal	Postal / ZIP code of the customer	false	string
region	State or region within the country	false	string

Get Site by ID - response - licenses

Name	Description	Required	Value
bundles	The licenses Bundles	false	see Get Site by ID - response - bundles table
modules	The licenses Add-ons	false	see Get Site by ID - response - modules table
settings	The licenses Settings	false	see Get Site by ID - response - settings table

Get Site by ID - response - bundles

Name	Description	Required	Value
------	-------------	----------	-------

displayName	The Bundle display name	false	string
majorVersion	The Bundle major version	false	integer
minorVersion	The Bundle minor version	false	integer
name	The Bundle internal api name	false	string
surfaces	The Surfaces in the Bundle	false	see Get Site by ID - response - surfaces table
totalSurfaces	The total number of Surfaces in this Bundle. -1 indicates unlimited count.	false	integer

Get Site by ID - response - surfaces

Name	Description	Required	Value
count	The Surface count. -1 indicates unlimited count	false	integer
name	The Surface name.	false	string

Get Site by ID - response - modules

Name	Description	Required	Value
displayName	The Add-on display name	false	string
majorVersion	The Add-on major version	false	integer
name	The Add-on internal api name	false	string

Get Site by ID - response - settings

Name	Description	Required	Value
displayName	[DEPRECATED] The Setting display name	false	string
groupName	The Setting group name	false	
setting	The Setting display name	false	
settingGroup	[DEPRECATED] The Setting group name	false	string
settingGroupDisplayName	The Setting group display name	false	string

Get Site by ID - response - promptFields

Name	Description	Required	Value
promptRegion	Region associated with the prompt	false	enum
promptTenantName	Tenant name associated with the prompt	false	string
promptUserEmail	Email of the user associated with the prompt	false	string
promptUserName	Name of the user associated with the prompt	false	string

Update Site

PUT /web/api/v2.1/sites/{site_id}

Change the policy and properties of the Site given by ID.
To get the ID, run 'sites'.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Site not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Site - response - data table
errors	Errors	false	array

Update Site - response - data

Name	Description	Required	Value
accountId	Account id	false	string
accountName	Account name	false	string
activeLicenses	Number of active licenses for the site	false	integer
createdAt	Timestamp of site creation	false	string
creator	Full name of the creating user	false	string
creatorId	Id of the creating user	false	string
description	The user-defined description for the Site	false	string
expiration	Expiration	false	string
externalId	Id of CRM external system	false	string
healthStatus	Obsolete. Always true	false	boolean
id	Site ID	false	string
inheritAccountExpiration	Inherit account expiration	false	boolean
irFields	Ir fields	false	see Update Site - response - irFields table
isDefault	Is default	false	boolean
licenses	The site licenses	false	see Update Site - response - licenses table
name	Name	false	string
promptFields	Prompt fields	false	see Update Site - response - promptFields table
registrationToken	[DEPRECATED] token generation in dedicated endpoint - /sites/<site_id>/token	false	
siteType	Site type	false	string
sku	[DEPRECATED] The sku of product features active for this site	false	enum
state	Site state	false	enum
suite	[DEPRECATED] Use sku instead	false	enum
totalLicenses	Total licenses	false	integer
unlimitedExpiration	True if the Site has no expiration date	false	
unlimitedLicenses	True if the Site has unlimited licenses	false	boolean

updatedAt	Timestamp of last update	false	string
usageType	Usage type	false	string

Update Site - response - irFields

Name	Description	Required	Value
companyName	The customer's company name	true	string
contactEmail	Business email of the customer contact. Must not match the IR partner domain, the submitter's own domain, or a free/personal email provider (e.g. Gmail, Yahoo, Hotmail)	true	string
contactFirstName	First name of the customer contact	true	string
contactLastName	Last name of the customer contact	true	string
country	Country of the customer	true	string
industry	Industry vertical of the customer	true	enum
numberOfEmployeesEndpoints	Estimated number of employees or endpoints at the customer	true	integer
city	City of the customer	false	string
postal	Postal / ZIP code of the customer	false	string
region	State or region within the country	false	string

Update Site - response - licenses

Name	Description	Required	Value
bundles	The licenses Bundles	false	see Update Site - response - bundles table
modules	The licenses Add-ons	false	see Update Site - response - modules table
settings	The licenses Settings	false	see Update Site - response - settings table

Update Site - response - bundles

Name	Description	Required	Value
------	-------------	----------	-------

displayName	The Bundle display name	false	string
majorVersion	The Bundle major version	false	integer
minorVersion	The Bundle minor version	false	integer
name	The Bundle internal api name	false	string
surfaces	The Surfaces in the Bundle	false	see Update Site - response - surfaces table
totalSurfaces	The total number of Surfaces in this Bundle. -1 indicates unlimited count.	false	integer

Update Site - response - surfaces

Name	Description	Required	Value
count	The Surface count. -1 indicates unlimited count	false	integer
name	The Surface name.	false	string

Update Site - response - modules

Name	Description	Required	Value
displayName	The Add-on display name	false	string
majorVersion	The Add-on major version	false	integer
name	The Add-on internal api name	false	string

Update Site - response - settings

Name	Description	Required	Value
displayName	[DEPRECATED] The Setting display name	false	string
groupName	The Setting group name	false	
setting	The Setting display name	false	
settingGroup	[DEPRECATED] The Setting group name	false	string
settingGroupDisplayName	The Setting group display name	false	string

Update Site - response - promptFields

Name	Description	Required	Value
promptRegion	Region associated with the prompt	false	enum
promptTenantName	Tenant name associated with the prompt	false	string
promptUserEmail	Email of the user associated with the prompt	false	string
promptUserName	Name of the user associated with the prompt	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Site - body - data table

Update Site - body - data

Name	Description	Required	Value
description	The user-defined description for the Site	false	string
expiration	Expiration	false	string
externalId	Id of CRM external system	false	string
id	Site ID	false	string
inheritAccountExpiration	True, if expiration should be inherited from account	false	boolean
inherits	True if the policy is inherited from Tenant, False if the site has its own edited policy	false	boolean
irFields	IR related fields	false	see Update Site - body - irFields table
licenses	The license configuration for the Site	false	see Update Site - body - licenses table
name	Name	false	string
policy	Policy	false	see Update Site - body - policy table
promptFields	Prompt related fields	false	see Update Site - body - promptFields table
siteType	Site type	false	enum
suite	[DEPRECATED] Use licenses instead	false	enum
totalLicenses	Total licenses	false	integer
unlimitedExpiration	Is expiration unlimited, if not expiration should be supplied	false	boolean
unlimitedLicenses	[DEPRECATED] True if the Site has unlimited licenses.	false	boolean
usageType	Usage type	false	enum

Update Site - body - irFields

Name	Description	Required	Value
companyName	The customer's company name	true	string
contactEmail	Business email of the customer	true	string

	contact. Must not match the IR partner domain, the submitter's own domain, or a free/personal email provider (e.g. Gmail, Yahoo, Hotmail)		
contactFirstName	First name of the customer contact	true	string
contactLastName	Last name of the customer contact	true	string
country	Country of the customer	true	string
industry	Industry vertical of the customer	true	enum
numberOfEmployeesEndpoints	Estimated number of employees or endpoints at the customer	true	integer
city	City of the customer	false	string
postal	Postal / ZIP code of the customer	false	string
region	State or region within the country	false	string

Update Site - body - licenses

Name	Description	Required	Value
bundles	The list of Bundles selected	false	see Update Site - body - bundles table
modules	The list of Add-ons selected	false	see Update Site - body - modules table

Update Site - body - bundles

Name	Description	Required	Value
name		true	string
majorVersion		false	integer
surfaces		false	see Update Site - body - surfaces table

Update Site - body - surfaces

Name	Description	Required	Value
name		true	string

count	The number of licenses per Surface. -1 indicates unlimited count.	false	integer
-------	--	-------	---------

Update Site - body - modules

Name	Description	Required	Value
name		true	string

Update Site - body - policy

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Update Site - body - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Update Site - body - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string

driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Update Site - body - dvAttributesPerEventType table
engines	The engines statuses	false	see Update Site - body - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Update Site - body - forensicsAutoTriggering table
identityConfigurationSettings	Identity configuration	false	see Update Site - body - identityConfigurationSettings table
identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Update Site - body - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Update Site - body - remoteOpsForensics table

remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Update Site - body - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean
researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first registration	false	boolean
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Update Site - body - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean

showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Update Site - body - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Update Site - body - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Update Site - body - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Update Site - body - behavioralIndicators table
commandScripts	Command scripts event	false	see Update Site - body - commandScripts table
crossProcess	Cross process event	false	see Update Site - body - crossProcess table
dataMasking	Data masking	false	see Update Site - body - dataMasking table
dllModuleLoad	DLL module load event	false	see Update Site - body - dllModuleLoad table
dns	Network event - DNS	false	see Update Site - body - dns table

driver	Driver	false	see Update Site - body - driver table
externalDeviceActivity	External Device Activity	false	see Update Site - body - externalDeviceActivity table
file	File event	false	see Update Site - body - file table
ip	Network event - IP	false	see Update Site - body - ip table
login	User login/logout event	false	see Update Site - body - login table
namedPipe	Named Pipe	false	see Update Site - body - namedPipe table
namedPipeExtended	Named Pipe Extended	false	see Update Site - body - namedPipeExtended table
openDirectoryActivity	Open Directory Activity	false	see Update Site - body - openDirectoryActivity table
process	Process event	false	see Update Site - body - process table
profileActivity	Profile Activity	false	see Update Site - body - profileActivity table
registry	Registry event	false	see Update Site - body - registry table
scheduledTask	Scheduled task event	false	see Update Site - body - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Update Site - body - smartFileMonitoring table
url	URL Actions event	false	see Update Site - body - url table
userSubstitution	User Substitution	false	see Update Site - body - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Update Site - body - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Update Site - body - windowsEventLogsExtended table

Update Site - body - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Update Site - body - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Update Site - body - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Update Site - body - crossProcess

Name	Description	Required	Value
dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Update Site - body - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Update Site - body - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Update Site - body - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Update Site - body - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Update Site - body - externalDeviceActivity

Name	Description	Required	Value
dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Update Site - body - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Update Site - body - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Update Site - body - login

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Update Site - body - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean
dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean

Update Site - body - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Update Site - body - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean

r			
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean
dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean

Update Site - body - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Update Site - body - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Update Site - body - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean

dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Update Site - body - scheduledTask

Name	Description	Required	Value
dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Update Site - body - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Update Site - body - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Update Site - body - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean

dvEventTypeSudo	sudo Event Type	false	boolean
-----------------	-----------------	-------	---------

Update Site - body - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Update Site - body - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Update Site - body - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum

remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Update Site - body - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean
macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Update Site - body - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Update Site - body - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean
externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Update Site - body - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection	false	integer

	process		
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Update Site - body - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Update Site - body - promptFields

Name	Description	Required	Value
promptRegion	Region associated with the prompt	false	enum

promptTenantName	Tenant name associated with the prompt	false	string
promptUserEmail	Email of the user associated with the prompt	false	string
promptUserName	Name of the user associated with the prompt	false	string

Delete Site

DELETE /web/api/v2.1/sites/{site_id}

Delete the Site of the given ID. To get the ID, run "sites".
You must have an Admin role with scope access that includes the Site.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Site - response - data table
errors	Errors	false	array

Delete Site - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Get Site registration token by ID

GET /web/api/v2.1/sites/{site_id}/token

Get the registration token of the Site of the ID.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

404 - Site not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Site registration token by ID - response - data table
errors	Errors	false	array

Get Site registration token by ID - response - data

Name	Description	Required	Value
token	Token	false	string

Revert Policy

PUT /web/api/v2.1/sites/{site_id}/revert-policy

When a Site is created through the Console, it gets the Global policy.
If you change the policy and later want it set to the Global policy, use this command.
The site_id is required. You can get it from "sites".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Revert Policy - response - data table
errors	Errors	false	array

Revert Policy - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	false	see Revert Policy - body - data table

Revert Policy - body - data

Name	Description	Required	Value
id	Id	false	string

Create duplicate site

POST /web/api/v2.1/sites/duplicate-site

[DEPRECATED] Create duplicate site.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create duplicate site - response - data table
errors	Errors	false	array

Create duplicate site - response - data

Name	Description	Required	Value
accountId	Account id	false	string
accountName	Account name	false	string
activeLicenses	Number of active licenses for the site	false	integer
createdAt	Timestamp of site creation	false	string
creator	Full name of the creating user	false	string
creatorId	Id of the creating user	false	string
description	The user-defined description for the Site	false	string
expiration	Expiration	false	string
externalId	Id of CRM external system	false	string
healthStatus	Obsolete. Always true	false	boolean
id	Site ID	false	string
inheritAccountExpiration	Inherit account expiration	false	boolean
irFields	Ir fields	false	see Create duplicate site - response - irFields table
isDefault	Is default	false	boolean
licenses	The site licenses	false	see Create duplicate site - response - licenses table
name	Name	false	string
promptFields	Prompt fields	false	see Create duplicate site - response - promptFields table
registrationToken	[DEPRECATED] token generation in dedicated endpoint - /sites/<site_id>/token	false	
siteType	Site type	false	string
sku	[DEPRECATED] The sku of product features active for this site	false	enum
state	Site state	false	enum
suite	[DEPRECATED] Use sku instead	false	enum
totalLicenses	Total licenses	false	integer
unlimitedExpiration	True if the Site has no expiration date	false	
unlimitedLicenses	True if the Site has unlimited licenses	false	boolean

updatedAt	Timestamp of last update	false	string
usageType	Usage type	false	string

Create duplicate site - response - irFields

Name	Description	Required	Value
companyName	The customer's company name	true	string
contactEmail	Business email of the customer contact. Must not match the IR partner domain, the submitter's own domain, or a free/personal email provider (e.g. Gmail, Yahoo, Hotmail)	true	string
contactFirstName	First name of the customer contact	true	string
contactLastName	Last name of the customer contact	true	string
country	Country of the customer	true	string
industry	Industry vertical of the customer	true	enum
numberOfEmployeesEndpoints	Estimated number of employees or endpoints at the customer	true	integer
city	City of the customer	false	string
postal	Postal / ZIP code of the customer	false	string
region	State or region within the country	false	string

Create duplicate site - response - licenses

Name	Description	Required	Value
bundles	The licenses Bundles	false	see Create duplicate site - response - bundles table
modules	The licenses Add-ons	false	see Create duplicate site - response - modules table
settings	The licenses Settings	false	see Create duplicate site - response - settings table

Create duplicate site - response - bundles

Name	Description	Required	Value
------	-------------	----------	-------

displayName	The Bundle display name	false	string
majorVersion	The Bundle major version	false	integer
minorVersion	The Bundle minor version	false	integer
name	The Bundle internal api name	false	string
surfaces	The Surfaces in the Bundle	false	see Create duplicate site - response - surfaces table
totalSurfaces	The total number of Surfaces in this Bundle. -1 indicates unlimited count.	false	integer

Create duplicate site - response - surfaces

Name	Description	Required	Value
count	The Surface count. -1 indicates unlimited count	false	integer
name	The Surface name.	false	string

Create duplicate site - response - modules

Name	Description	Required	Value
displayName	The Add-on display name	false	string
majorVersion	The Add-on major version	false	integer
name	The Add-on internal api name	false	string

Create duplicate site - response - settings

Name	Description	Required	Value
displayName	[DEPRECATED] The Setting display name	false	string
groupName	The Setting group name	false	
setting	The Setting display name	false	
settingGroup	[DEPRECATED] The Setting group name	false	string
settingGroupDisplayName	The Setting group display name	false	string

Create duplicate site - response - promptFields

Name	Description	Required	Value
promptRegion	Region associated with the prompt	false	enum
promptTenantName	Tenant name associated with the prompt	false	string
promptUserEmail	Email of the user associated with the prompt	false	string
promptUserName	Name of the user associated with the prompt	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Create duplicate site - body - data table

Create duplicate site - body - data

Name	Description	Required	Value
copyUsers	If true adds the duplicated site to all source site users	true	boolean
name	New Site Name	true	string
policySource	Source of duplicate site policy	true	enum
sourceSiteId	Site ID of origin site	true	integer
policy	Policy is mandatory if policy_source is new, else it will be ignored.	false	see Create duplicate site - body - policy table
totalLicenses	Total licenses for duplicate site, will be subtracted from freelicenses of the source site	false	integer
unlimitedLicenses	Is the site unlimited, if not then total_licenses must be supplied	false	boolean

Create duplicate site - body - policy

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Create duplicate site - body - agentUi table
agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer

autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Create duplicate site - body - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Create duplicate site - body - dvAttributesPerEventType table
engines	The engines statuses	false	see Create duplicate site - body - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Create duplicate site - body - forensicsAutoTriggering table
identityConfigurationSettings	Identity configuration	false	see Create duplicate site - body - identityConfigurationSettings table
identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified specifically for the current scope).	false	enum
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Create duplicate site - body - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean

mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Create duplicate site - body - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Create duplicate site - body - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean
researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first registration	false	boolean
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Create duplicate site - body - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string

contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Create duplicate site - body - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for uploaded files	false	integer
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Create duplicate site - body - dvAttributesPerEventType

Name	Description	Required	Value
------	-------------	----------	-------

autoInstallBrowserExtensions	Auto install browser extensions	false	see Create duplicate site - body - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Create duplicate site - body - behavioralIndicators table
commandScripts	Command scripts event	false	see Create duplicate site - body - commandScripts table
crossProcess	Cross process event	false	see Create duplicate site - body - crossProcess table
dataMasking	Data masking	false	see Create duplicate site - body - dataMasking table
dllModuleLoad	DLL module load event	false	see Create duplicate site - body - dllModuleLoad table
dns	Network event - DNS	false	see Create duplicate site - body - dns table
driver	Driver	false	see Create duplicate site - body - driver table
externalDeviceActivity	External Device Activity	false	see Create duplicate site - body - externalDeviceActivity table
file	File event	false	see Create duplicate site - body - file table
ip	Network event - IP	false	see Create duplicate site - body - ip table
login	User login/logout event	false	see Create duplicate site - body - login table
namedPipe	Named Pipe	false	see Create duplicate site - body - namedPipe table
namedPipeExtended	Named Pipe Extended	false	see Create duplicate site - body - namedPipeExtended table
openDirectoryActivity	Open Directory Activity	false	see Create duplicate site - body - openDirectoryActivity table
process	Process event	false	see Create duplicate site - body - process table
profileActivity	Profile Activity	false	see Create duplicate site - body - profileActivity table
registry	Registry event	false	see Create duplicate site - body - registry table
scheduledTask	Scheduled task event	false	see Create duplicate site - body - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Create duplicate site - body - smartFileMonitoring table
url	URL Actions event	false	see Create duplicate site - body - url table
userSubstitution	User Substitution	false	see Create duplicate site - body - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Create duplicate site - body - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Create duplicate site - body - windowsEventLogsExtended table

Create duplicate site - body - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Create duplicate site - body - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Create duplicate site - body - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Create duplicate site - body - crossProcess

Name	Description	Required	Value
dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Create duplicate site - body - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Create duplicate site - body - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Create duplicate site - body - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Create duplicate site - body - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Create duplicate site - body - externalDeviceActivity

Name	Description	Required	Value
dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Create duplicate site - body - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean
fullDiskScan	File Scan Event Type	false	boolean

Create duplicate site - body - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Create duplicate site - body - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Create duplicate site - body - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean
dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean

Create duplicate site - body - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Create duplicate site - body - openDirectoryActivity

Name	Description	Required	Value
dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean

r			
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean
dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean

Create duplicate site - body - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Create duplicate site - body - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Create duplicate site - body - registry

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Create duplicate site - body - scheduledTask

Name	Description	Required	Value
dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Create duplicate site - body - smartFileMonitoring

Name	Description	Required	Value
smartFileMonitoring	Smart file monitoring	false	boolean

Create duplicate site - body - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Create duplicate site - body - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Create duplicate site - body - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Create duplicate site - body - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Create duplicate site - body - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum
dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum

preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Create duplicate site - body - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean
macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Create duplicate site - body - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer

identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean
-----------------------------	--	-------	---------

Create duplicate site - body - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean
externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean
scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Create duplicate site - body - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Create duplicate site - body - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Create Site and User

POST /web/api/v2.1/site-with-admin

Create a Site and an Admin role user. This requires an Admin role with a Global scope or Account scope that has permissions over the Account to which the Site will belong.

You must have a license for a new Site.

In the body of this request, include the policy and user properties.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Site and User - response - data table
errors	Errors	false	array

Create Site and User - response - data

Name	Description	Required	Value
accountId	Account id	false	string
accountName	Account name	false	string
activeLicenses	Number of active licenses for the site	false	integer
createdAt	Timestamp of site creation	false	string
description	The user-defined description for the Site	false	string
expiration	Expiration	false	string
externalId	Id of CRM external system	false	string
healthStatus	Obsolete. Always true	false	boolean
id	Site ID	false	string
inheritAccountExpiration	Inherit account expiration	false	boolean
irFields	Ir fields	false	see Create Site and User - response - irFields table
isDefault	Is default	false	boolean
licenses	The site licenses	false	see Create Site and User - response - licenses table
name	Name	false	string
promptFields	Prompt fields	false	see Create Site and User - response - promptFields table
registrationToken	[DEPRECATED] token generation in dedicated endpoint - /sites/<site_id>/token	false	
siteType	Site type	false	string
sku	[DEPRECATED] The sku of product features active for this site	false	enum
state	Site state	false	enum
suite	[DEPRECATED] Use sku instead	false	enum
totalLicenses	Total licenses	false	integer
updatedAt	Timestamp of last update	false	string
usageType	Usage type	false	string
user	The data of the newly created site admin	false	see Create Site and User - response - user table

Create Site and User - response - irFields

Name	Description	Required	Value
companyName	The customer's company name	true	string
contactEmail	Business email of the customer contact. Must not match the IR partner domain, the submitter's own domain, or a free/personal email provider (e.g. Gmail, Yahoo, Hotmail)	true	string
contactFirstName	First name of the customer contact	true	string
contactLastName	Last name of the customer contact	true	string
country	Country of the customer	true	string
industry	Industry vertical of the customer	true	enum
numberOfEmployeesEndpoints	Estimated number of employees or endpoints at the customer	true	integer
city	City of the customer	false	string
postal	Postal / ZIP code of the customer	false	string
region	State or region within the country	false	string

Create Site and User - response - licenses

Name	Description	Required	Value
bundles	The licenses Bundles	false	see Create Site and User - response - bundles table
modules	The licenses Add-ons	false	see Create Site and User - response - modules table
settings	The licenses Settings	false	see Create Site and User - response - settings table

Create Site and User - response - bundles

Name	Description	Required	Value
displayName	The Bundle display name	false	string
majorVersion	The Bundle major version	false	integer
minorVersion	The Bundle minor version	false	integer

name	The Bundle internal api name	false	string
surfaces	The Surfaces in the Bundle	false	see Create Site and User - response - surfaces table
totalSurfaces	The total number of Surfaces in this Bundle. -1 indicates unlimited count.	false	integer

Create Site and User - response - surfaces

Name	Description	Required	Value
count	The Surface count. -1 indicates unlimited count	false	integer
name	The Surface name.	false	string

Create Site and User - response - modules

Name	Description	Required	Value
displayName	The Add-on display name	false	string
majorVersion	The Add-on major version	false	integer
name	The Add-on internal api name	false	string

Create Site and User - response - settings

Name	Description	Required	Value
displayName	[DEPRECATED] The Setting display name	false	string
groupName	The Setting group name	false	
setting	The Setting display name	false	
settingGroup	[DEPRECATED] The Setting group name	false	string
settingGroupDisplayName	The Setting group display name	false	string

Create Site and User - response - promptFields

Name	Description	Required	Value
promptRegion	Region associated with the prompt	false	enum
promptTenantName	Tenant name associated with the prompt	false	string
promptUserEmail	Email of the user associated with the prompt	false	string
promptUserName	Name of the user associated with the prompt	false	string

Create Site and User - response - user

Name	Description	Required	Value
email	Email	true	string
fullName	Full name	true	string
id	Id	false	string
primaryTwoFaMethod	Primary two fa method	false	string
twoFaEnabled	Two fa enabled	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Site and User - body - data table

Create Site and User - body - data

Name	Description	Required	Value
name	Name	true	string
user	The data of the admin user been created	true	see Create Site and User - body - user table
accountId	Associated account. Leave empty in single-account management consoles.	false	string
accountSfld		false	string
description	The user-defined description for the Site	false	string
expiration	Expiration	false	string
externalId	Id of CRM external system	false	string
inheritAccountExpiration	True, if expiration should be inherited from account	false	boolean
inherits	True if the policy is inherited from Tenant, False if the site has its own edited policy	false	boolean
irFields	IR related fields	false	see Create Site and User - body - irFields table
licenses	The license configuration for the Site	false	see Create Site and User - body - licenses table
policy	Policy is mandatory if inherits is false, else it will be ignored.	false	see Create Site and User - body - policy table
promptFields	Prompt related fields	false	see Create Site and User - body - promptFields table
siteType	Site types	false	enum
sku	[DEPRECATED] Use licenses instead	false	enum
suite	[DEPRECATED] Use licenses instead	false	enum
totalLicenses	Total licenses	false	integer
unlimitedExpiration	Is expiration unlimited, if not expiration should be supplied	false	boolean
unlimitedLicenses	Is the site unlimited, if not then total_licenses must be supplied	false	boolean
usageType	Usage type	false	enum

Create Site and User - body - user

Name	Description	Required	Value
email	Email	true	string
fullName	Full name	true	string
id	Id	false	string
password	Password	false	string
primaryTwoFaMethod	Primary two fa method	false	string
twoFaEnabled	Two fa enabled	false	boolean

Create Site and User - body - irFields

Name	Description	Required	Value
companyName	The customer's company name	true	string
contactEmail	Business email of the customer contact. Must not match the IR partner domain, the submitter's own domain, or a free/personal email provider (e.g. Gmail, Yahoo, Hotmail)	true	string
contactFirstName	First name of the customer contact	true	string
contactLastName	Last name of the customer contact	true	string
country	Country of the customer	true	string
industry	Industry vertical of the customer	true	enum
numberOfEmployeesEndpoints	Estimated number of employees or endpoints at the customer	true	integer
city	City of the customer	false	string
postal	Postal / ZIP code of the customer	false	string
region	State or region within the country	false	string

Create Site and User - body - licenses

Name	Description	Required	Value
------	-------------	----------	-------

bundles	The list of Bundles selected	false	see Create Site and User - body - bundles table
modules	The list of Add-ons selected	false	see Create Site and User - body - modules table

Create Site and User - body - bundles

Name	Description	Required	Value
name		true	string
majorVersion		false	integer
surfaces		false	see Create Site and User - body - surfaces table

Create Site and User - body - surfaces

Name	Description	Required	Value
name		true	string
count	The number of licenses per Surface. -1 indicates unlimited count.	false	integer

Create Site and User - body - modules

Name	Description	Required	Value
name		true	string

Create Site and User - body - policy

Name	Description	Required	Value
agentLoggingOn	True if logging is enabled in the agent	false	boolean
agentNotification	[DEPRECATED] Show end point notification on suspicious.Replaced by 'show_suspicious' in the agent UI section	false	boolean
agentUi	Agent ui	false	see Create Site and User - body - agentUi table

agentUiOn	[DEPRECATED] Show/hide Agent UI. Moved inside the agent UI section	false	boolean
allowRemoteShell	True if Remote Shell is enabled for the scope	false	boolean
allowUnprotectByApprovedProcess	Allow Unprotect By Approved Process on/off	false	boolean
antiTamperingOn	Anti tampering on/off	false	boolean
autoDecommissionDays	Automatic decommission period in days	false	integer
autoDecommissionOn	Auto decommission on	false	boolean
autoFileUpload	Automatic file upload configuration	false	see Create Site and User - body - autoFileUpload table
autoImmuneOn	Automatic immune on/off - this value must be true since all policies are immune by default	false	boolean
autoMitigationAction	Default action for auto mitigation	false	string
cloudValidationOn	Cloud validation on	false	
createdAt	Timestamp of policy creation	false	string
driftDetectionDelayTime	Drift detection delay time in seconds	false	integer
driverBlocking	Suspicious driver blocking engine on/off	false	boolean
dvAttributesPerEventType	The DV attributes	false	see Create Site and User - body - dvAttributesPerEventType table
engines	The engines statuses	false	see Create Site and User - body - engines table
forensicsAutoTriggering	Forensics auto triggering configuration	false	see Create Site and User - body - forensicsAutoTriggering table
identityConfigurationSettings	Identity configuration	false	see Create Site and User - body - identityConfigurationSettings table
identityEndpointReporting	Endpoint reporting level	false	enum
identityOn	Identity module on/off	false	boolean
identityReportInterval	Identity telemetry report interval in minutes	false	integer
identityThrottlingInterval	Identity duplicate command consolidation interval in minutes	false	integer
identityUpdateInterval	Identity update interval in minutes	false	integer
informationalAlertsOn	Informational alerts on/off	false	boolean
inheritedFrom	Indicates the parent scope from which this policy is inherited, or 'null' if it is not inherited (modified	false	enum

	specifically for the current scope).		
ioc	True if ioc is enabled	false	boolean
iocAttributes	The ioc attributes	false	see Create Site and User - body - iocAttributes table
iocSupported	ioc supported for the scope	false	boolean
isDefault	True if this is the tenant policy	false	boolean
isDvPolicyPerEventType	FE indication as to how to display DV policy	false	boolean
logCollectorEnabled	Log collector on/off	false	boolean
mitigationMode	Mitigation modes	false	enum
mitigationModeSuspicious	Mitigation mode	false	enum
monitorOnExecute	Monitor on execute on/off	false	boolean
monitorOnWrite	Monitor on write	false	boolean
networkProtectionInfra	Network Protection Infrastructure On/Off	false	boolean
networkQuarantineOn	Network quarantine on	false	boolean
remoteOpsForensics	Remote ops forensics configuration	false	see Create Site and User - body - remoteOpsForensics table
remoteScriptOrchestration	Remote script orchestration upload limits configuration	false	see Create Site and User - body - remoteScriptOrchestration table
removeMacros	Determines if macros should be removed from macro threats	false	boolean
removeMacrosML	Determines if malicious macros should be mitigated using ML Models	false	boolean
researchOn	Share data with SentinelOne	false	boolean
scanNewAgents	If True initiate full disk scan upon first registration	false	boolean
signedDriverBlockingOn	Suspicious signed driver blocking on/off	false	boolean
smbLateralMovementMitigation	SMB Lateral Movement Mitigation	false	boolean
snapshotsOn	True if snapshots are enabled	false	boolean
unsignedDriverBlockingOn	Suspicious unsigned driver blocking on/off	false	boolean
updatedAt	Time of the last update to the policy	false	string
userFullName	The user that created the policy	false	string
userId	The user id	false	string

Create Site and User - body - agentUi

Name	Description	Required	Value
agentUiOn	Agent ui on	false	boolean
contactCompany	Contact company	false	string
contactDirectMessage	Contact direct message	false	string
contactEmail	Contact email	false	string
contactFreeText	Contact free text	false	string
contactOther	Contact other	false	string
contactPhoneNumber	Contact phone number	false	string
contactSupportWebsite	Contact support website	false	string
devicePopUpNotifications	Device pop up notifications	false	boolean
maxEventAgeDays	Max event age days	false	integer
showAgentWarnings	Show agent warnings	false	boolean
showDeviceTab	Show device tab	false	boolean
showQuarantineTab	Show quarantine tab	false	boolean
showSupport	Show support	false	boolean
showSuspicious	Show suspicious	false	boolean
threatPopUpNotifications	Threat pop up notifications	false	boolean

Create Site and User - body - autoFileUpload

Name	Description	Required	Value
enabled	Automatic file upload on/off	false	boolean
includeBenignFiles	Upload benign files	false	boolean
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum file size (MB) to upload	false	integer
maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalDiskUsage	Maximum local disk usage (MB) for	false	integer

	uploaded files		
maxLocalDiskUsageLimit	Limit for the maximum local disk usage (MB) for uploaded files	false	integer

Create Site and User - body - dvAttributesPerEventType

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	see Create Site and User - body - autoInstallBrowserExtensions table
behavioralIndicators	Behavioral indicators event	false	see Create Site and User - body - behavioralIndicators table
commandScripts	Command scripts event	false	see Create Site and User - body - commandScripts table
crossProcess	Cross process event	false	see Create Site and User - body - crossProcess table
dataMasking	Data masking	false	see Create Site and User - body - dataMasking table
dllModuleLoad	DLL module load event	false	see Create Site and User - body - dllModuleLoad table
dns	Network event - DNS	false	see Create Site and User - body - dns table
driver	Driver	false	see Create Site and User - body - driver table
externalDeviceActivity	External Device Activity	false	see Create Site and User - body - externalDeviceActivity table
file	File event	false	see Create Site and User - body - file table
ip	Network event - IP	false	see Create Site and User - body - ip table
login	User login/logout event	false	see Create Site and User - body - login table
namedPipe	Named Pipe	false	see Create Site and User - body - namedPipe table
namedPipeExtended	Named Pipe Extended	false	see Create Site and User - body - namedPipeExtended table
openDirectoryActivity	Open Directory Activity	false	see Create Site and User - body - openDirectoryActivity table
process	Process event	false	see Create Site and User - body - process table
profileActivity	Profile Activity	false	see Create Site and User - body - profileActivity table
registry	Registry event	false	see Create Site and User - body - registry table
scheduledTask	Scheduled task event	false	see Create Site and User - body - scheduledTask table
smartFileMonitoring	Smart file monitoring	false	see Create Site and User - body - smartFileMonitoring table
url	URL Actions event	false	see Create Site and User - body - url table
userSubstitution	User Substitution	false	see Create Site and User - body - userSubstitution table
windowsEventLogs	Windows Event Log	false	see Create Site and User - body - windowsEventLogs table
windowsEventLogsExtended	Windows Event Log Extended	false	see Create Site and User - body - windowsEventLogsExtended table

Create Site and User - body - autoInstallBrowserExtensions

Name	Description	Required	Value
autoInstallBrowserExtensions	Auto install browser extensions	false	boolean

Create Site and User - body - behavioralIndicators

Name	Description	Required	Value
dvEventTypeBehavioralIndicators	Behavioral indicators event	false	boolean

Create Site and User - body - commandScripts

Name	Description	Required	Value
dvEventTypeCommandScripts	Command scripts event	false	boolean

Create Site and User - body - crossProcess

Name	Description	Required	Value
dvEventTypeCrossProcessDuplicateProcess	Duplicate Process Event Type	false	boolean
dvEventTypeCrossProcessDuplicateThread	Duplicate Thread Event Type	false	boolean
dvEventTypeCrossProcessOpenProcesses	Open Process Event Type	false	boolean
dvEventTypeCrossProcessRemoteThread	Remote Thread Event Type	false	boolean

Create Site and User - body - dataMasking

Name	Description	Required	Value
dataMasking	Data masking	false	boolean

Create Site and User - body - dllModuleLoad

Name	Description	Required	Value
dvEventTypeDllModuleLoad	DLL module load event	false	boolean

Create Site and User - body - dns

Name	Description	Required	Value
dvEventTypeDns	Network event - DNS	false	boolean
dvEventTypeExtendedDns	Extended DNS event	false	boolean

Create Site and User - body - driver

Name	Description	Required	Value
dvEventTypeDriverLoad	Driver Load	false	boolean

Create Site and User - body - externalDeviceActivity

Name	Description	Required	Value
dvEventTypeExternalDeviceConnect	External Device Connect Event Type	false	boolean
dvEventTypeExternalDeviceDisconnect	External Device Disconnect Event Type	false	boolean

Create Site and User - body - file

Name	Description	Required	Value
dvEventTypeFileCreation	File Creation Event Type	false	boolean
dvEventTypeFileDeletion	File Deletion Event Type	false	boolean
dvEventTypeFileModification	File Modification Event Type	false	boolean
dvEventTypeFileRename	File Rename Event Type	false	boolean

fullDiskScan	File Scan Event Type	false	boolean
--------------	----------------------	-------	---------

Create Site and User - body - ip

Name	Description	Required	Value
dvEventTypeIpConnect	IP Connect Event Type	false	boolean
dvEventTypeIpListen	IP Listen Event Type	false	boolean

Create Site and User - body - login

Name	Description	Required	Value
dvEventTypeLoginLoggedIn	User Login Event Type	false	boolean
dvEventTypeLoginLoggedOut	User Logout Event Type	false	boolean

Create Site and User - body - namedPipe

Name	Description	Required	Value
dvEventTypeNamedPipeConnection	Named Pipe Connection Event Type	false	boolean
dvEventTypeNamedPipeCreation	Named Pipe Creation Event Type	false	boolean

Create Site and User - body - namedPipeExtended

Name	Description	Required	Value
namedPipeExtended	Named Pipe Connection Extended Event Type	false	boolean

Create Site and User - body - openDirectoryActivity

Name	Description	Required	Value
------	-------------	----------	-------

dvEventTypeOpenDirectoryAddAttributeValue	Add Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryAddMemberToGroup	Add Member to Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateGroup	Create Group Event Type	false	boolean
dvEventTypeOpenDirectoryCreateUser	Create User Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteGroup	Delete Group Event Type	false	boolean
dvEventTypeOpenDirectoryDeleteUser	Delete User Event Type	false	boolean
dvEventTypeOpenDirectoryDisableUser	Disable User Event Type	false	boolean
dvEventTypeOpenDirectoryEnableUser	Enable User Event Type	false	boolean
dvEventTypeOpenDirectoryModifyPassword	Modify Password Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveAttributeValue	Remove Attribute Value Event Type	false	boolean
dvEventTypeOpenDirectoryRemoveMemberFromGroup	Remove Member from Group Event Type	false	boolean
dvEventTypeOpenDirectorySetAttributeValues	Set Attribute Values Event Type	false	boolean
dvEventTypeOpenDirectorySetMembersOfGroup	Set Members of Group Event Type	false	boolean

Create Site and User - body - process

Name	Description	Required	Value
dvEventTypeProcessCreation	Process Creation Event Type	false	boolean
dvEventTypeProcessExit	Process Exit Event Type	false	boolean
dvEventTypeProcessModification	Process Termination Event Type	false	boolean

Create Site and User - body - profileActivity

Name	Description	Required	Value
dvEventTypeProfileAddition	Profile Addition Event Type	false	boolean
dvEventTypeProfileRemoval	Profile Removal Event Type	false	boolean

Create Site and User - body - registry

Name	Description	Required	Value
dvEventTypeRegistryKeyCreated	Registry Key Created Event Type	false	boolean
dvEventTypeRegistryKeyDelete	Registry Key Delete Event Type	false	boolean
dvEventTypeRegistryKeyExport	Registry Key Export Event Type	false	boolean
dvEventTypeRegistryKeyImport	Registry Key Import Event Type	false	boolean
dvEventTypeRegistryKeyRename	Registry Key Rename Event Type	false	boolean
dvEventTypeRegistryKeySecurityChanged	Registry Key Security Changed Event Type	false	boolean
dvEventTypeRegistryValueCreated	Registry Value Crated Event Type	false	boolean
dvEventTypeRegistryValueDeleted	Registry Value Deleted Event Type	false	boolean
dvEventTypeRegistryValueModified	Registry Value Modified Event Type	false	boolean

Create Site and User - body - scheduledTask

Name	Description	Required	Value
dvEventTypeScheduledTaskDelete	Scheduled Task Delete Event Type	false	boolean
dvEventTypeScheduledTaskRegister	Scheduled Task Register Event Type	false	boolean
dvEventTypeScheduledTaskStart	Scheduled Task Start Event Type	false	boolean
dvEventTypeScheduledTaskTrigger	Scheduled Task Trigeer Event Type	false	boolean
dvEventTypeScheduledTaskUpdate	Scheduled Task Update Event Type	false	boolean

Create Site and User - body - smartFileMonitoring

Name	Description	Required	Value
------	-------------	----------	-------

smartFileMonitoring	Smart file monitoring	false	boolean
---------------------	-----------------------	-------	---------

Create Site and User - body - url

Name	Description	Required	Value
dvEventTypeUrl	URL Actions event	false	boolean

Create Site and User - body - userSubstitution

Name	Description	Required	Value
dvEventTypeSu	su Event Type	false	boolean
dvEventTypeSudo	sudo Event Type	false	boolean

Create Site and User - body - windowsEventLogs

Name	Description	Required	Value
dvEventTypeWindowsEventLogCreation	Windows Event Log Creation Event Type	false	boolean

Create Site and User - body - windowsEventLogsExtended

Name	Description	Required	Value
windowsEventLogsExtended	Windows Event Log Extended Event Type	false	boolean

Create Site and User - body - engines

Name	Description	Required	Value
applicationControl	application control	false	enum
applicationDetection	application detection	false	enum

dataFiles	data files	false	enum
driftDetection	drift detection	false	enum
executables	executables	false	enum
exploits	exploits	false	enum
idr	idr	false	enum
lateralMovement	lateral movement	false	enum
networkProtection	network protection	false	enum
penetration	penetration	false	enum
preExecution	on-write	false	enum
preExecutionSuspicious	pre execution suspicious	false	enum
pup	potentially unwanted applications (PUP)	false	enum
remoteShell	remote shell	false	enum
reputation	reputation	false	enum

Create Site and User - body - forensicsAutoTriggering

Name	Description	Required	Value
linuxEnabled	True if linux forensics is enabled	false	boolean
linuxProfileId	The profile id for the linux forensics	false	string
linuxProfileName	The profile name for the linux forensics	false	string
macosEnabled	True if macos forensics is enabled	false	boolean
macosProfileId	The profile id for the macos forensics	false	string
macosProfileName	The profile name for the macos forensics	false	string
windowsEnabled	True if windows forensics is enabled	false	boolean
windowsProfileId	The profile id for the windows forensics	false	string
windowsProfileName	The profile name for the windows forensics	false	string

Create Site and User - body - identityConfigurationSettings

Name	Description	Required	Value
identityMaxCpuThreshold	Identity maximum CPU threshold	false	integer
identityMaxDefinedMemoryLimit	Identity maximum defined memory limit in MB	false	integer
identityMaxMemoryLimit	Identity maximum memory limit in MB	false	integer
identityMaxMemoryUsage	Identity maximum memory usage	false	integer
identityThresholdMonitoring	True if Identity threshold monitoring is enabled	false	boolean

Create Site and User - body - iocAttributes

Name	Description	Required	Value
autoInstallBrowserExtensions	Update auto install browser extensions	false	boolean
behavioralIndicators	Update behavioral indicators	false	boolean
commandScripts	Update command scripts	false	boolean
crossProcess	Update cross process	false	boolean
dataMasking	Update data masking	false	boolean
dllModuleLoad	Update DLL module load	false	boolean
dns	Network event - DNS	false	boolean
driver	Driver	false	boolean
externalDeviceActivity	External Device Activity	false	boolean
fds	Full disk scan	false	boolean
file	File event	false	boolean
ip	Network event - IP	false	boolean
login	User login/logout event	false	boolean
namedPipe	Named Pipe	false	boolean
namedPipeExtended	Named Pipe Extended	false	boolean
openDirectoryActivity	Open Directory Activity	false	boolean
process	Process creation event	false	boolean
profileActivity	Profile Activity	false	boolean
registry	Registry event	false	boolean

scheduledTask	Scheduled task event	false	boolean
smartFileMonitoring	Smart file monitoring	false	boolean
url	loc URI	false	boolean
userSubstitution	User Substitution	false	boolean
windowsEventLogs	Windows Event Log	false	boolean
windowsEventLogsExtended	Windows Event Log Extended	false	boolean

Create Site and User - body - remoteOpsForensics

Name	Description	Required	Value
cpuLimit	CPU resources limit for collection process	false	integer
enabled	Enabled	false	boolean
maximumDailyUpload	Maximum size to upload daily	false	integer
maximumDailyUploadLimit	Limit for the maximum size to upload daily	false	integer
maximumFileSizeUpload	Maximum size for single file	false	integer
maximumFileSizeUploadLimit	Limit for the maximum file size to upload	false	integer
parsedArtifactsDestination	Default destination of parsed artifacts	false	enum

Create Site and User - body - remoteScriptOrchestration

Name	Description	Required	Value
alwaysUploadStreamToCloud	Always upload streams to cloud	false	boolean
maxDailyFileDownload	Maximum size (MB) to download daily	false	integer
maxDailyFileDownloadLimit	Limit for the maximum size (MB) to download daily	false	integer
maxDailyFileUpload	Maximum size (MB) to upload daily	false	integer
maxDailyFileUploadLimit	Limit for the maximum size (MB) to upload daily	false	integer
maxFileSize	Maximum size in bytes for single file	false	integer

maxFileSizeLimit	Limit for the maximum file size (MB) to upload	false	integer
maxLocalPackageDiskUsage	Maximum local disk usage (MB) for packages	false	integer
maxLocalPackageDiskUsageLimit	Limit for the maximum local disk usage (MB) for packages	false	integer

Create Site and User - body - promptFields

Name	Description	Required	Value
promptRegion	Region associated with the prompt	false	enum
promptTenantName	Tenant name associated with the prompt	false	string
promptUserEmail	Email of the user associated with the prompt	false	string
promptUserName	Name of the user associated with the prompt	false	string

Regenerate Site Key

PUT /web/api/v2.1/sites/{site_id}/regenerate-key

Regenerate the key for the given Site.
To get the site_id, use "sites".

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

403 - No permission for regenerating a key.

404 - Site not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Regenerate Site Key - response - data table
errors	Errors	false	array

Regenerate Site Key - response - data

Name	Description	Required	Value
registrationToken	Registration token	false	string

Reactivate Site

PUT /web/api/v2.1/sites/{site_id}/reactivate

Reactivate an expired Site.

You must have an Admin role with scope access that includes this Site, and you must have a license for the Site.

To get the site_id, run "sites".

Response Messages

200 - Site reactivated

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

404 - Site not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Reactivate Site - response - data table
errors	Errors	false	array

Reactivate Site - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Reactivate Site - body - data table

Reactivate Site - body - data

Name	Description	Required	Value
expiration	New expiration date for the site	false	string
unlimited	If false an expiration should be supplied	false	boolean

Expire Site

POST /web/api/v2.1/sites/{site_id}/expire-now

Expire the Site of the given ID (run "sites" to get the ID).
You must have an Admin role with scope access that includes this Site.

Response Messages

200 - Expire site now

401 - Unauthorized access - please sign in and retry.

404 - Site not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Expire Site - response - data table
errors	Errors	false	array

Expire Site - response - data

Name	Description	Required	Value
accountId	Account id	false	string
accountName	Account name	false	string
activeLicenses	Number of active licenses for the site	false	integer
createdAt	Timestamp of site creation	false	string
creator	Full name of the creating user	false	string
creatorId	Id of the creating user	false	string
description	The user-defined description for the Site	false	string
expiration	Expiration	false	string
externalId	Id of CRM external system	false	string
healthStatus	Obsolete. Always true	false	boolean
id	Site ID	false	string
inheritAccountExpiration	Inherit account expiration	false	boolean
irFields	Ir fields	false	see Expire Site - response - irFields table
isDefault	Is default	false	boolean
licenses	The site licenses	false	see Expire Site - response - licenses table
name	Name	false	string
promptFields	Prompt fields	false	see Expire Site - response - promptFields table
registrationToken	[DEPRECATED] token generation in dedicated endpoint - /sites/<site_id>/token	false	
siteType	Site type	false	string
sku	[DEPRECATED] The sku of product features active for this site	false	enum
state	Site state	false	enum
suite	[DEPRECATED] Use sku instead	false	enum
totalLicenses	Total licenses	false	integer
unlimitedExpiration	True if the Site has no expiration date	false	
unlimitedLicenses	True if the Site has unlimited licenses	false	boolean

updatedAt	Timestamp of last update	false	string
usageType	Usage type	false	string

Expire Site - response - irFields

Name	Description	Required	Value
companyName	The customer's company name	true	string
contactEmail	Business email of the customer contact. Must not match the IR partner domain, the submitter's own domain, or a free/personal email provider (e.g. Gmail, Yahoo, Hotmail)	true	string
contactFirstName	First name of the customer contact	true	string
contactLastName	Last name of the customer contact	true	string
country	Country of the customer	true	string
industry	Industry vertical of the customer	true	enum
numberOfEmployeesEndpoints	Estimated number of employees or endpoints at the customer	true	integer
city	City of the customer	false	string
postal	Postal / ZIP code of the customer	false	string
region	State or region within the country	false	string

Expire Site - response - licenses

Name	Description	Required	Value
bundles	The licenses Bundles	false	see Expire Site - response - bundles table
modules	The licenses Add-ons	false	see Expire Site - response - modules table
settings	The licenses Settings	false	see Expire Site - response - settings table

Expire Site - response - bundles

Name	Description	Required	Value
------	-------------	----------	-------

displayName	The Bundle display name	false	string
majorVersion	The Bundle major version	false	integer
minorVersion	The Bundle minor version	false	integer
name	The Bundle internal api name	false	string
surfaces	The Surfaces in the Bundle	false	see Expire Site - response - surfaces table
totalSurfaces	The total number of Surfaces in this Bundle. -1 indicates unlimited count.	false	integer

Expire Site - response - surfaces

Name	Description	Required	Value
count	The Surface count. -1 indicates unlimited count	false	integer
name	The Surface name.	false	string

Expire Site - response - modules

Name	Description	Required	Value
displayName	The Add-on display name	false	string
majorVersion	The Add-on major version	false	integer
name	The Add-on internal api name	false	string

Expire Site - response - settings

Name	Description	Required	Value
displayName	[DEPRECATED] The Setting display name	false	string
groupName	The Setting group name	false	
setting	The Setting display name	false	
settingGroup	[DEPRECATED] The Setting group name	false	string
settingGroupDisplayName	The Setting group display name	false	string

Expire Site - response - promptFields

Name	Description	Required	Value
promptRegion	Region associated with the prompt	false	enum
promptTenantName	Tenant name associated with the prompt	false	string
promptUserEmail	Email of the user associated with the prompt	false	string
promptUserName	Name of the user associated with the prompt	false	string

Update Sites

PUT /web/api/v2.1/sites/update-bulk

Change the properties of the Sites given by IDs.
To get the IDs, run 'sites'.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Sites - response - data table
errors	Errors	false	array

Update Sites - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Sites - body - data table
filter	Filter	true	see Update Sites - body - filter table

Update Sites - body - data

Name	Description	Required	Value
description	The description for the Site	false	string
expiration	Expiration	false	string
inheritAccountExpiration	True, if expiration should be inherited from account	false	boolean
inherits	True if the policy is inherited from Account, False is not supported in bulk update	false	boolean
licenses	The licenses configuration for the sites	false	see Update Sites - body - licenses table
siteType	Site type	false	enum
unlimitedExpiration	Is expiration unlimited	false	boolean

Update Sites - body - licenses

Name	Description	Required	Value
bundles	The list of Bundles selected	false	see Update Sites - body - bundles table

Update Sites - body - bundles

Name	Description	Required	Value
name		true	string
majorVersion		false	integer
surfaces		false	see Update Sites - body - surfaces table

Update Sites - body - surfaces

Name	Description	Required	Value
------	-------------	----------	-------

name		true	string
count	The number of licenses per Surface. -1 indicates unlimited count.	false	integer

Update Sites - body - filter

Name	Description	Required	Value
accountId	Account id	false	string
accountIds	List of Account IDs to filter by	false	string []
accountName__contains	Free-text filter by account name (supports multiple values)	false	string []
activeLicenses	Active licenses	false	integer
adminOnly	[DEPRECATED] Show sites the user has Admin privileges to	false	boolean
availableMoveSites	Only return sites the user can move agents to	false	boolean
createdAt	Timestamp of site creation	false	string
description	The description for the Site	false	string
description__contains	Free-text filter by site description (supports multiple values)	false	string []
expiration	Expiration	false	string
externalId	Id in a CRM external system	false	string
features	If sent return only sites that support this features	false	string []
healthStatus	Health status	false	boolean
isDefault	Is default	false	boolean
module	Module	false	string
name	Name	false	string
name__contains	Free-text filter by site name (supports multiple values)	false	string []
query	Full text search for fields: name, account_name, description. (Note: on single-account consoles account name will not be matched)	false	string
registrationToken	Registration token	false	string

sitelds	List of Site IDs to filter by	false	string []
siteType	Site type	false	enum
sku	SKU	false	string
state	Site state	false	enum
states	List of states to filter	false	string []
statesNin	List of states to not filter	false	string []
suite	[DEPRECATED] Use sku instead	false	enum
totalLicenses	Total licenses	false	integer
updatedAt	Timestamp of last update	false	string

Get local upgrade/downgrade Site authorization

GET /web/api/v2.1/sites/{site_id}/local-authorization

Get the time when authorization of local upgrades/downgrades expires, and the number of Agents authorized for local upgrades/downgrades, in this Site.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get local upgrade/downgrade Site authorization - response - data table
errors	Errors	false	array

Get local upgrade/downgrade Site authorization - response - data

Name	Description	Required	Value
authorizedAgents	Authorized agents	false	integer
siteAuthorization	Site authorization	false	string

Edit local upgrade/downgrade Site authorization

PUT /web/api/v2.1/sites/{site_id}/local-authorization

Edit when authorization of local upgrades/downgrades expires. Returns the number of Agents authorized for local upgrades/downgrades, in this Site.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Edit local upgrade/downgrade Site authorization - response - data table
errors	Errors	false	array

Edit local upgrade/downgrade Site authorization - response - data

Name	Description	Required	Value
authorizedAgents	Authorized agents	false	integer

Body Schema

Name	Description	Required	Value
siteAuthorization	New expiration date for Site local upgrade/downgrade authorization	false	string

Get a CSV file of local upgrade/downgrade Site authorization data

GET /web/api/v2.1/sites/{site_id}/local-upgrade-approved-agents-csv

Get a CSV file containing the Agents authorized for local upgrades/downgrades, in this Site.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get a CSV file of local upgrade/downgrade Site authorization data - response - data table
errors	Errors	false	array

Get a CSV file of local upgrade/downgrade Site authorization data - response - data

Name	Description	Required	Value
authorizedAgents	Authorized agents	false	integer
siteAuthorization	Site authorization	false	string

System

System Info

GET /web/api/v2.1/system/info

Get the Console build, version, patch, and release information.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see System Info - response - data table
errors	Errors	false	array

System Info - response - data

Name	Description	Required	Value
build	Build	false	string
latestAgentVersion	Latest agent version	false	string
patch	Patch	false	string
release	Release	false	string
version	Version	false	string

System Status

GET /web/api/v2.1/system/status

Get an indication of the system's health status.

This command always returns a positive response when the Management Console and API server are up and running. In these cases, some features or capabilities might be impaired. This command does not require authentication.

Rate limit: 1 call per second for each IP address that communicates with the Console.

Response Messages

200 - Success

Response Schema

Name	Description	Required	Value
data	Response data	false	see System Status - response - data table
errors	Errors	false	array

System Status - response - data

Name	Description	Required	Value
health	System health indicator. Always returns "ok" when it is up and running	false	string

Database Status

GET /web/api/v2.1/system/status/db

[DEPRECATED] Works the same way as "System Status" endpoint.

This command does not require authentication.

Rate limit: 1 call per second for each IP address that communicates with the Console.

Response Messages

200 - Success

Response Schema

Name	Description	Required	Value
data	Response data	false	see Database Status - response - data table
errors	Errors	false	array

Database Status - response - data

Name	Description	Required	Value
health	System health indicator. Always returns "ok" when it is up and running	false	string

Cache Status

GET /web/api/v2.1/system/status/cache

[DEPRECATED] Works the same way as "System Status" endpoint.

This command does not require authentication.

Rate limit: 1 call per second for each IP address that communicates with the Console.

Response Messages

200 - Success

Response Schema

Name	Description	Required	Value
data	Response data	false	see Cache Status - response - data table
errors	Errors	false	array

Cache Status - response - data

Name	Description	Required	Value
health	System health indicator. Always returns "ok" when it is up and running	false	string

Get System Config

GET /web/api/v2.1/system/configuration

Get the configuration of your SentinelOne system.

The response shows basic information of the deployed SKUs and licenses, 2FA, and the Management URL.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get System Config - response - data table
errors	Errors	false	array

Get System Config - response - data

Name	Description	Required	Value
accessibleUrl	External DNS name of the management	false	string
advancedMode	True if advanced mode is enabled.	false	boolean
advancedModeAllowChanges	True if advanced mode value can be updated from this scope.	false	boolean
allowDuplicateSite	[DEPRECATED] Allow site admins to duplicate sites in their accounts	false	boolean
allowedDomains	list of allowed domains for user creation.	false	see Get System Config - response - allowedDomains table
cloudIntelligenceOn	[DEPRECATED] Cloud intelligence on	false	boolean
cloudLastConnectionTime	Cloud last connection time	false	string
earlyAccess	True if early access mode is enabled.	false	boolean
earlyAccessPlatforms	Early access platforms	false	string []
globalSalesforceId	salesforce id field of tenant	false	string
globalSharedConsole	shared console field of tenant	false	boolean
globalTwoFaEnabled	Global two fa enabled	false	boolean
licenses	List of available licenses	false	see Get System Config - response - licenses table
maxCompleteLicenses	[DEPRECATED] Complete Licenses	false	integer
maxControlLicenses	[DEPRECATED] Control licenses	false	integer
maxCoreLicenses	[DEPRECATED] Core licenses	false	integer
passwordExpiration	Time in days until a user password expires	false	integer
passwordExpirationRange	Password expiration range (read-only)	false	see Get System Config - response - passwordExpirationRange table
region	The region of the management	false	string
rememberMeLength	Time in minutes until a user session expires	false	integer
rememberMeLengthRange	Remember me length range	false	see Get System Config - response - rememberMeLengthRange table
scalyrUrl	The Scalyr URL that sends data to this Console.	false	string
tfaEnrollmentExpiration	2FA enrollment expiration period	false	integer

uiInactivityTimeoutSeconds	Length of UI inactivity period	false	integer
uiInactivityTimeoutSecondsRange	UI inactivity timeout range	false	see Get System Config - response - uiInactivityTimeoutSecondsRange table
unlimitedComplete	[DEPRECATED] True if Complete licenses is unlimited	false	boolean
unlimitedControl	[DEPRECATED] True if Control licenses is unlimited	false	boolean
unlimitedCore	[DEPRECATED] True if Core licenses is unlimited	false	boolean

Get System Config - response - allowedDomains

Name	Description	Required	Value
domain	Allowed domain name for user creation.	false	string
inherited	True if this is an inherited domain	false	boolean

Get System Config - response - licenses

Name	Description	Required	Value
bundles	The licenses Bundles	false	see Get System Config - response - bundles table
modules	The licenses Add-ons	false	see Get System Config - response - modules table
settings	The licenses Settings	false	see Get System Config - response - settings table

Get System Config - response - bundles

Name	Description	Required	Value
displayName	The Bundle display name	false	string
majorVersion	The Bundle major version	false	integer
minorVersion	The Bundle minor version	false	integer
name	The Bundle internal api name	false	string
surfaces	The Surfaces in the Bundle	false	see Get System Config - response - surfaces table
totalSurfaces	The total number of Surfaces in this	false	integer

	Bundle. -1 indicates unlimited count.		
--	---------------------------------------	--	--

Get System Config - response - surfaces

Name	Description	Required	Value
count	The Surface count. -1 indicates unlimited count	false	integer
name	The Surface name.	false	string

Get System Config - response - modules

Name	Description	Required	Value
displayName	The Add-on display name	false	string
majorVersion	The Add-on major version	false	integer
name	The Add-on internal api name	false	string

Get System Config - response - settings

Name	Description	Required	Value
displayName	[DEPRECATED] The Setting display name	false	string
groupName	The Setting group name	false	
setting	The Setting display name	false	
settingGroup	[DEPRECATED] The Setting group name	false	string
settingGroupDisplayName	The Setting group display name	false	string

Get System Config - response - passwordExpirationRange

Name	Description	Required	Value
max	Maximum time in days until a user	false	integer

	password expires		
min	Minimum time in days until a user password expires	false	integer

Get System Config - response - rememberMeLengthRange

Name	Description	Required	Value
max	Maximum time interval in minutes before the session expires	false	integer
min	Minimum time interval in minutes before the session expires	false	integer

Get System Config - response - uiInactivityTimeoutSecondsRange

Name	Description	Required	Value
max	Maximum ui inactivity time in seconds before the session expires	false	integer
min	Minimum ui inactivity time in seconds before the session expires	false	integer

Set System Config

PUT /web/api/v2.1/system/configuration

Change the system configuration.

Before you run this, see Get System Config.

This command requires a Global Admin user or Support.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set System Config - response - data table
errors	Errors	false	array

Set System Config - response - data

Name	Description	Required	Value
accessibleUrl	External DNS name of the management	false	string
advancedMode	True if advanced mode is enabled.	false	boolean
advancedModeAllowChanges	True if advanced mode value can be updated from this scope.	false	boolean
allowDuplicateSite	[DEPRECATED] Allow site admins to duplicate sites in their accounts	false	boolean
allowedDomains	list of allowed domains for user creation.	false	see Set System Config - response - allowedDomains table
cloudIntelligenceOn	[DEPRECATED] Cloud intelligence on	false	boolean
cloudLastConnectionTime	Cloud last connection time	false	string
earlyAccess	True if early access mode is enabled.	false	boolean
earlyAccessPlatforms	Early access platforms	false	string []
globalSalesforceId	salesforce id field of tenant	false	string
globalSharedConsole	shared console field of tenant	false	boolean
globalTwoFaEnabled	Global two fa enabled	false	boolean
licenses	List of available licenses	false	see Set System Config - response - licenses table
maxCompleteLicenses	[DEPRECATED] Complete Licenses	false	integer
maxControlLicenses	[DEPRECATED] Control licenses	false	integer
maxCoreLicenses	[DEPRECATED] Core licenses	false	integer
passwordExpiration	Time in days until a user password expires	false	integer
passwordExpirationRange	Password expiration range (read-only)	false	see Set System Config - response - passwordExpirationRange table
region	The region of the management	false	string
rememberMeLength	Time in minutes until a user session expires	false	integer
rememberMeLengthRange	Remember me length range	false	see Set System Config - response - rememberMeLengthRange table
scalyrUrl	The Scalyr URL that sends data to this Console.	false	string
tfaEnrollmentExpiration	2FA enrollment expiration period	false	integer

uilnactivityTimeoutSeconds	Length of UI inactivity period	false	integer
uilnactivityTimeoutSecondsRange	UI inactivity timeout range	false	see Set System Config - response - uilnactivityTimeoutSecondsRange table
unlimitedComplete	[DEPRECATED] True if Complete licenses is unlimited	false	boolean
unlimitedControl	[DEPRECATED] True if Control licenses is unlimited	false	boolean
unlimitedCore	[DEPRECATED] True if Core licenses is unlimited	false	boolean

Set System Config - response - allowedDomains

Name	Description	Required	Value
domain	Allowed domain name for user creation.	false	string
inherited	True if this is an inherited domain	false	boolean

Set System Config - response - licenses

Name	Description	Required	Value
bundles	The licenses Bundles	false	see Set System Config - response - bundles table
modules	The licenses Add-ons	false	see Set System Config - response - modules table
settings	The licenses Settings	false	see Set System Config - response - settings table

Set System Config - response - bundles

Name	Description	Required	Value
displayName	The Bundle display name	false	string
majorVersion	The Bundle major version	false	integer
minorVersion	The Bundle minor version	false	integer
name	The Bundle internal api name	false	string
surfaces	The Surfaces in the Bundle	false	see Set System Config - response - surfaces table
totalSurfaces	The total number of Surfaces in this	false	integer

	Bundle. -1 indicates unlimited count.		
--	---------------------------------------	--	--

Set System Config - response - surfaces

Name	Description	Required	Value
count	The Surface count. -1 indicates unlimited count	false	integer
name	The Surface name.	false	string

Set System Config - response - modules

Name	Description	Required	Value
displayName	The Add-on display name	false	string
majorVersion	The Add-on major version	false	integer
name	The Add-on internal api name	false	string

Set System Config - response - settings

Name	Description	Required	Value
displayName	[DEPRECATED] The Setting display name	false	string
groupName	The Setting group name	false	
setting	The Setting display name	false	
settingGroup	[DEPRECATED] The Setting group name	false	string
settingGroupDisplayName	The Setting group display name	false	string

Set System Config - response - passwordExpirationRange

Name	Description	Required	Value
max	Maximum time in days until a user	false	integer

	password expires		
min	Minimum time in days until a user password expires	false	integer

Set System Config - response - rememberMeLengthRange

Name	Description	Required	Value
max	Maximum time interval in minutes before the session expires	false	integer
min	Minimum time interval in minutes before the session expires	false	integer

Set System Config - response - uiInactivityTimeoutSecondsRange

Name	Description	Required	Value
max	Maximum ui inactivity time in seconds before the session expires	false	integer
min	Minimum ui inactivity time in seconds before the session expires	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Set System Config - body - data table
filter	Filter section determines the configuration scope. Provide a site ID or leave empty for global configuration.	true	see Set System Config - body - filter table

Set System Config - body - data

Name	Description	Required	Value
accessibleUrl	External DNS name of the management	false	string
advancedMode	Advanced mode	false	boolean
allowDuplicateSite	[DEPRECATED] Allow site admins to duplicate sites in their accounts	false	boolean
allowedDomains	list of allowed domains for user creation.	false	see Set System Config - body - allowedDomains table
cloudIntelligenceOn	[DEPRECATED] Cloud intelligence on	false	boolean
cloudLastConnectionTime	Cloud last connection time	false	string
earlyAccess	Early access	false	boolean
earlyAccessPlatforms	Early access platforms	false	string []
globalTwoFaEnabled	Global two fa enabled	false	boolean
passwordExpiration	Time in days until a user password expires	false	integer
rememberMeLength	Time in minutes until a user session expires	false	integer
tfaEnrollmentExpiration	2FA expiration period	false	integer
uiInactivityTimeoutSeconds	Length of UI inactivity period	false	integer

Set System Config - body - allowedDomains

Name	Description	Required	Value
domain	Allowed domain name for user creation.	false	string
inherited	True if this is an inherited domain	false	boolean

Set System Config - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

System Environment

GET /web/api/v2.1/system/env

Get environment details of the system

Response Messages

200 - Success

Response Schema

Name	Description	Required	Value
data	Response data	false	see System Environment - response - data table
errors	Errors	false	array

System Environment - response - data

Name	Description	Required	Value
env	Env	false	string
isProd	Is prod	false	boolean
url	Url	false	string

Tag Manager

Create a new endpoint tag

POST /web/api/v2.1/tag-manager

Each tag must contain a type (endpoints) and key, Value is optional but recommended. A description is optional.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create a new endpoint tag - response - data table
errors	Errors	false	array

Create a new endpoint tag - response - data

Name	Description	Required	Value
createdAt	Created at	false	string
createdByld	A reference to the user which created the tag	false	string
description	Description	false	string
id	Tag ID	false	string
key	Key	false	string
scopeId	An ID reference to the containing scope	false	string
scopeLevel	Name of scope	false	string
type	e.g: manual-tagging	false	string
updatedAt	Updated at	false	string
updatedByld	A reference to the user which updated the tag	false	string
value	Value	false	string

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Create a new endpoint tag - body - filter table
data	Data	false	see Create a new endpoint tag - body - data table

Create a new endpoint tag - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Create a new endpoint tag - body - data

Name	Description	Required	Value
key	Key	true	string
type	Type	true	string
value	Value	true	string
description	Description	false	string

Delete tags

DELETE /web/api/v2.1/tag-manager

Delete all tags that match the filters.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Delete tags - response - data table
errors	Errors	false	array

Delete tags - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Delete tags - body - filter table

Delete tags - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
includeChildren	Return tags from children scope levels	false	boolean
includeParents	Return tags from parent scope levels	false	boolean
query	Free text search on fields key, value, description	false	string
siteIds	List of Site IDs to filter by	false	string []
tagIds	List of tag IDs	false	string []
tagIdsExcluded	List of tag IDs to exclude	false	string []
tenant	Indicates a tenant scope request	false	boolean

Edit an existing tag

PUT /web/api/v2.1/tag-manager/{tag_id}

Change the key, value, or description of a tag.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Edit an existing tag - response - data table
errors	Errors	false	array

Edit an existing tag - response - data

Name	Description	Required	Value
createdAt	Created at	false	string
createdById	A reference to the user which created the tag	false	string
description	Description	false	string
id	Tag ID	false	string
key	Key	false	string
scopeId	An ID reference to the containing scope	false	string
scopeLevel	Name of scope	false	string
type	e.g: manual-tagging	false	string
updatedAt	Updated at	false	string
updatedById	A reference to the user which updated the tag	false	string
value	Value	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Edit an existing tag - body - data table

Edit an existing tag - body - data

Name	Description	Required	Value
description	Description	false	string
key	Key	false	string
value	Value	false	string

Tags

Get Tags

GET /web/api/v2.1/tags

Get tags.

Parameters

type	required	Type in. Example: "firewall".
accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
disablepagination	optional	If true, all tags for requested filters will be returned
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
ids	optional	List of IDs to filter by. Example: "225494730938493804,225494730938493915".
kind	optional	Returns tags of this specific kind
limit	optional	Limit number of returned items (1-1000). Example: "10".

name__contains	optional	Free-text filter by tag name. Example: "tag_name,tag_na".
onlyparents	optional	If true returns all tags possible to inherit from parent scopes, otherwise returns all tags already inherited and tags from this scope.
query	optional	Free text search on tag name
scope	optional	Return tags from given scope level. Example: "account".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Tags - response - pagination table
data	Response data	false	see Get Tags - response - data table
errors	Errors	false	array

Get Tags - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Tags - response - data

Name	Description	Required	Value
type	Type	true	enum
affectedScopes	Affected scopes	false	integer
createdAt	Timestamp of site creation	false	string
creator	Location creator name	false	string
creatorId	Location creator ID	false	string
description	Description	false	string
id	Id	false	string
kind	Kind is a MGMT side indication to categorize special tags like `vulnerability`	false	string
linkedRules	Linked rules	false	integer
name	Name	false	string
scope	Scope	false	enum
scopeId	Scope id	false	string
scopeName	Scope name	false	string
updatedAt	Timestamp of last update	false	string
updater	Location updater name	false	string
updaterId	Location updater	false	string

Create Tags

POST /web/api/v2.1/tags

Add tags to create user-defined logical groups.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Tags - response - data table
errors	Errors	false	array

Create Tags - response - data

Name	Description	Required	Value
type	Type	true	enum
affectedScopes	Affected scopes	false	integer
createdAt	Timestamp of site creation	false	string
creator	Location creator name	false	string
creatorId	Location creator ID	false	string
description	Description	false	string
id	Id	false	string
kind	Kind is a MGMT side indication to categorize special tags like `vulnerability`	false	string
linkedRules	Linked rules	false	integer
name	Name	false	string
scope	Scope	false	enum
scopeId	Scope id	false	string
scopeName	Scope name	false	string
updatedAt	Timestamp of last update	false	string
updater	Location updater name	false	string
updaterId	Location updater	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Tags - body - data table
filter	Filter	true	see Create Tags - body - filter table

Create Tags - body - data

Name	Description	Required	Value
name	Name	true	string
type	Type	true	enum
description	Description	false	string
id	Id	false	string
kind	Kind	false	string

Create Tags - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Delete Tags

DELETE /web/api/v2.1/tags

Delete tags by given filter.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Tags - response - data table
errors	Errors	false	array

Delete Tags - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	false	see Delete Tags - body - filter table

Delete Tags - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
ids	List of IDs to filter by	false	string []
kind	Returns tags of this specific kind	false	string
name__contains	Free-text filter by tag name	false	string []
onlyParents	If true returns all tags possible to inherit from parent scopes, otherwise returns all tags already inherited and tags from this scope.	false	boolean
query	Free text search on tag name	false	string
scope	Return tags from given scope level	false	enum
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean
type	Type in	false	string []

Delete Tag by ID

DELETE /web/api/v2.1/tags/{tag_id}

Delete tag by ID.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Tag by ID - response - data table

errors	Errors	false	array
--------	--------	-------	-------

Delete Tag by ID - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Edit Tag

PUT /web/api/v2.1/tags/{tag_id}

Edit tag

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Edit Tag - response - data table
errors	Errors	false	array

Edit Tag - response - data

Name	Description	Required	Value
type	Type	true	enum
affectedScopes	Affected scopes	false	integer
createdAt	Timestamp of site creation	false	string
creator	Location creator name	false	string
creatorId	Location creator ID	false	string
description	Description	false	string
id	Id	false	string
kind	Kind is a MGMT side indication to categorize special tags like `vulnerability`	false	string
linkedRules	Linked rules	false	integer
name	Name	false	string
scope	Scope	false	enum
scopeId	Scope id	false	string
scopeName	Scope name	false	string
updatedAt	Timestamp of last update	false	string
updater	Location updater name	false	string
updaterId	Location updater	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Edit Tag - body - data table

Edit Tag - body - data

Name	Description	Required	Value
description	Description	false	string
id	Id	false	string
kind	Kind	false	string
name	Name	false	string

Tasks

Get Task Configuration

GET /web/api/v2.1/tasks-configuration

Get the task configuration of a scope.

Parameters

tasktype	required	Task type. Example: "agents_upgrade".
accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000

		items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

404 - Configuration not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Task Configuration - response - data table
errors	Errors	false	array

Get Task Configuration - response - data

Name	Description	Required	Value
inheritParentConcurrencyConfig	Inherit parent's scope Max Concurrent configuration	true	boolean
inheritParentMaintenanceConfig	Inherit parent's scope Maintenance windows configuration	true	boolean
maxConcurrent	Max concurrent	true	integer
timezoneGmt	Timezone gmt	true	string
concurrencyConfigUpdatedAt	Timestamp of last concurrency configuration update	false	string
concurrencyConfigUpdatedBy	User name of last updated concurrency configuration	false	string
maintenanceConfigUpdatedAt	Timestamp of last maintenance configuration update	false	string
maintenanceConfigUpdatedBy	User name of last updated maintenance configuration	false	string
maintenanceWindowsByDay	Stores the maintenance time for each day	false	object
parentMaxConcurrent	scope's parent max concurrent limit, must not exceed	false	integer
policyPayload	Flexible maintenance window policy (returned when set)	false	object
taskType	Defines task's type and priority	false	enum

Create Task

PUT /web/api/v2.1/tasks-configuration

Create a task configuration.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Operation is not allowed

404 - Configuration not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Task - response - data table
errors	Errors	false	array

Create Task - response - data

Name	Description	Required	Value
inheritParentConcurrencyConfig	Inherit parent's scope Max Concurrent configuration	true	boolean
inheritParentMaintenanceConfig	Inherit parent's scope Maintenance windows configuration	true	boolean
maxConcurrent	Max concurrent	true	integer
timezoneGmt	Timezone gmt	true	string
concurrencyConfigUpdatedAt	Timestamp of last concurrency configuration update	false	string
concurrencyConfigUpdatedBy	User name of last updated concurrency configuration	false	string
maintenanceConfigUpdatedAt	Timestamp of last maintenance configuration update	false	string
maintenanceConfigUpdatedBy	User name of last updated maintenance configuration	false	string
maintenanceWindowsByDay	Stores the maintenance time for each day	false	object
parentMaxConcurrent	scope's parent max concurrent limit, must not exceed	false	integer
policyPayload	Flexible maintenance window policy (returned when set)	false	object
taskType	Defines task's type and priority	false	enum

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Task - body - data table
filter	Filter	true	see Create Task - body - filter table

Create Task - body - data

Name	Description	Required	Value
inheritParentConcurrencyConfig	Inherit parent's scope Max Concurrent configuration	true	boolean
inheritParentMaintenanceConfig	Inherit parent's scope Maintenance windows configuration	true	boolean
maxConcurrent	Max concurrent	true	integer
timezoneGmt	Timezone gmt	true	string
maintenanceWindowsByDay	Stores the maintenance time for each day	false	object

Create Task - body - filter

Name	Description	Required	Value
taskType	Defines task's type and priority	true	enum
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Get Task Configuration (Flexible MW)

GET /web/api/v2.1/tasks-configuration/flexible

Get task configuration with flexible maintenance window format. Returns policy_payload when flexible MW is configured.

Parameters

tasktype	required	Task type. Example: "agents_upgrade".
accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
groupids	optional	List of Group IDs to filter by. Example:

		"225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

404 - Configuration not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Task Configuration (Flexible MW) - response - data table
errors	Errors	false	array

Get Task Configuration (Flexible MW) - response - data

Name	Description	Required	Value
active	Active	false	boolean
concurrencyConfigUpdatedAt	Concurrency config updated at	false	string
concurrencyConfigUpdatedBy	Concurrency config updated by	false	string
end	End	false	
frequency	Frequency	false	string
inheritParentConcurrencyConfig	Inherit parent concurrency config	false	boolean
inheritParentMaintenanceConfig	Inherit parent maintenance config	false	boolean
interval	Interval	false	integer
maintenanceConfigUpdatedAt	Maintenance config updated at	false	string
maintenanceConfigUpdatedBy	Maintenance config updated by	false	string
maxConcurrent	Max concurrent	false	integer
parentMaxConcurrent	Parent max concurrent	false	integer
rules	Rules	false	
startsOn	Starts on	false	string
taskType	Task type	false	enum
timezone	Timezone	false	string

Update Task Configuration (Flexible MW)

PUT /web/api/v2.1/tasks-configuration/flexible

Update task configuration with flexible maintenance window format. Requires mw_aup_advanced_flexibility or mw_lsu_advanced_flexibility global switch.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Operation is not allowed or feature not enabled

404 - Configuration not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Task Configuration (Flexible MW) - response - data table
errors	Errors	false	array

Update Task Configuration (Flexible MW) - response - data

Name	Description	Required	Value
active	Active	false	boolean
concurrencyConfigUpdatedAt	Concurrency config updated at	false	string
concurrencyConfigUpdatedBy	Concurrency config updated by	false	string
end	End	false	
frequency	Frequency	false	string
inheritParentConcurrencyConfig	Inherit parent concurrency config	false	boolean
inheritParentMaintenanceConfig	Inherit parent maintenance config	false	boolean
interval	Interval	false	integer
maintenanceConfigUpdatedAt	Maintenance config updated at	false	string
maintenanceConfigUpdatedBy	Maintenance config updated by	false	string
maxConcurrent	Max concurrent	false	integer
parentMaxConcurrent	Parent max concurrent	false	integer
rules	Rules	false	
startsOn	Starts on	false	string
taskType	Task type	false	enum
timezone	Timezone	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Task Configuration (Flexible MW) - body - data table
filter	Filter	true	see Update Task Configuration (Flexible MW) - body - filter table

Update Task Configuration (Flexible MW) - body - data

Name	Description	Required	Value
end	End configuration	true	see Update Task Configuration (Flexible MW) - body - end table
frequency	Policy frequency: daily, weekly, monthly, yearly, custom	true	enum
inheritParentConcurrencyConfig	Inherit parent's scope Max Concurrent configuration	true	boolean
inheritParentMaintenanceConfig	Inherit parent's scope Maintenance windows configuration	true	boolean
maxConcurrent	Max concurrent tasks	true	integer
timezone	IANA timezone identifier (e.g., 'America/New_York')	true	string
active	Whether the maintenance window is active	false	boolean
interval	Policy-level recurrence interval	false	integer
rules	Maintenance rules	false	see Update Task Configuration (Flexible MW) - body - rules table
startsOn	Policy start date in ISO format (computed for custom if omitted)	false	string

Update Task Configuration (Flexible MW) - body - end

Name	Description	Required	Value
mode	End mode: never, on_date, or after_count	true	enum
maxOccurrences	Max occurrences (required when mode=after_count)	false	integer
onDate	End date in ISO format (required when mode=on_date)	false	string

Update Task Configuration (Flexible MW) - body - rules

Name	Description	Required	Value
absolute	Absolute date-time window	false	see Update Task Configuration (Flexible MW) - body - absolute table
byMonth	Months: 1..12	false	integer []
byMonthDay	Days of month: 1..31 or -1..-31	false	integer []
bySetPos	Set position: e.g., [1]=1st, [-1]=last	false	integer []
byWeekday	Days of week: 0=Sun..6=Sat	false	integer []
effectiveEndOn	Rule effective end date in ISO format	false	string
effectiveStartOn	Rule effective start date in ISO format	false	string
frequency	Rule frequency (required for custom policy)	false	enum
interval	Repeat every N intervals	false	integer
timeWindows	Time windows for this rule	false	see Update Task Configuration (Flexible MW) - body - timeWindows table

Update Task Configuration (Flexible MW) - body - absolute

Name	Description	Required	Value
endAt	End datetime in YYYY-MM-DDTHH:MM format	true	string
startAt	Start datetime in YYYY-MM-DDTHH:MM format	true	string

Update Task Configuration (Flexible MW) - body - timeWindows

Name	Description	Required	Value
end	End time in HH:MM (24h) or HH:MM am/pm (12h) format	true	string
start	Start time in HH:MM (24h) or HH:MM am/pm (12h) format	true	string

Update Task Configuration (Flexible MW) - body - filter

Name	Description	Required	Value
------	-------------	----------	-------

taskType	Defines task's type and priority	true	enum
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Has Child Scopes

GET /web/api/v2.1/tasks-configuration/has-explicit-subscope

From a given scope, see if there are scopes under it that have local, explicit tasks. The response returns True if a sub-scope has a local (not inherited) task configuration.

Parameters

tasktype	required	Task type. Example: "agents_upgrade".
accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

404 - Configuration not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Has Child Scopes - response - data table
errors	Errors	false	array

Has Child Scopes - response - data

Name	Description	Required	Value
flag	Returns boolean value for the request	false	boolean

Get Child Scope Task Configuration

GET /web/api/v2.1/tasks-configuration/explicit-subscopes

Get the task configuration of child scopes of the given scope, if the tasks are not inherited.

Parameters

tasktype	required	Task type. Example: "agents_upgrade".
accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".
query	optional	Query
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed in this scope

404 - Configuration not found

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Child Scope Task Configuration - response - pagination table
data	Response data	false	see Get Child Scope Task Configuration - response - data table
errors	Errors	false	array

Get Child Scope Task Configuration - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Child Scope Task Configuration - response - data

Name	Description	Required	Value
accountId	Account id	false	string
accountName	Account name	false	string
groupId	Group id	false	string
groupName	Group name	false	string
siteId	Site id	false	string
siteName	Site name	false	string

Export Maintenance Windows as CSV

GET /web/api/v2.1/tasks-configuration/maintenance-windows/export

Export all maintenance window occurrences for a specific scope as CSV. Only supports flexible (policy_payload) maintenance window format. Date range: policies with end dates generate up to that date; policies with no end date generate for 5 years from start date. Returns a CSV file with columns: Date, Start Time, End Time. Maximum report size: 5MB.

Parameters

tasktype	required	Task type. Example: "agents_upgrade".
accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
groupids	optional	List of Group IDs to filter by. Example:

		"225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - CSV file with maintenance windows

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

404 - Configuration not found

500 - Report exceeds maximum size

Threat Intelligence

Get IOCs

GET /web/api/v2.1/threat-intelligence/iocs

Get the IOCs of a specified Account that match the filter.

Note: Using creationTime to sort results has been deprecated and should not be used. In the future, the ability to sort by creationTime will be removed. Please sort by uploadTime or updatedAt as an alternative.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "4,2,6,4,1,8,0,3,0,2,1,2,0,7,3,7,6,2".
batchid	optional	Unique ID of the uploaded indicators batch. Example: "atmtn000000028a881bcf939dc6d92ab55443".
campaignnames__in	optional	List of campaign names associated with the indicator.

category__in	optional	The categories of the Threat Intelligence indicator, e.g. the malware type associated with the IOC
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
creationtime__gt	optional	Creation Time as set by the user greater than. Example: "2021-07-12T20:33:29.007906Z".
creationtime__gte	optional	Creation Time as set by the user greater or equal than. Example: "2021-07-13T20:33:29.007906Z".
creationtime__lt	optional	Creation Time as set by the user lesser than. Example: "2021-07-13T20:33:29.007906Z".
creationtime__lte	optional	Creation Time as set by the user lesser or equal than. Example: "2021-07-11T20:33:29.007906Z".
creator__contains	optional	Free-text filter by the user uploaded the Threat Intelligence indicator (supports multiple values). Example: "admin@sentinelone.com".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
description__contains	optional	Free-text filter by the description of the indicator (supports multiple values). Example: "Malicious-activity".
externalid	optional	The unique identifier of the indicator as provided by the Threat Intelligence source. Example: "e277603e-1060-5ad4-9937-c26c97f1ca68".
labels__in	optional	List of labels associated with the indicator.
limit	optional	Limit number of returned items (1-1000). Example: "10".
malwarenames__in	optional	A list of malware names to filter by.
name__contains	optional	Free-text filter by the Indicator name (supports multiple values). Example: "foo.dll".
severity	optional	A list of severities to filter by (0-7)
siteids	optional	List of Site IDs to filter by. Example: "4,2,6,4,1,8,0,3,0,2,1,2,0,7,3,7,6,2".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.

sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
source	optional	List of the sources of the identified Threat Intelligence indicator. Example: "AlienVault".
tenant	optional	Indicates a tenant scope request
threatactors__in	optional	A list of threat actors to filter by
threatactortypes__in	optional	List of threat actor types associated with the indicator.
type	optional	The type of the Threat Intelligence indicator. Example: "IPv4".
updatedat__gt	optional	The time at which the indicator was last updated in SentinelOne DB greater than. Example: "2021-07-13T20:33:29.007906Z".
updatedat__gte	optional	The time at which the indicator was last updated in SentinelOne DB greater or equal than. Example: "2021-07-13T20:33:29.007906Z".
updatedat__lt	optional	The time at which the indicator was last updated in SentinelOne DB lesser than. Example: "2021-07-13T20:33:29.007906Z".
updatedat__lte	optional	The time at which the indicator was last updated in SentinelOne DB lesser or equal than. Example: "2021-07-13T20:33:29.007906Z".
uploadtime__gt	optional	The time at which the Threat Intelligence indicator was uploaded to SentinelOne DB greater than. Example: "2022-07-13T20:33:29.007906Z".
uploadtime__gte	optional	The time at which the Threat Intelligence indicator was uploaded to SentinelOne DB greater or equal than. Example: "2022-07-13T20:33:29.007906Z".
uploadtime__lt	optional	The time at which the Threat Intelligence indicator was uploaded to SentinelOne DB lesser than. Example: "2021-07-13T20:33:29.007906Z".
uploadtime__lte	optional	The time at which the Threat Intelligence indicator was uploaded to SentinelOne DB lesser or equal than. Example: "2022-07-13T20:33:29.007906Z".
uuids	optional	A list of unique Ids of the parent process of the indicator of compromise. Example: "2,c,f,f,a,e,8,7,1,1,9,7,f,2,0,d,8,6,4,f,e,8,3,6,3,e,e,e,6,6,5,1".
value	optional	The value of the Threat Intelligence indicator. Example: "175.45.176.1".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get IOCs - response - pagination table
data	Response data	false	see Get IOCs - response - data table
errors	Errors	false	array

Get IOCs - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get IOCs - response - data

Name	Description	Required	Value
source	The source of the identified Threat Intelligence indicator	true	string
type	The type of the Threat Intelligence indicator	true	enum
value	The value of the Threat Intelligence indicator	true	string
batchId	Unique ID of the uploaded Threat Intelligence indicators batch	false	string
campaignNames	Campaign names	false	string []
category	Category	false	string []
creationTime	The time at which the Threat Intelligence indicator was originally created (as indicated by the TI source)	false	string
creator	The user that uploaded the Threat Intelligence indicator	false	string
description	Description of the Threat Intelligence indicator	false	string
externalId	The unique identifier of the indicator as provided by the Threat Intelligence source	false	string
intrusionSets	Intrusion sets	false	string []

labels	Labels	false	string []
malwareNames	Malware names	false	string []
metadata	The metadata of the Threat Intelligence indicator	false	string
method	The comparison method used by SentinelOne to trigger the event	false	enum
mitreTactic	Mitre tactic	false	string []
name	Threat Intelligence indicator name	false	string
originalRiskScore	The relative level of risk associated with the Threat Intelligence indicator. An integer between 0 and 100, inclusive.	false	integer
parentScopeld	The Account id under which the Site is defined. null if it is Global or Account.	false	string
pattern	The detection pattern for this Indicator (expressed as a STIX Pattern, e.g. Comparison expression/ Boolean Operators etc.)	false	string
patternType	Characterize the pattern language that the indicator pattern is expressed in	false	string
reference	Reference	false	string []
scope	Scope of the IoC	false	enum
scopeld	The Group/Site/Account id depending on the Scope. null if it is Global.	false	string
severity	The potential impact of the Threat Intelligence indicator. Designed to work based on OCSF format for scores 0-7.	false	integer
threatActors	Threat actors	false	string []
threatActorTypes	Threat actor types	false	string []
updatedAt	The time at which the indicator was last updated in SentinelOne DB	false	string
uploadTime	The time at which the Threat Intelligence indicator was uploaded to SentinelOne DB	false	string

uuid	Unique Id of the Threat Intelligence indicator	false	string
validUntil	The date from which the indicator will no longer be monitored	false	string

Create IOCs

POST /web/api/v2.1/threat-intelligence/iocs

Add an IoC to the Threat Intelligence database.

These values under data are required fields: "source", "type", "value", and "method".

"Type" and "method" must be in upper case.

The "validUntil" field is mandatory, and must contain a date, for example, 2021-03-20 09:14:47.779000. "validUntil" determines when the IOC expires.

If the expiration date ("validUntil") is left blank, by default it will be the upload date plus a default offset value:

- 14 days for IPs
- 90 days for URLs and domains
- 180 days for file hashes (SHA1, SHA256, and MD5)

The maximum offset values allowed are:

- 30 days for IPs
- 180 days for URLs and Domains
- 180 days for hashes (SHA1, SHA256, and MD5)

The upload date is when the API gets a request to create an IOC.

If the expiration date is later than the upload date plus the the maximum offset value allowed, it will be adjusted to the upload date plus the maximum offset value allowed.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create IOCs - response - data table
errors	Errors	false	array

Create IOCs - response - data

Name	Description	Required	Value
source	The source of the identified Threat Intelligence indicator	true	string
type	The type of the Threat Intelligence indicator	true	enum
value	The value of the Threat Intelligence indicator	true	string
batchId	Unique ID of the uploaded Threat Intelligence indicators batch	false	string
campaignNames	Campaign names	false	string []
category	Category	false	string []
creationTime	The time at which the Threat Intelligence indicator was originally created (as indicated by the TI source)	false	string
creator	The user that uploaded the Threat Intelligence indicator	false	string
description	Description of the Threat Intelligence indicator	false	string
externalId	The unique identifier of the indicator as provided by the Threat Intelligence source	false	string
intrusionSets	Intrusion sets	false	string []
labels	Labels	false	string []
malwareNames	Malware names	false	string []
metadata	The metadata of the Threat Intelligence indicator	false	string
method	The comparison method used by SentinelOne to trigger the event	false	enum
mitreTactic	Mitre tactic	false	string []
name	Threat Intelligence indicator name	false	string
originalRiskScore	The relative level of risk associated with the Threat Intelligence indicator. An integer between 0 and 100,	false	integer

	inclusive.		
parentScopeld	The Account id under which the Site is defined. null if it is Global or Account.	false	string
pattern	The detection pattern for this Indicator (expressed as a STIX Pattern, e.g. Comparison expression/ Boolean Operators etc.)	false	string
patternType	Characterize the pattern language that the indicator pattern is expressed in	false	string
reference	Reference	false	string []
scope	Scope of the IoC	false	enum
scopeld	The Group/Site/Account id depending on the Scope. null if it is Global.	false	string
severity	The potential impact of the Threat Intelligence indicator. Designed to work based on OCSF format for scores 0-7.	false	integer
threatActors	Threat actors	false	string []
threatActorTypes	Threat actor types	false	string []
updatedAt	The time at which the indicator was last updated in SentinelOne DB	false	string
uploadTime	The time at which the Threat Intelligence indicator was uploaded to SentinelOne DB	false	string
uuid	Unique Id of the Threat Intelligence indicator	false	string
validUntil	The date from which the indicator will no longer be monitored	false	string

Body Schema

Name	Description	Required	Value
data	Data	false	see Create IOCs - body - data table
filter	Filter	false	see Create IOCs - body - filter table

Create IOCs - body - data

Name	Description	Required	Value
source	The source of the identified Threat Intelligence indicator	true	string
type	The type of the Threat Intelligence indicator	true	enum
value	The value of the Threat Intelligence indicator	true	string
campaignNames	Campaign names	false	string []
category	Category	false	string []
creationTime	The time at which the Threat Intelligence indicator was originally created (as indicated by the TI source)	false	string
creator	The user that uploaded the Threat Intelligence indicator	false	string
description	Description of the Threat Intelligence indicator	false	string
externalId	The unique identifier of the indicator as provided by the Threat Intelligence source	false	string
intrusionSets	Intrusion sets	false	string []
labels	Labels	false	string []
malwareNames	Malware names	false	string []
metadata	The metadata of the Threat Intelligence indicator	false	string
method	The comparison method used by SentinelOne to trigger the event	false	enum
mitreTactic	Mitre tactic	false	string []
name	Threat Intelligence indicator name	false	string
originalRiskScore	The relative level of risk associated with the Threat Intelligence indicator. An integer between 0 and 100, inclusive.	false	integer
pattern	The detection pattern for this Threat	false	string

	Intelligence indicator (expressed as a STIX Pattern, e.g. Comparison expression/Boolean Operators etc.)		
patternType	Characterize the pattern language that the Threat Intelligence indicator pattern is expressed in	false	
reference	Reference	false	string []
severity	The potential impact of the Threat Intelligence indicator. Designed to work based on OCSF format for scores 0-7.	false	integer
threatActors	Threat actors	false	string []
threatActorTypes	Threat actor types	false	string []
validUntil	Expiration date for the Threat Intelligence indicator	false	string

Create IOCs - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Delete IOCs

DELETE /web/api/v2.1/threat-intelligence/iocs

Delete an IoC from the Threat Intelligence database that matches a filter using the accountID and one other field.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete IOCs - response - data table
errors	Errors	false	array

Delete IOCs - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Delete IOCs - body - filter table

Delete IOCs - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
batchId	Unique ID of the uploaded indicators batch	false	string
campaignNames__in	List of campaign names associated with the indicator.	false	string []
category__in	The categories of the Threat Intelligence indicator, e.g. the malware type associated with the IOC	false	string
creationTime__gt	Creation Time as set by the user greater than	false	string
creationTime__gte	Creation Time as set by the user greater or equal than	false	string
creationTime__lt	Creation Time as set by the user lesser than	false	string
creationTime__lte	Creation Time as set by the user lesser or equal than	false	string
creator__contains	Free-text filter by the user uploaded the Threat Intelligence indicator (supports multiple values)	false	string []
description__contains	Free-text filter by the description of the indicator (supports multiple values)	false	string []
externalId	The unique identifier of the indicator as provided by the Threat Intelligence source	false	string
labels__in	List of labels associated with the indicator.	false	string []
malwareNames__in	A list of malware names to filter by.	false	string []
name__contains	Free-text filter by the Indicator name (supports multiple values)	false	string []
severity	A list of severities to filter by (0-7)	false	integer []
siteIds	List of Site IDs to filter by	false	string []

source	List of the sources of the identified Threat Intelligence indicator	false	string []
tenant	Indicates a tenant scope request	false	boolean
threatActors__in	A list of threat actors to filter by	false	string []
threatActorTypes__in	List of threat actor types associated with the indicator.	false	string []
type	The type of the Threat Intelligence indicator	false	enum
updatedAt__gt	The time at which the indicator was last updated in SentinelOne DB greater than	false	string
updatedAt__gte	The time at which the indicator was last updated in SentinelOne DB greater or equal than	false	string
updatedAt__lt	The time at which the indicator was last updated in SentinelOne DB lesser than	false	string
updatedAt__lte	The time at which the indicator was last updated in SentinelOne DB lesser or equal than	false	string
uploadTime__gt	The time at which the Threat Intelligence indicator was uploaded to SentinelOne DB greater than	false	string
uploadTime__gte	The time at which the Threat Intelligence indicator was uploaded to SentinelOne DB greater or equal than	false	string
uploadTime__lt	The time at which the Threat Intelligence indicator was uploaded to SentinelOne DB lesser than	false	string
uploadTime__lte	The time at which the Threat Intelligence indicator was uploaded to SentinelOne DB lesser or equal than	false	string
uuids	A list of unique Ids of the parent process of the indicator of compromise	false	string []
value	The value of the Threat Intelligence indicator	false	string

Create IOCs from STIX bundle

POST /web/api/v2.1/threat-intelligence/iocs/stix

Add IOCs to the Threat Intelligence database from a STIX 2.1 bundle. The API will transform STIX indicators into Threat Intelligence IOCs.

Must be a valid STIX 2.1 bundle containing indicator objects

Each indicator object should have a valid STIX pattern for one of these types:

-File hashes: [file:hashes.MD5 = ...], [file:hashes.SHA-1 = ...], [file:hashes.SHA-256 = ...]

-IP addresses: [ipv4-addr:value = ...]

-Domains: [domain-name:value = ...]

-URLs: [url:value = ...]

If the expiration date ("validUntil") is left blank, by default it will be the upload date plus a default offset value:

- 14 days for IPs

- 90 days for URLs and domains

- 180 days for file hashes (SHA1, SHA256, and MD5)

The maximum offset values allowed are:

- 30 days for IPs

- 180 days for URLs and Domains

- 180 days for hashes (SHA1, SHA256, and MD5)

The upload date is when the API gets a request to create an IOC.

If the expiration date is later than the upload date plus the the maximum offset value allowed, it will be adjusted to the upload date plus the maximum offset value allowed.

The API will also process these optional STIX relationships if present:

-Threat Actors (names and types)

-Malware names

-Campaign names

-Intrusion Sets

Other stix objects, or indicators with unsupported stix pattern, will be ignored.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create IOCs from STIX bundle - response - data table
errors	Errors	false	array

Create IOCs from STIX bundle - response - data

Name	Description	Required	Value
source	The source of the identified Threat Intelligence indicator	true	string
type	The type of the Threat Intelligence indicator	true	enum
value	The value of the Threat Intelligence indicator	true	string
batchId	Unique ID of the uploaded Threat Intelligence indicators batch	false	string
campaignNames	Campaign names	false	string []
category	Category	false	string []
creationTime	The time at which the Threat Intelligence indicator was originally created (as indicated by the TI source)	false	string
creator	The user that uploaded the Threat Intelligence indicator	false	string
description	Description of the Threat Intelligence indicator	false	string
externalId	The unique identifier of the indicator as provided by the Threat Intelligence source	false	string
intrusionSets	Intrusion sets	false	string []
labels	Labels	false	string []
malwareNames	Malware names	false	string []
metadata	The metadata of the Threat Intelligence indicator	false	string
method	The comparison method used by SentinelOne to trigger the event	false	enum
mitreTactic	Mitre tactic	false	string []
name	Threat Intelligence indicator name	false	string
originalRiskScore	The relative level of risk associated with the Threat Intelligence indicator. An integer between 0 and 100,	false	integer

	inclusive.		
parentScopeld	The Account id under which the Site is defined. null if it is Global or Account.	false	string
pattern	The detection pattern for this Indicator (expressed as a STIX Pattern, e.g. Comparison expression/ Boolean Operators etc.)	false	string
patternType	Characterize the pattern language that the indicator pattern is expressed in	false	string
reference	Reference	false	string []
scope	Scope of the IoC	false	enum
scopeld	The Group/Site/Account id depending on the Scope. null if it is Global.	false	string
severity	The potential impact of the Threat Intelligence indicator. Designed to work based on OCSF format for scores 0-7.	false	integer
threatActors	Threat actors	false	string []
threatActorTypes	Threat actor types	false	string []
updatedAt	The time at which the indicator was last updated in SentinelOne DB	false	string
uploadTime	The time at which the Threat Intelligence indicator was uploaded to SentinelOne DB	false	string
uuid	Unique Id of the Threat Intelligence indicator	false	string
validUntil	The date from which the indicator will no longer be monitored	false	string

Body Schema

Name	Description	Required	Value
bundle	Bundle	true	see Create IOCs from STIX bundle - body - bundle table
filter	Filter	false	see Create IOCs from STIX bundle - body - filter table

Create IOCs from STIX bundle - body - bundle

Name	Description	Required	Value
objects	List of STIX objects contained in the bundle	false	undefined []

Create IOCs from STIX bundle - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Get Threat Intelligence user config

GET /web/api/v2.1/threat-intelligence/user-config

Get the Threat Intelligence user config that match the filter.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "4,2,6,4,1,8,0,3,0,2,1,2,0,7,3,7,6,2".
siteids	optional	List of Site IDs to filter by. Example: "4,2,6,4,1,8,0,3,0,2,1,2,0,7,3,7,6,2".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Threat Intelligence user config - response - data table
errors	Errors	false	array

Get Threat Intelligence user config - response - data

Name	Description	Required	Value
createdAt	The time at which the user config was created in SentinelOne DB	true	string
updatedAt	The time at which the user config was last updated in SentinelOne DB	true	string
description	User defined description of the user config.	false	string
disableRh	The flag to disable Threat Intelligence RetroHunt feature.	false	boolean
disableThreat	The flag to disable Threat Intelligence Indicator based Threat creation for the entire account.	false	boolean
enableXdrMatching	The flag to enable XDR matching feature.	false	boolean
excludeTii	Exclude tii	false	string []
scopeId	The group/site/account id depending on the scope_level.	false	string
scopeLevel	Scope level of the user config	false	enum
threatExcludeFields	Threat exclude fields	false	string []
threatMinScore	The minimum score for a threat to be created.	false	integer

Create Threat Intelligence user config

POST /web/api/v2.1/threat-intelligence/user-config

Create Threat Intelligence user config.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create Threat Intelligence user config - response - data table
errors	Errors	false	array

Create Threat Intelligence user config - response - data

Name	Description	Required	Value
createdAt	The time at which the user config was created in SentinelOne DB	true	string
updatedAt	The time at which the user config was last updated in SentinelOne DB	true	string
description	User defined description of the user config.	false	string
disableRh	The flag to disable Threat Intelligence RetroHunt feature.	false	boolean
disableThreat	The flag to disable Threat Intelligence Indicator based Threat creation for the entire account.	false	boolean
enableXdrMatching	The flag to enable XDR matching feature.	false	boolean
excludeTii	Exclude tii	false	string []
scopeld	The group/site/account id depending on the scope_level.	false	string
scopeLevel	Scope level of the user config	false	enum
threatExcludeFields	Threat exclude fields	false	string []
threatMinScore	The minimum score for a threat to be created.	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Create Threat Intelligence user config - body - data table
filter	Filter	true	see Create Threat Intelligence user config - body - filter table

Create Threat Intelligence user config - body - data

Name	Description	Required	Value
description	User defined description of the user config.	false	string
disableRh	The flag to disable Threat Intelligence RetroHunt feature.	false	boolean
disableThreat	The flag to disable Threat Intelligence Indicator based Threat creation for the entire account.	false	boolean
enableXdrMatching	The flag to enable XDR matching feature.	false	boolean
excludeTii	Exclude tii	false	string []
threatExcludeFields	Threat exclude fields	false	string []
threatMinScore	The minimum score for a threat to be created.	false	integer

Create Threat Intelligence user config - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
groupIds	List of Group IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Delete Threat Intelligence user config

DELETE /web/api/v2.1/threat-intelligence/user-config

Delete Threat Intelligence user config that match the filter.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Threat Intelligence user config - response - data table
errors	Errors	false	array

Delete Threat Intelligence user config - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []
tenant	Indicates a tenant scope request	false	boolean

Threat Notes

Get Threat Notes

GET /web/api/v2.1/threats/{threat_id}/notes

Get the threat notes that match the filter.

Parameters

countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
creator__like	optional	Threat Note creator name (partially or full). Example: "John".
creatorid	optional	Threat Note creator ID. Example: "225494730938493804".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
limit	optional	Limit number of returned items (1-1000). Example: "10".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Threat Notes - response - pagination table
data	Response data	false	see Get Threat Notes - response - data table
errors	Errors	false	array

Get Threat Notes - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Threat Notes - response - data

Name	Description	Required	Value
createdAt	Timestamp of date creation	false	string
creator	Threat Note creator name	false	string
creatorId	Threat Note creator id	false	string
edited	Identify if the the note changed	false	boolean
id	Threat Note ID	false	string
text	Threat Note text	false	string
updatedAt	Timestamp of last update	false	string

Add Note to Multiple

POST /web/api/v2.1/threats/notes

Add a threat note to multiple threats.

Response Messages

200 - Threats note successfully created

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Add Note to Multiple - response - data table
errors	Errors	false	array

Add Note to Multiple - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer
details	Result details for each threat	false	see Add Note to Multiple - response - details table

Add Note to Multiple - response - details

Name	Description	Required	Value
threatId	Threat id	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Add Note to Multiple - body - data table
filter	Filter	true	see Add Note to Multiple - body - filter table

Add Note to Multiple - body - data

Name	Description	Required	Value
text	Threat Note text	true	string

Add Note to Multiple - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
agentIds	List of Agent IDs	false	string []
agentIsActive	Include Agents currently connected to the Management Console	false	boolean
agentMachineTypes	Include Agent machine types	false	string []
agentMachineTypesNin	Excluded Agent machine types	false	string []
agentTagsData	Filter threats by assigned tags to the related agent. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
agentVersions	Include Agent versions	false	string []
agentVersionsNin	Excluded Agent versions	false	string []
analystVerdicts	Filter threats by a specific analyst verdict	false	string []
analystVerdictsNin	Exclude threats with specific analyst verdicts	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []

azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
classifications	List of threat classifications to search	false	string []
classificationsNin	List of threat classifications not to search	false	string []
classificationSources	Classification sources list	false	string []
classificationSourcesNin	Classification sources list to exclude	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
collectionIds	List of collection IDs to search	false	string []
commandLineArguments__contains	Free-text filter by threat command line arguments (supports multiple values)	false	string []
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
confidenceLevels	Filter threats by a specific confidence level	false	string []
confidenceLevelsNin	Exclude threats with specific confidence level	false	string []
containerImageName__contains	Free-text filter by the endpoint container image name (supports multiple values)	false	string []
containerLabels__contains	Free-text filter by the endpoint container labels (supports multiple values)	false	string []

containerName__contains	Free-text filter by the endpoint container name (supports multiple values)	false	string []
contentHash__contains	Free-text filter by file content hash (supports multiple values)	false	string []
contentHashes	List of sha1 hashes to search for	false	string []
countsFor	comma-separated list of fields to be shown	false	string
createdAt__gt	Created at greater than.	false	string
createdAt__gte	Created at greater or equal than.	false	string
createdAt__lt	Created at lesser than.	false	string
createdAt__lte	Created at lesser or equal than.	false	string
detectionAgentDomain__contains	Free-text filter by Agent domain at detection time (supports multiple values)	false	string []
detectionAgentVersion__contains	Free-text filter by Agent version at detection time (supports multiple values)	false	string []
detectionEngines	Included engines	false	string []
detectionEnginesNin	Excluded engines	false	string []
displayName	Display name	false	string
engines	Included engines	false	string []
enginesNin	Excluded engines	false	string []
externalTicketExists	The threat contains ticket number	false	boolean
externalTicketId__contains	Free-text filter by the threat external ticket ID (supports multiple values)	false	string []
externalTicketIds	External ticket ID for the threat	false	string []
failedActions	At least one action failed on the threat	false	boolean
filePath__contains	Free-text filter by file path (supports multiple values)	false	string []
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasAgentTags	Include only Threats whose Agent is assigned any tags if True, or none if	false	boolean

	False		
ids	List of threat IDs	false	string []
incidentStatuses	Filter threats by a specific incident status	false	string []
incidentStatusesNin	Exclude threats with specific incident statuses	false	string []
initiatedBy	Only include threats from specific initiating sources	false	string []
initiatedByNin	Exclude threats with specific initiating sources	false	string []
initiatedByUsername__contains	Free-text filter by the username that initiated that threat (supports multiple values)	false	string []
k8sClusterName__contains	Free-text filter by the endpoint Kubernetes cluster name (supports multiple values)	false	string []
k8sControllerLabels__contains	Free-text filter by the endpoint Kubernetes controller labels (supports multiple values)	false	string []
k8sControllerName__contains	Free-text filter by the endpoint Kubernetes controller name (supports multiple values)	false	string []
k8sNamespaceLabels__contains	Free-text filter by the endpoint Kubernetes namespace labels (supports multiple values)	false	string []
k8sNamespaceName__contains	Free-text filter by the endpoint Kubernetes namespace name (supports multiple values)	false	string []
k8sNodeLabels__contains	Free-text filter by the endpoint Kubernetes node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by the endpoint Kubernetes node name (supports multiple values)	false	string []
k8sPodLabels__contains	Free-text filter by the endpoint Kubernetes pod labels (supports multiple values)	false	string []
k8sPodName__contains	Free-text filter by the endpoint Kubernetes pod name (supports multiple values)	false	string []

limit	Limit	false	integer
mitigatedPreemptively	If the threat was detected pre-execution or post-execution	false	boolean
mitigationStatuses	Filter threats by a specific status	false	string []
mitigationStatusesNin	Filter threats not by a specific status	false	string []
noteExists	The threat contains at least one note	false	boolean
originatedProcess__contains	Free-text filter by the originated process name of the threat (supports multiple values)	false	string []
osArchs	Included OS Architectures	false	string []
osNames		false	string []
osNamesNin		false	string []
osTypes	Included OS types	false	string []
osTypesNin	Excluded OS types	false	string []
pendingActions	At least one action is pending for the Agent for the threat	false	boolean
publisherName__contains	Free-text filter by threat's publisher name (supports multiple values)	false	string []
query	Full text search for fields: threat_details, content_hash, computer_name, file_path, uuid, detection_agent_version, realtime_agent_version, detection_agent_domain, command_line_arguments, initiated_by_username, storyline, originated_process, k8s_cluster_name, k8s_node_name, k8s_node_labels, k8s_namespace_name, k8s_namespace_labels, k8s_controller_name, k8s_controller_labels, k8s_pod_name, k8s_pod_labels, container_name, container_image_name, container_labels, external_ticket_id	false	string
realtimeAgentVersion__contains	Free-text filter by Agent version at current time (supports multiple values)	false	string []
rebootRequired	A reboot is required on any endpoint	false	boolean

	for at least one action on the threat		
resolved	This is used for backward-compatibility with API 2.0.	false	boolean
signerIdentity__contains	Free-text filter by threat's signer identity (certificate ID) (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storyline__contains	Free-text filter by threat storyline (supports multiple values)	false	string []
storylines	List of Agent context to search for	false	string []
tenant	Indicates a tenant scope request	false	boolean
threatDetails__contains	Free-text filter by threat details(supports multiple values)	false	string []
updatedAt__gt	Updated at greater than.	false	string
updatedAt__gte	Updated at greater or equal than.	false	string
updatedAt__lt	Updated at lesser than.	false	string
updatedAt__lte	Updated at lesser or equal than.	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []

Update Threat Note

PUT /web/api/v2.1/threats/{threat_id}/notes/{note_id}

Change the text of a threat note.

Response Messages

200 - Threat note successfully updated

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Update Threat Note - response - data table
errors	Errors	false	array

Update Threat Note - response - data

Name	Description	Required	Value
createdAt	Timestamp of date creation	false	string
creator	Threat Note creator name	false	string
creatorId	Threat Note creator id	false	string
edited	Identify if the the note changed	false	boolean
id	Threat Note ID	false	string
text	Threat Note text	false	string
updatedAt	Timestamp of last update	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Threat Note - body - data table

Update Threat Note - body - data

Name	Description	Required	Value
text	Threat Note text	true	string

Delete Threat Note

DELETE /web/api/v2.1/threats/{threat_id}/notes/{note_id}

Delete a threat note.

Response Messages

200 - Threat note successfully deleted

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Threat Note - response - data table
errors	Errors	false	array

Delete Threat Note - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Threats

Get Threats

GET /web/api/v2.1/threats

Get data of threats that match the filter.
Best Practice: Use the filters. Each threat gives a number of data lines that will quickly fill the page limit.

BEST PRACTICE

Use the filters. Each threat gives a number of data lines that will quickly fill the page limit.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
agentids	optional	List of Agent IDs. Example: "225494730938493804,225494730938493915".
agentisactive	optional	Include Agents currently connected to the Management Console
agentmachinetypes	optional	Include Agent machine types. Example: "unknown".
agentmachinetypesnin	optional	Excluded Agent machine types. Example: "unknown".
agenttagsdata	optional	Filter threats by assigned tags to the related agent. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key. Example: {"key1": ["value1_1", "value1_2"], "key2__nin": ["value2"]}
agentversions	optional	Include Agent versions. Example: "2.5.1.1320".

agentversionsnin	optional	Excluded Agent versions. Example: "2.5.1.1320".
analystverdicts	optional	Filter threats by a specific analyst verdict. Example: "true_positive,suspicious".
analystverdictsnin	optional	Exclude threats with specific analyst verdicts. Example: "true_positive,suspicious".
awsrole__contains	optional	Free-text filter by aws role(supports multiple values)
awssecuritygroups__contains	optional	Free-text filter by aws securityGroups(supports multiple values)
awssubnetids__contains	optional	Free-text filter by aws subnet ids (supports multiple values)
azureresourcegroup__contains	optional	Free-text filter by azure resource group(supports multiple values)
classifications	optional	List of threat classifications to search
classificationsnin	optional	List of threat classifications not to search
classificationsources	optional	Classification sources list. Example: "Cloud".
classificationsourcesnin	optional	Classification sources list to exclude. Example: "Cloud".
cloudaccount__contains	optional	Free-text filter by cloud account (supports multiple values)
cloudimage__contains	optional	Free-text filter by cloud image (supports multiple values)
cloudinstanceid__contains	optional	Free-text filter by cloud instance id(supports multiple values)
cloudinstancesize__contains	optional	Free-text filter by cloud instance size(supports multiple values)
cloudlocation__contains	optional	Free-text filter by cloud location (supports multiple values)
cloudnetwork__contains	optional	Free-text filter by cloud network (supports multiple values)
cloudprovider	optional	Agents from which cloud provider
cloudprovidernin	optional	Exclude Agents from these cloud provider
collectionids	optional	List of collection IDs to search. Example: "225494730938493804,225494730938493915".
commandlinearguments__contains	optional	Free-text filter by threat command line arguments (supports multiple values). Example: "/usr/sbin/,wget".

computername__contains	optional	Free-text filter by computer name (supports multiple values). Example: "john-office,WIN".
confidencelevels	optional	Filter threats by a specific confidence level. Example: "malicious".
confidencelevelsnin	optional	Exclude threats with specific confidence level. Example: "malicious".
containerimage__contains	optional	Free-text filter by the endpoint container image name (supports multiple values)
containerlabels__contains	optional	Free-text filter by the endpoint container labels (supports multiple values)
containername__contains	optional	Free-text filter by the endpoint container name (supports multiple values)
contenthash__contains	optional	Free-text filter by file content hash (supports multiple values). Example: "5f09bcff3".
contenthashes	optional	List of sha1 hashes to search for. Example: "d,d,d,5,0,3,0,a,3,d,0,2,9,f,3,8,4,5,f,c,1,0,5,2,4,1,9,8,2,9,f,0,8,f,3,1,2,2,4,0".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
countsfor	optional	comma-separated list of fields to be shown. Example: "osTypes,machineTypes".
createdat__gt	optional	Created at greater than. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Created at greater or equal than. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Created at lesser than. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Created at lesser or equal than. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
detectionagentdomain__contains	optional	Free-text filter by Agent domain at detection time (supports multiple values). Example: "sentinel,sentinelone.com".
detectionagentversion__contains	optional	Free-text filter by Agent version at detection time (supports multiple values). Example: "1.1.1.1,2.2".
detectionengines	optional	Included engines. Example: "reputation".

detectionenginesnin	optional	Excluded engines. Example: "reputation".
displayname	optional	Display name
engines	optional	Included engines. Example: "reputation".
enginesnin	optional	Excluded engines. Example: "reputation".
externalticketexists	optional	The threat contains ticket number
externalticketid__contains	optional	Free-text filter by the threat external ticket ID (supports multiple values)
externalticketids	optional	External ticket ID for the threat
failedactions	optional	At least one action failed on the threat
filepath__contains	optional	Free-text filter by file path (supports multiple values). Example: "\\MyUser\\Downloads".
gcpserviceaccount__contains	optional	Free-text filter by gcp service account (supports multiple values)
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
hasagenttags	optional	Include only Threats whose Agent is assigned any tags if True, or none if False
ids	optional	List of threat IDs. Example: "225494730938493804,225494730938493915".
incidentstatuses	optional	Filter threats by a specific incident status. Example: "unresolved,in_progress".
incidentstatusesnin	optional	Exclude threats with specific incident statuses. Example: "unresolved,in_progress".
initiatedby	optional	Only include threats from specific initiating sources. Example: "agent_policy,dv_command".
initiatedbynin	optional	Exclude threats with specific initiating sources. Example: "agent_policy,dv_command".
initiatedbyusername__contains	optional	Free-text filter by the username that initiated that threat (supports multiple values). Example: "John,John Doe".
k8sclustername__contains	optional	Free-text filter by the endpoint Kubernetes cluster name (supports multiple values)
k8scontrollerlabels__contains	optional	Free-text filter by the endpoint Kubernetes controller labels (supports multiple values)
k8scontrollername__contains	optional	Free-text filter by the endpoint Kubernetes controller name

contains		(supports multiple values)
k8snamespacelabels__contains	optional	Free-text filter by the endpoint Kubernetes namespace labels (supports multiple values)
k8snamespace__contains	optional	Free-text filter by the endpoint Kubernetes namespace name (supports multiple values)
k8snode__contains	optional	Free-text filter by the endpoint Kubernetes node labels (supports multiple values)
k8snode__contains	optional	Free-text filter by the endpoint Kubernetes node name (supports multiple values)
k8spodlabels__contains	optional	Free-text filter by the endpoint Kubernetes pod labels (supports multiple values)
k8spod__contains	optional	Free-text filter by the endpoint Kubernetes pod name (supports multiple values)
limit	optional	Limit number of returned items (1-1000). Example: "10".
mitigatedpreemptively	optional	If the threat was detected pre-execution or post-execution
mitigationstatuses	optional	Filter threats by a specific status. Example: "not_mitigated".
mitigationstatusesnin	optional	Filter threats not by a specific status. Example: "not_mitigated".
noteexists	optional	The threat contains at least one note
originatedprocess__contains	optional	Free-text filter by the originated process name of the threat (supports multiple values)
osarchs	optional	Included OS Architectures. Example: "32 bit".
osnames	optional	
osnamesnin	optional	
ostypes	optional	Included OS types. Example: "linux".
ostypesnin	optional	Excluded OS types. Example: "linux".
pendingactions	optional	At least one action is pending for the Agent for the threat
publishername__contains	optional	Free-text filter by threat's publisher name (supports multiple values). Example: "GOOGLE,Apple Inc.".
query	optional	Full text search for fields: threat_details, content_hash, computer_name, file_path, uuid, detection_agent_version, realtime_agent_version, detection_agent_domain, command_line_arguments, initiated_by_username, storyline, originated_process, k8s_cluster_name, k8s_node_name,

		k8s_node_labels, k8s_namespace_name, k8s_namespace_labels, k8s_controller_name, k8s_controller_labels, k8s_pod_name, k8s_pod_labels, container_name, container_image_name, container_labels, external_ticket_id
realtimeagentversion__contains	optional	Free-text filter by Agent version at current time (supports multiple values). Example: "1.1.1.1,2.2."
rebootrequired	optional	A reboot is required on any endpoint for at least one action on the threat
resolved	optional	This is used for backward-compatibility with API 2.0.
signeridentity__contains	optional	Free-text filter by threat's signer identity (certificate ID) (supports multiple values). Example: "3BDA323E552DB1FDC0A9DD871E8CADD2FCBB419".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
storyline__contains	optional	Free-text filter by threat storyline (supports multiple values). Example: "0000C2E97648,0006FC73-77B4-470F-AAC7-".
storylines	optional	List of Agent context to search for
tenant	optional	Indicates a tenant scope request
threatdetails__contains	optional	Free-text filter by threat details(supports multiple values). Example: "malware.exe,virus.exe".
updatedat__gt	optional	Updated at greater than. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Updated at greater or equal than. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Updated at lesser than. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Updated at lesser or equal than. Example: "2018-02-27T04:49:26.257525Z".
uuid__contains	optional	Free-text filter by Agent UUID (supports multiple values). Example:

		"e92-01928,b055".
--	--	-------------------

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Threats - response - pagination table
data	Response data	false	see Get Threats - response - data table
errors	Errors	false	array

Get Threats - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Threats - response - data

Name	Description	Required	Value
agentDetectionInfo	Agent detection time information	false	see Get Threats - response - agentDetectionInfo table
agentRealtimeInfo	Agent realtime information	false	see Get Threats - response - agentRealtimeInfo table
containerInfo	Threat container information	false	see Get Threats - response - containerInfo table
ecsInfo	Threat ECS information	false	see Get Threats - response - ecsInfo table
id	Threat ID	false	string
indicators	Indicators	false	see Get Threats - response - indicators table
kubernetesInfo	Threat kubernetes information	false	see Get Threats - response - kubernetesInfo table
mitigationStatus	Threat mitigation information	false	see Get Threats - response - mitigationStatus table
threatInfo	Threat information	false	see Get Threats - response - threatInfo table
whiteningOptions	Whitening options	false	string []

Get Threats - response - agentDetectionInfo

Name	Description	Required	Value
accountId	Orig account id	false	string
accountName	Orig account name	false	string
agentDetectionState	The Agent's detection state at time of detection	false	string

agentDomain	Network domain	false	string
agentIpV4	Orig agent ip v4	false	string
agentIpV6	Orig agent ip v6	false	string
agentLastLoggedInUpn	UPN of last logged in user	false	string
agentLastLoggedInUserMail	mail from AD of last logged in user	false	string
agentLastLoggedInUserName	Orig logged user	false	string
agentMitigationMode	Agent mitigation mode policy	false	enum
agentOsName	Orig agent os name	false	string
agentOsRevision	Orig agent os revision	false	string
agentRegisteredAt	Time of first registration to management console	false	string
agentUuid	UUID of the agent	false	string
agentVersion	Orig agent version	false	string
assetVersion	Orig asset version	false	string
cloudProviders	Cloud providers for this agent	false	object
externalIp	Orig agent external ip	false	string
groupId	Orig group id	false	string
groupName	Orig group name	false	string
siteId	Orig site id	false	string
siteName	Orig site name	false	string

Get Threats - response - agentRealtimeInfo

Name	Description	Required	Value
accountId	Account id	false	string
accountName	Account name	false	string
activeThreats	Active threats	false	integer
agentComputerName	Computer name	false	string
agentDecommissionedAt	Decommissioned at	false	boolean
agentDomain	Domain	false	string
agentId	Id	false	string
agentInfected	Agent infected	false	boolean

agentIsActive	Is active	false	boolean
agentIsDecommissioned	Is decommissioned	false	boolean
agentMachineType	Machine type	false	enum
agentMitigationMode	Agent mitigation mode policy	false	enum
agentNetworkStatus	Network status	false	enum
agentOsName	Os name	false	string
agentOsRevision	Os revision	false	string
agentOsType	OS type	false	enum
agentUuid	Uuid	false	string
agentVersion	Agent version	false	string
groupId	Group id	false	string
groupName	Group name	false	string
networkInterfaces	Device's network interfaces	false	see Get Threats - response - networkInterfaces table
operationalState	Agent operational state	false	string
rebootRequired	A reboot is required on the endpoint for at least one threat	false	boolean
scanAbortedAt	Abort time of last scan (If applicable)	false	string
scanFinishedAt	Finish time of last scan (If applicable)	false	string
scanStartedAt	Start time of last scan	false	string
scanStatus	Scan status	false	enum
siteId	Site id	false	string
siteName	Site name	false	string
storageName	Storage Name	false	string
storageType	Storage Type	false	string
userActionsNeeded	A list of pending user actions. List items possible values: "none, user_action_needed, reboot_needed, upgrade_needed, incompatible_os, unprotected, rebootless_without_dynamic_detection, extended_exclusions_partially_accepted, reboot_required, pending_deprecation, ne_not_running, ne_cf_not_active, pending_performance_insights".	false	string []

Get Threats - response - networkInterfaces

Name	Description	Required	Value
id	Id	false	string
inet	IPv4 addresses	false	string []
inet6	IPv6 addresses	false	string []
name	Name	false	string
physical	Interface's MAC address	false	string

Get Threats - response - containerInfo

Name	Description	Required	Value
id	Id	false	string
image	Image	false	string
isContainerQuarantine	True if the container is quarantined	false	boolean
labels	Labels	false	string []
name	Name	false	string

Get Threats - response - ecsInfo

Name	Description	Required	Value
clusterName	Cluster name	false	string
serviceArn	Service arn	false	string
serviceName	Service name	false	string
taskArn	Task arn	false	string
taskAvailabilityZone	Task availability zone	false	string
taskDefinitionArn	Task definition arn	false	string
taskDefinitionFamily	Task definition family	false	string
taskDefinitionRevision	Task definition revision	false	string
type	Type	false	string
version	Version	false	string

Get Threats - response - indicators

Name	Description	Required	Value
category	Category	false	string
categoryId	[DEPRECATED]	false	integer
description	Description	false	string
ids	List of all the indicators IDs	false	integer []
tactics	Tactics	false	see Get Threats - response - tactics table

Get Threats - response - tactics

Name	Description	Required	Value
id	Id	false	string
name	Name	false	string
source	Source	false	string
techniques	Techniques	false	see Get Threats - response - techniques table

Get Threats - response - techniques

Name	Description	Required	Value
id	Id	false	string
link	Link	false	string
name	Name	false	string

Get Threats - response - kubernetesInfo

Name	Description	Required	Value
cluster	Cluster	false	string
controllerKind	Controller kind	false	string
controllerLabels	Controller labels	false	string []

controllerName	Controller name	false	string
isContainerQuarantine	True if the container is quarantined	false	boolean
namespace	Namespace	false	string
namespaceLabels	Namespace labels	false	string []
node	Node	false	string
nodeLabels	Node labels	false	string []
pod	Pod	false	string
podLabels	Pod labels	false	string []

Get Threats - response - mitigationStatus

Name	Description	Required	Value
action	Action	false	enum
actionsCounters	Actions counters	false	see Get Threats - response - actionsCounters table
agentSupportsReport	The Agent generates a full mitigation report	false	boolean
groupNotFound	Agent could not find the threat	false	boolean
lastUpdate	Timestamp of last mitigation status update	false	string
latestReport	Report download URL. If None, there is no report	false	string
mitigationEndedAt	The time the Agent finished the mitigation	false	string
mitigationStartedAt	The time the Agent started the mitigation	false	string
reportId	ID of the mitigation report	false	string
status	Status	false	enum

Get Threats - response - actionsCounters

Name	Description	Required	Value
failed	Failed	false	integer

notFound	Not found	false	integer
pendingReboot	Pending reboot	false	integer
success	Success	false	integer
total	Total	false	integer

Get Threats - response - threatInfo

Name	Description	Required	Value
sha1	SHA1 hash of file content	true	string
analystVerdict	Analyst verdict	false	enum
analystVerdictDescription	Analyst verdict description	false	
automaticallyResolved	Automatically resolved	false	boolean
browserType	Browser type	false	string
certificateId	File Certificate ID	false	string
classification	Classification of the threat	false	string
classificationSource	Source of the threat Classification	false	enum
cloudFilesHashVerdict	Cloud files hash verdict	false	string
collectionId	Collection id	false	string
confidenceLevel	SentinelOne threat confidence level	false	enum
createdAt	Timestamp of date creation in the Management Console.	false	string
detectionEngines	List of engines that detected the threat	false	
detectionType	Detection type	false	enum
engines	[Deprecated] List of engines that detected the threat	false	
externalTicketExists	External ticket exists	false	
externalTicketId	External ticket id	false	string
failedActions	At least one action failed on the threat	false	boolean
fileExtension	File extension	false	string
fileExtensionType	File extension type	false	string
filePath	File path	false	

fileSize	File size	false	integer
fileVerificationType	File verification type	false	string
identifiedAt	Identified at	false	string
incidentStatus	Incident status	false	enum
incidentStatusDescription	Incident status description	false	
initiatedBy	Source of threat	false	enum
initiatedByDescription	Initiated by description	false	
initiatingUserId	Initiating user id	false	string
initiatingUsername	Initiating username	false	string
isFileless	Is fileless	false	
isValidCertificate	True if the certificate is valid	false	boolean
macroModules	List of macro modules	false	see Get Threats - response - macroModules table
maliciousProcessArguments	Malicious process arguments	false	string
md5	Md5	false	string
mitigatedPreemptively	True is the threat was blocked before execution	false	boolean
mitigationStatus	Mitigation status	false	enum
mitigationStatusDescription	Mitigation status description	false	
originatorProcess	Originator process	false	string
pendingActions	At least one action is pending on the threat	false	boolean
processUser	Process user	false	string
publisherName	Certificate publisher	false	string
reachedEventsLimit	Has number of OS events for this threat reached the limit, resulting in a partial attack storyline	false	boolean
rebootRequired	A reboot is required on the endpoint for at least one action on the threat	false	boolean
rootProcessUpn	Root process UPN	false	string
sha256	SHA256 hash of file content	false	string
storyline	Storyline identifier from agent	false	string
threatId	Threat id	false	string
threatName	Threat name	false	string
updatedAt	Timestamp of last update	false	string

Get Threats - response - macroModules

Name	Description	Required	Value
content	Macro content encoded in UTF-8	false	string
isMacroContentTruncated	Indicates if macro content was truncated	false	boolean
macroDetectionSource	Detection source	false	string
moduleName	Name of macro module	false	string
sha1	SHA-1 of the macro module	false	string
sha256	SHA-256 of the macro module	false	string

Mitigate Threats

POST /web/api/v2.1/threats/mitigate/{action}

Apply a mitigation action to a group of threats that match the filter. Valid values for mitigation: "kill", "quarantine", "remediate", "rollback-remediation", "un-quarantine","network-quarantine".

Your user role must have permissions to mitigate threats - Admin, IR Team, SOC. Only threats which you have permission to mitigate are counted as "affected" in response field.

Rollback is applied only on Windows. Remediate is applied only on macOS and Windows.

Response Messages

200 - Threat successfully mitigated

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Mitigate Threats - response - data table
errors	Errors	false	array

Mitigate Threats - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer
details	Single threat mitigation information	false	see Mitigate Threats - response - details table

Mitigate Threats - response - details

Name	Description	Required	Value
reports	List of latest mitigation reports created by the action trigger.	false	see Mitigate Threats - response - reports table
skipped	List of skipped mitigation actions with additional details.	false	see Mitigate Threats - response - skipped table
threatId	Threat id	false	string

Mitigate Threats - response - reports

Name	Description	Required	Value
action	Action	false	enum
actionsCounters	Actions counters	false	see Mitigate Threats - response - actionsCounters table
agentSupportsReport	The Agent generates a full mitigation report	false	boolean
groupNotFound	Agent could not find the threat	false	boolean
lastUpdate	Timestamp of last mitigation status update	false	string
latestReport	Report download URL. If None, there is no report	false	string
mitigationEndedAt	The time the Agent finished the mitigation	false	string
mitigationStartedAt	The time the Agent started the mitigation	false	string

reportId	ID of the mitigation report	false	string
status	Status	false	enum

Mitigate Threats - response - actionsCounters

Name	Description	Required	Value
failed	Failed	false	integer
notFound	Not found	false	integer
pendingReboot	Pending reboot	false	integer
success	Success	false	integer
total	Total	false	integer

Mitigate Threats - response - skipped

Name	Description	Required	Value
action	Action	false	enum
description	Description	false	string
reason	Reason	false	enum

Body Schema

Name	Description	Required	Value
filter	Use any of the filtering options to control the list of affected threats. You can use any combination of filters to narrow down the list (For example "apply to only active threats from Linux endpoints"). You can also leave this field empty to apply to all available threats.	true	see Mitigate Threats - body - filter table
data	Data	false	see Mitigate Threats - body - data table

Mitigate Threats - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
agentIds	List of Agent IDs	false	string []
agentsActive	Include Agents currently connected to the Management Console	false	boolean
agentMachineTypes	Include Agent machine types	false	string []
agentMachineTypesNin	Excluded Agent machine types	false	string []
agentTagsData	Filter threats by assigned tags to the related agent. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
agentVersions	Include Agent versions	false	string []
agentVersionsNin	Excluded Agent versions	false	string []
analystVerdicts	Filter threats by a specific analyst verdict	false	string []
analystVerdictsNin	Exclude threats with specific analyst verdicts	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
classifications	List of threat classifications to search	false	string []
classificationsNin	List of threat classifications not to search	false	string []
classificationSources	Classification sources list	false	string []

classificationSourcesNin	Classification sources list to exclude	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
collectionIds	List of collection IDs to search	false	string []
commandLineArguments__contains	Free-text filter by threat command line arguments (supports multiple values)	false	string []
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
confidenceLevels	Filter threats by a specific confidence level	false	string []
confidenceLevelsNin	Exclude threats with specific confidence level	false	string []
containerImageName__contains	Free-text filter by the endpoint container image name (supports multiple values)	false	string []
containerLabels__contains	Free-text filter by the endpoint container labels (supports multiple values)	false	string []
containerName__contains	Free-text filter by the endpoint container name (supports multiple values)	false	string []
contentHash__contains	Free-text filter by file content hash (supports multiple values)	false	string []
contentHashes	List of sha1 hashes to search for	false	string []

countsFor	comma-separated list of fields to be shown	false	string
createdAt__gt	Created at greater than.	false	string
createdAt__gte	Created at greater or equal than.	false	string
createdAt__lt	Created at lesser than.	false	string
createdAt__lte	Created at lesser or equal than.	false	string
detectionAgentDomain__contains	Free-text filter by Agent domain at detection time (supports multiple values)	false	string []
detectionAgentVersion__contains	Free-text filter by Agent version at detection time (supports multiple values)	false	string []
detectionEngines	Included engines	false	string []
detectionEnginesNin	Excluded engines	false	string []
displayName	Display name	false	string
engines	Included engines	false	string []
enginesNin	Excluded engines	false	string []
externalTicketExists	The threat contains ticket number	false	boolean
externalTicketId__contains	Free-text filter by the threat external ticket ID (supports multiple values)	false	string []
externalTicketIds	External ticket ID for the threat	false	string []
failedActions	At least one action failed on the threat	false	boolean
filePath__contains	Free-text filter by file path (supports multiple values)	false	string []
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasAgentTags	Include only Threats whose Agent is assigned any tags if True, or none if False	false	boolean
ids	List of threat IDs	false	string []
incidentStatuses	Filter threats by a specific incident status	false	string []
incidentStatusesNin	Exclude threats with specific incident statuses	false	string []

initiatedBy	Only include threats from specific initiating sources	false	string []
initiatedByNin	Exclude threats with specific initiating sources	false	string []
initiatedByUsername__contains	Free-text filter by the username that initiated that threat (supports multiple values)	false	string []
k8sClusterName__contains	Free-text filter by the endpoint Kubernetes cluster name (supports multiple values)	false	string []
k8sControllerLabels__contains	Free-text filter by the endpoint Kubernetes controller labels (supports multiple values)	false	string []
k8sControllerName__contains	Free-text filter by the endpoint Kubernetes controller name (supports multiple values)	false	string []
k8sNamespaceLabels__contains	Free-text filter by the endpoint Kubernetes namespace labels (supports multiple values)	false	string []
k8sNamespaceName__contains	Free-text filter by the endpoint Kubernetes namespace name (supports multiple values)	false	string []
k8sNodeLabels__contains	Free-text filter by the endpoint Kubernetes node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by the endpoint Kubernetes node name (supports multiple values)	false	string []
k8sPodLabels__contains	Free-text filter by the endpoint Kubernetes pod labels (supports multiple values)	false	string []
k8sPodName__contains	Free-text filter by the endpoint Kubernetes pod name (supports multiple values)	false	string []
limit	Limit	false	integer
mitigatedPreemptively	If the threat was detected pre-execution or post-execution	false	boolean
mitigationStatuses	Filter threats by a specific status	false	string []
mitigationStatusesNin	Filter threats not by a specific status	false	string []

noteExists	The threat contains at least one note	false	boolean
originatedProcess__contains	Free-text filter by the originated process name of the threat (supports multiple values)	false	string []
osArchs	Included OS Architectures	false	string []
osNames		false	string []
osNamesNin		false	string []
osTypes	Included OS types	false	string []
osTypesNin	Excluded OS types	false	string []
pendingActions	At least one action is pending for the Agent for the threat	false	boolean
publisherName__contains	Free-text filter by threat's publisher name (supports multiple values)	false	string []
query	Full text search for fields: threat_details, content_hash, computer_name, file_path, uuid, detection_agent_version, realtime_agent_version, detection_agent_domain, command_line_arguments, initiated_by_username, storyline, originated_process, k8s_cluster_name, k8s_node_name, k8s_node_labels, k8s_namespace_name, k8s_namespace_labels, k8s_controller_name, k8s_controller_labels, k8s_pod_name, k8s_pod_labels, container_name, container_image_name, container_labels, external_ticket_id	false	string
realtimeAgentVersion__contains	Free-text filter by Agent version at current time (supports multiple values)	false	string []
rebootRequired	A reboot is required on any endpoint for at least one action on the threat	false	boolean
resolved	This is used for backward-compatibility with API 2.0.	false	boolean
signerIdentity__contains	Free-text filter by threat's signer identity (certificate ID) (supports multiple values)	false	string []

sitelds	List of Site IDs to filter by	false	string []
storyline__contains	Free-text filter by threat storyline (supports multiple values)	false	string []
storylines	List of Agent context to search for	false	string []
tenant	Indicates a tenant scope request	false	boolean
threatDetails__contains	Free-text filter by threat details(supports multiple values)	false	string []
updatedAt__gt	Updated at greater than.	false	string
updatedAt__gte	Updated at greater or equal than.	false	string
updatedAt__lt	Updated at lesser than.	false	string
updatedAt__lte	Updated at lesser or equal than.	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []

Mitigate Threats - body - data

Add to Blocklist

POST /web/api/v2.1/threats/add-to-blacklist

Add threats that have a SHA1 hash and that match the filter to the Blocklist of the target scope: Global, Account, Site, or Group. Your role must have permissions to change the Blocklist - Admin, IR Team, SOC - and your user scope access must include the Agent. The target scope is the Group, Site, or Account of the Agent.

Response Messages

200 - Hash threat added to black list

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Add to Blocklist - response - data table
errors	Errors	false	array

Add to Blocklist - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer
details	Result details for each threat	false	see Add to Blocklist - response - details table

Add to Blocklist - response - details

Name	Description	Required	Value
analystVerdict	Result of changing the threat's analyst verdict as part of adding the threat to blocklist or exclusions	false	enum
result	Result of adding the threat to blocklist or exclusions	false	enum
threatId	Threat id	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Add to Blocklist - body - data table
filter	Use any of the filtering options to control the list of affected threats. You can use any combination of filters to narrow down the list (For example "apply to only active threats from Linux endpoints"). You can also leave this field empty to apply to all available threats.	true	see Add to Blocklist - body - filter table

Add to Blocklist - body - data

Name	Description	Required	Value
targetScope	Scope to be used for Restrictions	true	enum
description	Description	false	string
externalTicketId	External ticket id	false	string
note	Note	false	string

Add to Blocklist - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
agentIds	List of Agent IDs	false	string []
agentIsActive	Include Agents currently connected to the Management Console	false	boolean
agentMachineTypes	Include Agent machine types	false	string []
agentMachineTypesNin	Excluded Agent machine types	false	string []
agentTagsData	Filter threats by assigned tags to the related agent. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
agentVersions	Include Agent versions	false	string []
agentVersionsNin	Excluded Agent versions	false	string []
analystVerdicts	Filter threats by a specific analyst verdict	false	string []
analystVerdictsNin	Exclude threats with specific analyst verdicts	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws	false	string []

	securityGroups(supports multiple values)		
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
classifications	List of threat classifications to search	false	string []
classificationsNin	List of threat classifications not to search	false	string []
classificationSources	Classification sources list	false	string []
classificationSourcesNin	Classification sources list to exclude	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
collectionIds	List of collection IDs to search	false	string []
commandLineArguments__contains	Free-text filter by threat command line arguments (supports multiple values)	false	string []
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
confidenceLevels	Filter threats by a specific confidence level	false	string []
confidenceLevelsNin	Exclude threats with specific confidence level	false	string []
containerImageName__contains	Free-text filter by the endpoint	false	string []

	container image name (supports multiple values)		
containerLabels__contains	Free-text filter by the endpoint container labels (supports multiple values)	false	string []
containerName__contains	Free-text filter by the endpoint container name (supports multiple values)	false	string []
contentHash__contains	Free-text filter by file content hash (supports multiple values)	false	string []
contentHashes	List of sha1 hashes to search for	false	string []
countsFor	comma-separated list of fields to be shown	false	string
createdAt__gt	Created at greater than.	false	string
createdAt__gte	Created at greater or equal than.	false	string
createdAt__lt	Created at lesser than.	false	string
createdAt__lte	Created at lesser or equal than.	false	string
detectionAgentDomain__contains	Free-text filter by Agent domain at detection time (supports multiple values)	false	string []
detectionAgentVersion__contains	Free-text filter by Agent version at detection time (supports multiple values)	false	string []
detectionEngines	Included engines	false	string []
detectionEnginesNin	Excluded engines	false	string []
displayName	Display name	false	string
engines	Included engines	false	string []
enginesNin	Excluded engines	false	string []
externalTicketExists	The threat contains ticket number	false	boolean
externalTicketId__contains	Free-text filter by the threat external ticket ID (supports multiple values)	false	string []
externalTicketIds	External ticket ID for the threat	false	string []
failedActions	At least one action failed on the threat	false	boolean
filePath__contains	Free-text filter by file path (supports multiple values)	false	string []

gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasAgentTags	Include only Threats whose Agent is assigned any tags if True, or none if False	false	boolean
ids	List of threat IDs	false	string []
incidentStatuses	Filter threats by a specific incident status	false	string []
incidentStatusesNin	Exclude threats with specific incident statuses	false	string []
initiatedBy	Only include threats from specific initiating sources	false	string []
initiatedByNin	Exclude threats with specific initiating sources	false	string []
initiatedByUsername__contains	Free-text filter by the username that initiated that threat (supports multiple values)	false	string []
k8sClusterName__contains	Free-text filter by the endpoint Kubernetes cluster name (supports multiple values)	false	string []
k8sControllerLabels__contains	Free-text filter by the endpoint Kubernetes controller labels (supports multiple values)	false	string []
k8sControllerName__contains	Free-text filter by the endpoint Kubernetes controller name (supports multiple values)	false	string []
k8sNamespaceLabels__contains	Free-text filter by the endpoint Kubernetes namespace labels (supports multiple values)	false	string []
k8sNamespaceName__contains	Free-text filter by the endpoint Kubernetes namespace name (supports multiple values)	false	string []
k8sNodeLabels__contains	Free-text filter by the endpoint Kubernetes node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by the endpoint Kubernetes node name (supports multiple values)	false	string []

k8sPodLabels__contains	Free-text filter by the endpoint Kubernetes pod labels (supports multiple values)	false	string []
k8sPodName__contains	Free-text filter by the endpoint Kubernetes pod name (supports multiple values)	false	string []
limit	Limit	false	integer
mitigatedPreemptively	If the threat was detected pre-execution or post-execution	false	boolean
mitigationStatuses	Filter threats by a specific status	false	string []
mitigationStatusesNin	Filter threats not by a specific status	false	string []
noteExists	The threat contains at least one note	false	boolean
originatedProcess__contains	Free-text filter by the originated process name of the threat (supports multiple values)	false	string []
osArchs	Included OS Architectures	false	string []
osNames		false	string []
osNamesNin		false	string []
osTypes	Included OS types	false	string []
osTypesNin	Excluded OS types	false	string []
pendingActions	At least one action is pending for the Agent for the threat	false	boolean
publisherName__contains	Free-text filter by threat's publisher name (supports multiple values)	false	string []
query	Full text search for fields: threat_details, content_hash, computer_name, file_path, uuid, detection_agent_version, realtime_agent_version, detection_agent_domain, command_line_arguments, initiated_by_username, storyline, originated_process, k8s_cluster_name, k8s_node_name, k8s_node_labels, k8s_namespace_name, k8s_namespace_labels, k8s_controller_name, k8s_controller_labels, k8s_pod_name, k8s_pod_labels, container_name,	false	string

	container_image_name, container_labels, external_ticket_id		
realtimeAgentVersion__contains	Free-text filter by Agent version at current time (supports multiple values)	false	string []
rebootRequired	A reboot is required on any endpoint for at least one action on the threat	false	boolean
resolved	This is used for backward-compatibility with API 2.0.	false	boolean
signerIdentity__contains	Free-text filter by threat's signer identity (certificate ID) (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storyline__contains	Free-text filter by threat storyline (supports multiple values)	false	string []
storylines	List of Agent context to search for	false	string []
tenant	Indicates a tenant scope request	false	boolean
threatDetails__contains	Free-text filter by threat details(supports multiple values)	false	string []
updatedAt__gt	Updated at greater than.	false	string
updatedAt__gte	Updated at greater or equal than.	false	string
updatedAt__lt	Updated at lesser than.	false	string
updatedAt__lte	Updated at lesser or equal than.	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []

Fetch Threat File

POST /web/api/v2.1/threats/fetch-file

Fetch a file associated with the threat that matches the filter. Your user role must have permissions to Fetch Threat File - Admin, IR Team, SOC.

Response Messages

200 - Number of affected agents

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Fetch Threat File - response - data table
errors	Errors	false	array

Fetch Threat File - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Fetch Threat File - body - data table
filter	Use any of the filtering options to control the list of affected threats. You can use any combination of filters to narrow down the list (For example "apply to only active threats from Linux endpoints"). You can also leave this field empty to apply to all available threats. Note: Filter must match exactly one threat. Bulk operations are not supported.	true	see Fetch Threat File - body - filter table

Fetch Threat File - body - data

Name	Description	Required	Value
password	File encryption password	true	string

Fetch Threat File - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
agentIds	List of Agent IDs	false	string []
agentIsActive	Include Agents currently connected to the Management Console	false	boolean
agentMachineTypes	Include Agent machine types	false	string []
agentMachineTypesNin	Excluded Agent machine types	false	string []
agentTagsData	Filter threats by assigned tags to the related agent. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
agentVersions	Include Agent versions	false	string []
agentVersionsNin	Excluded Agent versions	false	string []
analystVerdicts	Filter threats by a specific analyst verdict	false	string []
analystVerdictsNin	Exclude threats with specific analyst verdicts	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []

azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
classifications	List of threat classifications to search	false	string []
classificationsNin	List of threat classifications not to search	false	string []
classificationSources	Classification sources list	false	string []
classificationSourcesNin	Classification sources list to exclude	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
collectionIds	List of collection IDs to search	false	string []
commandLineArguments__contains	Free-text filter by threat command line arguments (supports multiple values)	false	string []
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
confidenceLevels	Filter threats by a specific confidence level	false	string []
confidenceLevelsNin	Exclude threats with specific confidence level	false	string []
containerImageName__contains	Free-text filter by the endpoint container image name (supports multiple values)	false	string []
containerLabels__contains	Free-text filter by the endpoint container labels (supports multiple values)	false	string []

containerName__contains	Free-text filter by the endpoint container name (supports multiple values)	false	string []
contentHash__contains	Free-text filter by file content hash (supports multiple values)	false	string []
contentHashes	List of sha1 hashes to search for	false	string []
countsFor	comma-separated list of fields to be shown	false	string
createdAt__gt	Created at greater than.	false	string
createdAt__gte	Created at greater or equal than.	false	string
createdAt__lt	Created at lesser than.	false	string
createdAt__lte	Created at lesser or equal than.	false	string
detectionAgentDomain__contains	Free-text filter by Agent domain at detection time (supports multiple values)	false	string []
detectionAgentVersion__contains	Free-text filter by Agent version at detection time (supports multiple values)	false	string []
detectionEngines	Included engines	false	string []
detectionEnginesNin	Excluded engines	false	string []
displayName	Display name	false	string
engines	Included engines	false	string []
enginesNin	Excluded engines	false	string []
externalTicketExists	The threat contains ticket number	false	boolean
externalTicketId__contains	Free-text filter by the threat external ticket ID (supports multiple values)	false	string []
externalTicketIds	External ticket ID for the threat	false	string []
failedActions	At least one action failed on the threat	false	boolean
filePath__contains	Free-text filter by file path (supports multiple values)	false	string []
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasAgentTags	Include only Threats whose Agent is assigned any tags if True, or none if	false	boolean

	False		
ids	List of threat IDs	false	string []
incidentStatuses	Filter threats by a specific incident status	false	string []
incidentStatusesNin	Exclude threats with specific incident statuses	false	string []
initiatedBy	Only include threats from specific initiating sources	false	string []
initiatedByNin	Exclude threats with specific initiating sources	false	string []
initiatedByUsername__contains	Free-text filter by the username that initiated that threat (supports multiple values)	false	string []
k8sClusterName__contains	Free-text filter by the endpoint Kubernetes cluster name (supports multiple values)	false	string []
k8sControllerLabels__contains	Free-text filter by the endpoint Kubernetes controller labels (supports multiple values)	false	string []
k8sControllerName__contains	Free-text filter by the endpoint Kubernetes controller name (supports multiple values)	false	string []
k8sNamespaceLabels__contains	Free-text filter by the endpoint Kubernetes namespace labels (supports multiple values)	false	string []
k8sNamespaceName__contains	Free-text filter by the endpoint Kubernetes namespace name (supports multiple values)	false	string []
k8sNodeLabels__contains	Free-text filter by the endpoint Kubernetes node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by the endpoint Kubernetes node name (supports multiple values)	false	string []
k8sPodLabels__contains	Free-text filter by the endpoint Kubernetes pod labels (supports multiple values)	false	string []
k8sPodName__contains	Free-text filter by the endpoint Kubernetes pod name (supports multiple values)	false	string []

mitigatedPreemptively	If the threat was detected pre-execution or post-execution	false	boolean
mitigationStatuses	Filter threats by a specific status	false	string []
mitigationStatusesNin	Filter threats not by a specific status	false	string []
noteExists	The threat contains at least one note	false	boolean
originatedProcess__contains	Free-text filter by the originated process name of the threat (supports multiple values)	false	string []
osArchs	Included OS Architectures	false	string []
osNames		false	string []
osNamesNin		false	string []
osTypes	Included OS types	false	string []
osTypesNin	Excluded OS types	false	string []
pendingActions	At least one action is pending for the Agent for the threat	false	boolean
publisherName__contains	Free-text filter by threat's publisher name (supports multiple values)	false	string []
query	Full text search for fields: threat_details, content_hash, computer_name, file_path, uuid, detection_agent_version, realtime_agent_version, detection_agent_domain, command_line_arguments, initiated_by_username, storyline, originated_process, k8s_cluster_name, k8s_node_name, k8s_node_labels, k8s_namespace_name, k8s_namespace_labels, k8s_controller_name, k8s_controller_labels, k8s_pod_name, k8s_pod_labels, container_name, container_image_name, container_labels, external_ticket_id	false	string
realtimeAgentVersion__contains	Free-text filter by Agent version at current time (supports multiple values)	false	string []
rebootRequired	A reboot is required on any endpoint for at least one action on the threat	false	boolean

resolved	This is used for backward-compatibility with API 2.0.	false	boolean
signerIdentity__contains	Free-text filter by threat's signer identity (certificate ID) (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storyline__contains	Free-text filter by threat storyline (supports multiple values)	false	string []
storylines	List of Agent context to search for	false	string []
tenant	Indicates a tenant scope request	false	boolean
threatDetails__contains	Free-text filter by threat details(supports multiple values)	false	string []
updatedAt__gt	Updated at greater than.	false	string
updatedAt__gte	Updated at greater or equal than.	false	string
updatedAt__lt	Updated at lesser than.	false	string
updatedAt__lte	Updated at lesser or equal than.	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []

Disable Engines

POST /web/api/v2.1/threats/engines/disable

If your list of threats shows too many False Positives, use this command to troubleshoot the Agent Engines that return unexpected results in your deployment. Valid values: "penetration", "dataFiles","exploits", "reputation", "executables", "preExecutionSuspicious", "preExecution", "lateralMovement", and "pup".

Response Messages

200 - Engines disabled

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Disable Engines - response - data table
errors	Errors	false	array

Disable Engines - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	false	see Disable Engines - body - data table

Disable Engines - body - data

Name	Description	Required	Value
engines	List of engines	false	string []

Exclusion Options

GET /web/api/v2.1/threats/{threat_id}/whitening-options

Get the Exclusion types that can be created from the detection data.

For example, if a threat is a file with a detected SHA1 hash and pathname, the values of the whiteningOptions in the response are "path" and "file_hash". This command requires the ID of the threat, which you can get from "threats" (see Get Threats). To create an Exclusion, see Exclusions.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Exclusion Options - response - data table
errors	Errors	false	array

Exclusion Options - response - data

Name	Description	Required	Value
threatPolicy	Threat policy	false	string
threatType	Threat type	false	string []
whiteningOptions	Available exclusion options	false	string []

Get Events

GET /web/api/v2.1/threats/{threat_id}/explore/events

Get all threat events.

Parameters

countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
eventid	optional	Filter by a specific process key and its children
eventsubtypes	optional	Filter events by sub-type. Example: "PROCESSCREATION".
eventtypes	optional	Filter events by type. Example: "events".
limit	optional	Limit number of returned items (1-1000). Example: "10".
processname__like	optional	Filter by process name (substring)
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Events - response - pagination table
data	Response data	false	see Get Events - response - data table
errors	Errors	false	array

Get Events - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Events - response - data

Name	Description	Required	Value
agentDomain	Agent domain	true	string
agentGroupId	Agent group id	true	string
agentId	Agent id	true	string
agentInfected	Agent infected	true	boolean
agentIp	Agent ip	true	string
agentIsActive	Agent is active	true	boolean
agentIsDecommissioned	Agent is decommissioned	true	boolean
agentMachineType	Agent machine type	true	string
agentName	Agent name	true	string
agentNetworkStatus	Agent network status	true	string
agentOs	OS type	true	enum
agentUuid	Agent uuid	true	string
agentVersion	Agent version	true	string
createdAt	Created at	true	string
id	Id	true	string
objectType	Object type	true	enum
processName	Process name	true	string
siteId	Site id	true	string

siteName	Site name	true	string
activeContentFileId	Active content file id	false	string
activeContentHash	Active content hash	false	string
activeContentPath	Active content path	false	string
connectionStatus	Connection status	false	string
direction	Direction	false	string
dnsRequest	Dns request	false	string
dnsResponse	Dns response	false	string
dstIp	Dst ip	false	string
dstPort	Dst port	false	integer
eventType	Event type	false	string
fileFullName	File full name	false	string
fileId	File id	false	string
fileMd5	File md5	false	string
fileSha1	File sha1	false	string
fileSha256	File sha256	false	string
fileSize	File size	false	string
fileType	File type	false	string
hasActiveContent	Has active content	false	boolean
indicatorCategory	Indicator category	false	string
indicatorDescription	Indicator description	false	string
indicatorMetadata	Indicator metadata	false	string
indicatorName	Indicator name	false	string
loginsBaseType	Logins base type	false	string
loginsUserName	Logins user name	false	string
md5	Md5	false	string
networkMethod	Network method	false	string
networkSource	Network source	false	string
networkUrl	Network url	false	string
oldFileMd5	Old file md5	false	string
oldFileName	Old file name	false	string
oldFileSha1	Old file sha1	false	string

oldFileSha256	Old file sha256	false	string
parentPid	Parent pid	false	string
parentProcessGroupId	Parent process group id	false	string
parentProcessIsMalicious	Parent process is malicious	false	boolean
parentProcessName	Parent process name	false	string
parentProcessUniqueKey	Parent process unique key	false	string
pid	Pid	false	string
processCmd	Process cmd	false	string
processDisplayName	Process display name	false	string
processGroupId	Process group id	false	string
processImagePath	Process image path	false	string
processImageSha1Hash	Process image sha1 hash	false	string
processIntegrityLevel	Process integrity level	false	string
processIsMalicious	Process is malicious	false	boolean
processIsRedirectedCommandProcess or	Process is redirected command processor	false	string
processIsWow64	Process is wow64	false	string
processRoot	Process root	false	string
processSessionId	Process session id	false	string
processStartTime	Process start time	false	string
processSubSystem	Process sub system	false	string
processUniqueKey	Process unique key	false	string
processUserName	Process user name	false	string
protocol	Protocol	false	string
publisher	Publisher	false	string
registryClassification	Registry classification	false	string
registryId	Registry id	false	string
registryPath	Registry path	false	string
relatedToThreat	Related to threat	false	boolean
rpId	Rpid	false	string
sha1	Sha1	false	string
sha256	Sha256	false	string

signatureSignedInvalidReason	Signature signed invalid reason	false	string
signedStatus	Signed status	false	string
srcIp	Src ip	false	string
srcPort	Src port	false	integer
storyline	Storyline	false	string
taskName	Task name	false	string
taskPath	Task path	false	string
threatStatus	Threat status	false	string
tid	Tid	false	string
trueContext	[DEPRECATED] Use "storyline" instead	false	string
user	User	false	string
verifiedStatus	Verified status	false	string

Add to Exclusions

POST /web/api/v2.1/threats/add-to-exclusions

Add a threat to exclusions. The "whitening option" is required.

When you create an exclusion, you override the "malicious" verdict of the Agent for a detection. This can open holes in your security deployment. Use with caution.

Best practice: Use the most specific definition of the exclusion possible and the lowest mode possible.

BEST PRACTICE

Use the most specific definition of the exclusion possible and the lowest mode possible.

Response Messages

200 - Added to exclusions

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Add to Exclusions - response - data table
errors	Errors	false	array

Add to Exclusions - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer
details	Result details for each threat	false	see Add to Exclusions - response - details table

Add to Exclusions - response - details

Name	Description	Required	Value
analystVerdict	Result of changing the threat's analyst verdict as part of adding the threat to blocklist or exclusions	false	enum
result	Result of adding the threat to blocklist or exclusions	false	enum
threatId	Threat id	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Add to Exclusions - body - data table
filter	Use any of the filtering options to control the list of affected threats. You can use any combination of filters to narrow down the list (For example "apply to only active threats from Linux endpoints"). You can also leave this field empty to apply to all available threats.	true	see Add to Exclusions - body - filter table

Add to Exclusions - body - data

Name	Description	Required	Value
targetScope	Scope to be used for Exclusions	true	enum
type	Selected Exclusion type	true	enum
actions	Actions to perform	false	string []
description	Description	false	string
externalTicketId	External ticket id	false	string
macroModules	Macro modules	false	see Add to Exclusions - body - macroModules table
mode	Exclusion mode (path exclusion only)	false	enum
note	Note	false	string
pathExclusionType	Excluded path for a path exclusion list	false	string
value	Optional. If not provided, the relevant value from the Threat will be used	false	string

Add to Exclusions - body - macroModules

Name	Description	Required	Value
description	Description	false	string
hashes	Hashes	false	string []

Add to Exclusions - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
agentIds	List of Agent IDs	false	string []
agentsActive	Include Agents currently connected to the Management Console	false	boolean
agentMachineTypes	Include Agent machine types	false	string []
agentMachineTypesNin	Excluded Agent machine types	false	string []

agentTagsData	Filter threats by assigned tags to the related agent. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
agentVersions	Include Agent versions	false	string []
agentVersionsNin	Excluded Agent versions	false	string []
analystVerdicts	Filter threats by a specific analyst verdict	false	string []
analystVerdictsNin	Exclude threats with specific analyst verdicts	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
classifications	List of threat classifications to search	false	string []
classificationsNin	List of threat classifications not to search	false	string []
classificationSources	Classification sources list	false	string []
classificationSourcesNin	Classification sources list to exclude	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network	false	string []

	(supports multiple values)		
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
collectionIds	List of collection IDs to search	false	string []
commandLineArguments__contains	Free-text filter by threat command line arguments (supports multiple values)	false	string []
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
confidenceLevels	Filter threats by a specific confidence level	false	string []
confidenceLevelsNin	Exclude threats with specific confidence level	false	string []
containerImageName__contains	Free-text filter by the endpoint container image name (supports multiple values)	false	string []
containerLabels__contains	Free-text filter by the endpoint container labels (supports multiple values)	false	string []
containerName__contains	Free-text filter by the endpoint container name (supports multiple values)	false	string []
contentHash__contains	Free-text filter by file content hash (supports multiple values)	false	string []
contentHashes	List of sha1 hashes to search for	false	string []
countsFor	comma-separated list of fields to be shown	false	string
createdAt__gt	Created at greater than.	false	string
createdAt__gte	Created at greater or equal than.	false	string
createdAt__lt	Created at lesser than.	false	string
createdAt__lte	Created at lesser or equal than.	false	string
detectionAgentDomain__contains	Free-text filter by Agent domain at detection time (supports multiple values)	false	string []
detectionAgentVersion__contains	Free-text filter by Agent version at detection time (supports multiple values)	false	string []

detectionEngines	Included engines	false	string []
detectionEnginesNin	Excluded engines	false	string []
displayName	Display name	false	string
engines	Included engines	false	string []
enginesNin	Excluded engines	false	string []
externalTicketExists	The threat contains ticket number	false	boolean
externalTicketId__contains	Free-text filter by the threat external ticket ID (supports multiple values)	false	string []
externalTicketIds	External ticket ID for the threat	false	string []
failedActions	At least one action failed on the threat	false	boolean
filePath__contains	Free-text filter by file path (supports multiple values)	false	string []
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasAgentTags	Include only Threats whose Agent is assigned any tags if True, or none if False	false	boolean
ids	List of threat IDs	false	string []
incidentStatuses	Filter threats by a specific incident status	false	string []
incidentStatusesNin	Exclude threats with specific incident statuses	false	string []
initiatedBy	Only include threats from specific initiating sources	false	string []
initiatedByNin	Exclude threats with specific initiating sources	false	string []
initiatedByUsername__contains	Free-text filter by the username that initiated that threat (supports multiple values)	false	string []
k8sClusterName__contains	Free-text filter by the endpoint Kubernetes cluster name (supports multiple values)	false	string []
k8sControllerLabels__contains	Free-text filter by the endpoint Kubernetes controller labels (supports multiple values)	false	string []

k8sControllerName__contains	Free-text filter by the endpoint Kubernetes controller name (supports multiple values)	false	string []
k8sNamespaceLabels__contains	Free-text filter by the endpoint Kubernetes namespace labels (supports multiple values)	false	string []
k8sNamespaceName__contains	Free-text filter by the endpoint Kubernetes namespace name (supports multiple values)	false	string []
k8sNodeLabels__contains	Free-text filter by the endpoint Kubernetes node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by the endpoint Kubernetes node name (supports multiple values)	false	string []
k8sPodLabels__contains	Free-text filter by the endpoint Kubernetes pod labels (supports multiple values)	false	string []
k8sPodName__contains	Free-text filter by the endpoint Kubernetes pod name (supports multiple values)	false	string []
limit	Limit	false	integer
mitigatedPreemptively	If the threat was detected pre-execution or post-execution	false	boolean
mitigationStatuses	Filter threats by a specific status	false	string []
mitigationStatusesNin	Filter threats not by a specific status	false	string []
noteExists	The threat contains at least one note	false	boolean
originatedProcess__contains	Free-text filter by the originated process name of the threat (supports multiple values)	false	string []
osArchs	Included OS Architectures	false	string []
osNames		false	string []
osNamesNin		false	string []
osTypes	Included OS types	false	string []
osTypesNin	Excluded OS types	false	string []
pendingActions	At least one action is pending for the Agent for the threat	false	boolean
publisherName__contains	Free-text filter by threat's publisher	false	string []

	name (supports multiple values)		
query	Full text search for fields: threat_details, content_hash, computer_name, file_path, uuid, detection_agent_version, realtime_agent_version, detection_agent_domain, command_line_arguments, initiated_by_username, storyline, originated_process, k8s_cluster_name, k8s_node_name, k8s_node_labels, k8s_namespace_name, k8s_namespace_labels, k8s_controller_name, k8s_controller_labels, k8s_pod_name, k8s_pod_labels, container_name, container_image_name, container_labels, external_ticket_id	false	string
realtimeAgentVersion__contains	Free-text filter by Agent version at current time (supports multiple values)	false	string []
rebootRequired	A reboot is required on any endpoint for at least one action on the threat	false	boolean
resolved	This is used for backward- compatibility with API 2.0.	false	boolean
signerIdentity__contains	Free-text filter by threat's signer identity (certificate ID) (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storyline__contains	Free-text filter by threat storyline (supports multiple values)	false	string []
storylines	List of Agent context to search for	false	string []
tenant	Indicates a tenant scope request	false	boolean
threatDetails__contains	Free-text filter by threat details(supports multiple values)	false	string []
updatedAt__gt	Updated at greater than.	false	string
updatedAt__gte	Updated at greater or equal than.	false	string
updatedAt__lt	Updated at lesser than.	false	string
updatedAt__lte	Updated at lesser or equal than.	false	string

uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []
----------------	---	-------	-----------

Export Threats

GET /web/api/v2.1/threats/export

Export data of threats (as seen in the Console > Incidents) that match the filter. Note: Use the filter. This command exports only 20,000 items (each datum is an item).

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
agentids	optional	List of Agent IDs. Example: "225494730938493804,225494730938493915".
agentisactive	optional	Include Agents currently connected to the Management Console
agentmachinetypes	optional	Include Agent machine types. Example: "unknown".
agentmachinetypesnin	optional	Excluded Agent machine types. Example: "unknown".
agenttagsdata	optional	Filter threats by assigned tags to the related agent. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key. Example: {"key1": ["value1_1", "value1_2"], "key2__nin": ["value2"]}
agentversions	optional	Include Agent versions. Example: "2.5.1.1320".
agentversionsnin	optional	Excluded Agent versions. Example: "2.5.1.1320".
analystverdicts	optional	Filter threats by a specific analyst verdict. Example: "true_positive,suspicious".
analystverdictsnin	optional	Exclude threats with specific analyst verdicts. Example: "true_positive,suspicious".
awsrole__contains	optional	Free-text filter by aws role(supports multiple values)
awssecuritygroups__contains	optional	Free-text filter by aws securityGroups(supports multiple values)
awssubnetids__contains	optional	Free-text filter by aws subnet ids (supports multiple values)
azureresourcegroup__contains	optional	Free-text filter by azure resource group(supports multiple values)

classifications	optional	List of threat classifications to search
classificationsnin	optional	List of threat classifications not to search
classificationsources	optional	Classification sources list. Example: "Cloud".
classificationsourcesnin	optional	Classification sources list to exclude. Example: "Cloud".
cloudaccount__contains	optional	Free-text filter by cloud account (supports multiple values)
cloudimage__contains	optional	Free-text filter by cloud image (supports multiple values)
cloudinstanceid__contains	optional	Free-text filter by cloud instance id(supports multiple values)
cloudinstancesize__contains	optional	Free-text filter by cloud instance size(supports multiple values)
cloudlocation__contains	optional	Free-text filter by cloud location (supports multiple values)
cloudnetwork__contains	optional	Free-text filter by cloud network (supports multiple values)
cloudprovider	optional	Agents from which cloud provider
cloudprovidernin	optional	Exclude Agents from these cloud provider
collectionids	optional	List of collection IDs to search. Example: "225494730938493804,225494730938493915".
commandlinearguments__contains	optional	Free-text filter by threat command line arguments (supports multiple values). Example: "/usr/sbin/,wget".
computername__contains	optional	Free-text filter by computer name (supports multiple values). Example: "john-office,WIN".
confidencelevels	optional	Filter threats by a specific confidence level. Example: "malicious".
confidencelevelsnin	optional	Exclude threats with specific confidence level. Example: "malicious".
containerimagename__contains	optional	Free-text filter by the endpoint container image name (supports multiple values)
containerlabels__contains	optional	Free-text filter by the endpoint container labels (supports multiple values)
containername__contains	optional	Free-text filter by the endpoint container name (supports multiple values)
contenthash__contains	optional	Free-text filter by file content hash (supports multiple values). Example: "5f09bcff3".

contenthashes	optional	List of sha1 hashes to search for. Example: "d,d,d,5,0,3,0,a,3,d,0,2,9,f,3,8,4,5,f,c,1,0,5,2,4,1,9,8,2,9,f,0,8,f,3,1,2,2,4,0".
countsfor	optional	comma-separated list of fields to be shown. Example: "osTypes,machineTypes".
createdat__gt	optional	Created at greater than. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	Created at greater or equal than. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	Created at lesser than. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	Created at lesser or equal than. Example: "2018-02-27T04:49:26.257525Z".
detectionagentdomain__contains	optional	Free-text filter by Agent domain at detection time (supports multiple values). Example: "sentinel,sentinelone.com".
detectionagentversion__contains	optional	Free-text filter by Agent version at detection time (supports multiple values). Example: "1.1.1.1,2.2".
detectionengines	optional	Included engines. Example: "reputation".
detectionenginesnin	optional	Excluded engines. Example: "reputation".
displayname	optional	Display name
engines	optional	Included engines. Example: "reputation".
enginesnin	optional	Excluded engines. Example: "reputation".
externalticketexists	optional	The threat contains ticket number
externalticketid__contains	optional	Free-text filter by the threat external ticket ID (supports multiple values)
externalticketids	optional	External ticket ID for the threat
failedactions	optional	At least one action failed on the threat
filepath__contains	optional	Free-text filter by file path (supports multiple values). Example: "\\MyUser\\Downloads".
gcpserviceaccount__contains	optional	Free-text filter by gcp service account (supports multiple values)
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
hasagenttags	optional	Include only Threats whose Agent is assigned any tags if True, or none if False

ids	optional	List of threat IDs. Example: "225494730938493804,225494730938493915".
incidentstatuses	optional	Filter threats by a specific incident status. Example: "unresolved,in_progress".
incidentstatusesnin	optional	Exclude threats with specific incident statuses. Example: "unresolved,in_progress".
initiatedby	optional	Only include threats from specific initiating sources. Example: "agent_policy,dv_command".
initiatedbynin	optional	Exclude threats with specific initiating sources. Example: "agent_policy,dv_command".
initiatedbyusername__contains	optional	Free-text filter by the username that initiated that threat (supports multiple values). Example: "John,John Doe".
k8sclustername__contains	optional	Free-text filter by the endpoint Kubernetes cluster name (supports multiple values)
k8scontrollerlabels__contains	optional	Free-text filter by the endpoint Kubernetes controller labels (supports multiple values)
k8scontrollername__contains	optional	Free-text filter by the endpoint Kubernetes controller name (supports multiple values)
k8snamespacelabels__contains	optional	Free-text filter by the endpoint Kubernetes namespace labels (supports multiple values)
k8snamespace__contains	optional	Free-text filter by the endpoint Kubernetes namespace name (supports multiple values)
k8snodelabels__contains	optional	Free-text filter by the endpoint Kubernetes node labels (supports multiple values)
k8snodename__contains	optional	Free-text filter by the endpoint Kubernetes node name (supports multiple values)
k8spodlabels__contains	optional	Free-text filter by the endpoint Kubernetes pod labels (supports multiple values)
k8spodname__contains	optional	Free-text filter by the endpoint Kubernetes pod name (supports multiple values)
mitigatedpreemptively	optional	If the threat was detected pre-execution or post-execution
mitigationstatuses	optional	Filter threats by a specific status. Example: "not_mitigated".
mitigationstatusesnin	optional	Filter threats not by a specific status. Example: "not_mitigated".
noteexists	optional	The threat contains at least one note

originatedprocess__contains	optional	Free-text filter by the originated process name of the threat (supports multiple values)
osarchs	optional	Included OS Architectures. Example: "32 bit".
osnames	optional	
osnamesnin	optional	
ostypes	optional	Included OS types. Example: "linux".
ostypesnin	optional	Excluded OS types. Example: "linux".
pendingactions	optional	At least one action is pending for the Agent for the threat
publishername__contains	optional	Free-text filter by threat's publisher name (supports multiple values). Example: "GOOGLE,Apple Inc.".
query	optional	Full text search for fields: threat_details, content_hash, computer_name, file_path, uuid, detection_agent_version, realtime_agent_version, detection_agent_domain, command_line_arguments, initiated_by_username, storyline, originated_process, k8s_cluster_name, k8s_node_name, k8s_node_labels, k8s_namespace_name, k8s_namespace_labels, k8s_controller_name, k8s_controller_labels, k8s_pod_name, k8s_pod_labels, container_name, container_image_name, container_labels, external_ticket_id
realtimeagentversion__contains	optional	Free-text filter by Agent version at current time (supports multiple values). Example: "1.1.1.1,2.2.".
rebootrequired	optional	A reboot is required on any endpoint for at least one action on the threat
resolved	optional	This is used for backward-compatibility with API 2.0.
signeridentity__contains	optional	Free-text filter by threat's signer identity (certificate ID) (supports multiple values). Example: "3BDA323E552DB1FDC0A9DD871E8CADD A2FCBB419".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
storyline__contains	optional	Free-text filter by threat storyline (supports multiple values). Example: "0000C2E97648,0006FC73-77B4-470F-AAC7-".
storylines	optional	List of Agent context to search for
tenant	optional	Indicates a tenant scope request
threatdetails__contains	optional	Free-text filter by threat details(supports multiple values). Example: "malware.exe,virus.exe".

updatedat__gt	optional	Updated at greater than. Example: "2018-02-27T04:49:26.257525Z".
updatedat__gte	optional	Updated at greater or equal than. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lt	optional	Updated at lesser than. Example: "2018-02-27T04:49:26.257525Z".
updatedat__lte	optional	Updated at lesser or equal than. Example: "2018-02-27T04:49:26.257525Z".
uuid__contains	optional	Free-text filter by Agent UUID (supports multiple values). Example: "e92-01928,b055".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Add to Blocklist (Deep Visibility)

POST /web/api/v2.1/threats/dv-add-to-blacklist

From Deep Visibility results, add a SHA1 hash to the Blocklist. Set the scope of the Blocklist: Global, Account, Site, or Group. The SHA1 and the Agent ID are required (see Deep Visibility > Get Events). Your role must have permissions to change the Blocklist - Admin, IR Team, SOC - and your user scope access must include the scope of the Agent. The target scope is the Group, Site, or Account of the Agent. Deep Visibility requires Complete SKU.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Add to Blocklist (Deep Visibility) - response - data table
errors	Errors	false	array

Add to Blocklist (Deep Visibility) - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Add to Blocklist (Deep Visibility) - body - data table

Add to Blocklist (Deep Visibility) - body - data

Name	Description	Required	Value
targetScope	Scope of Restrictions to which each hash is added	true	enum
hashes	List of hashes with their source agents	false	see Add to Blocklist (Deep Visibility) - body - hashes table

Add to Blocklist (Deep Visibility) - body - hashes

Name	Description	Required	Value
agentId	Agent that reported the DV event	true	string
hash	Hash to add to Restrictions	false	string

Mark as Threat (Deep Visibility)

POST /web/api/v2.1/threats/dv-mark-as-threat

Mark an event from Deep Visibility data as a threat. (see Deep Visibility > Get Events).Your role must have permissions to Mark as Threat - Admin, IR Team, SOC. The item becomes marked as a threat and the Management adds it to the blocklist. If this threat is detected on an endpoint, the Agent blocks it immediately.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Mark as Threat (Deep Visibility) - response - data table
errors	Errors	false	array

Mark as Threat (Deep Visibility) - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Mark as Threat (Deep Visibility) - body - data table

Mark as Threat (Deep Visibility) - body - data

Name	Description	Required	Value
status	Desired status to mark the events with	true	enum
events	List of DV events with their agents	false	see Mark as Threat (Deep Visibility) - body - events table
initiatedBy	Initiated by	false	enum

Mark as Threat (Deep Visibility) - body - events

Name	Description	Required	Value
storyline	Storyline of the marked event	true	string
agentId	Id if an agent that reported the DV event. Is preceded by agent_uuid.	false	string
agentUuid	Uuid if an agent that reported the DV event. Takes precedence over agent_id.	false	string

Mitigate Alerts

POST /web/api/v2.1/threats/mitigate-alerts

Mark an alerts as a threat and run mitigation action from the Management UI.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Mitigate Alerts - response - data table
errors	Errors	false	array

Mitigate Alerts - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Mitigate Alerts - body - data table

Mitigate Alerts - body - data

Name	Description	Required	Value
action	Mitigation action	false	enum
alerts	List of alerts to mitigate	false	see Mitigate Alerts - body - alerts table

Mitigate Alerts - body - alerts

Name	Description	Required	Value
agentId	Agent ID that reported the alert	true	string
storyline	Storyline of the mitigated alert	true	string

Export Mitigation Report

GET /web/api/v2.1/threats/mitigation-report/{report_id}

Export the mitigation report as a CSV file.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Updated Threat Incident

POST /web/api/v2.1/threats/incident

Update the incident details of a threat.

Response Messages

200 - Threats incident successfully updated

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Updated Threat Incident - response - data table
errors	Errors	false	array

Updated Threat Incident - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer
details	Result details for each threat	false	see Updated Threat Incident - response - details table

Updated Threat Incident - response - details

Name	Description	Required	Value
analystVerdict	Result of changing the threat's analyst verdict as part of changing the threat's status	false	enum
result	Result of changing the threat's status	false	enum
threatId	Threat id	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Updated Threat Incident - body - data table
filter	Filter	true	see Updated Threat Incident - body - filter table

Updated Threat Incident - body - data

Name	Description	Required	Value
incidentStatus	Incident status	true	enum
analystVerdict	The analyst verdict to set for the Threats	false	enum

Updated Threat Incident - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
agentIds	List of Agent IDs	false	string []
agentIsActive	Include Agents currently connected to the Management Console	false	boolean
agentMachineTypes	Include Agent machine types	false	string []
agentMachineTypesNin	Excluded Agent machine types	false	string []
agentTagsData	Filter threats by assigned tags to the related agent. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
agentVersions	Include Agent versions	false	string []
agentVersionsNin	Excluded Agent versions	false	string []
analystVerdicts	Filter threats by a specific analyst verdict	false	string []
analystVerdictsNin	Exclude threats with specific analyst verdicts	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []

awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
classifications	List of threat classifications to search	false	string []
classificationsNin	List of threat classifications not to search	false	string []
classificationSources	Classification sources list	false	string []
classificationSourcesNin	Classification sources list to exclude	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
collectionIds	List of collection IDs to search	false	string []
commandLineArguments__contains	Free-text filter by threat command line arguments (supports multiple values)	false	string []
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
confidenceLevels	Filter threats by a specific confidence level	false	string []
confidenceLevelsNin	Exclude threats with specific confidence level	false	string []
containerImageName__contains	Free-text filter by the endpoint container image name (supports multiple values)	false	string []

containerLabels__contains	Free-text filter by the endpoint container labels (supports multiple values)	false	string []
containerName__contains	Free-text filter by the endpoint container name (supports multiple values)	false	string []
contentHash__contains	Free-text filter by file content hash (supports multiple values)	false	string []
contentHashes	List of sha1 hashes to search for	false	string []
countsFor	comma-separated list of fields to be shown	false	string
createdAt__gt	Created at greater than.	false	string
createdAt__gte	Created at greater or equal than.	false	string
createdAt__lt	Created at lesser than.	false	string
createdAt__lte	Created at lesser or equal than.	false	string
detectionAgentDomain__contains	Free-text filter by Agent domain at detection time (supports multiple values)	false	string []
detectionAgentVersion__contains	Free-text filter by Agent version at detection time (supports multiple values)	false	string []
detectionEngines	Included engines	false	string []
detectionEnginesNin	Excluded engines	false	string []
displayName	Display name	false	string
engines	Included engines	false	string []
enginesNin	Excluded engines	false	string []
externalTicketExists	The threat contains ticket number	false	boolean
externalTicketId__contains	Free-text filter by the threat external ticket ID (supports multiple values)	false	string []
externalTicketIds	External ticket ID for the threat	false	string []
failedActions	At least one action failed on the threat	false	boolean
filePath__contains	Free-text filter by file path (supports multiple values)	false	string []
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []

groupIds	List of Group IDs to filter by	false	string []
hasAgentTags	Include only Threats whose Agent is assigned any tags if True, or none if False	false	boolean
ids	List of threat IDs	false	string []
incidentStatuses	Filter threats by a specific incident status	false	string []
incidentStatusesNin	Exclude threats with specific incident statuses	false	string []
initiatedBy	Only include threats from specific initiating sources	false	string []
initiatedByNin	Exclude threats with specific initiating sources	false	string []
initiatedByUsername__contains	Free-text filter by the username that initiated that threat (supports multiple values)	false	string []
k8sClusterName__contains	Free-text filter by the endpoint Kubernetes cluster name (supports multiple values)	false	string []
k8sControllerLabels__contains	Free-text filter by the endpoint Kubernetes controller labels (supports multiple values)	false	string []
k8sControllerName__contains	Free-text filter by the endpoint Kubernetes controller name (supports multiple values)	false	string []
k8sNamespaceLabels__contains	Free-text filter by the endpoint Kubernetes namespace labels (supports multiple values)	false	string []
k8sNamespaceName__contains	Free-text filter by the endpoint Kubernetes namespace name (supports multiple values)	false	string []
k8sNodeLabels__contains	Free-text filter by the endpoint Kubernetes node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by the endpoint Kubernetes node name (supports multiple values)	false	string []
k8sPodLabels__contains	Free-text filter by the endpoint Kubernetes pod labels (supports multiple values)	false	string []

k8sPodName__contains	Free-text filter by the endpoint Kubernetes pod name (supports multiple values)	false	string []
limit	Limit	false	integer
mitigatedPreemptively	If the threat was detected pre-execution or post-execution	false	boolean
mitigationStatuses	Filter threats by a specific status	false	string []
mitigationStatusesNin	Filter threats not by a specific status	false	string []
noteExists	The threat contains at least one note	false	boolean
originatedProcess__contains	Free-text filter by the originated process name of the threat (supports multiple values)	false	string []
osArchs	Included OS Architectures	false	string []
osNames		false	string []
osNamesNin		false	string []
osTypes	Included OS types	false	string []
osTypesNin	Excluded OS types	false	string []
pendingActions	At least one action is pending for the Agent for the threat	false	boolean
publisherName__contains	Free-text filter by threat's publisher name (supports multiple values)	false	string []
query	Full text search for fields: threat_details, content_hash, computer_name, file_path, uuid, detection_agent_version, realtime_agent_version, detection_agent_domain, command_line_arguments, initiated_by_username, storyline, originated_process, k8s_cluster_name, k8s_node_name, k8s_node_labels, k8s_namespace_name, k8s_namespace_labels, k8s_controller_name, k8s_controller_labels, k8s_pod_name, k8s_pod_labels, container_name, container_image_name, container_labels, external_ticket_id	false	string
realtimeAgentVersion__contains	Free-text filter by Agent version at	false	string []

	current time (supports multiple values)		
rebootRequired	A reboot is required on any endpoint for at least one action on the threat	false	boolean
resolved	This is used for backward-compatibility with API 2.0.	false	boolean
signerIdentity__contains	Free-text filter by threat's signer identity (certificate ID) (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storyline__contains	Free-text filter by threat storyline (supports multiple values)	false	string []
storylines	List of Agent context to search for	false	string []
tenant	Indicates a tenant scope request	false	boolean
threatDetails__contains	Free-text filter by threat details(supports multiple values)	false	string []
updatedAt__gt	Updated at greater than.	false	string
updatedAt__gte	Updated at greater or equal than.	false	string
updatedAt__lt	Updated at lesser than.	false	string
updatedAt__lte	Updated at lesser or equal than.	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []

Update Threat Analyst Verdict

POST /web/api/v2.1/threats/analyst-verdict

Change the verdict of a threat, as determined by a Console user.

Response Messages

200 - Threats analyst verdict successfully updated

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Threat Analyst Verdict - response - data table
errors	Errors	false	array

Update Threat Analyst Verdict - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer
details	Result details for each threat	false	see Update Threat Analyst Verdict - response - details table

Update Threat Analyst Verdict - response - details

Name	Description	Required	Value
result	Result of changing the threat's analyst verdict	false	enum
threatId	Threat id	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Threat Analyst Verdict - body - data table
filter	Filter	true	see Update Threat Analyst Verdict - body - filter table

Update Threat Analyst Verdict - body - data

Name	Description	Required	Value
analystVerdict	Analyst verdict	true	enum

Update Threat Analyst Verdict - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
agentIds	List of Agent IDs	false	string []
agentIsActive	Include Agents currently connected to the Management Console	false	boolean
agentMachineTypes	Include Agent machine types	false	string []
agentMachineTypesNin	Excluded Agent machine types	false	string []
agentTagsData	Filter threats by assigned tags to the related agent. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
agentVersions	Include Agent versions	false	string []
agentVersionsNin	Excluded Agent versions	false	string []
analystVerdicts	Filter threats by a specific analyst verdict	false	string []
analystVerdictsNin	Exclude threats with specific analyst verdicts	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []

azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
classifications	List of threat classifications to search	false	string []
classificationsNin	List of threat classifications not to search	false	string []
classificationSources	Classification sources list	false	string []
classificationSourcesNin	Classification sources list to exclude	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
collectionIds	List of collection IDs to search	false	string []
commandLineArguments__contains	Free-text filter by threat command line arguments (supports multiple values)	false	string []
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
confidenceLevels	Filter threats by a specific confidence level	false	string []
confidenceLevelsNin	Exclude threats with specific confidence level	false	string []
containerImageName__contains	Free-text filter by the endpoint container image name (supports multiple values)	false	string []
containerLabels__contains	Free-text filter by the endpoint container labels (supports multiple values)	false	string []

containerName__contains	Free-text filter by the endpoint container name (supports multiple values)	false	string []
contentHash__contains	Free-text filter by file content hash (supports multiple values)	false	string []
contentHashes	List of sha1 hashes to search for	false	string []
countsFor	comma-separated list of fields to be shown	false	string
createdAt__gt	Created at greater than.	false	string
createdAt__gte	Created at greater or equal than.	false	string
createdAt__lt	Created at lesser than.	false	string
createdAt__lte	Created at lesser or equal than.	false	string
detectionAgentDomain__contains	Free-text filter by Agent domain at detection time (supports multiple values)	false	string []
detectionAgentVersion__contains	Free-text filter by Agent version at detection time (supports multiple values)	false	string []
detectionEngines	Included engines	false	string []
detectionEnginesNin	Excluded engines	false	string []
displayName	Display name	false	string
engines	Included engines	false	string []
enginesNin	Excluded engines	false	string []
externalTicketExists	The threat contains ticket number	false	boolean
externalTicketId__contains	Free-text filter by the threat external ticket ID (supports multiple values)	false	string []
externalTicketIds	External ticket ID for the threat	false	string []
failedActions	At least one action failed on the threat	false	boolean
filePath__contains	Free-text filter by file path (supports multiple values)	false	string []
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasAgentTags	Include only Threats whose Agent is assigned any tags if True, or none if	false	boolean

	False		
ids	List of threat IDs	false	string []
incidentStatuses	Filter threats by a specific incident status	false	string []
incidentStatusesNin	Exclude threats with specific incident statuses	false	string []
initiatedBy	Only include threats from specific initiating sources	false	string []
initiatedByNin	Exclude threats with specific initiating sources	false	string []
initiatedByUsername__contains	Free-text filter by the username that initiated that threat (supports multiple values)	false	string []
k8sClusterName__contains	Free-text filter by the endpoint Kubernetes cluster name (supports multiple values)	false	string []
k8sControllerLabels__contains	Free-text filter by the endpoint Kubernetes controller labels (supports multiple values)	false	string []
k8sControllerName__contains	Free-text filter by the endpoint Kubernetes controller name (supports multiple values)	false	string []
k8sNamespaceLabels__contains	Free-text filter by the endpoint Kubernetes namespace labels (supports multiple values)	false	string []
k8sNamespaceName__contains	Free-text filter by the endpoint Kubernetes namespace name (supports multiple values)	false	string []
k8sNodeLabels__contains	Free-text filter by the endpoint Kubernetes node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by the endpoint Kubernetes node name (supports multiple values)	false	string []
k8sPodLabels__contains	Free-text filter by the endpoint Kubernetes pod labels (supports multiple values)	false	string []
k8sPodName__contains	Free-text filter by the endpoint Kubernetes pod name (supports multiple values)	false	string []

limit	Limit	false	integer
mitigatedPreemptively	If the threat was detected pre-execution or post-execution	false	boolean
mitigationStatuses	Filter threats by a specific status	false	string []
mitigationStatusesNin	Filter threats not by a specific status	false	string []
noteExists	The threat contains at least one note	false	boolean
originatedProcess__contains	Free-text filter by the originated process name of the threat (supports multiple values)	false	string []
osArchs	Included OS Architectures	false	string []
osNames		false	string []
osNamesNin		false	string []
osTypes	Included OS types	false	string []
osTypesNin	Excluded OS types	false	string []
pendingActions	At least one action is pending for the Agent for the threat	false	boolean
publisherName__contains	Free-text filter by threat's publisher name (supports multiple values)	false	string []
query	Full text search for fields: threat_details, content_hash, computer_name, file_path, uuid, detection_agent_version, realtime_agent_version, detection_agent_domain, command_line_arguments, initiated_by_username, storyline, originated_process, k8s_cluster_name, k8s_node_name, k8s_node_labels, k8s_namespace_name, k8s_namespace_labels, k8s_controller_name, k8s_controller_labels, k8s_pod_name, k8s_pod_labels, container_name, container_image_name, container_labels, external_ticket_id	false	string
realtimeAgentVersion__contains	Free-text filter by Agent version at current time (supports multiple values)	false	string []
rebootRequired	A reboot is required on any endpoint	false	boolean

	for at least one action on the threat		
resolved	This is used for backward-compatibility with API 2.0.	false	boolean
signerIdentity__contains	Free-text filter by threat's signer identity (certificate ID) (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storyline__contains	Free-text filter by threat storyline (supports multiple values)	false	string []
storylines	List of Agent context to search for	false	string []
tenant	Indicates a tenant scope request	false	boolean
threatDetails__contains	Free-text filter by threat details(supports multiple values)	false	string []
updatedAt__gt	Updated at greater than.	false	string
updatedAt__gte	Updated at greater or equal than.	false	string
updatedAt__lt	Updated at lesser than.	false	string
updatedAt__lte	Updated at lesser or equal than.	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []

Update Threat External Ticket ID

POST /web/api/v2.1/threats/external-ticket-id

Change the external ticket ID of a threat.

Response Messages

200 - Threats external ticket id successfully updated

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Update Threat External Ticket ID - response - data table
errors	Errors	false	array

Update Threat External Ticket ID - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Threat External Ticket ID - body - data table
filter	Filter	true	see Update Threat External Ticket ID - body - filter table

Update Threat External Ticket ID - body - data

Name	Description	Required	Value
externalTicketId	External ticket id	true	string

Update Threat External Ticket ID - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
agentIds	List of Agent IDs	false	string []
agentIsActive	Include Agents currently connected to the Management Console	false	boolean
agentMachineTypes	Include Agent machine types	false	string []
agentMachineTypesNin	Excluded Agent machine types	false	string []
agentTagsData	Filter threats by assigned tags to the related agent. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
agentVersions	Include Agent versions	false	string []
agentVersionsNin	Excluded Agent versions	false	string []
analystVerdicts	Filter threats by a specific analyst verdict	false	string []
analystVerdictsNin	Exclude threats with specific analyst verdicts	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []

azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
classifications	List of threat classifications to search	false	string []
classificationsNin	List of threat classifications not to search	false	string []
classificationSources	Classification sources list	false	string []
classificationSourcesNin	Classification sources list to exclude	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
collectionIds	List of collection IDs to search	false	string []
commandLineArguments__contains	Free-text filter by threat command line arguments (supports multiple values)	false	string []
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
confidenceLevels	Filter threats by a specific confidence level	false	string []
confidenceLevelsNin	Exclude threats with specific confidence level	false	string []
containerImageName__contains	Free-text filter by the endpoint container image name (supports multiple values)	false	string []
containerLabels__contains	Free-text filter by the endpoint container labels (supports multiple values)	false	string []

containerName__contains	Free-text filter by the endpoint container name (supports multiple values)	false	string []
contentHash__contains	Free-text filter by file content hash (supports multiple values)	false	string []
contentHashes	List of sha1 hashes to search for	false	string []
countsFor	comma-separated list of fields to be shown	false	string
createdAt__gt	Created at greater than.	false	string
createdAt__gte	Created at greater or equal than.	false	string
createdAt__lt	Created at lesser than.	false	string
createdAt__lte	Created at lesser or equal than.	false	string
detectionAgentDomain__contains	Free-text filter by Agent domain at detection time (supports multiple values)	false	string []
detectionAgentVersion__contains	Free-text filter by Agent version at detection time (supports multiple values)	false	string []
detectionEngines	Included engines	false	string []
detectionEnginesNin	Excluded engines	false	string []
displayName	Display name	false	string
engines	Included engines	false	string []
enginesNin	Excluded engines	false	string []
externalTicketExists	The threat contains ticket number	false	boolean
externalTicketId__contains	Free-text filter by the threat external ticket ID (supports multiple values)	false	string []
externalTicketIds	External ticket ID for the threat	false	string []
failedActions	At least one action failed on the threat	false	boolean
filePath__contains	Free-text filter by file path (supports multiple values)	false	string []
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasAgentTags	Include only Threats whose Agent is assigned any tags if True, or none if	false	boolean

	False		
ids	List of threat IDs	false	string []
incidentStatuses	Filter threats by a specific incident status	false	string []
incidentStatusesNin	Exclude threats with specific incident statuses	false	string []
initiatedBy	Only include threats from specific initiating sources	false	string []
initiatedByNin	Exclude threats with specific initiating sources	false	string []
initiatedByUsername__contains	Free-text filter by the username that initiated that threat (supports multiple values)	false	string []
k8sClusterName__contains	Free-text filter by the endpoint Kubernetes cluster name (supports multiple values)	false	string []
k8sControllerLabels__contains	Free-text filter by the endpoint Kubernetes controller labels (supports multiple values)	false	string []
k8sControllerName__contains	Free-text filter by the endpoint Kubernetes controller name (supports multiple values)	false	string []
k8sNamespaceLabels__contains	Free-text filter by the endpoint Kubernetes namespace labels (supports multiple values)	false	string []
k8sNamespaceName__contains	Free-text filter by the endpoint Kubernetes namespace name (supports multiple values)	false	string []
k8sNodeLabels__contains	Free-text filter by the endpoint Kubernetes node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by the endpoint Kubernetes node name (supports multiple values)	false	string []
k8sPodLabels__contains	Free-text filter by the endpoint Kubernetes pod labels (supports multiple values)	false	string []
k8sPodName__contains	Free-text filter by the endpoint Kubernetes pod name (supports multiple values)	false	string []

limit	Limit	false	integer
mitigatedPreemptively	If the threat was detected pre-execution or post-execution	false	boolean
mitigationStatuses	Filter threats by a specific status	false	string []
mitigationStatusesNin	Filter threats not by a specific status	false	string []
noteExists	The threat contains at least one note	false	boolean
originatedProcess__contains	Free-text filter by the originated process name of the threat (supports multiple values)	false	string []
osArchs	Included OS Architectures	false	string []
osNames		false	string []
osNamesNin		false	string []
osTypes	Included OS types	false	string []
osTypesNin	Excluded OS types	false	string []
pendingActions	At least one action is pending for the Agent for the threat	false	boolean
publisherName__contains	Free-text filter by threat's publisher name (supports multiple values)	false	string []
query	Full text search for fields: threat_details, content_hash, computer_name, file_path, uuid, detection_agent_version, realtime_agent_version, detection_agent_domain, command_line_arguments, initiated_by_username, storyline, originated_process, k8s_cluster_name, k8s_node_name, k8s_node_labels, k8s_namespace_name, k8s_namespace_labels, k8s_controller_name, k8s_controller_labels, k8s_pod_name, k8s_pod_labels, container_name, container_image_name, container_labels, external_ticket_id	false	string
realtimeAgentVersion__contains	Free-text filter by Agent version at current time (supports multiple values)	false	string []
rebootRequired	A reboot is required on any endpoint	false	boolean

	for at least one action on the threat		
resolved	This is used for backward-compatibility with API 2.0.	false	boolean
signerIdentity__contains	Free-text filter by threat's signer identity (certificate ID) (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storyline__contains	Free-text filter by threat storyline (supports multiple values)	false	string []
storylines	List of Agent context to search for	false	string []
tenant	Indicates a tenant scope request	false	boolean
threatDetails__contains	Free-text filter by threat details(supports multiple values)	false	string []
updatedAt__gt	Updated at greater than.	false	string
updatedAt__gte	Updated at greater or equal than.	false	string
updatedAt__lt	Updated at lesser than.	false	string
updatedAt__lte	Updated at lesser or equal than.	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []

Download from cloud

GET /web/api/v2.1/threats/{threat_id}/download-from-cloud

Download threat file from cloud.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Download from cloud - response - data table

errors	Errors	false	array
--------	--------	-------	-------

Download from cloud - response - data

Name	Description	Required	Value
downloadUrl	Threat file download URL	false	string
fileName	Threat file name	false	string

Disconnect Container

POST /web/api/v2.1/threats/actions/container-network-disconnect

Network quarantine a specific container

Response Messages

200 - Disconnect command was created

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Disconnect Container - response - data table
errors	Errors	false	array

Disconnect Container - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Disconnect Container - body - data table
filter	Use any of the filtering options to control the list of affected threats. You can use any combination of filters to narrow down the list (For example "apply to only active threats from Linux endpoints"). You can also leave this field empty to apply to all available threats.	true	see Disconnect Container - body - filter table

Disconnect Container - body - data

Name	Description	Required	Value
containerId	Container id	true	string

Disconnect Container - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
agentIds	List of Agent IDs	false	string []
agentIsActive	Include Agents currently connected to the Management Console	false	boolean
agentMachineTypes	Include Agent machine types	false	string []
agentMachineTypesNin	Excluded Agent machine types	false	string []
agentTagsData	Filter threats by assigned tags to the related agent. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
agentVersions	Include Agent versions	false	string []
agentVersionsNin	Excluded Agent versions	false	string []
analystVerdicts	Filter threats by a specific analyst verdict	false	string []
analystVerdictsNin	Exclude threats with specific analyst verdicts	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []

azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
classifications	List of threat classifications to search	false	string []
classificationsNin	List of threat classifications not to search	false	string []
classificationSources	Classification sources list	false	string []
classificationSourcesNin	Classification sources list to exclude	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
collectionIds	List of collection IDs to search	false	string []
commandLineArguments__contains	Free-text filter by threat command line arguments (supports multiple values)	false	string []
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
confidenceLevels	Filter threats by a specific confidence level	false	string []
confidenceLevelsNin	Exclude threats with specific confidence level	false	string []
containerImageName__contains	Free-text filter by the endpoint container image name (supports multiple values)	false	string []
containerLabels__contains	Free-text filter by the endpoint container labels (supports multiple values)	false	string []

containerName__contains	Free-text filter by the endpoint container name (supports multiple values)	false	string []
contentHash__contains	Free-text filter by file content hash (supports multiple values)	false	string []
contentHashes	List of sha1 hashes to search for	false	string []
countsFor	comma-separated list of fields to be shown	false	string
createdAt__gt	Created at greater than.	false	string
createdAt__gte	Created at greater or equal than.	false	string
createdAt__lt	Created at lesser than.	false	string
createdAt__lte	Created at lesser or equal than.	false	string
detectionAgentDomain__contains	Free-text filter by Agent domain at detection time (supports multiple values)	false	string []
detectionAgentVersion__contains	Free-text filter by Agent version at detection time (supports multiple values)	false	string []
detectionEngines	Included engines	false	string []
detectionEnginesNin	Excluded engines	false	string []
displayName	Display name	false	string
engines	Included engines	false	string []
enginesNin	Excluded engines	false	string []
externalTicketExists	The threat contains ticket number	false	boolean
externalTicketId__contains	Free-text filter by the threat external ticket ID (supports multiple values)	false	string []
externalTicketIds	External ticket ID for the threat	false	string []
failedActions	At least one action failed on the threat	false	boolean
filePath__contains	Free-text filter by file path (supports multiple values)	false	string []
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasAgentTags	Include only Threats whose Agent is assigned any tags if True, or none if	false	boolean

	False		
ids	List of threat IDs	false	string []
incidentStatuses	Filter threats by a specific incident status	false	string []
incidentStatusesNin	Exclude threats with specific incident statuses	false	string []
initiatedBy	Only include threats from specific initiating sources	false	string []
initiatedByNin	Exclude threats with specific initiating sources	false	string []
initiatedByUsername__contains	Free-text filter by the username that initiated that threat (supports multiple values)	false	string []
k8sClusterName__contains	Free-text filter by the endpoint Kubernetes cluster name (supports multiple values)	false	string []
k8sControllerLabels__contains	Free-text filter by the endpoint Kubernetes controller labels (supports multiple values)	false	string []
k8sControllerName__contains	Free-text filter by the endpoint Kubernetes controller name (supports multiple values)	false	string []
k8sNamespaceLabels__contains	Free-text filter by the endpoint Kubernetes namespace labels (supports multiple values)	false	string []
k8sNamespaceName__contains	Free-text filter by the endpoint Kubernetes namespace name (supports multiple values)	false	string []
k8sNodeLabels__contains	Free-text filter by the endpoint Kubernetes node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by the endpoint Kubernetes node name (supports multiple values)	false	string []
k8sPodLabels__contains	Free-text filter by the endpoint Kubernetes pod labels (supports multiple values)	false	string []
k8sPodName__contains	Free-text filter by the endpoint Kubernetes pod name (supports multiple values)	false	string []

limit	Limit	false	integer
mitigatedPreemptively	If the threat was detected pre-execution or post-execution	false	boolean
mitigationStatuses	Filter threats by a specific status	false	string []
mitigationStatusesNin	Filter threats not by a specific status	false	string []
noteExists	The threat contains at least one note	false	boolean
originatedProcess__contains	Free-text filter by the originated process name of the threat (supports multiple values)	false	string []
osArchs	Included OS Architectures	false	string []
osNames		false	string []
osNamesNin		false	string []
osTypes	Included OS types	false	string []
osTypesNin	Excluded OS types	false	string []
pendingActions	At least one action is pending for the Agent for the threat	false	boolean
publisherName__contains	Free-text filter by threat's publisher name (supports multiple values)	false	string []
query	Full text search for fields: threat_details, content_hash, computer_name, file_path, uuid, detection_agent_version, realtime_agent_version, detection_agent_domain, command_line_arguments, initiated_by_username, storyline, originated_process, k8s_cluster_name, k8s_node_name, k8s_node_labels, k8s_namespace_name, k8s_namespace_labels, k8s_controller_name, k8s_controller_labels, k8s_pod_name, k8s_pod_labels, container_name, container_image_name, container_labels, external_ticket_id	false	string
realtimeAgentVersion__contains	Free-text filter by Agent version at current time (supports multiple values)	false	string []
rebootRequired	A reboot is required on any endpoint	false	boolean

	for at least one action on the threat		
resolved	This is used for backward-compatibility with API 2.0.	false	boolean
signerIdentity__contains	Free-text filter by threat's signer identity (certificate ID) (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storyline__contains	Free-text filter by threat storyline (supports multiple values)	false	string []
storylines	List of Agent context to search for	false	string []
tenant	Indicates a tenant scope request	false	boolean
threatDetails__contains	Free-text filter by threat details(supports multiple values)	false	string []
updatedAt__gt	Updated at greater than.	false	string
updatedAt__gte	Updated at greater or equal than.	false	string
updatedAt__lt	Updated at lesser than.	false	string
updatedAt__lte	Updated at lesser or equal than.	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []

Reconnect Container

POST /web/api/v2.1/threats/actions/container-network-connect

Restore network to a container that was disconnected

Response Messages

200 - Reconnect command was created

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Reconnect Container - response - data table
errors	Errors	false	array

Reconnect Container - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Reconnect Container - body - data table
filter	Use any of the filtering options to control the list of affected threats. You can use any combination of filters to narrow down the list (For example "apply to only active threats from Linux endpoints"). You can also leave this field empty to apply to all available threats.	true	see Reconnect Container - body - filter table

Reconnect Container - body - data

Name	Description	Required	Value
containerId	Container id	true	string

Reconnect Container - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
agentIds	List of Agent IDs	false	string []
agentIsActive	Include Agents currently connected to the Management Console	false	boolean
agentMachineTypes	Include Agent machine types	false	string []
agentMachineTypesNin	Excluded Agent machine types	false	string []
agentTagsData	Filter threats by assigned tags to the related agent. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
agentVersions	Include Agent versions	false	string []
agentVersionsNin	Excluded Agent versions	false	string []
analystVerdicts	Filter threats by a specific analyst verdict	false	string []
analystVerdictsNin	Exclude threats with specific analyst verdicts	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []

azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
classifications	List of threat classifications to search	false	string []
classificationsNin	List of threat classifications not to search	false	string []
classificationSources	Classification sources list	false	string []
classificationSourcesNin	Classification sources list to exclude	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
collectionIds	List of collection IDs to search	false	string []
commandLineArguments__contains	Free-text filter by threat command line arguments (supports multiple values)	false	string []
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
confidenceLevels	Filter threats by a specific confidence level	false	string []
confidenceLevelsNin	Exclude threats with specific confidence level	false	string []
containerImageName__contains	Free-text filter by the endpoint container image name (supports multiple values)	false	string []
containerLabels__contains	Free-text filter by the endpoint container labels (supports multiple values)	false	string []

containerName__contains	Free-text filter by the endpoint container name (supports multiple values)	false	string []
contentHash__contains	Free-text filter by file content hash (supports multiple values)	false	string []
contentHashes	List of sha1 hashes to search for	false	string []
countsFor	comma-separated list of fields to be shown	false	string
createdAt__gt	Created at greater than.	false	string
createdAt__gte	Created at greater or equal than.	false	string
createdAt__lt	Created at lesser than.	false	string
createdAt__lte	Created at lesser or equal than.	false	string
detectionAgentDomain__contains	Free-text filter by Agent domain at detection time (supports multiple values)	false	string []
detectionAgentVersion__contains	Free-text filter by Agent version at detection time (supports multiple values)	false	string []
detectionEngines	Included engines	false	string []
detectionEnginesNin	Excluded engines	false	string []
displayName	Display name	false	string
engines	Included engines	false	string []
enginesNin	Excluded engines	false	string []
externalTicketExists	The threat contains ticket number	false	boolean
externalTicketId__contains	Free-text filter by the threat external ticket ID (supports multiple values)	false	string []
externalTicketIds	External ticket ID for the threat	false	string []
failedActions	At least one action failed on the threat	false	boolean
filePath__contains	Free-text filter by file path (supports multiple values)	false	string []
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasAgentTags	Include only Threats whose Agent is assigned any tags if True, or none if	false	boolean

	False		
ids	List of threat IDs	false	string []
incidentStatuses	Filter threats by a specific incident status	false	string []
incidentStatusesNin	Exclude threats with specific incident statuses	false	string []
initiatedBy	Only include threats from specific initiating sources	false	string []
initiatedByNin	Exclude threats with specific initiating sources	false	string []
initiatedByUsername__contains	Free-text filter by the username that initiated that threat (supports multiple values)	false	string []
k8sClusterName__contains	Free-text filter by the endpoint Kubernetes cluster name (supports multiple values)	false	string []
k8sControllerLabels__contains	Free-text filter by the endpoint Kubernetes controller labels (supports multiple values)	false	string []
k8sControllerName__contains	Free-text filter by the endpoint Kubernetes controller name (supports multiple values)	false	string []
k8sNamespaceLabels__contains	Free-text filter by the endpoint Kubernetes namespace labels (supports multiple values)	false	string []
k8sNamespaceName__contains	Free-text filter by the endpoint Kubernetes namespace name (supports multiple values)	false	string []
k8sNodeLabels__contains	Free-text filter by the endpoint Kubernetes node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by the endpoint Kubernetes node name (supports multiple values)	false	string []
k8sPodLabels__contains	Free-text filter by the endpoint Kubernetes pod labels (supports multiple values)	false	string []
k8sPodName__contains	Free-text filter by the endpoint Kubernetes pod name (supports multiple values)	false	string []

limit	Limit	false	integer
mitigatedPreemptively	If the threat was detected pre-execution or post-execution	false	boolean
mitigationStatuses	Filter threats by a specific status	false	string []
mitigationStatusesNin	Filter threats not by a specific status	false	string []
noteExists	The threat contains at least one note	false	boolean
originatedProcess__contains	Free-text filter by the originated process name of the threat (supports multiple values)	false	string []
osArchs	Included OS Architectures	false	string []
osNames		false	string []
osNamesNin		false	string []
osTypes	Included OS types	false	string []
osTypesNin	Excluded OS types	false	string []
pendingActions	At least one action is pending for the Agent for the threat	false	boolean
publisherName__contains	Free-text filter by threat's publisher name (supports multiple values)	false	string []
query	Full text search for fields: threat_details, content_hash, computer_name, file_path, uuid, detection_agent_version, realtime_agent_version, detection_agent_domain, command_line_arguments, initiated_by_username, storyline, originated_process, k8s_cluster_name, k8s_node_name, k8s_node_labels, k8s_namespace_name, k8s_namespace_labels, k8s_controller_name, k8s_controller_labels, k8s_pod_name, k8s_pod_labels, container_name, container_image_name, container_labels, external_ticket_id	false	string
realtimeAgentVersion__contains	Free-text filter by Agent version at current time (supports multiple values)	false	string []
rebootRequired	A reboot is required on any endpoint	false	boolean

	for at least one action on the threat		
resolved	This is used for backward-compatibility with API 2.0.	false	boolean
signerIdentity__contains	Free-text filter by threat's signer identity (certificate ID) (supports multiple values)	false	string []
sitelds	List of Site IDs to filter by	false	string []
storyline__contains	Free-text filter by threat storyline (supports multiple values)	false	string []
storylines	List of Agent context to search for	false	string []
tenant	Indicates a tenant scope request	false	boolean
threatDetails__contains	Free-text filter by threat details(supports multiple values)	false	string []
updatedAt__gt	Updated at greater than.	false	string
updatedAt__gte	Updated at greater or equal than.	false	string
updatedAt__lt	Updated at lesser than.	false	string
updatedAt__lte	Updated at lesser or equal than.	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []

Get Quarantined Files

GET /web/api/v2.1/threats/{threat_id}/quarantined-files

Get quarantined files for a single threat by alert ID with pagination.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".

limit	optional	Limit number of returned items (1-1000). Example: "10".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.

Response Messages

200 - List of quarantined files for the threat

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Quarantined Files - response - pagination table
data	Response data	false	see Get Quarantined Files - response - data table
errors	Errors	false	array

Get Quarantined Files - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Quarantined Files - response - data

Name	Description	Required	Value
fileName	Name of the quarantined file	false	string
filePath	Path of the quarantined file	false	string
fileSize	Size of the quarantined file in bytes	false	integer

Delete Quarantined Files

POST /web/api/v2.1/threats/actions/delete-quarantined-files

Delete all quarantined files from selected threats. Sends commands to agents to remove quarantined files for the specified malicious groups.

Response Messages

200 - Delete quarantined files commands created successfully

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
------	-------------	----------	-------

data	Response data	false	see Delete Quarantined Files - response - data table
errors	Errors	false	array

Delete Quarantined Files - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer
details	Result details for each threat	false	see Delete Quarantined Files - response - details table

Delete Quarantined Files - response - details

Name	Description	Required	Value
skipped	Skip details if threat was skipped, null if processed successfully	false	see Delete Quarantined Files - response - skipped table
threatId	Threat id	false	string

Delete Quarantined Files - response - skipped

Name	Description	Required	Value
description	Human-readable description	false	string
reason	Reason	false	enum

Body Schema

Name	Description	Required	Value
filter	Use any of the filtering options to control the list of affected threats. You can use any combination of filters to narrow down the list (For example "apply to only active threats from Linux endpoints"). You can also leave this field empty to apply to all available threats.	true	see Delete Quarantined Files - body - filter table
data	Data	false	see Delete Quarantined Files - body - data table

Delete Quarantined Files - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
agentIds	List of Agent IDs	false	string []
agentsActive	Include Agents currently connected to the Management Console	false	boolean
agentMachineTypes	Include Agent machine types	false	string []
agentMachineTypesNin	Excluded Agent machine types	false	string []
agentTagsData	Filter threats by assigned tags to the related agent. Given in form of a JSON where each key represents a tag key, and each value represents a list of string values to filter by. To filter by unassigned tag values, use __nin suffix in the tag key.	false	string
agentVersions	Include Agent versions	false	string []
agentVersionsNin	Excluded Agent versions	false	string []
analystVerdicts	Filter threats by a specific analyst verdict	false	string []
analystVerdictsNin	Exclude threats with specific analyst verdicts	false	string []
awsRole__contains	Free-text filter by aws role(supports multiple values)	false	string []
awsSecurityGroups__contains	Free-text filter by aws securityGroups(supports multiple values)	false	string []
awsSubnetIds__contains	Free-text filter by aws subnet ids (supports multiple values)	false	string []
azureResourceGroup__contains	Free-text filter by azure resource group(supports multiple values)	false	string []
classifications	List of threat classifications to search	false	string []
classificationsNin	List of threat classifications not to search	false	string []
classificationSources	Classification sources list	false	string []

classificationSourcesNin	Classification sources list to exclude	false	string []
cloudAccount__contains	Free-text filter by cloud account (supports multiple values)	false	string []
cloudImage__contains	Free-text filter by cloud image (supports multiple values)	false	string []
cloudInstanceId__contains	Free-text filter by cloud instance id(supports multiple values)	false	string []
cloudInstanceSize__contains	Free-text filter by cloud instance size(supports multiple values)	false	string []
cloudLocation__contains	Free-text filter by cloud location (supports multiple values)	false	string []
cloudNetwork__contains	Free-text filter by cloud network (supports multiple values)	false	string []
cloudProvider	Agents from which cloud provider	false	string []
cloudProviderNin	Exclude Agents from these cloud provider	false	string []
collectionIds	List of collection IDs to search	false	string []
commandLineArguments__contains	Free-text filter by threat command line arguments (supports multiple values)	false	string []
computerName__contains	Free-text filter by computer name (supports multiple values)	false	string []
confidenceLevels	Filter threats by a specific confidence level	false	string []
confidenceLevelsNin	Exclude threats with specific confidence level	false	string []
containerImageName__contains	Free-text filter by the endpoint container image name (supports multiple values)	false	string []
containerLabels__contains	Free-text filter by the endpoint container labels (supports multiple values)	false	string []
containerName__contains	Free-text filter by the endpoint container name (supports multiple values)	false	string []
contentHash__contains	Free-text filter by file content hash (supports multiple values)	false	string []
contentHashes	List of sha1 hashes to search for	false	string []

countsFor	comma-separated list of fields to be shown	false	string
createdAt__gt	Created at greater than.	false	string
createdAt__gte	Created at greater or equal than.	false	string
createdAt__lt	Created at lesser than.	false	string
createdAt__lte	Created at lesser or equal than.	false	string
detectionAgentDomain__contains	Free-text filter by Agent domain at detection time (supports multiple values)	false	string []
detectionAgentVersion__contains	Free-text filter by Agent version at detection time (supports multiple values)	false	string []
detectionEngines	Included engines	false	string []
detectionEnginesNin	Excluded engines	false	string []
displayName	Display name	false	string
engines	Included engines	false	string []
enginesNin	Excluded engines	false	string []
externalTicketExists	The threat contains ticket number	false	boolean
externalTicketId__contains	Free-text filter by the threat external ticket ID (supports multiple values)	false	string []
externalTicketIds	External ticket ID for the threat	false	string []
failedActions	At least one action failed on the threat	false	boolean
filePath__contains	Free-text filter by file path (supports multiple values)	false	string []
gcpServiceAccount__contains	Free-text filter by gcp service account (supports multiple values)	false	string []
groupIds	List of Group IDs to filter by	false	string []
hasAgentTags	Include only Threats whose Agent is assigned any tags if True, or none if False	false	boolean
ids	List of threat IDs	false	string []
incidentStatuses	Filter threats by a specific incident status	false	string []
incidentStatusesNin	Exclude threats with specific incident statuses	false	string []

initiatedBy	Only include threats from specific initiating sources	false	string []
initiatedByNin	Exclude threats with specific initiating sources	false	string []
initiatedByUsername__contains	Free-text filter by the username that initiated that threat (supports multiple values)	false	string []
k8sClusterName__contains	Free-text filter by the endpoint Kubernetes cluster name (supports multiple values)	false	string []
k8sControllerLabels__contains	Free-text filter by the endpoint Kubernetes controller labels (supports multiple values)	false	string []
k8sControllerName__contains	Free-text filter by the endpoint Kubernetes controller name (supports multiple values)	false	string []
k8sNamespaceLabels__contains	Free-text filter by the endpoint Kubernetes namespace labels (supports multiple values)	false	string []
k8sNamespaceName__contains	Free-text filter by the endpoint Kubernetes namespace name (supports multiple values)	false	string []
k8sNodeLabels__contains	Free-text filter by the endpoint Kubernetes node labels (supports multiple values)	false	string []
k8sNodeName__contains	Free-text filter by the endpoint Kubernetes node name (supports multiple values)	false	string []
k8sPodLabels__contains	Free-text filter by the endpoint Kubernetes pod labels (supports multiple values)	false	string []
k8sPodName__contains	Free-text filter by the endpoint Kubernetes pod name (supports multiple values)	false	string []
limit	Limit	false	integer
mitigatedPreemptively	If the threat was detected pre-execution or post-execution	false	boolean
mitigationStatuses	Filter threats by a specific status	false	string []
mitigationStatusesNin	Filter threats not by a specific status	false	string []

noteExists	The threat contains at least one note	false	boolean
originatedProcess__contains	Free-text filter by the originated process name of the threat (supports multiple values)	false	string []
osArchs	Included OS Architectures	false	string []
osNames		false	string []
osNamesNin		false	string []
osTypes	Included OS types	false	string []
osTypesNin	Excluded OS types	false	string []
pendingActions	At least one action is pending for the Agent for the threat	false	boolean
publisherName__contains	Free-text filter by threat's publisher name (supports multiple values)	false	string []
query	Full text search for fields: threat_details, content_hash, computer_name, file_path, uuid, detection_agent_version, realtime_agent_version, detection_agent_domain, command_line_arguments, initiated_by_username, storyline, originated_process, k8s_cluster_name, k8s_node_name, k8s_node_labels, k8s_namespace_name, k8s_namespace_labels, k8s_controller_name, k8s_controller_labels, k8s_pod_name, k8s_pod_labels, container_name, container_image_name, container_labels, external_ticket_id	false	string
realtimeAgentVersion__contains	Free-text filter by Agent version at current time (supports multiple values)	false	string []
rebootRequired	A reboot is required on any endpoint for at least one action on the threat	false	boolean
resolved	This is used for backward-compatibility with API 2.0.	false	boolean
signerIdentity__contains	Free-text filter by threat's signer identity (certificate ID) (supports multiple values)	false	string []

sitelds	List of Site IDs to filter by	false	string []
storyline__contains	Free-text filter by threat storyline (supports multiple values)	false	string []
storylines	List of Agent context to search for	false	string []
tenant	Indicates a tenant scope request	false	boolean
threatDetails__contains	Free-text filter by threat details(supports multiple values)	false	string []
updatedAt__gt	Updated at greater than.	false	string
updatedAt__gte	Updated at greater or equal than.	false	string
updatedAt__lt	Updated at lesser than.	false	string
updatedAt__lte	Updated at lesser or equal than.	false	string
uuid__contains	Free-text filter by Agent UUID (supports multiple values)	false	string []

Delete Quarantined Files - body - data

Get Threat Timeline

GET /web/api/v2.1/threats/{threat_id}/timeline

Get a threat's timeline.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
activitytypes	optional	Return only these activity codes (comma-separated list). Example: "52,53,71,72".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".

limit	optional	Limit number of returned items (1-1000). Example: "10".
query	optional	Full text search for fields: hash, primary_description, secondary_description
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Threat Timeline - response - pagination table
data	Response data	false	see Get Threat Timeline - response - data table
errors	Errors	false	array

Get Threat Timeline - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Threat Timeline - response - data

Name	Description	Required	Value
accountId	Related account (If applicable)	false	string
activityType	Activity type	false	integer
agentId	Related Agent (If applicable)	false	string
agentUpdatedVersion	Agent's new version (If applicable)	false	string
createdAt	Activity creation time (UTC)	false	string
data	Extra activity specific data	false	object
groupId	Related group (If applicable)	false	string
hash	Threat file hash (If applicable)	false	string
id	Activity ID	false	string
osFamily	Agent's OS type (if applicable)	false	enum
primaryDescription	Primary description	false	string
secondaryDescription	Secondary description	false	string
siteId	Related site (If applicable)	false	string
threatId	Related threat (If applicable)	false	string
updatedAt	Activity last updated time (UTC)	false	string
userId	The user who invoked the activity (If applicable)	false	string

Export Threat Timeline

GET /web/api/v2.1/export/threats/{threat_id}/timeline

Export a threat's timeline.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
activitytypes	optional	Return only these activity codes (comma-separated list). Example: "52,53,71,72".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
query	optional	Full text search for fields: hash, primary_description, secondary_description
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Export Events

GET /web/api/v2.1/export/threats/{threat_id}/explore/events

Export threat events in CSV or JSON format.

Parameters

format	required	Exported file format. Example: "json".
eventid	optional	Filter by a specific process key and its children
eventsubtypes	optional	Filter events by sub-type. Example: "PROCESSCREATION".
eventtypes	optional	Filter events by type. Example: "events".

processname__like	optional	Filter by process name (substring)
-------------------	----------	------------------------------------

Response Messages

- 200 - Success
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.

Unprotected Endpoints Discovery

Get Unprotected Endpoints Discovery Table

GET /web/api/v2.1/rogues/table-view

Get the data for each row in the Unprotected Endpoints Discovery Device Inventory Table.
Best practice: Set filters. Each row is a set of parameters that quickly fills the pagination limits.

BEST PRACTICE
Set filters. Each row is a set of parameters that quickly fills the pagination limits.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
devicetype	optional	Device type. Example: "Server/Workstation/...".
devicetypes	optional	Device types
externalip	optional	Search using external IP

externalip__contains	optional	Free-text filter by visible IP (supports multiple values). Example: "192.168.0.1/24,10.1".
firstseen__between	optional	Date range refor first seen(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
firstseen__gt	optional	Devices first seen after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
firstseen__gte	optional	Devices first seen after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
firstseen__lt	optional	Devices first seen before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
firstseen__lte	optional	Devices first seen before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
hostnames	optional	Hostnames
hostnames__contains	optional	Free-text filter by hostanem (supports multiple values). Example: "s1_host,SomeHost".
ids	optional	List of device ids. Example: "225494730938493804,225494730938493915".
lastseen__between	optional	Date range for last seen(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
lastseen__gt	optional	Devices last seen after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastseen__gte	optional	Devices last seen after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastseen__lt	optional	Devices last seen before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastseen__lte	optional	Devices last seen before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
limit	optional	Limit number of returned items (1-1000). Example: "10".
localip	optional	Search using local IP
localip__contains	optional	Free-text filter by IP Address (supports multiple values). Example: "192.168.0.1/24,10.1".

macaddress	optional	A mac address to search for
macaddress__contains	optional	Free-text filter by mac address (supports multiple values). Example: "aa:ee:b1".
manufacturer	optional	Manufacturer of the device or network interface
manufacturer__contains	optional	Free-text filter by manufacturer (supports multiple values). Example: "Company".
osname	optional	Os name
ostype	optional	OS type
ostypes	optional	Included OS types
osversion	optional	Os version
osversion__contains	optional	Free-text filter by OS full name and version (supports multiple values). Example: "Service Pack 1".
query	optional	Query
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Unprotected Endpoints Discovery Table - response - pagination table
data	Response data	false	see Get Unprotected Endpoints Discovery Table - response - data table
errors	Errors	false	array

Get Unprotected Endpoints Discovery Table - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Unprotected Endpoints Discovery Table - response - data

Name	Description	Required	Value
deviceFunction	Function of the device	false	string
deviceType	Role of the device	false	string
externallp	Main Gateway Visible IP	false	string
firstSeen	Time the device was first seen	false	string
hostnames	Array of host names	false	string []
id	Id of the device	false	string
lastSeen	Time the device was last seen	false	string
localip	Local ip of the device	false	string
macAddress	Mac address of the device	false	string
manufacturer	Manufacturer of the device or network interface	false	string
osName	OS Name/Version of the device	false	string
osType	Os Type of the device	false	string
osVersion	OS Version of the device	false	string

Export Unprotected Endpoints Discovery Data

GET /web/api/v2.1/rogues/report/csv

Export Unprotected Endpoints Discovery data to CSV. You can set filters to get only relevant data. The response sends the CSV data as text.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
devicetype	optional	Device type. Example: "Server/Workstation/...".
devicetypes	optional	Device types
externalip	optional	Search using external IP
externalip__contains	optional	Free-text filter by visible IP (supports multiple values). Example: "192.168.0.1/24,10.1".
firstseen__between	optional	Date range refor first seen(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
firstseen__gt	optional	Devices first seen after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
firstseen__gte	optional	Devices first seen after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
firstseen__lt	optional	Devices first seen before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
firstseen__lte	optional	Devices first seen before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
hostnames	optional	Hostnames
hostnames__contains	optional	Free-text filter by hostname (supports multiple values). Example: "s1_host,SomeHost".
ids	optional	List of device ids. Example: "225494730938493804,225494730938493915".
lastseen__between	optional	Date range for last seen(format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
lastseen__gt	optional	Devices last seen after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastseen__gte	optional	Devices last seen after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastseen__lt	optional	Devices last seen before this timestamp. Example:

		"2018-02-27T04:49:26.257525Z".
lastseen__lte	optional	Devices last seen before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
localip	optional	Search using local IP
localip__contains	optional	Free-text filter by IP Address (supports multiple values). Example: "192.168.0.1/24,10.1".
macaddress	optional	A mac address to search for
macaddress__contains	optional	Free-text filter by mac address (supports multiple values). Example: "aa:ee:b1".
manufacturer	optional	Manufacturer of the device or network interface
manufacturer__contains	optional	Free-text filter by manufacturer (supports multiple values). Example: "Company".
osname	optional	Os name
ostype	optional	OS type
ostypes	optional	Included OS types
osversion	optional	Os version
osversion__contains	optional	Free-text filter by OS full name and version (supports multiple values). Example: "Service Pack 1".
query	optional	Query
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Get Unprotected Endpoints Discovery Settings

GET /web/api/v2.1/rogues/settings

Unprotected Endpoints Discovery gives full visibility of all unsecured devices connected to your network. Unprotected Endpoints Discovery scans your corporate environment to identify and manage connected devices, even those not protected by or supported by SentinelOne. Unprotected Endpoints Discovery identifies devices as:

* UnSecured - End-user computer or laptop, or server, without a SentinelOne Agent.

When you install Windows Agents with Unprotected Endpoints Discovery, the Agents can become scanners. Selected scanners from networks that you enable for scanning find connected devices with passive and active scan techniques. The scanners send the collected data to Unprotected Endpoints Discovery page on the Management. Unprotected Endpoints Discovery then runs fingerprinting to identify and classify unique devices and to update the Device Inventory Table in the Management Console. With port scanning, it is important that you understand the legal and ethical considerations and that you document an Unprotected Endpoints Discovery plan and implementation. See Legal Considerations and Proper Implementation in the Console Help.

* minAgentsInNetworkToScan - To help you determine which networks are corporate, Unprotected Endpoints Discovery looks at the number of secured endpoints (Agents) in a network. If there are not enough Agents in a network - set by this parameter value - Unprotected Endpoints Discovery considers the network to be non-corporate and will not scan it.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get Unprotected Endpoints Discovery Settings - response - data table
errors	Errors	false	array

Get Unprotected Endpoints Discovery Settings - response - data

Name	Description	Required	Value
accountId	Account id	false	string
enabled	Is the Network Discovery collection enabled for the account	false	boolean
minAgentsInNetworkToScan	Minimum agents required in a network to be listed as selectable for scan.Valid values are 2, 10 and 100 if Unprotected Endpoints Discovery is enabled	false	integer
restrictions	A set of IP addresses that should not be scanned in the specific network	false	see Get Unprotected Endpoints Discovery Settings - response - restrictions table
specificPorts	[FUTURE] A set of specific ports allowed to be used as source ports for an active scan	false	see Get Unprotected Endpoints Discovery Settings - response - specificPorts table
useSpecificPorts	[FUTURE] Use only specific ports defined in specific ports as source ports of active scans	false	boolean

Get Unprotected Endpoints Discovery Settings - response - restrictions

Name	Description	Required	Value
annotation	An optional note with the reason for the restriction	false	string
type		false	enum
values	It will be one IP or one CIDR or two values for a Range	false	string []

Get Unprotected Endpoints Discovery Settings - response - specificPorts

Name	Description	Required	Value
type		false	enum

values	It can be a single port or two ports [start, end] for a Range	false	integer []
--------	---	-------	------------

Update Unprotected Endpoints Discovery Settings

PUT /web/api/v2.1/rogues/settings

Change the Unprotected Endpoints Discovery Settings. Best Practice: Get the current settings before you change them. See: [Get Unprotected Endpoints Discovery Settings](#).

BEST PRACTICE
Get the current settings before you change them. See: [Get Unprotected Endpoints Discovery Settings](#).

Response Messages

- 200 - Success
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.
- 403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update Unprotected Endpoints Discovery Settings - response - data table
errors	Errors	false	array

Update Unprotected Endpoints Discovery Settings - response - data

Name	Description	Required	Value
accountId	Account id	false	string
enabled	Is the Network Discovery collection enabled for the account	false	boolean
minAgentsInNetworkToScan	Minimum agents required in a network to be listed as selectable for scan.Valid values are 2, 10 and 100 if Unprotected Endpoints Discovery is enabled	false	integer
restrictions	A set of IP addresses that should not be scanned in the specific network	false	see Update Unprotected Endpoints Discovery Settings - response - restrictions table
specificPorts	[FUTURE] A set of specific ports allowed to be used as source ports for an active scan	false	see Update Unprotected Endpoints Discovery Settings - response - specificPorts table
useSpecificPorts	[FUTURE] Use only specific ports defined in specific ports as source ports of active scans	false	boolean

Update Unprotected Endpoints Discovery Settings - response - restrictions

Name	Description	Required	Value
annotation	An optional note with the reason for the restriction	false	string
type		false	enum
values	It will be one IP or one CIDR or two values for a Range	false	string []

Update Unprotected Endpoints Discovery Settings - response - specificPorts

Name	Description	Required	Value
type		false	enum

values	It can be a single port or two ports [start, end] for a Range	false	integer []
--------	--	-------	------------

Body Schema

Name	Description	Required	Value
data	Data	true	see Update Unprotected Endpoints Discovery Settings - body - data table
filter	Filter	true	see Update Unprotected Endpoints Discovery Settings - body - filter table

Update Unprotected Endpoints Discovery Settings - body - data

Name	Description	Required	Value
accountId	Account id	false	string
enabled	Is the Network Discovery collection enabled for the account	false	boolean
minAgentsInNetworkToScan	Minimum agents required in a network to be listed as selectable for scan.Valid values are 2, 10 and 100 if Unprotected Endpoints Discovery is enabled	false	integer
restrictions	A set of IP addresses that should not be scanned in the specific network	false	see Update Unprotected Endpoints Discovery Settings - body - restrictions table
specificPorts	[FUTURE] A set of specific ports allowed to be used as source ports for an active scan	false	see Update Unprotected Endpoints Discovery Settings - body - specificPorts table
useSpecificPorts	[FUTURE] Use only specific ports defined in specific ports as source ports of active scans	false	boolean

Update Unprotected Endpoints Discovery Settings - body - restrictions

Name	Description	Required	Value
annotation	An optional note with the reason for the restriction	false	string
type		false	enum
values	It will be one IP or one CIDR or two values for a Range	false	string []

Update Unprotected Endpoints Discovery Settings - body - specificPorts

Name	Description	Required	Value
type		false	enum

values	It can be a single port or two ports [start, end] for a Range	false	integer []
--------	---	-------	------------

Update Unprotected Endpoints Discovery Settings - body - filter

Name	Description	Required	Value
accountIds	List of Account IDs to filter by	false	string []
siteIds	List of Site IDs to filter by	false	string []

Updates

Latest Packages by OS

GET /web/api/v2.1/update/agent/latest-packages

[DEPRECATED] Use "Latest packages" API call instead ("GET /web/api/v2.1/update/agent/packages").

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
packagetype	optional	Package type. Example: "Agent".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Latest Packages by OS - response - data table
errors	Errors	false	array

Latest Packages by OS - response - data

Name	Description	Required	Value
osTypes	Os types	true	see Latest Packages by OS - response - osTypes table
registrationToken	Registration token	false	string

Latest Packages by OS - response - osTypes

Name	Description	Required	Value
linux	Linux	false	see Latest Packages by OS - response - linux table
macos	Macos	false	see Latest Packages by OS - response - macos table
windows	Windows	false	see Latest Packages by OS - response - windows table
windowsLegacy	Windows legacy	false	see Latest Packages by OS - response - windowsLegacy table

Latest Packages by OS - response - linux

Name	Description	Required	Value
accounts	Accounts where the update package is available for download	false	see Latest Packages by OS - response - accounts table
createdAt	Created at	false	string
fileExtension	File extension	false	enum
fileName	File name	false	string
fileSize	File size (bytes)	false	integer
id	Id	false	string
link	Link	false	
majorVersion	Major version	false	string
minorVersion	Minor version	false	string
osArch	Package OS architecture (32/64 bit), applicable to Windows packages only	false	enum
osType	Platform type	false	enum

packageType	Package type	false	enum
platformType	Platform type	false	enum
rangerVersion	Network Scanner version if applicable	false	string
scopeLevel	Package scope. If "global", it will be available in all sites. If "site", it will be available only to sites specified in the "siteIds" attribute.	false	enum
sha1	Package hash	false	string
sites	Sites where the update package is available for download	false	see Latest Packages by OS - response - sites table
status	Status	false	enum
supportedOsVersions	Supported os versions	false	string
updatedAt	Updated at	false	string
version	Agent version	false	string

Latest Packages by OS - response - accounts

Name	Description	Required	Value
id	Id	true	string
name	Name	true	string

Latest Packages by OS - response - sites

Name	Description	Required	Value
id	Id	true	string
name	Name	true	string

Latest Packages by OS - response - macos

Name	Description	Required	Value
accounts	Accounts where the update package is available for download	false	see Latest Packages by OS - response - accounts table

createdAt	Created at	false	string
fileExtension	File extension	false	enum
fileName	File name	false	string
fileSize	File size (bytes)	false	integer
id	Id	false	string
link	Link	false	
majorVersion	Major version	false	string
minorVersion	Minor version	false	string
osArch	Package OS architecture (32/64 bit), applicable to Windows packages only	false	enum
osType	Platform type	false	enum
packageType	Package type	false	enum
platformType	Platform type	false	enum
rangerVersion	Network Scanner version if applicable	false	string
scopeLevel	Package scope. If "global", it will be available in all sites. If "site", it will be available only to sites specified in the "siteIds" attribute.	false	enum
sha1	Package hash	false	string
sites	Sites where the update package is available for download	false	see Latest Packages by OS - response - sites table
status	Status	false	enum
supportedOsVersions	Supported os versions	false	string
updatedAt	Updated at	false	string
version	Agent version	false	string

Latest Packages by OS - response - accounts

Name	Description	Required	Value
id	Id	true	string
name	Name	true	string

Latest Packages by OS - response - sites

Name	Description	Required	Value
id	Id	true	string
name	Name	true	string

Latest Packages by OS - response - windows

Name	Description	Required	Value
accounts	Accounts where the update package is available for download	false	see Latest Packages by OS - response - accounts table
createdAt	Created at	false	string
fileExtension	File extension	false	enum
fileName	File name	false	string
fileSize	File size (bytes)	false	integer
id	Id	false	string
link	Link	false	
majorVersion	Major version	false	string
minorVersion	Minor version	false	string
osArch	Package OS architecture (32/64 bit), applicable to Windows packages only	false	enum
osType	Platform type	false	enum
packageType	Package type	false	enum
platformType	Platform type	false	enum
rangerVersion	Network Scanner version if applicable	false	string
scopeLevel	Package scope. If "global", it will be available in all sites. If "site", it will be available only to sites specified in the "siteIds" attribute.	false	enum
sha1	Package hash	false	string
sites	Sites where the update package is available for download	false	see Latest Packages by OS - response - sites table
status	Status	false	enum
supportedOsVersions	Supported os versions	false	string
updatedAt	Updated at	false	string

version	Agent version	false	string
---------	---------------	-------	--------

Latest Packages by OS - response - accounts

Name	Description	Required	Value
id	Id	true	string
name	Name	true	string

Latest Packages by OS - response - sites

Name	Description	Required	Value
id	Id	true	string
name	Name	true	string

Latest Packages by OS - response - windowsLegacy

Name	Description	Required	Value
accounts	Accounts where the update package is available for download	false	see Latest Packages by OS - response - accounts table
createdAt	Created at	false	string
fileExtension	File extension	false	enum
fileName	File name	false	string
fileSize	File size (bytes)	false	integer
id	Id	false	string
link	Link	false	
majorVersion	Major version	false	string
minorVersion	Minor version	false	string
osArch	Package OS architecture (32/64 bit), applicable to Windows packages only	false	enum
osType	Platform type	false	enum
packageType	Package type	false	enum

platformType	Platform type	false	enum
rangerVersion	Network Scanner version if applicable	false	string
scopeLevel	Package scope. If "global", it will be available in all sites. If "site", it will be available only to sites specified in the "siteIds" attribute.	false	enum
sha1	Package hash	false	string
sites	Sites where the update package is available for download	false	see Latest Packages by OS - response - sites table
status	Status	false	enum
supportedOsVersions	Supported os versions	false	string
updatedAt	Updated at	false	string
version	Agent version	false	string

Latest Packages by OS - response - accounts

Name	Description	Required	Value
id	Id	true	string
name	Name	true	string

Latest Packages by OS - response - sites

Name	Description	Required	Value
id	Id	true	string
name	Name	true	string

Get Latest Packages

GET /web/api/v2.1/update/agent/packages

Get the Agent packages that are uploaded to your Management.
The response shows the data of each package, including the IDs, which you can use in other commands.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
accountname__contains	optional	Free-text filter by account name
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
fileextension	optional	File extension. Example: ".msi".
fileextensions	optional	File extension. Example: ".msi".
filename__contains	optional	Free-text filter by file name
filesize__contains	optional	Free-text filter by file size
ids	optional	Package ID list. Example: "225494730938493804,225494730938493915".
limit	optional	Limit number of returned items (1-1000). Example: "10".
majorversions	optional	Package major versions
minorversion	optional	Package minor version
minorversions	optional	Package minor versions
osarches	optional	Package OS architecture (32/64 bit), applicable to Windows packages only. Example: "64 bit".
osrevision	optional	Agent os revision
ostypes	optional	Os type in. Example: "threat_detection_netapp".
packagetype	optional	Package type. Example: "Agent".
packagetypes	optional	Package type in. Example: "Agent".
platformtype	optional	Platform type. Example: "threat_detection_netapp".
platformtypes	optional	Platform type in. Example: "threat_detection_netapp".
query	optional	A free-text search term, will match applicable attributes
rangerversion	optional	Network Scanner version. Example: "2.5.1.1320".
rangerversion__contains	optional	Free-text filter by Network Scanner version
sha1	optional	Package hash. Example:

		"2fd4e1c67a2d28fced849ee1bb76e7391b93eb12".
sha1__contains	optional	Free-text filter by SHA1 hash
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
sitename__contains	optional	Free-text filter by site name
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
status	optional	Status in. Example: "beta".
version	optional	Agent version. Example: "2.5.1.1320".
versionstr__contains	optional	Free-text filter by version string

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see Get Latest Packages - response - pagination table
data	Response data	false	see Get Latest Packages - response - data table
errors	Errors	false	array

Get Latest Packages - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

Get Latest Packages - response - data

Name	Description	Required	Value
accounts	Accounts where the update package is available for download	false	see Get Latest Packages - response - accounts table
createdAt	Created at	false	string
fileExtension	File extension	false	enum
fileName	File name	false	string
fileSize	File size (bytes)	false	integer
id	Id	false	string
link	Link	false	
majorVersion	Major version	false	string
minorVersion	Minor version	false	string
osArch	Package OS architecture (32/64 bit), applicable to Windows packages only	false	enum
osType	Platform type	false	enum
packageType	Package type	false	enum
platformType	Platform type	false	enum
rangerVersion	Network Scanner version if applicable	false	string
scopeLevel	Package scope. If "global", it will be available in all sites. If "site", it will be available only to sites specified in the "siteIds" attribute.	false	enum

sha1	Package hash	false	string
sites	Sites where the update package is available for download	false	see Get Latest Packages - response - sites table
status	Status	false	enum
supportedOsVersions	Supported os versions	false	string
updatedAt	Updated at	false	string
version	Agent version	false	string

Get Latest Packages - response - accounts

Name	Description	Required	Value
id	Id	true	string
name	Name	true	string

Get Latest Packages - response - sites

Name	Description	Required	Value
id	Id	true	string
name	Name	true	string

Delete Packages

DELETE /web/api/v2.1/update/agent/packages

Delete Agent packages from your Management. Use the IDs from Get Latest Packages.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete Packages - response - data table
errors	Errors	false	array

Delete Packages - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Delete Packages - body - data table

Delete Packages - body - data

Name	Description	Required	Value
ids	Package IDs to delete	false	string []

Update package

PUT /web/api/v2.1/update/agent/packages/{package_id}

Update the metadata for an existing package.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

404 - Package not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update package - response - data table
errors	Errors	false	array

Update package - response - data

Name	Description	Required	Value
status	Status	true	enum
accounts	Accounts where the update package is available for download	false	see Update package - response - accounts table
createdAt	Created at	false	string
fileExtension	File extension	false	enum
fileName	File name	false	string
fileSize	File size (bytes)	false	integer
id	Id	false	string
link	Link	false	
minorVersion	Minor version	false	string
osArch	Package OS architecture (32/64 bit), applicable to Windows packages only	false	enum
osType	Platform type	false	enum
packageType	Package type	false	enum
platformType	Platform type	false	enum
rangerVersion	Network Scanner version if applicable	false	string
scopeLevel	Package scope. If "global", it will be available in all sites. If "site", it will be available only to sites specified in the "siteIds" attribute.	false	enum
sha1	Package hash	false	string
sites	Sites where the update package is available for download	false	see Update package - response - sites table
supportedOsVersions	Supported os versions	false	string
updatedAt	Updated at	false	string
version	Agent version	false	string

Update package - response - accounts

Name	Description	Required	Value
id	Id	true	string
name	Name	true	string

Update package - response - sites

Name	Description	Required	Value
id	Id	true	string
name	Name	true	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Update package - body - data table

Update package - body - data

Name	Description	Required	Value
accountIds	List of accounts to make the package available in. Applicable only if scopeLevel is set to "account".	false	string []
minorVersion	Minor version	false	string
osArch	Package OS architecture (32/64 bit), applicable to Windows packages only	false	enum
rangerVersion	Network Scanner version if applicable	false	string
scopeLevel	Package scope. If "global", it will be available in all sites. If "site", it will be available only to sites specified in the "siteIds" attribute.	false	enum
siteIds	List of sites to make the package available in. Applicable only if scopeLevel is set to "site".	false	string []
status	Status	false	enum
supportedOsVersions	Supported os versions	false	string
version	Agent version	false	string

Upload Agent Package

POST /web/api/v2.1/upload/agent/software

If you have an On-Prem Management or you are a participant in the Beta program, you can use this command to upload an Agent package to the Management. Then you can deploy the Agent to update endpoints.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Upload Agent Package - response - data table
errors	Errors	false	array

Upload Agent Package - response - data

Name	Description	Required	Value
status	Status	true	enum
accounts	Accounts where the update package is available for download	false	see Upload Agent Package - response - accounts table
createdAt	Created at	false	string
fileExtension	File extension	false	enum
fileName	File name	false	string
fileSize	File size (bytes)	false	integer
id	Id	false	string
link	Link	false	
minorVersion	Minor version	false	string
osArch	Package OS architecture (32/64 bit), applicable to Windows packages only	false	enum
osType	Platform type	false	enum
packageType	Package type	false	enum
platformType	Platform type	false	enum
rangerVersion	Network Scanner version if applicable	false	string
scopeLevel	Package scope. If "global", it will be available in all sites. If "site", it will be available only to sites specified in the "siteIds" attribute.	false	enum
sha1	Package hash	false	string
sites	Sites where the update package is available for download	false	see Upload Agent Package - response - sites table
supportedOsVersions	Supported os versions	false	string
updatedAt	Updated at	false	string
version	Agent version	false	string

Upload Agent Package - response - accounts

Name	Description	Required	Value
id	Id	true	string
name	Name	true	string

Upload Agent Package - response - sites

Name	Description	Required	Value
id	Id	true	string
name	Name	true	string

Body Schema

Name	Description	Required	Value
formData		false	see Upload Agent Package - body - formData table

Upload Agent Package - body - formData

Name	Description	Required	Value
file	File	true	file
status	Status. Example: "beta".	true	enum
accountIds	List of accounts to make the package available in. Applicable only if scopeLevel is set to "account". Example: "225494730938493804,225494730938493915".	false	string []
minorVersion	Package minor version. Example: "SP1".	false	string
osType	Platform type. Example: "threat_detection_netapp".	false	enum
platformType	Platform type. Example: "threat_detection_netapp".	false	enum
scopeLevel	Package scope. If "global", it will be available in all sites. Otherwise, it will only be available to the sites/ accounts specified in "siteIds"/"accountIds" attribute. Example: "site".	false	enum
siteIds	List of sites to make the package available in. Applicable only if scopeLevel is set to "site". Example: "225494730938493804,225494730938493915".	false	string []
version	Version. Example: "2.5.1.1320".	false	string

Upload System Package

POST /web/api/v2.1/upload/software

If you have an On-Prem Management or otherwise require a manual package upload, use this command to upload an Agent package or a Management package. Then you can deploy the update (see Deploy System Package).

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Upload System Package - response - data table
errors	Errors	false	array

Upload System Package - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
formData		false	see Upload System Package - body - formData table

Upload System Package - body - formData

Name	Description	Required	Value
file	File	true	file

Deploy System Package

POST /web/api/v2.1/upload/software/deploy

If you have an On-Prem Management or you are a participant in the Beta program, you can upload a Management package and then use this command to deploy the new Management. You must first upload the package (see Upload System Package).

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Deploy System Package - response - data table
errors	Errors	false	array

Deploy System Package - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Download Agent Package

GET /web/api/v2.1/update/agent/download/{package_id}

[DEPRECATED] Download an agent package by package ID. Rate limit: 2 call per minute for each different user token

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

404 - Package not found

Download Package

GET /web/api/v2.1/update/agent/download/{site_id}/{package_id}

Download a package by site_id ("sites") and filename.

Rate limit: 2 call per minute for each user token.

Use this command to manually deploy Agent updates that cannot be deployed with the update-software command (see Agent Actions > Update Software) or through the Console.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

404 - Package not found or bad site

Users

User by token

GET /web/api/v2.1/user

Get a user by token.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
groupids	optional	List of Group IDs to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
tenant	optional	Indicates a tenant scope request

Response Messages

200 - User retrieved correctly.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see User by token - response - data table
errors	Errors	false	array

User by token - response - data

Name	Description	Required	Value
scope	User Scope	true	enum
agreedEula	True if EULA was agreed for user's sites	false	boolean
agreementUrl	Link to EULA agreement if it was not agreed yet	false	string
allowRemoteShell	[DEPRECATED] Unused field. The user's role will determine if it is allowed to use remote_shell.	false	boolean
apiToken	Api token	false	see User by token - response - apiToken table
canGenerateApiToken	Can generate api token	false	boolean
dateJoined	Date joined	false	string
elevatedSessionDurationMinutes	Defines for how many minutes can the user call protected actions once their session is elevated.	false	integer
email	Email	false	string
emailReadOnly	True if email cannot be modified	false	boolean
emailVerified	True if user verification completed successfully	false	boolean
firstLogin	First login	false	string
fullName	Full name	false	string
fullNameReadOnly	True if full name cannot be modified	false	boolean
globalOrganizationId	Global organization id	false	string
globalUserId	Global user id	false	string
groupsReadOnly	[Deprecated]	false	boolean
id	Id	false	string
isExternalLoginUser	Is external login user	false	boolean
isSystem		false	boolean
lastLogin	Last login	false	string
lowestRole	[DEPRECATED] in RBAC there's no 'lowest' role. Returns Admin if user	false	string

	has admin permission on all sites, otherwise a different role.		
primaryTwoFaMethod	Primary two fa method	false	string
scopeRoles	Roles of the scope user	false	see User by token - response - scopeRoles table
siteRoles	[DEPRECATED] Role and site ids for the user. Using scopeRoles is more consistent.	false	see User by token - response - siteRoles table
source	Source	false	string
tenantRoles	[DEPRECATED] Role ids for the tenant user. Using scopeRoles is more consistent.	false	undefined []
twoFaConfigured	User 2FA Auth is configured	false	boolean
twoFaEnabled	Two fa enabled	false	boolean
twoFaEnabledReadOnly	True if two fa option cannot be modified	false	boolean
twoFaStatus	State of 2FA setup	false	enum

User by token - response - apiToken

Name	Description	Required	Value
createdAt	Created at	false	string
expiresAt	Expires at	false	string

User by token - response - scopeRoles

Name	Description	Required	Value
accountName	Scope name	true	string
name	Scope name	true	string
id	Scope ID	false	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the	false	string []

	desired role name in this scope. Use role_id or role_name instead.		
--	--	--	--

User by token - response - siteRoles

Name	Description	Required	Value
id	Site ID	true	string
name	Site name	true	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the desired role name in this scope. Use role_id instead.	false	string []

List users

GET /web/api/v2.1/users

Get a list of users.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
apitokenexpiresat__between	optional	Date range for when the API token expires (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
apitokenexpiresat__gt	optional	API token expires after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
apitokenexpiresat__gte	optional	API token expires after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
apitokenexpiresat__lt	optional	API token expires before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
apitokenexpiresat__lte	optional	API token expires before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".

cangenerateapitoken	optional	Can generate api token
countonly	optional	If true, only total number of items will be returned, without any of the actual objects.
createdat__between	optional	Date range for when the user was created (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdat__gt	optional	User was created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	User was created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	User was created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	User was created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
cursor	optional	Cursor position returned by the last request. Use to iterate over more than 1000 items. Example: "YWdlbnRfaWQ6NTgwMjkzODE=".
datejoined	optional	Date joined. Example: "2018-02-27T04:49:26.257525Z".
email	optional	Email. Example: "admin@sentinelone.com".
email__contains	optional	Match email partially (substring)
emailreadonly	optional	True if email cannot be changed
emailverified	optional	Return only verified/unverified users
firstlogin	optional	First login. Example: "2018-02-27T04:49:26.257525Z".
fullname	optional	Full name
fullname__contains	optional	Match full name partially (substring)
fullnamereadonly	optional	True if full name cannot be changed
groupsreadonly	optional	[DEPRECATED] True if permissions cannot be changed
hasvalidapitoken	optional	Has valid api token
ids	optional	List of user IDs to filter by. Example: "225494730938493804,225494730938493915".
lastactivation__between	optional	Date range for when the user was last active (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".

lastactivation__gt	optional	User was last active after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastactivation__gte	optional	User was last active after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastactivation__lt	optional	User was last active before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastactivation__lte	optional	User was last active before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastlogin	optional	Last login. Example: "2018-02-27T04:49:26.257525Z".
limit	optional	Limit number of returned items (1-1000). Example: "10".
primarytwofamethod	optional	Primary two fa method
query	optional	Full text search for fields: full_name, email, description
roleids	optional	List of rbac roles to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
skip	optional	Skip first number of items (0-1000). To iterate over more than 1000 items, use "cursor". Example: "150".
skipcount	optional	If true, total number of items will not be calculated, which speeds up execution time.
sortby	optional	The column to sort the results by. Example: "id".
sortorder	optional	Sort direction. Example: "asc".
source	optional	User Source. Example: "mgmt".
sources	optional	Source in. Example: "mgmt".
twofaenabled	optional	Two fa enabled
twofastatus	optional	Two fa status
twofastatuses	optional	Two fa status in

Response Messages

200 - List of users retrieved successfully.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
pagination	Pagination information	true	see List users - response - pagination table
data	Response data	false	see List users - response - data table
errors	Errors	false	array

List users - response - pagination

Name	Description	Required	Value
totalItems	Total number of items found matching your query	true	integer
nextCursor	Pass this value as "cursor" on your next request, to get the next page of results (Will be "null" when last page reached)	false	string

List users - response - data

Name	Description	Required	Value
scope	User Scope	true	enum
agreedEula	True if EULA was agreed for user's sites	false	boolean
agreementUrl	Link to EULA agreement if it was not agreed yet	false	string
allowRemoteShell	[DEPRECATED] Unused field. The user's role will determine if it is allowed to use remote_shell.	false	boolean
apiToken	Api token	false	see List users - response - apiToken table
canGenerateApiToken	Can generate api token	false	boolean
dateJoined	Date joined	false	string
email	Email	false	string
emailReadOnly	True if email cannot be modified	false	boolean
emailVerified	True if user verification completed successfully	false	boolean
firstLogin	First login	false	string
fullName	Full name	false	string
fullNameReadOnly	True if full name cannot be modified	false	boolean
globalOrganizationId	Global organization id	false	string
globalUserId	Global user id	false	string

groupsReadOnly	[Deprecated]	false	boolean
id	Id	false	string
isSystem		false	boolean
lastLogin	Last login	false	string
lowestRole	[DEPRECATED] in RBAC there's no 'lowest' role. Returns Admin if user has admin permission on all sites, otherwise a different role.	false	string
primaryTwoFaMethod	Primary two fa method	false	string
scopeRoles	Roles of the scope user	false	see List users - response - scopeRoles table
siteRoles	[DEPRECATED] Role and site ids for the user. Using scopeRoles is more consistent.	false	see List users - response - siteRoles table
source	Source	false	string
tenantRoles	[DEPRECATED] Role ids for the tenant user. Using scopeRoles is more consistent.	false	undefined []
twoFaConfigured	User 2FA Auth is configured	false	boolean
twoFaEnabled	Two fa enabled	false	boolean
twoFaEnabledReadOnly	True if two fa option cannot be modified	false	boolean
twoFaStatus	State of 2FA setup	false	string

List users - response - apiToken

Name	Description	Required	Value
createdAt	Created at	false	string
expiresAt	Expires at	false	string

List users - response - scopeRoles

Name	Description	Required	Value
accountName	Scope name	true	string

name	Scope name	true	string
id	Scope ID	false	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the desired role name in this scope. Use role_id or role_name instead.	false	string []

List users - response - siteRoles

Name	Description	Required	Value
id	Site ID	true	string
name	Site name	true	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the desired role name in this scope. Use role_id instead.	false	string []

Create User

POST /web/api/v2.1/users

Create a new user.

Response Messages

200 - User created successfully.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Not enough permissions to create user.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Create User - response - data table
errors	Errors	false	array

Create User - response - data

Name	Description	Required	Value
scope	User Scope	true	enum
agreedEula	True if EULA was agreed for user's sites	false	boolean
agreementUrl	Link to EULA agreement if it was not agreed yet	false	string
allowRemoteShell	[DEPRECATED] Unused field. The user's role will determine if it is allowed to use remote_shell.	false	boolean
apiToken	Api token	false	see Create User - response - apiToken table
canGenerateApiToken	Can generate api token	false	boolean
dateJoined	Date joined	false	string
elevatedSessionDurationMinutes	Defines for how many minutes can the user call protected actions once their session is elevated.	false	integer
email	Email	false	string
emailReadOnly	True if email cannot be modified	false	boolean
emailVerified	True if user verification completed successfully	false	boolean
firstLogin	First login	false	string
fullName	Full name	false	string
fullNameReadOnly	True if full name cannot be modified	false	boolean
globalOrganizationId	Global organization id	false	string
globalUserId	Global user id	false	string
groupsReadOnly	[Deprecated]	false	boolean
id	Id	false	string
isExternalLoginUser	Is external login user	false	boolean
isSystem		false	boolean
lastLogin	Last login	false	string
lowestRole	[DEPRECATED] in RBAC there's no 'lowest' role. Returns Admin if user	false	string

	has admin permission on all sites, otherwise a different role.		
primaryTwoFaMethod	Primary two fa method	false	string
scopeRoles	Roles of the scope user	false	see Create User - response - scopeRoles table
siteRoles	[DEPRECATED] Role and site ids for the user. Using scopeRoles is more consistent.	false	see Create User - response - siteRoles table
source	Source	false	string
tenantRoles	[DEPRECATED] Role ids for the tenant user. Using scopeRoles is more consistent.	false	undefined []
twoFaConfigured	User 2FA Auth is configured	false	boolean
twoFaEnabled	Two fa enabled	false	boolean
twoFaEnabledReadOnly	True if two fa option cannot be modified	false	boolean
twoFaStatus	State of 2FA setup	false	enum

Create User - response - apiToken

Name	Description	Required	Value
createdAt	Created at	false	string
expiresAt	Expires at	false	string

Create User - response - scopeRoles

Name	Description	Required	Value
accountName	Scope name	true	string
name	Scope name	true	string
id	Scope ID	false	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the	false	string []

	desired role name in this scope. Use role_id or role_name instead.		
--	--	--	--

Create User - response - siteRoles

Name	Description	Required	Value
id	Site ID	true	string
name	Site name	true	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the desired role name in this scope. Use role_id instead.	false	string []

Body Schema

Name	Description	Required	Value
data	Data	true	see Create User - body - data table

Create User - body - data

Name	Description	Required	Value
email	The email of the user	true	string
fullName	Full name of the user	true	string
scope	User scope	true	enum
allowRemoteShell	[DEPRECATED] Unused field. The user's role will determine if it is allowed to use remote_shell.	false	boolean
forceCredentialAuth	If true, default behaviour is ignored, credential auth type is forced	false	boolean
password	User password. Not allowed if automatic onboarding feature is enabled.	false	string
scopeRoles	List of id and role id, id is mandatory for user in scope account/site. Role name is deprecated and will work only for predefined roles, please use role id. User in tenant (global) role does not need to provide an id.	false	see Create User - body - scopeRoles table
siteRoles	[DEPRECATED] Please use scopeRoles instead.	false	see Create User - body - siteRoles table
tenantRoles	[DEPRECATED] Use roles instead. List of tenant roles.	false	string []
twoFaEnabled	Two fa enabled	false	boolean

Create User - body - scopeRoles

Name	Description	Required	Value
id	Scope ID	false	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the	false	string []

	desired role name in this scope. Use role_id or role_name instead.		
--	--	--	--

Create User - body - siteRoles

Name	Description	Required	Value
id	Site ID	true	string
name	[DEPRECATED] Site name	false	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the desired role name in this scope. Use role_id instead.	false	string []

Export Users

GET /web/api/v2.1/export/users

Export User data to a CSV, for Users that match the filter.

Parameters

accountids	optional	List of Account IDs to filter by. Example: "225494730938493804,225494730938493915".
apitokenexpiresat__between	optional	Date range for when the API token expires (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
apitokenexpiresat__gt	optional	API token expires after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
apitokenexpiresat__gte	optional	API token expires after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
apitokenexpiresat__lt	optional	API token expires before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
apitokenexpiresat__lte	optional	API token expires before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".

cangenerateapitoken	optional	Can generate api token
createdat__between	optional	Date range for when the user was created (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
createdat__gt	optional	User was created after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__gte	optional	User was created after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lt	optional	User was created before this timestamp. Example: "2018-02-27T04:49:26.257525Z".
createdat__lte	optional	User was created before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
datejoined	optional	Date joined. Example: "2018-02-27T04:49:26.257525Z".
email	optional	Email. Example: "admin@sentinelone.com".
email__contains	optional	Match email partially (substring)
emailreadonly	optional	True if email cannot be changed
emailverified	optional	Return only verified/unverified users
firstlogin	optional	First login. Example: "2018-02-27T04:49:26.257525Z".
fullname	optional	Full name
fullname__contains	optional	Match full name partially (substring)
fullnamereadonly	optional	True if full name cannot be changed
groupsreadonly	optional	[DEPRECATED] True if permissions cannot be changed
hasvalidapitoken	optional	Has valid api token
ids	optional	List of user IDs to filter by. Example: "225494730938493804,225494730938493915".
lastactivation__between	optional	Date range for when the user was last active (format: <from_timestamp>-<to_timestamp>, inclusive). Example: "1514978890136-1514978650130".
lastactivation__gt	optional	User was last active after this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastactivation__gte	optional	User was last active after or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastactivation__lt	optional	User was last active before this timestamp. Example:

		"2018-02-27T04:49:26.257525Z".
lastactivation_lte	optional	User was last active before or at this timestamp. Example: "2018-02-27T04:49:26.257525Z".
lastlogin	optional	Last login. Example: "2018-02-27T04:49:26.257525Z".
primarytwofamethod	optional	Primary two fa method
query	optional	Full text search for fields: full_name, email, description
roleids	optional	List of rbac roles to filter by. Example: "225494730938493804,225494730938493915".
siteids	optional	List of Site IDs to filter by. Example: "225494730938493804,225494730938493915".
source	optional	User Source. Example: "mgmt".
sources	optional	Source in. Example: "mgmt".
twofaenabled	optional	Two fa enabled
twofastatus	optional	Two fa status
twofastatuses	optional	Two fa status in

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Get User

GET /web/api/v2.1/users/{user_id}

Get a user by ID.

Response Messages

200 - User retrieved successfully.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions.

404 - Could not retrieve user.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Get User - response - data table
errors	Errors	false	array

Get User - response - data

Name	Description	Required	Value
scope	User Scope	true	enum
account	Relevant if the user is a site level user or single account	false	see Get User - response - account table
agreedEula	True if EULA was agreed for user's sites	false	boolean
agreementUrl	Link to EULA agreement if it was not agreed yet	false	string
allowRemoteShell	[DEPRECATED] Unused field. The user's role will determine if it is allowed to use remote_shell.	false	boolean
apiToken	Api token	false	see Get User - response - apiToken table
canGenerateApiToken	Can generate api token	false	boolean
dateJoined	Date joined	false	string
elevatedSessionDurationMinutes	Defines for how many minutes can the user call protected actions once their session is elevated.	false	integer
email	Email	false	string
emailReadOnly	True if email cannot be modified	false	boolean
emailVerified	True if user verification completed successfully	false	boolean
firstLogin	First login	false	string
fullName	Full name	false	string
fullNameReadOnly	True if full name cannot be modified	false	boolean
globalOrganizationId	Global organization id	false	string
globalUserId	Global user id	false	string
groupsReadOnly	[Deprecated]	false	boolean
id	Id	false	string
isExternalLoginUser	Is external login user	false	boolean
isSystem		false	boolean
lastLogin	Last login	false	string

lowestRole	[DEPRECATED] in RBAC there's no 'lowest' role. Returns Admin if user has admin permission on all sites, otherwise a different role.	false	string
pages	Pages	false	see Get User - response - pages table
primaryTwoFaMethod	Primary two fa method	false	string
scopeRoles	Roles of the scope user	false	see Get User - response - scopeRoles table
siteRoles	[DEPRECATED] Role and site ids for the user. Using scopeRoles is more consistent.	false	see Get User - response - siteRoles table
source	Source	false	string
tenantRoles	[DEPRECATED] Role ids for the tenant user. Using scopeRoles is more consistent.	false	undefined []
twoFaConfigured	User 2FA Auth is configured	false	boolean
twoFaEnabled	Two fa enabled	false	boolean
twoFaEnabledReadOnly	True if two fa option cannot be modified	false	boolean
twoFaStatus	State of 2FA setup	false	enum

Get User - response - account

Name	Description	Required	Value
id	The id of the account	false	string
name	The name of the account	false	string

Get User - response - apiToken

Name	Description	Required	Value
createdAt	Created at	false	string
expiresAt	Expires at	false	string

Get User - response - pages

Name	Description	Required	Value
identifier	Identifier	false	string
name	Name	false	string
permissions	Permissions	false	see Get User - response - permissions table

Get User - response - permissions

Name	Description	Required	Value
additionalDescription	Additional description	false	string
dependsOn	Depends on	false	string []
description	Description	false	string
disabledReason	Disabled reason	false	string
disabledReasonCode	Disabled reason code	false	string
groupName	Group name	false	string
identifier	Identifier	false	string
title	Title	false	string
type	Type	false	string
value	Value	false	boolean

Get User - response - scopeRoles

Name	Description	Required	Value
accountName	Scope name	true	string
name	Scope name	true	string
id	Scope ID	false	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the desired role name in this scope. Use role_id or role_name instead.	false	string []

Get User - response - siteRoles

Name	Description	Required	Value
id	Site ID	true	string
name	Site name	true	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the desired role name in this scope. Use role_id instead.	false	string []

Delete User

DELETE /web/api/v2.1/users/{user_id}

Delete a user by ID.

Response Messages

200 - User deleted successfully.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete User - response - data table
errors	Errors	false	array

Delete User - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Update User

PUT /web/api/v2.1/users/{user_id}

Change properties of the user of the given ID.

Response Messages

200 - User updated successfully.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Forbidden.

404 - User not found.

409 - User or Email already taken.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Update User - response - data table
errors	Errors	false	array

Update User - response - data

Name	Description	Required	Value
scope	User Scope	true	enum
agreedEula	True if EULA was agreed for user's sites	false	boolean
agreementUrl	Link to EULA agreement if it was not agreed yet	false	string
allowRemoteShell	[DEPRECATED] Unused field. The user's role will determine if it is allowed to use remote_shell.	false	boolean
apiToken	Api token	false	see Update User - response - apiToken table
canGenerateApiToken	Can generate api token	false	boolean
dateJoined	Date joined	false	string
elevatedSessionDurationMinutes	Defines for how many minutes can the user call protected actions once their session is elevated.	false	integer
email	Email	false	string
emailReadOnly	True if email cannot be modified	false	boolean
emailVerified	True if user verification completed successfully	false	boolean
firstLogin	First login	false	string
fullName	Full name	false	string
fullNameReadOnly	True if full name cannot be modified	false	boolean
globalOrganizationId	Global organization id	false	string
globalUserId	Global user id	false	string
groupsReadOnly	[Deprecated]	false	boolean
id	Id	false	string
isExternalLoginUser	Is external login user	false	boolean
isSystem		false	boolean
lastLogin	Last login	false	string
lowestRole	[DEPRECATED] in RBAC there's no 'lowest' role. Returns Admin if user	false	string

	has admin permission on all sites, otherwise a different role.		
primaryTwoFaMethod	Primary two fa method	false	string
scopeRoles	Roles of the scope user	false	see Update User - response - scopeRoles table
siteRoles	[DEPRECATED] Role and site ids for the user. Using scopeRoles is more consistent.	false	see Update User - response - siteRoles table
source	Source	false	string
tenantRoles	[DEPRECATED] Role ids for the tenant user. Using scopeRoles is more consistent.	false	undefined []
twoFaConfigured	User 2FA Auth is configured	false	boolean
twoFaEnabled	Two fa enabled	false	boolean
twoFaEnabledReadOnly	True if two fa option cannot be modified	false	boolean
twoFaStatus	State of 2FA setup	false	enum

Update User - response - apiToken

Name	Description	Required	Value
createdAt	Created at	false	string
expiresAt	Expires at	false	string

Update User - response - scopeRoles

Name	Description	Required	Value
accountName	Scope name	true	string
name	Scope name	true	string
id	Scope ID	false	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the	false	string []

	desired role name in this scope. Use role_id or role_name instead.		
--	--	--	--

Update User - response - siteRoles

Name	Description	Required	Value
id	Site ID	true	string
name	Site name	true	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the desired role name in this scope. Use role_id instead.	false	string []

Body Schema

Name	Description	Required	Value
data	Data	true	see Update User - body - data table

Update User - body - data

Name	Description	Required	Value
scope	User scope	true	enum
allowRemoteShell	[DEPRECATED] Unused field. The user's role will determine if it is allowed to use remote_shell.	false	boolean
canGenerateApiToken	Can generate api token	false	boolean
currentPassword	User password, new name for backward compatibility	false	string
email	[DEPRECATED] The email of the user	false	string
fullName	Full name of the user	false	string
id	Id	false	string
password	User password	false	string
scopeRoles	List of id and role id, id is mandatory for user in scope account/site. Role name is deprecated and will work only for predefined roles, please use role id. User in tenant (global) role does not need to provide an id.	false	see Update User - body - scopeRoles table
siteRoles	[DEPRECATED] Please use scopeRoles instead.	false	see Update User - body - siteRoles table
tenantRoles	[DEPRECATED] Use roles instead. List of tenant roles.	false	string []
twoFaCode	Two-Factor Authorization code	false	string
twoFaEnabled	Two fa enabled	false	boolean

Update User - body - scopeRoles

Name	Description	Required	Value
id	Scope ID	false	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will	false	string

	work only for predefined roles		
roles	[DEPRECATED] List containing the desired role name in this scope. Use role_id or role_name instead.	false	string []

Update User - body - siteRoles

Name	Description	Required	Value
id	Site ID	true	string
name	[DEPRECATED] Site name	false	string
roleId	ID of the wanted role	false	string
roleName	[DEPRECATED] Name of the role, will work only for predefined roles	false	string
roles	[DEPRECATED] List containing the desired role name in this scope. Use role_id instead.	false	string []

Bulk Delete Users

POST /web/api/v2.1/users/delete-users

Delete all users that match the filter.

Response Messages

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Bulk Delete Users - body - filter table
data	Data	false	see Bulk Delete Users - body - data table

Bulk Delete Users - body - filter

Name	Description	Required	Value
apiTokenExpiresAt__between	Date range for when the API token expires (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
apiTokenExpiresAt__gt	API token expires after this timestamp	false	string
apiTokenExpiresAt__gte	API token expires after or at this timestamp	false	string
apiTokenExpiresAt__lt	API token expires before this timestamp	false	string
apiTokenExpiresAt__lte	API token expires before or at this timestamp	false	string
canGenerateApiToken	Can generate api token	false	boolean
createdAt__between	Date range for when the user was created (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	User was created after this timestamp	false	string
createdAt__gte	User was created after or at this timestamp	false	string
createdAt__lt	User was created before this timestamp	false	string
createdAt__lte	User was created before or at this timestamp	false	string
dateJoined	Date joined	false	string
email	Email	false	string
email__contains	Match email partially (substring)	false	string []
emailReadOnly	True if email cannot be changed	false	boolean
emailVerified	Return only verified/unverified users	false	boolean
firstLogin	First login	false	string
fullName	Full name	false	string
fullName__contains	Match full name partially (substring)	false	string []
fullNameReadOnly	True if full name cannot be changed	false	boolean

groupsReadOnly	[DEPRECATED] True if permissions cannot be changed	false	boolean
hasValidApiToken	Has valid api token	false	boolean
ids	List of user IDs to filter by	false	string []
lastActivation__between	Date range for when the user was last active (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActivation__gt	User was last active after this timestamp	false	string
lastActivation__gte	User was last active after or at this timestamp	false	string
lastActivation__lt	User was last active before this timestamp	false	string
lastActivation__lte	User was last active before or at this timestamp	false	string
lastLogin	Last login	false	string
primaryTwoFaMethod	Primary two fa method	false	string
query	Full text search for fields: full_name, email, description	false	string
roleIds	List of rbac roles to filter by	false	string []
source	User Source	false	enum
sources	Source in	false	string []
twoFaEnabled	Two fa enabled	false	boolean
twoFaStatus	Two fa status	false	string
twoFaStatuses	Two fa status in	false	string []

Bulk Delete Users - body - data

Generate iFrame Token

POST /web/api/v2.1/users/generate-iframe-token

Get a new iFrame token with the provided limitations.

Response Messages

200 - User created successfully.

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Not enough permissions to create user.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Generate iFrame Token - response - data table
errors	Errors	false	array

Generate iFrame Token - response - data

Name	Description	Required	Value
iframeToken	User's iframe token	true	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Generate iFrame Token - body - data table

Generate iFrame Token - body - data

Name	Description	Required	Value
accountId	Account id	true	string
agentUids	A list of included UUIDs	false	string []
role	[DEPRECATED]Name of the role	false	string
roleName	RBAC role name	false	string
userName	The username that will be displayed	false	string

Enable 2FA

POST /web/api/v2.1/users/2fa/enable

Enable two-factor authentication for a given user.

Response Messages

200 - 2FA successfully enabled

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - No permission for the action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Enable 2FA - response - data table
errors	Errors	false	array

Enable 2FA - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Enable 2FA - body - data table

Enable 2FA - body - data

Name	Description	Required	Value
id	User ID	true	string
currentPassword	Current password	false	string
twoFaCode	Two-Factor Authorization code	false	string

Disable 2FA

POST /web/api/v2.1/users/2fa/disable

Disable Two-Factor Authentication for one user. This requires the ID of the user (run "users").

Response Messages

200 - 2FA successfully disabled

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - No permission for the action

Response Schema

Name	Description	Required	Value
data	Response data	false	see Disable 2FA - response - data table
errors	Errors	false	array

Disable 2FA - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Disable 2FA - body - data table

Disable 2FA - body - data

Name	Description	Required	Value
id	User ID	true	string
currentPassword	Current password	false	string
twoFaCode	Two-Factor Authorization code	false	string

Generate API Token

POST /web/api/v2.1/users/generate-api-token

Get the API token for the authenticated user.

Response Messages

200 - API token delivered to user

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

409 - API token conflict (already generated)

Response Schema

Name	Description	Required	Value
data	Response data	false	see Generate API Token - response - data table
errors	Errors	false	array

Generate API Token - response - data

Name	Description	Required	Value
token	User's API token	true	string

Body Schema

Name	Description	Required	Value
data	Data	false	see Generate API Token - body - data table

Generate API Token - body - data

Name	Description	Required	Value
forceLegacy	Temporary attribute for WA: If the flag is set to True the legacy token will be generated even if the auth_tokens global switch is turned on	false	boolean

Revoke API Token

POST /web/api/v2.1/users/revoke-api-token

Revoke an API token.

Response Messages

200 - Api token revoked

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

404 - User not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Revoke API Token - response - data table
errors	Errors	false	array

Revoke API Token - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Revoke API Token - body - data table

Revoke API Token - body - data

Name	Description	Required	Value
id	User ID	true	string
currentPassword	Current password	false	string
twoFaCode	Two-Factor Authorization code	false	string

API Token by User ID

GET /web/api/v2.1/users/{user_id}/api-token-details

Get the details of the API token generated for a given user.

Response Messages

200 - Success

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

404 - User not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see API Token by User ID - response - data table
errors	Errors	false	array

API Token by User ID - response - data

Name	Description	Required	Value
createdAt	Created at	false	string
expiresAt	Expires at	false	string

API Token Details

POST /web/api/v2.1/users/api-token-details

Get details of the API token that matches the filter.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

Response Schema

Name	Description	Required	Value
data	Response data	false	see API Token Details - response - data table
errors	Errors	false	array

API Token Details - response - data

Name	Description	Required	Value
createdAt	Created at	false	string
expiresAt	Expires at	false	string

Body Schema

Name	Description	Required	Value
data	Data	false	see API Token Details - body - data table

API Token Details - body - data

Name	Description	Required	Value
apiToken	Api token	false	string

Enable 2FA App

POST /web/api/v2.1/users/enable-app

Enable support for the 2FA app (such as Duo or Google Authenticator) that your Console users will use to log in.

Response Messages

200 - 2FA app enabled

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Enable 2FA App - response - data table
errors	Errors	false	array

Enable 2FA App - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Enable 2FA App - body - data table

Enable 2FA App - body - data

Name	Description	Required	Value
code	Code	false	string
id	Id	false	string

Request 2FA App

POST /web/api/v2.1/users/request-app

Request 2FA App response.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Request 2FA App - response - data table
errors	Errors	false	array

Request 2FA App - response - data

Name	Description	Required	Value
code	Code	false	string
qrCode	Qr code	false	string

Body Schema

Name	Description	Required	Value
currentPassword	User password	false	string

Change Password

POST /web/api/v2.1/users/change-password

Change the user password.

Response Messages

- 200 - Password changed
- 400 - Invalid user input received. See error details for further information.
- 401 - Unauthorized access - please sign in and retry.
- 403 - Insufficient permissions
- 404 - User not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Change Password - response - data table
errors	Errors	false	array

Change Password - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Change Password - body - data table

Change Password - body - data

Name	Description	Required	Value
id	User ID	true	string
confirmNewPassword	Confirm new password	false	string
currentPassword	Current password	false	string
newPassword	New password	false	string
twoFaCode	Two-Factor Authorization code	false	string

Auth Elevate

POST /web/api/v2.1/users/auth/elevate

Elevate a session with a third-party app, such as DUO or Google Authenticator.

Response Messages

200 - Elevated

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Auth Elevate - response - data table
errors	Errors	false	array

Auth Elevate - response - data

Name	Description	Required	Value
duration	Duration	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Auth Elevate - body - data table

Auth Elevate - body - data

Name	Description	Required	Value
code	Code	true	string

Sign EULA

POST /web/api/v2.1/users/auth/eula

Mark the End User License Agreement (EULA) as signed for user scopes.

Response Messages

200 - Authenticated

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Sign EULA - response - data table
errors	Errors	false	array

Sign EULA - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Check Global User

GET /web/api/v2.1/users/tenant-admin-auth-check

See if logged in user is a user with the Global scope of access.

Response Messages

200 - User is Global.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Check Global User - response - data table
errors	Errors	false	array

Check Global User - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Check Remote Shell Permissions

GET /web/api/v2.1/users/rs-auth-check

See if the logged in user is allowed to use Remote Shell.

Response Messages

200 - User is allowed to use remote shell feature.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Check Remote Shell Permissions - response - data table
errors	Errors	false	array

Check Remote Shell Permissions - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Check Viewer

GET /web/api/v2.1/users/viewer-auth-check

See if the logged in user has only viewer permissions.

Response Messages

200 - User is a viewer.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Check Viewer - response - data table
errors	Errors	false	array

Check Viewer - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Email Verification

POST /web/api/v2.1/users/onboarding/verify

When a new user verifies their email, the Management gets a token. Use this command to verify the token and set a new password.

Response Messages

200 - User successfully verified

400 - Invalid user input received. See error details for further information.

401 - Verification failed

404 - A user matching the input verification token wasn't found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Email Verification - response - data table
errors	Errors	false	array

Email Verification - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Body Schema

Name	Description	Required	Value
data	Data	true	see Email Verification - body - data table

Email Verification - body - data

Name	Description	Required	Value
password	User selected password	true	string
token	Verification token	true	string
resetPasswordFlow	Reset password flow	false	boolean

Validate Verification Token

GET /web/api/v2.1/users/onboarding/validate-token

When a new user verifies their email, the Management gets a token. Use this command to validate the token.

Parameters

token	required	Verification token
resetpasswordflow	optional	Reset password flow

Response Messages

200 - Token is valid

400 - Invalid user input received. See error details for further information.

401 - Verification failed

404 - A user matching the input verification token wasn't found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Validate Verification Token - response - data table
errors	Errors	false	array

Validate Verification Token - response - data

Name	Description	Required	Value
success	Indicates a successful operation	false	boolean

Send Verification Email

POST /web/api/v2.1/users/onboarding/send-verification-email

Send verification email to users that match the filter. Warning: Active users will be locked out of the Management Console until they verify (unless set_user_password_methods is on)their email. If your Management Console has Onboarding enabled, when you create a new user, the user gets an email invitation. If the user does not respond in time or loses the email, you can send it again. You can send the email invitation to multiple users. Your SMTP server must be correctly configured in Settings > SMTP for the Global scope. Changing the Global SMTP settings requires an Admin role with Global scope or Support.

Response Messages

200 - Success

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Send Verification Email - response - data table
errors	Errors	false	array

Send Verification Email - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Send Verification Email - body - filter table
data	Data	false	see Send Verification Email - body - data table

Send Verification Email - body - filter

Name	Description	Required	Value
apiTokenExpiresAt__between	Date range for when the API token expires (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
apiTokenExpiresAt__gt	API token expires after this timestamp	false	string
apiTokenExpiresAt__gte	API token expires after or at this timestamp	false	string
apiTokenExpiresAt__lt	API token expires before this timestamp	false	string
apiTokenExpiresAt__lte	API token expires before or at this timestamp	false	string
canGenerateApiToken	Can generate api token	false	boolean
createdAt__between	Date range for when the user was created (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	User was created after this timestamp	false	string
createdAt__gte	User was created after or at this timestamp	false	string
createdAt__lt	User was created before this timestamp	false	string
createdAt__lte	User was created before or at this timestamp	false	string
dateJoined	Date joined	false	string
email	Email	false	string
email__contains	Match email partially (substring)	false	string []
emailReadOnly	True if email cannot be changed	false	boolean
emailVerified	Return only verified/unverified users	false	boolean
firstLogin	First login	false	string
fullName	Full name	false	string
fullName__contains	Match full name partially (substring)	false	string []
fullNameReadOnly	True if full name cannot be changed	false	boolean

groupsReadOnly	[DEPRECATED] True if permissions cannot be changed	false	boolean
hasValidApiToken	Has valid api token	false	boolean
ids	List of user IDs to filter by	false	string []
lastActivation__between	Date range for when the user was last active (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActivation__gt	User was last active after this timestamp	false	string
lastActivation__gte	User was last active after or at this timestamp	false	string
lastActivation__lt	User was last active before this timestamp	false	string
lastActivation__lte	User was last active before or at this timestamp	false	string
lastLogin	Last login	false	string
primaryTwoFaMethod	Primary two fa method	false	string
query	Full text search for fields: full_name, email, description	false	string
roleIds	List of rbac roles to filter by	false	string []
source	User Source	false	enum
sources	Source in	false	string []
twoFaEnabled	Two fa enabled	false	boolean
twoFaStatus	Two fa status	false	string
twoFaStatuses	Two fa status in	false	string []

Send Verification Email - body - data

Reset 2FA

POST /web/api/v2.1/users/reset-2fa

Reset 2FA for users.

Response Messages

200 - 2FA reset completed

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

404 - User not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Reset 2FA - response - data table
errors	Errors	false	array

Reset 2FA - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Reset 2FA - body - data table

Reset 2FA - body - data

Name	Description	Required	Value
enroll	[DEPRECATED] Not used, deprecated	false	boolean
ids	A list of user ids	false	string []

Delete 2FA

POST /web/api/v2.1/users/delete-2fa

Delete 2FA for users.

Response Messages

200 - 2FA delete completed

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

404 - User not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Delete 2FA - response - data table
errors	Errors	false	array

Delete 2FA - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Delete 2FA - body - data table

Delete 2FA - body - data

Name	Description	Required	Value
ids	A list of user ids	false	string []

Enroll 2FA

POST /web/api/v2.1/users/enroll-2fa

Enroll users for 2FA setup.

Response Messages

200 - 2FA enrollment completed

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

404 - User not found

Response Schema

Name	Description	Required	Value
data	Response data	false	see Enroll 2FA - response - data table
errors	Errors	false	array

Enroll 2FA - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer
expiration	The number of hours until 2FA enrollment expires	false	integer

Body Schema

Name	Description	Required	Value
data	Data	true	see Enroll 2FA - body - data table

Enroll 2FA - body - data

Name	Description	Required	Value
ids	A list of user ids	false	string []

Redirect to SSO

GET /web/api/v2.1/users/login/sso-saml2

If SSO is enabled for a deployment or scope, and a user attempts to log in with name and password, this command redirects the login to SSO.

Parameters

email	optional	Email address of the user trying to log in. Example: "me@sentinelone.com".
scopeid	optional	The scope the desired SSO IdP is configured on. email is irrelevant when using scope_id. If both are provided, email is ignored. Example: "225494730938493804".

Response Messages

302 - Login redirected.

400 - Invalid user input received. See error details for further information.

401 - Not authenticated user.

Redirect to SSO for re-authentication

GET /web/api/v2.1/users/sso-saml2/re-auth

Initiates re-authentication with user's identity provider.

Response Messages

302 - Redirect user to their IDP for re-authentication.

401 - Unauthorized access - please sign in and retry.

403 - User is not allowed to re-authenticate with their IDP

500 - Error in SAML handler initialization.

Auth by SSO

POST /web/api/v2.1/users/login/sso-saml2/{scope_id}

Authenticate a Single Sign-On response over SAML v2 protocol.

Response Messages

302 - SSO authenticated.

401 - Not authenticated user.

404 - Site not found.

Login

POST /web/api/v2.1/users/login

Authenticate a user by username and password and return an authentication token. Rate limit: 1 call per second for each different IP address that communicates with the Console.

Response Messages

200 - User authenticated successfully.

400 - Invalid user input received. See error details for further information.

401 - Login failed. May be the result of bad credentials, or a wrong authentication method if SSO or 2FA is required. A temporary token might be provided to do the required next step. The error code defines the cause and the next step.
Basic error codes:4010010 - authentication failed,4010040 - generic login error.Error codes related to password changes and expiration:4010091 - user must change password - /users/login/set-password,4010092 - password expired - /users/login/set-password,4010093 - password expires soon - /users/login-continue.Error codes related to LDAP (Active Directory):4010050 - generic LDAP error,4010060 - user has no email,4010070 - user is disabled.Error codes related to 2FA:4010035 - 2FA configuration - /users/request-app,4010030 - 2FA required - /users/auth/app,4010031 - 2FA not enrolled,4010032 - 2FA enrollment expired.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Login - response - data table
errors	Errors	false	array

Login - response - data

Name	Description	Required	Value
token	Generated authentication token	true	string
csrf	Generated csrf token	false	string
status	User verification status	false	enum
twoFaMethod	Two-factor authentication method (if enabled)	false	enum

Body Schema

Name	Description	Required	Value
password	Your password	true	string
username	The user email	true	string
rememberMe	User should be remembered across sessions	false	boolean

Logout

POST /web/api/v2.1/users/logout

Log out the authenticated user.

Response Messages

200 - User logged out successfully.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Logout - response - data table
errors	Errors	false	array

Logout - response - data

Name	Description	Required	Value
redirectTo	Where the browser should be redirected after the logout	false	string

Login by API Token

POST /web/api/v2.1/users/login/by-api-token

Log in to the API with a token. To learn more about temporary and 6-month tokens and how to generate them, see <https://support.sentinelone.com/hc/en-us/articles/360004195934>.

Response Messages

200 - user logged in

400 - Invalid user input received. See error details for further information.

401 - User authentication failed

Response Schema

Name	Description	Required	Value
data	Response data	false	see Login by API Token - response - data table
errors	Errors	false	array

Login by API Token - response - data

Name	Description	Required	Value
token	User token	true	string
realUser	When logging in from Atlas, specifies the actual user who logged in	false	string
redirectTo	Relative url to redirect to	false	string
redirectToParams	Query params for the redirect to, without '?' prefix	false	string
removedSavedScope	Removed saved scope	false	string

Body Schema

Name	Description	Required	Value
data	Data	false	see Login by API Token - body - data table

Login by API Token - body - data

Name	Description	Required	Value
apiToken	Api token	false	string
reason	When logging in from Atlas, specifies the login reason	false	string

Login by Token

GET /web/api/v2.1/users/login/by-token

Log in with user token.

Parameters

token	required	User token. Example: "bfd9070c1afa88516d3cdfd722e62fe433e42bad6bb14da27088140ad785585f8582adaccd56fb69".
redirectto	optional	Relative url to redirect to
redirecttoparams	optional	Query params for the redirect to, without '?' prefix
removedsavedscope	optional	Removed saved scope

Response Messages

200 - user logged in

400 - Invalid user input received. See error details for further information.

401 - User authentication failed

Continue with login due to upcoming password expiration or SSO 2FA setup

POST /web/api/v2.1/users/login-continue

For SSO 2FA setup tokens, allows users to skip setting up the 2FA and proceed with their login. Accepts a temporary token from SSO login flow with error code 4010035.

For password expiration tokens, allows users to decide if they want to change their soon to expire password now or later.
Users can also choose not to receive the notification again for this password cycle.
Accepts a temporary token from /users/login with error code 4010093.
For users eligible to be onboarded to global identity allows to decide if they want to skip and finish their login

Response Messages

200 - Login can continue

400 - Invalid user input received. See error details for further information.

401 - Unauthorized.
In password expiration flow, a temporary token might be provided to do the required next step. The error code defines the cause and the next step.

Error codes:4010010 - invalid token,4010094 - change password with /users/login/set-password

Response Schema

Name	Description	Required	Value
data	Response data	false	see Continue with login due to upcoming password expiration or SSO 2FA setup - response - data table
errors	Errors	false	array

Continue with login due to upcoming password expiration or SSO 2FA setup - response - data

Name	Description	Required	Value
token	Generated authentication token	true	string
csrf	Generated csrf token	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Continue with login due to upcoming password expiration or SSO 2FA setup - body - data table

Continue with login due to upcoming password expiration or SSO 2FA setup - body - data

Name	Description	Required	Value
token	Temporary JWT	true	string
dontShowAgain	Indicates if the user wants to skip the continue next time	false	boolean
resetPassword	Indicates if the user wants to change the password	false	boolean

Set a New Password

POST /web/api/v2.1/users/login/set-password

Sets a new password for the user.

Used by forced password reset and password expiration flows.

Accepts temporary tokens from /users/login with error codes 4010091 and 4010092.

Response Messages

200 - Password was set

400 - Invalid user input received. See error details for further information.

401 - Unauthorized

Response Schema

Name	Description	Required	Value
data	Response data	false	see Set a New Password - response - data table
errors	Errors	false	array

Set a New Password - response - data

Name	Description	Required	Value
token	Generated authentication token	true	string
csrf	Generated csrf token	false	string

Body Schema

Name	Description	Required	Value
data	Data	true	see Set a New Password - body - data table

Set a New Password - body - data

Name	Description	Required	Value
password	The new password	true	string
token	Verification token	true	string

Prompt reset password

POST /web/api/v2.1/users/login/send-reset-password-email

Prompt reset password for users.

Response Messages

200 - Prompt reset password completed

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Prompt reset password - response - data table
errors	Errors	false	array

Prompt reset password - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Prompt reset password - body - filter table
data	Data	false	see Prompt reset password - body - data table

Prompt reset password - body - filter

Name	Description	Required	Value
apiTokenExpiresAt__between	Date range for when the API token expires (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
apiTokenExpiresAt__gt	API token expires after this timestamp	false	string
apiTokenExpiresAt__gte	API token expires after or at this timestamp	false	string
apiTokenExpiresAt__lt	API token expires before this timestamp	false	string
apiTokenExpiresAt__lte	API token expires before or at this timestamp	false	string
canGenerateApiToken	Can generate api token	false	boolean
createdAt__between	Date range for when the user was created (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	User was created after this timestamp	false	string
createdAt__gte	User was created after or at this timestamp	false	string
createdAt__lt	User was created before this timestamp	false	string
createdAt__lte	User was created before or at this timestamp	false	string
dateJoined	Date joined	false	string
email	Email	false	string
email__contains	Match email partially (substring)	false	string []
emailReadOnly	True if email cannot be changed	false	boolean
emailVerified	Return only verified/unverified users	false	boolean
firstLogin	First login	false	string
fullName	Full name	false	string
fullName__contains	Match full name partially (substring)	false	string []
fullNameReadOnly	True if full name cannot be changed	false	boolean

groupsReadOnly	[DEPRECATED] True if permissions cannot be changed	false	boolean
hasValidApiToken	Has valid api token	false	boolean
ids	List of user IDs to filter by	false	string []
lastActivation__between	Date range for when the user was last active (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActivation__gt	User was last active after this timestamp	false	string
lastActivation__gte	User was last active after or at this timestamp	false	string
lastActivation__lt	User was last active before this timestamp	false	string
lastActivation__lte	User was last active before or at this timestamp	false	string
lastLogin	Last login	false	string
primaryTwoFaMethod	Primary two fa method	false	string
query	Full text search for fields: full_name, email, description	false	string
roleIds	List of rbac roles to filter by	false	string []
source	User Source	false	enum
sources	Source in	false	string []
twoFaEnabled	Two fa enabled	false	boolean
twoFaStatus	Two fa status	false	string
twoFaStatuses	Two fa status in	false	string []

Prompt reset password - body - data

Reset password on next login

POST /web/api/v2.1/users/login/force-reset-password-on-login

Force users to reset their password on next login.

Response Messages

200 - Users marked to reset password on next login successfully

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

403 - Insufficient permissions

Response Schema

Name	Description	Required	Value
data	Response data	false	see Reset password on next login - response - data table
errors	Errors	false	array

Reset password on next login - response - data

Name	Description	Required	Value
affected	Number of entities affected by the requested operation	false	integer

Body Schema

Name	Description	Required	Value
filter	Filter	true	see Reset password on next login - body - filter table
data	Data	false	see Reset password on next login - body - data table

Reset password on next login - body - filter

Name	Description	Required	Value
apiTokenExpiresAt__between	Date range for when the API token expires (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
apiTokenExpiresAt__gt	API token expires after this timestamp	false	string
apiTokenExpiresAt__gte	API token expires after or at this timestamp	false	string
apiTokenExpiresAt__lt	API token expires before this timestamp	false	string
apiTokenExpiresAt__lte	API token expires before or at this timestamp	false	string
canGenerateApiToken	Can generate api token	false	boolean
createdAt__between	Date range for when the user was created (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
createdAt__gt	User was created after this timestamp	false	string
createdAt__gte	User was created after or at this timestamp	false	string
createdAt__lt	User was created before this timestamp	false	string
createdAt__lte	User was created before or at this timestamp	false	string
dateJoined	Date joined	false	string
email	Email	false	string
email__contains	Match email partially (substring)	false	string []
emailReadOnly	True if email cannot be changed	false	boolean
emailVerified	Return only verified/unverified users	false	boolean
firstLogin	First login	false	string
fullName	Full name	false	string
fullName__contains	Match full name partially (substring)	false	string []
fullNameReadOnly	True if full name cannot be changed	false	boolean

groupsReadOnly	[DEPRECATED] True if permissions cannot be changed	false	boolean
hasValidApiToken	Has valid api token	false	boolean
ids	List of user IDs to filter by	false	string []
lastActivation__between	Date range for when the user was last active (format: <from_timestamp>-<to_timestamp>, inclusive)	false	string
lastActivation__gt	User was last active after this timestamp	false	string
lastActivation__gte	User was last active after or at this timestamp	false	string
lastActivation__lt	User was last active before this timestamp	false	string
lastActivation__lte	User was last active before or at this timestamp	false	string
lastLogin	Last login	false	string
primaryTwoFaMethod	Primary two fa method	false	string
query	Full text search for fields: full_name, email, description	false	string
roleIds	List of rbac roles to filter by	false	string []
source	User Source	false	enum
sources	Source in	false	string []
twoFaEnabled	Two fa enabled	false	boolean
twoFaStatus	Two fa status	false	string
twoFaStatuses	Two fa status in	false	string []

Reset password on next login - body - data

Auth App

POST /web/api/v2.1/users/auth/app

Authenticate a user with a third-party app, such as DUO or Google Authenticator, for deployments that require Two Factor Authentication.

Response Messages

200 - Authenticated

400 - Invalid user input received. See error details for further information.

401 - Unauthorized access - please sign in and retry.

Response Schema

Name	Description	Required	Value
data	Response data	false	see Auth App - response - data table
errors	Errors	false	array

Auth App - response - data

Name	Description	Required	Value
token	Generated authentication token	true	string
csrf	Generated csrf token	false	string
status	User verification status	false	enum
twoFaMethod	Two-factor authentication method (if enabled)	false	enum

Body Schema

Name	Description	Required	Value
data	Data	true	see Auth App - body - data table

Auth App - body - data

Name	Description	Required	Value
code	Code	false	string
rememberMe	User should be remembered across sessions	false	boolean

VCS Integration

Fetch filter count

GET /web/api/v2.1/cnapp/vcs/filters/count

Fetch filter count

Parameters

scopeids	required	
scopetype	required	

Response Messages

200 - Filter count fetched successfully

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	string []

Delete a VCS Integration

GET /web/api/v2.1/cnapp/vcs/integration/{integrationId}/offboarding

This API is used to off-board a VCS integration.

Parameters

scopeids	required	
scopetype	required	

Response Messages

200 - VCS offboarding app url created successfully

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
appUrl		false	string

Disable scanning for repositories in a VCS integration

PUT /web/api/v2.1/cnapp/vcs/integration/{integrationId}/repos/disable-scan

Deactivate scanning for repositories associated with the given VCS integration.

Parameters

scopeids	required	
scopetype	required	

Response Messages

200 - Successfully disabled repositories

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	object

Body Schema

Name	Description	Required	Value
data		false	see Disable scanning for repositories in a VCS integration - body - data table

Disable scanning for repositories in a VCS integration - body - data

Name	Description	Required	Value
repositoryIds		false	string []

Edit tags for repositories in a VCS integration

PUT /web/api/v2.1/cnapp/vcs/integration/{integrationId}/repos/edit-tags

Allows modification of tags associated with one or more repositories under a specified VCS integration. This operation supports adding, removing, or updating tags to help organize and categorize repositories effectively.

Parameters

scopeids	required	
scopetype	required	

Response Messages

200 - Tags updated successfully

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	object

Body Schema

Name	Description	Required	Value
data		false	see Edit tags for repositories in a VCS integration - body - data table

Edit tags for repositories in a VCS integration - body - data

Name	Description	Required	Value
action		true	enum
repositoryIds		false	string []
tagIds		false	string []

Enable scanning for repositories in a VCS integration

PUT /web/api/v2.1/cnapp/vcs/integration/{integrationId}/repos/enable-scan

Activates scanning for repositories associated with the given VCS integration.

Parameters

scopeids	required	
scopetype	required	

Response Messages

200 - Successfully enabled repositories

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	object

Body Schema

Name	Description	Required	Value
data		false	see Enable scanning for repositories in a VCS integration - body - data table

Enable scanning for repositories in a VCS integration - body - data

Name	Description	Required	Value
repositoryIds		false	string []

Fetch repository tags

POST /web/api/v2.1/cnapp/vcs/integration/{integrationId}/repos/get-tags

This endpoint retrieves tags associated with repositories under a VCS integration.

Parameters

scopeIds	required	
scopeType	required	

Response Messages

200 - Repositories tags fetched successfully

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	undefined []

Body Schema

Name	Description	Required	Value
data		false	see Fetch repository tags - body - data table

Fetch repository tags - body - data

Name	Description	Required	Value
repositoryIds		false	string []

Delete a VCS integration

DELETE /web/api/v2.1/cnapp/vcs/integration/{vcsIntegrationId}

This endpoint permanently deletes a VCS integration.

Parameters

scopeids	required	
scopetype	required	

Response Messages

200 - VCS integration deleted successfully

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	see Delete a VCS integration - response - data table

Delete a VCS integration - response - data

Name	Description	Required	Value
uninstall		false	boolean

Update a VCS integration

PUT /web/api/v2.1/cnapp/vcs/integration/{vcsIntegrationId}

This endpoint allows users to update configuration details for a VCS integration.

Parameters

scopeids	required	
scopetype	required	

Response Messages

200 - VCS integration updated successfully

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	object

Body Schema

Name	Description	Required	Value
data		false	see Update a VCS integration - body - data table

Update a VCS integration - body - data

Name	Description	Required	Value
description		false	string
settings		false	see Update a VCS integration - body - settings table
tags		false	string []
title		false	string

Update a VCS integration - body - settings

Name	Description	Required	Value
devNewRepositoryAlertSeverity		true	enum
monitorDevNewPublicRepositories		true	boolean
monitorOrgNewPublicRepositories		true	boolean
orgNewRepositoryAlertSeverity		true	enum
scanDevPublicRepositories		true	boolean
scanOrgPrivateRepositories		true	boolean
scanOrgPublicRepositories		true	boolean

List VCS integration repositories

GET /web/api/v2.1/cnapp/vcs/integration/{vcsIntegrationId}/repos

Fetches a list of repositories associated with the VCS integration

Parameters

cursor	optional	
limit	optional	
scopeids	optional	
scopetype	optional	
skip	optional	

Response Messages

200 - Successfully retrieved the list of repositories

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	see List VCS integration repositories - response - data table
pagination	Pagination information	false	see List VCS integration repositories - response - pagination table

List VCS integration repositories - response - data

Name	Description	Required	Value
repos		false	undefined []

List VCS integration repositories - response - pagination

Name	Description	Required	Value
totalItems		true	integer
nextCursor		false	string

Resync VCS Integration Repositories

PUT /web/api/v2.1/cnapp/vcs/integration/{vcsIntegrationId}/repos/resync

Initiates a process to resynchronize repositories associated with the specified VCS integration

Parameters

scopeids	required	
scopetype	required	

Response Messages

200 - Resynchronization initiated successfully

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	object

List VCS integrations

GET /web/api/v2.1/cnapp/vcs/integrations

Fetches a list of all configured VCS integrations.

Parameters

limit	optional	
scopeids	optional	
scopetype	optional	
skip	optional	

Response Messages

200 - Successfully retrieved the list of VCS integrations

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	undefined []
pagination	Pagination information	false	see List VCS integrations - response - pagination table

List VCS integrations - response - pagination

Name	Description	Required	Value
totalItems		true	integer
nextCursor		false	string

Edit tags for a VCS integration

PUT /web/api/v2.1/cnapp/vcs/integrations/edit-tags

Allows modification of tags in a VCS integration. This operation supports adding, removing, or updating tags to help organize and categorize integration repositories effectively.

Parameters

scopeids	required	
scopetype	required	

Response Messages

200 - Tags updated successfully

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	object

Body Schema

Name	Description	Required	Value
data		false	see Edit tags for a VCS integration - body - data table

Edit tags for a VCS integration - body - data

Name	Description	Required	Value
action		true	enum
integrationIds		false	string []
tagIds		false	string []

Onboard a new VCS integration

POST /web/api/v2.1/cnapp/vcs/onboarding

This endpoint allows users to onboard a new VCS integration, enabling automated scanning for secrets and IaC misconfigurations.

Parameters

scopeids	required	
scopetype	required	

Response Messages

200 - VCS onboarding completed successfully

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
appUrl		false	string

Body Schema

Name	Description	Required	Value
data		false	see Onboard a new VCS integration - body - data table

Onboard a new VCS integration - body - data

Name	Description	Required	Value
provider		true	enum
azureOrganizationUrl		false	string
azurePersonalAccessToken		false	string
description		false	string
githubAppId		false	string
githubAppPrivateKey		false	string
githubInstallationId		false	string
gitlabPersonalAccessToken		false	string
serverHost		false	string
serverPort		false	integer
settings		false	see Onboard a new VCS integration - body - settings table
tags		false	string []
title		false	string

Onboard a new VCS integration - body - settings

Name	Description	Required	Value
devNewRepositoryAlertSeverity		true	enum
monitorDevNewPublicRepositories		true	boolean
monitorOrgNewPublicRepositories		true	boolean
orgNewRepositoryAlertSeverity		true	enum
scanDevPublicRepositories		true	boolean
scanOrgPrivateRepositories		true	boolean
scanOrgPublicRepositories		true	boolean

List VCS and CICD scanner policies

GET /web/api/v2.1/cnapp/vcs/scanner-policies

This endpoint retrieves a list of all configured scanner policies used for VCS and CICD integrations.

Parameters

limit	optional	
scopeids	optional	
scopetype	optional	
skip	optional	

Response Messages

200 - Scanner policies fetched successfully

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	undefined []
pagination	Pagination information	false	see List VCS and CICD scanner policies - response - pagination table

List VCS and CICD scanner policies - response - pagination

Name	Description	Required	Value
totalItems		true	integer
nextCursor		false	string

Create a VCS and CICD scanner policy

POST /web/api/v2.1/cnapp/vcs/scanner-policy

Defines a scanning policy for a VCS integration, configuring parameters for detecting secrets, IaC misconfigurations, and vulnerabilities within repositories.

Parameters

scopeids	required	
scopetype	required	

Response Messages

200 - Scanner policy created successfully

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	see Create a VCS and CICD scanner policy - response - data table

Create a VCS and CICD scanner policy - response - data

Name	Description	Required	Value
policyId		false	string

Body Schema

Name	Description	Required	Value
data		false	see Create a VCS and CICD scanner policy - body - data table

Create a VCS and CICD scanner policy - body - data

Name	Description	Required	Value
priority		true	integer
branch		false	string
description		false	string
name		false	string
scope		false	see Create a VCS and CICD scanner policy - body - scope table

Create a VCS and CICD scanner policy - body - scope

Name	Description	Required	Value
id		false	string
type		false	string

Get max allowed priority

GET /web/api/v2.1/cnapp/vcs/scanner-policy/max-allowed-priority

This endpoint returns the maximum allowed value for the priority in scanner policies.

Parameters

scopeids	required	
scopetype	required	
targetscopeid	required	
targetscopetype	required	

Response Messages

200 - Max allowed priority fetched successfully

400 - Bad Request

Response Schema

Name	Description	Required	Value
data		false	see Get max allowed priority - response - data table

Get max allowed priority - response - data

Name	Description	Required	Value
maxAllowedPriority		false	integer

Delete a VCS and CICD scanner policy

DELETE /web/api/v2.1/cnapp/vcs/scanner-policy/{policyId}

This endpoint deletes a scanner policy.

Parameters

scopeids	required	
scopetype	required	

Response Messages

200 - VCS scanner policy deleted successfully

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	object

Get a VCS and CICD scanner policy

GET /web/api/v2.1/cnapp/vcs/scanner-policy/{policyId}

Get a VCS and CICD scanner policy

Parameters

scopeids	required	
scopetype	required	

Response Messages

200 - This endpoint fetches detailed information for a scanner policy.

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	see Get a VCS and CICD scanner policy - response - data table

Get a VCS and CICD scanner policy - response - data

Name	Description	Required	Value
branch		false	string
createdAt		false	string
createdBy		false	string
description		false	string
iacConfig		false	object
id		false	string
name		false	string
priority		false	integer
s1TenancyId		false	string
scope		false	see Get a VCS and CICD scanner policy - response - scope table
scopeInfo		false	object
scopePath		false	string
secretConfig		false	object
tags		false	undefined []
updatedAt		false	string
vulnerabilityConfig		false	object

Get a VCS and CICD scanner policy - response - scope

Name	Description	Required	Value
id		false	string
type		false	string

Update a VCS and CICD scanner policy

PUT /web/api/v2.1/cnapp/vcs/scanner-policy/{policyId}

This endpoint updates an existing scanner policy. A scanner policy defines how secrets, IaC misconfigurations, and vulnerabilities should be detected and handled within a VCS integration/CICD.

Parameters

scopeids	required	
scopetype	required	

Response Messages

200 - Scanner policy updated successfully

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	object

Body Schema

Name	Description	Required	Value
data		false	see Update a VCS and CICD scanner policy - body - data table

Update a VCS and CICD scanner policy - body - data

Name	Description	Required	Value
name		true	string
priority		true	integer
branch		false	string
description		false	string
iacConfig		false	see Update a VCS and CICD scanner policy - body - iacConfig table
secretConfig		false	see Update a VCS and CICD scanner policy - body - secretConfig table
tagIds		false	string []
vulnerabilityConfig		false	see Update a VCS and CICD scanner policy - body - vulnerabilityConfig table

Update a VCS and CICD scanner policy - body - iacConfig

Name	Description	Required	Value
enabled		true	boolean
exitConditions		false	see Update a VCS and CICD scanner policy - body - exitConditions table

Update a VCS and CICD scanner policy - body - exitConditions

Name	Description	Required	Value
action		true	enum
severity		true	enum
commentOnlyWhenIssuesFound		false	boolean

Update a VCS and CICD scanner policy - body - secretConfig

Name	Description	Required	Value
enabled		true	boolean

excludeExtensions		false	string []
exitConditions		false	see Update a VCS and CICD scanner policy - body - exitConditions table

Update a VCS and CICD scanner policy - body - exitConditions

Name	Description	Required	Value
action		true	enum
severity		true	enum
commentOnlyWhenIssuesFound		false	boolean
exitOnlyOnVerifiedSecret		false	boolean

Update a VCS and CICD scanner policy - body - vulnerabilityConfig

Name	Description	Required	Value
enabled		true	boolean
cveExceptions		false	undefined []
exitConditions		false	see Update a VCS and CICD scanner policy - body - exitConditions table

Update a VCS and CICD scanner policy - body - exitConditions

Name	Description	Required	Value
severity		true	enum

Register Tunnel User

POST /web/api/v2.1/cnapp/vcs/tunnel/user

This API is used to register a new tunnel user. It sets up the necessary tunnel configuration and credentials for secure access.

Parameters

scopeids	required	
----------	----------	--

scopetype	required	
-----------	----------	--

Response Messages

200 - Tunnel user registered successfully

400 - Bad Request

500 - Internal Server Error

Response Schema

Name	Description	Required	Value
data		false	see Register Tunnel User - response - data table

Register Tunnel User - response - data

Name	Description	Required	Value
apiServerAddress		false	string
apiServerPort		false	integer
password		false	string
serverAddress		false	string
serverPort		false	integer
tunnelPort		false	integer
user		false	string

Body Schema

Name	Description	Required	Value
data		false	see Register Tunnel User - body - data table

Register Tunnel User - body - data

Name	Description	Required	Value
provider		true	enum
serverPort		true	integer
gitlabPersonalAccessToken		false	string
serverHost		false	string
