

1. When does Exceptions in Java arises in code sequence?

- a) Run Time
- b) Compilation Time
- c) Can Occur Any Time
- d) None of the mentioned

2. Which of these keywords is not a part of exception handling?

- a) try
- b) finally
- c) thrown
- d) catch

3. Which of these keywords must be used to monitor for exceptions?

- a) try
- b) finally
- c) throw
- d) catch

4. Which of these keywords must be used to handle the exception thrown by try block in some rational manner?

- a) try
- b) finally
- c) throw
- d) catch

5. Which of these keywords is used to manually throw an exception?

- a) try
- b) finally
- c) throw

6. What will be the output of the following Java program?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            System.out.print("Hello" + " " + 1 / 0);
        }
        catch(ArithmeticException e)
        {
            System.out.print("World");
        }
    }
}
```

- a) Hello
- b) World
- c) HelloWorld
- d) Hello World

7. What will be the output of the following Java program?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            int a, b;
            b = 0;
            a = 5 / b;
            System.out.print("A");
        }
        catch(ArithmeticException e)
        {
            System.out.print("B");
        }
    }
}
```

a) A
b) B
c) Compilation Error
d) Runtime Error

8. What will be the output of the following Java program?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            int a, b;
            b = 0;
            a = 5 / b;
            System.out.print("A");
        }
        catch(ArithmeticException e)
        {
            System.out.print("B");
        }
        finally
        {
            System.out.print("C");
        }
    }
}
```

a) A
b) B
c) AC

d) BC

9. What will be the output of the following Java program?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            int i, sum;
            sum = 10;
            for (i = -1; i < 3 ;++i)
                sum = (sum / i);
        }
        catch(ArithmeticException e)
        {
            System.out.print("0");
        }
        System.out.print(sum);
    }
}
```

a) 0

b) 05

c) Compilation Error

d) Runtime Error

Exceptional handling:

10. Which of the following keywords is used for throwing exception manually?

a) finally

b) try

c) throw

d) catch

11. Which of the following classes can catch all exceptions which cannot be caught?

a) RuntimeException

b) Error

c) Exception

d) ParentException

12. Which of the following is a super class of all exception type classes?

a) Catchable

b) RuntimeExceptions

c) String

d) Throwable

13. Which of the following operators is used to generate instance of an exception which can be thrown using throw?

a) thrown

b) alloc

- c) malloc
- d) new

14. Which of the following keyword is used by calling function to handle exception thrown by called function?

- a) throws
- b) throw
- c) try
- d) catch

15. Which of the following handles the exception when a catch is not used?

- a) finally
- b) throw handler
- c) default handler
- d) java run time system

16. Which part of code gets executed whether exception is caught or not?

- a) finally
- b) try
- c) catch
- d) throw

17. Which of the following should be true of the object thrown by a thrown statement?

- a) Should be assignable to String type
- b) Should be assignable to Exception type
- c) Should be assignable to Throwable type
- d) Should be assignable to Error type

18. At runtime, error is recoverable.

- a) True
- b) False

19. Which of these is a super class of all exceptional type classes?

- a) String
- b) RuntimeExceptions
- c) Throwable
- d) Cacheable

20. Which of these class is related to all the exceptions that can be caught by using catch?

- a) Error
- b) Exception
- c) RuntimeException
- d) All of the mentioned

21. Which of these class is related to all the exceptions that cannot be caught?

- a) Error
- b) Exception
- c) RuntimeException
- d) All of the mentioned

22. Which of these handles the exception when no catch is used?

- a) Default handler
- b) finally
- c) throw handler
- d) Java run time system

23. What exception thrown by parseInt() method?

- a) ArithmeticException
- b) ClassNotFoundException
- c) NullPointerException
- d) NumberFormatException

24. What will be the output of the following Java code?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            System.out.print("Hello" + " " + 1 / 0);
        }
        finally
        {
            System.out.print("World");
        }
    }
}
```

- a) Hello
- b) World
- c) Compilation Error
- d) First Exception then World

25. What will be the output of the following Java code?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            int i, sum;
            sum = 10;
            for (i = -1; i < 3 ;++i)
            {
                sum = (sum / i);
                System.out.print(i);
            }
        }
        catch(ArithmeticException e)
        {
            System.out.print("0");
        }
    }
}
```

```
    }  
  }  
a) -1  
b) 0  
c) -10  
d) -101
```

26. Which of these keywords is used to generate an exception explicitly?

a) try
b) finally
c) throw
d) catch

27. Which of these class is related to all the exceptions that are explicitly thrown?

a) Error
b) Exception
c) Throwable
d) Throw

28. Which of these operator is used to generate an instance of an exception than can be thrown by using throw?

a) new
b) malloc
c) alloc
d) thrown

29. Which of these keywords is used to by the calling function to guard against the exception that is thrown by called function?

a) try
b) throw
c) throws
d) catch

30. What will be the output of the following Java code?

```
class exception_handling  
{  
    public static void main(String args[])  
    {  
        try  
        {  
            int a = args.length;  
            int b = 10 / a;  
            System.out.print(a);  
            try  
            {  
                if (a == 1)  
                    a = a / a - a;  
                if (a == 2)  
                {  
                    int []c = {1};  
                    c[8] = 9;  
                }  
            }  
        }  
    }  
}
```

```

    }
    catch (ArrayIndexOutOfBoundsException e)
    {
        System.out.println("TypeA");
    }
    catch (ArithmeticException e)
    {
        System.out.println("TypeB");
    }
}
}
}

```

- a) TypeA
- b) TypeB
- c) Compile Time Error
- d) 0TypeB

31. What will be the output of the following Java code?

```

class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            System.out.print("A");
            throw new NullPointerException ("Hello");
        }
        catch(ArithmeticException e)
        {
            System.out.print("B");
        }
    }
}

```

- a) A
- b) B
- c) Hello
- d) Runtime Exception

32. What will be the output of the following Java code?

```

public class San
{
    public static void main(String[] args)
    {
        try
        {
            return;
        }
        finally
        {
            System.out.println( "Finally" );
        }
    }
}

```

```
}  
}
```

- a) Finally
- b) Compilation fails
- c) The code runs with no output
- d) An exception is thrown at runtime

33. What will be the output of the following Java code?

```
public class San  
{  
    public static void main(String args[])  
    {  
        try  
        {  
            System.out.print("Hello world ");  
        }  
        finally  
        {  
            System.out.println("Finally executing ");  
        }  
    }  
}
```

- a) The program will not compile because no exceptions are specified
- b) The program will not compile because no catch clauses are specified
- c) Hello world
- d) Hello world Finally executing

34. Which of these clause will be executed even if no exceptions are found?

- a) throws
- b) finally
- c) throw
- d) catch

35. A single try block must be followed by which of these?

- a) finally
- b) catch
- c) finally & catch
- d) none of the mentioned

36. Which of these exceptions handles the divide by zero error?

- a) ArithmeticException
- b) MathException
- c) IllegalAccessException
- d) IllegalException

37. Which of these exceptions will occur if we try to access the index of an array beyond its length?

- a) ArithmeticException
- b) ArrayException

- c) ArrayIndexException
- d) ArrayIndexOutOfBoundsException

38. What will be the output of the following Java code?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            int a = args.length;
            int b = 10 / a;
            System.out.print(a);
        }
        catch (ArithmeticException e)
        {
            System.out.println("1");
        }
    }
}
```

Note : Execution command line : \$ java exception_handling

- a) 0
- b) 1
- c) Compilation Error
- d) Runtime Error

39. What will be the output of the following Java code?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            throw new NullPointerException ("Hello");
        }
        catch(ArithmeticException e)
        {
            System.out.print("B");
        }
    }
}
```

- a) A
- b) B
- c) Compilation Error
- d) Runtime Error

40. What will be the output of the following Java code?

```

class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            int a = 1;
            int b = 10 / a;
            try
            {
                if (a == 1)
                    a = a / a - a;
                if (a == 2)
                {
                    int c[] = {1};
                    c[8] = 9;
                }
            }
            finally
            {
                System.out.print("A");
            }
        }
        catch (Exception e)
        {
            System.out.println("B");
        }
    }
}

```

- a) A
- b) B
- c) AB
- d) BA

41. What will be the output of the following Java code?

```

class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            int a = args.length;
            int b = 10 / a;
            System.out.print(a);
            try
            {
                if (a == 1)
                    a = a / a - a;
                if (a == 2)

```

```

        {
            int []c = {1};
            c[8] = 9;
        }
    }
    catch (ArrayIndexOutOfBoundsException e)
    {
        System.out.println("TypeA");
    }
    catch (ArithmeticException e)
    {
        System.out.println("TypeB");
    }
}
}

```

Note: Execution command line: \$ java exception_handling one two

- a) TypeA
- b) TypeB
- c) **Compilation Error**
- d) Runtime Error

42. What is the use of try & catch?

- a) It allows us to manually handle the exception
- b) It allows to fix errors
- c) It prevents automatic terminating of the program in cases when an exception occurs
- d) **All of the mentioned**

43. Which of these keywords are used for the block to be examined for exceptions?

- a) **try**
- b) catch
- c) throw
- d) check

44. Which of these keywords are used for the block to handle the exceptions generated by try block?

- a) try
- b) **catch**
- c) throw
- d) check

45. Which of these keywords are used for generating an exception manually?

- a) try
- b) catch
- c) **throw**
- d) check

46. Which of these statements is incorrect?

- a) try block need not to be followed by catch block
- b) try block can be followed by finally block instead of catch block
- c) try can be followed by both catch and finally block

d) try need not to be followed by anything

47. What will be the output of the following Java code?

```
class Output
{
    public static void main(String args[])
    {
        try
        {
            int a = 0;
            int b = 5;
            int c = b / a;
            System.out.print("Hello");
        }
        catch(Exception e)
        {
            System.out.print("World");
        }
    }
}
```

- a) Hello
- b) World
- c) HelloWorld
- d) Compilation Error

48. What will be the output of the following Java code?

```
class Output
{
    public static void main(String args[])
    {
        try
        {
            int a = 0;
            int b = 5;
            int c = a / b;
            System.out.print("Hello");
        }
        catch(Exception e)
        {
            System.out.print("World");
        }
    }
}
```

- a) Hello
- b) World
- c) HelloWorld
- d) Compilation Error

49. What will be the output of the following Java code?

```

class Output
{
    public static void main(String args[])
    {
        try
        {
            int a = 0;
            int b = 5;
            int c = b / a;
            System.out.print("Hello");
        }
    }
}

```

- a) Hello
- b) World
- c) HelloWOrld
- d) Compilation Error

50. What will be the output of the following Java code?

```

class Output
{
    public static void main(String args[])
    {
        try
        {
            int a = 0;
            int b = 5;
            int c = a / b;
            System.out.print("Hello");
        }
        finally
        {
            System.out.print("World");
        }
    }
}

```

- a) Hello
- b) World
- c) HelloWOrld
- d) Compilation Error

51. What will be the output of the following Java code?

```

class Output
{
    public static void main(String args[])
    {
        try

```

```
{
    int a = 0;
    int b = 5;
    int c = b / a;
    System.out.print("Hello");
}
catch(Exception e)
{
    System.out.print("World");
}
finally
{
    System.out.print("World");
}
}
```

- a) Hello
- b) World
- c) HelloWorld
- d) WorldWorld

52. Which of these classes is used to define exceptions?

- a) Exception
- b) Throwable
- c) Abstract
- d) System

53. Which of these methods return description of an exception?

- a) getException()
- b) getMessage()
- c) obtainDescription()
- d) obtainException()

54. Which of these methods is used to print stack trace?

- a) obtainStackTrace()
- b) printStackTrace()
- c) getStackTrace()
- d) displayStackTrace()

55. Which of these methods return localized description of an exception?

- a) **getLocalizedMessage()**
- b) getMessage()
- c) obtainLocalizedMessage()
- d) printLocalizedMessage()

56. Which of these classes is super class of Exception class?

- a) **Throwable**
- b) System
- c) RunTime
- d) Class

57. What will be the output of the following Java code?

```
class Myexception extends Exception
{
    int detail;
    Myexception(int a)
    {
        detail = a;
    }
    public String toString()
    {
        return "detail";
    }
}
class Output
{
    static void compute (int a) throws Myexception
    {
        throw new Myexception(a);
    }
    public static void main(String args[])
    {
        try
        {
            compute(3);
        }
        catch(Myexception e)
        {
            System.out.print("Exception");
        }
    }
}
```

a) 3

- b) **Exception**
- c) Runtime Error
- d) Compilation Error

58. What will be the output of the following Java code?

```
class Myexception extends Exception
{
    int detail;
    Myexception(int a)
    {
        detail = a;
    }
    public String toString()
    {
        return "detail";
    }
}
class Output
{
    static void compute (int a) throws Myexception
    {
        throw new Myexception(a);
    }
    public static void main(String args[])
    {
        try
        {
            compute(3);
        }
        catch(DevideByZeroException e)
        {
            System.out.print("Exception");
        }
    }
}
```

- a) 3
- b) Exception
- c) Runtime Error
- d) Compilation Error

59. What will be the output of the following Java code?

```
class exception_handling
{
    public static void main(String args[])
    {
        try
        {
            throw new NullPointerException ("Hello");
            System.out.print("A");
        }
        catch(ArithmeticException e)
        {

```



```

        System.out.print("B");
    }
}

```

- a) A
- b) B
- c) Compilation Error**
- d) Runtime Error

60. What will be the output of the following Java code?

```

class Myexception extends Exception
{
    int detail;
    Myexception(int a)
    {
        detail = a;
    }
    public String toString()
    {
        return "detail";
    }
}
class Output
{
    static void compute (int a) throws Myexception
    {
        throw new Myexception(a);
    }
    public static void main(String args[])
    {
        try
        {
            compute(3);
        }
        catch(Exception e)
        {
            System.out.print("Exception");
        }
    }
}

```

- a) 3
- b) Exception**
- c) Runtime Error
- d) Compilation Error

61. What will be the output of the following Java code?

```

class exception_handling

```

```

{
    public static void main(String args[])
    {
        try
        {
            int a = args.length;
            int b = 10 / a;
            System.out.print(a);
            try
            {
                if (a == 1)
                    a = a / a - a;
                if (a == 2)
                {
                    int c = {1};
                    c[8] = 9;
                }
            }
        }
        catch (ArrayIndexOutOfBoundsException e)
        {
            System.out.println("TypeA");
        }
        catch (ArithmeticException e)
        {
            System.out.println("TypeB");
        }
    }
}

```

Note : Execution command line : \$ java exception_handling one

a) TypeA

b) TypeB

c) Compilation Error

d) Runtime Error