



ChatGPT



Write a beginner-friendly C++ console program called "AI Roast Generator".

Requirements:

- * Ask the user to enter their name.
- * Store at least 10 funny roast templates in a vector.
- * Each roast should include a placeholder {name}.
- * Randomly select one roast each time the program runs.
- * Replace {name} with the actual input.
- * Display the roast.

Add comments so it is easy to unde



Ask anything



He.

prompt (clean + beginner-friendly, ready



ChatGPT



Here's the **exact result** matching your prompt (clean + beginner-friendly, ready to screenshot) 📌

Result

C++



```
#include <iostream>
#include <vector>
#include <string>
#include <cstdlib>

using namespace std;

// Function to replace {name} with actual name
string replaceName(string roast, string name) {
    size_t pos = roast.find("{name}")

    // Loop until all {name} placeholders are replaced
    while (pos != string::npos) {
        roast.replace(pos, 6, name);
        pos = roast.find("{name}");
    }

    return roast;
}

int main() {
    string name; ↓
```

```
// Ask user for their name
```



Ask anything



```
// Store roast templates in a vector
```

6:09

LTE 35%

= ChatGPT



```
        return roast;
    }

int main() {
    string name;

    // Ask user for their name
    cout << "Enter your name: ";
    cin >> name;

    // Store roast templates in a vector
    vector<string> roasts = {
        "{name} writes code so slow e",
        "If laziness were an Olympic",
        "{name}'s debugging is just s",
        "{name} doesn't fix bugs, the",
        "{name}'s code has more drama",
        "{name} uses Google more than",
        "{name} compiles code and hop",
        "{name} opens IDE just for vi",
        "{name}'s logic went missing.",
        "{name} writes code like plot",
    };

    // Randomly select a roast
    int index = rand() % roasts.size();

    // Replace {name} with actual input
    string finalRoast = replaceName(roasts[index], name);

    // Display the roast
    cout << finalRoast << endl;

    return 0;
}
```



+ Ask anything



Send the next prompt

ChatGPT



The program is not replacing {name} with the actual user input.

Can you fix the code so that {name} is replaced properly in the output?

Here's the **exact result** for your prompt (fixed placeholder issue) 📌

Result

C++



```
#include <iostream>
#include <vector>
#include <string>
#include <cstdlib>
```

```
using namespace std;
```



```
// Function to replace {name} with actual user input
```

+ Ask anything



```
// Replace all occurrences of {name} with actual user input
while (pos != string::npos) {
```


= ChatGPT std;



```
// Function to replace {name} with actual
string replaceName(string roast, string name,
    size_t pos = roast.find("{name}"))

// Replace all occurrences of {name}
while (pos != string::npos) {
    roast.replace(pos, 6, name);
    pos = roast.find("{name}");
}

return roast;
}

int main() {
    string name;

    // Ask user for their name
    cout << "Enter your name: ";
    cin >> name;

    // Store roast templates
    vector<string> roasts = {
        "{name} writes code so slow everyone gives up",
        "If laziness were an Olympic sport, {name} would win the gold medal",
        "{name}'s debugging is just a series of 'why is this happening?'",
        "{name} doesn't fix bugs, they just move them to a different part of the code",
        "{name}'s code has more drama than a soap opera",
        "{name} uses Google more than they use their own code",
        "{name} compiles code and hopes for the best",
        "{name} opens IDE just for visual noise",
        "{name}'s logic went missing during compilation",
        "{name} writes code like plot twists in a bad movie"
    };

    // Randomly select a roast
    int index = rand() % roasts.size();

    // Replace placeholder with actual name
    string finalRoast = replaceName(roasts[index], name);

    // Display result
    cout << finalRoast << endl;
```

+ Ask anything



6:09

LTE 34

ChatGPT



Share Message

Here's the **exact result** for your prompt...

```
int main() {
    string name;

    // Ask user for their name
    cout << "Enter your name: ";
    cin >> name;

    // Store roast templates
    vector<string> roasts = {
        "{name} writes code so slow e
        "If laziness were an Olympic
        "{name}'s debugging is just s
        "{name} doesn't fix bugs, the
        "{name}'s code has more drama
        "{name} uses Google more than
        "{name} compiles code and hop
        "{name} opens IDE just for vi
        "{name}'s logic went missing.
        "{name} writes code like plot
    };

    // Randomly select a roast
    int index = rand() % roasts.size(

    // Replace placeholder with actual
    string finalRoast = replaceName(r

    // Display result
    cout << finalRoast << endl;

    return 0;
}
```



+ Ask anything





My program gives the same roast every time I run it.

I am using rand(), but the output is not changing.

Can you fix this and explain the issue?

Here's the **exact result** for your prompt (randomness fixed + explanation) 📌

Result

C++



```
#include <iostream>
#include <vector>
#include <string>
#include <cstdlib>
#include <ctime>
```



```
using namespace std;
```

+ Ask anything



ac

```
string replaceName(string roast, string name) {
    size_t pos = roast.find("{name}")
```

c: ChatGPT



```
using namespace std;

// Function to replace {name} with ac
string replaceName(string roast, stri
    size_t pos = roast.find("{name}")

    // Replace all occurrences of {na
    while (pos != string::npos) {
        roast.replace(pos, 6, name);
        pos = roast.find("{name}");
    }

    return roast;
}

int main() {
    string name;

    // Ask user for their name
    cout << "Enter your name: ";
    cin >> name;

    // Store roast templates
    vector<string> roasts = {
        "{name} writes code so slow e
        "If laziness were an Olympic
        "{name}'s debugging is just s
        "{name} doesn't fix bugs, the
        "{name}'s code has more drama
        "{name} uses Google more than
        "{name} compiles code and hop
        "{name} opens IDE just for vi
        "{name}'s logic went missing.
        "{name} writes code like plot
    };

    // FIX: Seed the random number ge
```

+ Ask anything



```
int index = rand() % roasts.size(
```


= ChatGPT ;



```
int main() {
    string name;

    // Ask user for their name
    cout << "Enter your name: ";
    cin >> name;

    // Store roast templates
    vector<string> roasts = {
        "{name} writes code so slow e
        "If laziness were an Olympic
        "{name}'s debugging is just s
        "{name} doesn't fix bugs, the
        "{name}'s code has more drama
        "{name} uses Google more than
        "{name} compiles code and hop
        "{name} opens IDE just for vi
        "{name}'s logic went missing.
        "{name} writes code like plot
    };

    // FIX: Seed the random number ge
    srand(time(0));

    // Randomly select a roast
    int index = rand() % roasts.size(

    // Replace placeholder with actua
    string finalRoast = replaceName(r

    // Display result
    cout << finalRoast << endl;

    return 0;
}
```



+ Ask anything



Explanation (screenshot)



Improve the program:

- Handle full name input (use getline instead of cin)
- Handle empty input
- Make output look better

Here's the **exact result** for your improvement prompt (final polished version) 🙌

Result

C++



```
#include <iostream>
#include <vector>
#include <string>
#include <cstdlib>
#include <ctime>
```

```
using namespace std;
```

```
// Function to replace {name} with actual name
string replaceName(string roast, string name) {
```

+ Ask anything



6:10

LTE 34

ChatGPT



```
using namespace std;
```

```
// Function to replace {name} with ac  
string replaceName(string roast, stri  
size_t pos = roast.find("{name}")
```

```
// Replace all occurrences of {na  
while (pos != string::npos) {  
    roast.replace(pos, 6, name);  
    pos = roast.find("{name}");  
}
```

```
return roast;
```

```
}
```

```
int main() {  
    string name;
```

```
// Ask user for full name  
cout << "Enter your name: ";  
getline(cin, name);
```

```
// Handle empty input  
if (name.empty()) {  
    cout << "⚠ Please enter a va  
    return 0;  
}
```

```
// Store roast templates  
vector<string> roasts = {  
    "{name} writes code so slow e  
    "If laziness were an Olympic  
    "{name}'s debugging is just s  
    "{name} doesn't fix bugs, the  
    "{name}'s code has more drama  
    "{name} ↓ ; Google more than  
    "{name} compiles code and hop
```

+ Ask anything



ChatGPT

```
// Ask user for full name
cout << "Enter your name: ";
getchar();
name);

// Handle empty input
if (name.empty()) {
    cout << "⚠ Please enter a valid name\n";
    return 0;
}

// Store roast templates
vector<string> roasts = {
    "{name} writes code so slow everyone gives up",
    "If laziness were an Olympic sport, {name} would win gold",
    "{name}'s debugging is just a series of 'maybe's",
    "{name} doesn't fix bugs, they just hide them",
    "{name}'s code has more drama than a soap opera",
    "{name} uses Google more than their own code",
    "{name} compiles code and hopes for the best",
    "{name} opens IDE just for the dopamine hit",
    "{name}'s logic went missing somewhere",
    "{name} writes code like a drunkard",
};

// Seed random generator
srand(time(0));

// Randomly select a roast
int index = rand() % roasts.size();

// Replace placeholder with actual name
string finalRoast = replaceName(roasts[index], name);

// Display result with better formatting
cout << "\n🔥 Your AI Roast 🔥\n";
cout << "-----\n";
cout << finalRoast << endl;
cout << "-----\n";

return 0;
}
```