

---

**Rule 0.26** *(Cache Array Length in Loops)*

---

<pre>[...] <b>contract</b> A {   [...]   <b>function</b> f(pds) {     [...]     <b>for</b>(init; i &lt; arr.length; upd) {       stmts     }     stmts'   }   [...] }</pre>	=	<pre>[...] <b>contract</b> A' {   [...]   <b>function</b> f(pds) {     [...]     <b>uint</b> len = arr.length;     <b>for</b>(init; i &lt; len; upd) {       stmts     }     stmts'   }   [...] }</pre>
---	---	---

**where**

*arr* is an array whose length is accessed in the loop condition;  
*arr.length* is the array length property accessed in each loop iteration;  
*len* is a local variable that caches the array length;  
*init* and *upd* are the loop initialization and update expressions;  
*i* is the loop index variable;  
*stmts* represents the loop body statements;  
*pds* are the parameter declarations of function *f*;  
*stmts'* represents statements following the loop.

**provided**

The array length is accessed in the loop condition on every iteration;  
The array *arr* is not modified within the loop in a way that changes its length;  
No operations within the loop (e.g., **push**, **pop**) alter the array size;  
Caching the length does not affect the correctness of the loop;  
The cached length remains valid throughout loop execution.

**Invariant:**

Let  $s_i$  and  $s'_i$  be the initial state of *A* and *A'*, respectively.  
Let  $s_f$  and  $s'_f$  be the state reached by *A* and *A'*, respectively, after *A.f()* and *A'.f()* are executed from  $s_i$  and  $s'_i$ , respectively.  
Then, the coupling invariant is

$$\forall s_i, s'_i. (s_i = s'_i) \rightarrow (s_f = s'_f)$$

---