

---

**Rule 0.1** Single Line Swap.

---

|                                                                                                                                                                                                                                                            |   |                                                                                                                                                                                                                              |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre>[...] contract &lt;A&gt; {   [...]   function &lt;f&gt;(&lt;parameters&gt;) [...] {     [...]     &lt;tmp&gt; = &lt;varA&gt;     &lt;P&gt;     &lt;varA&gt; = &lt;varB&gt;     &lt;Q&gt;     &lt;varB&gt; = &lt;tmp&gt;     [...]   }   [...] }</pre> | = | <pre>[...] contract &lt;A&gt; {   [...]   function &lt;f&gt;(&lt;parameters&gt;) [...] {     [...]     (&lt;varA&gt;, &lt;varB&gt;) = (&lt;varB&gt;, &lt;varA&gt;)     &lt;P&gt;     &lt;Q&gt;     [...]   }   [...] }</pre> |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**where**  $A$ ,  $f$ ,  $tmp$ ,  $varA$  and  $varB$  are identifiers,  $parameters$  is a list of identifiers,  $P$  and  $Q$  are Solidity commands, and  $[...]$  denote Solidity constructs;

**provided**  $tmp$ ,  $varA$  and  $varB$  do not occur in  $P$  or in  $Q$ .

---