LIVING CHECKLIST · UPDATED WITH EVERY CHANGE

FOX_Checklist

What this is: every FoxByte feature and its sub-features — built or not, and how it was tested — so it's clear where we are and what's next. How each feature works is in `FOX_Feature_Implemented.pdf` (same ids).

Last updated: 22 September 2026 · **Reflects:** `main` @ `2778762` (v1.0.1, exact repository path PR #1) + the FoxByte rename and brand indirection (`chore/foxbyte`)

Source: `docs/FOX_Checklist.html` → `make feature-doc` → this PDF

✅ Done & tested — automated tests (unit, VM integration or CI) ☑ Done — tested by hand only ◐ Partial — gaps, or not verified end to end ☒ Known issue ☐ Not started

Sub-features: ✓ built ◐ partly ! a known limit → planned, not built □ not built yet ✕ broken **The badge rule** (audit v2 G31, which found 47 rows badged done while carrying an open item): a row is *done* or *done (manual)* only when nothing in it is ◐, □ or ✕, and `scripts/test_feature_checklist.sh` fails the build otherwise. A ! is a limit of what the feature does and a → is a planned extension — neither makes the row's own claim untrue. How thoroughly something was tested belongs in "Tested by", not in the sub-features. · "VM §n" = section of `make integration` ; "v2 §n" = `make integration-v2` ; "update" = `make integration-update`

Where we are

Area	Features	Done & tested	Done (manual)	Partial	Known issue	Not started	Progress
A · Install & setup	9	4	3	2	·	·	78%
B · CLI & services	3	3	·	·	·	·	100%
C · Branching & storage	8	7	·	1	·	·	88%
D · Durability	6	5	·	1	·	·	83%
E · Security foundations	3	3	·	·	·	·	100%
F · SQL gateway	7	6	1	·	·	·	100%
G · Accounts & auth	6	5	·	1	·	·	83%
H · Blackbox (record of schema changes)	18	16	·	2	·	·	89%
I · Import & migration	13	5	8	·	·	·	100%
J · ETL pipelines (experimental)	4	2	2	·	·	·	100%
K · APIs, SDKs & agents	6	4	2	·	·	·	100%
L · Web console	11	1	10	·	·	·	100%
M · Build, CI & releases	9	7	1	1	·	·	89%
N · Realtime change feed	1	1	·	·	·	·	100%
Total (features built or started)	**104**	**69**	**27**	**8**	**·**	**·**	**92%**
Z · Not started (roadmap)	7	1	·	·	·	6	14%

Storage engine — not implemented, by design

FoxByte does **not** have its own storage engine. Data is stored by **PostgreSQL's own engine** (heap tables, B-tree indexes, write-ahead log) running on local disk inside the stock `postgres:18-bookworm` image plus wal-g (`postgres:16-bookworm` for an install created before 21 Sep 2026). This was a locked architecture decision: a Neon-style engine that separates compute from storage over the network adds latency to every transaction, and transaction speed must never be compromised.

What **is** built is a storage *layer* around Postgres: copy-on-write branch drivers — ZFS on macOS/Linux, btrfs on Windows — behind one interface in `internal/branch/storage.go` (C1), quotas (C6), capacity reporting (C7), and durability to object storage with wal-g + MinIO: WAL archiving, base backups, point-in-time restore (D1–D3). Networked storage disaggregation is listed in the README roadmap but not started (see "Not started").

Suggested next steps

1. **The claims are checkable now**: a restore is proved weekly and by `fox backup verify` (D2), a tag cannot ship past a red or stale nightly (M2), every command the engine runs has a deadline so nothing hangs for ever (G30's useful half), containers restart on crash (B2), and CI runs the race detector. Before this, the most consequential thing the product claims — that the backups restore — had never been tested end to end on a real install.
2. **This checklist's own badge rule is enforced** (audit v2 G31): no row can be badged done while carrying an open sub-item, and `scripts/test_feature_checklist.sh` fails the build if one is. The 45 sub-items that broke the rule were each put somewhere honest — built, a limit (!), planned (→), or a note in "Tested by" — and nine of them turned out to be things we had already shipped and never ticked off, including automated UI tests, per-user access control, SDK contract tests and the first signed release.
3. Run on real machines what the throwaway VM cannot: `fox update` across a real release on macOS and Windows (A9); on Windows, the zstd distro image's unpack (M5), the btrfs holding area of `fox pg upgrade` (D6), and an export's copy to the host (D5).
4. Automated tests for the imports (I1–I3, I7) — the last area with none.
5. Gate release tags on the nightly suites, so a tag cannot ship past a red suite (M2).
6. Decide how this checklist shows partial work (audit v2 G31): 9 features are badged done while carrying an open sub-item (`C7, D5, D6, F5, G3, H16, H17, I13, M7`) — down from 34. Each of those sub-items is a disclosed limit rather than unfinished work, so the remaining question is whether a limit belongs in the sub-item list at all.
7. **The object store's images are FoxByte's own** (M6): MinIO left Docker Hub in 2026 and then quay.io stopped serving it anonymously — every tag there answers 401 — so a fresh install on macOS or Linux could not start, while existing installs carried on from their cache and Windows carried on because its distro image ships them inside it. They are mirrored to `ghcr.io/thefoxbyte` by `.github/workflows/mirror-images.yml`, which takes them out of a published release's distro asset rather than from a registry

that will not serve us. **Run it once and pin what it prints.** It can only be dispatched after it is on the default branch, and until the digests are pinned `release.yml` refuses to publish.

8. **Promotion is built** (H18, audit G29): a branch's recorded statements, reviewed, then applied to another branch in one transaction — attributed to whoever wrote them, with the approver beside them. Schema only. An agent can propose and cannot approve its own request.
9. **From the audit, deliberately left:** HA beyond the demo — automatic failover and fencing across hosts (D4, G21); metrics and alerts, and supervision of the background servers themselves (B2, G27 — the containers restart); splitting the branch package and running its SQL through pgx (G30 — the deadlines are in); quotas on btrfs and per-branch CPU/memory (C6, G33).

A Install & setup

7 of 9 done

	ID	Feature · sub-features		Tested by
☑	A1	**One-line installer (macOS / Linux)** ✓ Detects OS / CPU, downloads the release binary ✓ Installs to the prefix (sudo only if needed) ✓ Stages the Linux engine for the VM on macOS ✓ `FOX_VERSION`, `FOX_REPO`, `FOX_DIST`, `FOX_PREFIX`	✓ Verifies every download against `SHA256SUMS`; refuses what it can't check ✓ Release signature checked (OpenSSL 3; warns with LibreSSL)	Unit (`test_install_sh.sh`, CI); manual
◐	A2	**Windows installer (install.ps1)** ✓ Installs WSL, elevates, resumes after reboot ✓ Downloads fox.exe, engine, image build context ✓ Ubuntu rootfs verified against Ubuntu's checksums ✓ Adds to PATH and runs `fox setup`	✓ Prefers the prebuilt distro image, falls back to the rootfs ✓ Verifies FoxByte's own downloads ✓ Run on a real Windows machine (distro image downloaded and verified)	Pester (Windows CI); Windows run 16 Sep
☑	A3	**`fox setup` on macOS (Lima)** ✓ Creates / starts the Lima VM ✓ Installs Docker and ZFS ✓ Reinstalls the engine on every run ✓ Starts the stack	✓ Repairs an interrupted provisioning on the next run (dpkg interrupted, half-installed packages) ✓ Image builds from the copy inside fox when it cannot be pulled (C8)	Unit; run against a deliberately broken VM, 21 Sep
☑	A4	**`fox setup` on Windows (WSL2 + btrfs)** ✓ Imports a dedicated distro with systemd ✓ Docker, btrfs and a storage mount unit ✓ Quiet steps, detail in install.log ✓ Waits for systemd on a cold distro	✓ Preloaded images tagged as the engine runs them ✓ Summary with API key and `sslmode` ✓ Fresh install from v0.8.6 on Windows: preload used, no apt, key in the summary	Unit (`host_wsl_test.go`); Windows run 16 Sep
☑	A5	**Linux native** ✓ Engine runs in-process, no VM ✓ `fox setup` explains nothing is needed	✓ Services listen on loopback by default (`FOX_LISTEN` to expose)	VM integration (all suites run on Linux)
☑	A6	**Command forwarding & host file streaming** ✓ macOS → Lima VM, starts the VM if stopped ✓ Windows → WSL distro	✓ `fox import` streams a host file over stdin → Stream `pipeline run` spec files too	Unit (`TestImportLocalFile`, `TestWSLArgs`)
☑	A7	**Always-latest engine binary** ✓ Downloads the newest engine into the cache (ELF check) ✓ `FOX_NO_REFRESH`, `FOX_VERSION`	✓ Verified against `SHA256SUMS`; keeps the staged engine if not ✓ Seen verifying on a real Windows install	Unit (`host_test.go`, `update_test.go`); Windows run 16 Sep
☑	A8	**New-release notice on `fox start`** ✓ Background check, 1.5 s limit, printed last ✓ Only a promoted, newer, complete release	✓ One request per start; a found release remembered 6 h, never "up to date" ✓ Off switch; never on dev builds; silent offline	Unit; update §1, §1b, §2, §3, §8; real Mac check
◐	A9	**`fox update`** ✓ Downloads and verifies everything before changing anything ✓ Stops servers, installs engine, restarts old one on failure ✓ `up`, Blackbox upgrade, `start` on the new engine ✓ Replaces host `fox`, keeps previous binaries ✓ `--check`, `--yes`, `--version` ✓ Linux path verified end to end ✓ macOS path run against real releases (v0.8.3 → v0.8.4 → v0.8.5)	☐ Windows path run against a real release (deferred) ✓ Release signatures (Ed25519 over SHA256SUMS) ✓ The version line stays readable by older installs, so `fox update` works from any released version ✓ A previously released version is shown to accept each build (nightly `upgrade` suite) and each release (`release-verify`)	Unit; update §4–§7; a real Mac run

B CLI & services

3 of 3 done

	ID	Feature · sub-features		Tested by
☑	B1	**The `fox` command set** ✓ Stack: setup, start, stop, up, down, status, check, logs, connect, psql, demo, update ✓ Branching, backup / restore, HA ✓ Blackbox, policy, impact ✓ Import, pipelines ✓ backup export / restore, pg status / upgrade	✓ Users, API keys, admin ✓ `fox vm status` / `fox vm shell` (Lima, WSL; Linux says there is no VM) ✓ `branch create --from` ✓ `fox uninstall` removes it all, retired installs included	Unit (`main_test.go`, `update_test.go`); VM suites
☑	B2	**Background services (daemon)** ✓ Control plane :8080, gateway :6432, agent API :8088 ✓ Detached, pidfiles and logs in `~/.fox` ✓ Stop (TERM then KILL), status, logs	✓ Containers restart on crash and after a reboot (`--restart=unless-stopped`); a container stopped on purpose stays stopped ! The three background servers themselves are not supervised (`fox check` reports them)	Unit (`TestStopTerminatesProcess`); VM §1

✅	B3	**First run (sample data, `check`, `connect`)** ✓ Sample data seeded into `main` on a first start: `users`, `projects`, `events`, five rows each, two foreign keys ✓ `fox demo seed|drop|sql` on any branch; `FOX_NO_DEMO=1` starts empty ✓ The console opens itself, with the one-time setup token already in the link ✓ Declines to open a browser in the VM, over SSH, with no display, or with `FOX_NO_BROWSER`	✓ `fox check`: version, console, storage, main, three servers, three ports, TLS, Blackbox, backup age, sample data — each failure with the command that fixes it ✓ `fox connect [branch]` prints the application's connection string, then opens psql; `fox psql` takes a branch ✓ `fox branch create` ends with the connection string and how long it took ✓ Plain-English errors in the CLI and the console (`internal/errhint`, `web/src/errhint.ts`)	Unit; v1 §11d

C Branching & storage

7 of 8 done

	ID	Feature · sub-features		Tested by
✅	C1	**Storage drivers (ZFS / btrfs)** ✓ ZFS snapshot + clone per branch (macOS VM, Linux) ✓ btrfs subvolume snapshots (Windows) ✓ Pool / filesystem created on a loopback file	✓ One storage interface for both ✓ Delete removes the clone's own origin snapshot, so a non-main parent can be re-used	Unit; VM §2, §2b (ZFS); btrfs manual on Windows
✅	C2	**Branch lifecycle** ✓ Create, list, delete ✓ Reset to parent ✓ Suspend / resume ✓ Recreate a container from its surviving data	✓ Create from any branch (`--from`, REST `from`, Dashboard picker) ✓ Names validated in the CLI and at the API boundary (one check, branch.checkName)	Unit; VM §2, §2b, §4
✅	C3	**Protection of `main`** ✓ Delete and reset refused	✓ Suspend refused for main, the HA standby and whichever container serves main	Unit; VM §4, §6
✅	C4	**Private networking (no host ports)** ✓ Branch databases reachable only through the gateway ✓ Published ports (object store, restore, debug) on loopback only; standby unpublished	✓ An older install's public object store is re-created on start	Unit (`TestParsePublishedPort`, `TestDSN`); VM §1c
✅	C5	**Scale-to-zero & wake on connect** ✓ Idle branches suspended automatically ✓ Next connection wakes the branch (~0.3–0.7 s)	✓ HA standby never suspended → Idle clocks survive a gateway restart	VM §7
◐	C6	**Storage quotas** ✓ Space reserved for main (ZFS) ◐ Per-branch cap (opt-in)	☐ Quotas on btrfs	Manual
✅	C7	**Capacity & status** ✓ Services, main health, backups, branches ✓ Storage used / available	! btrfs "used" is apparent size	VM §1
✅	C8	**Provisioning & image pull** ✓ Docker, storage pool and image prepared on `up` ✓ Pulls from GHCR, builds locally as fallback	✓ The build context is built into fox, so the fallback works on any install	Unit; VM §11b

D Durability

5 of 6 done

	ID	Feature · sub-features		Tested by
✅	D1	**WAL archiving to object storage** ✓ wal-g ships main's WAL to MinIO, off the commit path ✓ MinIO images pinned on quay.io ✓ Branches are disposable by design (export one that matters) ✓ Remote S3 target (`fox backup target set`), keys in 0600 env files	✓ Object Lock reported; tested on MinIO ✓ `fox check` warns while the archive is still on the same disk as main, naming the consequence and the one command that fixes it (HA plan, phase 0)	VM §3; VM §11c; not yet run against AWS S3
✅	D2	**Base backups** ✓ Create and list ✓ Follow the primary after a failover; listing works with main stopped ✓ Read-only listing: `GET /api/backups` and a Dashboard panel ✓ Schedule and retention (`FOX_BACKUP_INTERVAL`, `FOX_BACKUP_RETAIN`) ✓ A first backup at install	✓ Age shown and warned in `fox status` and the status API ✓ Proven, not assumed: `fox backup verify` writes a probe row, waits for its WAL segment to be archived, restores the newest base backup into a container of its own and reads the row back ✓ On a schedule (weekly; `FOX_RESTORE_CHECK_INTERVAL`), with the result in `fox check`	VM §3, §3b, §6; VM §11c
✅	D3	**Point-in-time restore** ✓ Restore to a timestamp or latest on :5433 ✓ Per-install credentials	✓ Starts from the newest base backup that precedes the target ✓ A point no backup precedes is refused, naming the oldest	Unit; VM §3, §3b, §6; v2 §1a

	ID	Feature · sub-features		Tested by
◐	D4	**HA standby & failover** ✓ Streaming hot standby ✓ Manual failover, `main` rerouted ✓ Nothing deletes or stops the promoted standby ✓ `fox up` brings it back, not the old main ✓ `fox ha failback`, keeping every write ✓ The promoted standby archives WAL, so backups and PITR cover the failover ✓ With the change feed on, the standby's own physical slot and a conninfo with a database name, so realtime subscribers keep their position across a promotion (N1) ✓ **A replication role of its own** (HA plan phase 1, first item): `db_replica` copies the database and can read none of it, admitted by one `pg_hba` rule naming it and this install's own network. Replaces `host replication all all` plus a standby connecting as the bootstrap superuser — the wide rule is deleted rather than outranked, the superuser can no longer replicate over the network while its ordinary connections are untouched, and `fox check` warns on an install whose HA was enabled by an older version and still carries the old rule ✓ **TLS on replication, and publishing a primary at all** (HA plan phase 1): `fox node expose` — opt-in, one address, TLS required with a per-install CA the standby verifies, `db_replica` only, one peer `/32` only. Verified between two machines: without TLS refused, the superuser refused even over TLS, a real base backup over TLS succeeded. The private key is kept out of `PGDATA`, which `pg_basebackup` copies. The join token carries the CA and one role's password — never the install secret, from which the superuser's could be derived ✓ **A standby node is told what its licence costs it** (HA plan §3.1): `node join` warns when this machine has no licence that unlocks the paid features — a licence is per-install state and joining copies the database, not `~/.fox`, so a fresh standby has none and refuses paid features immediately on promotion, with no grace. Corrects the plan, which assumed a mismatched fingerprint lapses after 14 days: it never lapses, so the dangerous state is an absent licence, not a mismatched one □ The licence *policy* for HA pairs is still a decision (plan §6.1) — site licence, fingerprint set, or per-node. Recommended: site licences, the only option needing no new code	✓ **Fencing across machines** (HA plan phase 3, first half): `ha failover` on a machine following a remote primary refuses while that primary answers, because promoting would make a second one — a split brain that phase 1 shipped and that was measured (both machines accepting writes). Verified refused with the primary alive, promoted once it was stopped; `--force` warns before proceeding; a promotion says the old primary must re-join rather than restart as a primary. It cannot tell a dead primary from an unreachable one, which needs a failover manager □ The rest of phase 3 — a failover manager for automatic detection — is a decision first: `pg_auto_failover` is installable for PG 18 but its last release predates it, and either manager wants to own `synchronous_standby_names`, which phase 5 made ours ✓ **A standby on another machine** (HA plan phase 1, complete): `fox node join <token>` copies the primary over TLS and runs it as a standby, verifying that primary's certificate. Demonstrated by killing the primary's database with SIGKILL and promoting the survivor, which took writes with every acknowledged row intact. A promotion clears the join, since the survivor follows nobody; `ha enable` refuses on a joined machine rather than silently rebuilding the standby from the local main. Two VMs share a kernel and a disk, so this proves networking, credentials, TLS and promotion — not survival of a power cut ✓ **Failover drills** (HA plan phase 6): `fox ha drill --yes` kills the primary with writes in flight, recovers through the real failover path, and writes a dated RPO/RTO report to `~/.fox/drills/`. Measured 0 of 60 acknowledged writes lost and 400ms to service. The report refuses to let a figure be misquoted — zero under asynchronous replication is an observation, zero under zero-data-loss mode is a guarantee — and names what it did not test: losing a machine, noticing, and a second site ✓ **Zero data loss, opt in** (HA plan phase 5): `fox ha sync on|off` — a commit waits until the standby has it on disk. Off by default; with one standby, if it stops writes stop, and the CLI says so. The release works while commits are stalled, a failover clears it so the promoted node is never left waiting for a standby it does not have, and `fox check` calls "on but nothing counted" a failure □ Automatic failover, fencing, multi-host	Unit; VM §6, §7
✓	D5	**Portable export & restore** ✓ Every non-agent branch: pg_dump, its roles, the Blackbox head; SHA256SUMS over all ✓ Copied out of the VM and verified on the host; a copy that fails is deleted	✓ Damaged, incomplete or path-escaping archives refused ✓ Restore into a new branch, same or newer major; Blackbox checked exact	Unit; VM pg-upgrade §1; the host copy on macOS/Windows is unit-tested only
✓	D6	**PostgreSQL major upgrade** ✓ `fox pg status`: the major of the install and of each branch ✓ Plan with every change crossed, found-in-your-data first; refusals say what to do ✓ Asks, exports, then reloads every carried branch on the new major	✓ Data, roles, API keys and every Blackbox entry come across ✓ Old databases held outside the branch namespace; rollback and finalize ✓ Each upgraded cluster archives WAL under its own prefix → Carry agent branches; upgrade with HA on	Unit; VM pg-upgrade (72 / 72); the btrfs (Windows) holding area has not been run

E Security foundations

3 of 3 done

	ID	Feature · sub-features		Tested by
✓	E1	**Per-install generated secrets** ✓ Generated Postgres and MinIO passwords ✓ Used by restore too	✓ Each login role has its own derived password ✓ Never on a command line (docker `--env-file`)	Unit (indirect); v2 §1a; VM §1d
✓	E2	**TLS everywhere** ✓ Self-signed TLS on all three services, zero setup ✓ TLS required from other machines (loopback clients may skip it)	✓ No plain-HTTP fallback except on loopback	Unit (`TestReadStartupUpgradesTLS`)
✓	E3	**Keys are made by a person, not by start** ✓ Start creates no account and no key, and caches none on disk ✓ The banner shows the connection string and how to make a key	✓ The first account created gets the admin grant on main ✓ First account over HTTP needs the setup token (`fox setup-token`) ✓ Exactly one first account, however many sign up at once	Integration §1

F SQL gateway

7 of 7 done

	ID	Feature · sub-features		Tested by

✅	F1	**Routing by database name** ✓ One endpoint :6432, database name = branch	→ Connection pooling, rate limiting	Unit; VM §1, §6
✅	F2	**API-key authentication** ✓ `key_` key as the Postgres password ✓ Bad key rejected with a Postgres error	✓ Startup deadline and connection cap ✓ An account key opens main, its own branches, or any for an admin	VM §1
✅	F3	**Backend login (SCRAM)** ✓ Cleartext, md5, SCRAM-SHA-256	✓ Clients never see the database password	VM §1, §6, §8 (exercised); no unit test for SCRAM yet
☑	F4	**Per-user Postgres login roles** ✓ Role per user, actor can't be forged ✓ Permissions of non-superuser `db_client`	✓ Own password per role	Manual
✅	F5	**Attribution session settings** ✓ Actor kind, branch, session id per connection	! Kind / branch / session client-settable	VM §8
✅	F6	**Ctrl-C (CancelRequest) forwarding** ✓ Cancel a running query through the gateway		Unit
✅	F7	**Errors & insecure build tag** ✓ Real Postgres error responses	✓ No-auth bypass impossible in release builds	Unit (`TestSendError`)

G Accounts & auth

5 of 6 done

	ID	Feature · sub-features		Tested by
✅	G1	**Auth store (SQLite)** ✓ Users, keys, sessions, OAuth ids, pipelines ✓ Safe under concurrent use (WAL, busy timeout), including a new store created by three services at once	→ Roles / permissions, multi-tenant projects	Unit (`TestVerifyKeyConcurrent` , `TestConcurrentFirstOpen`); VM §1
✅	G2	**Email & password users** ✓ Create account, log in ✓ Password change (signs out other sessions); admin reset at the CLI → Self-service reset by email ✓ List and delete users (admins)	✓ Emails validated; at most 63 bytes (a role name) ✓ Forgotten password: `fox user passwd` , named on the login page, README and Guide ! No self-service reset by email — it needs the machine, which suits a local install and not a hosted one	Unit; VM §1; VM §1d
✅	G3	**API keys** ✓ Create (shown once), list, revoke ✓ Bearer / X-API-Key and gateway password	✓ Revoking an id that is not there is refused (404), not reported as revoked	Unit; VM §1
✅	G4	**Web sessions & signup control** ✓ httpOnly session cookie ✓ Sign-up closed by default (`FOX_SIGNUP=open`)	✓ Failed sign-ins throttled	Unit (`TestSessions`)
◐	G5	**OAuth (GitHub / Google)** ✓ Sign-in flows built ✓ Defaults match what the engine serves (`https://localhost:8080` ; web origin = public URL) ✓ Session cookie `Secure` / `SameSite` follow the origin	☐ Tested with a real OAuth app ✓ Only a provider-verified email joins or creates an account; closed sign-up respected ✓ State cookie one-use, `Secure` , `SameSite=Lax`	Unit; VM §1b
✅	G6	**Security log** ✓ Sign-ins, failures, keys, passwords, accounts, admin grants, refusals ✓ Hash-chained, append-only, anchored and signed	✓ `fox audit` , `verify` , `GET /api/audit` → Included in `fox backup export`	Unit; VM §1d

H Blackbox (record of schema changes)

16 of 18 done

	ID	Feature · sub-features		Tested by
✅	H1	**DDL recording** ✓ Who, tool, branch, statement, status, risk ✓ Inherited by every branch ✓ A restart records nothing: the install script's own statements are not captured ! Role / database changes, some dropped object types ✓ Agents' UPDATE and DELETE recorded; TRUNCATE by anyone	✓ An agent's UPDATE or DELETE with no WHERE is refused, and the attempt recorded — a superuser or db_admin can let one through ✓ Triggers on every table, protected from drop/disable/rename	VM §8; v2 §9; v2 §10
◐	H2	**Hash chain, append-only & verify** ✓ Rows can't be edited or deleted normally ✓ `fox ledger verify` ◐ Superuser rewrite caught only via anchors (H10–H12)	✓ `bb.policy` changes recorded (append-only, not chained)	VM §8; v2 §0, §6b
✅	H3	**Attribution** ✓ Humans via their login role ✓ Agents via their own `agent-<id>` role	✓ Kind derived from the role, so neither can pose as the other ✓ Tool and session are client-declared by design, and labelled so	Unit; VM §8; v2 §1c

☑	H4	**Destructive-DDL guardrail** ✓ DROP TABLE / DROP SCHEMA refused, attempt recorded ✓ Override only superusers / `db_admin`, use recorded	✓ "flag" and "allow" actions; unknown actions refused ✓ No hang when blocked after a write in the same transaction ✓ TRUNCATE blocked by default, recorded	VM §8; v2 §1b, §6b
☑	H5	**Risk flags** ✓ Type change, drop column flagged ✓ Judged on the running statement (no comments or literals)	✓ Automated test	Unit; v2 §6b
☑	H6	**Blackbox access (CLI / REST / MCP / UI / SDK)** ✓ CLI, REST with filters, MCP, web page, SDKs	✓ Per-user access control (internal/access: owner or admin)	v2 §0, §5
☑	H7	**`fox ledger revert --to`** ✓ Help and output say it's a point-in-time restore of main	✓ Points to H13 for a branch from before a change	Unit (help text); VM §3 (the restore)
☑	H8	**Override permission (db_admin) & upgrade** ✓ `fox admin grant|revoke|list` ✓ First user granted automatically	✓ `fox blackbox upgrade [--all]` ✓ Grant / revoke from the web (admins only)	v2 §1b, §6
☑	H9	**Blackbox 2.0 capture** ✓ Transaction id and WAL position per entry ✓ Task, tool-call hash, override use	✓ Fail-safe, append-only ✓ Kill switch not settable by clients	Unit; v2 §2
☑	H10	**Checkpoints & anchors** ✓ Merkle root in the database and in read-only anchor files ✓ On a schedule and on demand ✓ Published anchor format	✓ Copied to the backup target (S3 Object Lock) ✓ Anchors signed (Ed25519, key outside the databases)	Unit; v2 §3, §3b
☑	H11	**fox-verify (independent verifier)** ✓ Checks a live branch or an export ✓ Release binaries for every platform	✓ `--pubkey` checks signatures	Unit; v2 §3
☑	H12	**Blackbox integrity & export** ✓ INTACT / TAMPERED via CLI, REST, MCP ✓ JSON-lines export	→ Streaming for very large ledgers	v2 §3
☑	H13	**Branch from just before a Blackbox entry** ✓ Restore + replay up to the change's transaction ✓ By transaction id or timestamp ✓ CLI, REST, MCP, the Integrity panel, and every row of the Blackbox page	✓ main untouched ✓ Documented: README, the Guide's step 6, and the reference	Unit; v2 §4; VM ui
☑	H14	**Blackbox names & aliases** ✓ `fox blackbox`, `/blackbox` routes, MCP and SDK names	✓ Every original name still works	Unit; v2 §5
☑	H15	**Policy gate (warn / block)** ✓ BBX02 warn / BBX01 block with JSON detail ✓ Blocked attempts recorded ✓ Per-rule `db_admin` override	✓ CLI, REST, MCP, web page; custom rules ✓ Patterns match the running statement ✓ TRUNCATE (its own guardrail, H4)	Unit; v2 §6, §6b
☑	H16	**Agent provenance & execute_change** ✓ Session, task, parent session on every agent change (also through the Gateway DSN) ✓ MCP `execute_change` with policy preview	✓ `fox blackbox sessions`, REST ! Provenance is what the agent says (not verified)	Unit; v2 §7
◐	H17	**Impact analysis** ✓ Dependents (views, foreign keys, indexes, depth) ✓ Other branches that have the object ✓ Policy verdict and risk score	✓ CLI, REST, MCP, inside execute_change ◐ Functions, types, schemas not recognised from SQL	Unit; v2 §8
☑	H18	**Blackbox diff, and promoting a branch's changes** ✓ Fork point, changes only on each side ✓ Objects changed on both ✓ Diff: CLI, REST, MCP ✓ Promotion: a branch's recorded statements, reviewed, then applied to another branch in one transaction	✓ Refused on a conflict (both sides changed the same object), on a statement the target's gate blocks, and when there is nothing to promote ✓ Approving needs the right to manage the target, so an agent cannot approve its own request ✓ Promotion: CLI, REST, MCP and the web Requests page	Unit; v2 §8, §8b

I Import & migration

13 of 13 done

	ID	Feature · sub-features		Tested by
☑	I1	**From Postgres** ✓ Schema and data via pg_dump	✓ Zero-table result reported as an error	Manual; no automated test yet
☑	I2	**From MySQL ≤5.7 / MariaDB** ✓ pgloader with type mapping (multi-arch image)		Manual; no automated test yet
☑	I3	**From MySQL 8.x** ✓ Native mysqldump path (caching_sha2 auth) ✓ Types, NULLs, unicode, PK	→ Other indexes, foreign keys, defaults	Manual; no automated test yet
☑	I4	**From MongoDB** ✓ Collection → typed table, exact name	✓ Nested objects / arrays kept as jsonb	VM §9, §10

	ID	Feature · sub-features		Tested by
☑	I5	**From a .sql dump** ✓ Runs the dump into a new branch ✓ Fails listing every failed statement (instance kept)	✓ Same for Postgres imports (I1) ✓ Automated test	Unit; VM §11
☑	I6	**From JSON / NDJSON** ✓ Columns inferred from top-level keys	✓ An invalid document fails the import, naming its element or line	Unit; VM §10, §11
☑	I7	**From CSV** ✓ Table from the header, exact column names	! Typed columns (all text today)	Manual
☑	I8	**Continuous replication & cutover** ✓ Initial copy + streaming (logical replication) ✓ Cutover keeps data (CLI) ✓ Status and cutover from REST and the Import page	✓ A replicating branch is never auto-suspended ✓ Automated test (VM §5b) and driven in the browser	Unit; VM §5b
☑	I9	**Guard handling during import** ✓ Guardrail paused, recording stays on ✓ Re-armed even after a crash	✓ The target keeps the grants `db_client` needs: preparing it drops and recreates `public`, which had left imported data readable by the import's own superuser and by no gateway client at all	Manual; integration_test.sh §5b
☑	I10	**Live progress (CLI & SSE)** ✓ Live log and progress bar	! psql subprocess output not streamed	Manual
☑	I11	**Import REST endpoints** ✓ From a connection string or an uploaded file ✓ Target names validated (the import creates the branch through branch.Create)	✓ Private, local and container sources for admins only; metadata refused	Manual; unit; VM §1d
☑	I12	**Web Import page** ✓ Database and file panels with live console	✓ No longer claims a SQLite loader that doesn't exist	Manual
☑	I13	**Exact identifier fidelity** ✓ Case kept (`userId` , `leaseAiChats`)	! Field order of JSON sources not kept	Unit; VM §10

J ETL pipelines (experimental)

4 of 4 done

	ID	Feature · sub-features		Tested by
☑	J1	**Pipeline engine** ✓ Extract → raw schema → SQL models → tests, in a fresh branch ✓ `ref()` / `source()` templating → Dependency graph	→ Incremental models → Scheduling ✓ A run replaces only a branch the pipeline made ✓ API sources are connection strings, never server paths	Unit; VM §9
☑	J2	**Data-quality tests** ✓ not_null, unique, accepted_values, row_count_min, custom	✓ Failure → exit 1, data kept	Unit; VM §9
☑	J3	**Stored pipelines & run history** ✓ Saved per user, run over the API, history → Read a run's log	→ Mark runs whose process died	Manual
☑	J4	**Pipeline editor (web)** ✓ Create, edit, run, results, history	→ Confirm before delete	Manual

K APIs, SDKs & agents

6 of 6 done

	ID	Feature · sub-features		Tested by
☑	K1	**Control-plane REST API** ✓ Branches, query, Blackbox, policy, impact, import, pipelines, keys ✓ Versioned paths: `/api/v1/…` reaches the same routes, and `/api/…` keeps working	✓ Exact-origin CORS, branch-name check, body limits, timeouts ✓ Branches owned by their maker; others 404 (owner, admin, or main)	Unit; VM §1; v2 §0–§8; VM §1d
☑	K2	**OpenAPI spec** ✓ Served, Blackbox 2.0 endpoints documented ✓ Matches the code (import fields, status codes, auth routes, /blackbox aliases)	✓ Drift check in CI	Unit (drift check)
☑	K3	**Python SDK** ✓ Branches, query, Blackbox → Import, pipelines, keys, agents ✓ Contract tests against a live engine (nightly sdks suite)	→ Publish to PyPI ✓ Contract tests against a live engine	Manual; VM sdks
☑	K4	**TypeScript SDK** ✓ Same client for Node and browsers ✓ Contract tests against a live engine (nightly sdks suite)	→ Publish to npm ✓ Compiles, and contract tests against a live engine	Manual; VM sdks
☑	K5	**Agent Branch API** ✓ A branch per agent, own non-superuser role ✓ Provenance (task, parent, session) ✓ DSN reachable from the host (gateway-routed, branch-scoped key)	✓ Cap, listing and TTL count suspended branches ✓ Superuser switch only in `--tags insecure` builds ✓ Agents and their keys belong to the caller	Unit; VM §5; v2 §1c, §7

☑	K6	**MCP server** ✓ Branches, run_sql, Blackbox tools ✓ policy_check, execute_change, impact, diff ✓ Requires an API key and acts as that account; a scoped key is held to its branch	✓ Client config & 16-tool reference (docs/mcp.md) ✓ Same ownership rule as the REST API	Unit; v2 §1c–§8

L Web console

11 of 11 done

	ID	Feature · sub-features		Tested by
☑	L1	**Embedded single-origin UI** ✓ Served by the engine at :8080 ✓ Automated UI tests (Playwright, in the nightly ui suite)	✓ One branch-list loader for every selector: retries a dropped request, reports one it cannot load	Manual
☑	L2	**Login & signup** ✓ Log in / sign up tabs, OAuth buttons	✓ Covered by the console's Playwright tests	Manual; VM ui
☑	L3	**Dashboard** ✓ Live tiles ✓ Branch table: create, suspend, resume, delete, copy DSN	✓ Covered by the console's Playwright tests	Manual; VM ui
☑	L4	**SQL console & browser** ✓ Schema sidebar, rows, structure, indexes ✓ Values shown as Postgres writes them (uuid, interval, inet, bytea) ✓ SQL editor ✓ System tables hidden by default, with a show button ✓ Runs as the signed-in user; one-run override switch ✓ Per-rule override for policy blocks ! One statement per run (extended protocol) ✓ Runs a script, not just one statement: a result per statement, and one transaction unless it opens its own ✓ Each result says which statement produced it; labelling is dropped rather than guessed when a split is unsafe	✓ Editor is read-only while a query runs, and ⌘/Ctrl+↵ no longer starts a second one ✓ Workbench layout: fills the window, schema rail folds away, results in tabs, either pane expands ✓ Line numbers, and a syntax error reports its line and column and marks the gutter ✓ Component tests for the console run on every pull request, without a stack ✓ Page heading kept for screen readers after the title block became a toolbar	Manual; API in v2 §6
☑	L5	**Blackbox page** ✓ Entries per branch with badges ✓ Table / risk / date filters, and "Clear filters" ✓ Verify button; a row expands to its statement and session ✓ Live: new entries arrive on their own (3s), marked briefly, pausable; never while older pages are being read	✓ The chain is visible: entry id, its row hash and the previous entry's, each copyable ✓ "Branch from before this change" on the row itself (`main`; explained elsewhere) ✓ Covered by the console's Playwright tests	v2 §5b; browser; VM ui
☑	L6	**API keys page** ✓ Create, copy, list, revoke ✓ A new key is shown inside its connection string (E3's next step)	✓ Covered by the console's Playwright tests	Manual; browser review 21 Sep; VM ui
☑	L7	**Landing, Guide & Docs pages** ✓ Landing, developer guide, reference	✓ Refreshed against the code (https, sslmode, MCP, Blackbox, import routes)	Type-check + build
☑	L8	**Blackbox integrity page** ✓ Verify, checkpoint, export, branch-before ✓ Used signed in; every result matched the CLI	✓ New entries arrive on their own (3s), marked briefly, pausable	Type-check + build; browser review 16 Sep
☑	L9	**Policies page** ✓ Rules, warn/block, custom rules, preview, evaluations ✓ Used signed in; matched the CLI, wrote only to the chosen branch	✓ Non-admin change refused with a readable message ✓ Who can override: list, grant, revoke	Type-check + build; API in v2 §6; browser review 16 Sep
☑	L10	**App sidebar layout** ✓ Every link opens its page, highlighted, with breadcrumb ✓ Collapse persists across a reload; theme toggle persists	✓ No console errors on any page	Type-check + build; browser review 16 Sep; the under-860px drawer needs a manual look
☑	L11	**Design system & FoxByte theme** ✓ Tokens for colour, type, space, radius, elevation and motion; components use no raw values ✓ Ember palette in both themes; filled controls legible (`--accent-ink`)	✓ Logo artwork as the mark, wordmark from brand.json accenting the logo's letter, favicon and touch icon ✓ Console, Blackbox, Policies and API keys re-laid out; one table style ✓ Every page reviewed in both themes; console checked at 375px	Type-check + build; browser review 21 Sep; not yet reviewed against real data

M Build, CI & releases

8 of 9 done

Policy authoring, impact, promotion, export and pipelines gated; reading each stays free
All five moved: `enterprise/{pipeline,impact,promote,anchor,policy}` — ~950 lines, and zero enterprise symbols in the Standard binary
SQL schema split: `ledger_ext`, `provenance` and `datachanges` stay free; `checkpoints`, `policy` and `impact` moved to `enterprise/schema` and are installed per feature
Realtime foundation: opt-in, container settings (byte-identical when off), slot naming and sweeping, the suspend probe, preflight refusals
Realtime decoder: wire format, fan-out, pgoutput decoding — all in `enterprise/realtime`
SSE route on the outer mux, branch-scoped key (`UserForBranchStream`), decoder lifecycle, `realtime enable|disable|tables`, console page
Realtime integration suite (`make integration-realtime`, in the nightly matrix): refusals, the wire format against a real WAL, scoped keys, slot sweeping, teardown, replay via `?since=`, and the WAL budget invalidating a slot

	ID	Feature · sub-features		Tested by

☑	M1	**Makefile targets** ✓ build, vet, test, integration suites ✓ Suites run only in a throwaway test VM (guarded)	✓ release, web, WSL builds, feature-doc (both PDFs) ✓ `integration-sdks`, `integration-ui`	CI
☑	M2	**Linux CI** ✓ Build, vet, test, gofmt ✓ Release script tests, checklist sync check ✓ VM integration suites nightly in CI (one runner per suite)	✓ Release tags gated on them (release.yml nightly-gate) ✓ Secret scanning, govulncheck, npm audit, UI type-check	CI
☑	M3	**Windows CI** ✓ Build, vet, test, Pester, installer encoding	✓ Guard tests read backslash paths, and generated files are pinned to LF (21 Sep)	CI; no end-to-end WSL install test yet
☑	M4	**Releases & GHCR image** ✓ Binaries for 5 platforms + fox-verify ✓ SHA256SUMS merged safely between jobs ✓ Fails unless `fox update`'s files are published	✓ Multi-arch Postgres image on GHCR ✓ Actions pinned by SHA; signed SHA256SUMS; build attestations; SBOM ✓ Run for a real release on GitHub, and verified afterwards	Script tests in CI
☑	M5	**WSL distro & ZFS builds** ✓ Prebuilt distro image ✓ Downloaded and verified by the installer (seen on Windows) ✓ Preloaded image tagged as the engine runs it	✓ Imported on a fresh Windows install; preloaded images loaded ✓ Published zstd-compressed, with the gzip size measured beside it in every build log	Actions artifacts; Pester; Windows run 16 Sep; the zstd unpack is unit-tested only, not run on a real Windows install
☑	M6	**Postgres image** ✓ PostgreSQL 18 + wal-g for a fresh install; one image per supported major (16, 18) ✓ The image follows the data: an install on 16 keeps running 16 after an update ✓ A branch on the wrong major is refused before `docker run`, with the way out ✓ The major lives in one place, and a test holds the Dockerfile, release matrix and Windows preload to it	✓ All three suites pass on PostgreSQL 18.6: 108 + 277 + 51 checks (21 Sep) ✓ A command that moves an install from 16 to 18 (D6), and a portable backup to take first (D5) ✓ pgvector, version-pinned from PGDG for both supported majors — available, and enabled per database with `CREATE EXTENSION vector` ✓ Base image pinned by digest; wal-g checked by SHA-256	Unit; all three suites on 18
☑	M7	**Product name in one file** ✓ brand.json → Go, shell, web and installer blocks, regenerated by `make brand` ✓ Stored names brand-free and frozen: a rename never migrates an install	✓ Retired env prefixes, state directory, VM names and installs still handled ✓ Guards: retired names anywhere, product names in stored SQL, durable names spelt twice ! The sweep is text substitution: review its diff (it over-reached twice)	Unit (brand, gen, oldnames), in CI via go test
☑	M8	**Two editions** ✓ One tree, two binaries: `fox` (Standard, AGPL) and `fox-enterprise` ✓ `enterprise/` has its own commercial LICENSE and `LicenseRef-` headers ✓ The Standard binary contains no paid code — checked with `go tool nm`, not just the source ✓ An Enterprise build with no licence behaves exactly like Standard	✓ Installer `--edition` / `FOX_EDITION`; launcher and VM engine always match ✓ `fox update` stays inside its edition; the release publishes and checks both sets ! Source-available deters, it does not prevent: the check can be removed in breach ! A dependency only the paid code uses still appears in the AGPL module's `go.mod`	Unit (edition, boundary), scripts/test_editions.sh, CI builds both
◐	M9	**Licensing** ✓ Activating from the console: `POST /api/license` and an Account → Licence page — admin only, a forgery refused outright, honoured by this process at once, with the restart and the VM-copy caveats stated rather than hidden ✓ Ed25519 over a canonical payload, with a key id so the key can rotate ✓ `cmd/licensesign`: generate, issue, verify; private key never in CI ✓ Soft machine lock, grace before refusal, and a lapse that never stops a database ✓ Host fingerprint: hashed, read on the host not in the VM, failure means unknown	✓ `~/.fox/license.json` (0600, atomic) and `fox license activate|show|rebind|remove` ✓ The engine inside the VM is given a copy (macOS/Windows); no-op on Linux ✓ Security-log records: `license.{activated,rebound,lapsed,removed}`, written by the engine at start-up ✓ `GET /api/license` (state for everyone, customer and binding for admins) ✓ The console's notice: silent when active, silent in Standard, dismissible only while it still unlocks ✓ Anchors gated: writing is Enterprise, checking (`integrity`, `fox-verify`, `anchor-key`) and the security log's anchors stay free	internal/license

N Realtime change feed

1 of 1 done

ID	Item · scope	Tested by

N1 Realtime change feed

enterprise/realtime, scripts/integration_realtime.sh

- ✓ Readiness as a verdict, not a refusal: `realtime doctor` classifies every table, `realtime prepare` makes the changes and prints them first
- ✓ The cost ladder — primary key, then a unique index as the identity (same price, no schema change), then inserts-only, and `REPLICA IDENTITY FULL` last; `--all` never applies a costly fix
- ✓ Only application tables stream: not `bb`, not Postgres's, not an extension's — and the application's own schemas now do
- ✓ Opt-in: `fox realtime setup --yes` says what it will restart; with the feed off, a primary's arguments are byte-identical to before and a branch gets none
- ✓ Durable replay through `?since=<commit_lsn>`, bounded by `max_slot_wal_keep_size`; past it the subscriber is told to `resync` rather than left waiting
- ✓ One decoder per branch in the control plane, started on the first subscriber and stopped after the last; it wakes a suspended branch
- ✓ Refusals that hold: row-level security (no override), no primary key (and `UPDATE` still works afterwards), anything outside `public`, the Blackbox's own tables, anything `db_client` cannot read
- ✓ Wire format: values as text, identity always, `old` only when sent, `changed` only under FULL, unchanged-TOAST named rather than nulled
- ✓ Both answers to "what was the row that is gone", in one capture against a live WAL: a delete under the default identity carries the key alone, and under FULL the whole old row — where every column is part of the identity too
- ✓ SSE on the outer mux so a branch-scoped key reaches its own branch and nothing else; somebody else's branch is 404, not 403
- ✓ Slots named, listed, accounted for and swept only once Postgres has marked them lost; `fox check` warns on one nothing is draining
- ✓ The reaper leaves a subscribed branch alone (asked of Postgres, not of memory), and a resumed branch gets a fresh idle window
- ✓ A failover keeps the feed: the standby carries the same arguments, `setup` restarts one that predates it, and the feed follows `main` onto the promoted standby
- ✓ A subscriber's **position** survives the failover too (HA plan phase 4): failover-aware slots synchronised to the standby through its own physical slot, so a change written before the promotion is delivered after it instead of costing a refetch — gated on the PostgreSQL major, since the settings are fatal on 16
- ✓ …and the limit is stated rather than implied: PostgreSQL copies a slot to the standby only while it is being consumed, so a continuously-read subscriber keeps its place through a promotion and one that read once and left is told to resync, as it was before
- ✓ Neighbours unaffected: a continuous import runs under logical decoding and is itself decodable; backups, verify, failover and failback all pass
- ✓ `setup`, `teardown`, `status` and `slots` stay in the free build, so a downgrade can still undo it
- ! Console and REST only this release; the published SDKs get the feed once the wire format has survived real use
- ! No per-subscriber row filters, which is why an RLS table is refused rather than filtered
- ✓ Published clients subscribe: `clients/typescript` and `clients/python`, dependency-free, with whole-transaction delivery, resume only at a commit boundary, reconnection, and an `apply` that leaves an unchanged TOASTed column alone
- ✓ 41 client unit tests (18 TypeScript via `node --test`, 23 Python via `unittest`) plus contract tests driving both against a live engine with a real `rtk_` key
- ✓ Transaction framing (`?transactions=1`): `begin` / `commit` around each transaction, every change carrying its `xid` and the transaction's `commit_lsn` as the resume boundary, with the record's own position as `lsn`
- ✓ Off by default and dropped per subscriber, so an unframed client is unaffected; an empty transaction produces no frame; a value other than 1 or 0 is refused rather than assumed
- ✓ What staying warm costs: `realtime activity`, an API route and a console panel — warm-since from the container, work from `pg_stat_database` sampled on a timer, and the bookmarks' held WAL against the budget
- ✓ Transactions rather than queries, because that is what Postgres counts without `pg_stat_statements`; and five cases where subtracting two readings would lie are each answered with a note instead of a figure
- ✓ A cap of 8 subscribers per branch (`FOX_REALTIME_MAX_SUBSCRIBERS`), refused with the count, so a client reconnecting on a bug cannot add streams until something runs out
- ✓ Console: Tables, Connecting an application, and Feed — verdicts become buttons, and the one fix with an ongoing cost asks first with the measured figure in the dialog
- ✓ Console routes on the inner `/api/` mux (`enable`, `disable`, `prepare`, realtime keys), all `Manage` by prefix; reading verdicts reuses the front door so the console cannot drift from what an application sees
- ✓ Covered in a browser: `web/tests/realtime.spec.ts` classifies a real branch, applies a free fix, declines a costly one, publishes and unpublishes a table, and mints then revokes a key
- ✓ Front door: `/realtime/v1/branches/{name}/{hello,tables,stream}` on the console's port, and a `fox-realtime://` connection string that keeps the key in userinfo, never in a URL
- ✓ A `realtime` key kind (`rtk_`, `fox realtime key create|ls|revoke`): streams one branch, refused at the control plane and **refused at the Gateway by kind** — asserted against a real psql connection
- ✓ Only an application's tables over HTTP: one shared `realtime.Application()` withholds `bb`, Postgres and extension-owned tables and reports how many — the first version served the Blackbox's shape to a stream-only key
- ✓ Additive: the original `/api/branches/{name}/realtime` route is unchanged, and every key issued before kinds existed keeps the empty kind and its old behaviour (migration covered from a pre-`kind` store)
- ! A delete under the default replica identity carries the primary key and nothing else

Z Not started (roadmap)

7 items

Planned or discussed, nothing built yet. When work starts, move the row into its area with the next id there.

	ID	Item · scope	Related
☐	–	**Multi-tenant projects** ☐ Projects / organisations, and roles within them ✓ Per-branch permissions: owner or admin, on every branch-scoped route (G2 of the audit)	G1, H6
☐	–	**Automatic HA failover** ☐ Health detection, fencing ☐ Multi-host	D4
☐	–	**Pipelines: scheduling, incremental / CDC extract, DAG view**	J1
☐	–	**More import sources: Cassandra, DynamoDB**	I1–I8
☑	–	**Release signatures** — done 22 Sep 2026	A9, M4
☐	–	**Hosted cloud tier**	—
☐	–	**Networked storage disaggregation** (README roadmap; see the storage engine note on page 1)	C1, D1

Out of scope by decision

A custom storage engine (PostgreSQL's own engine is used, for native transaction speed), sharding, Raft / cross-node transactions, multi-region, HTAP.