

Skill Week-7

Session-13

Task 1: To parse Input Redirection, Open Files, Redirect stdin, Handle Missing Files, Restore Streams, Test File Inputs

```
nirvighna@DESKTOP-VS57D2I:~$ nano session13_task1.c
nirvighna@DESKTOP-VS57D2I:~$ gcc session13_task1.c -o session13_task1
nirvighna@DESKTOP-VS57D2I:~$ echo -e "Line 1\nLine 2\nLine 3\nLine 4" > input.txt
nirvighna@DESKTOP-VS57D2I:~$ cat input.txt
Line 1
Line 2
Line 3
Line 4
nirvighna@DESKTOP-VS57D2I:~$ ./session13_task1
Session 11 - Input Redirection
Enter command with input redirection:
myshell> wc < input.txt

Command      : wc
Input file   : input.txt
Redirection  : stdin < file

Input file opened successfully.
Executing command with redirected stdin...
4

Input redirection completed successfully.
File descriptor cleaned up.
Parent process restored normal stdin.
nirvighna@DESKTOP-VS57D2I:~$ |
```

```

GNU nano 8.7.1
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <fcntl.h>
#include <sys/wait.h>

#define MAX_INPUT 200

int main()
{
    char input[MAX_INPUT];
    char command[100];
    char filename[100];

    printf("Session 11 - Input Redirection\n");
    printf("Enter command with input redirection:\n");
    printf("myshell> ");

    if (fgets(input, sizeof(input), stdin) == NULL)
        return 1;

    input[strcspn(input, "\n")] = '\0';

    /* Parse input redirection */
    char *redirect = strchr(input, '<');

    if (redirect == NULL)
    {
        printf("No input redirection found.\n");
        return 1;
    }

    *redirect = '\0';

    strcpy(command, input);

    /* Remove spaces before filename */
    char *file = redirect + 1;

    while (*file == ' ' || *file == '\t')
        file++;

    strcpy(filename, file);

    if (strlen(filename) == 0)
    {
        printf("Error: Missing input file.\n");
        return 1;
    }

    printf("\nCommand      : %s\n", command);

```

```

GNU nano 8.7.1
printf("\nCommand      : %s\n", command);
printf("Input file      : %s\n", filename);
printf("Redirection      : stdin < file\n");

/* Open input file */
int fd = open(filename, O_RDONLY);

if (fd == -1)
{
    perror("Error opening input file");
    return 1;
}

printf("\nInput file opened successfully.\n");

pid_t pid = fork();

if (pid < 0)
{
    perror("fork failed");
    close(fd);
    return 1;
}

if (pid == 0)
{
    /* Redirect stdin to file */
    if (dup2(fd, STDIN_FILENO) == -1)
    {
        perror("dup2 failed");
        close(fd);
        exit(EXIT_FAILURE);
    }

    close(fd);

    printf("Executing command with redirected stdin...\n");

    execlp("wc", "wc", "-l", NULL);

    perror("exec failed");
    exit(EXIT_FAILURE);
}

/* Parent closes file descriptor */
close(fd);

/* Wait for child */
waitpid(pid, NULL, 0);

printf("\nInput redirection completed successfully.\n");
printf("File descriptor cleaned up.\n");
printf("Parent process restored normal stdin.\n");

return 0;
}

```

Task 2: To Parse Output Redirection, Create Output Files, Redirect stdout, Handle Permissions, Verify Output Data, Test Redirection

```
nirvighna@DESKTOP-VS57D2I:~$ nano session13_task2.c
nirvighna@DESKTOP-VS57D2I:~$ gcc session13_task2.c -o session13_task2
nirvighna@DESKTOP-VS57D2I:~$ ./session13_task2
```

Session 13 - Output Redirection

Enter command with output redirection:

```
myshell> echo hello > output.txt
```

```
Command       : echo hello
Output file    : output.txt
Redirection    : stdout > file
```

Output file opened successfully.

Output redirection completed successfully.

File descriptor cleaned up.

Parent process restored normal stdout.

Verified output data:

Output redirected successfully

Output verification completed successfully.

```
nirvighna@DESKTOP-VS57D2I:~$
```

```
GNU nano 8.7.1
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <fcntl.h>
#include <sys/types.h>
#include <sys/wait.h>

#define MAX_INPUT 200

int main()
{
    char input[MAX_INPUT];
    char command[100];
    char filename[100];

    printf("Session 13 - Output Redirection\n");
    printf("Enter command with output redirection:\n");
    printf("myshell> ");

    if (fgets(input, sizeof(input), stdin) == NULL)
        return 1;

    input[strcspn(input, "\n")] = '\0';

    /* Find output redirection symbol */
    char *redirect = strchr(input, '>');

    if (redirect == NULL)
    {
        printf("No output redirection found.\n");
        return 1;
    }

    *redirect = '\0';

    strcpy(command, input);

    /* Remove spaces before filename */
    char *file = redirect + 1;

    while (*file == ' ' || *file == '\t')
        file++;

    strcpy(filename, file);
}
```

GNU nano 8.7.1

```
if (strlen(filename) == 0)
{
    printf("Error: Missing output file.\n");
    return 1;
}

printf("\nCommand      : %s\n", command);
printf("Output file   : %s\n", filename);
printf("Redirection    : stdout > file\n");

/* Create or truncate output file */
int fd = open(filename, O_WRONLY | O_CREAT | O_TRUNC, 0644);

if (fd == -1)
{
    perror("Error opening output file");
    return 1;
}

printf("\nOutput file opened successfully.\n");

pid_t pid = fork();

if (pid < 0)
{
    perror("fork failed");
    close(fd);
    return 1;
}

if (pid == 0)
{
    /* Redirect stdout to the output file */
    if (dup2(fd, STDOUT_FILENO) == -1)
    {
        perror("dup2 failed");
        close(fd);
        exit(EXIT_FAILURE);
    }

    close(fd);

    /* Execute command */
    execlp("echo", "echo", "Output redirected successfully", NULL);

    perror("exec failed");
}
```

```

        perror("exec failed");
        exit(EXIT_FAILURE);
    }

    /* Parent closes its copy of the descriptor */
    close(fd);

    /* Wait for child */
    waitpid(pid, NULL, 0);

    printf("\nOutput redirection completed successfully.\n");
    printf("File descriptor cleaned up.\n");
    printf("Parent process restored normal stdout.\n");

    /* Verify output data */
    FILE *fp = fopen(filename, "r");

    if (fp == NULL)
    {
        perror("Error verifying output file");
        return 1;
    }

    char buffer[200];

    printf("\nVerified output data:\n");

    while (fgets(buffer, sizeof(buffer), fp) != NULL)
    {
        printf("%s", buffer);
    }

    fclose(fp);

    printf("\nOutput verification completed successfully.\n");

    return 0;
}

```

Session-14

Task 1: To Parse Append Operator, Open Files in Append Mode, Redirect Streams, Preserve Existing Data, Validate Appends, Test Scenarios

```

nirvighna@DESKTOP-VS57D2I:~$ nano session14_task1.c
nirvighna@DESKTOP-VS57D2I:~$ gcc session14_task1.c -o session14_task1
nirvighna@DESKTOP-VS57D2I:~$ ./session14_task1
Session 13 - Append Redirection
Enter command with append redirection:
myshell> echo hello >> output.txt

Command      : echo hello
Output file   : output.txt
Redirection   : stdout >> file

Output file opened in append mode.

Append operation completed successfully.
Existing data was preserved.
File descriptor cleaned up.

File contents after append:
Output redirected successfully
New data appended successfully

Append validation completed successfully.
nirvighna@DESKTOP-VS57D2I:~$ |

```

GNU nano 8.7.1

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <fcntl.h>
#include <sys/types.h>
#include <sys/wait.h>

#define MAX_INPUT 200

int main()
{
    char input[MAX_INPUT];
    char command[100];
    char filename[100];

    printf("Session 13 - Append Redirection\n");
    printf("Enter command with append redirection:\n");
    printf("myshell> ");

    if (fgets(input, sizeof(input), stdin) == NULL)
        return 1;

    input[strcspn(input, "\n")] = '\0';

    /* Find append operator */
    char *redirect = strstr(input, ">>");

    if (redirect == NULL)
    {
        printf("No append redirection found.\n");
        return 1;
    }

    *redirect = '\0';

    strcpy(command, input);

    /* Get filename */
    char *file = redirect + 2;

    while (*file == ' ' || *file == '\t')
        file++;

    strcpy(filename, file);

    if (strlen(filename) == 0)
    {
        printf("Error: Missing output file.\n");
        return 1;
    }
}
```

GNU nano 8.7.1

```
printf("\nCommand      : %s\n", command);
printf("Output file   : %s\n", filename);
printf("Redirection    : stdout >> file\n");

/* Open file in append mode */
int fd = open(filename, O_WRONLY | O_CREAT | O_APPEND, 0644);

if (fd == -1)
{
    perror("Error opening output file");
    return 1;
}

printf("\nOutput file opened in append mode.\n");

pid_t pid = fork();

if (pid < 0)
{
    perror("fork failed");
    close(fd);
    return 1;
}

if (pid == 0)
{
    /* Redirect stdout to file */
    if (dup2(fd, STDOUT_FILENO) == -1)
    {
        perror("dup2 failed");
        close(fd);
        exit(EXIT_FAILURE);
    }

    close(fd);

    /* Execute command */
    execlp("echo", "echo",
           "New data appended successfully", NULL);

    perror("exec failed");
    exit(EXIT_FAILURE);
}

/* Parent closes descriptor */
close(fd);

/* Wait for child */
waitpid(pid, NULL, 0);

printf("\nAppend operation completed successfully.\n");
printf("Existing data was preserved.\n");
```

```

waitpid(pid, NULL, 0);

printf("\nAppend operation completed successfully.\n");
printf("Existing data was preserved.\n");
printf("File descriptor cleaned up.\n");

/* Verify appended data */
FILE *fp = fopen(filename, "r");

if (fp == NULL)
{
    perror("Error verifying output file");
    return 1;
}

char buffer[200];

printf("\nFile contents after append:\n");

while (fgets(buffer, sizeof(buffer), fp) != NULL)
{
    printf("%s", buffer);
}

fclose(fp);

printf("\nAppend validation completed successfully.\n");

return 0;
}

```

Task 2: TO parse stderr Redirection, Redirect Error Streams, Capture Error Output, Verify File Contents, Handle Failures, Test Error Cases

```

nirvighna@DESKTOP-VS57D2I:~$ nano session14_task2.c
nirvighna@DESKTOP-VS57D2I:~$ gcc session14_task2.c -o session14_task2
nirvighna@DESKTOP-VS57D2I:~$ ./session14_task2
Session 13 - stderr Redirection
Enter command with error redirection:
myshell> ls /nonexistent_directory 2> error.txt

Command       : ls /nonexistent_directory
Error file     : error.txt
Redirection    : stderr 2> file

Error output file opened successfully.

Error stream redirection completed.
Error output captured in file.
Child exit status: 2

Captured error output:
ls: cannot access '/nonexistent_directory': No such file or directory

stderr redirection validation completed successfully.
nirvighna@DESKTOP-VS57D2I:~$ :~$ |

```

```

GNU nano 8.7.1
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <fcntl.h>
#include <sys/types.h>
#include <sys/wait.h>

#define MAX_INPUT 200

int main()
{
    char input[MAX_INPUT];
    char command[100];
    char filename[100];

    printf("Session 13 - stderr Redirection\n");
    printf("Enter command with error redirection:\n");
    printf("myshell> ");

    if (fgets(input, sizeof(input), stdin) == NULL)
        return 1;

    input[strcspn(input, "\n")] = '\0';

    /* Find stderr redirection operator */
    char *redirect = strstr(input, "2>");

    if (redirect == NULL)
    {
        printf("No stderr redirection found.\n");
        return 1;
    }

    *redirect = '\0';

    strcpy(command, input);

    /* Get output filename */
    char *file = redirect + 2;

    while (*file == ' ' || *file == '\t')
        file++;

    strcpy(filename, file);

    if (strlen(filename) == 0)
    {
        printf("Error: Missing error output file.\n");
        return 1;
    }
}

```

```
printf("\nCommand      : %s\n", command);
printf("Error file     : %s\n", filename);
printf("Redirection    : stderr 2> file\n");

/* Open file for stderr */
int fd = open(filename, O_WRONLY | O_CREAT | O_TRUNC, 0644);

if (fd == -1)
{
    perror("Error opening error file");
    return 1;
}

printf("\nError output file opened successfully.\n");

pid_t pid = fork();

if (pid < 0)
{
    perror("fork failed");
    close(fd);
    return 1;
}

if (pid == 0)
{
    /* Redirect stderr to file */
    if (dup2(fd, STDERR_FILENO) == -1)
    {
        perror("dup2 failed");
        close(fd);
        exit(EXIT_FAILURE);
    }

    close(fd);

    /* Generate an error intentionally */
    execlp("ls", "ls", "/nonexistent_directory", NULL);

    perror("exec failed");
    exit(EXIT_FAILURE);
}

/* Parent closes descriptor */
close(fd);

/* Wait for child */
int status;
waitpid(pid, &status, 0);

| printf("\nError stream redirection completed.\n");
```

```
printf("\nError stream redirection completed.\n");
printf("Error output captured in file.\n");

if (WIFEXITED(status))
{
    printf("Child exit status: %d\n",
           WEXITSTATUS(status));
}

/* Verify file contents */
FILE *fp = fopen(filename, "r");

if (fp == NULL)
{
    perror("Error reading error file");
    return 1;
}

char buffer[300];

printf("\nCaptured error output:\n");

while (fgets(buffer, sizeof(buffer), fp) != NULL)
{
    printf("%s", buffer);
}

fclose(fp);

printf("\n\nstderr redirection validation completed successfully.\n");

return 0;
}
```