

Week-3 skill

Session-5

Task-1

TO Apply Single Quotes, Preserve Literal Content, Ignore Variable Expansion, Store Quoted Strings,
Validate Parsing Results, Test Edge Cases

```
pavani@DESKTOP-38OLEIN: ~/ossp
GNU nano 8.7.1 task5.c *
#include <stdio.h>
#include <string.h>

#define MAX_INPUT 500
#define MAX_OUTPUT 500

void parseSingleQuotes(char *input, char *output) {
    int i = 0;
    int j = 0;
    int inSingleQuote = 0;

    while (input[i] != '\0') {

        if (input[i] == '\\') {
            inSingleQuote = !inSingleQuote;
            i++;
            continue;
        }

        output[j++] = input[i];
        i++;
    }

    output[j] = '\0';
}

int validateQuotes(char *input) {
    int singleQuoteCount = 0;

    for (int i = 0; input[i] != '\0'; i++) {
        if (input[i] == '\\') {
            singleQuoteCount++;
        }
    }

    if (singleQuoteCount % 2 != 0) {
        return 0;
    }

    return 1;
}

int main() {

    char input[MAX_INPUT];
    char output[MAX_OUTPUT];

    printf("=====\n");
```

OUTPUT:

```
Exiting shell...
lenovo@Manya:~$ nano task1.c
lenovo@Manya:~$ gcc task1.c -o task1
lenovo@Manya:~$ ./task1
Enter command: echo 'Hello World'
Parsed output: echo Hello World
lenovo@Manya:~$ ./task1
Enter command: echo '$HOME'
Parsed output: echo $HOME
lenovo@Manya:~$ ./task1
Enter command: echo 'Hello
Error: unmatched single quote
lenovo@Manya:~$ |
```

Report: In this task, I implemented handling of single quotes in a shell command using C. The text inside single quotes was treated as literal content, so spaces and special characters were preserved. Variable names such as \$HOME were not expanded. The program also checked whether the single quotes were properly closed and displayed an error for unmatched quotes. Different inputs were tested to verify the parsing results.

Task-2

To Apply Double Quotes, Preserve Spaces, Allow Variable Expansion, Parse Nested Tokens, Validate Outputs, Test Quoted Commands

pavani@DESKTOP-38OLEIN: ~/ossp

GNU nano 8.7.1

task6.c *

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <ctype.h>

#define MAX_INPUT 500
#define MAX_OUTPUT 1000

/* Check whether double quotes are balanced */
int validateQuotes(char *input) {
    int count = 0;

    for (int i = 0; input[i] != '\0'; i++) {
        if (input[i] == '"')
            count++;
    }

    return count % 2 == 0;
}

/* Expand environment variables */
void expandVariable(char *input, int *i, char *output, int *j) {
    char variable[100];
    int k = 0;

    (*i)++; // Skip $

    while (input[*i] != '\0' &&
           (isalnum(input[*i]) || input[*i] == '_')) {
        if (k < 99)
            variable[k++] = input[*i];

        (*i)++;
    }

    variable[k] = '\0';

    char *value = getenv(variable);

    if (value != NULL) {
        strcpy(&output[*j], value);
        *j += strlen(value);
    } else {
        output[(*j)++] = '$';
    }
}
```

OUTPUT:

```
lenovo@Manya:~$ nano task2.c
lenovo@Manya:~$ gcc task2.c -o task2
lenovo@Manya:~$ ./task2
Enter command: echo "Hello World"
Parsed output: echo Hello World
lenovo@Manya:~$ ./task2
Enter command: echo "Hello $USER"
Parsed output: echo Hello lenovo
lenovo@Manya:~$ ./task2
Enter command: echo "Home is $HOME"
Parsed output: echo Home is /home/lenovo
lenovo@Manya:~$ ./task2
Enter command: echo "Hello
Error: unmatched double quote
lenovo@Manya:~$ |
```

Report: In this task, I implemented double quote handling in C. Double quotes were used to preserve spaces within a command while allowing environment variables such as \$USER and \$HOME to be expanded. The program checked for unmatched double quotes and displayed the parsed output. Different quoted commands were tested to verify that spaces and variables were handled correctly.

Session-6

Task-1

To Create Process Escape Sequences, Handle Escaped Spaces, Escape Special Symbols, Preserve Characters, Validate Parser Output, Test Complex Inputs

pavani@DESKTOP-38OLEIN: ~/ossp

GNU nano 8.7.1

task7.c *

```
#include <stdio.h>
#include <string.h>

#define MAX_INPUT 500
#define MAX_OUTPUT 500

void parseEscapes(char *input, char *output) {
    int i = 0;
    int j = 0;

    while (input[i] != '\0') {

        if (input[i] == '\\') {
            i++;

            if (input[i] != '\0') {
                output[j++] = input[i];
                i++;
            }
        } else {
            output[j++] = input[i];
            i++;
        }
    }

    output[j] = '\0';
}

int main() {
    char input[MAX_INPUT];
    char output[MAX_OUTPUT];

    printf("=====\n");
    printf("    ESCAPE SEQUENCE PARSER\n");
    printf("=====\n");

    printf("\nEnter a command:\n");
    printf("shell> ");

    fgets(input, MAX_INPUT, stdin);

    input[strcspn(input, "\n")] = '\0';

    parseEscapes(input, output);

    printf("\nOriginal Input : %s\n", input);
    printf("Parsed Output  : %s\n", output);
}
```

```
lenovo@Manya:~$ nano task3.c
lenovo@Manya:~$ gcc task3.c -o task3
lenovo@Manya:~$ ./task3
Enter command: Hello\World
Parsed output: HelloWorld
lenovo@Manya:~$ ./task3
Enter command: Hello\!World
Parsed output: Hello!World
lenovo@Manya:~$ ./task3
Enter command: Hello\$HOME
Parsed output: Hello$HOME
lenovo@Manya:~$ |
```

OUTPUT:

Report: In this task, I implemented escape sequence handling using the backslash character. Escaped spaces and special characters were processed so that they were treated as normal characters. The backslash was removed during parsing while the escaped character was preserved. Different inputs containing spaces, special symbols, and variables were tested to check the parser output.

Task-2: To Create Child Processes, Execute Programs, Handle Execution Errors, Pass Arguments, Manage Parent Process, Test Command Launching

pavani@DESKTOP-38OLEIN: ~/ossp

GNU nano 8.7.1

task8.c *

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/wait.h>

int main() {
    pid_t pid;
    int status;

    printf("=====\n");
    printf("    PROCESS CREATION AND EXECUTION\n");
    printf("=====\n");

    printf("\nParent process started.");
    printf("\nParent PID: %d\n", getpid());

    /* Create child process */
    pid = fork();

    if (pid < 0) {
        perror("fork failed");
        return 1;
    }

    /* Child process */
    if (pid == 0) {

        printf("\nChild process created.");
        printf("\nChild PID: %d\n", getpid());

        printf("Executing: ls -l\n\n");

        /* Execute program with arguments */
        execlp("ls", "ls", "-l", NULL);

        /* This executes only if exec fails */
        perror("exec failed");
        exit(1);
    }

    /* Parent process */
    else {

        printf("\nParent is waiting for child...\n");

        if (waitpid(pid, &status, 0) == -1) {
            perror("waitpid failed");
            return 1;
        }
    }
}
```



```

pavani@DESKTOP-38OLEIN: ~/ossp

Escape sequences were processed successfully.
pavani@DESKTOP-38OLEIN:~/ossp$ nano task8.c
pavani@DESKTOP-38OLEIN:~/ossp$ gcc -Wall task8.c -o task8
pavani@DESKTOP-38OLEIN:~/ossp$ ./task8
=====
PROCESS CREATION AND EXECUTION
=====

Parent process started.
Parent PID: 925

Parent is waiting for child...

Child process created.
Child PID: 926
Executing: ls -l

total 248
-rw-r--r-- 1 pavani pavani 0 Aug 4 05:07 LICENSE
-rw-r--r-- 1 pavani pavani 0 Aug 4 05:07 Makefile
-rw-r--r-- 1 pavani pavani 0 Aug 4 05:07 README.md
drwxr-xr-x 2 pavani pavani 4096 Aug 4 05:09 assets
drwxr-xr-x 2 pavani pavani 4096 Aug 4 05:07 bin
drwxr-xr-x 2 pavani pavani 4096 Aug 4 05:08 docs
-rwxr-xr-x 1 pavani pavani 16088 Aug 4 05:31 fork_example
-rw-r--r-- 1 pavani pavani 443 Aug 4 05:36 fork_example.c
-rwxr-xr-x 1 pavani pavani 16040 Aug 4 05:34 fork_exec
-rw-r--r-- 1 pavani pavani 389 Aug 4 05:34 fork_exec.c
drwxr-xr-x 2 pavani pavani 4096 Aug 4 05:08 include
drwxr-xr-x 2 pavani pavani 4096 Aug 4 05:07 obj
drwxr-xr-x 2 pavani pavani 4096 Aug 4 05:08 scripts
drwxr-xr-x 2 pavani pavani 4096 Aug 4 05:07 src
-rwxr-xr-x 1 pavani pavani 19072 Aug 12 08:46 task2
-rw-r--r-- 1 pavani pavani 3976 Aug 12 08:46 task2.c
-rwxr-xr-x 1 pavani pavani 16448 Aug 12 08:50 task3
-rw-r--r-- 1 pavani pavani 5425 Aug 12 08:50 task3.c
-rwxr-xr-x 1 pavani pavani 26872 Aug 12 08:53 task4
-rw-r--r-- 1 pavani pavani 9401 Aug 12 08:53 task4.c
-rwxr-xr-x 1 pavani pavani 16256 Aug 12 09:09 task5
-rw-r--r-- 1 pavani pavani 1527 Aug 12 09:09 task5.c
-rwxr-xr-x 1 pavani pavani 16472 Aug 12 09:12 task6
-rw-r--r-- 1 pavani pavani 2349 Aug 12 09:12 task6.c
-rwxr-xr-x 1 pavani pavani 16208 Aug 12 09:14 task7
-rw-r--r-- 1 pavani pavani 1041 Aug 12 09:14 task7.c
-rwxr-xr-x 1 pavani pavani 16304 Aug 12 09:17 task8
-rw-r--r-- 1 pavani pavani 1359 Aug 12 09:17 task8.c
drwxr-xr-x 2 pavani pavani 4096 Aug 4 05:08 tests

Child exited with status: 0
Parent process completed.
pavani@DESKTOP-38OLEIN:~/ossp$

```

OUTPUT: pavani@DESKTOP-38OLEIN:~/ossp\$

Report: In this task, I implemented process creation and program execution using fork(), exec() and waitpid(). The parent process created a child process, and the child executed the ls command with

arguments using `execlp()`. The parent waited for the child process to finish and checked its exit status. Error handling was also implemented for cases where the command could not be executed. The program successfully demonstrated process creation, execution, argument passing, and parent-child process management.

pavani@DESKTOP-38OLEIN: ~/ossp

Escape sequences were processed successfully.

pavani@DESKTOP-38OLEIN:~/ossp\$ nano task8.c

pavani@DESKTOP-38OLEIN:~/ossp\$ gcc -Wall task8.c -o task8

pavani@DESKTOP-38OLEIN:~/ossp\$./task8

```
=====
PROCESS CREATION AND EXECUTION
=====
```

Parent process started.

Parent PID: 925

Parent is waiting for child...

Child process created.

Child PID: 926

Executing: ls -l

total 248

```
-rw-r--r-- 1 pavani pavani    0 Aug  4 05:07 LICENSE
-rw-r--r-- 1 pavani pavani    0 Aug  4 05:07 Makefile
-rw-r--r-- 1 pavani pavani    0 Aug  4 05:07 README.md
drwxr-xr-x 2 pavani pavani 4096 Aug  4 05:09 assets
drwxr-xr-x 2 pavani pavani 4096 Aug  4 05:07 bin
drwxr-xr-x 2 pavani pavani 4096 Aug  4 05:08 docs
-rwxr-xr-x 1 pavani pavani 16088 Aug  4 05:31 fork_example
-rw-r--r-- 1 pavani pavani   443 Aug  4 05:36 fork_example.c
-rwxr-xr-x 1 pavani pavani 16040 Aug  4 05:34 fork_exec
-rw-r--r-- 1 pavani pavani   389 Aug  4 05:34 fork_exec.c
drwxr-xr-x 2 pavani pavani 4096 Aug  4 05:08 include
drwxr-xr-x 2 pavani pavani 4096 Aug  4 05:07 obj
drwxr-xr-x 2 pavani pavani 4096 Aug  4 05:08 scripts
drwxr-xr-x 2 pavani pavani 4096 Aug  4 05:07 src
-rwxr-xr-x 1 pavani pavani 19072 Aug 12 08:46 task2
-rw-r--r-- 1 pavani pavani   396 Aug 12 08:46 task2.c
-rwxr-xr-x 1 pavani pavani 16448 Aug 12 08:50 task3
-rw-r--r-- 1 pavani pavani   5425 Aug 12 08:50 task3.c
-rwxr-xr-x 1 pavani pavani 26872 Aug 12 08:53 task4
-rw-r--r-- 1 pavani pavani   9401 Aug 12 08:53 task4.c
-rwxr-xr-x 1 pavani pavani 16256 Aug 12 09:09 task5
-rw-r--r-- 1 pavani pavani   1527 Aug 12 09:09 task5.c
-rwxr-xr-x 1 pavani pavani 16472 Aug 12 09:12 task6
-rw-r--r-- 1 pavani pavani   2349 Aug 12 09:12 task6.c
-rwxr-xr-x 1 pavani pavani 16208 Aug 12 09:14 task7
-rw-r--r-- 1 pavani pavani   1041 Aug 12 09:14 task7.c
-rwxr-xr-x 1 pavani pavani 16304 Aug 12 09:17 task8
-rw-r--r-- 1 pavani pavani   1359 Aug 12 09:17 task8.c
drwxr-xr-x 2 pavani pavani 4096 Aug  4 05:08 tests
```

Child exited with status: 0

Parent process completed.

pavani@DESKTOP-38OLEIN:~/ossp\$