

Gouki Scheme: An embedded Scheme implementation for Async Rust

Matthew Plant
maplant@protonmail.com

Abstract

GoukiScheme is the first-of-its-kind JIT compiler for the R6RS dialect of Scheme that supports call-with-current-continuation while being embeddable within a compiled language that supports async: Rust.

ACM Reference Format:

Matthew Plant. 2025. Gouki Scheme: An embedded Scheme implementation for Async Rust. In *Proceedings of ACM Conference (Conference'17)*. ACM, New York, NY, USA, 6 pages. <https://doi.org/10.1145/nnnnnnnn.nnnnnnnn>

1 Introduction

Over the last decade Rust has become an increasingly popular choice for systems programming. Since the introduction of async runtimes to the Rust language, async Rust programs have also become increasingly popular for writing highly IO bound applications such as web servers. While Rust is extremely performant for such applications, async Rust applications tend to be difficult to develop and debug with. Part of the problem is long compilation times; Rust applications must be stopped, rebuilt, and restarted, extending development time and reducing the ability for developers to iterate.

Glue code written in a dynamic language has long been a solution for enabling rapid prototyping and interoperability in a language with long build times. Under this model, the performance critical code that does not often need to be rebuilt is written in the slower compiled language, while a dynamic perhaps interpreted language is embedded into the built to allow for gluing components together without the need for slow rebuilds. Changes to the glue code can be seen just be re-loading the applications, or perhaps a hot reloading mechanism can bring them into the application simply by saving to a file. In either case, iteration speeds are improved dramatically.

Unpublished working draft. Not for distribution.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, to republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Conference'17, July 2017, Washington, DC, USA

© 2025 Association for Computing Machinery.

ACM ISBN 978-x-xxxx-xxxx-x/YY/MM...\$15.00

<https://doi.org/10.1145/nnnnnnnn.nnnnnnnn>

2025-07-05 23:25. Page 1 of 1-6.

Another advantage of embedding a dynamic language in an application is that the application can provide a Read-Eval-Print-Loop, or REPL. Interactive prompts can expand the debugging capabilities of a application by allowing for inspection of the application while it is live. The application can be debugged, inspected, and orchestrated as a plastic system rather than a rigid daemon that can only be started, stopped or interacted with in small fixed languages.

Scheme has shown success as a embedded dynamic language, but its use has been limited to synchronous (but perhaps multithreaded) applications. Scheme implementations exist for embedding within Rust, but they are limited to running sync Rust code and cannot be async themselves. Since async is a Rust language feature that touches all parts of the code base, a new implementation of Scheme is required that is built with async Rust in mind to take full advantage of the async runtime and more importantly integrate frictionlessly into the async application.

GoukiScheme[15] is a Scheme implementation designed to integrate flawlessly with async Rust; GoukiScheme code can execute asynchronously embedded in an async Rust application and can in turn execute async Rust functions. Arbitrary Rust objects can be stored in GoukiScheme variables and passed to GoukiScheme functions with little modification. This is done without sacrificing potential performance by architecting GoukiScheme as a tree-walking AST; indeed GoukiScheme is fully JIT compiled and takes advantage of a CPS based mid-level IR to compile to LLVM SSA. GoukiScheme does this while providing a completely Safe API.

This integration allows for Scheme programs to be written that take advantage of the Rust async ecosystem, such as this example of an echo server adapted from tokio:

```
(define (echo socket)
  (let ((buff (await (read-all socket))))
    (await (write-all socket buff))
    (echo socket)))

(define (listen listener)
  (let-values (((socket _) (await (accept listener))))
    (spawn (lambda () (echo socket)))
    (listen listener)))

(listen (await (bind-tcp "127.0.0.1:8080")))
```

In this example, the functions `read-all`, `write-all`, `accept`, and `bind-tcp` are all Rust functions accessible via Scheme that call the appropriate tokio functions. `await` is also a builtin that checks that its argument is a `Future` and awaits it.

2 Alternatives

There are several solutions currently available for embedding Scheme in Rust, one of the most straightforward is to use the C bindings provided by the Guile implementation, of which there are several bindings available in the Rust registry, although most of them are fairly rudimentary and incomplete. Additionally, none of these implementations provide any support for async Rust, since no such support is available from Guile.

Steel[14] is a pure Rust interpreter for Scheme that has support for calling async functions and utilizing async runtimes. Gouki and Steel differ in two primary ways. The first is in implementation: Steel is implemented via a bytecode interpreter, while Gouki is JIT compiled. The second is to what degree async is required by the implementation: Steel allows for an async runtime to be provided optionally, while Gouki requires an async runtime as that is its primary use case.

At the time of publication, Gouki Scheme is the only JIT compiled implementation of a language with support for `call-with-current-continuation` that can be embedded in a compiled language with support for async programming.

3 Memory Management

In order to properly implement the Scheme programming language, some form of garbage collection must be implemented by the system. One very popular algorithm for garbage collection is known as tracing, in which objects that are not determined to be reachable from so-called “root” objects are retained while the remaining objects are considered garbage and deallocated[13].

The root objects of a Scheme program are local and global variables active on the current Scheme call-stack, which is easy for our implementation to collect. However, when values escape into Rust code, the root objects for the entire program must be expanded to include that of the Rust code as well. Unfortunately, determining the roots of Rust program is not feasible[11].

A common Rust technique for automatic memory management is to use reference counting, which does not require knowing the roots of a program. However, this by itself is insufficient for our implementation due to the inability of reference counted systems to collect cycles[10]. We can extend this technique to support all valid Scheme programs by utilizing concurrent cycle collection[9].

The API for garbage collection in GoukiScheme is simple. GoukiScheme provides a `Gc` type that implements the same interface as `Arc`:

```
pub struct Gc<T>
where
    T: ?Sized,
{
    // private fields
}
```

Fundamentally the `Gc` type intends to mimic the behavior of a scheme variable. It can be read from and written to and arbitrarily passed around as a reference. Scheme variables can be passed to Rust code as a `Gc`.

Allocating a new garbage-collected `T` is done via the `Gc::new` function, and creating a new copy of the pointer to that object is done via the `Clone` method.

Additionally, the `Gc` type provides a `write` and `read` method in order to provide thread-safe mutations and reads to the allocated data. Since GoukiScheme can arbitrarily spawn threads that reference shared or global variables, it is important for all writes and reads to variables to be safe and atomic. This is achieved by embedded `RwLock` in the `Gc` type.

After the `init_gc` function is called once, GoukiScheme spawns a task dedicated to collecting garbage. This task is shut down automatically when the main function returns. This provides a smooth and intuitive interface to the memory manager that is also performant.

```
#[tokio::main]
fn main() {
    init_gc();
    let a = Gc::new("hello");
    let b = a.clone();
    {
        *a.write() = "world";
    }
    assert_eq!(b.read(), "world");
}
```

No signal needs to be sent to shutdown the collector thread. This interface is only possible with async Rust.

Whenever a `Gc` is cloned or dropped, the change in reference count is sent to the collector task over an unbounded channel called the mutation buffer. The collector task receives those mutations in a loop, in what essentially amounts to the following code:

```
fn init_gc() {
    // Spawn the collector task:
    let _ = spawn(async move {
        let mut mutations = Vec::new();
        loop {
            BUFFER.recv_many(
```

```

221         &mut mutations
222     ).await;
223     process_mutation(mutation);
224     mutations.clear();
225 }
226 });
227 }

```

The collector can be an asynchronous coroutine (in tokio what is called a task) because its loop is receiving from an asynchronous channel. Since it is a task, which is a Future (also known as a promise), it is subject to cancellation[17] when it yields at `.await` points. One common cause of cancellation is when the tokio runtime is shutdown, i.e. when the main function returns. Therefore, no manual intervention is required by the user to shut down the garbage collection task, as it will properly shut down at the end of the program's lifetime.

3.1 Tracing and Finalizing

One limitation of the cycle collection scheme (and indeed even tracing garbage collection schemes) and therefore the Gc smart pointer is the requirement to enumerate every reference from within a single Gc in order to properly determine cycles. Additionally, properly finalizing a cycle is non-trivial and needs information about the contents of the type. This limits us to storing types in a Gc that implement the Trace trait:

```

250 unsafe trait Trace: 'static {
251     unsafe fn visit_children(
252         &self,
253         visitor: unsafe fn(OpaqueGcPtr)
254     );
255
256     unsafe fn finalize(&mut self);
257 }

```

Implementing this function is tedious and requires the user to implement potentially memory unsafe code. However, it is not difficult to implement based on the syntactic form of the data type being implemented from. For example, here is the corresponding Trace implementation for a sample struct:

```

265 struct Example {
266     a: Gc<Example>,
267     b: OtherStruct,
268 }
269
270 unsafe impl Trace for Example {
271     unsafe fn visit_children(
272         &self,
273         visitor: unsafe fn(OpaqueGcPtr)
274     ) {

```

```

276         visitor(self.a.as_opaque());
277         self.b.visit_children(visitor);
278     }
279
280     unsafe fn finalize(&mut self) {
281         self.b.finalize();
282     }
283 }

```

The rules for implementing a Trace for a function is simple. First, we must assume that each field implements Trace or is a Gc. If the fields do not implement Trace and are not a Gc, then a compilation error will surface later when we attempt to call the `visit_children` and `finalize` functions. After we assume this, we can implement Trace as follows:

```

291 for field ∈ fields do
292     if typeof(field) = Gc then
293         Visitor(AsOpaque(field));
294     else VisitChildren(field);
295 end

```

Algorithm 1: visit children

```

300 for field ∈ fields do
301     if typeof(field) ≠ Gc then
302         Finalize(field)
303     end
304 end

```

Algorithm 2: finalize

Since these algorithms can be clearly implemented from the syntactic form of the data type (or rather it nearly can; we can assume the type of a field is equal to a Gc if it is spelled Gc - while this is not true in some pathological cases, such as when a local Gc type is defined, it is a good enough heuristic for nearly all cases), they are a prime candidate to be implemented with a procedural macro, or more specifically a derive macro[1]:

```

316 #[derive(Trace)]
317 struct NamedCell {
318     name: &'static str,
319     cell: Gc<Value>,
320 }
321
322 let foo = Gc::new(NamedCell { .. });

```

While this covers a large number of cases, some types can never implement Trace. One such example is types defined in external crates that do not already implement Trace; such types cannot implement Trace due to the orphan rule[2]. Storing these types requires an extra level of indirection through Rust's built-in reference counted type, the Arc[3].

Extra care must be taken when using this escape hatch as previously mentioned these types do not provide any way to collect cyclical references.

3.2 Enabling Back-Pressure from the Garbage Collector

Because we are running the garbage collector concurrently and are sending mutations to the collector over an unbounded channel, the allocating tasks receive no back pressure from the collector task. As a result should the pace of new allocations out pace the collectors ability to free garbage, the process would exhibit what appears to be a memory leak. While rare, it can satill occur and thus we allow for a way to convert the unbounded channel into backpressure:

```
async fn yield_until_gc_cleared() {
    while PENDING_MUTATIONS > MAX_ALLOWED {
        tokio::task::yield_now().await
    }
}
```

This function is automatically called in the evaluation trampoline to prevent runaway memory allocations. This means that while the collection scheme is always concurrent, it is only *parallel* for some amount of pending mutations.

4 Values

The Value type represents a Scheme Value. It has the dual responsibility of story any possible Scheme value while also allowing for the storage of any Rust values. Additionally, if a Scheme value has a reasonable native equivalent in Rust (which almost all of them do), conversion should be convenient and efficient. The Value type should also be convenient to pass to and use in our JIT compiled functions.

```
#[repr(transparent)]
pub struct Value(u64);
```

We use a tagged pointer[16] scheme to achieve these constraints with minimal overhead. A rather large tag size of four bits allowing for 16 tags in order to represent the most common Scheme values without an extra level of indirection.

```
pub enum ValueType {
    Null = 0,
    Boolean = 1,
    Character = 2,
    Number = 3,
    String = 4,
    Symbol = 5,
    Vector = 6,
    ByteVector = 7,
    Syntax = 8,
    Closure = 9,
```

```
Record = 10,
RecordType = 11,
Pair = 12,
SchemeCompatible = 13,
HashMap = 14,
}
```

As a small optimization, an extra "Undefined" value, the result of reading a variable that has not been defined, is a Pair with a null pointer, or a value of 12.

This large number of tags allows us to map all of the primitive values in the serde data model[4] into a single Value without an extra level of indirection. As a result, any Rust type that implements Serialize can automatically be converted into a Value.

We also utilize Rust's dynamic dispatch to allow for the storing of any type that implements the SchemeCompatible and Trace traits. Using this trait we can create new Scheme values that present themselves as sealed records.

```
trait SchemeCompatible: Any {
    fn record_type(&self) -> Arc<RecordType>;

    fn eqv(&self, rhs: &Value) -> bool;
}
```

Objects that implement this trait can be stored as a Gc<dyn SchemeCompatible>, which can then be converted into a Value. Values, in turn, can be converted back to a Gc<dyn SchemeCompatible>, which can then be downcast to a concrete type.

5 Evaluation

Evaluation of Scheme code in Rust is achieved through two primary objects: the Closure and Application struct.

As the name implies, the Closure struct represents a Scheme closure, which includes a captured environment and some code:

```
struct Closure {
    env: Box<[Gc<Value>]>,
    func: FuncPtr,
    runtime: Gc<Runtime>,
    // some fields omitted
}
```

The env field points to an array of variables that can be accessed from the function. It includes all non-local variables that are captured as part of the reifying a function definition into a closure.

The function pointer type FuncPtr is the heart of the bridge between asynchronous Rust and Scheme code. It is sum type of three different pointer types:


```

441 pub enum FuncPtr {
442     Continuation(ContinuationPtr),
443     Closure(ClosurePtr),
444     Bridge(BridgePtr),
445 }

```

The ContinuationPtr and ClosurePtr types are JIT compiled Scheme functions and the BridgePtr type is a Rust function that has been cast to a function pointer. Therefore all Scheme code is treated synchronously but can switch over to async Rust whenever it needs to await the result of a future. This is achieved by a trampoline; each call to a function returns an application to another function:

```

456 pub struct Application {
457     op: Option<Gc<Closure>>,
458     args: Vec<Value>,
459     // some fields omitted
460 }

```

However, in the case of Rust bridge functions - which can be potentially async - the function returns the *future* of an application. That means the body of trampoline loop is async:

```

467 impl Application {
468     pub async fn(mut self) ->
469         Result<Vec<Value>, Exception>
470     {
471         while let Application {
472             op: Some(op),
473             args,
474         } = self
475         {
476             self = op.apply(&args).await;
477         }
478     }
479 }

```

This allows for the JIT compiled ContinuationPtr and ClosurePtrs and for the Rust bridge functions to seamlessly interact with each other. The synchronous JIT compiled function pass their continuation to the async Rust code to evaluate the async result after it is awaited in the CPS trampoline.

6 Registering Bridge Functions

Using the inventory[5] crate we can create a global registry of Rust functions which can be imported into Scheme code. Functions with the signature of BridgePtr can be registered manually, but a procedural macro is provided to convert functions of many different signatures:

2025-07-05 23:25. Page 5 of 1-6.

```

496 #[bridge(
497     name = "read-file-to-string",
498     lib = "(tokio)"
499 )]
500 async fn read_file(file: &Value) ->
501     Result<Vec<Value>, Condition>
502 {
503     let file = file.to_string();
504     let contents =
505         read_to_string(&file)
506         .await
507         .map_err(|_| Condition::Error)?;
508     Ok(vec![Value::from(contents)])
509 }

```

Every function that registers with this inventory will be available automatically defined in their respective library in any Registry object created, GoukiScheme's notion of a package registry.

7 JIT Compilation

After the macro expansion phase, Scheme code is converted to a simple, reduced CPS mid level IR using the algorithm described in Compiling with Continuations[8]. After optimization the CPS IR is converted to LLVM SSA[12] for JIT compilation. LLVM was chosen due to its relative familiarity and large set of supported platforms, but the relative simplicity of the CPS mid level IR does not rule out the adding of additional backends such as Cranelift[6] which may have different performance characteristics.

Interacting with the LLVM JIT compiler to produce an object that can easily be interacted with in Rust (i.e. a Closure object described earlier) requires some care. When a Closure goes out of scope, we need a way to free the memory allocated for its function. LLVM's JIT compiler requires that we only have one handle to this memory per thread, which we call the Context[7]. In order to provide a safe interface that satisfies this guarantee, we create a handle to a separate thread that fully owns the JIT executor, called the Runtime:

```

537 struct Runtime {
538     comp_tasks_tx: Sender<CompilationTask>
539 }

```

Creating a new Runtime spawns a new thread which handles all of our compilation tasks. When the Runtime goes out of scope, its sender is dropped and the compilation task exits, freeing all of the JIT compiled functions.

Once we have a context for which we can JIT compile functions, we need to send those functions back to the caller, via function pointers. In Rust function pointers are of the static lifetime, which is to say they have the lifetime of the entire program. This is obviously incorrect in this instance

496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550

as the lifetime of Runtime is not guaranteed to last the entire program - a user could create a Runtime, create a Closure and summarily drop the given Runtime while continuing to use Closure. Therefore, we need to add a pointer from the Closure back to the Runtime from which it was created:

```
struct Closure {
    // ...
    runtime: Gc<Runtime>,
}
```

This ensures that if the Runtime is dropped before the Closure, there will still be a live reference preventing the function pointers from being deallocated.

8 Putting It All Together

Now that we have all of the requisite pieces, we can construct a Rust program that compiles and executes async Scheme code at runtime:

```
let rt = Runtime::new();
let registry =
    Registry::new(&runtime).await;
let env = Environment::from(
    registry.import("(base)")
);
let value = rt.eval(
    &env,
    // Sleep for 10 seconds and return a string
    "(begin (await (sleep 10)) \"hello world\")"
).await.unwrap();
println!("{value}");
```

9 Conclusion

GoukiScheme provides a purely safe, easy-to-use interface for interacting with async Scheme code from within async Rust. It does this by implementing a novel JIT compilation and evaluation scheme.

References

- [1] [n. d.]. . <https://doc.rust-lang.org/reference/procedural-macros.html#derive-macros>
- [2] [n. d.]. . <https://doc.rust-lang.org/reference/items/implementations.html#r-items.impl.trait.orphan-rule.intro>
- [3] [n. d.]. . <https://doc.rust-lang.org/std/sync/struct.Arc.html>
- [4] [n. d.]. . <https://serde.rs/data-model.html>
- [5] [n. d.]. . <https://github.com/dtolnay/inventory>
- [6] [n. d.]. . <https://cranelift.dev/>
- [7] [n. d.]. . https://llvm.org/doxygen/classllvm_1_1LLVMContext.html#details To quote the documentation: “LLVMContext itself provides no locking guarantees, so you should be careful to have one context per thread”.
- [8] Andrew W. Appel. 2007. *Compiling with Continuations*. Cambridge University Press, USA.
- [9] David F. Bacon and V. T. Rajan. 2001. Concurrent Cycle Collection in Reference Counted Systems. In *ECOOP 2001 — Object-Oriented Programming*, Jørgen Lindskov Knudsen (Ed.). Springer Berlin Heidelberg, Berlin, Heidelberg, 207–235.
- [10] Kevin G. Cassidy. 1985. *The Feasibility of Automatic Storage Reclamation with Concurrent Program Execution in a LISP Environment*. Master’s thesis. Naval Postgraduate School.
- [11] Felix S Klock II. 2016. *GC and Rust Part 2: The Roots of the Problem*. <https://blog.pnkfx.org/blog/2016/01/01/gc-and-rust-part-2-roots-of-the-problem/>
- [12] Chris Lattner and Vikram Adve. 2004. LLVM: A Compilation Framework for Lifelong Program Analysis & Transformation. In *Proceedings of the International Symposium on Code Generation and Optimization: Feedback-Directed and Runtime Optimization* (Palo Alto, California) (CGO ’04). IEEE Computer Society, USA, 75.
- [13] John McCarthy. 1960. Recursive functions of symbolic expressions and their computation by machine - I, Vol. 3. ACM, 184–195.
- [14] Matthew Paras. 2020. *An embeddable and extensible scheme dialect built in Rust*. <https://github.com/mattwparas/steel>
- [15] Matthew Plant. 2023. *Embedded Scheme for the Async Rust Ecosystem*. <https://github.com/maplant/scheme-rs>
- [16] P.A. Steenkiste. 1991. *Tags and run-time type checking*. The MIT Press. 3–24 pages.
- [17] Yoshua Wuyts. 2021. *Async Cancellation I*. <https://blog.yoshuawuyts.com/async-cancellation-1>