

2025/08/30

Lot number	GTL250830-19-36				Materials				A105					
Furnace number	521037				Forging ratio				≥3					
Forging temp	800~1250℃				Heat treatment condition				Normalizing					
HTT	920℃				Holding time				1.5h					
Composition (%)	C	Mn	Si	S	P	Cr	Ni	Mo	V	Cu				
	0.23	0.87	0.27	0.013	0.018	0.02	0.01	0.02	0.01	0.01				
Mechanical properties	Rm MPa	Rp _{0.2} MPa	A (%)	Impulse test			Temp ℃	KV2 J	HBW					
	545	310	30	0	59/63/65			145						
NDT	Method	Standard		Level		Conclusion								
	—	—		—		—								
Appearance quality, standard provisions												Result	Conclusion	
There is no visible crack, sandwich, folding, slag inclusion.												Qualified		Qualified
The grinding part is too smooth, and the clearing depth meets the specified requirements.														
Shape, size and surface quality meet the requirements of the order drawing.														
Item	Specifications		Quantity	Item	Specifications							Quantity		
1	Flange 1,5" WN #900/1500 RTJ SCH80		10	10	Flange 3" WN #150 RF SCH40							400		
2	Flange 1,5" WN #900/1500 RF SCH80		10	11	Flange 3" WN #300 RF SCH40							100		
3	Flange 2" BL #150		100	12	Flange 4" BL #150							50		
4	Flange 2" BL #300		50	13	F l a n g e 4 " B L # 3 0 0							10		
5	Flange 2" BL #600		30	14	Flange 4" BL #600							20		
6	Flange 2" SO #150		600	15	Flange 4" SO #150							600		
7	Flange 2" WN #150 RF SCH40		800	16	Flange 4" WN #150 RF SCH40							150		
8	Flange 2" WN #150 RF SCH80		150	17	Flange 4" WN #600 RF SCH80							10		
9	Flange 2,5" SO #150		10	18	Flange 4" WN #900 RTJ SCH80							10		
Conclusion: This batch of forgings meets the technical requirements of NB/T47008-2017 standard														