

3.1 Certificate of Seamless Fittings

CNEE: OIL METAL SA

License number: TS25136-2026

Certificate NO: GTL251020-03

Item	Product	Batch	Size	Material	QTY	Standard	Chemical Composition										Raw Material	
							C	Si	Mn	P	S	Cr	Ni	Cu	Mo	V	Heat No.	Material Standard
1	ER	251020-14	3" X 1 1/2" SCH 40	WPB A234	5	ASME16.9	0.22	0.23	0.46	0.016	0.012	0.01	0.02	0.01	0.002	0.002	25-430195	ASME SA106-2023
2	ER	251020-15	3" X 2 1/2" SCH 40	WPB A234	10	ASME16.9	0.22	0.23	0.46	0.016	0.012	0.01	0.02	0.01	0.002	0.002	25-430195	ASME SA106-2023
3	RT	251020-16	3" X 1 1/2" SCH 40	WPB A234	25	ASME16.9	0.22	0.23	0.46	0.016	0.012	0.01	0.02	0.01	0.002	0.002	25-430195	ASME SA106-2023
4	RT	251020-17	3" X 2 1/2" SCH 40	WPB A234	10	ASME16.9	0.22	0.23	0.46	0.016	0.012	0.01	0.02	0.01	0.002	0.002	25-430195	ASME SA106-2023
5	CR	251020-18	3" X 2" SCH 40/80	WPB A234	30	ASME16.9	0.23	0.25	0.45	0.017	0.013	0.02	0.02	0.01	0.003	0.001	25-710125	ASME SA106-2023
6	T	251020-19	3" SCH XXS	WPB A234	20	ASME16.9	0.21	0.26	0.47	0.018	0.013	0.02	0.01	0.02	0.001	0.002	25-896420	ASME SA106-2023
7	Elbow	251020-20	90° 4" SCH 40	WPB A234	100	ASME16.9	0.22	0.26	0.45	0.015	0.012	0.01	0.02	0.01	0.002	0.002	25-715206	ASME SA106-2023
8	CR	251020-21	4" X 2" SCH 40	WPB A234	20	ASME16.9	0.22	0.26	0.45	0.015	0.012	0.01	0.02	0.01	0.002	0.002	25-715206	ASME SA106-2023
9	CR	251020-22	4" X 3" SCH 40	WPB A234	30	ASME16.9	0.22	0.26	0.45	0.015	0.012	0.01	0.02	0.01	0.002	0.002	25-715206	ASME SA106-2023
10	ER	251020-23	4" X 3" SCH 40	WPB A234	10	ASME16.9	0.22	0.26	0.45	0.015	0.012	0.01	0.02	0.01	0.002	0.002	25-715206	ASME SA106-2023
11	ER	251020-24	4" X 2 1/2" SCH 40	WPB A234	10	ASME16.9	0.22	0.26	0.45	0.015	0.012	0.01	0.02	0.01	0.002	0.002	25-715206	ASME SA106-2023
12	Elbow	251020-25	45° 4" SCH 80	WPB A234	100	ASME16.9	0.23	0.26	0.48	0.016	0.011	0.01	0.02	0.01	0.003	0.001	25-904267	ASME SA106-2023
Other inspection items			Mechanical Properties							Appearance quality and standard regulations							Conclusion	
Item	Heat treatment method	NDT	Impact test		YieldN/mm ²	Tensile StrengthN/mm ²	Elongation%	HBW	There are no visible cracks, splits, curled edges or wrinkles to the naked eye. The surface is smooth without burrs, oxide scales or other defects.							Approved		
			Testing temperature℃	KV2/J														
1	Normalizing	/	/	/	318	472	28	/									Inspector: Liu Guohui Quality Assurance Specialist: Wang Zhenzhong This batch of pipe fittings has been inspected for quality and meets the requirements of the "Safety Technical Supervision Regulations for Pressure Pipelines - Industrial Pipelines", design drawings and industry standards Production date: Oct. 20th , 2025	
2	Normalizing	/	/	/	318	472	28	/										
3	Normalizing	/	/	/	318	472	28	/										
4	Normalizing	/	/	/	318	472	28	/	GREATLAND VALVE CO., LTD 大地实业有限公司 Authorized Signature(s)									
5	Normalizing	/	/	/	307	468	29.5	/										
6	Normalizing	/	/	/	312	475	28.5	/										
7	Normalizing	/	/	/	309	476	30.5	/										
8	Normalizing	/	/	/	309	476	30.5	/										
9	Normalizing	/	/	/	309	476	30.5	/										
10	Normalizing	/	/	/	309	476	30.5	/										
11	Normalizing	/	/	/	309	476	30.5	/										
12	Normalizing	/	/	/	312	472	28.5	/										