

GREATLAND VALVE CO., LTD

3.1 Certificate of Seamless Fittings

CNEE: OIL METAL SA

License number: TS25136-2026

Certificate NO: GTL251020-04

Item	Product	Batch	Size	Material	QTY	Standard	Chemical Composition										Raw Material	
							C	Si	Mn	P	S	Cr	Ni	Cu	Mo	V	Heat No.	Material Standard
1	CR	251020-26	4" X 3" SCH 80	WPB A234	20	ASME16.9	0.23	0.26	0.48	0.016	0.011	0.01	0.02	0.01	0.003	0.001	25-904267	ASME SA106-2023
2	ER	251020-27	4" X 2" SCH 80	WPB A234	15	ASME16.9	0.23	0.26	0.48	0.016	0.011	0.01	0.02	0.01	0.003	0.001	25-904267	ASME SA106-2023
3	CUSHION TEE	251020-28	4" SCH 80	WPB A234	10	ASME16.9	0.23	0.26	0.48	0.016	0.011	0.01	0.02	0.01	0.003	0.001	25-904267	ASME SA106-2023
4	Elbow	251020-29	45° 4" SCH 120	WPB A234	12	ASME16.9	0.21	0.25	0.46	0.015	0.013	0.02	0.02	0.01	0.002	0.001	25-645123	ASME SA106-2023
5	Elbow	251020-30	90° 4" SCH 120	WPB A234	15	ASME16.9	0.21	0.25	0.46	0.015	0.013	0.02	0.02	0.01	0.002	0.001	25-645123	ASME SA106-2023
6	RT	251020-31	4" X 2" SCH 120/80	WPB A234	10	ASME16.9	0.21	0.25	0.46	0.015	0.013	0.02	0.02	0.01	0.002	0.001	25-645123	ASME SA106-2023
7	ER	251020-32	4" X 2" SCH 80/160	WPB A234	5	ASME16.9	0.22	0.26	0.45	0.018	0.012	0.01	0.01	0.02	0.002	0.001	25-754106	ASME SA106-2023
8	RT	251020-33	4" X 2" SCH 80/160	WPB A234	10	ASME16.9	0.22	0.26	0.45	0.018	0.012	0.01	0.01	0.02	0.002	0.001	25-754106	ASME SA106-2023
9	Elbow	251020-34	45° 6" SCH 40	WPB A234	50	ASME16.9	0.21	0.24	0.47	0.017	0.011	0.02	0.01	0.01	0.002	0.001	25-894120	ASME SA106-2023
10	Elbow	251020-35	90° 6" SCH 40	WPB A234	50	ASME16.9	0.21	0.24	0.47	0.017	0.011	0.02	0.01	0.01	0.002	0.001	25-894120	ASME SA106-2023
11	ER	251020-36	6" X 4" SCH 40	WPB A234	30	ASME16.9	0.21	0.24	0.47	0.017	0.011	0.02	0.01	0.01	0.002	0.001	25-894120	ASME SA106-2023
12	RT	251020-37	6" X 3" SCH 40	WPB A234	20	ASME16.9	0.21	0.24	0.47	0.017	0.011	0.02	0.01	0.01	0.002	0.001	25-894120	ASME SA106-2023

Other inspection items			Mechanical Properties						Appearance quality and standard regulations		Conclusion
Item	Heat treatment method	NDT	Impact test		Yield N/mm²	Tensile StrengthN/mm²	Elongation%	HBW	There are no visible cracks, splits, curled edges or wrinkles to the naked eye. The surface is smooth without burrs, oxide scales or other defects. Inspector: Liu Guohui <i>For and on behalf of</i> Quality Assurance Specialist: Wang Zhenzhong GREATLAND VALVE CO., LTD This batch of pipe fittings has been inspected for quality and meets the requirements of the "Safety Technical Supervision Regulations for Pressure Pipelines - Industrial Pipelines", design drawings and industry standards <i>Authorized Signature(s)</i> Production date: Oct. 20th, 2025		
			Testing temperature °C	KV2/J							
1	Normalizing	/	/	/	312	472	28.5	/			
2	Normalizing	/	/	/	312	472	28.5	/			
3	Normalizing	/	/	/	312	472	28.5	/			
4	Normalizing	/	/	/	309	478	29	/			
5	Normalizing	/	/	/	309	478	29	/			
6	Normalizing	/	/	/	309	478	29	/			
7	Normalizing	/	/	/	315	469	30.5	/			
8	Normalizing	/	/	/	315	469	30.5	/			
9	Normalizing	/	/	/	322	482	29.5	/			
10	Normalizing	/	/	/	322	482	29.5	/			
11	Normalizing	/	/	/	322	482	29.5	/			
12	Normalizing	/	/	/	322	482	29.5	/			