HEBEI JINSHENG PIPE FITTING MANUFACTURING CO.,LTD
Tel:0086-0311-87367207 Fax:0086-0317-6392878 sales4@chinajsgj.com

# MILL TEST CERTIFICATE -（EN10204 3.1）

| | | | |
|---|---|---|---|
| CUSTOMER（客户）: | OIL METAL S.A. | CERTIFICATE NO（证书号）.: | Y04250729-1 |
| COMM PN16ODITY（商品): | Butt weld pipe fittings | CONTRACT NO.（合同号）: | 25Z040328 |
| MANUFACTURING STANDARD（制造标准）: | ANSI B16.9 | DATE OF DEVERILY（发货日期）: | August,2025 |

| NO. | Heat No. 炉号 | Item(产品) | Material 材质 | QTY 数量 | CHEMICAL COMPOSITION（化学成分） | | | | | | | | | | MECHANICAL PROPERTIES（力学性能） | | | | DIMENSION TOLERANCE (尺寸公差) | SURFACE QUALITY (表面质量) | BENDING TEST (弯曲试验) | MAGNETIC PARTICLE EXAMINATION (无损探伤) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | C% ≤0.30 | Si% ≥0.10 | Mn% 0.29-1.06 | S% ≤0.058 | P% ≤0.050 | Ni% ≤0.40 | Cr% ≤0.40 | Mo% ≤0.15 | Cu% ≤0.40 | V% ≤0.08 | Y.S (Mpa) 屈服强度 ≥240 | T.S (Mpa) 抗拉强度 415-585 | EL(%) 伸长率 ≥22 | Hardness (HB)硬度 ≤197HB | | | | |
| 26 | 63168 | REDUCTION TEE 6" X 2" SCH 80 | A234 WPB | 10pcs | 0.19 | 0.22 | 0.43 | 0.011 | 0.013 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 254 | 482 | 23 | 128 | pass | pass | pass | pass |
| 27 | 63168 | Con Reducer 6" X 2" SCH 80 | A234 WPB | 10pcs | 0.19 | 0.22 | 0.43 | 0.011 | 0.013 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 254 | 482 | 23 | 128 | pass | pass | pass | pass |
| 28 | 27572 | ECC Reducer 6" X 2" SCH 40/80 | A234 WPB | 20pcs | 0.19 | 0.21 | 0.47 | 0.011 | 0.011 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 256 | 481 | 25 | 131 | pass | pass | pass | pass |
| 29 | 27572 | Con Reducer 6" X 4" SCH 40 | A234 WPB | 40pcs | 0.19 | 0.21 | 0.47 | 0.011 | 0.011 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 256 | 481 | 25 | 131 | pass | pass | pass | pass |
| 30 | 63168 | Con Reducer 6" X 4" SCH 80 | A234 WPB | 50pcs | 0.19 | 0.22 | 0.43 | 0.011 | 0.013 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 254 | 482 | 23 | 128 | pass | pass | pass | pass |
| 31 | 63168 | ECC Reducer 6" X 4" SCH 80 | A234 WPB | 50pcs | 0.19 | 0.22 | 0.43 | 0.011 | 0.013 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 254 | 482 | 23 | 128 | pass | pass | pass | pass |
| 32 | 45912 | ELBOW LR 45° 8" SCH 20 | A234 WPB | 20pcs | 0.19 | 0.21 | 0.58 | 0.015 | 0.011 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 253 | 486 | 23 | 138 | pass | pass | pass | pass |
| 33 | 45912 | ELBOW LR 90° 8" SCH 20 | A234 WPB | 100pcs | 0.19 | 0.21 | 0.58 | 0.015 | 0.011 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 253 | 486 | 23 | 138 | pass | pass | pass | pass |
| 34 | 25477 | TEE TOT 8" SCH 20 | A234 WPB | 20pcs | 0.18 | 0.19 | 0.57 | 0.012 | 0.013 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 266 | 479 | 27 | 123 | pass | pass | pass | pass |
| 35 | 25219 | ECC Reducer 8" X 4" SCH 40 | A234 WPB | 20pcs | 0.19 | 0.21 | 0.55 | 0.013 | 0.012 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 256 | 481 | 25 | 135 | pass | pass | pass | pass |
| 36 | 25219 | ECC Reducer 8" X 6" SCH 40 | A234 WPB | 70pcs | 0.19 | 0.21 | 0.55 | 0.013 | 0.012 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 256 | 481 | 25 | 135 | pass | pass | pass | pass |
| 37 | 45912 | ELBOW LR 45° 10" SCH 20 | A234 WPB | 50pcs | 0.19 | 0.21 | 0.58 | 0.015 | 0.011 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 253 | 486 | 23 | 138 | pass | pass | pass | pass |
| 38 | 45912 | ELBOW LR 90° 10" SCH 20 | A234 WPB | 50pcs | 0.19 | 0.21 | 0.58 | 0.015 | 0.011 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 253 | 486 | 23 | 138 | pass | pass | pass | pass |
| 39 | 75732 | ELBOW LR 45° 10" SCH 40 | A234 WPB | 30pcs | 0.18 | 0.22 | 0.55 | 0.011 | 0.011 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 267 | 478 | 26 | 124 | pass | pass | pass | pass |
| 40 | 75732 | ELBOW LR 90° 10" SCH 40 | A234 WPB | 20pcs | 0.18 | 0.22 | 0.55 | 0.011 | 0.011 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 267 | 478 | 26 | 124 | pass | pass | pass | pass |
| 41 | 12273 | ELBOW LR 90° 10" SCH 120 | A234 WPB | 10pcs | 0.19 | 0.24 | 0.56 | 0.011 | 0.012 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 253 | 487 | 26 | 133 | pass | pass | pass | pass |
| 42 | 25637 | TEE TOT 10" SCH 20 | A234 WPB | 35pcs | 0.17 | 0.23 | 0.53 | 0.011 | 0.01 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 264 | 477 | 26 | 130 | pass | pass | pass | pass |
| 43 | 61258 | TEE TOT 10" SCH 60 | A234 WPB | 5pcs | 0.19 | 0.22 | 0.43 | 0.011 | 0.013 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 254 | 482 | 23 | 128 | pass | pass | pass | pass |
| 44 | 52444 | CAP 10" SCH 40 | A234 WPB | 5pcs | 0.19 | 0.22 | 0.43 | 0.011 | 0.013 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 254 | 482 | 23 | 128 | pass | pass | pass | pass |
| 45 | 63273 | Con Reducer 10" X 4" SCH 80 | A234 WPB | 3pcs | 0.19 | 0.24 | 0.48 | 0.011 | 0.011 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 256 | 487 | 24 | 125 | pass | pass | pass | pass |
| 46 | 25273 | TEE RED 10" X 6" SCH 20/40 | A234 WPB | 15pcs | 0.18 | 0.24 | 0.47 | 0.011 | 0.012 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 257 | 479 | 26 | 125 | pass | pass | pass | pass |
| 47 | 25273 | Con Reducer 10" X 6" SCH 40 | A234 WPB | 10pcs | 0.18 | 0.24 | 0.47 | 0.011 | 0.012 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 257 | 479 | 26 | 125 | pass | pass | pass | pass |
| 48 | 25273 | ECC Reducer 10" X 6" SCH 20/40 | A234 WPB | 5pcs | 0.18 | 0.24 | 0.47 | 0.011 | 0.012 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 257 | 479 | 26 | 125 | pass | pass | pass | pass |
| 49 | 45611 | ELBOW LR 45° 12" SCH 20 | A234 WPB | 15pcs | 0.19 | 0.22 | 0.43 | 0.011 | 0.013 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 254 | 482 | 23 | 128 | pass | pass | pass | pass |
| 50 | 25325 | ECC Reducer 12" X 6" SCH 40 | A234 WPB | 5pcs | 0.17 | 0.23 | 0.48 | 0.011 | 0.01 | 0.01 | 0.01 | 0.02 | 0.01 | 0.01 | 258 | 475 | 26 | 137 | pass | pass | pass | pass |

Notes：Y.S=Yield Strength T.S=Tensile Strength EL=Elongation

The inspected products conform to the above standards,so they should be delivered.

Remarks备注:Ceq=C+Mn/6+(Cr+V+Mo)/5+(Cu+Ni)/15 approved.

Seal盖章: TEST CERTIFICATE

Verifier审核: 杨东