HEBEI JINSHENG PIPE FITTING MANUFACTURING CO.,LTD
Tel:0086-0311-87367207 Fax:0086-0317-6392878 sales4@chinajsgj.com

MILL TEST CERTIFICATE -（EN10204 3.1）

CUSTOMER（客户）:	OIL METAL S.A.	CERTIFICATE NO（证书号）.:	Y04250729-1
COMM PN16ODITY（商品):	Butt weld pipe fittings	CONTRACT NO.（合同号）:	25Z040328
MANUFACTURING STANDARD（制造标准）:	ANSI B16.9	DATE OF DEVERILY（发货日期）:	August,2025

NO.	Heat No. 炉号	Item(产品)	Material 材质	QTY 数量	CHEMICAL COMPOSITION（化学成分）										MECHANICAL PROPERTIES（力学性能）				DIMENSION TOLERANCE (尺寸公差)	SURFACE QUALITY (表面质量)	BENDING TEST (弯曲试验)	MAGNETIC PARTICLE EXAMINATION (无损探伤)
					C% ≤0.30	Si% ≥0.10	Mn% 0.29-1.06	S% ≤0.058	P% ≤0.050	Ni% ≤0.40	Cr% ≤0.40	Mo% ≤0.15	Cu% ≤0.40	V% ≤0.08	Y.S (Mpa) 屈服强度 ≥240	T.S (Mpa) 抗拉强度 415-585	EL(%) 伸长率 ≥22	Hardness (HB)硬度 ≤197HB				
26	63168	REDUCTION TEE 6" X 2" SCH 80	A234 WPB	10pcs	0.19	0.22	0.43	0.011	0.013	0.01	0.01	0.02	0.01	0.01	254	482	23	128	pass	pass	pass	pass
27	63168	Con Reducer 6" X 2" SCH 80	A234 WPB	10pcs	0.19	0.22	0.43	0.011	0.013	0.01	0.01	0.02	0.01	0.01	254	482	23	128	pass	pass	pass	pass
28	27572	ECC Reducer 6" X 2" SCH 40/80	A234 WPB	20pcs	0.19	0.21	0.47	0.011	0.011	0.01	0.01	0.02	0.01	0.01	256	481	25	131	pass	pass	pass	pass
29	27572	Con Reducer 6" X 4" SCH 40	A234 WPB	40pcs	0.19	0.21	0.47	0.011	0.011	0.01	0.01	0.02	0.01	0.01	256	481	25	131	pass	pass	pass	pass
30	63168	Con Reducer 6" X 4" SCH 80	A234 WPB	50pcs	0.19	0.22	0.43	0.011	0.013	0.01	0.01	0.02	0.01	0.01	254	482	23	128	pass	pass	pass	pass
31	63168	ECC Reducer 6" X 4" SCH 80	A234 WPB	50pcs	0.19	0.22	0.43	0.011	0.013	0.01	0.01	0.02	0.01	0.01	254	482	23	128	pass	pass	pass	pass
32	45912	ELBOW LR 45° 8" SCH 20	A234 WPB	20pcs	0.19	0.21	0.58	0.015	0.011	0.01	0.01	0.02	0.01	0.01	253	486	23	138	pass	pass	pass	pass
33	45912	ELBOW LR 90° 8" SCH 20	A234 WPB	100pcs	0.19	0.21	0.58	0.015	0.011	0.01	0.01	0.02	0.01	0.01	253	486	23	138	pass	pass	pass	pass
34	25477	TEE TOT 8" SCH 20	A234 WPB	20pcs	0.18	0.19	0.57	0.012	0.013	0.01	0.01	0.02	0.01	0.01	266	479	27	123	pass	pass	pass	pass
35	25219	ECC Reducer 8" X 4" SCH 40	A234 WPB	20pcs	0.19	0.21	0.55	0.013	0.012	0.01	0.01	0.02	0.01	0.01	256	481	25	135	pass	pass	pass	pass
36	25219	ECC Reducer 8" X 6" SCH 40	A234 WPB	70pcs	0.19	0.21	0.55	0.013	0.012	0.01	0.01	0.02	0.01	0.01	256	481	25	135	pass	pass	pass	pass
37	45912	ELBOW LR 45° 10" SCH 20	A234 WPB	50pcs	0.19	0.21	0.58	0.015	0.011	0.01	0.01	0.02	0.01	0.01	253	486	23	138	pass	pass	pass	pass
38	45912	ELBOW LR 90° 10" SCH 20	A234 WPB	50pcs	0.19	0.21	0.58	0.015	0.011	0.01	0.01	0.02	0.01	0.01	253	486	23	138	pass	pass	pass	pass
39	75732	ELBOW LR 45° 10" SCH 40	A234 WPB	30pcs	0.18	0.22	0.55	0.011	0.011	0.01	0.01	0.02	0.01	0.01	267	478	26	124	pass	pass	pass	pass
40	75732	ELBOW LR 90° 10" SCH 40	A234 WPB	20pcs	0.18	0.22	0.55	0.011	0.011	0.01	0.01	0.02	0.01	0.01	267	478	26	124	pass	pass	pass	pass
41	12273	ELBOW LR 90° 10" SCH 120	A234 WPB	10pcs	0.19	0.24	0.56	0.011	0.012	0.01	0.01	0.02	0.01	0.01	253	487	26	133	pass	pass	pass	pass
42	25637	TEE TOT 10" SCH 20	A234 WPB	35pcs	0.17	0.23	0.53	0.011	0.01	0.01	0.01	0.02	0.01	0.01	264	477	26	130	pass	pass	pass	pass
43	61258	TEE TOT 10" SCH 60	A234 WPB	5pcs	0.19	0.22	0.43	0.011	0.013	0.01	0.01	0.02	0.01	0.01	254	482	23	128	pass	pass	pass	pass
44	52444	CAP 10" SCH 40	A234 WPB	5pcs	0.19	0.22	0.43	0.011	0.013	0.01	0.01	0.02	0.01	0.01	254	482	23	128	pass	pass	pass	pass
45	63273	Con Reducer 10" X 4" SCH 80	A234 WPB	3pcs	0.19	0.24	0.48	0.011	0.011	0.01	0.01	0.02	0.01	0.01	256	487	24	125	pass	pass	pass	pass
46	25273	TEE RED 10" X 6" SCH 20/40	A234 WPB	15pcs	0.18	0.24	0.47	0.011	0.012	0.01	0.01	0.02	0.01	0.01	257	479	26	125	pass	pass	pass	pass
47	25273	Con Reducer 10" X 6" SCH 40	A234 WPB	10pcs	0.18	0.24	0.47	0.011	0.012	0.01	0.01	0.02	0.01	0.01	257	479	26	125	pass	pass	pass	pass
48	25273	ECC Reducer 10" X 6" SCH 20/40	A234 WPB	5pcs	0.18	0.24	0.47	0.011	0.012	0.01	0.01	0.02	0.01	0.01	257	479	26	125	pass	pass	pass	pass
49	45611	ELBOW LR 45° 12" SCH 20	A234 WPB	15pcs	0.19	0.22	0.43	0.011	0.013	0.01	0.01	0.02	0.01	0.01	254	482	23	128	pass	pass	pass	pass
50	25325	ECC Reducer 12" X 6" SCH 40	A234 WPB	5pcs	0.17	0.23	0.48	0.011	0.01	0.01	0.01	0.02	0.01	0.01	258	475	26	137	pass	pass	pass	pass

Notes：Y.S=Yield Strength T.S=Tensile Strength EL=Elongation

The inspected products conform to the above standards,so they should be delivered.

Remarks备注:Ceq=C+Mn/6+(Cr+V+Mo)/5+(Cu+Ni)/15 approved.

Seal盖章: TEST CERTIFICATE

Verifier审核: 杨东