

Cliente / Customer TUBOS RENARD SA			Orden de Fabricaciyn/Manufacturing order 5/8680-01		Numero / Number T - 116755/1	Fecha / Date 22/04/2025	P6g./Page 1/5
Producto / Product CONDUCCION - AL CARB.P/SERV A ALTAS TEMP.TREF EN FRI0			Orden de Compra/Purchaser Order 2145		Item 1125	Referencia del Cliente/Customer Reference	
Norma / Standard ASTM A 106M 14 - ASTM A 53- 13			Grado / Grade B			Extremo / Ends CORTADO ESCUADRA-REBABADO/SQUARED CUT	
Dimensiones / Dimensions		Schedule	Peso Nominal/Nominal Weight	Longitud / Length	Superficie Externa / External Surface	Cantidades / Quantities	
26.7 x 5.56 mm		160	2.90 Kg/Mt	5.0/12.0	Aceitado	185 Pz	1632.83 m
3/ 4 x 0.219 Inches			1.94 Lb/Ft	RL 16" 4,8"/39" 4,4"	Oiled	185 Pcs	5357.04 Ft
						4851 Kg	10696 Lb

Ensayos / Tests:

Ensayos Tests	Mínimo Minimum	Máximo Maximum	Colada Heat	Colada Heat	Muestra Nro / Sample Number					
					243997	243999	245343	245345	244000	243998
Colada/Heat O.P.			25072	26024	25072 75259	25072 75259	26024 75954	26024 75954	25072 75259	25072 75259
Analisis Quimico			Satisfactorio	Satisfactorio	Satisfactorio	Satisfactorio	Satisfactorio	Satisfactorio		
Chemical Analysis			Ok	Ok	Ok	Ok	Ok	Ok		
C %		0.2500 %	0.2000	0.1900	0.1900	0.1900	0.1900	0.2000		
Mn %	0.2900 %	1.3500 %	0.4400	0.4600	0.4500	0.4500	0.4500	0.4600		
S %		0.0350 %	0.0010	0.0005	0.0006	0.0007	0.0003	0.0010		
P %		0.0350 %	0.0110	0.0110	0.0110	0.0120	0.0100	0.0120		
Si %	0.1000 %		0.2300	0.2400	0.2400	0.2400	0.2400	0.2500		
Ni %		0.4000 %	0.0530	0.0380	0.0410	0.0420	0.0390	0.0370		
Cr %		0.4000 %	0.0500	0.1000	0.0400	0.0400	0.1000	0.1100		
Mo %		0.1500 %	0.0100	0.0200	0.0100	0.0100	0.0200	0.0200		
V %		0.0800 %	0.0020	0.0020	0.0020	0.0020	0.0010	0.0010		
Cu %		0.4000 %	0.1000	0.0800	0.1100	0.1100	0.1000	0.0900		
Cr+Cu+Mo+Ni+V %		1.0000 %			0.2030	0.2040	0.2600	0.2580		
Traccion					Satisfactorio		Satisfactorio			
Tensile					Ok		Ok			
Tipo Seccion/Sect.Type	mm				TUBULAR		TUBULAR			
Long.Inicial/Init.Length	50.8				50.800		50.800			
Alargamiento/Elongation %	30.000 %				47.000		45.000			
FL 0.5%Mpa/YS 0.5%Mpa %	0.500 %				286.000		292.000			
Rotura/UTS MPA	415.000 MPA				458.000		453.000			

Inspection Certificate

(EN 10204 3.1 - ISO 10474 3.1B)

Siderca S.A.I.C
Dr Jorge A. Simini 250
(B2804MHA) Campana
Buenos Aires, Argentina
(54) 3489 433100 tel
(54) 3489 433405 fax

Cliente / Customer TUBOS RENARD SA			Orden de Fabricaciyn/Manufacturing order 5/8680-01		Número / Number T - 116755/1	Fecha / Date 22/04/2025	P6g./Page 2/5
Producto / Product CONDUCCION - AL CARB.P/SERV A ALTAS TEMP.TREF EN FRIO			Orden de Compra/Purchaser Order 2145		Item 1125	Referencia del Cliente/Customer Reference	
Norma / Standard ASTM A 106M 14 - ASTM A 53- 13			Grado / Grade B			Extremo / Ends CORTADO ESCUADRA-REBABADO/SQUARED CUT	
Dimensiones / Dimensions 26.7 x 5.56 mm 3/ 4 x 0.219 Inches	Schedule 160	Peso Nominal/Nominal Weight 2.90 Kg/Mt 1.94 Lb/Ft	Longitud / Length 5.0/12.0 RL 16" 4,8"/39" 4,4"		Superficie Externa / External Surface Aceitado Oiled	Cantidades / Quantities 185 Pz 1632.83 m 4851 Kg 185 Pcs 5357.04 Ft 10696 Lb	

Ensayos / Tests:

Ensayos Tests	Mínimo Minimum	Máximo Maximum	Colada Heat	Colada Heat	Muestra Nro / Sample Number					
					243997	243999	245343	245345	244000	243998
Colada/Heat O.P.			25072	26024	25072 75259	25072 75259	26024 75954	26024 75954	25072 75259	25072 75259
Dureza							Satisfactorio		Satisfactorio	
Hardness							Ok		Ok	
Esp.Conifg.Tipo/TW T.Config							2		2	
Curvado					Satisfactorio	Satisfactorio	Satisfactorio	Satisfactorio	Satisfactorio	Satisfactorio
Bending					Ok	Ok	Ok	Ok	Ok	Ok

Cliente / Customer TUBOS RENARD SA			Orden de Fabricaciyn/Manufacturing order 5/8680-01		Numero / Number T - 116755/1	Fecha / Date 22/04/2025	P6g./Page 3/5
Producto / Product CONDUCCION - AL CARB.P/SERV A ALTAS TEMP.TREF EN FRIO			Orden de Compra/Purchaser Order 2145		Item 1125	Referencia del Cliente/Customer Reference	
Norma / Standard ASTM A 106M 14 - ASTM A 53- 13			Grado / Grade B		Extremo / Ends CORTADO ESCUADRA-REBABADO/SQUARED CUT		
Dimensiones / Dimensions 26.7 x 5.56 mm 3/ 4 x 0.219 Inches		Schedule 160	Peso Nominal/Nominal Weight 2.90 Kg/Mt 1.94 Lb/Ft		Longitud / Length 5.0/12.0 RL 16" 4,8"/39" 4,4"		Superficie Externa / External Surface Aceitado Oiled
					Cantidades / Quantities 185 Pz 1632.83 m 4851 Kg 185 Pcs 5357.04 Ft 10696 Lb		

Ensayos / Tests:

Inspection Certificate

(EN 10204 3.1 - ISO 10474 3.1B)

Siderca S.A.I.C
Dr Jorge A. Simini 250
(B2804MHA) Campana
Buenos Aires, Argentina
(54) 3489 433100 tel
(54) 3489 433405 fax

Cliente / Customer TUBOS RENARD SA			Orden de Fabricaciyn/Manufacturing order 5/8680-01		Número / Number T - 116755/1	Fecha / Date 22/04/2025	P6g./Page 4/5
Producto / Product CONDUCCION - AL CARB.P/SERV A ALTAS TEMP.TREF EN FRIO			Orden de Compra/Purchaser Order 2145		Item 1125	Referencia del Cliente/Customer Reference	
Norma / Standard ASTM A 106M 14 - ASTM A 53- 13			Grado / Grade B			Extremo / Ends CORTADO ESCUADRA-REBABADO/SQUARED CUT	
Dimensiones / Dimensions 26.7 x 5.56 mm 3/ 4 x 0.219 Inches	Schedule 160	Peso Nominal/Nominal Weight 2.90 Kg/Mt 1.94 Lb/Ft	Longitud / Length 5.0/12.0 RL 16" 4,8"/39" 4,4"		Superficie Externa / External Surface Aceitado Oiled	Cantidades / Quantities 185 Pz 185 Pcs 1632.83 m 5357.04 Ft 4851 Kg 10696 Lb	

Ensayos / Tests:

Ensayos Tests	Mínimo Minimum	Máximo Maximum	Muestra Nro / Sample Number							
			245344							
Colada/Heat O.P.			26024 75954							
Dureza										
Hardness										
Esp.Conifg.Tipo/TW T.Config										
Curvado			Satisfactorio							
Bending			Ok							

Inspection Certificate

(EN 10204 3.1 - ISO 10474 3.1B)

Siderca S.A.I.C
Dr Jorge A. Simini 250
(B2804MHA) Campana
Buenos Aires, Argentina
(54) 3489 433100 tel
(54) 3489 433405 fax

Cliente / Customer TUBOS RENARD SA			Orden de Fabricaci�n/Manufacturing order 5/8680-01		N�mero / Number T - 116755/1	Fecha / Date 22/04/2025	P�g./Page 5/5
Producto / Product CONDUCCION - AL CARB.P/SERV A ALTAS TEMP.TREF EN FRIO			Orden de Compra/Purchaser Order 2145		Item 1125	Referencia del Cliente/Customer Reference	
Norma / Standard ASTM A 106M 14 - ASTM A 53- 13			Grado / Grade B			Extremo / Ends CORTADO ESCUADRA-REBABADO/SQUARED CUT	
Dimensiones / Dimensions		Schedule	Peso Nominal/Nominal Weight	Longitud / Length	Superficie Externa / External Surface	Cantidades / Quantities	
26.7 x 5.56 mm		160	2.90 Kg/Mt	5.0/12.0	Aceitado	185 Pz	1632.83 m
3/ 4 x 0.219 Inches			1.94 Lb/Ft	RL 16" 4,8"/39" 4,4"	Oiled	185 Pcs	5357.04 Ft
							4851 Kg
							10696 Lb

Observaciones:

Remito Nro: R090100080331
Tratamiento termico: Normalizado 920  C
100% EDDY CURRENT ASTM E 309
Fabricacion de acero: Fundicion por arco electrico/ L F y Colado continuo - Acero Calmado al Aluminio.
La practica de afino en el horno-cuchara incluye una inyeccion final de una varilla de Siliciuro de Calcio para obtener una forma globular de eventuales microinclusiones.
Fabricacion de tubo: Sin Costura Trefilado
Material libre de contaminacion de Mercurio
Control Visual y Dimensional = Satisfactorio

Remarks:

Sending Note: R090100080331
Heat treatment: Normalized 920  C
100% EDDY CURRENT ASTM E 309
Steel making process: E.A.F./L.F and continuos casting.
Full aluminium killed and fine grain practice.
The LF practice includes a final injection of Calcium Silice wire for microinclusion shape control.
Pipe manufacturing process: Seamless Cold Drawn
Material free from Mercury contamination.
Visual and Dimensional Control = Satisfactory

Por la presente certificamos que el material aqui descripto ha sido fabricado de acuerdo con las normas y especificaciones solicitadas en vuestra orden y satisface los correspondientes requerimientos.	We hereby certify that material herein described has been manufactured in accordance with the standards and specifications required in your order and satisfies the corresponding requirements.	 QUALITY CERTIFICATION DEPT. DTO CERTIFICACION DE CALIDAD JORGE REALE	 QUALITY CERTIFICATION DEPT. DTO CERTIFICACION DE CALIDAD SOLEDAD PAOLINA
Este certificado se emite mediante un sistema computarizado y es valido con firma electr�nica. En el certificado en papel el logo TENARIS (verde), est� impreso en el centro de la hoja. En caso que el poseedor del certificado entregue una copia del mismo, deber� garantizar la conformidad con el original, haci�ndose responsable por cualquier uso ilegal o indebido.	This certificate is issued by a computarized system and it is valid with electronic signature. On the original on paper the TENARIS green coloured trade-mark is stamped on the center of the page. In case the owner of the certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use.		
Cualquier alteraci�n y / o falsificaci�n estar� sujeta a la ley. Si necesita asegurar la autenticidad de este certificado, contactarse con Siderca SAIC, e-mail: spaolina@tenaris.com	Any alteration and / or falsification will be subject to the law. If you need to assure the authenticity of this certificate, please do not hesitate to contact Siderca SAIC through this e-addrss: spaolina@tenaris.com		