

[illegible]



河北屹洋管道设备有限公司
HE BEI WPHY CO.,LTD

B 机械性能/Mechanical							
试样号 Specimen	试验温度 Test Temp	屈服强度 Yield Strength	拉伸强度 Tensile Strength	延伸率% Elongation	收缩率% Reduction Area	硬度 Hardness	冲击试验 Charpy Impact
Nr./No.	25℃	Mpa	Mpa	%	Z%	HRB	--
ASTM A182 F316L		≥205	≥520	≥40	≥50	≤149	--
NY230131AS07		288	578	49	59	121	--

C 无损探伤, 尺寸检查及水压试验/Hydrostatic Test, NDT and Dimension check:

试验/Testing	结果/Result	试验/Testing	结果/Result
尺寸检查/ Dimension check	OK	水压试验/Hydrostatic pressure test	N/A
表面检查/Surface quality inspection	OK	100%PMI Test	PASSED
晶腐/IGC to ASTM A262-2013 "E"	OK	X 射线/X-ray test	N/A

D 备注/Remarks:

1. 热处理 / 固溶 Heat treatment/Solution (at 1050℃ not less than 15 min) and quenched

2. The material manufactured according to a Quality management system approved and registered to ISO 9001 .

3. We hereby certify that the product described herein has been manufactured in accordance with the specifications concerned and also with the purchaser's requirements and that the test results shown herein are correct.

制单: 复验: 审核:
Inspector: 朱雨晴 Approved: 孙少龙 Approvaled: 刘建新