

检验证书/Certificate:		证书号/Certificate No.:				ISO 证书号/ISO certificate No:						
EN10204:2004-3.1		MTC-WPHY-YY2026041704				UQ231687R0						
客户/ Customer: OIL METAL S.A. 订单号/ Order No.: PO00010088 品名/ Article: 锻制管件/ Forged Fittings 技术条件/ Specification: ASME B16.11 & MSS SP 97 & MSS SP 95 & MSS SP 83 材料/ Material: ASTM A105 加工工艺/ Workmanship: 锻制/ Forging 交货状态/ Delivery Conditions: Finishing, Anti-rust oil						标识/ Marking: 管件型式 Manufacture's mark: WPHY Standard: ASME B16.11 & MSS SP 97 & MSS SP 95 & MSS SP 83 Grade Material: ASTM A105						
						Heat Number: 12501115						
产品交货范围/ Material Delivery Extent												
序号	品名		规格		数量		炉号		备注			
Item No.	Description		Dimension		Quantity		Heat No.		Remark			
3	HEX NIPPLE		2" NPT 3000		650		12501115		B16.11			
4	DOUBLE UNION		2" NPT 3000		460		12501115		MSS SP 83			
7	BOUSHING REDUCTION		3/4" X 1/2" BSPT 3000		100		12501115		B16.11			
8	COUPLING		1 1/2" BSPT 3000		200		12501115		B16.11			
9	HEX NIPPLE		2" BSPT 3000		150		12501115		B16.11			
12	DOUBLE UNION		1/2" NPT 3000		500		12501115		MSS SP 83			
16	COUPLING REDUCTION		11/2" X 1" NPT 3000		100		12501115		B16.11			
18	BOUSHING REDUCTION		1" X 3/4" BSPT 3000		100		12501115		B16.11			
26	ELBOLET		3/4" 6000 SW 36"-2"		10		12501115		B16.11			
28	ELBOW 90° MALE-FEMALE		3/4" THREAD BSPT 3000		100		12501115		B16.11			
29	ELBOW 90° MALE-FEMALE		3/8" THREAD BSPT 3000		150		12501115		B16.11			
30	ELBOW 90°		1/4" BSPT 3000		150		12501115		B16.11			
39	TE RED		1 1/2" X 3/4" SW 3000		150		12501115		B16.11			
40	BOUSHING REDUCTION		3/4" X 1/2" BSPT 3000		200		12501115		B16.11			
41	BOUSHING REDUCTION		1/2 X 1/4 BSPT/BSPP3000		250		12501115		B16.11			
42	BOUSHING REDUCTION		1 1/2" X 1" BSPT/BSPP3000		150		12501115		B16.11			
试验结果/ Test Results: 标准要求已符合, 见如下表格/ The requirements are fulfilled as listed in Annex.												
A 化学成分/ chemical composition:												
炉号/ Heat No.	C%	Si%	Mn%	S%	P%	Cr%	Mo%	V%	Ni%	Cu%	Ti%	CE
ASTM A105	≤0.35	0.10-0.35	0.60--1.06	≤0.040	≤0.035	≤0.3	≤0.12	≤0.08	≤0.4	--	--	--
12501115	0.19	0.23	0.84	0.005	0.015	0.040	0.002	0.001	0.008	0.007		0.34
B 机械性能/ Mechanical												
试样号 Specimen	试验温度 Test Temp	屈服强度 Yield Strength	拉伸强度 Tensile Strength	延伸率% Elongation	收缩率% Reduction Area	硬度 Hardness	冲击试验 Charpy Impact					
Nr./No.	24℃	Mpa	Mpa	%	Z%	HRB	--					
ASTM A105		≥250	≥485	≥22	≥30	≤187						
12501115		327	522	31	43	151	--					
C 无损探伤, 尺寸检查及水压试验/ Hydrostatic Test, NDT and Dimension check:												
试验/ Testing		结果/ Result		试验/ Testing			结果/ Result					
尺寸检查/ Dimension check		OK		水压试验/ Hydrostatic pressure test			N/A					
表面检查/ Surface quality inspection		OK		100%PMI Test			PASSED					
晶腐/ IGC to ASTM A262-2013 "E"		N/A		X 射线/ X-ray test			N/A					



河北屹洋管道设备有限公司
HE BEI WPHY CO.,LTD

D 备注/Remarks:		
1.热处理 / 正火 Heat treatment/normalizing (at 900℃ not less than 60.min)		
2.The material manufactured according to a Quality management system approved and registered to ISO 9001 .		
3.We hereby certify that the product described herein has been manufactured in accordance with the specifications concerned and also with the purchaser's requirements and that the test results shown herein are correct.		
地址: 沧州 河北 中国 Address: CANGZHOU HEBEI CHINA		日期 :2026-04-17 Date:Apr.17.,2026
制单: Inspector: 朱雨晴	复验: Approved:孙少龙	审核: Approvaled: 刘建新