



河北屹洋管道设备有限公司
HE BEI WPHY CO.,LTD

MILL TEST CERTIFICATE

工厂检测证书

(EN10204 3.1)

检验证书/Certificate:		证书号/Certificate No.:		ISO 证书号/ISO certificate No.:								
EN10204:2004-3.1		MTC-WPHY-YY2026041708		UQ231687R0								
客户/Customer: OIL METAL S.A. 订单号/Order No.: PO00010088 品名/Article: 管件/Fittings 技术条件/Specification: ASME B16.9 材料/Material: ASTM A234 GR WPB 加工工艺/Workmanship: 热成型/Hot Forming 交货状态/Delivery Conditions: Solution ,descaled ,Anti-rust paint				标识/Marking: 管件型式 Manufacture's mark: WPHY Standard: ASME B16.9 Grade Material: ASTM A234 GR WPB Heat Number: 859461, 23551212, 4755126								
产品交货范围/Material Delivery Extent												
序号	品名	规格	数量	炉号	备注							
Item No.	Description	Dimension	Quantity	Heat No.	Remark							
13	ELBOW SHORT RADIUS 90°	6" SCH 40	10	859461	--							
19	TEE TOT	6" SCH 40	300	859461								
37	REDUCTION CONCENTRIC	6" X 4" SCH 40	100	859461								
38	REDUCTION CONCENTRIC	4" X 3" SCH 40	50	23551212								
43	CAP	2" SCH 80	50	4755126								
试验结果/Test Results: 标准要求已符合, 见如下表格/The requirements are fulfilled as listed in Annex.												
A 化学成分/chemical composition:												
炉号/Heat No.	C%	Si%	Mn%	S%	P%	Cr%	Mo%	V%	Ni%	Cu%	Ti%	CE
ASTMA234 GR WPB	≤0.030	≥0.10	0.29--1.06	≤0.05	≤0.05	--	--	--	--	--	--	--
859461	0.18	0.23	0.45	0.010	0.015	0.09			0.04	0.04		0.28
23551212	0.18	0.32	0.49	0.006	0.012	0.005			0.01	0.001		0.26
4755126	0.17	0.33	0.41	0.013	0.02	0.01			0.01	0.002		0.24
B 机械性能/Mechanical												
试样号 Specimen	试验温度 Test Temp	屈服强度 Yield Strength	拉伸强度 Tensile Strength	延伸% Elongation	收缩率% Reduction Area	硬度 Hardness	冲击试验 Charpy Impact					
Nr./No.		Mpa	Mpa	A%	Z%	HRB						
ASTMA234 GR WPB	25℃	≥240	415--585	≥20	≥55	≤197	--					
859461		332	488	35	57	163						
23551212		279	484	29	58	142						
4755126		288	448	30	63	98						
C 无损探伤, 尺寸检查及水压试验/Hydrostatic Test,NDT and Dimension check:												
试验/Testing	结果/Result	试验/Testing	结果/Result									
尺寸检查/ Dimension check	OK	水压试验/Hydrostatic pressure test	N/A									
表面检查/Surface quality inspection	OK	100%PMI Test	PASSED									
晶腐/IGC to ASTM A262-2013 "E"	N/A	X 射线/X-ray test	N/A									
D 备注/Remarks:												
1.热处理 / 正火 Heat treatment/normalizing (at 900℃ not less than 30.min)												
2.The material manufactured according to a Quality management system approved and registered to ISO 9001 .												
3.We hereby certify that the product described herein has been manufactured in accordance with the specifications concerned and also with the purchaser's requirements and that the test results shown herein are correct.												
地址: 沧州 河北 中国 Address: CANGZHOU HEBEI CHINA		日期:2026-04-17 Date:Apr.17.,2026										
制单: Inspector: 朱雨晴		复验: Approved:孙少龙										
		审核: Approved: 刘建新										