

| **Last Exported:** 2026-08-17 11:34:29 UTC

Step 1: Collect

!!! overview **Tool:** Project Location Model (PLM) (v4 as of 01.07.2026)

****Performed by:**** external consultants

****Maintained by:**** Geodata-Desk

****Previous step:**** –

****Next step:**** [2 Validate](02-validate.md)

Purpose

Collect Project Location data using the Project Location Model (PLM) template. Project Locations can be represented by different geometry types (i.e. points, lines, polygons). Outputs can be in Excel or GeoJSON format.

!!! note “Updating an existing collection?” If your team already started collecting Project Locations with an **older version of the PLM template**, please read Updating existing data first. The version number is indicated in the filename. Then return here for **Points-based** or **Geometry-based** instructions under Procedure.

Requirements

- Access the latest version of the Project Location Model (PLM) template Please fill out one file per BMZ project number. Each file can contain multiple Project Locations associated with the single BMZ number.
- For geometry-based locations: QGIS installed on your KfW computer

Procedure

=== “Points-based”

1. Download and open the PLM (MS Excel template)
2. Fill in the project-level location metadata; all of the columns are mandatory. Include values for both the **Latitude** and **Longitude** columns to specify point coordinates. Please refer to the example line in the file and pay attention to the pop-up instructions on how to fill each column correctly. Only correctly filled out templates will generate valid maps later on.
3. Save completed PLM (*.xlsx format)

=== “Geometry-based”

Certain Project Locations are represented as **lines** or **polygons**, rather than points. In these cases, geometries must be provided, in addition to the PLM, which contains the associated metadata. A common column of data must exist in both the GeoJSON and PLM to establish a connection between the geometries and metadata.

For demonstration purposes, the examples below use the Frankfurt Botanical Garden (Unique ID value `1234567890`).

1. Download and open the PLM (MS Excel template)
2. Fill in the project-level location metadata with all of the columns, **excluding** the Latitude and Longitude columns.

![PLM example with Unique ID](../assets/images/collect-qgis-plm-example.png)
3. Start a new QGIS project. If you are not yet unfamiliar with using QGIS, please reach out to a Geodata-Scout or the Geodata-Desk for further support.
 - Select the **New Project** icon, or choose **Project → New** in the menu bar.
 - Select the **Save** icon, or choose **Project → Save**, to create or save the project file.
4. Create a new layer: **Layer → Create Layer → New Temporary Scratch Layer**
 - Add a **Layer name** (e.g. `example-polygon`)
 - Set **Geometry type** to **Polygon** (or the appropriate type for your locations)
 - Set the **CRS** to **EPSG:4326 – WGS 84** (required for

GeoJSON)

- Create at least one attribute field (e.g. `id`) and select ****Add to Fields List****

This attribute field should contain the same metadata value(s) that appear in the PLM, so that a join can be established between the two files. While field names can differ, the ****values must match exactly****. For example, attribute fields named `id` (in GeoJSON) and `Unique ID` (in PLM) both contain the value `1234567890`. Once attributes are defined, select ****OK**** to confirm.

```

```

!!! warning "Join field requirements"

Values in both attribute fields to be joined must be exact matches:

- Same data type (e.g. both text/string or both integer)
- Same case and no extra spaces
- Ideally, values should be unique or have a 1:1

correspondence

5. The new layer appears with the editing pencil enabled in the table of contents. The ****Toggle Editing**** feature can also be activated and deactivated in the toolbar.

```
![Toggle editing enabled](../assets/images/collect-qgis-
toggle-editing.jpeg)
```

6. It generally helps to add a reference dataset to assist with digitizing geometries.

- Select ****Layer → Data Source Manager****, or the ****Open Data Source Manager**** icon.
- To add a satellite basemap: ****Web → QuickMapServices → Google Satellite****
- If this option is not visible, activate the ****NextGIS QuickMapServices**** plugin via ****Plugins → Manage and Install Plugins****, then in the plugin settings click ****More Services → Get contributed pack****.
- Zoom to the area where you want to draw the geometry, or enter coordinates in decimal degrees in the ****Coordinate**** field at the bottom of the window.
- In this example, the Frankfurt Botanical Garden is located at ****(50.124, 8.650)****.

![Basemap and coordinate entry](../assets/images/collect-qgis-basemap.jpeg)

7. Draw polygon features

- Select the temporary scratch layer in the table of contents.
- If drawing options are not visible, enable the **Shape Digitizing Toolbar** by right-clicking the toolbar and selecting the correct panel.
- Select the **Add Polygon Feature** icon in the toolbar.
- Draw the polygon (circle, rectangle, or custom multi-vertex geometry as appropriate).
- Right-click to close the polygon when finished.
- Enter attribute values for the fields created earlier, then click **OK**.
- Use **Layer → Save Layer Edits** frequently while digitizing.

![Draw polygon feature](../assets/images/collect-qgis-draw-polygon.jpeg)

8. Repeat step 7 to create a geometry for each Project Location.

9. Export to GeoJSON

- Click the pencil icon in the toolbar to **stop editing** the layer.
- Right-click the temporary layer → **Export → Save Features As**.
- Set format to **GeoJSON**, choose the output path, then click **OK**.
- The permanent GeoJSON layer appears in the table of contents. You may remove the temporary layer at this point.

![Export layer as GeoJSON](../assets/images/collect-qgis-export-geojson.png)

10. Right-click the GeoJSON data layer in the table of contents → **Open Attribute Table**.

![GeoJSON attribute table](../assets/images/collect-qgis-attribute-table.jpeg)

11. Drag the PLM Excel file from Windows File Manager or Finder into the QGIS table of contents area.

![Add PLM Excel layer](../assets/images/collect-qgis-add-plm.png)

12. Join PLM to GeoJSON

- Right-click the GeoJSON layer → **Properties** → **Joins** tab → click the **+** button.
- Select the PLM as the **join layer**.
- Choose the **join field** (from Excel) and the **target field** (from GeoJSON).
- Click **OK** to confirm.

![Configure join between GeoJSON and PLM](../assets/images/collect-qgis-join-fields.png)

13. Verify the join

- Open the **Attribute Table** of the GeoJSON layer and check **Layer Properties → Information**.
- Metadata from the PLM should appear in the joined layer.
- Alternatively, select the **Identify Features** icon and click the polygon to verify joined attributes.

![Verify joined metadata](../assets/images/collect-qgis-verify-join.jpeg)

Outputs

Item	Format	Notes
File for validation	Excel or GeoJSON	Multi-geometry Project Locations with metadata