Dragoss Oumari	FORM	
Process Owner: IT Operations	Adding APN IPs to Elastix Firewall Configuration	F-CMG-3.1

Request Information				
Requestor	Jan	Jan Francis Lictao		
Implementing Team	Serv	Server Operation		
Ticket Number/s	201	916251		
Change Classification		Major	Х	Minor
After the fact	Х	Yes		No
Emergency		Yes	Х	No
Proposed Change Date	ATF			
Proposed Change Start/End Time	ATF			
Proposed Change Verification Time	ATF			

Objective of the change

To allow the connection of APN to our server and fix the NDY call issue.

Technical/Operational Impact of the change				
Negative:	Beneficial:	Neutral:		
No negative impact to the	Resolved the dead air call issue			
production.	of NDY numbers.			

Affected IT Infrastructure components			
Site	Hostname	IP Address	Function
Jaka	Kalliope	10.1.0.250	Dialer

Affected Departments and corresponding contact persons				
Department	Contact Name	Contact Info		
Server Operation	Rovie Salvatiera	0917-627-4325		

Test Environment implementation and Verification Summary

No testing done since it was ATF.

Test Environment Results Summary

No testing done since it was ATF.



D	FORM	
Process Owner: IT Operations	Adding APN IPs to Elastix Firewall Configuration	F-CMG-3.1

Configuration Change Template

Baseline File	3.1.103 ELASTIX
Baseline Version	3.0

Baseline File Changes:

Existing Configuration	Proposed Change	Impact	Section
APN IP are allowed in firewall on the other Network adapter (eth0)	Add the following IPs to firewall and pointed in active network adapter (eth1)	No impact to production.	Firewall
	208.74.75.250 208.74.75.252 208.74.75.246		
	38.102.225.8 38.102.225.13 38.102.225.14		

Physical Implementation Procedures / Advisory

No physical implementation will be facilitated.

Backup Procedures

1. Backup DB and Conifigurations.

Refer to KB Article: Back-up and Retention Process for Elastix Configuration and Database



Back-up and Retention Process fo

Backup Name	Date	Action
elastixbackup-20190509164932-65.tar	09/05/2019 16:49:32	Restore

2. Backup existing firewall configurations.

cp /opt/firewall /home/jlictao/firewall.6102019



D	FORM	
Process Owner: IT Operations	Adding APN IPs to Elastix Firewall Configuration	F-CMG-3.1

Technical Configuration Procedures

- 1. Login to Elastix server, 10.1.0.25 0 via SSH and switch to super user.
- 2. Edit the /opt/firewall to add the APN IP address.

[root@Kalliope ~]# vi /opt/firewall

####APN####

- -A INPUT -i eth1 -s 208.74.75.250/255.255.255.255 -j ACCEPT
- -A INPUT -i eth1 -s 38.102.225.8/255.255.255.255 -j ACCEPT
- -A INPUT -i eth1 -s 208.74.75.252/255.255.255.255 -j ACCEPT
- -A INPUT -i eth1 -s 208.74.75.246/255.255.255.255 -j ACCEPT
- -A INPUT -i eth1 -s 38.102.225.13/255.255.255.255 -j ACCEPT
- -A INPUT -i eth1 -s 38.102.225.14/255.255.255.255 -j ACCEPT
- 3. Pres ESC + :wq! to save the file configuration.
- 4. Run iptables restore to load the changes.

[root@Kalliope ~]# iptables-restore < /opt/firewall

Verification Procedures

1. Run iptables -L to list the current firewall configurations and the added IP must reflected.

[root@Kalliope ~]# iptables -L

.

anywhere	all 208.74.75.250	ACCEPT
anywhere	all 38.102.225.8	ACCEPT
anywhere	all 208.74.75.252	ACCEPT
anywhere	all 208.74.75.246	ACCEPT
anywhere	all 38.102.225.13	ACCEPT
anywhere	all 38.102.225.14	ACCEPT



Dragoss Oumari	FORM	
Process Owner: IT Operations	Adding APN IPs to Elastix Firewall Configuration	F-CMG-3.1

2. After all installation, conduct a test call to all local Extension, outbound and inbound call. For outbound call, dial any international Toll Free number (e.g. 1800 10 463 3339 FedEx US) For inbound call, dial OAM US number (+1 650-276-5399) and Marketing team must receive the call.

Back-out Procedures

1. Copy back the backup firewall configurations.

cp /home/jlictao/firewall.6102019 /opt/firewall

