SAMSUNG

Chapter Quiz

Coding and Programming

Together for Tomorrow!
Enabling People
Education for Future Generations

Quiz

Chapter 2

For Student

ⓒ2023 SAMSUNG. All rights reserved.
Samsung Electronics Corporate Citizenship Office holds the copyright of this document.
This document is a literary property protected by copyright law so reprint and reproduction without permission are prohibited.
To use this document other than the curriculum of Samsung innovation Campus, you must receive written consent from copyright holder.

Q. 10-01

If there are two lists l1 and l2 with the following strings, use the combination of l1 and l2 to print as follows.
Coding guideline: Use nested loops to print it out.

```
l1 = ['I like', 'I love']
l2 = ['pancake.', 'kiwi juice.', 'espresso.']
```

```
I like pancake.
I like kiwi juice.
I like espresso.
I love pancake.
I love kiwi juice.
I love espresso.
```

Q. 11-01

The person dictionary is defined as follows. Add a new item to this person dictionary with the key 'Father' and the value 'John Doe'. And then print the person dictionary.
Coding guideline: After defining the person dictionary, write a code to add new items.

```
person = {'Name' : 'David Doe', 'Age' : 26, 'Weight' : 82, 'Job': 'Data scientist' }
```

Q. 12-01

With tuple data, the values of two variables can be swapped without using a temporary variable. Using this swapping method, write a program that moves the largest value in the given list to the last.
Coding guideline: Use a for loop. When swapping values in a list, additional variables such as temp should not be used.

```
lst = [5, 6, 3, 9, 2, 12, 3, 8, 7]
```

Q. 13-01

The two-dimensional array a contains the values [[1, 2], [3, 4], [5, 6]]. Change this two-dimensional array to a one-dimensional array like [1, 2, 3, 4, 5, 6], and print it out.
Coding guideline: Use a for loop. Define a new array and put the elements of a into this array.

Q. 14-01

There is a dictionary variable maria as follows. In this dictionary variable, courses such as ‘korean' and ‘english' and their scores are stored as key:value. Print the average score of 89.25 for maria's subject scores.
Coding guideline: Use a dictionary method such as values() and len() function.

```
maria = {'korean': 94, 'english': 91, 'mathematics': 89, 'science': 83}
```

Q. 15-01

Declare a nested dictionary school as follows. Next, use the deepcopy() function of the copy module to write a program that 'copy' to another variable, school2. (Check that school and school2 are different variables through the is operator.)
Coding guideline: Print so that the result of school is school2 is false.

```
school = {'kim' : {'age': 16, 'hei': 170, 'grade': 3}, 'lee' : {'age': 15, 'hei': 168, 'grade': 2},
          'choi' : {'age': 14, 'hei': 173, 'grade': 1}}
```

Q. 16-01

There is a scores tuple as follows. This tuple contains information about four students, including each student's name and English, math, and science grades. For example, 'Hyun' has an English score of 88, a math score of 95, and a science score of 90. Extract only math scores by unpacking the scores tuple. Write a code that calculates the average of these extracted math scores.
Coding guideline: Use the zip function to solve the problem.

```
scores = (('Hyun', 88, 95, 90), ('Kang', 85, 90, 95), ('Park', 70, 90, 80), ('Hong', 90, 90, 95))
```