

[Back](#)

## Module 3 Graded Quiz

Graded Quiz • 30 min

Due Sep 20, 12:29 PM +0530

# Module 3 Graded Quiz

Latest Submission Grade 80%

1. What is the output of the following code?

1 / 1 point

☒ Go Mike

☐ Mike

☐ Stop Mike

☒ Correct

[Back](#)

## Module 3 Graded Quiz

Graded Quiz • 30 min

Due Sep 20, 12:29 PM +0530

2. What is the result of the following lines of code?

1 / 1 point

☒ True

☐ False



Correct

Correct

3. What is the output of the following few lines of code?

1 / 1 point

3. What is the output of the following few lines of code?

1 / 1 point

☒ 0

1

☐ 0

1

2

☐ 0

1

3

4



Correct

Correct

4. What is the result of running the following lines of code ?

1 / 1 point

☐ x=1;☒ x=1 y=2☐ y=2

Correct

correct

[Back](#)

### Module 3 Graded Quiz

Graded Quiz • 30 min

Due Sep 20, 12:29 PM +0530

5. What is the output of the following few lines of code?

1 / 1 point

☒ 0 AA

1 BB

2 CC

☐ 0 A

1 B

2 C

☐ 0 A

2 B

4 C

[Back](#)

## Module 3 Graded Quiz

Graded Quiz • 30 min

Due Sep 20, 12:29 PM +0530



Correct

Correct

6. What is the result of running the following lines of code ?

1 / 1 point



x=2 y=2



x=1 y=2



x=1 y=1



Correct

correct,

[Back](#)

## Module 3 Graded Quiz

Graded Quiz • 30 min

Due Sep 20, 12:29 PM +0530

7. Consider the function delta, when will the function return a value of 1?

0 / 1 point

☐ When the input is anything but 0

☒ When the input is 1

☐ Never

☐ When the input is 0

✗ **Incorrect**

incorrect, the value of y is 1 only if x is 0

8. What is the output of the following lines of code?

1 / 1 point

☒ 2

☐ 1

☐ NameError: name 'a' is not defined



Correct

correct, the value of **a** in the global scope will be used

9. Write a function name **add** that takes two parameter **a** and **b**, then return the output of **a + b** (Do not use any other variable! You do not need to run it. Only write the code about how you define it.)

0 / 1 point



[Back](#)

## Module 3 Graded Quiz

Graded Quiz • 30 min

Due Sep 20, 12:29 PM +0530

9. Write a function name **add** that takes two parameter **a** and **b**, then return the output of **a + b** (Do not use any other variable! You do not need to run it. Only write the code about how you define it.)

0 / 1 point

✖ Incorrect

```
RuntimeErrorElement(RuntimeError,Error on line 1:
  def add(a,b)
    ^
SyntaxError: invalid syntax
)
```

10. Why is it best practice to have multiple except statements with each type of error labeled correctly?

1 / 1 point

- ☐ Ensure the error is caught so the program will terminate
- ☒ In order to know what type of error was thrown and the location within the program

```
SyntaxError: invalid syntax  
)
```

10. Why is it best practice to have multiple except statements with each type of error labeled correctly?

1 / 1 point

- ☐ Ensure the error is caught so the program will terminate
- ☒ In order to know what type of error was thrown and the location within the program
- ☐ To skip over certain blocks of code during execution
- ☐ It is not necessary to label errors

✓ Correct