

# Deduction Guides for `packaged_task`

Document #: PxxxxR0  
Date: 2018-04-19  
Project: Programming Language C++  
Library Evolution Group  
Reply-to: Marc Mutz  
<[marc.mutz@kdab.com](mailto:marc.mutz@kdab.com)>

## 1 Introduction

`std::function` has deduction guides, but `std::packaged_task`, which is otherwise very similar to `std::function`, does not. We propose to add deduction guides for `packaged_task` that are compatible with the ones for `function`.

## 2 Impact on the Standard

Minimal. We propose to add deduction guides to `packaged_task`, which lacked them. This enables code that did not previously compile, but does not change the meaning of existing code.

## 3 Proposed Wording

In `[futures.task.members]`, before the non-member `swap` function declaration, add:

```
template<class R, class... ArgTypes>
    packaged_task(R*)(ArgTypes...) -> packaged_task<R(ArgTypes...)>;

template<class F> packaged_task(F) -> packaged_task<see below>;
```

In `[futures.task.members]`, after the `packaged_task(F&&)` constructor description, add:

```
template<class F> packaged_task(F) -> packaged_task<see below>;
```

*Remarks:* This deduction guide participates in overload resolution only if `&F::operator()` is well-formed when treated as an unevaluated operand. In that case, if `decltype(&F::operator())` is of the form `R(G::*)(A...) cv &opt noexceptopt` for a class type `G`, then the deduced type is `packaged_task<R(A...)>`.