

the failure weight set (v4_failure_only): each cell is the value the token's out-transition is multiplied by on a failure verdict, with the letter of the declared rule that produced it

		Recon.	Res. dev.	Init. access	Execution	Persistence	Priv. esc.	Stealth	Def. imp.	Cred. access	Discovery	Lat. move.	C2	Collection	Exfiltration	Impact
preparation	Reconnaissance		0.7 G	0.4 B	0.05 C	0.0125 C	0.0125 C	0.0125 C	0.0125 C	0.0125 C	0.0125 C	0.0125 C	0.0125 C	0 C	0 C	0 C
	Resource development	0.7 G		0.3 I	0.3 I	0.075 I	0.075 I	0.075 I	0.075 I	0.075 I	0.075 I	0.075 I	0.075 I	0 I	0 I	0 I
intrusion	Initial access	0.9 F	0.9 F		0.02 A	0.02 A	0.02 A	0.02 A	0.02 A	0.02 A	0.02 A	0.02 A	0.02 A	0.005 A	0.005 A	0.005 A
	Execution	0.25 D	0.25 D	0.7 G		0.35 H	0.35 H	0.35 H	0.35 H	0.35 H	0.35 H	0.35 H	0.35 H	0.0875 H	0.0875 H	0.0875 H
post-intrusion	Persistence	0.0625 D	0.0625 D	0.25 D	0.35 E		0.7 G	0.7 G	0.7 G	0.7 G	0.7 G	0.7 G	0.7 G	0.35 H	0.35 H	0.35 H
	Privilege escalation	0.0625 D	0.0625 D	0.25 D	0.35 E	0.7 G		0.7 G	0.7 G	0.7 G	0.7 G	0.7 G	0.7 G	0.35 H	0.35 H	0.35 H
	Stealth	0.0625 D	0.0625 D	0.25 D	0.35 E	0.7 G	0.7 G		0.7 G	0.7 G	0.7 G	0.7 G	0.7 G	0.35 H	0.35 H	0.35 H
	Defense impairment	0.0625 D	0.0625 D	0.25 D	0.35 E	0.7 G	0.7 G	0.7 G		0.7 G	0.7 G	0.7 G	0.7 G	0.35 H	0.35 H	0.35 H
	Credential access	0.0625 D	0.0625 D	0.25 D	0.35 E	0.7 G	0.7 G	0.7 G	0.7 G		0.7 G	0.7 G	0.7 G	0.35 H	0.35 H	0.35 H
	Discovery	0.0625 D	0.0625 D	0.25 D	0.35 E	0.7 G	0.7 G	0.7 G	0.7 G	0.7 G		0.7 G	0.7 G	0.35 H	0.35 H	0.35 H
	Lateral movement	0.0625 D	0.0625 D	0.25 D	0.35 E	0.7 G	0.7 G	0.7 G	0.7 G	0.7 G	0.7 G		0.7 G	0.35 H	0.35 H	0.35 H
objective	Command and control	0.0625 D	0.0625 D	0.25 D	0.35 E	0.7 G	0.7 G	0.7 G	0.7 G	0.7 G	0.7 G	0.7 G		0.35 H	0.35 H	0.35 H
	Collection	0 D	0 D	0.0625 D	0.0875 E	0.9 F	0.9 F	0.9 F	0.9 F	0.9 F	0.9 F	0.9 F	0.9 F		0.7 G	0.7 G
	Exfiltration	0 D	0 D	0.0625 D	0.0875 E	0.9 F	0.9 F	0.9 F	0.9 F	0.9 F	0.9 F	0.9 F	0.9 F	0.7 G		0.7 G
	Impact	0 D	0 D	0.0625 D	0.0875 E	0.9 F	0.9 F	0.9 F	0.9 F	0.9 F	0.9 F	0.9 F	0.9 F	0.7 G	0.7 G	

rule key (match order; each value is then multiplied by the lifecycle-distance factor):

A ia_gate_foothold = 0.02

B recon_gate_initial_access = 0.4

C recon_gate_deep = 0.05

D preintrusion_damper = 0.25

E execution_damper = 0.35

F backward = 0.9

G lateral = 0.7

H forward_from_foothold = 0.35

I forward_from_prep = 0.3